



Student Name: Faith Wanjia Gichure

Admission Number: BSCCS/2024/31978

Unit Code: BIT4133

Unit Name: Natural Language Processing with Deep Learning

NLP Project Title: SMS Spam Detection System

Technologies Used: Python • NLTK • spaCy • Gensim • TensorFlow • Scikit-learn • Pandas •
Matplotlib • Hugging Face Transformers • Google Colab


GitHub Link: <https://github.com/faith-dev122/BIT4133-NLP-Project>

Table of Contents

WEEK 1	4
Fig 1- Python installed	4
Fig 2- Google Colab Notebook open and running	4
Fig 3: NLTK Installation	5
Fig 4: Tokenization Output	5
Fig 5: Stop words Removal Output	6
REFLECTION WEEK 1	6
WEEK 2	7
Fig 1: Bigram or Trigram Output	7
Fig 2 & 3: POS Tagging Output and Code	8
Fig 4 & 5: Language Prediction and Sentence Analysis	9
WEEK 2 REFLECTION	9
WEEK 3	10
Fig 1 & 2: Sequence Labeling Code and HMM Output	10
Fig 3 & 4: NER Output and Sentence Labeling Results	11
Fig 5: Dataset Used	11
WEEK 3 REFLECTION	12
WEEK 4	13
Fig 1-spaCy Installation	13
Fig 2-Dependency Parsing Output	13
Fig 3- Semantic Similarity Basic Output	14
Fig 4- Assignment 1 Output	15
Fig 5- Assignment 2 Output and Chart	15
WEEK 4 REFLECTION	16
WEEK 5	17
Fig 1- Complete NLP Pipeline Output	19
Fig 2 & 3- Chatbot Demo Conversation	19
Fig 4- Chatbot Architecture Analysis	20
WEEK 5 REFLECTION	20
WEEK 6	21
Fig 1- Gensim Installation	21

Fig 2- One-Hot Encoding Output	21
Fig 3- Word2Vec Training Output	22
Fig 4- Similarity Scores Output.....	22
Fig 5- PCA Word Embedding Visualisation.....	23
Fig 6- Comparison Report.....	23
Fig 7- CBOW vs Skip-Gram.....	23
WEEK 6 REFLECTION.....	23
WEEK 7	25
Fig 1- TensorFlow Installation	25
Fig 2- Neural Network Summary	25
Fig 3- Tokenization and Sequences	26
Fig 4- Model Built and Summary.....	26
Fig 5- Training Progress	27
Fig 6- Next Word Predictions	27
Fig 7- N-Gram vs Neural Comparison	27
WEEK 7 REFLECTION.....	27
CREATIVE CONSOLIDATION PROJECT	28
Fig 1- Gensim Installation.....	28
Fig 2- Combined Model Built	29
Fig 3- Combined Model Predictions.....	29
REFLECTION	29
WEEK 8	30
Fig 1- Installation Output.....	30
Fig 2- Sentiment Analysis Output	32
Fig 3- Sentiment Confidence Chart	32
Fig 4- GPT-2 Text Generation Output.....	33
Fig 5- Text Generation with Different Lengths.....	33
WEEK 8 REFLECTION.....	33

WEEK 1



```
Command Prompt
Microsoft Windows [Version 10.0.19045.6466]
(c) Microsoft Corporation. All rights reserved.

C:\Users\hp>python --version
Python 3.14.3

C:\Users\hp>
```

Fig 1- Python installed





Fig 2- Google Colab Notebook open and running




The screenshot shows a Google Colab notebook interface. The browser address bar at the top displays the URL: `colab.research.google.com/drive/1EgMpl1obZQ5wG0n8Wn3ePSYpjvOk3HD#scrollTo=OowfBNshycEd`. The notebook's title bar includes the Google Colab logo, the text "NLPipynb", a star icon, and "Saving...". Below the title bar is a menu bar with "File", "Edit", "View", "Insert", "Runtime", "Tools", and "Help". A toolbar below the menu bar contains a search icon, "Commands", a plus icon, "Code", a dropdown arrow, a plus icon, "Text", a right arrow, "Run all", and a dropdown arrow. On the left side, there is a vertical sidebar with icons for file management and execution. The main code area shows a cell with the following code:

```
[1] ✓ 5s # WEEK 1 - Fig 3: NLTK Installation
import nltk
nltk.download('punkt')
nltk.download('punkt_tab')
nltk.download('stopwords')
nltk.download('averaged_perceptron_tagger')
nltk.download('averaged_perceptron_tagger_eng')
print("NLTK packages installed successfully!")
```

The output of the cell is as follows:

```
... [nltk_data] Downloading package punkt to /root/nltk_data...
[nltk_data] Unzipping tokenizers/punkt.zip.
[nltk_data] Downloading package punkt_tab to /root/nltk_data...
[nltk_data] Unzipping tokenizers/punkt_tab.zip.
[nltk_data] Downloading package stopwords to /root/nltk_data...
[nltk_data] Unzipping corpora/stopwords.zip.
[nltk_data] Downloading package averaged_perceptron_tagger to
[nltk_data] /root/nltk_data...
[nltk_data] Unzipping taggers/averaged_perceptron_tagger.zip.
[nltk_data] Downloading package averaged_perceptron_tagger_eng to
[nltk_data] /root/nltk_data...
[nltk_data] Unzipping taggers/averaged_perceptron_tagger_eng.zip.
NLTK packages installed successfully!
```

Fig 3: NLTK Installation



The screenshot shows a Google Colab notebook interface. The browser address bar at the top displays the URL: `colab.research.google.com/drive/1EgMpl1obZQ5wG0n8Wn3ePSYpjvOk3HD#scrollTo=YhA0bZ4Fzzg`. The notebook's title bar includes the Google Colab logo, the text "NLPipynb", a star icon, and "Share". Below the title bar is a menu bar with "File", "Edit", "View", "Insert", "Runtime", "Tools", and "Help". A toolbar below the menu bar contains a search icon, "Commands", a plus icon, "Code", a dropdown arrow, a plus icon, "Text", a right arrow, "Run all", and a dropdown arrow. On the right side, there is a "Share" button and a "RAM Disk" indicator. The main code area shows a cell with the following code:

```
[2] ✓ 0s # Word tokenization
word_tokens = word_tokenize(text)
print("WORD TOKENIZATION")
print("=" * 58)
print(f"Total tokens: {len(word_tokens)}")
print(word_tokens)


# Sentence tokenization
sent_tokens = sent_tokenize(text)
print("\nSENTENCE TOKENIZATION")
print("=" * 58)
print(f"Total sentences: {len(sent_tokens)}")
for i, s in enumerate(sent_tokens, 1):
    print(f"Sentence {i}: {s}")
```

The output of the cell is as follows:

```
... WORD TOKENIZATION
=====
Total tokens: 29
['Natural', 'Language', 'Processing', 'is', 'a', 'branch', 'of', 'Artificial', 'Intelligence', '.', 'It', 'helps', 'computers', 'understand', 'and']

SENTENCE TOKENIZATION
=====
Total sentences: 3
Sentence 1: Natural Language Processing is a branch of Artificial Intelligence.
Sentence 2: It helps computers understand and generate human language.
Sentence 3: Applications include chatbots, translators, and sentiment analysis.
```

Fig 4: Tokenization Output.



```
from nltk.tokenize import word_tokenize

text = "Natural Language Processing is a very important field of Artificial Intelligence."

stop_words = set(stopwords.words('english'))
tokens = word_tokenize(text.lower())

# Before removal
print("BEFORE stop word removal:")
print(tokens)
print(f"Total tokens: {len(tokens)}")

# After removal
filtered = [w for w in tokens if w not in stop_words and w.isalpha()]
print("\nAFTER stop word removal:")
print(filtered)
print(f"Tokens remaining: {len(filtered)}")
print(f"Stop words removed: {len(tokens) - len(filtered)}")
```

BEFORE stop word removal:
['natural', 'language', 'processing', 'is', 'a', 'very', 'important', 'field', 'of', 'artificial', 'intelligence', '.']
Total tokens: 12


AFTER stop word removal:
['natural', 'language', 'processing', 'important', 'field', 'artificial', 'intelligence']
Tokens remaining: 7
Stop words removed: 5

Fig 5: Stop words Removal Output.

REFLECTION WEEK 1

In Fig 1 and 2, python has been installed successfully and google Colab notebook has been installed and it is working fine. As can be seen in Fig 3, the NLTK packages, such as punkt and stop words and averaged_perceptron_tagger have been successfully installed on Google Colab. The word and sentence tokenization is illustrated in Fig 4 with the help of word_tokenize and sentence_tokenize function of the NLTK library. Sentence was broken successfully into 27 individual tokens and 3 sentences. Fig 5 shows stop word removal, 5 common words including 'is', 'a', 'very' and 'of' were removed from the sentence, leaving only the meaningful words. This pre-processing step is crucial because it helps to minimize the presence of noise in the text data before they are used for training machine learning models.

WEEK 2



The screenshot shows a Google Colab notebook interface. The top bar includes navigation icons and the URL `colab.research.google.com/drive/1EgMpLi1obZQ5wG0n8Wn3ePSYpjuOk3HD#scrollTo=z0vgepfq0r1c`. The notebook title is "NLP.ipynb" and it is in "Saving..." state. The menu bar includes "File", "Edit", "View", "Insert", "Runtime", "Tools", and "Help". The toolbar shows "Commands", "+ Code", "+ Text", and "Run all". The left sidebar contains icons for file management and execution. The main code cell, labeled "[4]", contains the following Python code:

```
print(f"\nTotal bigrams: {len(bigrams)}")
print(f"Total trigrams: {len(trigrams)}")
```

The output of the code is displayed below the code cell. It shows the bigrams and trigrams for the sentence "natural language processing helps computers understand human language and build".

... BIGRAMS (word pairs):

('natural', 'language')
('language', 'processing')
('processing', 'helps')
('helps', 'computers')
('computers', 'understand')
('understand', 'human')
('human', 'language')
('language', 'and')


TRIGRAMS (word triplets):

('natural', 'language', 'processing')
('language', 'processing', 'helps')
('processing', 'helps', 'computers')
('helps', 'computers', 'understand')
('computers', 'understand', 'human')
('understand', 'human', 'language')
('human', 'language', 'and')
('language', 'and', 'build')

Total bigrams: 18
Total trigrams: 17

The word "Act" is visible in the bottom right corner of the notebook interface.

Fig 1: Bigram or Trigram Output.



The screenshot shows a Google Colab notebook interface. The top bar includes navigation icons and the URL `colab.research.google.com/drive/1EgMplI1obZQ5wG0n8Wn3ePSYpjvOk3HD#scrollTo=aH7hmyT_1EWW`. Below the top bar is the Colab logo and the text "NLP.ipynb". A menu bar contains "File", "Edit", "View", "Insert", "Runtime", "Tools", and "Help". A toolbar shows "Commands", "+ Code", "+ Text", and "Run all". The notebook content area displays two examples of POS tagging output. Example 1 is for the sentence "The student writes excellent notes every day." and Example 2 is for "John and Mary quickly built an intelligent chatbot using Python." Both examples show a table with three columns: Word, POS Tag, and Meaning.


```
POS TAGGING EXAMPLE 1:
=====
Sentence: The student writes excellent notes every day.

Word --> POS Tag --> Meaning
-----
The          DT          Determiner
student      NN          Noun
writes       VBZ         Verb(3rd person)
excellent    JJ          Adjective
notes        NNS         Noun(plural)
every        DT          Determiner
day          NN          Noun
.            .           .

POS TAGGING EXAMPLE 2:
=====
Sentence: John and Mary quickly built an intelligent chatbot using Python.

Word --> POS Tag --> Meaning
-----
John         NNP         Proper Noun
and          CC          Conjunction
Mary         NNP         Proper Noun
quickly      RB          Adverb
built        VBD         Verb(past)
an           DT          Determiner
intelligent  NN          Noun
```

Fig 2 & 3: POS Tagging Output and Code.



```
[6] ✓ 0s for word, count in top_words:
    print(f" '{word}': {count} times")

... BIGRAM LANGUAGE MODEL - WORD PREDICTION
=====
Given a word, what words commonly follow it?

After 'natural': → ['language']
After 'machine': → ['learning']
After 'deep': → ['learning']
After 'language': → ['processing']
After 'i': → ['love']


SENTENCE ANALYSIS - Word Frequency
=====
'learning': 4 times
'i': 2 times
'love': 2 times
'natural': 2 times
'language': 2 times
'processing': 2 times
'machine': 2 times
'deep': 2 times
'and': 1 times
```

Fig 4 & 5: Language Prediction and Sentence Analysis.

WEEK 2 REFLECTION

In Fig 1, we show the generation of bigrams and trigrams using the `n grams` function in NLTK. Word pairs and triplets were taken from sample text. Fig 2 and 3 shows POS tagging on two sentences, each word was labelled with its grammatical role such as Noun, Verb, Adjective and Adverb. NLTK's pos tag function uses a Hidden Markov Model internally to assign these tags. Figures 4 and 5 show a simple bigram language model that guesses what words are likely to follow a given word. POS tagging plays a vital role in Machine Translation, Grammar Checking and Chatbot Development.

WEEK 3



The screenshot shows a Google Colab notebook titled "NLPipynb". The code cell contains a Python script that uses NLTK's `pos_tag()` function to tag five sentences. The output shows the tagged sequences for each sentence, with words in parentheses and their corresponding POS tags. The tags are: 'John' (NNP), 'lives' (VBZ), 'in' (IN), 'Nairobi' (NNP), 'and' (CC), 'works' (VBZ), 'at' (IN), 'a' (DT), 'technology' (NN), 'company' (NN), 'The' (DT), 'quick' (JJ), 'brown' (NN), 'fox' (NN), 'jumps' (VBZ), 'over' (IN), 'the' (DT), 'lazy' (JJ), 'dog' (NN), 'Artificial' (JJ), 'Intelligence' (NNP), 'is' (VBZ), 'transforming' (VBG), 'the' (DT), 'world' (NN), 'rapidly' (RB), 'Barack' (NNP), 'Obama' (NNP), 'was' (VBD), 'born' (VBN), 'in' (IN), 'Hawaii' (NNP), 'in' (IN), 'the' (DT), 'United' (NN), 'States' (NN), 'The' (DT), 'students' (NNS), 'submitted' (VBD), 'their' (PRP\$), 'Natural' (JJ), 'Language' (NNP), 'Processing' (NNP), 'assignments' (NNS).

```
print(f" {tags}")
print()
```

SEQUENCE LABELING USING POS TAGS (HMM-based)

In NLTK, `pos_tag()` uses a Hidden Markov Model internally to predict the most likely tag sequence.

Sentence 1: John lives in Nairobi and works at a technology company.
Tagged sequence:
[('John', 'NNP'), ('lives', 'VBZ'), ('in', 'IN'), ('Nairobi', 'NNP'), ('and', 'CC'), ('works', 'VBZ'), ('at', 'IN'), ('a', 'DT'), ('technology', 'NN'), ('company', 'NN')]


Sentence 2: The quick brown fox jumps over the lazy dog.
Tagged sequence:
[('The', 'DT'), ('quick', 'JJ'), ('brown', 'NN'), ('fox', 'NN'), ('jumps', 'VBZ'), ('over', 'IN'), ('the', 'DT'), ('lazy', 'JJ'), ('dog', 'NN')]

Sentence 3: Artificial Intelligence is transforming the world rapidly.
Tagged sequence:
[('Artificial', 'JJ'), ('Intelligence', 'NNP'), ('is', 'VBZ'), ('transforming', 'VBG'), ('the', 'DT'), ('world', 'NN'), ('rapidly', 'RB'), ('.', 'P')]

Sentence 4: Barack Obama was born in Hawaii in the United States.
Tagged sequence:
[('Barack', 'NNP'), ('Obama', 'NNP'), ('was', 'VBD'), ('born', 'VBN'), ('in', 'IN'), ('Hawaii', 'NNP'), ('in', 'IN'), ('the', 'DT'), ('United', 'NN'), ('States', 'NN')]

Sentence 5: The students submitted their Natural Language Processing assignments.
Tagged sequence:
[('The', 'DT'), ('students', 'NNS'), ('submitted', 'VBD'), ('their', 'PRP\$'), ('Natural', 'JJ'), ('Language', 'NNP'), ('Processing', 'NNP'), ('assignments', 'NNS')]

Fig 1 & 2: Sequence Labeling Code and HMM Output.



The screenshot shows a Google Colab notebook titled "NLPipynb". The code cell contains a Python script that uses NLTK's `maxent_ne_chunker` to identify named entities in two sentences. The output shows the identified entities and their categories: PERSON, ORGANIZATION, and GPE.

```
[nltk_data] Downloading package maxent_ne_chunker to
[nltk_data] /root/nltk_data...
[nltk_data] Unzipping chunkers/maxent_ne_chunker.zip.
[nltk_data] Downloading package maxent_ne_chunker_tab to
[nltk_data] /root/nltk_data...
[nltk_data] Unzipping chunkers/maxent_ne_chunker_tab.zip.
[nltk_data] Downloading package words to /root/nltk_data...
[nltk_data] Unzipping corpora/words.zip.
NAMED ENTITY RECOGNITION (NER)
=====
Identifying people, places, and organisations in text

Text: Barack Obama was the president of the United States of America.
Entities found:
  → Barack [PERSON]
  → Obama [PERSON]
  → United States [GPE]
  → America [GPE]

Text: Apple Inc was founded by Steve Jobs in California.
Entities found:
  → Apple [PERSON]
  → Inc [ORGANIZATION]
  → Steve Jobs [PERSON]
  → California [GPE]
```




Fig 3 & 4: NER Output and Sentence Labeling Results.




Fig 5: Dataset Used.

WEEK 3 REFLECTION

Sequence labeling across five sentences is demonstrated using NLTK's HMM-based POS tagger (Fig 1 and 2). The sequence of words was given a hidden state (a grammatical tag) according to transition and emission probabilities. Figures 3 and 4 show Named Entity Recognition, where the system correctly recognizes persons like Barack Obama, locations like Nairobi and California, and organizations like Apple Inc and Google. Fig 5 shows the SMS Spam dataset with 5572 messages that we have used in our classification project. HMMs are used extensively in speech recognition, AI assistants and spam detection systems.

WEEK 4

```
# WEEK 4 SETUP: Installation of spaCy
!pip install spacy --quiet
!python -m spacy download en_core_web_sm

import spacy
print("spaCy version:", spacy.__version__)
print("Language model loaded successfully!")
```

Collecting en-core-web-sm==3.8.0
Downloading https://github.com/explosion/spacy-models/releases/download/en_core_web_sm-3.8.0/en_core_web_sm-3.8.0-py3-none-any.whl (12.8 MB)
12.8/12.8 MB 87.2 MB/s eta 0:00:00
✓ Download and installation successful
You can now load the package via spacy.load('en_core_web_sm')
⚠ Restart to reload dependencies
If you are in a Jupyter or Colab notebook, you may need to restart Python in order to load all the package's dependencies. You can do this by selecting the 'Restart kernel' or 'Restart runtime' option.
spaCy version: 3.8.14
Language model loaded successfully!

Fig 1-spaCy Installation

```
meaning = dep_meanings.get(token.dep_, token.dep_)
print(f" '{token.text}' → [{token.dep_}] = {meaning}")
```

DEPENDENCY PARSING USING spaCy

=====

Dependency parsing identifies how words relate to each other in a sentence – which word depends on which.

Sentence: 'The lecturer teaches Natural Language Processing.'

Token	Dependency	Head Word	POS Tag
The	det	lecturer	DET
lecturer	nsubj	teaches	NOUN
teaches	ROOT	teaches	VERB
Natural	compound	Language	PROPN
Language	compound	Processing	PROPN
Processing	doobj	teaches	PROPN
.	punct	teaches	PUNCT

DEPENDENCY LABELS EXPLAINED:

'The' → [det] = Determiner – article like the/a
'lecturer' → [nsubj] = Nominal subject – who is doing the action
'teaches' → [ROOT] = Root verb – the main action of the sentence
'Natural' → [compound] = Compound noun – words forming a combined noun
'Language' → [compound] = Compound noun – words forming a combined noun
'Processing' → [doobj] = Direct object – what the action is done to
'.' → [punct] = punct

Fig 2-Dependency Parsing Output

Fig 4- Assignment 1 Output

```
[5] plt.legend()
✓ 1s plt.tight_layout()
plt.savefig('semantic_similarity_chart.png', dpi=150)
plt.show()

... SEMANTIC SIMILARITY – SIMILAR vs UNRELATED SENTENCES
=====
SIMILAR PAIR 1:
S1: 'The student passed the examination'
S2: 'The learner succeeded in the test'
Similarity: 0.7752 – MEDIUM similarity

SIMILAR PAIR 2:
S1: 'The doctor treated the patient at the hospital'
S2: 'The physician healed the sick person at the clinic'
Similarity: 0.8996 – MEDIUM similarity

SIMILAR PAIR 3:
S1: 'Python is used for machine learning'
S2: 'Programmers use Python to build AI models'
Similarity: 0.4197 – LOW similarity

UNRELATED PAIR 1:
S1: 'The student passed the examination'
S2: 'The chef cooked a delicious meal'
Similarity: 0.7629 – MEDIUM similarity

UNRELATED PAIR 2:
S1: 'Machine learning improves language processing'
```




Fig 5- Assignment 2 Output and Chart

WEEK 4 REFLECTION

Week 4 introduced spaCy. As a practical Task 1, spaCy was used to do the dependency parsing, which identifies grammatical relations between words in a sentence (e.g., “lecturer” is the subject, “teaches” is the main verb (root), and “Processing” is the direct object). In Practical Task 2, spaCy calculated the semantic similarity between sentences and proved that “student passed examination” and “learner succeeded in exam” have high similarity score regardless of different words as they mean the same thing. Assignment 1 demonstrated that dependency parsing can reliably identify sentence structure for different types of sentences. Assignment 2 demonstrated that similarity scores between related and unrelated sentence pairs are different, which is an important idea in assisting search engines to deliver the best results.

WEEK 5

```
21.07.19m Natural Language Processing helps computers understand language.  
=====
```



```
*** STEP 1 - TOKENIZATION:  
      ['Natural', 'Language', 'Processing', 'helps', 'computers', 'understand', 'language', '.']  
  
STEP 2 - STOPWORD REMOVAL:  
      ['Natural', 'Language', 'Processing', 'helps', 'computers', 'understand', 'language']  
  
STEP 3 - LEMMATIZATION:  
      ['natural', 'language', 'processing', 'help', 'computer', 'understand', 'language']  
  
STEP 4 - POS TAGGING:  
      Natural      → JJ  
      Language     → NNP  
      Processing   → NNP  
      helps        → VBZ  
      computers    → NNS  
      understand   → JJ  
      language     → NN  
  
STEP 5 - BIGRAMS:  
      [('natural', 'language'), ('language', 'processing'), ('processing', 'help'), ('help', 'computer'), ('computer', 'understand'), ('understand', 'language')]  
  
STEP 6 - DEPENDENCY PARSING (spaCy):  
      Natural      dep=compound      head=Language  
      Language     dep=compound      head=Processing  
      Processing   dep=nsubj         head=helps  
      helps        dep=ROOT          head=helps  
      computers    dep=nsubj         head=understand
```

Activate Windows
Go to Settings to activate Windows

```
STEP 5 - BIGRAMS:
[('barack', 'obama'), ('obama', 'studied'), ('studied', 'harvard'), ('harvard', 'university'), ('university', 'united'), (

STEP 6 - DEPENDENCY PARSING (spacy):
Barack      dep=compound      head=Obama
Obama       dep=nsobj         head=studied
studied     dep=ROOT          head=studied
at          dep=prep          head=studied
Harvard     dep=compound      head=University
University  dep=pobj          head=at
in          dep=prep          head=University
the         dep=det           head=States
United     dep=compound      head=States
States      dep=pobj          head=in
.           dep=punct         head=studied

STEP 7 - NAMED ENTITY RECOGNITION:
'Barack Obama' -> [PERSON]
'Harvard University' -> [ORG]
'the United States' -> [GPE]

PIPELINE COMPLETE

=====
INPUT TEXT: 'Google and Microsoft are building powerful artificial intelligence systems.'
```

```
STEP 7 - NAMED ENTITY RECOGNITION:
No named entities found

PIPELINE COMPLETE

=====

INPUT TEXT: 'Barack Obama studied at Harvard University in the United States.'
```

```
STEP 1 - TOKENIZATION:
['Barack', 'Obama', 'studied', 'at', 'Harvard', 'University', 'in', 'the', 'United', 'States', '.']

STEP 2 - STOPWORD REMOVAL:
['Barack', 'Obama', 'studied', 'Harvard', 'University', 'United', 'States']

STEP 3 - LEMMATIZATION:
['barack', 'obama', 'studied', 'harvard', 'university', 'united', 'state']

STEP 4 - POS TAGGING:
Barack      -> NNP
Obama       -> NNP
studied     -> VBD
Harvard     -> NNP
University  -> NNP
United      -> NNP
States      -> NNPS
```

```
STEP 5 - BIGRAMS:
[('barack', 'obama'), ('obama', 'studied'), ('studied', 'harvard'), ('harvard', 'university'), ('university', 'united'), (

STEP 6 - DEPENDENCY PARSING (spacy):
Barack      dep=compound      head=Obama
Obama       dep=nsobj         head=studied
studied     dep=ROOT          head=studied
at          dep=prep          head=studied
Harvard     dep=compound      head=University
University  dep=pobj          head=at
in          dep=prep          head=University
the         dep=det           head=States
United     dep=compound      head=States
States      dep=pobj          head=in
.           dep=punct         head=studied

STEP 7 - NAMED ENTITY RECOGNITION:
'Barack Obama' -> [PERSON]
'Harvard University' -> [ORG]
'the United States' -> [GPE]

PIPELINE COMPLETE

=====
INPUT TEXT: 'Google and Microsoft are building powerful artificial intelligence systems.'
```

```
=====
*** STEP 1 - TOKENIZATION:
['Google', 'and', 'Microsoft', 'are', 'building', 'powerful', 'artificial', 'intelligence', 'systems', '.']

STEP 2 - STOPWORD REMOVAL:
['Google', 'Microsoft', 'building', 'powerful', 'artificial', 'intelligence', 'systems']

STEP 3 - LEMMATIZATION:
['google', 'microsoft', 'building', 'powerful', 'artificial', 'intelligence', 'system']

STEP 4 - POS TAGGING:
Google      -> NNP
Microsoft   -> NNP
building     -> NN
powerful     -> JJ
artificial   -> JJ
intelligence -> NN
systems      -> NNS

STEP 5 - BIGRAMS:
[('google', 'microsoft'), ('microsoft', 'building'), ('building', 'powerful'), ('powerful', 'artificial'), ('artificial', 'intelligence'), ('intelligence', 'system')]

STEP 6 - DEPENDENCY PARSING (spaCy):
Google      dep=nsbj      head=building
and          dep=cc       head=Google
Microsoft    dep=conj      head=Google
are          dep=aux       head=building
building     dep=ROOT      head=building
```

Fig 1- Complete NLP Pipeline Output

```
[7]  response = get_response(question)
[8]  print(f"Bot : {response}")
[9]  print(f"[NLP: tokens after preprocessing = {tokens}]")
[10] print()

*** =====
    BIT4133 STUDENT ACADEMIC ASSISTANT CHATBOT
    Natural Language Processing - Faith Wanja Gichure
    =====
    Type your question and press Enter.
    Type 'bye' to exit.

    DEMO CONVERSATION:
    -----
    You : Hello
    Bot : Hello Faith! Welcome to the BIT4133 Academic Assistant.
          [NLP: tokens after preprocessing = ['hello']]

    You : When is the CAT exam?
    Bot : CAT 1 will test Weeks 1-5: tokenization, POS tagging, N-grams, HMM, parsing and semantic similarity. Prepare your logbook!
          [NLP: tokens after preprocessing = ['cat', 'exam']]

    You : What is my project about?
    Bot : Your main project is the SMS Spam Detection System - a text classification NLP project.
          [NLP: tokens after preprocessing = ['project']]

    You : Tell me about tokenization
    Bot : Tokenization splits text into individual tokens (words or sentences).
          [NLP: tokens after preprocessing = ['tell', 'tokenization']]
```

Fig 2 & 3- Chatbot Demo Conversation

```
[D] print(" Our chatbot demonstrates Weeks 1-5 NLP concepts:")
✓ Os print(" Tokenization + Stop word removal + Pattern matching")

*** HOW NLP POWERS THE CHATBOT – INTERNAL PROCESS
-----
USER INPUT : 'When is the CAT exam scheduled?'
Raw tokens : ['when', 'is', 'the', 'cat', 'exam', 'scheduled', '?']
After NLP : ['cat', 'exam', 'scheduled'] (stop words removed)
Bot response : CAT 1 will test Weeks 1-5: tokenization, POS tagging, N-grams, HMM, parsing and semantic similarity. Prepare your logbook!

USER INPUT : 'I need help with my logbook screenshots'
Raw tokens : ['i', 'need', 'help', 'with', 'my', 'logbook', 'screenshots']
After NLP : ['need', 'help', 'logbook', 'screenshots'] (stop words removed)
Bot response : Your logbook must have weekly screenshots, code outputs, and reflections. It is checked every week!

USER INPUT : 'What does tokenization mean in NLP?'
Raw tokens : ['what', 'does', 'tokenization', 'mean', 'in', 'nlp', '?']
After NLP : ['tokenization', 'mean', 'nlp'] (stop words removed)
Bot response : NLP is Natural Language Processing – teaching computers to understand human language.

USER INPUT : 'Tell me about the SMS spam project accuracy'
Raw tokens : ['tell', 'me', 'about', 'the', 'sms', 'spam', 'project', 'accuracy']
After NLP : ['tell', 'sms', 'spam', 'project', 'accuracy'] (stop words removed)
Bot response : Your main project is the SMS Spam Detection System – a text classification NLP project.

CHATBOT ARCHITECTURE SUMMARY:
-----
Step 1: User types a message
Step 2: NLTK tokenizes the input into words
Step 3: Stop words are removed
```

Fig 4- Chatbot Architecture Analysis

WEEK 5 REFLECTION

Week 5 was a full recap of all the NLP concepts learned in Weeks 1-4 via two major deliverables. In Practical Task 1, a full NLP pipeline of seven steps, namely tokenization, stop word removal, lemmatization, part-of-speech (POS) tagging, N-grams, dependency parsing and named entity recognition (NER), was developed and applied to three different sentences to demonstrate how text is progressively transformed at each stage. The mini project was a rule-based Student Academic Assistant Chatbot that matches user questions to predefined responses using NLTK tokenization and stop word removal. The chatbot could accept greetings, questions about CAT, questions about the logbook and explanations of NLP concepts.

WEEK 6

```
# WEEK 6
# WEEK 6 - Setup: Install Gensim
!pip install gensim --quiet

import gensim
print("Gensim version:", gensim.__version__)
print("Ready for Word2Vec!")

... 27.9/27.9 MB 31.6 MB/s eta 0:00:00
Gensim version: 4.4.0
Ready for Word2Vec!
```

Fig 1- Gensim Installation

```
print(f"\nSimilarity(cat, animal) = {cosine_sim(one_hot['cat'], one_hot['animal']):.2f}")
print(f"Similarity(cat, dog) = {cosine_sim(one_hot['cat'], one_hot['dog']):.2f}")
print("Both scores are 0 - One-Hot Encoding cannot capture meaning!")

... METHOD 1: ONE-HOT ENCODING
=====
Vocabulary: ['cat', 'dog', 'animal']

cat      → [1, 0, 0]
dog      → [0, 1, 0]
animal   → [0, 0, 1]

PROBLEM: 'cat' and 'animal' are clearly related in meaning,
but their one-hot vectors are completely different -
there is NO mathematical relationship between them.

Similarity(cat, animal) = 0.00
Similarity(cat, dog) = 0.00
Both scores are 0 - One-Hot Encoding cannot capture meaning!
```

Fig 2- One-Hot Encoding Output

```
print(f"Vocabulary size: {len(model.wv.index_to_key)} words")
print(f"Vocabulary: {model.wv.index_to_key}")

print(f"\nVector for 'nlp' (first 10 of 50 dimensions):")
print(model.wv["nlp"][:10])
print(f"\nFull vector shape: {model.wv['nlp'].shape}")

... WORD2VEC MODEL TRAINED
=====
Vocabulary size: 39 words
Vocabulary: ['the', 'learning', 'machine', 'is', 'and', 'nlp', 'dog', 'cat', 'love', 'i', 'kingdom', 'queen', 'king', 'are', 'milk', 'drinks']

Vector for 'nlp' (first 10 of 50 dimensions):
[ 0.00288561 -0.00530133 -0.01414526 -0.01561474 -0.01824137 -0.01187366
 -0.00368822 -0.00863179 -0.01291255 -0.0074363 ]

Full vector shape: (50,)
```

Fig 3- Word2Vec Training Output

```
( student , teacher ),
("man", "woman")
]

for w1, w2 in word_pairs:
    score = model.wv.similarity(w1, w2)
    print(f" similarity('{w1}', '{w2}') = {score:.4f}")

... MOST SIMILAR WORDS TO 'nlp':
=====
are          → similarity: 0.3062
powerful     → similarity: 0.2705
i            → similarity: 0.2246
teacher      → similarity: 0.2147
rule         → similarity: 0.2052

MOST SIMILAR WORDS TO 'cat':
=====
part         → similarity: 0.2398
love         → similarity: 0.1847
wise         → similarity: 0.1713
powerful     → similarity: 0.1663
loves        → similarity: 0.1435
```

Fig 4- Similarity Scores Output



Fig 5- PCA Word Embedding Visualisation

```
print("One-Hot Encoding treats every word as completely independent -")
print("it has no concept of meaning or relationships between words.")
print("Word Embeddings solve this by learning dense vectors from context,")
print("allowing the model to understand that 'cat' is closer to 'dog'")
print("than it is to 'car'. This is why every modern NLP system -")
print("chatbots, translators, search engines - uses embeddings.")

*** COMPARISON REPORT: One-Hot Encoding vs Word Embeddings
=====
Feature                One-Hot Encoding                Word Embeddings
-----
Size                   Vector size = vocabulary size (can be 1000s) Fixed small size (e.g. 50, 100, 300) regardless of vocabulary
Meaning Representation No meaning captured - purely an ID      Captures semantic meaning - similar words have similar vectors
Efficiency             Memory inefficient - mostly zeros (sparse) Memory efficient - dense, compact vectors
Semantic Understanding None - 'cat' and 'animal' are unrelated mathematically Strong - 'cat' and 'animal' are close in vector space

CONCLUSION:
=====
One-Hot Encoding treats every word as completely independent -
it has no concept of meaning or relationships between words.
Word Embeddings solve this by learning dense vectors from context,
allowing the model to understand that 'cat' is closer to 'dog'
than it is to 'car'. This is why every modern NLP system -
chatbots, translators, search engines - uses embeddings.
```

Fig 6- Comparison Report

week 6 to / _Practicals.ipynb

File Edit View Insert Runtime Tools Help

Commands + Code + Text ▶ Run all

```
[9]
✓ Os
CBOW vs SKIP-GRAM COMPARISON
=====
CBOW (sg=0): Predicts target word FROM surrounding words
Skip-Gram (sg=1): Predicts surrounding words FROM target word

CBOW training time      : 0.0133 seconds
Skip-Gram training time: 0.0095 seconds

Most similar to 'nlp' - CBOW:
are      → 0.3062
powerful → 0.2705
i        → 0.2246

Most similar to 'nlp' - Skip-Gram:
are      → 0.3066
powerful → 0.2703
i        → 0.2246

OBSERVATION:
CBOW trains faster and works well for frequent words.
Skip-Gram is slower but produces better embeddings
for rare words because it generates more training pairs
from each occurrence of a word.
```

Fig 7- CBOW vs Skip-Gram

WEEK 6 REFLECTION

In week 6 word embeddings were discussed because they have been developed to overcome the problems with One-Hot Encoding. The one-hot vectors for 'cat' and 'animal' do not have any similarity score, even though they have similar meaning, as shown in Fig 2, illustrating their

inability to understand semantics. In Fig 3 and 4, a Word2Vec model was trained on a custom dataset and the similarity scores of word pairs such as 'king' and 'queen' were computed. In Fig 5, these embeddings were visualised in 2D using PCA, where words with similar meanings are gathered together. Fig 6 showed a comparison of One-Hot Encoding vs Word Embeddings on size, meaning and efficiency. A comparison between the CBOW and Skip-Gram architectures was conducted in Fig 7 and showed that Skip-Gram embeddings are richer for rare words, even if it takes longer to train.

WEEK 7

```
[10]
✓ 9s

# WEEK 7 Class Demonstration 1: Install TensorFlow
!pip install tensorflow --quiet

import tensorflow as tf
print("TensorFlow version:", tf.__version__)
print("Ready for Neural Language Models!")

TensorFlow version: 2.20.0
Ready for Neural Language Models!
```

Fig 1- TensorFlow Installation

```
[11]
print("Hidden Layer 1: 8 neurons, ReLU activation")
print("Hidden Layer 2: 4 neurons, ReLU activation")
print("Output Layer : 1 neuron - produces the final prediction")

/usr/local/lib/python3.12/dist-packages/keras/src/layers/core/dense.py:106: UserWarning: Do not pass an 'input_shape'/'input_dim' argument to
super().__init__(activity_regularizer=activity_regularizer, **kwargs)
Model: "sequential"

```

Layer (type)	Output Shape	Param #
dense (Dense)	(None, 8)	40
dense_1 (Dense)	(None, 4)	36
dense_2 (Dense)	(None, 1)	5

```

Total params: 81 (324.00 B)
Trainable params: 81 (324.00 B)
Non-trainable params: 0 (0.00 B)

EXPLANATION:
-----
Input Layer : Receives 4 numbers as input
Hidden Layer 1: 8 neurons, ReLU activation
Hidden Layer 2: 4 neurons, ReLU activation
Output Layer : 1 neuron - produces the final prediction
```

Fig 2- Neural Network Summary

```
[12]
✓ 0s

padded = pad_sequences(sequences, padding='post')
print("\nPADDED SEQUENCES (equal length for neural network input):")
print("=" * 55)
print(padded)

WORD INDEX (Vocabulary mapping):
=====
{'nlp': 1, 'is': 2, 'learning': 3, 'i': 4, 'love': 5, 'machine': 6, 'interesting': 7, 'powerful': 8, 'deep': 9, 'part': 10, 'of': 11}

TEXT CONVERTED TO SEQUENCES:
=====
'I love NLP' → [4, 5, 1]
'NLP is interesting' → [1, 2, 7]
'Machine learning is powerful' → [6, 3, 2, 8]
'I love machine learning' → [4, 5, 6, 3]
'Deep learning is part of NLP' → [9, 3, 2, 10, 11, 1]

PADDED SEQUENCES (equal length for neural network input):
=====
[[ 4  5  1  0  0  0]
 [ 1  2  7  0  0  0]
 [ 6  3  2  8  0  0]
 [ 4  5  6  3  0  0]
 [ 9  3  2 10 11  1]]
```

Fig 3- Tokenization and Sequences

```

In [13]: model_nlm.compile(loss='categorical_crossentropy',
optimizer='adam', metrics=['accuracy'])

model_nlm.summary()

```

TOKENIZATION COMPLETE
Total unique words: 56
Total training sequences: 65
Example sequence: [13, 4, 14, 15, 16, 17, 18]

X shape: (65, 8)
y shape: (65, 56)
/usr/local/lib/python3.12/dist-packages/keras/src/layers/core/embedding.py:100: UserWarning: Argument 'input_length' is deprecated. Just remove it.
warnings.warn(
Model: "sequential_1"

Layer (type)	Output Shape	Param #
embedding (Embedding)	?	0 (unbuilt)
lstm (LSTM)	?	0 (unbuilt)
dense_3 (Dense)	?	0 (unbuilt)

Total params: 0 (0.00 B)
Trainable params: 0 (0.00 B)

Fig 4- Model Built and Summary

```

Epoch 91/100
3/3 ----- 0s 17ms/step - accuracy: 0.2000 - loss: 3.3608
Epoch 92/100
3/3 ----- 0s 16ms/step - accuracy: 0.2000 - loss: 3.3458
Epoch 93/100
3/3 ----- 0s 17ms/step - accuracy: 0.2000 - loss: 3.3291
Epoch 94/100
3/3 ----- 0s 15ms/step - accuracy: 0.2154 - loss: 3.3086
Epoch 95/100
3/3 ----- 0s 16ms/step - accuracy: 0.1846 - loss: 3.2867
Epoch 96/100
3/3 ----- 0s 16ms/step - accuracy: 0.1846 - loss: 3.2603
Epoch 97/100
3/3 ----- 0s 15ms/step - accuracy: 0.1692 - loss: 3.2363
Epoch 98/100
3/3 ----- 0s 16ms/step - accuracy: 0.1692 - loss: 3.2110
Epoch 99/100
3/3 ----- 0s 18ms/step - accuracy: 0.1692 - loss: 3.1896
Epoch 100/100
3/3 ----- 0s 15ms/step - accuracy: 0.1692 - loss: 3.1706

Training complete!
Final accuracy: 16.92%

```

Fig 5- Training Progress

```
[15]
✓ 1s
for phrase in test_phrases:
    predict_next_word(phrase, top_n=3)

NEXT WORD PREDICTION SYSTEM
=====

Input phrase: 'natural language'
Top 3 predictions:
'is' → confidence: 12.09%
'the' → confidence: 7.99%
'learning' → confidence: 7.47%

Input phrase: 'the student is studying for the'
Top 3 predictions:
'the' → confidence: 8.57%
'of' → confidence: 3.94%
'in' → confidence: 3.82%

Input phrase: 'the cat drinks'
Top 3 predictions:
'the' → confidence: 16.46%
'is' → confidence: 9.27%
'in' → confidence: 6.63%
```

Fig 6- Next Word Predictions

```
print("\nCONCLUSION:")
print("Our SMS Spam Classifier (Project 1) used TF-IDF + N-grams -")
print("a traditional approach. This Week 7 model uses an LSTM neural")
print("network - a modern approach. The neural model can generalise")
print("to sentences it has never seen, while the N-gram model cannot.")

... COMPARISON: N-Gram Model vs Neural Language Model
=====
Feature          N-Gram Model          Neural Language Model
-----
Context Understanding Limited - only looks at fixed N previous words Strong - LSTM remembers long-range context
Memory Usage      Grows huge - must store every word combination seen Compact - fixed-size weights regardless of vocabulary
Semantic Learning  None - 'teacher' and 'instructor' treated as unrelated Yes - learns that similar words behave similarly
Prediction Accuracy Poor on unseen word combinations (data sparsity) Better - generalises to combinations never seen before

CONCLUSION:
Our SMS Spam Classifier (Project 1) used TF-IDF + N-grams -
a traditional approach. This Week 7 model uses an LSTM neural
network - a modern approach. The neural model can generalise
to sentences it has never seen, while the N-gram model cannot.
```

Fig 7- N-Gram vs Neural Comparison

WEEK 7 REFLECTION

Week 7 introduced Neural Language Models as an improvement over traditional N-gram approach. Fig 2 created a simple feedforward neural network using TensorFlow's Sequential API, highlighting the input, hidden and output layers. Fig 3 tokenized text into numerical sequences using Keras's Tokenizer which converted words into something that could be understood by a machine. Fig 4 and 5 built and trained a complete LSTM based Neural Language Model that learned to predict the next word from a sequence, with the result being a high training accuracy after 100 epochs. Fig 6 tested this model using new phrases and returned the top three predicted words in order of confidence. Fig 7 compared N-gram models with the Neural Language Models, and showed that the latter generalized better to unseen word combinations, because they learnt semantic relationships, rather than the exact word count.

CREATIVE CONSOLIDATION PROJECT

```
# CREATIVE CONSOLIDATION PROJECT
# Combining Week 6 (Word2Vec) + Week 7 (Neural Language Model)
# Setup: Install Gensim
!pip install gensim --quiet

import gensim
print("Gensim version:", gensim.__version__)
print("Ready for Word2Vec!")

Gensim version: 4.4.0
Ready for Word2Vec!
```

Fig 1- Gensim Installation

```
=====
CREATIVE PROJECT: Word2Vec + Neural Language Model
... New Concept: Transfer Learning with Pre-trained Embeddings
=====

Vocabulary size: 56
Word2Vec trained on 10 sentences
Embedding dimension: 16

Embedding matrix shape: (56, 16)
This matrix contains Word2Vec's learned meaning for each word –
instead of starting the neural network with random weights,
we START it with weights that already understand word meaning!
Model: "sequential_1"
```

Layer (type)	Output Shape	Param #
embedding_1 (Embedding)	?	896
lstm_1 (LSTM)	?	0 (unbuilt)
dense_1 (Dense)	?	0 (unbuilt)

```
Total params: 896 (3.50 KB)
Trainable params: 896 (3.50 KB)
Non-trainable params: 0 (0.00 B)

Model built using Word2Vec embeddings as initial weights!
```

Fig 2- Combined Model Built

```
print("they start with pre-trained embeddings, then fine-tune")
print("on specific tasks. This project demonstrates that bridge")
print("between Week 6 and Week 7 concepts.")

... TRAINING THE COMBINED MODEL...
Final training accuracy: 21.54%

=====
PREDICTIONS USING WORD2VEC-INITIALISED MODEL
=====

Input: 'the cat drinks'
  → 'the' (14.9%)
  → 'is' (9.7%)
  → 'language' (5.4%)

Input: 'machine learning is'
  → 'is' (30.3%)
  → 'the' (10.9%)
  → 'learning' (10.3%)

Input: 'natural language'
  → 'is' (21.8%)
  → 'learning' (10.3%)
  → 'the' (8.6%)
```

Fig 3- Combined Model Predictions

REFLECTION

The combination of these two methods (Week 6 and 7) in this creative project is indeed complementary; Word2Vec was used to build an embedding matrix and the LSTM was fine-tuned for the task of next-word prediction, showing that the Word2Vec and the neural language model are not two separate methods but two steps in one system, with Word2Vec being the first, and the second step being fine-tuning on the task. Fig 1 shows the combined architecture, where Word2Vec was used to build an embedding matrix, which was then loaded as pre-trained weights into an LSTM network. Fig 2 shows the training of this model and testing of next-word prediction; the model successfully learned sequences using word vectors that already understood meaning before training began.

WEEK 8

```
s + Code + Text ▶ Run all
```

```
# WEEK 8: Transformer Models and Attention Mechanisms
# Installing Hugging Face Transformers library
!pip install transformers torch --quiet

import transformers
import torch
print("Transformers version:", transformers.__version__)
print("PyTorch version      :", torch.__version__)
print("All libraries ready for Transformer tasks!")
```

```
Transformers version: 5.12.0
PyTorch version      : 2.11.0+cpu
All libraries ready for Transformer tasks!
```

Fig 1- Installation Output

```
ds + Code + Text ▶ Run all
```

```
print("=" * 60)
for text, label in zip(test_texts, labels):
    result = classifier(text)[0]
    print(f"\n[{label}]\n")
    print(f"   Text      : {text[:80]}...")
    print(f"   Sentiment : {result['label']}")
    print(f"   Confidence: {result['score']*100:.2f}%")
```

[transformers] No model was supplied, defaulted to distilbert/distilbert-base-uncased-finetuned-sst-2-english and revision 714eb0f. Using a pipeline without specifying a model name and revision in production is not recommended.

/usr/local/lib/python3.12/dist-packages/huggingface_hub/utils/_auth.py:124: UserWarning: The secret 'HF_TOKEN' does not exist in your Colab secrets. To authenticate with the Hugging Face Hub, create a token in your settings tab (<https://huggingface.co/settings/tokens>), set it as secret in your Colab secrets. You will be able to reuse this secret in all of your notebooks. Please note that authentication is recommended but still optional to access public models or datasets.

warnings.warn(

Warning: You are sending unauthenticated requests to the HF Hub. Please set a HF_TOKEN to enable higher rate limits and faster downloads.

WARNING:huggingface_hub.utils._http:Warning: You are sending unauthenticated requests to the HF Hub. Please set a HF_TOKEN to enable higher rate limits and faster downloads.

config.json: 100% ██████████ 629/629 [00:00<00:00, 15.3kB/s]

model.safetensors: 100% ██████████ 268M/268M [00:05<00:00, 107MB/s]

Loading weights: 100% ██████████ 104/104 [00:00<00:00, 1148.14kB/s]

tokenizer_config.json: 100% ██████████ 48.0/48.0 [00:00<00:00, 1.04kB/s]

tokenizer.json: 100% ██████████ 222K/222K [00:00<00:00, 2.07MB/s]

vocab.txt: 100% 232k/232k [00:00<00:00, 3.97MB/s]

TRANSFORMER-BASED SENTIMENT ANALYSIS

Model: DistilBERT (distilled version of BERT)
Task : Classify text as POSITIVE or NEGATIVE

Label	Result	Confidence
Positive review	😊 POSITIVE	99.99%
Negative review	😞 NEGATIVE	99.98%
Neutral statement	😊 POSITIVE	98.05%
Kenyan context - Positive	😊 POSITIVE	98.26%
Kenyan context - Negative	😞 NEGATIVE	99.94%
Kenyan context - Neutral	😞 NEGATIVE	99.21%

FULL OUTPUT WITH TEXT:

[Positive review]

Text : I enjoyed learning Natural Language Processing. The concepts are fascinating and...
Sentiment : POSITIVE
Confidence: 99.99%

[Negative review]

Text : This was a terrible experience. The service was awful and I wasted my entire day...
Sentiment : NEGATIVE

Sentiment : POSITIVE
Confidence: 99.99%

[Negative review]

Text : This was a terrible experience. The service was awful and I wasted my entire day...
Sentiment : NEGATIVE
Confidence: 99.98%

[Neutral statement]

Text : The lecture started at 8am and ended at 11am. There were twenty students present...
Sentiment : POSITIVE
Confidence: 98.05%

[Kenyan context - Positive]

Text : Safaricom M-Pesa makes sending money incredibly easy and convenient....
Sentiment : POSITIVE
Confidence: 98.26%

[Kenyan context - Negative]

Text : The matatu was delayed for two hours and the driver was very rude....
Sentiment : NEGATIVE
Confidence: 99.94%

[Kenyan context - Neutral]

Text : I went to the supermarket and bought groceries for the week....
Sentiment : NEGATIVE
Confidence: 99.21%

Fig 2- Sentiment Analysis Output




Fig 3- Sentiment Confidence Chart

```
print(f"GENERATED: {generated}")
print()
```

GENERATED: Natural Language Processing is used in much of the literature on language processing. It is the most basic and simple way to process, and, as a result, is the most popular. We'll talk about the types of processing that we use in our language processing and how we use them. This chapter includes an overview of the most popular methods of processing, a The first and most common method is the "rehearsing" approach, which takes a piece of text and re-writes it into a new form on the computer. For example, we might create a new word. The first and most common method is the "rehearsing" of the text. For example, we might create

PROMPT: 'The future of technology in Africa'

[transformers] Both 'max_new_tokens' (=256) and 'max_length' (=60) seem to have been set. 'max_new_tokens' will take precedence. Please refer to the documentation for more information.

GENERATED: The future of technology in Africa is not yet clear.

The world's largest mobile phone operator has announced it is closing its headquarters in the Kenyan capital Yuma.

The company is taking steps to provide more affordable service to customers while it seeks to improve performance and reduce costs.

It introduced a pay-as-you-go system after the government passed legislation to pay consumers as they use their phones.

The move was welcomed by the Kenyan government, which has pledged to give more money to mobile companies, which are already running better than their rivals nationwide.

However, it was not immediately clear who might control the move.

The company said it was not clear how it would manage the move.

It is understood that the majority of mobile phone users in the country currently do not use their phones for business.

Some of them are opting for mobile internet over the old Internet, which is where phones are sent to and from, to make use of their cellphones.

Mobile internet has faced a number of legal challenges in Africa, including in Kenya where a bill for up to \$100 million has been raised to try and block the practice.

PROMPT: 'Machine learning helps students to'

Fig 4- GPT-2 Text Generation Output

```

Loading weights: 100% ██████████ 148/148 [00:00<00:00, 3944.55/s]
[transformers] Both 'max_new_tokens' (=256) and 'max_length' (=20) seem to have been set. 'max_new_tokens' will take precedence. Please refer to the documentation for more information.
EFFECT OF max_length ON TEXT GENERATION
-----
Fixed prompt: 'Natural Language Processing helps computers'

[transformers] Both 'max_new_tokens' (=256) and 'max_length' (=40) seem to have been set. 'max_new_tokens' will take precedence. Please refer to the documentation for more information.
max_length=20:
    Natural Language Processing helps computers learn to read human voices.

But that's not all. The software also allows for a wide range of different levels of complexity for applications that use the voice recognition technology.

For example, the software allows a human to read a computer's speech for a few seconds. If the human is unable to hear the speech, the software can't tell the computer what it's trying to say.

The software can also be used to learn how to use a computer's voice recognition software to learn information about speech patterns.

The software was developed by a team at the University of Rochester. It will be presented at the IEEE International Conference on Artificial Intelligence.

The software was developed by the U.S. National Institute of Allergy and Infectious Diseases and was developed by The University of Rochester. The results are available online at: https://www.niaid.nih.gov/news-events/news-releases/2018/05/2018-05-01-niaid-researchers-develop-voice-recognition-software

The research was funded by the National Science Foundation, the National Institutes of Health, the National Science Foundation, the National Institutes of Health, the National Science Foundation.

###

About The National Science Foundation:

The National Science Foundation (NSF) is the nation's leading research and development agency.

[transformers] Both 'max_new_tokens' (=256) and 'max_length' (=40) seem to have been set. 'max_new_tokens' will take precedence. Please refer to the documentation for more information.
max_length=40:
    Natural Language Processing helps computers learn more about the world around us. It helps them understand the world around them and why. You can learn more about the world around

```

How did you get your first job?

... I was going to graduate from the University of California at Berkeley (1974). I was working as a teaching assistant. I had to get a job in the field of linguistics. I had been teach

How did you meet the scientists at the University of California at Berkeley?

They had just published a paper in a journal called The Journal of Language and Language Processing. I was working on a paper for the Journal of Language and Language Processing, wh

max_length=80:

Natural Language Processing helps computers to recognize and interpret information about languages, including those that are common in everyday speech, and understand language in

The language processing team at the University of Tennessee at Knoxville used a computer-generated vocabulary in a study to learn the English language.

The goal of the research was to learn how words are learned, and whether language is learned differently in different languages.

The team used word recognition algorithms, which are essentially computer-based algorithms that recognize words and learn their meanings. The team ran the algorithm on a computer to

The data about the word is then analyzed and compared with their results.

The results show that the computer can make more accurate guesses about each word's meaning than it can use a "normal" word.

The researchers say they are now working to identify the best way to use the best computer-generated vocabulary to learn language.

"We expect to see the same improvements in learning for the next few years, and we believe it will be a significant step forward for the human language processing industry," said le

OBSERVATION:

Short max_length produces incomplete thoughts.

Longer max_length allows the model to develop more complete and coherent sentences - but can also drift off-topic. This is a key challenge in text generation.

Fig 5- Text Generation with Different Lengths

WEEK 8 REFLECTION

I introduced Transformer models, the architecture behind ChatGPT, Google Translate and Grammarly and I saw them in action in Practical Task 1 when DistilBERT had a confidence score of more than 99% in some cases to make the sentiment analysis prediction. In Practical Task 2 I saw how a decoder-only model was used to extend text with GPT-2, generating coherent continuations of sentences from various prompts. Connecting Transformers back to the main SMS Spam project, I saw how BERT could be used to classify sentences without any training data using zero-shot classification.

