

# Quiz: Limited Direct Execution

Total points **54/55**

Take the quiz solo, but feel free to consult a partner student, the book, the videos or other resources if needed. Re-take quiz if your score is less than 80% or if you just want some more practice.

The respondent's email (**faiyaz@pdx.edu**) was recorded on submission of this form.

✓ What's the primary benefit of "Direct Execution"? \*

5/5

- ☐ Ease of Use
- ☐ Honesty
- ☐ Security
- ☒ Speed/Performance
- ☐ Portability



✓ Why do we need limits on direct execution? \*

5/5

- ☐ prevent all uses of I/O devices
- ☐ performance
- ☐ prevent programmer errors (bugs)
- ☒ prevent OS crashes and process crashes caused by other processes' behavior
- ☐ fairness of resource use
- ☐ honesty



✓ Is a segmentation fault an example of limited direct execution? \* 5/5

- ☐ Yes, concurrent access to I/O devices is not allowed
- ☐ No, it is a fault not an interrupt
- ☒ Yes, the MMU limits which memory addresses can be accessed by a program ✓
- ☐ No, seg faults are caused by programmer error

✓ How do system calls help to implement limits on direct execution? \* 5/5

- ☐ because there are a limited number of system calls
- ☐ system calls are invoked mainly via timer interrupts which may not be altered by the application programmer
- ☐ by handling faults for such problems as divide by zero
- ☐ by allowing the OS to run before and during the application's request. the OS can then enforce whatever limits it needs to.
- ☒ system calls allow the OS to expose a limited set of functionality to application programs ✓

✓ A typical processor chip has multiple cores. The OS runs a process on one core and a different process on a different core. This is an example of what kind of sharing? \*5/5

- ☐ time sharing
- ☒ space sharing ✓



- ✓ An OS allocates some memory for a process. Then, when that process is not running, the OS reclaims the physical memory and allows another process to use the same frames of memory. This is an example of what kind of sharing? \*5/5

☒ time sharing



☐ space sharing

How frequently is each type of limit used, checked or invoked? \*

	Multiple times per instruction	Approximately once per instruction	Once per many (variable number of) instructions	Approximately once per 10ms	Score	
MMU address translation	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	1/1	✓
status register mode bit	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	1/1	✓
system call interface	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	1/1	✓
timer interrupt	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	1/1	✓



Which limit prevents which bad thing from occurring? \*

	MMU	Timer Interrupt	System Call Interface	OS does not limit this	Mode bit in Status Register	Score	
program tries to write file for which it does not have privileges	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	1/1	✓
program attempts to run forever	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	1/1	✓
rewriting an interrupt handler	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	1/1	✓
program has a logical bug	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	1/1	✓
modify the time period of the timer interrupt	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	1/1	✓
changing the interrupt vector	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	1/1	✓
program tries to read memory of another program	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	1/1	✓
changing	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	0/1	✗



the mode  
bit

✓ Can the trap instruction (called "int" on Intel x86 chips) be called from user application code? \*5/5

☒ Yes



☐ No

When does the OS run? \*

	yes, OS runs at this time	no, OS does not run at this time	Score	
within a program's while loop	<input type="radio"/>	<input checked="" type="radio"/>	1/1	✓
when a timer interrupt occurs	<input checked="" type="radio"/>	<input type="radio"/>	1/1	✓
at boot time	<input checked="" type="radio"/>	<input type="radio"/>	1/1	✓
during a function call	<input type="radio"/>	<input checked="" type="radio"/>	1/1	✓
during each CPU instruction	<input type="radio"/>	<input checked="" type="radio"/>	1/1	✓
when a fault occurs	<input checked="" type="radio"/>	<input type="radio"/>	1/1	✓
on every I/O device interrupt	<input checked="" type="radio"/>	<input type="radio"/>	1/1	✓
during a system call	<input checked="" type="radio"/>	<input type="radio"/>	1/1	✓



This form was created inside of Portland State University.

# Google Forms

