Date:

Q no: 4

Input:
days = 1 to 7
for each day: numOrders, each order amount > 0
Output:
Per day: total, average (2 decimals), highest order
festival Summary: total festival sales, day with highest
Bar chart: * per 100 Rs.

Pseudocode:
```
Function getValidDays()
 Repeat
Print "Enter number of festival days (1-7):"
 input days
Until day >=1 and day <=7
Return days
End function
Function calculateDailySales(day number)
 Return float.
input numOrders
Repeat validation numOrder >=1
 total=0, highest=0
for i=1 to numOrders
   Repeat
      Input amount
Until amount >0
  total+= amount
if amount > highest then highest = amount
 End for
```

Date:

```
avg = total / numOrders
Print total, avg, highest
Return total
End function
function findHighestSalesDay(dailySales[], numDays)
  return int.
  maxIndex = 0
for i = 1 to numDay - 1.
  if dailySales[i] > dailySales[maxIndex] then
     maxIndex = i
  End if
End for
 Return maxIndex+1
End function.
function displayBarchart(dailySales[], numdays)
  for i = 0 to numDay - 1
   stars = dailySales[i] / 100
   Print "Day", i+1,
Repeat "Day" stars times, Print "*"
Print "Rs", dailySales[i],"
End for
End function -
```