

PENETRATION TESTING REPORT

FOOTPRINTING, RECONNAISSANCE & NETWORK SCANNING PHASES

W2-PM-FINAL | CYBERSECURITY | NETWORKWALKS

Pentester Name (Cybersecurity Professional)	Faizan Manazir
Program/Batch	B083-Networkwalks
Date	26 September 2026
Modules completed	W2-PM1 (Multiple Kali Tools) W2-PM2 (GHDB) W2-PM3 (Maltego) W2-PM4 (theHarvester) W2-PM5 (Zenmap Scanning)
Client/Target	1. networkwalks.com — assigned educational reconnaissance target 2. My own local LAN Network
Permission secured from client?	Yes — activities were performed within the assigned educational scope and on my own local network.
Phases covered	Phase 1: Reconnaissance & Footprinting Phase 2: Scanning & Network Discovery Phase 3-5: Reconnaissance exercises and supporting information gathering

1. Liability Disclaimer

I have performed these activities only within the assigned educational cybersecurity scope and on systems and devices that I own or was authorized to assess. All materials are for education and research purposes only. Do not use anything from this report to break the law. The instructor, the authors and Networkwalks are not responsible for misuse of this knowledge. Every action taken outside an authorized scope is the responsibility of the person performing it. Unauthorized access can be a criminal offence even when no damage is caused.

2. Introduction

This report covers the Week 2 practical activities completed as part of the Cybersecurity & Ethical Hacking program at Networkwalks. The work includes footprinting the networkwalks.com domain using multiple Kali Linux tools (W2-PM1), Google Hacking Database reconnaissance (W2-PM2), Maltego relationship analysis (W2-PM3), passive reconnaissance with theHarvester (W2-PM4), and network discovery with Zenmap (W2-PM5).

All practical activities were performed in Kali Linux. The reconnaissance exercises focused on publicly available information and the network-scanning activity was performed against my own local LAN. Every section below records the command or method used, the result observed, and a short explanation of why the observation matters from a cybersecurity perspective. Evidence screenshots are intentionally omitted from this report and can be inserted at the marked locations.

3. Tools Used

The table below lists each tool used in this report and its purpose.

Tool	Purpose
Kali Linux	Operating system used for reconnaissance, passive information gathering and network scanning.
WHOIS	Find publicly available domain registration details, dates and name servers.
WhatWeb	Fingerprint publicly observable web technologies, CMS and plugins.
nslookup	Resolve the domain name to its IP address using DNS.
curl -I	Read HTTP response headers from the website.
wafw00f	Detect whether a Web Application Firewall is publicly identifiable.
dnsrecon	Enumerate DNS records such as NS, MX, SPF, TXT and service-related records.
Google / GHDB	Perform search-engine reconnaissance using specialized search operators.
Maltego	Create a visual graph of entities and relationships and run reconnaissance transforms.
theHarvester	Collect publicly available emails, hosts, IPs and related information from supported sources.
Zenmap / Nmap	Discover live hosts on the authorized local subnet and visualize network topology.

4. Activities Performed

4.1 Footprinting & Reconnaissance

I performed reconnaissance against the networkwalks.com domain using six Kali Linux tools: WHOIS, WhatWeb, Nslookup, Curl, Wafw00f and DNSRecon. Each tool was used to collect a different category of publicly observable information.

First, I used WHOIS to obtain publicly available domain registration information and identify the domain's name servers. The results provided information about the domain registration and hosting infrastructure.

I then used WhatWeb to identify technologies used by the website. The results identified WordPress 7.0.4 and WP Download Manager 3.3.58, along with other information exposed by the website. Using Nslookup, I resolved the domain name to its IP address. The recorded result identified 192.232.216.135.

I used Curl with the -I option to inspect the HTTP response headers. This provided additional information about the web application and exposed the WordPress REST API endpoint /wp-json/. Next, I used Wafw00f to determine whether a Web Application Firewall was protecting the website. The recorded result identified ModSecurity (SpiderLabs).

Finally, I used DNSRecon to enumerate DNS records. The results provided information relating to name servers, mail servers, SPF/TXT records, service records and DNS software information.

4.2 Google Hacking Database (GHDB)

The GHDB activity introduced search-engine reconnaissance using specialized Google operators. The practical work focused on identifying publicly indexed security-camera related results and directory listings containing mathematics PDF material. The captured search results were documented in the accompanying worksheet.

For the security-camera search, ten result entries were recorded from the captured Google results. The entries included results from Alliance for Coastal Technologies, 100.42.92, Course Hero, Exploit-DB, Accio Work, Blogger and xvideosbr.to. The report records the search-result sources without reproducing direct camera-access URLs or credentials.

#	Source	Recorded Search Result
1	Alliance for Coastal Technologies	Live view - AXIS 215 PTZ Network Camera
2	100.42.92	Live View - AXIS 211 Network Camera version 4.11
3	Course Hero	Cameras-Long.txt — ViewerFrame / Live View - AXIS
4	Exploit-DB	tilt title: Live View / - AXIS
5	Exploit-DB	intitle: MJPG Live Demo / intext: Select preset position
6	Accio Work	Live View Axis: Find Top PTZ Cameras & Streaming Devices
7	Blogger.com	Inurl Live View Axis Night Club Anyone Want To Hack Into ...
8	Exploit-DB	intitle: Live View / - AXIS — Various Online Devices GHDB
9	xvideosbr.to	Site query involving inurl:view.shtml / intitle: Live View / - AXIS
10	Exploit-DB	tilt intitle: Live View / - AXIS inurl:view/view.shtml

The mathematics directory-listing exercise produced the following ten documented entries.

#	Source	Directory Listing	URL
1	University of New Mexico	Index of ~/megrad/Math	http://www.unm.edu/~megrad/Math/
2	Ochicken.net	Index of /library/Mathematics/	https://ochicken.net/library/Mathematics/
3	University of Liverpool	Index of /maths	http://pcwww.liv.ac.uk/maths/
4	The Netlib	Index of /math/docpdf	https://www.netlib.org/math/docpdf/
5	ИПТ РАН	Index of /ebooks/books/open	http://www.iisp.ac.ru/ebooks/books/open/
6	University of Galway	Index of ~/rquinlan/linearalgebra	https://maths.nuigalway.ie/~rquinlan/linearalgebra/
7	Case Western Reserve University	Index of /artsci/math/singer/publish	https://case.edu/artsci/math/singer/publish/
8	Dartmouth Mathematics	Index of ~/carlp/PDF	https://www.math.dartmouth.edu/~carlp/PDF/
9	Jsoftware	Index of /books/pdf	https://www.jsoftware.com/books/pdf/
10	Carnegie Mellon University	Index of /users/math/wow/osummerinst	https://www.cmu.edu/users/math/wow/osummerinst/

[Evidence: PM2 — GHDB search-result screenshots and completed worksheet — insert screenshot here]

4.3 Maltego

Maltego was used to create a Domain entity for networkwalks.com and run the transform [Utilities] To Emails @domain [Search Engine]. The transform completed successfully on one entity. The captured output showed that 10 unified credits were consumed, leaving 190 credits. The graph remained centered on the networkwalks.com domain entity and no additional linked email entity was displayed in the captured graph.

Item	Recorded Result
Domain entity	networkwalks.com
Transform	[Utilities] to emails @domain [Search Engine]
Entities processed	1
Execution status	Completed
Credits consumed	10 unified credits
Credits remaining	190
Visible graph result	Domain node remained visible; no additional linked entity displayed in the captured graph.

4.4 Footprinting with theHarvester

The theHarvester exercise used microsoft.com as the module-specified passive reconnaissance target. Task 1 was performed with Baidu and a result limit of 1000. Task 2 was performed using all supported sources with a result limit of 50. The outputs were preserved separately as raw text because the all-source result was too large to reproduce completely in the report.

Task	Command	Observed Result
------	---------	-----------------

Task 1	theHarvester -d microsoft.com -l 1000 -b baidu	0 IPs found; 0 emails found; 0 people found; 2 hosts found: cla.opensource.microsoft.com and support.microsoft.com.
Task 2	theHarvester -d microsoft.com -l 50 -b all	All-source passive reconnaissance output was captured separately as raw output. The complete terminal output is intentionally not reproduced here because it was large.

4.5 Network Scanning with Zenmap

For the final activity, I used Zenmap to perform network discovery on my own local network. The practical required me to identify my local IP address and subnet, discover live hosts, identify their IP and MAC addresses, and generate a network topology.

I first used the Kali Linux `ip` command to identify the active interface and local IPv4 address. The `eth0` interface was assigned 10.0.0.3/24, which corresponds to the local subnet 10.0.0.0/24.

I then entered the subnet into Zenmap and selected Ping Scan. Zenmap used the command `nmap -sn 10.0.0.0/24` and scanned 256 IP addresses. Three live hosts were identified.

IP Address	MAC Address	Status
10.0.0.1	52:54:00:12:35:00	Up
10.0.0.2	08:00:27:53:38:90	Up
10.0.0.3	08:00:27:5A:87:BC	Up — Kali host

The MAC address for 10.0.0.3 was also confirmed directly from the `eth0` interface using `ip link show eth0`. After completing the scan, I opened the Topology section in Zenmap and generated the network topology.

5. Risk Analysis / Impact

Based on the information collected during the reconnaissance, GHDB, passive harvesting and local network scanning activities, I identified the following potential risks. These are observations from information gathering and host discovery, not confirmed vulnerabilities.

#	Risk / Finding	Evidence / Observation	Potential Impact	Risk Level
1	Web technology information exposed	WhatWeb identified WordPress and WP Download Manager	Attackers may use exposed technology/version information to identify software requiring further security review	• Medium
2	Server IP address identifiable	Nslookup resolved the domain to 192.232.216.135	Provides information about the network location of the web service	• Low
3	HTTP technical information exposed	Curl returned HTTP response headers and exposed <code>/wp-json/</code>	May assist technology fingerprinting and further enumeration	• Low
4	WAF technology identifiable	Wafw00f identified ModSecurity (SpiderLabs)	Reveals information about the web application's security architecture	• Low
5	DNS infrastructure information exposed	DNSRecon identified DNS, mail and service-related records	DNS information can help build a broader infrastructure profile	• Medium
6	Publicly indexed information discoverable	GHDB searches returned indexed camera-related and directory-listing results	Search-engine indexing can expose information that assists reconnaissance and profiling	• Medium
7	Public-source host information collected	theHarvester identified two microsoft.com hostnames during the Baidu task	Public host information can support external reconnaissance and infrastructure mapping	• Low
8	Multiple live hosts visible on local network	Zenmap identified three live hosts in the 10.0.0.0/24 network	Unknown or unauthorized devices may potentially be present on a network	• Medium

Risk level key: • Critical • Medium • Low

The risks above are observations from the reconnaissance and scanning exercises, not confirmed vulnerabilities. The practical exercises primarily involved information gathering, public-source enumeration and host discovery. No exploitation or vulnerability validation was performed as part of these activities.

Therefore, the presence of information such as a software version, IP address, DNS record, indexed search result or hostname does not by itself mean that the system is vulnerable. Further authorized security testing would be required to confirm any actual vulnerability.

6. Recommendations

Based on the observations from these activities, I recommend the following security improvements:

1. Review publicly exposed technology information

Organizations should regularly review what information about their web technologies, CMS and plugins is publicly visible.

2. Keep software updated

CMS platforms, plugins and other web technologies should be regularly updated and reviewed against current security advisories.

3. Review HTTP headers

HTTP response headers should be reviewed to determine whether unnecessary technical information is being exposed.

4. Review DNS records regularly

DNS records should be checked periodically to ensure that only required information and services are publicly exposed.

5. Properly configure and monitor the WAF

Keep the WAF enabled and appropriately tuned, and review its configuration and logs regularly.

6. Review search-engine indexing

Organizations should periodically check search-engine results for information that should not be publicly indexed.

7. Review public directories and files

Publicly accessible directory listings and files should be reviewed and restricted where they are not intended for public access.

8. Review external information exposure

Use passive reconnaissance periodically to understand what infrastructure information can be collected by an external observer.

9. Perform regular internal network discovery

Organizations should periodically scan their own networks to identify active devices.

10. Investigate unknown devices

Any unexpected device discovered during network scanning should be investigated and verified.

11. Maintain network documentation

Network topology and device information should be documented and updated regularly.

12. Perform security testing with authorization

Reconnaissance and scanning should only be performed against systems and networks where appropriate authorization has been provided.

7. Conclusion

During Week 2 of my Cybersecurity & Ethical Hacking internship, I completed practical activities covering footprinting, reconnaissance, search-engine intelligence gathering, passive harvesting and network scanning.

In the footprinting activity, I used six Kali Linux tools to collect information about the networkwalks.com domain. I learned how WHOIS can provide domain information, WhatWeb can identify web technologies, Nslookup can resolve domain names, Curl can inspect HTTP headers, Wafw00f can identify a WAF, and DNSRecon can provide additional DNS information.

The GHDB activity demonstrated how search-engine operators can be used to locate publicly indexed information. I documented ten security-camera-related search results and ten mathematics directory listings. The exercise showed how search engines can unintentionally expose information that contributes to an attacker's reconnaissance.

In the Maltego activity, I created a domain entity for networkwalks.com and executed a search-engine email-domain transform. The transform completed successfully, although no additional linked entity was displayed in the captured graph.

The theHarvester exercise demonstrated passive reconnaissance using different public-source configurations. The Baidu task returned two hostnames and no IP, email or people results, while the all-source task generated a larger output that was preserved separately as raw evidence.

Finally, I used Zenmap to identify my local network configuration and discover active hosts. The local Kali interface was 10.0.0.3/24, the scanned subnet was 10.0.0.0/24, and three live hosts were identified. I also collected IP and MAC address information and created a network topology.

The exercises showed me that information gathering is an important part of cybersecurity. Even before attempting to exploit a system, a security professional can learn a significant amount about an environment by carefully analyzing publicly available information and network responses.

I also learned that technical findings should be documented clearly. A good cybersecurity report should explain what was performed, what was discovered, what the observation means, what risk it may create, and what can be done to reduce that risk.

Finally, I learned that reconnaissance and scanning must always be performed within an authorized scope. These activities were completed as part of the assigned educational cybersecurity lab and on my own local network.

8. Evidences Collected

1. PM1 — WHOIS output

```
(kali@kali)-[/media/sf_Downloads/Raw Output/PM1-Footprinting/Task1-WHOIS]
$ whois networkwalks.com | tee WHOIS.txt
Domain Name: NETWORKWALKS.COM
Registry Domain ID: 2452319255_DOMAIN_COM-VRSN
Registrar WHOIS Server: whois.godaddy.com
Registrar URL: http://www.godaddy.com
Updated Date: 2025-11-12T10:08:43Z
Creation Date: 2019-11-06T22:51:46Z
Registry Expiry Date: 2027-11-06T22:51:46Z
Registrar: GoDaddy.com, LLC
Registrar IANA ID: 146
Registrar Abuse Contact Email: abuse@godaddy.com
Registrar Abuse Contact Phone: 480-624-2505
Domain Status: clientDeleteProhibited https://icann.org/epp#clientDeleteProhibited
Domain Status: clientRenewProhibited https://icann.org/epp#clientRenewProhibited
Domain Status: clientTransferProhibited https://icann.org/epp#clientTransferProhibited
Domain Status: clientUpdateProhibited https://icann.org/epp#clientUpdateProhibited
Name Server: NS6135.HOSTGATOR.COM
Name Server: NS6136.HOSTGATOR.COM
DNSSEC: unsigned
URL of the ICANN Whois Inaccuracy Complaint Form: https://www.icann.org/wicf/
>>> Last update of whois database: 2026-09-26T07:35:05Z <<<

For more information on Whois status codes, please visit https://icann.org/epp
```

2. PM1 — WhatWeb output

```
(kali@kali)-[/media/sf_Downloads/Raw Output/PM1-Footprinting/Task2-WhatWeb]
$ whatweb networkwalks.com
http://networkwalks.com [301 Moved Permanently] Apache, Cookies[__wpedm_client], Country[UNITED STATES][US], HTTPServer[Apache], HttpOnly[__wpedm_client], IP[192.232.216.135], RedirectLocation[https://networkwalks.com/], UncommonHeaders[permissions-policy,x-redirect-by,upgrade]
https://networkwalks.com [200 OK] Apache, Bootstrap[7.1.2], Cookies[__wpedm_client], Country[UNITED STATES][US], Email[info@networkwalks.com], Frame, Google-Tag-Manager, HTML5, HTTPServer[Apache], HttpOnly[__wpedm_client], IP[192.232.216.135], JQuery[3.7.1], MetaGenerator[WordPress 7.1.2,WordPress Download Manager 3.3.58], Open-Graph-Protocol[website], Script[4684NR-IPiB&pidnVar2=50511&prtVar2=7&scvVar2=12,application/json,application/ld+json,module,speculationrules,text/javascript], Title[Networkwalks Academy], UncommonHeaders[permissions-policy,link,upgrade], WordPress[7.1.2]
https://networkwalks.com/ [200 OK] Apache, Bootstrap[7.1.2], Country[UNITED STATES][US], Email[info@networkwalks.com], Frame, Google-Tag-Manager, HTML5, HTTPServer[Apache], IP[192.232.216.135], JQuery[3.7.1], MetaGenerator[WordPress 7.1.2,WordPress Download Manager 3.3.58], Open-Graph-Protocol[website], Script[4684NR-IPiB&pidnVar2=50511&prtVar2=7&scvVar2=12,application/json,application/ld+json,module,speculationrules,text/javascript], Title[Networkwalks Academy], UncommonHeaders[permissions-policy,link,upgrade], WordPress[7.1.2]
```

3. PM1 — Nslookup output

```
kali@kali: /media/sf_Downloads/Raw Output/PM1-Footprinting/Task3-NSLookup

Session Actions Edit View Help

(kali@kali)-[/media/sf_Downloads/Raw Output/PM1-Footprinting/Task3-NSLookup]
$ nslookup networkwalks.com
Server:      1.1.1.1
Address:     1.1.1.1#53

Non-authoritative answer:
Name:   networkwalks.com
Address: 192.232.216.135
```


4. PM1 — Curl HTTP headers

```
kali@kali: /media/sf_Downloads/Raw Output/PM1-Footprinting/Task4-Curl

Session Actions Edit View Help

(kali@kali)-[/media/sf_Downloads/Raw Output/PM1-Footprinting/Task4-Curl]
$ curl -I https://networkwalks.com
HTTP/2 200
permissions-policy: private-state-token-redemption=(self "https://www.google.com" "https://www.gstatic.com" "https://recaptcha.net" "https://challenges.cloudflare.com" "https://hcaptcha.com"), private-state-token-issuance=(self "https://www.google.com" "https://www.gstatic.com" "https://recaptcha.net" "https://challenges.cloudflare.com" "https://hcaptcha.com")
link: <https://networkwalks.com/wp-json/>; rel="https://api.w.org/", <https://networkwalks.com/wp-json/wp/v2/pages/53>; rel="alternate"; title="JSON"; type="application/json", <https://networkwalks.com/>; rel=shortlink
set-cookie: __wpedm_client=36cf582078de60df164dd9ab2f0e713d; path=/; domain=networkwalks.com; secure; HttpOnly
content-type: text/html; charset=UTF-8
date: Sat, 26 Sep 2026 07:39:19 GMT
server: Apache
```

5. PM1 — Wafw00f output



```
kali@kali: /media/sf_Downloads/Raw Output/PM1-Footprinting/Task5-Wafw00f
Session Actions Edit View Help


(kali@kali)-[/media/sf_Downloads/Raw Output/PM1-Footprinting/Task5-Wafw00f]
$ wafw00f networkwalks.com

Plates
Computer
kali
Desktop
Icons
Trash
Videos
~ WAFW00F : v2.4.2 ~
The Web Application Firewall Fingerprinting Toolkit

[*] Checking https://networkwalks.com
[+] The site https://networkwalks.com is behind ModSecurity (SpiderLabs) WAF.
[~] Number of requests: 2

(kali@kali)-[/media/sf_Downloads/Raw Output/PM1-Footprinting/Task5-Wafw00f]
$
```


6. PM1 — DNSRecon output




```
kali@kali: /media/sf_Downloads/Raw Output/PM1-Footprinting/Task6-DNSRecon
Session Actions Edit View Help

(kali@kali)-[/media/sf_Downloads/Raw Output/PM1-Footprinting/Task6-DNSRecon]
$ dnsrecon -d networkwalks.com
2026-09-26T03:41:22.148788-0400 INFO Starting enumeration for domain: networkwalks.com
2026-09-26T03:41:22.149416-0400 INFO std: Performing General Enumeration against: networkwalks.com ...
2026-09-26T03:41:22.936198-0400 ERROR No answer for DNSSEC query for networkwalks.com
2026-09-26T03:41:23.927409-0400 INFO SOA ns6135.hostgator.com 50.87.144.87
2026-09-26T03:41:28.609492-0400 INFO NS ns6135.hostgator.com 50.87.144.87
2026-09-26T03:41:28.762983-0400 ERROR Recursion enabled on NS Server 50.87.144.87
2026-09-26T03:41:29.925486-0400 INFO MX mail.networkwalks.com 192.232.216.135
2026-09-26T03:41:33.992869-0400 INFO TXT networkwalks.com google-site-verification=rr04eRmqHoWY3XemnizDNVK4q75X-Ij-mjgEeg-UsYI
2026-09-26T03:41:33.993148-0400 INFO TXT networkwalks.com v=spf1 +a +mx +ip4:50.87.144.87 +include:websitewelcome.com ~all
2026-09-26T03:41:34.790807-0400 INFO Enumerating SRV Records
2026-09-26T03:41:40.795701-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.203.9 443
2026-09-26T03:41:40.795886-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.203.15 443
2026-09-26T03:41:40.796018-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.204.15 443
2026-09-26T03:41:40.796148-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.204.9 443
2026-09-26T03:41:40.796267-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.204.14 443
2026-09-26T03:41:40.796385-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.203.14 443
2026-09-26T03:41:40.796501-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.204.11 443
2026-09-26T03:41:40.796617-0400 INFO SRV _autodiscover._tcp.networkwalks.com cpanelmaildiscovery.cpanel.net 184.94.203.11 443
2026-09-26T03:41:42.559682-0400 INFO 8 Records Found
2026-09-26T03:41:42.560180-0400 INFO Completed enumeration for domain: networkwalks.com
```

7. PM3 — Maltego domain graph



8. PM3 — Maltego transform output



9. PM4 — theHarvester Baidu output

```
kali@kali: ~
Session Actions Edit View Help

(kali@kali)-[~]
$ mkdir -p "/media/sf_Downloads/Raw Output/PM4-theHarvester"

(kali@kali)-[~]
$ theHarvester -d microsoft.com -l 1000 -b baidu
Read proxies.yaml from /etc/theHarvester/proxies.yaml
*****
*
* [TheHarvester]
*
* theHarvester 4.11.1
* Coded by Christian Martorella
* Edge-Security Research
* cmartorella@edge-security.com
*
*****

[*] Target: microsoft.com

[*] Searching Baidu.

[*] No IPs found.

[*] No emails found.

[*] No people found.

[*] Hosts found: 2
cla.opensource.microsoft.com
support.microsoft.com
```

10. PM4 — theHarvester all-source raw output

```
kali@kali: ~
Session Actions Edit View Help

(kali@kali)-[~]
$ theHarvester -d microsoft.com -l 50 -b all
Read proxies.yaml from /etc/theHarvester/proxies.yaml
*****
*
* [TheHarvester]
*
* theHarvester 4.11.1
* Coded by Christian Martorella
* Edge-Security Research
* cmartorella@edge-security.com
*
*****


[*] Target: microsoft.com

Read api-keys.yaml from /etc/theHarvester/api-keys.yaml
Failed to process bevigil search for word: 'microsoft.com'
Error Message:
[!] Missing API key for bevigil.
Read api-keys.yaml from /etc/theHarvester/api-keys.yaml


[!] Missing API key for Bitbucket.
Read api-keys.yaml from /etc/theHarvester/api-keys.yaml
Failed to process bufferoverrun search for word: 'microsoft.com'
Error Message:
[!] Missing API key for bufferoverrun.
Read api-keys.yaml from /etc/theHarvester/api-keys.yaml
Failed to perform BuiltWith search for word: 'microsoft.com'
A Missing Key Error occurred in builtwith:
[!] Missing API key for BuiltWith.
Read api-keys.yaml from /etc/theHarvester/api-keys.yaml
Failed to process brave search for word: 'microsoft.com'
Error Message:
[!] Missing API key for Brave Search.
Read api-keys.yaml from /etc/theHarvester/api-keys.yaml
Censys API key is missing or invalid:
[!] Missing API key for Censys ID and/or Secret.
Read api-keys.yaml from /etc/theHarvester/api-keys.yaml
Read api-keys.yaml from /etc/theHarvester/api-keys.yaml
A Missing key error occurred in criminalip:
[!] Missing API key for criminalip.
Read api-keys.yaml from /etc/theHarvester/api-keys.yaml
A Missing Key error occurred in dehashed:
[!] Missing API key for Dehashed.
Read api-keys.yaml from /etc/theHarvester/api-keys.yaml

[!] Missing API key for DNSDumpster.
Read api-keys.yaml from /etc/theHarvester/api-keys.yaml
A Missing Key error occurred in dymo:
```

11. PM5 — Zenmap Ping Scan output



12. PM5 — Zenmap topology



Author

Faizan Manazir

Cybersecurity Professional B083

LinkedIn: <https://www.linkedin.com/in/faizan-manazir-38046527a/>

Project Information

Program Name: Cybersecurity program at Networkwalks | Week: 02 | Repository: [GitHub](#)