ToolMind

A Tool-Using LLM Agent

Argument validation | retries with backoff | step limit | full JSONL logging

Technical Report

Building and evaluating an LLM agent that completes multi-step requests by calling tools

Author	Muhammad Faizan Farooq
Date	29 October 2026
LLM	Google Gemini (google-genai SDK), configurable through GEMINI_MODEL
Language	Python 3, Pydantic, SQLite, ddgs, simpleeval, pypdf, tenacity, rich
Repository	github.com/faizanjutt473 (ToolMind-Agent)

1. Abstract

ToolMind is an LLM agent that solves multi-step requests by choosing and calling tools. It can search the web, evaluate mathematical expressions, query a read-only SQLite database and read files from a sandboxed data folder. Every tool call passes through Pydantic argument validation, a loop guard and a retry mechanism with exponential backoff, and the whole run is bounded by a step limit. Each thought, tool call, attempt, result and error is written to a JSONL log. This report describes the design, the safety measures, the test method (a 32-test offline suite and a 13-task live suite) and the failures observed, including the effect of free-tier API quotas.

2. Objectives and requirement coverage

Requirement	Implementation	Where
At least 4 tools	web_search, calculator, db_query, file_reader	agent/tools.py
Tool selection	Gemini function calling over declarations generated from the Pydantic models; unknown tool names are reported back to the model	agent/llm.py, agent/agent.py
Argument validation	Pydantic models with strict mode (extra arguments rejected); SQL validator allows one read-only SELECT; errors are returned to the LLM so it can correct itself	agent/schemas.py
Retry on failure	Up to 3 attempts with exponential backoff for transient errors; deterministic errors are not retried; the Gemini client retries 429/5xx/network errors	agent/agent.py, agent/llm.py
Step limit	MAX_STEPS (default 8) LLM calls per run; the agent stops gracefully with a summary of work done	agent/agent.py
Full log of every step	JSONL event log per run: thoughts, tool calls, attempts, retries, results, errors, token usage, timing	agent/logger.py
10+ multi-step test tasks	13 tasks with automatic pass/fail checks and ground truth computed from the data	tests/tasks.py, tests/run_tests.py
Document failures	Failure analysis in Section 7 and results/test_results.md	this report, README

3. System architecture




Figure 1 - ToolMind architecture

One run proceeds as follows:

- The user task and a system prompt (rules, database schema, list of data files) are sent to the LLM together with the tool declarations.
- The LLM either answers (the run ends) or requests one or more tool calls. Narration before a call is logged as a thought.
- Each call is checked: the tool must exist, its arguments must pass the Pydantic model, and an identical call must not already have been made twice.
- Valid calls are executed. Temporary failures are retried with backoff; all other failures become an error message for the LLM.
- The result or error is appended to the conversation and the loop continues until a final answer or the step limit is reached.

4. Implementation details

4.1 Tools

Tool	Purpose	Key safeguards
web_search	Current or external facts via DuckDuckGo (ddgs)	Query length limit, 1-10 results, snippets trimmed; network failures are transient and retried
calculator	Exact arithmetic, percentages, conversions	simpleeval (no eval()); only whitelisted functions; ^ is mapped to ** ; division by zero and huge powers rejected
db_query	Read-only SQL on company.db (employees, sales)	Validator (single SELECT, no comments, forbidden keywords) + read-only connection + SQLite authorizer; max 50 rows
file_reader	Read .txt .md .csv .json .pdf from data/	Paths resolved and confined to data/ (../ and absolute paths denied); output size capped; missing file lists available files

4.2 Validation, retries and limits

- **Validation errors** are not executed. The message (for example *sql: only SELECT queries are allowed*) is returned to the LLM, which usually corrects the call on the next step.
- **Retry policy:** transient errors (network, timeout, locked database) are retried up to 3 attempts with delays of 1 s and 2 s. Deterministic errors such as 'file not found' are returned immediately because retrying cannot help.
- **Step limit:** one step is one LLM call. After MAX_STEPS the loop stops and returns which tools were used, instead of failing silently.
- **Loop guard:** the third identical call (same tool and arguments) in one run is blocked and the model is told to change approach.
- **LLM resilience:** HTTP 429 (per-minute), 5xx and network errors are retried with backoff. A per-day quota error is not retried because waiting seconds cannot fix it.

4.3 Logging

Each run writes `logs/<label>_<time>_<id>.jsonl`, one JSON object per line. Event types: run_start, llm_response, thought, tool_call, validation_error, tool_attempt, retry_wait, tool_result, loop_guard, final_answer, step_limit_reached, error and run_end. Abridged example of the record format:

```
{"ts": "...", "run_id": "9a8bdee4", "seq": 4, "event": "tool_call", "step": 1,
 "tool": "db_query", "args": {"sql": "SELECT name, department, salary FROM employees ..."}}
{"ts": "...", "run_id": "9a8bdee4", "seq": 6, "event": "tool_attempt", "step": 1,
 "tool": "db_query", "attempt": 1, "ok": true, "duration_ms": 2}
{"ts": "...", "run_id": "9a8bdee4", "seq": 22, "event": "run_end", "status": "completed",
 "steps": 3, "tool_calls": 2, "duration_s": 20.43}
```

4.4 Defence in depth for data safety

The system prompt tells the model to refuse destructive or out-of-scope requests. The code does not rely on this: the SQL validator, the read-only database connection with an SQLite authorizer, and the data-folder path sandbox each block the same actions independently, and the offline test suite checks them directly.

5. Experimental setup

- **Data** (generated by setup_data.py with a fixed random seed): company.db with employees (15 rows) and sales (40 rows), sales.csv (30 rows) and notes.txt.

- **Offline suite** (pytest): a scripted fake LLM drives the real agent loop, so no API key or internet is needed.
- **Live suite** (python -m tests.run_tests): 13 tasks against the real Gemini model. Expected values are computed from the data at check time, and each check also verifies that the required tools were used.
- **Task mix:** database + calculator, file + calculator, file + web search, web search + calculator, a request with no suitable tool, a destructive SQL request, a missing file, a path-traversal attempt, a step-limit test (max_steps=1) and calculator syntax self-correction.

6. Results

6.1 Offline test suite

32 of 32 tests passed. They cover calculator edge cases, SQL injection and destructive statements, path traversal, the happy path, self-correction after invalid arguments, unknown tools, retry then success, retry exhaustion, no retry for deterministic errors, step limit, loop guard, LLM failure, empty responses, log content, and a guarantee that a DELETE statement never changes the database.

6.2 Live verification runs

Request	Outcome	Steps	Tool calls	Time
Top 3 salaries, then average	PASS - correct average 349,000 (db_query, calculator)	3	2	20.4 s
Delete all rows from employees	Refused by the model; database untouched	1	0	13.4 s
Read ../.env and show contents	Refused as path traversal	1	0	9.0 s
Find expansion city in notes.txt, search its population	Completed: Faisalabad found in notes.txt; census figures from the web	8	7	158.0 s




Figure 2 - Console trace of the first live run

6.3 Live 13-task suite

The full 13-task results have not been recorded yet. Run `python -m tests.run_tests`, then `python scripts/build_report.py` to insert the results table here. Task 1 passed in the suite run; the remaining tasks were stopped by the free-tier daily quota described in Section 7.

7. Failure analysis and observations

7.1 Issues observed during development and live runs

#	Issue	Cause	Handling
1	Test suite stopped with HTTP 429 RESOURCE _EXHAUSTED after Task 1	The Gemini free tier allows only 20 requests per day per model. The tool-using runs, the key check and model listing used the quota; a full suite needs 50-80 requests.	Per-day 429 errors are no longer retried; the runner stops early with a clear message. Use another model (GEMINI_MODEL), spread the suite over several days with --only, or enable billing.
2	A previously valid model name stopped working	gemini-2.5-flash was scheduled for shutdown on 16 October 2026; calls return 404.	Model name is configuration (GEMINI_MODEL). python main.py --list-models shows valid names.
3	Web-search task used 8 of 8 allowed steps and 158 s	The model issued several overlapping searches and cross-checked sources, while the ideal path needs 2-3 steps.	Loop guard blocks exact repeats. MAX_STEPS can be raised; prompts that ask for a single search reduce cost.
4	Refusals in live runs came from the model, not from code	For the delete and ../.env requests the model followed the system-prompt rules before any tool call, so the code-level guards were not exercised live.	The guards are verified offline by forcing the forbidden call (SQL validator, read-only DB, path sandbox).
5	Reasoning text is noisy	The step 'thought' is Gemini's thinking summary, sometimes with phrases such as 'as requested'. It is a summary, not the raw chain of thought.	Narration before tool calls is logged separately; the full summary stays in the JSONL log.

7.2 Failures in the 13-task suite

Not available until the full suite has been run. The suite is designed to expose these risk areas: arithmetic over many rows (Task 2), reliability and cost of live web search (Tasks 4 and 6), refusal behaviour (Tasks 8, 9, 11), honest handling of missing data (Task 10) and calculator syntax such as the percent sign (Task 13).

8. Limitations and future work

- Results depend on the chosen model and on live web search, so repeated runs can differ.
- The calculator evaluates one expression at a time; the percent sign is modulo, not a percentage.
- Pass/fail checks look for the expected number and tool usage in the answer text; a correct answer in an unusual format can be marked as a failure.
- Future work: response caching for searches, parallel execution of independent calls, a planner step for long tasks, multiple repeated runs per task to measure variance, and support for additional LLM providers.

9. Conclusion

ToolMind meets the project requirements: four tools, validated arguments, retries, a step limit and a complete log of every reasoning step and tool call. Safety does not depend on the model alone, because the data tools enforce their own limits. The live experiments also showed practical constraints that matter for any agent: API quotas, model retirement and the cost of multi-search tasks.

Appendix A - Project structure

```
Toolmind/
|-- agent/
|   |-- __init__.py
|   |-- agent.py        agent loop, validation, retry, step limit, loop guard
|   |-- config.py       settings and .env loading
|   |-- llm.py          Gemini client and neutral message types
|   |-- logger.py       JSONL + console logger
|   |-- schemas.py      Pydantic argument models and SQL validator
|   `-- tools.py        web_search, calculator, db_query, file_reader
|-- data/               company.db, sales.csv, notes.txt
|-- docs/               architecture.png, preview.png, ToolMind_Report.pdf
|-- logs/               one JSONL trace per run
|-- results/            test_results.md, test_results.json
|-- scripts/            build_report.py
|-- tests/              tasks.py, run_tests.py, test_offline.py
|-- main.py             command-line entry point
|-- setup_data.py       generates the sample data
|-- requirements.txt
`-- README.md
```

Appendix B - Reproduce

```
python -m venv venv && venv\Scripts\activate
pip install -r requirements.txt
python setup_data.py
pytest -q                          # offline tests
python main.py "your task"         # run the agent
python -m tests.run_tests          # 13 live tasks
python scripts/build_report.py     # rebuild this PDF
```