
Async with Example

— Rusty weirdness —



Rust Async Programming

- **async** in Rust may be a bit different from what you're used to in other languages. Having done asynchronous coding mostly in JavaScript and C#, it certainly was to me. Here's a few key things to understand:



Rust Async Programming

- An **async** function does not (necessarily) start executing immediately
- To start an **asynchronous** function, you must either `.await` it or launch a task using an executor (we'll get to that in a moment).
Until this happens, all you have is a **Future** that has not started.
Let's look at an example to make it clearer:



Rust Async Programming

```
use async_std::task;

async fn negate_async(n: i32) -> i32 {
    println!("Negating {}", n);
    task::sleep(std::time::Duration::from_secs(5)).await;
    println!("Finished sleeping for {}!", n);
    n * -1
}
```

Rust Async Programming

```
async fn f() -> i32 {  
    let neg = negate_async(1);  
    let neg_task = task::spawn(negate_async(2));  
    task::sleep(std::time::Duration::from_secs(1)).await;  
    neg.await + neg_task.await  
}
```

[dependencies]

async-std = "1"



Rust Async Programming

- The first line imports **async_std::task**. There's more on this below, but we need an external library to run futures as the standard library does not come with an **executor**.
- The async function **negate_async** takes as input a signed integer, sleeps for 5 seconds, and returns the negated version of that integer.



Rust Async Programming

- The async function `f` is more interesting:
- The first line (`let neg ...`) creates a Future of the `negate_async` function and assigns it to the `neg` variable. Importantly, it does not start executing yet.
- The next line of code (`let neg_task ...`) uses the `task::spawn` function to start executing the Future returned by `negate_async`. Like with `neg`, the Future returned by `negate_async` is assigned to the `neg_task` variable.



Rust Async Programming

- Next: we sleep for a second. This is so that it will be obvious from the output when a task starts running.
- Finally, we await both futures, add them together, and return them. By awaiting `neg`, we start executing the Future and run it to completion. Since `neg_task` has already been started, we just wait for it to finish.



Resources

Book : <https://rust-lang.github.io/async-book/>

Link to the article : <https://thomashartmann.dev/blog/async-rust/>

Source code repository : <https://github.com/PIAIC-IOT/Quarter3-Online.git>

Summary