COMPILER CONSTRUCTION PROJECT

ROMAN URDU COMPILER

README AND USER MANUAL

Project Phase	Phase 1: Interpreter Development
	Phase 2: LLVM AOT Compiler Development
Target Platform	Linux (Ubuntu 24.04 tested)

Submitted By

Name	Roll Number
Muhammad Faizan	23L-0567
Maahi Ibn Ahmar	23L-0990
Mahad Bin Atif	22L-4951

Table of Contents

1. Supported Language Features
2. Linux Dependencies
3. Compile the Project
4. Phase 1: Run the Interpreter
5. Phase 2: Generate LLVM IR and Build an Executable
6. Language Example
7. Run the Automated Tests
8. Optional Docker Verification
9. Project Files
10. Troubleshooting
11. Clean Generated Files

About this document

This manual explains how to install the required software, build both project phases, run Roman Urdu programs, generate LLVM IR, create a native executable, and execute the supplied tests on Linux.

Commands were checked using Ubuntu 24.04, Flex 2.6.4, Bison 3.8.2, and Clang 18.

1. Supported Language Features

- Integer variables using `adad`
- Assignment and arithmetic: `+`, `-`, `*`, `/`, `%`
- Comparisons: `<`, `<=`, `>`, `>=`, `==`, `!=`
- Boolean operators: `&&`, `||`, `!`
- Conditional blocks using `agar` and `warna`
- While loops using `jabtak`
- Integer and string output using `dikhao`
- Program return values using `wapis`
- Statement termination using `kardo`
- Line comments beginning with `#` or `//`

2. Linux Dependencies

The project is designed and tested for Ubuntu 24.04. Install the required packages with:

```
sudo apt update
sudo apt install -y build-essential flex bison clang make
```

Required tools:

- GCC or another C11 compiler for building the interpreter and compiler
- Flex 2.6 or newer for lexical analysis
- Bison 3.8 or newer for parsing
- Clang/LLVM 18 or newer for compiling generated LLVM IR
- GNU Make for the supplied build targets

No third-party C libraries are required.

3. Compile the Project

From the project root, run:

```
make clean
make
```

This creates:

- `bin/roman-urdu-interpreter` - Phase 1 interpreter
- `bin/roman-urdu-compiler` - Phase 2 LLVM IR generator

Individual phases can be built separately:

```
make phase1
make phase2
```

4. Phase 1: Run the Interpreter

Pass one Roman Urdu source file to the interpreter:

```
./bin/roman-urdu-interpreter examples/demo.ru
```

Expected output:

```
y bara hai
1 se 5 tak jama:
15
```

The interpreter returns the value supplied to `wapis`. A syntax error includes its source line number. Runtime errors, such as use of an undefined variable or division by zero, are written to standard error.

5. Phase 2: Generate LLVM IR and Build an Executable

Generate LLVM IR:

```
./bin/roman-urdu-compiler examples/demo.ru build/demo.ll
```

Compile the IR into a native executable:

```
clang build/demo.ll -o build/demo
```

Run the executable:

```
./build/demo
```

The result matches the interpreter output. If the output filename is omitted, the compiler writes LLVM IR to standard output:

```
./bin/roman-urdu-compiler examples/demo.ru > build/demo.ll
```

The complete three-command workflow is also available through:

```
make demo
```

6. Language Example

Roman Urdu source files conventionally use the `.ru` extension.

```
adad n = 5 kardo
adad factorial = 1 kardo

jabtak (n > 1) {
    factorial = factorial * n kardo
    n = n - 1 kardo
}

agar (factorial == 120) {
    dikhao("jawab durust hai") kardo
} warna {
    dikhao("jawab ghalat hai") kardo
}

dikhao(factorial) kardo
wapis 0 kardo
```

Keyword reference:

Roman Urdu	Meaning
`adad`	Declare an integer variable
`agar`	If
`warna`	Else
`jabtak`	While
`dikhao`	Print a string or integer expression
`wapis`	Return from the program

Roman Urdu	Meaning
`kardo`	End a statement

Variables must be declared before they are used at runtime. This first version uses a single program-wide integer namespace; nested block scopes and user-defined functions are outside the project scope. Integer expressions use signed 32-bit LLVM values in the AOT compiler.

7. Run the Automated Tests

Build both phases and run end-to-end tests:

```
make test
```

The test script checks the demo and factorial programs in both modes. For Phase 2 it generates LLVM IR, compiles the IR with Clang, runs the native binaries, and compares their output with the expected results.

Expected final line:

```
All Phase 1 and Phase 2 tests passed.
```

8. Optional Docker Verification

If Docker is available, reproduce the tested Ubuntu environment with:

```
docker build -t roman-urdu-compiler .
docker run --rm roman-urdu-compiler
```

The image builds the project and runs all tests during image creation. Its default command runs the demo.

9. Project Files

- `phase1/lexer.l` - Flex scanner for the interpreter.
- `phase1/parser.y` - Bison grammar and Phase 1 command-line entry point.
- `phase2/lexer.l` - Flex scanner for the AOT compiler.
- `phase2/parser.y` - Bison grammar and Phase 2 command-line entry point.
- `include/ast.h` - AST node definitions and interpreter interface.
- `include/codegen.h` - LLVM IR code generator interface.
- `src/ast.c` - AST construction, cleanup, symbol table, and interpreter execution.
- `src/codegen.c` - LLVM IR emission for expressions, variables, output, branches, and loops.
- `examples/demo.ru` - Full demonstration of variables, branches, loops, strings, and arithmetic.
- `examples/factorial.ru` - Small factorial example.
- `tests/run_tests.sh` - End-to-end regression tests for both phases.
- `Makefile` - Linux build, test, demo, and cleanup targets.
- `Dockerfile` - Reproducible Ubuntu 24.04 build and test environment.
- `README.md` - Markdown version of the project guide.
- `README.pdf` - Submission-ready PDF version of the project guide.
- `Roman_Urdu_Compiler.pdf` - Original project idea document.
- `LICENSE` - MIT license.

Generated files are placed under `build/` and `bin/`; both directories can be removed safely with `make clean`.

10. Troubleshooting

- `flex: command not found` or `bison: command not found`: install the packages listed under Linux Dependencies.
- `clang: command not found`: install `clang` with APT.
- `line N: syntax error`: check for a missing `kardo`, parenthesis, or brace near the reported line.
- `runtime error: undefined variable`: declare the variable with `adad` before assigning or reading it.
- `Permission denied` when running a script: invoke it through `sh tests/run_tests.sh`; executable permission is not required in that form.

11. Clean Generated Files

```
make clean
```

This removes only generated `bin/` and `build/` directories. Source files and documentation remain unchanged.