



# Bacalhau FAQs

## Can I use multiple data sources in the same job?

You can use the `--input` or `-i` flag multiple times with multiple different CIDs, URLs or S3 objects, and give each of them a path to be mounted at.

For example, doing

```
bacalhau run cat/main.wasm -i ipfs://CID1:/input1 -i ipfs://CID2:/input2
```

will result in both the `input1` and `input2` folders being available to your running WASM with the CID contents. You can use `-i` as many times as you need.

## How can I submit Job requests through CLI to communicate with my Node directly?

To ensure the CLI can communicate with our node directly ( `bacalhau --api-host <MY_NODE_PUBLIC_IP> version` ), you

need to make sure the **1234** port is open.

## Why does my API server listening on `/ip4/127.0.0.1/tcp/5001` when I invoke IPFS Daemon when fetching an IPFS Multiaddress?

Bacalhau communicates with IPFS via it's API port and not the swarm port which is why it's **5001** and not **4001**.

The key thing is whether the IPFS node is running on the same host as the Bacalhau daemon. If it is, then **127.0.0.1** is enough to route traffic between the two (because they are both on the same node). If IPFS is running on a different node than Bacalhau, then we need to replace **127.0.0.1** with the IP that the IPFS server is running on.

## What to do when I get error connection refused when running Bacalhau API?

### Problem

When running

```
bacalhau --api-host <MY_NODE_PUBLIC_IP> version
```

 and you get this error message:

Error running version: publicapi: after posting request

## What to do

First, you'll need to check that the bacalhau server is up and running on the same host then it should be connecting using `127.0.0.1`. This can be checked by running `telnet 127.0.0.1 1234`. If telnet is not connecting to **127.0.0.1 1234** on the machine that bacalhau is running then one of 3 things:

1. Bacalhau is running on a different machine
2. it's running on a different port
3. it's not running

## Can I run Bacalhau in a containerized setup (nested containers)?

We don't support this as it will result in the classic Dind(Docker In Docker) problem.

## Can I run non Docker jobs?

Yes! You can run programs using WebAssembly instead. See the [onboarding WebAssembly](#) for information on how

to do that.

## **How do I run a script that requires installing packages from a package repository like pypi or apt?**

Networking is supported by Bacalhau which enables one to run a script that requires packages from external repository. This is only for Docker workloads

## **How do I see a job's progress while it's running?**

If your job writes to stdout, or stderr, while it is running, you can view the output with the [logs](#) command.

## **How can I download and query SQLite when it complains about being in read-only directory?**


When downloading content to run your code against, it is written to a read-only directory. Unfortunately, by default,

SQLite requires the directory to be writable so that it can create utility files during its use.

If you run your command with the `immutable` setting set to 1, then it will work. From the `sqlite3` command you can use `.open 'file:/inputs/database.db?immutable=1'` where you should replace "database.db" with your downloaded database filename.

## Can I run `bacalhau serve` on my home machine? What are the requirements?

You can run `bacalhau serve` on any machine that fits the prerequisites listed [here](#).

-  The walkthrough in the docs has been tested only on Ubuntu 22, bacalhau is being developed on Linux/macOS environments and therefore should work fine there as well. However, Windows hosts are supported with [limitations](#).

## Can I stop a running job?

Yes. Given a valid `job ID`, you can use the [cancel command](#) to cancel the job, and stop it from running.

[Previous](#)  
Setting up Dev Environment

Next  
[Release Notes](#)

