

LAPORAN PRAKTIKUM BASIS DATA II
“QUERY LANJUTAN”



Dosen Pengampu : Muhammad Aiurohman,S.Kom

Disusun Oleh : Muhammad Fakhri Azzaam

NIM : 2502021

Kelas : TI 2A

TEKNIK INFORMATIKA 2A D-III
POLITEKNIK PURBAYA
TAHUN 2025/2026

Hasil Praktikum 6

1. Penggunaan Subquery

Menampilkan sayur dengan harga di atas rata-rata.

```
MariaDB [penjualan_sayurr]> SELECT nama_sayur, harga
-> FROM sayur
-> WHERE harga > (
->     SELECT AVG(harga)
->     FROM sayur
-> );
```

nama_sayur	harga
Wortel	6000

1 row in set (0.002 sec)

2. Penggunaan Subquery dengan Banyak Kolom

Menampilkan data transaksi dan pembeli.

```
MariaDB [penjualan_sayurr]> SELECT *
-> FROM (
->     SELECT id_pembeli, nama, alamat
->     FROM pembeli
-> ) AS data_pembeli;
```

id_pembeli	nama	alamat
1	Budi	Medan
2	Siti	Binjai

2 rows in set (0.001 sec)

3. Pairwise Comparison Subquery

Membandingkan dua kolom sekaligus.

```
MariaDB [penjualan_sayurr]> SELECT *
-> FROM detail_transaksi
-> WHERE (id_transaksi, id_sayur) IN (
->     SELECT id_transaksi, id_sayur
->     FROM detail_transaksi
-> );
```

id_detail	id_transaksi	id_sayur	jumlah	subtotal
1	1	1	2	10000
2	1	2	1	5000
3	2	3	3	18000
4	3	2	3	12000

4 rows in set (0.001 sec)

4. Nonpairwise Comparison Subquery

Membandingkan satu kolom dengan hasil subquery.

```
MariaDB [penjualan_sayurr]> SELECT *  
-> FROM sayur  
-> WHERE harga = (  
->     SELECT MAX(harga)  
->     FROM sayur  
-> );  
+-----+-----+-----+-----+  
| id_sayur | nama_sayur | harga | stok |  
+-----+-----+-----+-----+  
|          3 | Wortel      | 6000  | 30   |  
+-----+-----+-----+-----+  
1 row in set (0.001 sec)
```

Menampilkan sayur dengan harga paling mahal.

5. Penggunaan Query dalam Klausa FROM

Subquery di dalam FROM.

```
MariaDB [penjualan_sayurr]> SELECT rata_rata.harga_rata  
-> FROM (  
->     SELECT AVG(harga) AS harga_rata  
->     FROM sayur  
-> ) AS rata_rata;  
+-----+  
| harga_rata |  
+-----+  
| 5000.0000 |  
+-----+  
1 row in set (0.001 sec)
```

6. Ekspresi Scalar Subquery

Subquery menghasilkan satu nilai.

```
MariaDB [penjualan_sayurr]> SELECT nama_sayur,  
->     harga,  
->     (SELECT AVG(harga) FROM sayur) AS rata_rata  
-> FROM sayur;  
+-----+-----+-----+  
| nama_sayur | harga | rata_rata |  
+-----+-----+-----+  
| Bayam      | 5000  | 5000.0000 |  
| Kangkung   | 4000  | 5000.0000 |  
| Wortel     | 6000  | 5000.0000 |  
+-----+-----+-----+  
3 rows in set (0.001 sec)
```

7. Penggunaan Klausa WITH (CTE)

Membuat query sementara.

```
MariaDB [penjualan_sayurr]> WITH sayur_mahal AS (  
->     SELECT nama_sayur, harga  
->     FROM sayur  
->     WHERE harga > 5000  
-> )  
-> SELECT *  
-> FROM sayur_mahal;  
+-----+-----+  
| nama_sayur | harga |  
+-----+-----+  
| Wortel     | 6000  |  
+-----+-----+  
1 row in set (0.001 sec)
```