

Database Schema Reference

Every schema, table, column, constraint, index, trigger, function and role of the gambut database.

Project	Peat Rewetting Planning for 337 Peat Hydrological Units (KHG)
Document	Database Schema
Version	1.0, 1 October 2026
Author	Fairuz Akmal Pradana
Repository	github.com/fakmalpradana/pembasahan-gambut-337khg

Contents

Introduction

Conventions

Schemas

Schema ref

- ref.desa
- ref.fungsi_kawasan
- ref.jenis_kanal
- ref.kabupaten
- ref.kecamatan
- ref.kerusakan_eg
- ref.khg
- ref.kondisi_sumur
- ref.penutupan_lahan
- ref.perusahaan
- ref.provinsi
- ref.status_alur
- ref.status_kanal
- ref.status_pompa
- ref.status_sekat

Schema peta

- peta.areal_terbakar
- peta.hotspot
- peta.kanal
- peta.ketebalan_gambut
- peta.konsesi
- peta.logger_tmat
- peta.pintu_air
- peta.pompa
- peta.posko_karhutla
- peta.sekat
- peta.sekat_bangunan
- peta.sekat_konteks
- peta.sumur_bor
- peta.sumur_debit
- peta.sungai
- peta.tmat_bacaan
- peta.v_khg_legenda
- peta.v_sekat

peta.v_sumur_bor

peta.v_tmat_alert

Schema analisis

analisis.kontur

analisis.kontur_lidar

analisis.unit_nasional

analisis.unit_target_2026

Schema alur

alur.ekspor_poster

alur.khg_versi

alur.komentar

alur.pengguna

alur.perubahan

alur.template_poster

alur.v_dashboard

alur.v_khg_daftar

alur.v_khg_status

Schema api

api.khg_statistik

api.areal_terbakar

api.desa

api.hotspot

api.kanal

api.ketebalan_gambut

api.khg

api.konsesi

api.kontur

api.kontur_lidar

api.sekat

api.sumur_bor

api.unit_nasional

api.unit_target_2026

Functions

Roles and privileges

Introduction

This document is the reference for every table, view, column, constraint, index, trigger and function in the `gambut` database. It is generated from the live database catalogue (PostgreSQL 17.5, PostGIS 3.5.2, database size 6022 MB).

Conventions

Topic	Convention
Coordinate system	Every geometry is stored in EPSG:4326 (longitude, latitude). Distances in metres are computed on the geography type.
Primary keys	<code>bigint</code> or <code>int</code> identity column <code>id</code> , one geometry column per table, GiST index on every geometry. This keeps QGIS editing smooth.
Names	Indonesian domain names in snake case, matching the language of the analysts (see the DDD glossary).
Code lists	Small tables in <code>ref</code> referenced by foreign keys, not ENUM types.
Audit columns	Every <code>peta</code> layer has <code>khg_id</code> , <code>created_at</code> , <code>created_by</code> , <code>updated_at</code> , <code>updated_by</code> , <code>updated_via</code> (<code>qgis</code> , <code>web</code> , <code>api</code> , <code>sync</code> or <code>import</code>) and <code>rev</code> (optimistic lock counter). They are filled by triggers.
Codes	Human codes (<code>P-n</code> , <code>SK-n</code> , <code>K-n</code>) are unique per KHG and assigned by a trigger when empty.
Identity of the writer	<code>app.pengguna</code> and <code>app.via</code> session settings, falling back to the login role and its default channel.

Schemas

Schema	Purpose	Tables	Views	Rows	Size
ref	Reference data and code lists	15	0	9,131	71 MB
peta	Operational map layers, most of them editable	16	4	2,146,860	1,269 MB
analisis	Large read-only analysis layers	4	0	1,964,745	4,661 MB
alur	Plan versions, audit and poster exports	6	3	866	0 MB
api	Public read model for the OGC API	0	14	0	0 MB

Schema ref

Reference data and code lists.

ref.desa

table, 5,860 rows, 18.1 MB. Village. The 2,004 target villages for 2026 carry a boundary polygon.

Column	Type	Null	Default or note
id	integer identity	no	primary key
kecamatan_id	integer	no	references ref.kecamatan
nama	text	no	-
kode_bps	text	yes	-
target_pemulihan_2026	boolean	no	default false
geom	geometry(MultiPolygon,4326)	yes	-

Constraints:

- UNIQUE (kecamatan_id, nama)
- UNIQUE (kode_bps)

Indexes:

- CREATE UNIQUE INDEX desa_kecamatan_id_nama_key USING btree (kecamatan_id, nama)
- CREATE UNIQUE INDEX desa_kode_bps_key USING btree (kode_bps)
- CREATE INDEX desa_geom_idx USING gist (geom)

ref.fungsi_kawasan

table, 14 rows, 0.0 MB. Code list: forest area function (for example HP, HL, APL).

Column	Type	Null	Default or note
kode	text	no	primary key
label	text	no	-

ref.jenis_kanal

table, 3 rows, 0.0 MB. Code list: canal class (1 primary, 2 secondary, 3 tertiary).

Column	Type	Null	Default or note
kode	smallint	no	primary key
label	text	no	-

Constraints:

- `UNIQUE (label)`

Indexes:

- `CREATE UNIQUE INDEX jenis_kanal_label_key USING btree (label)`

ref.kabupaten

table, 142 rows, 0.0 MB. Regency or city within a province.

Column	Type	Null	Default or note
id	integer identity	no	primary key
provinsi_id	smallint	no	references ref.provinsi
nama	text	no	-

Constraints:

- `UNIQUE (provinsi_id, nama)`

Indexes:

- `CREATE UNIQUE INDEX kabupaten_provinsi_id_nama_key USING btree (provinsi_id, nama)`

ref.kecamatan

table, 892 rows, 0.2 MB. District within a regency.

Column	Type	Null	Default or note
id	integer identity	no	primary key
kabupaten_id	integer	no	references ref.kabupaten
nama	text	no	-

Constraints:

- `UNIQUE (kabupaten_id, nama)`

Indexes:

- `CREATE UNIQUE INDEX kecamatan_kabupaten_id_nama_key USING btree (kabupaten_id, nama)`

ref.kerusakan_eg

table, 5 rows, 0.0 MB. Code list: peat ecosystem damage level 2024 with severity order.

Column	Type	Null	Default or note
nama	text	no	primary key
urutan	smallint	yes	-

ref.khg

table, 866 rows, 52.5 MB. Peat Hydrological Unit (KHG). Boundary dissolved from national analysis units.

Column	Type	Null	Default or note
id	integer identity	no	primary key
kode	text	yes	-
nama	text	no	-
provinsi_utama_id	smallint	no	references ref.provinsi
target_2026	boolean	no	default false
luas_ha	numeric(12,2)	yes	-
geom	geometry(MultiPolygon,4326)	yes	-

Constraints:

- UNIQUE (kode)
- UNIQUE (nama)

Indexes:

- CREATE UNIQUE INDEX khg_kode_key USING btree (kode)
- CREATE UNIQUE INDEX khg_nama_key USING btree (nama)
- CREATE INDEX khg_geom_idx USING gist (geom)

ref.kondisi_sumur

table, 3 rows, 0.0 MB. Code list: deep well condition (working, damaged, unverified).

Column	Type	Null	Default or note
kode	text	no	primary key
label	text	no	-
warna	text	yes	-

ref.penutupan_lahan

table, 26 rows, 0.0 MB. Code list: land cover class 2022.

Column	Type	Null	Default or note
nama	text	no	primary key

ref.perusahaan

table, 1,267 rows, 0.2 MB. Company holding a plantation, forestry or mining permit.

Column	Type	Null	Default or note
id	integer identity	no	primary key
nama	text	no	-
izin_usaha	text	yes	-

Constraints:

- `UNIQUE (nama)`

Indexes:

- `CREATE UNIQUE INDEX perusahaan_nama_key USING btree (nama)`

ref.provinsi

table, 38 rows, 0.0 MB. Province (38 rows, official Ministry of Home Affairs codes as primary key).

Column	Type	Null	Default or note
id	smallint	no	primary key
nama	text	no	-
singkatan	text	no	-
pulau	text	no	-

Constraints:

- `UNIQUE (nama)`

Indexes:

- `CREATE UNIQUE INDEX provinsi_nama_key USING btree (nama)`

ref.status_alur

table, 5 rows, 0.0 MB. Code list: plan version status with display order and colour.

Column	Type	Null	Default or note
kode	text	no	primary key
label	text	no	-
urutan	smallint	yes	-
warna	text	yes	-

ref.status_kanal

table, 3 rows, 0.0 MB. Code list: canal survey status (active, inactive, blocked).

Column	Type	Null	Default or note
kode	text	no	primary key
label	text	no	-
warna	text	yes	-

ref.status_pompa

table, 3 rows, 0.0 MB. Code list: pump status (planned, installed, damaged).

Column	Type	Null	Default or note
kode	text	no	primary key
label	text	no	-
warna	text	yes	-

ref.status_sekat

table, 4 rows, 0.0 MB. Code list: canal block status (planned, existing, damaged, removed).

Column	Type	Null	Default or note
kode	text	no	primary key
label	text	no	-
warna	text	yes	-

Schema peta

Operational map layers, most of them editable.

peta.areal_terbakar

table, 584,723 rows, 564.0 MB. Burned area polygon with the list of burn years 2015 to 2026.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
tahun_terbakar	smallint[]	no	-
frekuensi	smallint generated	yes	cardinality(tahun_terbakar)
geom	geometry(MultiPolygon,4326)	no	-
khg_id	integer	yes	references ref.khg
created_at	timestamp with time zone	no	default now()
created_by	text	yes	-
updated_at	timestamp with time zone	no	default now()
updated_by	text	yes	-
updated_via	text	yes	-
rev	integer	no	default 1

Constraints:

- `CHECK ((updated_via = ANY (ARRAY['qgis'::text, 'web'::text, 'api'::text, 'sync'::text, 'import'::text])))`

Indexes:

- `CREATE INDEX areal_terbakar_geom_idx USING gist (geom)`
- `CREATE INDEX areal_terbakar_khg_id_idx USING btree (khg_id)`
- `CREATE INDEX areal_terbakar_tahun_terbakar_idx USING gin (tahun_terbakar)`

Triggers:

- `a_meta: BEFORE INSERT OR UPDATE executes alur.isi_meta()`

peta.hotspot

table, 167,718 rows, 49.6 MB. Satellite fire hotspot (MODIS or VIIRS), January to September 2026.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
waktu	timestamp with time zone	no	-

Column	Type	Null	Default or note
satelit	text	yes	-
instrumen	text	yes	-
kepercayaan	text	yes	-
kepercayaan_nilai	smallint	yes	-
frp_mw	numeric(8,2)	yes	-
brightness_k	numeric(6,2)	yes	-
siang_malam	character(1)	yes	-
provinsi	text	yes	-
kabupaten	text	yes	-
kecamatan	text	yes	-
desa	text	yes	-
format_sumber	text	no	-
berkas_sumber	text	yes	-
geom	geometry(Point,4326)	no	-
khg_id	integer	yes	references ref.khg
created_at	timestamp with time zone	no	default now()
created_by	text	yes	-
updated_at	timestamp with time zone	no	default now()
updated_by	text	yes	-
updated_via	text	yes	-
rev	integer	no	default 1

Constraints:

- `CHECK ((kepercayaan = ANY (ARRAY['tinggi'::text, 'sedang'::text, 'rendah'::text])))`
- `CHECK ((updated_via = ANY (ARRAY['qgis'::text, 'web'::text, 'api'::text, 'sync'::text, 'import'::text])))`

Indexes:

- `CREATE INDEX hotspot_geom_idx USING gist (geom)`
- `CREATE INDEX hotspot_khg_id_idx USING btree (khg_id)`
- `CREATE INDEX hotspot_waktu_idx USING btree (waktu)`

Triggers:

- `a_meta: BEFORE INSERT OR UPDATE executes alur.isi_meta()`

peta.kanal

table, 657,621 rows, 266.9 MB. Canal segment from the 2025 OpenStreetMap seamless canal layer. Editable.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
kode	text	yes	-
jenis_kanal	smallint	yes	references ref.jenis_kanal
status	text	yes	references ref.status_kanal
keterangan	text	yes	-
sumber	text	yes	-
id_asal	bigint	yes	-
geom	geometry(MultiLineString,4326)	no	-
panjang_m	numeric generated	yes	round((st_length((geom)::geography))::numeric, 1)
khg_id	integer	yes	references ref.khg
created_at	timestamp with time zone	no	default now()
created_by	text	yes	-
updated_at	timestamp with time zone	no	default now()
updated_by	text	yes	-
updated_via	text	yes	-
rev	integer	no	default 1

Constraints:

- `CHECK ((updated_via = ANY (ARRAY['qgis'::text, 'web'::text, 'api'::text, 'sync'::text, 'import'::text])))`

Indexes:

- `CREATE INDEX kanal_geom_idx USING gist (geom)`
- `CREATE INDEX kanal_khg_id_idx USING btree (khg_id)`
- `CREATE UNIQUE INDEX kanal_khg_id_kode_idx USING btree (khg_id, kode)`
- `CREATE INDEX kanal_sumber_id_asal_idx USING btree (sumber, id_asal)`

Triggers:

- `a_meta: BEFORE INSERT OR UPDATE executes alur.isi_meta()`
- `b_kode: BEFORE INSERT executes alur.isi_kode('K')`
- `z_audit: AFTER INSERT OR DELETE OR UPDATE executes alur.catat_perubahan()`

peta.ketebalan_gambut

table, 2,938 rows, 128.2 MB. Peat thickness class polygon per KHG.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
kelas	text	yes	-
tebal_min_m	numeric(4,1)	yes	-
tebal_max_m	numeric(4,1)	yes	-
geom	geometry(MultiPolygon,4326)	no	-
khg_id	integer	yes	references ref.khg
created_at	timestamp with time zone	no	default now()
created_by	text	yes	-
updated_at	timestamp with time zone	no	default now()
updated_by	text	yes	-
updated_via	text	yes	-
rev	integer	no	default 1

Constraints:

- `CHECK ((updated_via = ANY (ARRAY['qgis'::text, 'web'::text, 'api'::text, 'sync'::text, 'import'::text])))`

Indexes:

- `CREATE INDEX ketebalan_gambut_geom_idx USING gist (geom)`
- `CREATE INDEX ketebalan_gambut_khg_id_idx USING btree (khg_id)`

Triggers:

- `a_meta: BEFORE INSERT OR UPDATE executes alur.isi_meta()`

peta.konsesi

table, 1,070 rows, 16.7 MB. Concession polygon per company, dissolved from analysis units.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
perusahaan_id	integer	yes	references ref.perusahaan
jenis	text	yes	-
sumber	text	yes	-
geom	geometry(MultiPolygon,4326)	no	-
khg_id	integer	yes	references ref.khg
created_at	timestamp with time zone	no	default now()
created_by	text	yes	-

Column	Type	Null	Default or note
updated_at	timestamp with time zone	no	default now()
updated_by	text	yes	-
updated_via	text	yes	-
rev	integer	no	default 1

Constraints:

- `CHECK ((updated_via = ANY (ARRAY['qgis'::text, 'web'::text, 'api'::text, 'sync'::text, 'import'::text])))`

Indexes:

- `CREATE INDEX konsesi_geom_idx USING gist (geom)`
- `CREATE INDEX konsesi_khg_id_idx USING btree (khg_id)`

Triggers:

- `a_meta`: BEFORE INSERT OR UPDATE executes `alur.isi_meta()`
- `z_audit`: AFTER INSERT OR DELETE OR UPDATE executes `alur.catat_perubahan()`

peta.logger_tmat

table, 0 rows, 0.0 MB. Groundwater level logger location. Editable.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
kode	text	yes	-
ext_id	text	yes	-
geom	geometry(Point,4326)	no	-
khg_id	integer	yes	references ref.khg
created_at	timestamp with time zone	no	default now()
created_by	text	yes	-
updated_at	timestamp with time zone	no	default now()
updated_by	text	yes	-
updated_via	text	yes	-
rev	integer	no	default 1

Constraints:

- `CHECK ((updated_via = ANY (ARRAY['qgis'::text, 'web'::text, 'api'::text, 'sync'::text, 'import'::text])))`
- `UNIQUE (ext_id)`
- `UNIQUE (kode)`

Indexes:

- `CREATE UNIQUE INDEX logger_tmat_ext_id_key USING btree (ext_id)`
- `CREATE UNIQUE INDEX logger_tmat_kode_key USING btree (kode)`
- `CREATE INDEX logger_tmat_geom_idx USING gist (geom)`
- `CREATE INDEX logger_tmat_khg_id_idx USING btree (khg_id)`

Triggers:

- `a_meta`: BEFORE INSERT OR UPDATE executes `alur.isi_meta()`
- `z_audit`: AFTER INSERT OR DELETE OR UPDATE executes `alur.catat_perubahan()`

peta.pintu_air

table, 48 rows, 0.1 MB. Water gate. Editable.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
kode	text	yes	-
keterangan	text	yes	-
tahun_bangun	smallint	yes	-
bahan	text	yes	-
pelaksana	text	yes	-
perusahaan_id	integer	yes	references ref.perusahaan
sumber	text	yes	-
geom	geometry(Point,4326)	no	-
khg_id	integer	yes	references ref.khg
created_at	timestamp with time zone	no	default now()
created_by	text	yes	-
updated_at	timestamp with time zone	no	default now()
updated_by	text	yes	-
updated_via	text	yes	-
rev	integer	no	default 1

Constraints:

- `CHECK ((updated_via = ANY (ARRAY['qgis'::text, 'web'::text, 'api'::text, 'sync'::text, 'import'::text])))`

Indexes:

- `CREATE INDEX pintu_air_geom_idx USING gist (geom)`
- `CREATE INDEX pintu_air_khg_id_idx USING btree (khg_id)`

Triggers:

- `a_meta`: BEFORE INSERT OR UPDATE executes `alur.isi_meta()`
- `z_audit`: AFTER INSERT OR DELETE OR UPDATE executes `alur.catat_perubahan()`

peta.pompa

table, 0 rows, 0.1 MB. Planned or installed pump with suitability scores. Editable.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
kode	text	yes	-
status	text	no	references <code>ref.status_pompa</code> ; default <code>'rencana'::text</code>
kapasitas_m3_menit	numeric(8,2)	yes	-
sungai_id	bigint	yes	references <code>peta.sungai</code>
kanal_id	bigint	yes	references <code>peta.kanal</code>
jarak_sungai_m	numeric(8,1)	yes	-
estimasi_layanan_ha	numeric(10,1)	yes	-
skor	numeric(3,2)	yes	-
skor_sumber_air	numeric(3,2)	yes	-
skor_kanal	numeric(3,2)	yes	-
skor_gambut	numeric(3,2)	yes	-
skor_terbakar	numeric(3,2)	yes	-
geom	geometry(Point,4326)	no	-
khg_id	integer	yes	references <code>ref.khg</code>
created_at	timestamp with time zone	no	default <code>now()</code>
created_by	text	yes	-
updated_at	timestamp with time zone	no	default <code>now()</code>
updated_by	text	yes	-
updated_via	text	yes	-
rev	integer	no	default <code>1</code>

Constraints:

- `CHECK (((skor ≥ (0)::numeric) AND (skor ≤ (1)::numeric)))`
- `CHECK (((skor_gambut ≥ (0)::numeric) AND (skor_gambut ≤ (1)::numeric)))`
- `CHECK (((skor_kanal ≥ (0)::numeric) AND (skor_kanal ≤ (1)::numeric)))`

- `CHECK (((skor_sumber_air ≥ (0)::numeric) AND (skor_sumber_air ≤ (1)::numeric)))`
- `CHECK (((skor_terbakar ≥ (0)::numeric) AND (skor_terbakar ≤ (1)::numeric)))`
- `CHECK ((updated_via = ANY (ARRAY['qgis'::text, 'web'::text, 'api'::text, 'sync'::text, 'import'::text])))`

Indexes:

- `CREATE INDEX pompa_geom_idx USING gist (geom)`
- `CREATE INDEX pompa_khg_id_idx USING btree (khg_id)`
- `CREATE UNIQUE INDEX pompa_khg_id_kode_idx USING btree (khg_id, kode)`

Triggers:

- `a_meta`: BEFORE INSERT OR UPDATE executes `alur.isi_meta()`
- `b_kode`: BEFORE INSERT executes `alur.isi_kode('P')`
- `z_audit`: AFTER INSERT OR DELETE OR UPDATE executes `alur.catat_perubahan()`

peta.posko_karhutla

table, 0 rows, 0.0 MB. Forest and land fire post. Editable.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
nama	text	yes	-
keterangan	text	yes	-
geom	geometry(Point,4326)	no	-
khg_id	integer	yes	references ref.khg
created_at	timestamp with time zone	no	default now()
created_by	text	yes	-
updated_at	timestamp with time zone	no	default now()
updated_by	text	yes	-
updated_via	text	yes	-
rev	integer	no	default 1

Constraints:

- `CHECK ((updated_via = ANY (ARRAY['qgis'::text, 'web'::text, 'api'::text, 'sync'::text, 'import'::text])))`

Indexes:

- `CREATE INDEX posko_karhutla_geom_idx USING gist (geom)`
- `CREATE INDEX posko_karhutla_khg_id_idx USING btree (khg_id)`

Triggers:

- `a_meta`: BEFORE INSERT OR UPDATE executes `alur.isi_meta()`

- `z_audit`: AFTER INSERT OR DELETE OR UPDATE executes `alur.catat_perubahan()`

peta.sekat

table, 366,371 rows, 122.1 MB. Canal block, planned or existing. Editable. Aggregate root.

Column	Type	Null	Default or note
<code>id</code>	<code>bigint identity</code>	no	primary key
<code>kode</code>	<code>text</code>	yes	-
<code>status</code>	<code>text</code>	no	references <code>ref.status_sekat</code> ; default <code>'rencana'::text</code>
<code>kanal_id</code>	<code>bigint</code>	yes	references <code>peta.kanal</code>
<code>id_kontur_asal</code>	<code>bigint</code>	yes	-
<code>jenis_kanal</code>	<code>smallint</code>	yes	references <code>ref.jenis_kanal</code>
<code>panjang_kanal_m</code>	<code>numeric</code>	yes	-
<code>elevasi_kontur_m</code>	<code>numeric(8,2)</code>	yes	-
<code>sumber</code>	<code>text</code>	no	default <code>'manual'::text</code>
<code>fid_asal</code>	<code>bigint</code>	yes	-
<code>qc_flag</code>	<code>text</code>	yes	-
<code>geom</code>	<code>geometry(Point,4326)</code>	no	-
<code>khg_id</code>	<code>integer</code>	yes	references <code>ref.khg</code>
<code>created_at</code>	<code>timestamp with time zone</code>	no	default <code>now()</code>
<code>created_by</code>	<code>text</code>	yes	-
<code>updated_at</code>	<code>timestamp with time zone</code>	no	default <code>now()</code>
<code>updated_by</code>	<code>text</code>	yes	-
<code>updated_via</code>	<code>text</code>	yes	-
<code>rev</code>	<code>integer</code>	no	default <code>1</code>

Constraints:

- `CHECK ((updated_via = ANY (ARRAY['qgis'::text, 'web'::text, 'api'::text, 'sync'::text, 'import'::text])))`
- `UNIQUE (fid_asal)`

Indexes:

- `CREATE UNIQUE INDEX sekat_fid_asal_key USING btree (fid_asal)`
- `CREATE INDEX sekat_geom_idx USING gist (geom)`

- `CREATE INDEX sekat_kanal_id_idx USING btree (kanal_id)`
- `CREATE INDEX sekat_khg_id_idx USING btree (khg_id)`
- `CREATE UNIQUE INDEX sekat_khg_id_kode_idx USING btree (khg_id, kode)`
- `CREATE INDEX sekat_status_idx USING btree (status)`

Triggers:

- `a_meta`: BEFORE INSERT OR UPDATE executes `alur.isi_meta()`
- `b_kode`: BEFORE INSERT executes `alur.isi_kode('SK')`
- `z_audit`: AFTER INSERT OR DELETE OR UPDATE executes `alur.catat_perubahan()`

peta.sekat_bangunan

table, 46,913 rows, 6.2 MB. One to one construction details of an existing canal block (budget, contractor, material, year).

Column	Type	Null	Default or note
sekat_id	bigint	no	primary key; references peta.sekat
kodefikasi	text	yes	-
kode_rencana	text	yes	-
khg_nama_asal	text	yes	-
tipe	text	yes	-
jenis_bangunan	text	yes	-
bahan	text	yes	-
tahun_bangun	smallint	yes	-
anggaran	text	yes	-
kegiatan	text	yes	-
pekerjaan	text	yes	-
pelaksana	text	yes	-
perusahaan_id	integer	yes	references ref.perusahaan
perijinan	text	yes	-
kode_pt	text	yes	-
tahun_data	smallint	yes	-
keterangan	text	yes	-
sumber_data	text	yes	-
sisfo_id	text	yes	-
detail	text	yes	-

peta.sekat_konteks

table, 319,458 rows, 115.4 MB. One to one overlay context of a planned canal block (village, permit, land cover, peat, burn history).

Column	Type	Null	Default or note
sekat_id	bigint	no	primary key; references peta.sekat
desa_id	integer	yes	references ref.desa
perusahaan_id	integer	yes	references ref.perusahaan
nama_kawasan_konservasi	text	yes	-
fungsi_kawasan	text	yes	references ref.fungsi_kawasan
penutupan_lahan_2022	text	yes	references ref.penutupan_lahan
kerusakan_eg_2024	text	yes	references ref.kerusakan_eg
fungsi_eg_250k	text	yes	-
fungsi_eg_ketebalan	text	yes	-
tebal_gambut_kelas	text	yes	-
tanah_gambut	text	yes	-
sk_feg_50k	text	yes	-
kedalaman_gambut_bbsdip	text	yes	-
kematangan_gambut	text	yes	-
landform	text	yes	-
gambut_bbsdip	boolean	yes	-
lahan_gambut	boolean	yes	-
buffer	text	yes	-
tahun_terbakar	smallint[]	yes	-
frekuensi_terbakar	text	yes	-
terdampak_kanal	boolean	yes	-
program_dmpg	text	yes	-
prioritas_intervensi	text	yes	-
luas_poligon_analisis_ha	numeric	yes	-

Indexes:

- CREATE INDEX sekat_konteks_desa_id_idx USING btree (desa_id)
- CREATE INDEX sekat_konteks_perusahaan_id_idx USING btree (perusahaan_id)

peta.sumur_bor

table, 0 rows, 0.0 MB. Deep well. Synchronised from the external Deep Well system. Editable.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
kode	text	yes	-
desa_id	integer	yes	references ref.desa
kedalaman_m	numeric(5,1)	yes	-
kondisi	text	no	references ref.kondisi_sumur ; default 'belum_verifikasi' :: text
tahun_bangun	smallint	yes	-
pelaksana	text	yes	-
penanggung_jawab	text	yes	-
catatan	text	yes	-
ext_id	text	yes	-
synced_at	timestamp with time zone	yes	-
geom	geometry(Point,4326)	no	-
khg_id	integer	yes	references ref.khg
created_at	timestamp with time zone	no	default now()
created_by	text	yes	-
updated_at	timestamp with time zone	no	default now()
updated_by	text	yes	-
updated_via	text	yes	-
rev	integer	no	default 1

Constraints:

- `CHECK ((updated_via = ANY (ARRAY['qgis'::text, 'web'::text, 'api'::text, 'sync'::text, 'import'::text])))`
- `UNIQUE (ext_id)`
- `UNIQUE (kode)`

Indexes:

- `CREATE UNIQUE INDEX sumur_bor_ext_id_key USING btree (ext_id)`
- `CREATE UNIQUE INDEX sumur_bor_kode_key USING btree (kode)`
- `CREATE INDEX sumur_bor_geom_idx USING gist (geom)`
- `CREATE INDEX sumur_bor_khg_id_idx USING btree (khg_id)`

Triggers:

- `a_meta`: BEFORE INSERT OR UPDATE executes `alur.isi_meta()`
- `z_audit`: AFTER INSERT OR DELETE OR UPDATE executes `alur.catat_perubahan()`

peta.sumur_debit

table, 0 rows, 0.0 MB. Daily discharge of a deep well.

Column	Type	Null	Default or note
sumur_id	bigint	no	primary key; references <code>peta.sumur_bor</code>
tanggal	date	no	primary key
debit_lps	numeric(6,2)	yes	-
catatan	text	yes	-

peta.sungai

table, 0 rows, 0.1 MB. River line used as a water source for pumps. Editable.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
nama	text	yes	-
geom	geometry(MultiLineString,4326)	no	-
khg_id	integer	yes	references <code>ref.khg</code>
created_at	timestamp with time zone	no	default <code>now()</code>
created_by	text	yes	-
updated_at	timestamp with time zone	no	default <code>now()</code>
updated_by	text	yes	-
updated_via	text	yes	-
rev	integer	no	default 1

Constraints:

- `CHECK ((updated_via = ANY (ARRAY['qgis'::text, 'web'::text, 'api'::text, 'sync'::text, 'import'::text])))`

Indexes:

- `CREATE INDEX sungai_geom_idx USING gist (geom)`
- `CREATE INDEX sungai_khg_id_idx USING btree (khg_id)`

Triggers:

- `a_meta`: BEFORE INSERT OR UPDATE executes `alur.isi_meta()`

- `z_audit`: AFTER INSERT OR DELETE OR UPDATE executes `alur.catat_perubahan()`

peta.tmat_bacaan

table, 0 rows, 0.0 MB. Groundwater depth reading per logger and timestamp.

Column	Type	Null	Default or note
logger_id	bigint	no	primary key; references peta.logger_tmat
waktu	timestamp with time zone	no	primary key
tmat_m	numeric(5,2)	no	-

peta.v_khg_legenda

view. View: feature count per layer and KHG (map legend numbers).

Column	Type	Null	Default or note
khg_id	integer	yes	-
layer	text	yes	-
jumlah	bigint	yes	-

peta.v_sekat

view. View: canal block with overlay context and region names.

Column	Type	Null	Default or note
id	bigint	yes	-
kode	text	yes	-
status	text	yes	-
jenis_kanal	smallint	yes	-
jenis_kanal_label	text	yes	-
elevasi_kontur_m	numeric(8,2)	yes	-
khg_id	integer	yes	-
nama_khg	text	yes	-
provinsi	text	yes	-
kabupaten	text	yes	-
kecamatan	text	yes	-
desa	text	yes	-
perusahaan	text	yes	-

Column	Type	Null	Default or note
izin_usaha	text	yes	-
fungsi_kawasan	text	yes	-
penutupan_lahan_2022	text	yes	-
kerusakan_eg_2024	text	yes	-
fungsi_eg_ketebalan	text	yes	-
tebal_gambut_kelas	text	yes	-
kedalaman_gambut_bbsd1p	text	yes	-
kematangan_gambut	text	yes	-
landform	text	yes	-
tahun_terbakar	smallint[]	yes	-
frekuensi_terbakar	text	yes	-
program_dmpg	text	yes	-
prioritas_intervensi	text	yes	-
qc_flag	text	yes	-
geom	geometry(Point,4326)	yes	-

peta.v_sumur_bor

view. View: deep well with latest discharge.

Column	Type	Null	Default or note
id	bigint	yes	-
kode	text	yes	-
desa	text	yes	-
nama_khg	text	yes	-
khg_id	integer	yes	-
kedalaman_m	numeric(5,1)	yes	-
kondisi	text	yes	-
tahun_bangun	smallint	yes	-
pelaksana	text	yes	-
penanggung_jawab	text	yes	-
tanggal_debit	date	yes	-
debit_terakhir_lps	numeric(6,2)	yes	-
synced_at	timestamp with time zone	yes	-

Column	Type	Null	Default or note
geom	geometry(Point,4326)	yes	-

peta.v_tmat_alert

view. View: loggers whose latest groundwater depth exceeds 0.4 m.

Column	Type	Null	Default or note
logger_id	bigint	yes	-
kode	text	yes	-
khg_id	integer	yes	-
waktu	timestamp with time zone	yes	-
tmat_m	numeric(5,2)	yes	-
geom	geometry(Point,4326)	yes	-

Schema analysis

Large read-only analysis layers.

analysis.kontur

table, 159,043 rows, 2,094.8 MB. Contour line from WorldDEM for 108 BRGM target KHG.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
khg_id	integer	yes	references ref.khg
elevasi_m	numeric(8,2)	yes	-
geom	geometry(MultiLineString,4326)	no	-

Indexes:

- CREATE INDEX kontur_geom_idx USING gist (geom)
- CREATE INDEX kontur_khg_id_idx USING btree (khg_id)

analysis.kontur_lidar

table, 26,968 rows, 196.0 MB. Contour line at 50 cm interval from LiDAR (Riau, Jambi, South Sumatra).

Column	Type	Null	Default or note
id	bigint identity	no	primary key
khg_id	integer	yes	references ref.khg
elevasi_m	numeric(8,2)	yes	-
geom	geometry(MultiLineString,4326)	no	-

Indexes:

- CREATE INDEX kontur_lidar_geom_idx USING gist (geom)
- CREATE INDEX kontur_lidar_khg_id_idx USING btree (khg_id)

analysis.unit_nasional

table, 989,398 rows, 1,399.5 MB. National analysis unit (overlay of KHG, village, permit, forest function, peat and burn history).

Column	Type	Null	Default or note
id	bigint identity	no	primary key
khg_id	integer	yes	-
desa_id	integer	yes	-

Column	Type	Null	Default or note
perusahaan_id	integer	yes	-
jenis_kanal	smallint	yes	-
nama_kawasan_konservasi	text	yes	-
fungsi_kawasan	text	yes	-
penutupan_lahan_2022	text	yes	-
kerusakan_eg_2024	text	yes	-
fungsi_eg_250k	text	yes	-
fungsi_eg_ketebalan	text	yes	-
tebal_gambut_kelas	text	yes	-
tanah_gambut	text	yes	-
sk_feg_50k	text	yes	-
kedalaman_gambut_bbsd1p	text	yes	-
kematangan_gambut	text	yes	-
landform	text	yes	-
gambut_bbsd1p	boolean	yes	-
lahan_gambut	boolean	yes	-
buffer	text	yes	-
tahun_terbakar	smallint[]	yes	-
frekuensi_terbakar	text	yes	-
terdampak_kanal	boolean	yes	-
program_dmpg	text	yes	-
prioritas_intervensi	text	yes	-
luas_ha	numeric	yes	-
geom	geometry(MultiPolygon,4326)	no	-

Indexes:

- CREATE INDEX unit_nasional_desa_id_idx USING btree (desa_id)
- CREATE INDEX unit_nasional_geom_idx USING gist (geom)
- CREATE INDEX unit_nasional_khg_id_idx USING btree (khg_id)
- CREATE INDEX unit_nasional_perusahaan_id_idx USING btree (perusahaan_id)

analisis.unit_target_2026

table, 789,336 rows, 970.3 MB. Analysis unit inside the 2,004 target villages for 2026.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
khg_id	integer	yes	references ref.khg
desa_id	integer	yes	references ref.desa
perusahaan_id	integer	yes	references ref.perusahaan
jenis_kanal	smallint	yes	references ref.jenis_kanal
nama_kawasan_konservasi	text	yes	-
fungsi_kawasan	text	yes	references ref.fungsi_kawasan
penutupan_lahan_2022	text	yes	references ref.penutupan_lahan
kerusakan_eg_2024	text	yes	references ref.kerusakan_eg
fungsi_eg_250k	text	yes	-
fungsi_eg_ketebalan	text	yes	-
tebal_gambut_kelas	text	yes	-
tanah_gambut	text	yes	-
sk_feg_50k	text	yes	-
kedalaman_gambut_bbsd1p	text	yes	-
kematangan_gambut	text	yes	-
landform	text	yes	-
gambut_bbsd1p	boolean	yes	-
lahan_gambut	boolean	yes	-
buffer	text	yes	-
tahun_terbakar	smallint[]	yes	-
frekuensi_terbakar	text	yes	-
terdampak_kanal	boolean	yes	-
program_dmpg	text	yes	-
prioritas_intervensi	text	yes	-
luas_ha	numeric	yes	-
geom	geometry(MultiPolygon,4326)	no	-

Indexes:

- CREATE INDEX unit_target_2026_desa_id_idx USING btree (desa_id)
- CREATE INDEX unit_target_2026_geom_idx USING gist (geom)

- `CREATE INDEX unit_target_2026_khg_id_idx USING btree (khg_id)`
- `CREATE INDEX unit_target_2026_perusahaan_id_idx USING btree (perusahaan_id)`

Schema alur

Plan versions, audit and poster exports.

alur.ekspor_poster

table, 0 rows, 0.1 MB. Poster export job with paper size, progress and output file.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
versi_id	bigint	no	references alur.khg_versi
template_id	integer	no	references alur.template_poster
batch_id	uuid	yes	-
kertas	text	no	-
orientasi	text	no	-
periode_mulai	date	yes	-
periode_selesai	date	yes	-
dpi	smallint	no	default 300
status	text	no	default 'menunggu'::text
progres	smallint	no	default 0
file_path	text	yes	-
ukuran_bytes	bigint	yes	-
pesan_error	text	yes	-
dibuat_oleh	text	no	default SESSION_USER
created_at	timestamp with time zone	no	default now()
selesai_at	timestamp with time zone	yes	-

Constraints:

- CHECK ((kertas = ANY (ARRAY['A0'::text, 'A1'::text, 'A2'::text, 'A3'::text])))
- CHECK ((orientasi = ANY (ARRAY['lanskap'::text, 'potret'::text])))
- CHECK (((progres ≥ 0) AND (progres ≤ 100)))
- CHECK ((status = ANY (ARRAY['menunggu'::text, 'merender'::text, 'selesai'::text, 'gagal'::text, 'dibatalkan'::text])))

Indexes:

- CREATE INDEX ekspor_poster_batch_id_idx USING btree (batch_id)
- CREATE INDEX ekspor_poster_status_created_at_idx USING btree (status, created_at)

Triggers:

- `ekspor_selesai`: AFTER UPDATE OF status executes `alur.tandai_dicetak()`

alur.khg_versi

table, 866 rows, 0.2 MB. Plan version of a KHG. Aggregate root of the review workflow.

Column	Type	Null	Default or note
<code>id</code>	<code>bigint identity</code>	no	primary key
<code>khg_id</code>	<code>integer</code>	no	references <code>ref.khg</code>
<code>nomor</code>	<code>integer</code>	no	-
<code>status</code>	<code>text</code>	no	references <code>ref.status_alur</code> ; default <code>'draft'::text</code>
<code>dibuat_at</code>	<code>timestamp with time zone</code>	no	default <code>now()</code>
<code>diajukan_oleh</code>	<code>text</code>	yes	-
<code>diajukan_at</code>	<code>timestamp with time zone</code>	yes	-
<code>reviewer</code>	<code>text</code>	yes	-
<code>diputuskan_at</code>	<code>timestamp with time zone</code>	yes	-
<code>catatan_reviewer</code>	<code>text</code>	yes	-
<code>validasi</code>	<code>jsonb</code>	yes	-

Constraints:

- `UNIQUE (khg_id, nomor)`

Indexes:

- `CREATE UNIQUE INDEX khg_versi_khg_id_nomor_key USING btree (khg_id, nomor)`
- `CREATE UNIQUE INDEX khg_versi_satu_terbuka USING btree (khg_id) WHERE (status = ANY (ARRAY['draft'::text, 'review'::text, 'revisi'::text]))`

alur.komentar

table, 0 rows, 0.0 MB. Review comment on a version or on a single feature, with threaded replies.

Column	Type	Null	Default or note
<code>id</code>	<code>bigint identity</code>	no	primary key
<code>versi_id</code>	<code>bigint</code>	no	references <code>alur.khg_versi</code>
<code>tabel</code>	<code>text</code>	yes	-
<code>fitur_id</code>	<code>bigint</code>	yes	-

Column	Type	Null	Default or note
parent_id	bigint	yes	references alur.komentar
pengguna	text	no	-
isi	text	no	-
selesai	boolean	no	default false
created_at	timestamp with time zone	no	default now()

Constraints:

- `CHECK (((tabel IS NULL) = (fitur_id IS NULL)))`

Indexes:

- `CREATE INDEX komentar_tabel_fitur_id_idx USING btree (tabel, fitur_id)`
- `CREATE INDEX komentar_versi_id_idx USING btree (versi_id)`

alur.pengguna

table, 0 rows, 0.0 MB. Application user profile (name, agency, role).

Column	Type	Null	Default or note
id	integer identity	no	primary key
username	text	no	-
nama	text	no	-
instansi	text	yes	-
peran	text	no	-

Constraints:

- `CHECK ((peran = ANY (ARRAY['analisis'::text, 'reviewer'::text, 'admin'::text])))`
- `UNIQUE (username)`

Indexes:

- `CREATE UNIQUE INDEX pengguna_username_key USING btree (username)`

alur.perubahan

table, 0 rows, 0.1 MB. Change record written by the audit trigger for every create, update and delete.

Column	Type	Null	Default or note
id	bigint identity	no	primary key
waktu	timestamp with time zone	no	default now()
tabel	text	no	-

Column	Type	Null	Default or note
fitur_id	bigint	no	-
khg_id	integer	yes	references ref.khg
versi_id	bigint	yes	references alur.khg_versi
aksi	character(1)	no	-
via	text	no	-
pengguna	text	no	-
data_lama	jsonb	yes	-
data_baru	jsonb	yes	-

Constraints:

- `CHECK ((aksi = ANY (ARRAY['I'::bpchar, 'U'::bpchar, 'D'::bpchar])))`

Indexes:

- `CREATE INDEX perubahan_khg_id_waktu_idx USING btree (khg_id, waktu DESC)`
- `CREATE INDEX perubahan_tabel_fitur_id_idx USING btree (tabel, fitur_id)`
- `CREATE INDEX perubahan_versi_id_idx USING btree (versi_id)`

alur.template_poster

table, 0 rows, 0.0 MB. Poster layout template (QGIS print layout file).

Column	Type	Null	Default or note
id	integer identity	no	primary key
nama	text	no	-
versi	text	yes	-
file_path	text	no	-
aktif	boolean	no	default true

alur.v_dashboard

view. View: one row of national dashboard indicators.

Column	Type	Null	Default or note
khg_disetujui	bigint	yes	-
khg_total	bigint	yes	-
khg_disetujui_minggu_ini	bigint	yes	-
pompa_rencana	bigint	yes	-
pompa_minggu_ini	bigint	yes	-

Column	Type	Null	Default or note
kanal_aktif_km	numeric	yes	-
kanal_total_km	numeric	yes	-
hotspot_30h	bigint	yes	-
hotspot_30h_sebelumnya	bigint	yes	-
logger_alert	bigint	yes	-
khg_alert	bigint	yes	-
sekat_total	bigint	yes	-
sekat_existing	bigint	yes	-
status_alur	jsonb	yes	-

alur.v_khg_daftar

view. View: KHG list with counts and priority score (internal).

Column	Type	Null	Default or note
id	integer	yes	-
kode	text	yes	-
nama	text	yes	-
provinsi	text	yes	-
provinsi_id	smallint	yes	-
luas_ha	numeric	yes	-
hotspot_30h	bigint	yes	-
pompa	bigint	yes	-
kanal_aktif_km	numeric	yes	-
kanal_total_km	numeric	yes	-
sekat	bigint	yes	-
sekat_rencana	bigint	yes	-
sekat_existing	bigint	yes	-
versi_id	bigint	yes	-
versi	integer	yes	-
status	text	yes	-
terakhir_diubah	timestamp with time zone	yes	-
diubah_via	text	yes	-
diubah_oleh	text	yes	-

Column	Type	Null	Default or note
skor_prioritas	integer	yes	-

alur.v_khg_status

view. View: latest version and status per KHG.

Column	Type	Null	Default or note
khg_id	integer	yes	-
versi_id	bigint	yes	-
nomor	integer	yes	-
status	text	yes	-
diajukan_oleh	text	yes	-
diajukan_at	timestamp with time zone	yes	-
reviewer	text	yes	-
diputuskan_at	timestamp with time zone	yes	-
dibuat_at	timestamp with time zone	yes	-

Schema api

Public read model for the OGC API.

api.khg_statistik

materialized view, 866 rows, 0.2 MB. Materialized view: expensive KHG statistics, refreshed daily.

Column	Type	Null	Default or note
khg_id	integer	yes	-
hotspot_30h	bigint	yes	-
hotspot_tahun_ini	bigint	yes	-
kanal_km	numeric	yes	-
sekat_rencana	bigint	yes	-
sekat_existing	bigint	yes	-
pintu_air	bigint	yes	-
porsi_pernah_terbakar	numeric	yes	-
porsi_gambut_dalam	numeric	yes	-

Indexes:

- `CREATE UNIQUE INDEX khg_statistik_khg_id_idx USING btree (khg_id)`

api.areal_terbakar

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	bigint	yes	-
tahun_terbakar	text	yes	-
frekuensi	smallint	yes	-
tahun_terakhir	smallint	yes	-
khg	text	yes	-
geom	geometry(MultiPolygon,4326)	yes	-

api.desa

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	integer	yes	-
kode_bps	text	yes	-
desa	text	yes	-
kecamatan	text	yes	-
kabupaten	text	yes	-
provinsi	text	yes	-
target_pemulihan_2026	boolean	yes	-
geom	geometry(MultiPolygon,4326)	yes	-

api.hotspot

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	bigint	yes	-
waktu	timestamp with time zone	yes	-
satelit	text	yes	-
instrumen	text	yes	-
kepercayaan	text	yes	-
frp_mw	numeric(8,2)	yes	-
provinsi	text	yes	-
kabupaten	text	yes	-
desa	text	yes	-
khg	text	yes	-
format_sumber	text	yes	-
geom	geometry(Point,4326)	yes	-

api.kanal

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	bigint	yes	-
kode	text	yes	-
jenis_kanal	text	yes	-
status	text	yes	-

Column	Type	Null	Default or note
panjang_m	numeric	yes	-
khg	text	yes	-
sumber	text	yes	-
geom	geometry(MultiLineString,4326)	yes	-

api.ketebalan_gambut

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	bigint	yes	-
khg	text	yes	-
kelas	text	yes	-
tebal_min_m	numeric(4,1)	yes	-
tebal_max_m	numeric(4,1)	yes	-
geom	geometry(MultiPolygon,4326)	yes	-

api.khg

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	integer	yes	-
kode	text	yes	-
nama	text	yes	-
provinsi	text	yes	-
provinsi_singkat	text	yes	-
target_2026	boolean	yes	-
luas_ha	numeric(12,2)	yes	-
versi	integer	yes	-
status	text	yes	-
diajukan_oleh	text	yes	-
diajukan_at	timestamp with time zone	yes	-
reviewer	text	yes	-
diputuskan_at	timestamp with time zone	yes	-
hotspot_30h	bigint	yes	-

Column	Type	Null	Default or note
hotspot_tahun_ini	bigint	yes	-
kanal_km	numeric	yes	-
sekat_rencana	bigint	yes	-
sekat_existing	bigint	yes	-
pintu_air	bigint	yes	-
pompa	bigint	yes	-
kanal_aktif_km	numeric	yes	-
porsi_pernah_terbakar	numeric	yes	-
porsi_gambut_dalam	numeric	yes	-
skor_prioritas	integer	yes	-
geom	geometry(MultiPolygon,4326)	yes	-

api.konsesi

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	bigint	yes	-
perusahaan	text	yes	-
jenis	text	yes	-
sumber	text	yes	-
geom	geometry(MultiPolygon,4326)	yes	-

api.kontur

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	bigint	yes	-
elevasi_m	numeric(8,2)	yes	-
khg	text	yes	-
geom	geometry(MultiLineString,4326)	yes	-

api.kontur_lidar

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	bigint	yes	-
elevasi_m	numeric(8,2)	yes	-
khg	text	yes	-
geom	geometry(MultiLineString,4326)	yes	-

api.sekat

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	bigint	yes	-
kode	text	yes	-
status	text	yes	-
sumber	text	yes	-
jenis_kanal	text	yes	-
kanal_id	bigint	yes	-
elevasi_kontur_m	numeric(8,2)	yes	-
khg	text	yes	-
desa	text	yes	-
perusahaan	text	yes	-
kodefikasi	text	yes	-
tipe	text	yes	-
jenis_bangunan	text	yes	-
bahan	text	yes	-
tahun_bangun	smallint	yes	-
pelaksana	text	yes	-
anggaran	text	yes	-
penutupan_lahan_2022	text	yes	-
kerusakan_eg_2024	text	yes	-
tebal_gambut_kelas	text	yes	-
tahun_terbakar	smallint[]	yes	-
prioritas_intervensi	text	yes	-
program_dmpg	text	yes	-
qc_flag	text	yes	-

Column	Type	Null	Default or note
updated_at	timestamp with time zone	yes	-
updated_via	text	yes	-
geom	geometry(Point,4326)	yes	-

api.sumur_bor

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	bigint	yes	-
kode	text	yes	-
desa	text	yes	-
nama_khg	text	yes	-
khg_id	integer	yes	-
kedalaman_m	numeric(5,1)	yes	-
kondisi	text	yes	-
tahun_bangun	smallint	yes	-
pelaksana	text	yes	-
penanggung_jawab	text	yes	-
tanggal_debit	date	yes	-
debit_terakhir_lps	numeric(6,2)	yes	-
synced_at	timestamp with time zone	yes	-
geom	geometry(Point,4326)	yes	-

api.unit_nasional

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	bigint	yes	-
khg	text	yes	-
desa	text	yes	-
perusahaan	text	yes	-
izin_usaha	text	yes	-
jenis_kanal	text	yes	-
nama_kawasan_konservasi	text	yes	-

Column	Type	Null	Default or note
fungsi_kawasan	text	yes	-
penutupan_lahan_2022	text	yes	-
kerusakan_eg_2024	text	yes	-
fungsi_eg_ketebalan	text	yes	-
tebal_gambut_kelas	text	yes	-
kedalaman_gambut_bbsd1p	text	yes	-
kematangan_gambut	text	yes	-
landform	text	yes	-
lahan_gambut	boolean	yes	-
buffer	text	yes	-
tahun_terbakar	text	yes	-
frekuensi_terbakar	text	yes	-
terdampak_kanal	boolean	yes	-
program_dmpg	text	yes	-
prioritas_intervensi	text	yes	-
luas_ha	numeric	yes	-
geom	geometry(MultiPolygon,4326)	yes	-

api.unit_target_2026

view. Public view published as OGC API collection. Readable names instead of foreign keys.

Column	Type	Null	Default or note
id	bigint	yes	-
khg	text	yes	-
desa	text	yes	-
perusahaan	text	yes	-
izin_usaha	text	yes	-
jenis_kanal	text	yes	-
nama_kawasan_konservasi	text	yes	-
fungsi_kawasan	text	yes	-
penutupan_lahan_2022	text	yes	-
kerusakan_eg_2024	text	yes	-
fungsi_eg_ketebalan	text	yes	-

Column	Type	Null	Default or note
tebal_gambut_kelas	text	yes	-
kedalaman_gambut_bbsd1p	text	yes	-
kematangan_gambut	text	yes	-
landform	text	yes	-
lahan_gambut	boolean	yes	-
buffer	text	yes	-
tahun_terbakar	text	yes	-
frekuensi_terbakar	text	yes	-
terdampak_kanal	boolean	yes	-
program_dmpg	text	yes	-
prioritas_intervensi	text	yes	-
luas_ha	numeric	yes	-
geom	geometry(MultiPolygon,4326)	yes	-

Functions

Function	Returns	Security	Purpose
<code>alur.ajukan_review(p_versi bigint)</code>	<code>void</code>	definer	Submits a draft or revision for review with a validation snapshot.
<code>alur.catat_perubahan()</code>	<code>trigger</code>	definer	Trigger: writes a change record linked to the open version.
<code>alur.daftar_singkat(a text[], n integer default 10)</code>	<code>text</code>	invoker	Formats a list of codes, shortened after ten items.
<code>alur.isi_kode()</code>	<code>trigger</code>	invoker	Trigger: next human code per KHG.
<code>alur.isi_meta()</code>	<code>trigger</code>	invoker	Trigger: KHG from geometry, audit columns, revision counter.
<code>alur.putuskan(p_versi bigint, p_keputusan text, p_catatan text default NULL::text)</code>	<code>void</code>	definer	Records the reviewer decision (approved or revisi).
<code>alur.tandai_dicetak()</code>	<code>trigger</code>	definer	Trigger: marks an approved version as printed after a poster export.
<code>alur.validasi_khg(p_versi bigint, p_maks_jarak_air numeric default 500)</code>	<code>TABLE(cek text, tingkat text, lolos boolean, pesan text)</code>	invoker	Runs the five automatic validation rules for a version.
<code>alur.versi_terbuka(p_khg integer)</code>	<code>bigint</code>	definer	Returns the open version of a KHG, creating version n+1 when needed.
<code>api.refresh_statistik()</code>	<code>timestamp with time zone</code>	definer	Refreshes the materialized KHG statistics.

Function	Returns	Security	Purpose
peta.saran_lokasi_pompa(p_khg integer, p_maks_jarak numeric default 500, p_min_tebal numeric default 3, p_buffer_konsesi numeric default 100, p_jarak_sampel numeric default 100, p_limit integer default 3)	TABLE(peringkat bigint, skor numeric, skor_sumber_air numeric, skor_kanal numeric, skor_gambut numeric, skor_terbakar numeric, jarak_sungai_m numeric, sungai_id bigint, kanal_id bigint, tebal_gambut_m numeric, jarak_konsesi_m numeric, geom geometry)	invoker	Ranks candidate pump locations along active canals.

Roles and privileges

Role	Login	Member of	Settings	Purpose
editor_qgis	yes	gambut_edit	app.via=qgis	Example QGIS editor account
gambut_baca	no	-	-	Read all layers and public views
gambut_edit	no	gambut_baca	-	Write planning layers, comments and exports
ogc_reader	yes	gambut_baca	default_transaction_read_only=on , statement_timeout=30s	pygeoapi read connection
ogc_writer	yes	gambut_edit	app.via=api	pygeoapi write connection
web_app	yes	gambut_edit	-	Web application backend