



# The Duckietown Book



The last version of this book and other documents are available at the URL  
<http://book.duckietown.org/>

# TABLE OF CONTENTS

|  |           |
|--|-----------|
| <b>Part 1 - Meta - The Duckietown project .....</b>                  | <b>8</b>  |
| <b>Chapter 1 - What is Duckietown?.....</b>                          | <b>9</b>  |
| Section 1.1 - Goals and objectives.....                              | 9         |
| Section 1.2 - Results obtained so far .....                          | 9         |
| Section 1.3 - Learn about the platform.....                          | 9         |
| Section 1.4 - Learn about the educational experience .....           | 9         |
| Section 1.5 - Learn about the platform.....                          | 9         |
| <b>Chapter 2 - Duckietown history and future.....</b>                | <b>10</b> |
| Section 2.1 - The beginnings of Duckietown .....                     | 10        |
| Section 2.2 - Duckietown around the world .....                      | 10        |
| Section 2.3 - Coming up.....   | 10        |
| <b>Chapter 3 - First steps.....</b>                                  | <b>11</b> |
| Section 3.1 - How to get started .....                               | 11        |
| Section 3.2 - Duckietown for instructors .....                       | 11        |
| Section 3.3 - Duckietown for self-guided learners .....              | 11        |
| Section 3.4 - Introduction for companies.....                        | 11        |
| Section 3.5 - How to keep in touch .....                             | 11        |
| Section 3.6 - How to contribute .....                                | 11        |
| <b>Chapter 4 - Frequently Asked Questions .....</b>                  | <b>12</b> |
| Section 4.1 - General questions.....                                 | 12        |
| Section 4.2 - FAQ by students / independent learners .....           | 12        |
| Section 4.3 - FAQ by instructors .....                               | 12        |
| <b>Chapter 5 - Accounts .....</b>                                    | <b>13</b> |
| Section 5.1 - Complete list of accounts.....                         | 13        |
| Section 5.2 - For other contributors.....                            | 13        |
| <br>   |           |
| <b>Part 2 - Meta - How to contribute .....</b>                       | <b>14</b> |
| <b>Chapter 6 - Contributing to the documentation .....</b>           | <b>15</b> |
| Section 6.1 - Where the documentation is .....                       | 15        |
| Section 6.2 - Editing links.....                                     | 15        |
| Section 6.3 - Comments .....   | 15        |
| Section 6.4 - Installing the documentation system .....              | 15        |
| Section 6.5 - Compiling the documentation .....                      | 16        |
| Section 6.6 - The workflow to edit documentation .....               | 17        |
| Section 6.7 - *Deploying the documentation .....                     | 17        |
| Section 6.8 - *Compiling the PDF version .....                       | 18        |
| <b>Chapter 7 - Features of the documentation writing system.....</b> | <b>20</b> |
| Section 7.1 - Embedded LaTeX .....                                   | 20        |
| Section 7.2 - Variables in command lines and command output .....    | 20        |
| Section 7.3 - Character escapes .....                                | 21        |
| Section 7.4 - Keyboard keys .....                                    | 21        |
| Section 7.5 - Figures .....  | 21        |
| Section 7.6 - Shortcut for tables .....                              | 22        |
| Section 7.7 - Troubleshooting.....                                   | 22        |
| <b>Chapter 8 - Documentation style guide .....</b>                   | <b>23</b> |
| Section 8.1 - General guidelines for technical writing.....          | 23        |
| Section 8.2 - Style guide for the Duckietown documentation.....      | 23        |
| Section 8.3 - Writing command lines .....                            | 23        |
| Section 8.4 - Frequently misspelled words .....                      | 24        |
| Section 8.5 - Other conventions .....                                | 24        |
| Section 8.6 - Troubleshooting sections.....                          | 24        |
| <b>Chapter 9 - Knowledge graph .....</b>                             | <b>25</b> |
| Section 9.1 - Formalization.....                                     | 25        |

|   |           |
|---|-----------|
| Section 9.2 - Atoms properties .....                                      | 25        |
| Section 9.3 - Markdown format for text-like atoms .....                   | 26        |
| Section 9.4 - How to describe the semantic graphs of atoms .....          | 26        |
| Section 9.5 - How to describe modules .....                               | 27        |
| <br>  |           |
| <b>Part 3 - Operation manual - Duckiebot.....</b>                         | <b>28</b> |
| <b>Chapter 10 - Duckiebot configurations.....</b>                         | <b>29</b> |
| Section 10.1 - Configuration list .....                                   | 29        |
| Section 10.2 - Configuration functionality.....                           | 29        |
| <b>Chapter 11 - Acquiring the parts for the Duckiebot CØ.....</b>         | <b>30</b> |
| Section 11.1 - Bill of materials.....                                     | 30        |
| Section 11.2 - Chassis .....  | 30        |
| Section 11.3 - Raspberry Pi 3 (RPI-3) .....                               | 31        |
| Section 11.4 - Camera .....   | 32        |
| Section 11.5 - Wifi Augmenter .....                                       | 34        |
| Section 11.6 - Joypad .....   | 34        |
| Section 11.7 - DC Stepper Motor HAT - Mini Kit.....                       | 34        |
| Section 11.8 - 16-Channel PWM/Servo HAT for Raspberry Pi - Mini Kit ..... | 35        |
| Section 11.9 - Battery .....  | 35        |
| Section 11.10 - Standoffs, Nuts and Screws .....                          | 36        |
| Section 11.11 - Ziptie .....  | 36        |
| Section 11.12 - LEDs .....  | 37        |
| Section 11.13 - Bumpers .....   | 37        |
| Section 11.14 - Passive Electric Components .....                         | 38        |
| <b>Chapter 12 - Soldering boards for CØ .....</b>                         | <b>39</b> |
| <b>Chapter 13 - Assembling the Duckiebot CØ.....</b>                      | <b>40</b> |
| <b>Chapter 14 - Reproducing the image.....</b>                            | <b>41</b> |
| Section 14.1 - Download and uncompress the Ubuntu Mate image.....         | 41        |
| Section 14.2 - Burn the image to an SD card .....                         | 41        |
| Section 14.3 - Raspberry Pi Config .....                                  | 42        |
| Section 14.4 - Install packages .....                                     | 42        |
| Section 14.5 - Install Edimax driver .....                                | 43        |
| Section 14.6 - Install ROS .....  | 43        |
| Section 14.7 - Wireless configuration (old version) .....                 | 43        |
| Section 14.8 - Wireless configuration .....                               | 44        |
| Section 14.9 - SSH server config.....                                     | 45        |
| Section 14.10 - Create swap Space .....                                   | 45        |
| Section 14.11 - Passwordless sudo .....                                   | 46        |
| Section 14.12 - Ubuntu user configuration .....                           | 46        |
| <b>Chapter 15 - Installing Ubuntu on laptops.....</b>                     | <b>48</b> |
| Section 15.1 - Install Ubuntu .....                                       | 48        |
| Section 15.2 - Install useful software .....                              | 48        |
| Section 15.3 - Install ROS .....  | 49        |
| Section 15.4 - Other suggested software.....                              | 49        |
| Section 15.5 - Passwordless sudo .....                                    | 49        |
| Section 15.6 - SSH and Git setup.....                                     | 49        |
| <b>Chapter 16 - Duckiebot Initialization .....</b>                        | <b>51</b> |
| Section 16.1 - Acquire and burn the image.....                            | 51        |
| Section 16.2 - Turn on the Duckiebot.....                                 | 51        |
| Section 16.3 - Connect the Duckiebot to a network.....                    | 52        |
| Section 16.4 - Ping the Duckiebot .....                                   | 52        |
| Section 16.5 - SSH to the Duckiebot .....                                 | 52        |
| Section 16.6 - (For D17-C1) Configure the robot-generated network .....   | 52        |
| Section 16.7 - Setting up wireless network configuration .....            | 53        |
| Section 16.8 - Update the system .....                                    | 54        |
| Section 16.9 - Give a name to the Duckiebot .....                         | 54        |
| Section 16.10 - Change the hostname .....                                 | 54        |
| Section 16.11 - Create your user .....                                    | 55        |
| Section 16.12 - Other customizations .....                                | 56        |
| Section 16.13 - Hardware check: camera .....                              | 56        |

## TABLE OF CONTENTS

|   |    |
|---|----|
| <b>Chapter 17 - Software setup and RC remote control .....</b>            | 58 |
| Section 17.1 - Clone the Duckietown repository.....                       | 58 |
| Section 17.2 - Set up ROS environment on the Duckiebot.....               | 58 |
| Section 17.3 - Add your vehicle to the machines file .....                | 59 |
| Section 17.4 - Test that the joystick is detected .....                   | 59 |
| Section 17.5 - Run the joystick demo .....                                | 60 |
| Section 17.6 - The proper shutdown procedure for the Raspberry Pi .....   | 61 |
| <b>Chapter 18 - Reading from the camera .....</b>                         | 62 |
| Section 18.1 - Check the camera hardware.....                             | 62 |
| Section 18.2 - Create two windows.....                                    | 62 |
| Section 18.3 - First window: launch the camera nodes .....                | 62 |
| Section 18.4 - Second window: view published topics.....                  | 63 |
| <b>Chapter 19 - RC control launched remotely .....</b>                    | 64 |
| Section 19.1 - Two ways to launch a program .....                         | 64 |
| Section 19.2 - Download and setup Software repository on the laptop ..... | 64 |
| Section 19.3 - Edit the machines files on your laptop .....               | 64 |
| Section 19.4 - Start the demo.....  | 64 |
| Section 19.5 - Watch the program output using rqt_console.....            | 65 |
| Section 19.6 - Troubleshooting.....                                       | 65 |
| <b>Chapter 20 - RC+camera remotely .....</b>                              | 66 |
| Section 20.1 - Assumptions .....  | 66 |
| Section 20.2 - Terminal setup .....                                       | 66 |
| Section 20.3 - First window: launch the joystick demo .....               | 66 |
| Section 20.4 - Second window: launch the camera nodes.....                | 67 |
| Section 20.5 - Third window: view data flow .....                         | 67 |
| Section 20.6 - Fourth window: visualize the image using rviz .....        | 67 |
| Section 20.7 - Proper shutdown procedure .....                            | 67 |
| <b>Chapter 21 - Interlude: Ergonomics .....</b>                           | 69 |
| Section 21.1 - set_ros_master.sh .....                                    | 69 |
| Section 21.2 - SSH aliases .....  | 69 |
| <b>Chapter 22 - Wheel calibration .....</b>                               | 70 |
| <b>Chapter 23 - Camera calibration .....</b>                              | 71 |
| <b>Chapter 24 - Taking a log .....</b>                                    | 72 |
| <br>  |    |
| <b>Part 4 - Operation manual - Duckietowns .....</b>                      | 73 |
| <b>Chapter 25 - Duckietown parts .....</b>                                | 74 |
| <b>Chapter 26 - Duckietown Assembly .....</b>                             | 75 |
| <b>Chapter 27 - The Duckietown specification .....</b>                    | 76 |
| Section 27.1 - Topology .....   | 76 |
| Section 27.2 - Signs placement .....                                      | 76 |
| <b>Chapter 28 - Traffic lights .....</b>                                  | 77 |
| <br>  |    |
| <b>Part 5 - Operation manual - Duckiebot with LEDs .....</b>              | 78 |
| <b>Chapter 29 - D17-1 (LEDs) parts .....</b>                              | 79 |
| <b>Chapter 30 - D17-1 (LEDs) assembly .....</b>                           | 80 |
| <b>Chapter 31 - D17-1 (LEDs) setup .....</b>                              | 81 |
| <br>  |    |
| <b>Part 6 - Theory chapters .....</b>                                     | 82 |
| <b>Chapter 32 - Chapter template .....</b>                                | 83 |
| <b>Chapter 33 - Linear algebra .....</b>                                  | 84 |
| <b>Chapter 34 - Probability basics .....</b>                              | 85 |
| <b>Chapter 35 - Dynamics .....</b>  | 86 |
| <b>Chapter 36 - Autonomy overview .....</b>                               | 87 |
| Section 36.1 - Perception, planning, control .....                        | 87 |
| <b>Chapter 37 - Autonomy architectures .....</b>                          | 88 |
| <b>Chapter 38 - Representations .....</b>                                 | 89 |
| <b>Chapter 39 - Software architectures and middlewares .....</b>          | 90 |
| <b>Chapter 40 - Modern signal processing .....</b>                        | 91 |
| <b>Chapter 41 - Basic Kinematics .....</b>                                | 92 |

|   |     |
|---|-----|
| Chapter 42 - Basic Dynamics .....                                   | 93  |
| Chapter 43 - Odometry Calibration.....                              | 94  |
| Chapter 44 - Computer vision basics.....                            | 95  |
| Chapter 45 - Illumination invariance.....                           | 96  |
| Chapter 46 - Line Detection .....                                   | 97  |
| Chapter 47 - Feature extraction .....                               | 98  |
| Chapter 48 - Place recognition .....                                | 99  |
| Chapter 49 - Filtering 1 .....                                      | 100 |
| Chapter 50 - Filtering 2.....                                       | 101 |
| Chapter 51 - Mission planning.....                                  | 102 |
| Chapter 52 - Planning in discrete domains .....                     | 103 |
| Chapter 53 - Motion planning.....                                   | 104 |
| Chapter 54 - RRT .....  | 105 |
| Chapter 55 - Feedback control .....                                 | 106 |
| Chapter 56 - PID Control.....                                       | 107 |
| Chapter 57 - MPC Control.....                                       | 108 |
| Chapter 58 - Object detection.....                                  | 109 |
| Chapter 59 - Object classification .....                            | 110 |
| Chapter 60 - Object tracking .....                                  | 111 |
| Chapter 61 - Reacting to obstacles.....                             | 112 |
| Chapter 62 - Semantic segmentation .....                            | 113 |
| Chapter 63 - Text recognition.....                                  | 114 |
| Chapter 64 - SLAM - Problem formulation .....                       | 115 |
| Chapter 65 - SLAM - Broad categories .....                          | 116 |
| Chapter 66 - VINS .....   | 117 |
| Chapter 67 - Advanced place recognition .....                       | 118 |
| Chapter 68 - Fleet level planning (placeholder).....                | 119 |
| Chapter 69 - Fleet level planning (placeholder).....                | 120 |
| Chapter 70 - Bibliography.....                                      | 121 |
| Chapter 71 - Exercises.....   | 122 |
| Chapter 72 - Line detection .....                                   | 123 |
| <br>Part 7 - Software manuals.....                                  | 124 |
| Chapter 73 - Setup Github access .....                              | 125 |
| Section 73.1 - Create a Github account .....                        | 125 |
| Section 73.2 - Become a member of the Duckietown organization ..... | 125 |
| Section 73.3 - Add a public key to Github.....                      | 125 |
| Chapter 74 - Linux .....  | 127 |
| Section 74.1 - Background reading .....                             | 127 |
| Section 74.2 - Ubuntu packaging.....                                | 127 |
| Section 74.3 - Measuring resource usage .....                       | 127 |
| Section 74.4 - How to burn an image to an SD card .....             | 128 |
| Chapter 75 - Networking tools .....                                 | 130 |
| Section 75.1 - Visualizing information about the network .....      | 130 |
| Section 75.2 - Wireless networks .....                              | 130 |
| Chapter 76 - Compilers.....   | 132 |
| Chapter 77 - Accessing computers using SSH.....                     | 133 |
| Section 77.1 - Background reading .....                             | 133 |
| Section 77.2 - Installation of SSH.....                             | 133 |
| Section 77.3 - Local configuration .....                            | 133 |
| Section 77.4 - How to login with SSH and a password .....           | 133 |
| Section 77.5 - Creating an SSH keypair.....                         | 134 |
| Section 77.6 - How to login without a password .....                | 135 |
| Section 77.7 - Fixing SSH Permissions .....                         | 136 |
| Section 77.8 - SCP.....   | 136 |
| Section 77.9 - RSync .....  | 136 |
| Chapter 78 - Editors .....  | 137 |
| Section 78.1 - VIM .....  | 137 |
| Section 78.2 - Atom .....   | 137 |
| Section 78.3 - Eclipse .....  | 137 |

## TABLE OF CONTENTS

|  |            |
|--|------------|
| <b>Chapter 79 - Source code control with Git.....</b>                            | <b>138</b> |
| Section 79.1 - Background reading .....  | 138        |
| Section 79.2 - Installation .....  | 138        |
| Section 79.3 - Setting up global configurations for Git .....                    | 138        |
| Section 79.4 - Git tips .....  | 138        |
| Section 79.5 - Git troubleshooting .....   | 138        |
| <b>Chapter 80 - Shells .....</b>   | <b>140</b> |
| Section 80.1 - Byobu .....   | 140        |
| <b>Chapter 81 - Other things to know .....</b>                                   | <b>142</b> |
| Section 81.1 - Markdown .....  | 142        |
| <br>   |            |
| <b>Part 8 - Software development guie.....</b>                                   | <b>143</b> |
| <b>Chapter 82 - Python .....</b>   | <b>144</b> |
| Section 82.1 - Background reading .....  | 144        |
| Section 82.2 - Python virtual environments .....                                 | 144        |
| Section 82.3 - Useful libraries.....   | 144        |
| <b>Chapter 83 - Introduction to ROS.....</b>                                     | <b>145</b> |
| Section 83.1 - Install ROS .....   | 145        |
| Section 83.2 - rqt_console .....   | 145        |
| Section 83.3 - roslaunch .....   | 145        |
| Section 83.4 - rviz .....  | 145        |
| Section 83.5 - rostopic .....  | 146        |
| <b>Chapter 84 - What the duck! .....</b>   | <b>147</b> |
| Section 84.1 - Adding more tests to what-the-duck .....                          | 147        |
| Section 84.2 - Tests already added .....   | 147        |
| Section 84.3 - List of tests to add .....  | 148        |
| <b>Chapter 85 - How to create a ROS package .....</b>                            | <b>149</b> |
| Section 85.1 - Conforming ROS package checklist .....                            | 149        |
| <b>Chapter 86 - Integrate package in the architecture.....</b>                   | <b>150</b> |
| <b>Chapter 87 - Creating unit tests .....</b>                                    | <b>151</b> |
| <br>   |            |
| <b>Part 9 - Fall 2017.....</b>   | <b>152</b> |
| <b>Chapter 88 - General remarks .....</b>  | <b>153</b> |
| Section 88.1 - The rules of Duckietown .....                                     | 153        |
| Section 88.2 - Synchronization between classes.....                              | 153        |
| Section 88.3 - Accounts for students .....                                       | 153        |
| Section 88.4 - Accounts for all instructors and TAs.....                         | 153        |
| <b>Chapter 89 - Additional information for ETH Z&amp;uuml;rich students.....</b> | <b>155</b> |
| <b>Chapter 90 - Additional information for UdeM students.....</b>                | <b>156</b> |
| <b>Chapter 91 - Additional information for TTIC students .....</b>               | <b>157</b> |
| <b>Chapter 92 - Additional information for NCTU students .....</b>               | <b>158</b> |
| <b>Chapter 93 - Milestone: ROS node working .....</b>                            | <b>159</b> |
| <b>Chapter 94 - Homework: Take and process a log .....</b>                       | <b>160</b> |
| <b>Chapter 95 - Milestone: Calibrated robot .....</b>                            | <b>161</b> |
| <b>Chapter 96 - Homework: Camera geometry.....</b>                               | <b>162</b> |
| <b>Chapter 97 - Milestone: Illumination invariance .....</b>                     | <b>163</b> |
| <b>Chapter 98 - Homework: Place recognition .....</b>                            | <b>164</b> |
| <b>Chapter 99 - Milestone: Lane following .....</b>                              | <b>165</b> |
| <b>Chapter 100 - Homework: localization .....</b>                                | <b>166</b> |
| <b>Chapter 101 - Milestone: Navigation .....</b>                                 | <b>167</b> |
| <b>Chapter 102 - Homework: group forming .....</b>                               | <b>168</b> |
| <b>Chapter 103 - Milestone: Ducks in a row .....</b>                             | <b>169</b> |
| <b>Chapter 104 - Homework: Comparison of PID .....</b>                           | <b>170</b> |
| <b>Chapter 105 - Homework: RRT .....</b>   | <b>171</b> |
| <b>Chapter 106 - Caffe tutorial.....</b>   | <b>172</b> |
| <b>Chapter 107 - Milestone: Object Detection .....</b>                           | <b>173</b> |
| <b>Chapter 108 - Homework: Object Detection .....</b>                            | <b>174</b> |
| <b>Chapter 109 - Milestone: Semantic perception .....</b>                        | <b>175</b> |
| <b>Chapter 110 - Homework: Semantic perception .....</b>                         | <b>176</b> |

|  |            |
|--|------------|
| Chapter 111 - Milestone: Reacting to obstacles.....                          | 177        |
| Chapter 112 - Homework: Reacting to obstacles .....                          | 178        |
| Chapter 113 - Milestone: SLAM demo .....                                     | 179        |
| Chapter 114 - Homework: SLAM .....   | 180        |
| Chapter 115 - Milestone: fleet demo .....                                    | 181        |
| Chapter 116 - Homework: fleet.....   | 182        |
| Chapter 117 - Project proposals .....  | 183        |
| Chapter 118 - Template of a project.....                                     | 184        |
| Section 118.1 - Checklist for students .....                                 | 184        |
| Section 118.2 - Checklist for TAs .....                                      | 184        |
| <br>   |            |
| <b>Part 10 - Drafts or pieces to remove.....</b>                             | <b>185</b> |
| <b>Chapter 119 - Laptop setup .....</b>                                      | <b>186</b> |
| Section 119.1 - Setup passwordless SSH to log in using the ubuntu user ..... | 186        |

PART 1

## Meta - The Duckietown project

# CHAPTER 1

## What is Duckietown?

### 1.1. Goals and objectives

Duckietown is a robotics educations and outreach effort.

The most tangible goal of the project is to provide a low-cost educational platform for learning autonomy, consisting of the Duckiebots, an autonomous robot, and the Duckietowns, the infrastructure in which the Duckiebots navigates.

However, we focus on the *learning experience* as a whole, by providing a set of modules teaching plans and other guides, as well as a curated role-play experience.

We have two targets:

1. For **instructors**, we want to create a “class-in-a-box” that allows to offer a modern and engaging learning experience. Currently, this is feasible at the advanced undergraduate and graduate level, though in the future we would like to present the platform as multi-grade experiences.
2. For **self-guided learners**, we want to create a “self-learning experience”, that allows to go from zero knowledge of robotics to graduate-level understanding.

In addition, the Duckietown platform has been used as a research platform.

### 1.2. Results obtained so far

While we are at the early phases of the project, many people have been used the materials in the past year.

### 1.3. Learn about the platform

The best way to get a sense of how the platform looks is to watch these videos. They show off the capabilities of the platform.

This video is part of the Red Hat documentary:

### 1.4. Learn about the educational experience

These papers present a more formal description of the technical side of the project as well as the educational side.

This paper [1] describes the course design for Duckietown: learning objectives, teaching methods, etc.

This video is a Duckumentary about the first version of the class, during Spring 2016. The Duckumentary was shot by Chris Welch.

### 1.5. Learn about the platform

The paper [2] describes the Duckiebot and its software. With 29 authors, we made the record for a robotics conference.

## CHAPTER 2

# Duckietown history and future

Assigned to: Liam

### 2.1. The beginnings of Duckietown

Duckietown started as an MIT class during Spring 2016.

### 2.2. Duckietown around the world

1) Duckietown High School

---

### 2.3. Coming up

In 2017, the class will be offered contemporaneously at:

- ETH Zurich
- University of Montreal
- University of Chicago

as well as:

---

## CHAPTER 3

# First steps

### 3.1. How to get started

If you are an instructor, please jump to [Section 3.2](#).

If you are a self-guided learner, please jump to [Section 3.3](#).

If you are a company, and interested in working with Duckietown, please jump to [Section 3.4](#).

### 3.2. Duckietown for instructors

### 3.3. Duckietown for self-guided learners

### 3.4. Introduction for companies

### 3.5. How to keep in touch

### 3.6. How to contribute

## CHAPTER 4

# Frequently Asked Questions

### 4.1. General questions

*Q: What is Duckietown?*

Duckietown is a low-cost educational and research platform.

*Q: Is Duckietown free to use?*

Yes. All materials are released according to an open source license.

*Q: Is everything ready?*

Not quite! Please [sign up to our mailing list](#) to get notified when things are a bit more ready.

*Q: How can I start?*

See the next section, Getting started.

*Q: How can I help?*

If you would like to help actively, please email [duckietown@mit.edu](mailto:duckietown@mit.edu).

### 4.2. FAQ by students / independent learners

*Q: I want to build my own Duckiebot. How do I get started?*

### 4.3. FAQ by instructors

*Q: How large a class can it be? I teach large classes.*

*Q: What is the budget for the robot?*

*Q: I want to teach a Duckietown class. How do I get started?*

Please get in touch with us at [duckietown@mit.edu](mailto:duckietown@mit.edu). We will be happy to get you started and sign you up to the Duckietown instructors mailing list.

*Q: Why the duckies?*

Compared to other educational robotics projects, the presence of the duckies is what makes this project stand out. Why the duckies?

We want to present robotics in an accessible and friendly way.

## CHAPTER 5

# Accounts

### 5.1. Complete list of accounts

Currently, Duckietown has the following accounts:

- Github: for source code, and issue tracking;
- Slack: a forum for wide communication;
- Twist: to be used for instructors coordination;
- Google Drive: to be used for instructors coordination, maintaining TODOs, etc;
- Dropbox Folders (part of Andrea's personal accounts): to be abandoned;
- Vimeo, for storing the videos;
- The `duckietown-teaching` mailing list, for low-rate communication with instructors;
- We also have a list of addresses, of people signed up on the website, that we didn't use yet;
- The Facebook page.

### 5.2. For other contributors

If you are an international contributor:

- Sign up on Slack, to keep up with the project.
- (optional) Get Github permissions if you do frequent updates to the repositories.

PART 2

## Meta - How to contribute

# CHAPTER 6

## Contributing to the documentation

### 6.1. Where the documentation is

All the documentation is in the repository `duckietown/duckuments`.

The documentation is written as a series of small files in Markdown format.

It is then processed by a series of scripts to create this output:

- a publication-quality PDF;
- an online HTML version, split in multiple pages and with comments boxes.

### 6.2. Editing links

The simplest way to contribute to the documentation is to click any of the “” icons next to the headers.

They link to the “edit” page in Github. There, one can make and commit the edits in only a few seconds.

### 6.3. Comments

In the multiple-page version, each page also includes a comment box powered by a service called Disqus. This provides a way for people to write comments with a very low barrier. (We would periodically remove the comments.)

### 6.4. Installing the documentation system

In the following, we are going to assume that the documentation system is installed in `~/duckuments`. However, it can be installed anywhere.

We are also going to assume that you have setup a Github account with working public keys.

#### 1) Dependencies

---

On Ubuntu 16.04, these are the dependencies to install:

```
$ sudo apt install libxml2-dev libxslt1-dev  
$ sudo apt install libffi6 libffi-dev  
$ sudo apt install python-dev python-numpy python-matplotlib  
$ sudo apt install virtualenv
```

#### 2) Download the `duckuments` repo

---

Download the `duckietown/duckuments` repository in that directory:

```
$ git clone git@github.com:duckietown/duckuments ~/duckuments
```

### 3) Setup the virtual environment

Next, we will create a virtual environment using inside the `~/duckuments` directory.

Change into that directory:

```
$ cd ~/duckuments
```

Create the virtual environment using `virtualenv`:

```
$ virtualenv --system-site-packages deploy
```

Other distributions: In other distributions you might need to use `venv` instead of `virtualenv`.

Activate the virtual environment:

```
$ source ~/duckuments/deploy/bin/activate
```

### 4) Setup the `mcdp` external repository

Make sure you are in the directory:

```
$ cd ~/duckuments
```

Clone the `mcdp` external repository, with the branch `duckuments`.

```
$ git clone -b duckuments git@github.com:AndreaCensi/mcdp
```

Install it and its dependencies:

```
$ cd ~/duckuments/mcdp  
$ python setup.py develop
```

**Note:** If you get a permission error here, it means you have not properly activated the virtual environment.

Other distributions: If you are not on Ubuntu 16, depending on your system, you might need to install these other dependencies:

```
$ pip install numpy matplotlib
```

## 6.5. Compiling the documentation

### Check before you continue

Make sure you have deployed and activated the virtual environment. You can check this by checking which `python` is active:

```
$ which python  
/home/[user]/duckuments/deploy/bin/python
```

Then:

```
$ cd ~/duckuments  
$ make duckuments-dist
```

This creates the directory `duckuments-dist`, which contains another checked out copy of the repository, but with the branch `gh-pages`, which is the branch that is published by Github using the “Github Pages” mechanism.

### Check before you continue

At this point, please make sure that you have these two `.git` folders:

```
~/duckuments/.git  
~/duckuments/duckuments-dist/.git
```

To compile the docs, run `make clean compile`:

```
$ make clean compile
```

To see the result, open the file

```
./duckuments-dist/master/duckiebook/index.html
```

#### 1) Incremental compilation

If you want to do incremental compilation, you can omit the `clean` and just use:

```
$ make compile
```

This will be faster. However, sometimes it might get confused. At that point, do `make clean`.

## 6.6. The workflow to edit documentation.

This is the workflow:

1. Edit the Markdown in the `master` branch of the `duckuments` repository.
2. Run `make compile` to make sure it compiles.
3. Commit the Markdown and push on the `master` branch.

Done. A bot will redo the compilation and push the changes in the `gh-pages` branch.

Step 2 is there so you know that the bot will not encounter errors.

## 6.7. \*Deploying the documentation

**Note:** This part is now done by a bot, so you don't need to do it manually.

To deploy the documentation, jump into the `DUCKUMENTS/duckuments-dist` directory.

Run the command `git branch`. If the output does not say that you are on the branch `gh-pages`, then one of the steps before was done incorrectly.

```
$ cd $DUCKUMENTS/duckuments-dist
$ git branch
...
* gh-pages
...
```

Now, after triple checking that you are in the `gh-pages` branch, you can use `git status` to see the files that were added or modified, and simply use `git add`, `git commit` and `git push` to push the files to Github.

## 6.8. \*Compiling the PDF version

**Note:** The dependencies below are harder to install. If you don't manage to do it, then you only lose the ability to compile the PDF. You can do `make compile` to compile the HTML version, but you cannot do `make compile-pdf`.

### 1) Installing nodejs

---

Ensure the latest version (>6) of nodejs is installed.

Run:

```
$ nodejs --version
6.xx
```

If the version is 4 or less, remove nodejs:

```
$ sudo apt remove nodejs
```

Install nodejs using [the instructions at this page](#).

Next, install the necessary Javascript libraries using `npm`:

```
$ cd $DUCKUMENTS
$ npm install MathJax-node jsdom@9.3 less
```

### 2) Troubleshooting nodejs installation problems

---

The only pain point in the installation procedure has been the installation of nodejs packages using `npm`. For some reason, they cannot be installed globally (`npm install -g`).

Do not use `sudo` for installation. It will cause problems.

If you use `sudo`, you probably have to delete a bunch of directories, such as: `REROOT/node_modules`, `~/.npm`, and `~/.node_modules`, if they exist.

### 3) Installing Prince

---

Install PrinceXML from [this page](#).

### 4) Installing fonts

---

Download STIX fonts from [this site](#).

Unzip and copy the ttf to `~/.fonts`:

```
$ cp -R STIXv2.0.0 ~/.fonts
```

and then rebuild the font cache using:

```
$ fc-cache -fv
```

## 5) Compiling the PDF

---

To compile the PDF, use:

```
$ make compile-pdf
```

This creates the file:

```
./duckuments-dist/master/duckiebook.pdf
```

## CHAPTER 7

# Features of the documentation writing system

The Duckiebook is written in a Markdown dialect. A subset of LaTeX is supported.

There are also some additional features that make it possible to create publication-worthy materials.

## 7.1. Embedded LaTeX

You can use ***LaTeX*** math, environment, and references. For example, take a look at

$$x^2 = \int_0^t f(\tau) d\tau$$

or refer to [Proposition 1](#).

**Proposition 1.** (Proposition example) This is an example proposition:  $2x = x + x$ .

The above was written as in [Figure 1](#).

```
You can use $LaTeX$ math, environment, and references.
For example, take a look at

\[ x^2 = \int_0^t f(\tau) \text{d}\tau
\]

or refer to [](#prop:example).

\begin{proposition}[Proposition example]\label{prop:example}
This is an example proposition: $2x = x + x$.
\end{proposition}
```

Figure 1. Use of LaTeX code.

## 7.2. Variables in command lines and command output

Use the syntax “[name]” for describing the variables in the code.

### Example 1.

For example, to obtain:

```
$ ssh ![robot name].local
```

Use the following:

```
For example, to obtain:
```

```
$ ssh ![robot name].local
```

Make sure to quote (with 4 spaces) all command lines. Otherwise, the dollar symbol confuses the LaTeX interpreter.

### 7.3. Character escapes

Use the string “`&#36;`” to write the dollar symbol “\$”, otherwise it gets confused with LaTeX math materials. Also notice that you should probably use “USD” to refer to U.S. dollars.

Other symbols to escape are shown in [Table 1](#).

TABLE 1. SYMBOLS TO ESCAPE

|                            |               |
|----------------------------|---------------|
| use <code>&amp;#36;</code> | instead of \$ |
| use <code>&amp;#96;</code> | instead of `  |
| use <code>&amp;#lt;</code> | instead of <  |
| use <code>&amp;gt;</code>  | instead of >  |

### 7.4. Keyboard keys

Use the `kbd` element for keystrokes.

#### Example 1.

For example, to obtain:

Press `a` then `Ctrl-C`.

use the following:

```
Press <kbd>a</kbd> then <kbd>Ctrl</kbd>-<kbd>C</kbd>.
```

### 7.5. Figures

For any element, adding an attribute called `figure-id` with value `fig:![figure ID]` or `tab:![table ID]` will create a figure that wraps the element.

For example:

```
<div figure-id="fig:![figure ID]">
  ! [figure content]
</div>
```

It will create HMTL of the form:

```
<div id='fig:code-wrap' class='generated-figure-wrap'>
  <figure id='fig:![figure ID]' class='generated-figure'>
    <div>
      ! [figure content]
    </div>
  </figure>
</div>
```

To add a caption, add an attribute `figure-caption`:

```
<div figure-id="fig:![figure ID]" figure-caption="This is my caption">
  ! [figure content]
</div>
```

Alternatively, you can put anywhere an element `figcaption` with ID `![figure id]:caption`:

```
<element figure-id="fig:[figure ID]">
  ![figure content]
</element>

<figcaption id='fig:[figure ID]:caption'>
  This is the caption figure.
</figcaption>
```

To refer to the figure, use an empty link:

Please see [](#fig:[figure ID]).

The code will put a reference to “Figure XX”.

## 7.6. Shortcut for tables

The shortcuts col2, col3, col4, col5 are expanded in tables with 2, 3, 4 or 5 columns.

The following code:

```
<col2 figure-id="tab:mytable" figure-caption="My table">
  <span>A</span>
  <span>B</span>
  <span>C</span>
  <span>D</span>
</col2>
```

gives the following result:

TABLE 1. MY TABLE

|   |   |
|---|---|
| A | B |
| C | D |

## 7.7. Troubleshooting

**Symptom:** “Invalid XML”

**Resolution:** “Markdown” doesn’t mean that you can put anything in a file. Except for the code blocks, it must be valid XML. For example, if you use “>” and “<” without quoting, it will likely cause a compile error.

**Symptom:** “Tabs are evil”

**Resolution:** Do not use tab characters. The error message in this case is quite helpful in telling you exactly where the tabs are.

**Symptom:** The error message contains `ValueError: Suspicious math fragment '$\LaTeX$'`

**Resolution:** You probably have forgotten to indent a command line by at least 4 spaces. The dollar in the command line is now being confused for a math formula.

# CHAPTER 8

## Documentation style guide

This chapter describes the conventions for writing the technical documentation.

### 8.1. General guidelines for technical writing

The following holds for all technical writing.

- The documentation is written in correct English.
- Do not say “should” when you mean “must”. “Must” and “should” have precise meanings and they are not interchangeable. These meanings are explained [in this document](#).
- “Please” is unnecessary in technical documentation.
  - ✗ “Please remove the SD card.”
  - ✓ “Remove the SD card”.
- Do not use colloquialisms or abbreviations.
  - ✗ “The pwd is ubuntu.”
  - ✓ “The password is ubuntu.”
- Do not use emojis.
- Do not use ALL CAPS.
- Make infrequent use of **bold statements**.
- Do not use exclamation points.

### 8.2. Style guide for the Duckietown documentation

- It’s ok to use “it’s” instead of “it is”, “can’t” instead of “cannot”, etc.
- All the filenames and commands must be enclosed in code blocks using Markdown backticks.
  - ✗ “Edit the `~/.ssh/config` file using vi.”
  - ✓ “Edit the `~/.ssh/config` file using vi.”
- `Ctrl`-`C`, ssh etc. are not verbs.
  - ✗ “`Ctrl`-`C` from the command line”.
  - ✓ “Use `Ctrl`-`C` from the command line”.
- Subtle humor and puns about duckies are encouraged.

### 8.3. Writing command lines

Use either “laptop” or “duckiebot” (not capitalized, as a hostname) as the prefix for the command line.

For example, for a command that is supposed to run on the laptop, use:

```
laptop $ cd ~/duckietown
```

It will become:

 \$ cd ~/duckietown

For a command that must run on the Duckiebot, use:

duckiebot \$ cd ~/duckietown

It will become:

 \$ cd ~/duckietown

If the command is supposed to be run on both, omit the hostname:

\$ cd ~/duckietown

## 8.4. Frequently misspelled words

- “Duckiebot” is always capitalized.
- Use “Raspberry Pi”, not “PI”, “raspi”, etc.
- These are other words frequently misspelled: 5 GHz WiFi

## 8.5. Other conventions

When the user must edit a file, just say: “edit /this/file”.

Writing down the command line for editing, like the following:

\$ vi /this/file

is too much detail.

(If people need to be told how to edit a file, Duckietown is too advanced for them.)

## 8.6. Troubleshooting sections

Write the documentation as if every step succeeds.

Then, at the end, make a “Troubleshooting” section.

Organize the troubleshooting section as a list of symptom/resolution.

The following is an example of a troubleshooting section.

### 1) Troubleshooting

---

| **Symptom:** This strange thing happens.

Resolution: Maybe the camera is not inserted correctly. Remove and reconnect.

| **Symptom:** This other strange thing happens.

Resolution: Maybe the plumbus is not working correctly. Try reformatting the plumbus.

# CHAPTER 9

## Knowledge graph

### 9.1. Formalization

#### 1) Atoms

---

**Definition 1.** (Atom) An *atom* is a concrete resource (text, video) that is the smallest unit that is individually addressable. It is indivisible.

Examples of atoms include:

- text (usually referred to as “chapters”);
- setup instructions;
- demo instructions;
- exercises;
- lecture slides;
- lecture videos.

#### 2) Semantic graph of atoms

---

Atoms form a directed graph, called “semantic graph”.

Each node is an atom.

The graph has four different types of edges:

- “Requires” edges describe a strong dependency: “You need to have done this. Otherwise it will not work.”
- “Recommended” edges describe a weaker dependency; it is not strictly necessary to have done that other thing, but it will significantly improve the result of this.
- “Reference” edges describe background information. “If you don’t know / don’t remember, you might want to see this”
- “See also” edges describe interesting materials for the interested reader. Completely optional; it will not impact the result of the current procedure.

#### 3) Modules

---

A “module” is an abstraction from the point of view of the teacher.

**Definition 1.** (Module) A *module* is a directed graph, where the nodes are either atoms or other modules, and the edges can be of the four types described in [Subsection 9.1.2](#).

Because modules can contain other modules, they allow to describe hierarchical contents. For example, a class module is a module that contains other modules; a “degree” is a module that contains “class” modules, etc.

Modules can overlap. For example, a “Basic Object Detection” and an “Advanced Object Detection” module might have a few atoms in common.

### 9.2. Atoms properties

Each atom has the following properties:

- An ID (alphanumeric + - and '\_'). The ID is used for cross-referencing. It is the same in all languages.
- A type, one of text, setup, demo, exercise.

There might be different versions of each atom. This is used primarily for dealing with translations of texts, different representations of the same image, Powerpoint vs Keynote, etc.

A version is a tuple of attributes.

The attributes are:

- Language: A language code, such as en-US (default), zh-CN, etc.
- Mime type: a MIME type.

Each atom version has:

- A status: one of draft, ready.
- A human-readable title.
- A human-readable summary (1 short paragraph).

### 9.3. Markdown format for text-like atoms

For the text-like resources, they are described in Markdown files.

The name of the file does not matter.

All files are encoded in UTF-8.

Each file starts with a H1 header. The contents is the title.

The header has the following attributes:

1. The ID. (#ID)
2. The language is given by an attribute lang ({lang=en-US}).
3. The type is given by an attribute type ({type=demo}).
4. The status is given by an attribute status ({status=draft}).

Here is an example of a header with all the attributes:

```
# Odometry calibration {#odometry-calibration lang=en-US type=demo status=ready}
```

This first paragraph will be used as the "summary" for this text.

Listing 1. calibration.en.md

And this is how the Italian translation would look like:

```
# Calibrazione dell'odometria {#odometry-calibration lang=it type=demo status=draft}
```

Questo paragrafo sarà usato come un sommario del testo.

Listing 1. calibration.it.md

### 9.4. How to describe the semantic graphs of atoms

In the text, you describe the semantic graph using tags and IDs.

In Markdown, you can give IDs to sections using the syntax:

```
# Setup step 1 {#setup-step1}
```

This is the first setup step.

Then, when you write the second step, you can add a semantic edge using the following.

```
# Setup step 2 {#setup-step2}
```

This is the second setup step.

Requires: You have completed the first step in [](#setup-step1).

The following table describes the syntax for the different types of semantic links:

TABLE 1. SEMANTIC LINKS

|             |   |
|-------------|---|
| Requires    | Requires: You need to have done [](#setup-step).  |
| Recommended | Recommended: It is better if you have setup Wifi as in [](#setup-wifi).                               |
| Reference   | Reference: For more information about rostopic,<br>see [](#rostopic).                                 |
| See also    | See also: If you are interested in feature detection, you might<br>want to learn about [SIFT](#SIFT). |

## 9.5. How to describe modules

**PART 3**

**Operation manual - Duckiebot**

## CHAPTER 10

# Duckiebot configurations

### 10.1. Configuration list

Configuration D17-0: Only camera and motors.

Configuration D17-0+w: Previous one + an additional WiFi card (Edimax).

Configuration D17-0+j: Previous one + joystick.

Configuration D17-1: LED lights and bumpers

### 10.2. Configuration functionality

## CHAPTER 11

# Acquiring the parts for the Duckiebot

Assigned to: Jacopo

The trip begins with acquiring the parts. Here, we provide a link to all bits and pieces that are needed to build a Duckiebot, along with their price tag.

In general, keep in mind that:

- The links might expire, or the prices might vary.
- In general, substitutions are OK for the mechanical components, and not OK for all the electronics, unless you are OK in writing some software.

Resources necessaries:

- Cost: USD ???
- Time: ??? days (average shipping)

Results:

- A kit of parts ready to be assembled.

### 11.1. Bill of materials

TABLE 1. BILL OF MATERIALS

|   |                |
|---|----------------|
| Chassis   | USD 20         |
| Camera with 160-FOV Fisheye Lens                                      | USD 39         |
| Camera Mount  | USD 8.50       |
| 300mm Camera Cable  | USD 2          |
| Raspberry Pi 3 - Model B  | USD 35         |
| Heat Sinks  | USD 5          |
| Power supply  | USD 7.50       |
| Class 10 MicroSD Card   | USD 20         |
| Female/Female Jumper Wires (300mm)                                    | USD 8          |
| Stepper Motor HAT - Mini Kit  | USD 22.50      |
| GPIO Stacking Headers - DC motor hat headers 2x20 Stacking Extra Long | USD 2.50       |
| 16-Channel PWM/Servo HAT for Raspberry Pi - Mini Kit                  | USD 17.50      |
| Battery   | USD 20         |
| 16 Nylon Standoffs (M2.5 12mm F 6mm M)                                | USD 0.05/piece |
| 4 Nylon Hex Nuts (M2.5)   | USD 0.02/piece |
| 4 Nylon Screws (M2.5x10)  | USD 0.05/piece |
| Zip Ties 300x5mm  | USD 8.99       |
| Joypad  | USD 10.50      |
| Premium Male/Male Jumper Wires (150mm) D17-1                          | USD 1.95       |
| Wifi Augmenter D17-θ+w  | USD 20         |
| LEDs D17-1  | USD 10         |
| GPIO Header - 40 pin female header                                    | USD 1.50       |
| LED HAT D17-1   | USD            |
| Bumpers   | USD ??         |
| Total for minimum configuration                                       | USD ??         |
| Total for fancy configuration   | USD ??         |

### 11.2. Chassis

We selected the Magician Chassis as the basic chassis for the robot ([Figure 2](#)).

We chose it because it has a double-decker configuration, and so we can put the battery in the lower part.

The chassis pack includes the motors and wheels as well as the structural part.

The price for this in the US is about USD 15-30.



Figure 2. The Magician Chassis

### 11.3. Raspberry Pi 3 (RPI-3)

The RPI-3 is the central computer of the Duckiebot. Duckiebot version D17 uses Model B ([Figure 3](#)) (A1.2GHz 64-bit quad-core ARMv8 CPU, 1GB RAM), a small but powerful computer.



Figure 3. The Raspberry Pi 3 Model B

The price for this in the US is about USD 35.

#### 1) Power Supply

---

We want a hard-wired power source (5VDC, 2.4A, Micro USB) to supply the RPI-3 ([Figure 4](#)).



Figure 4. The Power Supply

The price for this in the US is about USD 5-10.

## 2) Heat Sinks

The RPI-3 will heat up significantly during use. It is warmly recommended to add heat sinks, as in [Figure 5](#). Since we will be stacking HATs on top of the RPI-3 with 15 mm standoffs, the maximum height of the heat sinks should be well below 15 mm. The chip dimensions are 15x15 mm and 10x10 mm.



Figure 5. The Heat Sinks

## 3) Class 10 MicroSD Card

The MicroSD card [Figure 6](#) is the hard disk of the RPI-3. 16 GigaBytes of capacity are sufficient.



Figure 6. The MicroSD card

## 11.4. Camera

The Camera is the main sensor of the Duckiebot. Version 017 equips a 5 Mega Pixels 1080p camera with wide field of view ( $160^\circ$ ) fisheye lens ([Figure 7](#)).



Figure 7. The Camera with Fisheye Lens

### 1) Camera Mount

---

The camera mount ([Figure 8](#)) serves to keep the camera looking forward at the right angle to the road (looking slightly down). The front cover is not essential.




Figure 8. The Camera Mount

### 2) 300mm Camera Cable

---

A longer (300 mm) camera cable [Figure 9](#) make assembling the Duckiebot easier, allowing for more freedom in the relative positioning of camera and computational stack.




Figure 9. A 300 mm camera cable for the RPI-3

### 11.5. Wifi Augmenter

The Edimax AC1200 EW-7822ULC wifi adapter [Figure 10](#) improves the interactions with the Duckiebot by improving the connectivity between Duckiebot and laptop, especially useful in crowded environments (e.g., classroom).



Figure 10. The Edimax AC1200 EW-7822ULC wifi adapter

### 11.6. Joypad

The joypad is used to manually remote control the Duckiebot. Any 2.4 GHz wireless controller (with a *tiny* USB dongle) will do.

The model link in the table ([Figure 11](#)) does not include batteries (2 AA 1.5V)!



Figure 11. A Wireless Joypad

### 11.7. DC Stepper Motor HAT - Mini Kit

We use the DC+Stepper motor HAT to control the motors that drive the wheels.




Figure 12. The Stepper Motor HAT

### 1) Male-Male Jumper Wires

---




Figure 13. Premier Male-Male Jumper Wires

### 2) GPIO Stacking Headers

---



Figure 14. The Stacking Headers

## 11.8. 16-Channel PWM/Servo HAT for Raspberry Pi - Mini Kit




Figure 15. The PWM-Servo HAT

## 11.9. Battery

The battery provides power to the Duckiebot.

We choose this ([Figure 16](#)) battery because it has a good combination of size (to fit in the lower deck of the Magician Chassis), high output amperage (2.4A and 2.1A at 5V DC) over two USB outputs, a good capacity (10400 mAh) at an affordable price (USD 20).



Figure 16. The Battery

### 11.10. Standoffs, Nuts and Screws

We use non electrically conductive standoffs (M2.5 12mm F 6mm M), nuts (M2.5), and screws (M2.5x10mm) to hold the RPI-3 to the chassis and the HATs stacked on top of the RPI-3.

In versions D17-0 and D17-0+w, the Duckiebot requires 12 standoffs, 4 nuts and 4 screws.

In version D17-1, the Duckiebot requires 16 standoffs, 4 nuts and 4 screws.




Figure 17. Standoffs, Nuts and Screws

### 11.11. Ziptie

Two long (300x5 mm) zip ties are going to be useful to keep the battery at the lower deck from moving around.



Figure 18. The zip ties

## 11.12. LEDs

In the *fancy* version D17-1, the Duckiebot is equipped with 5 RGB LEDs. LEDs can be used to signal to other Duckiebots, or just make cool patterns!

The pack of LEDs linked in the table above holds 10 LEDs, enough for two Duckiebots.




Figure 19. The RGB LEDs

### 1) LED HAT

---

Daughterboard for Adafruit 16-Channel PWM / Servo HAT that enables connection with RGB LEDs, ADS1015 12 Bit, 4 Channel ADC, Monochrome 128x32 I2C OLED graphic display, and Adafruit 9-DOF IMU Breakout - L3GD20H + LSM303.




Figure 20. The LED HAT

### 2) Female-Female Jumper Wires

---



Figure 21. Premier Female-Female Jumper Wires

## 11.13. Bumpers




Figure 22. The Bumpers

#### 11.14. Passive Electric Components

## CHAPTER 12

# Soldering boards for ~~co~~

Assigned to: Shiying

Resources necessaries:

- ...
- Time: ??? minutes

Results:

- ...

## CHAPTER 13

# Assembling the Duckiebot

Assigned to: Shiying



Resources necessaries:

- Duckiebot D17-C0 parts.

Requires: The acquisition process is explained in [Chapter 11](#).

- Time: about ??? minutes.

Results:

- An assembled Duckiebot in configuration D17-C0.

Shiying: here will be the instruction about assembling the Duckiebot. :-)

# CHAPTER 14

## Reproducing the image

Assigned to: Andrea

These are the instructions to reproduce the Ubuntu image that we use.

Please note that the image is already available, so you don't need to do this manually. However, this documentation might be useful if you would like to port the software to a different distribution.

Resources necessaries:

- Internet connection to download the packages.
- A PC running any Linux with an SD card reader.
- Time: about 20 minutes.

Results:

- A baseline Ubuntu Mate 16.04.2 image with updated software.

### 14.1. Download and uncompress the Ubuntu Mate image

Download the image from the page

<https://ubuntu-mate.org/download/>

The file we are looking for is:

```
filename: ubuntu-mate-16.04.2-desktop-armhf-raspberry-pi.img.xz  
size: 1.2 GB  
SHA256: dc3afcadc68a5de3ba683dc30d2093a3b5b3cd6b2c16c0b5de8d50fede78f75c2
```

After download, run the command `sha256sum` to make sure you have the right version:

```
█ $ sha256sum ubuntu-mate-16.04.2-desktop-armhf-raspberry-pi.img.xz  
dc3afcadc68a5de3ba683dc30d2093a3b5b3cd6b2c16c0b5de8d50fede78f75c2
```

If the string does not correspond exactly, your download was corrupted. Delete the file and try again.

Then decompress using the command `xz`:

```
█ $ xz -d ubuntu-mate-16.04.2-desktop-armhf-raspberry-pi.img.xz
```

### 14.2. Burn the image to an SD card

Next, burn the image on to the SD card.

→ This procedure is explained in [Section 74.4](#).

#### 1) Verify that the SD card was created correctly

Remove the SD card and plug it in again in the laptop.

Ubuntu will mount two partitions, by the name of `PI_ROOT` and `PI_BOOT`.

## 2) Installation

---

Boot the disk in the Raspberry Pi.

Choose the following options:

```
language: English  
username: ubuntu  
password: ubuntu  
hostname: duckiebot
```

Choose the option to log in automatically.

Reboot.

## 3) Update installed software

---

The WiFi was connected to airport network `duckietown` with password `quackquack`.

Afterwards I upgraded all the software preinstalled with these commands:



```
$ sudo apt update  
$ sudo apt dist-upgrade
```

Expect `dist-upgrade` to take quite a long time (up to 2 hours).

### 14.3. Raspberry Pi Config

The Raspberry Pi is not accessible by SSH by default.

Run `raspi-config`:



```
$ sudo raspi-config
```

choose “3. Interfacing Options”, and enable SSH,

We need to enable the camera and the I2C bus.

choose “3. Interfacing Options”, and enable camera, and I2C.

Also disable the graphical boot

### 14.4. Install packages

Install these packages.

Etckeeper:



```
$ sudo apt install etckeeper
```

Editors / shells:



```
$ sudo apt install -y vim emacs byobu zsh
```

Git:



```
$ sudo apt install -y git git-extras
```

Other:



```
$ sudo apt install htop atop nethogs iftop  
$ sudo apt install aptitude apt-file
```

Development:



```
$ sudo apt install -y build-essential libblas-dev liblapack-dev libatlas-base-dev gfortran  
libyaml-cpp-dev
```

Python:



```
$ sudo apt install -y python-dev ipython python-sklearn python-smbus  
$ sudo pip install scipy --upgrade
```

I2C:



```
$ sudo apt install -y i2c-tools
```

## 14.5. Install Edimax driver

First, mark the kernel packages as not upgradeable:

```
$ sudo apt-mark hold raspberrypi-kernel raspberrypi-kernel-headers  
raspberrypi-kernel set on hold.  
raspberrypi-kernel-headers set on hold
```

Then, download and install the Edimax driver from [this repository](#).

## 14.6. Install ROS

Install ROS.

→ The procedure is given in [Section 83.1](#).

## 14.7. Wireless configuration (old version)

This is the old version.

There are two files that are important to edit.

The file /etc/network/interfaces should look like this:

```
# interfaces(5) file used by ifup(8) and ifdown(8)  
# Include files from /etc/network/interfaces.d:  
#source-directory /etc/network/interfaces.d  
  
auto wlan0  
  
# The loopback network interface  
auto lo  
iface lo inet loopback  
  
# Wireless network interface  
allow-hotplug wlan0  
iface wlan0 inet dhcp  
wpa-conf /etc/wpa_supplicant/wpa_supplicant.conf  
iface default inet dhcp
```

The file `/etc/wpa_supplicant/wpa_supplicant.conf` should look like this:

```
ctrl_interface=DIR=/var/run/wpa_supplicant GROUP=netdev
update_config=1

network={
    ssid="duckietown"
    psk="quackquack"
    proto=RSN
    key_mgmt=WPA-PSK
    pairwise=CCMP
    auth_alg=OPEN
}
network={
    key_mgmt=NONE
}
```

## 14.8. Wireless configuration

The files that describe the network configuration are in the directory

```
/etc/NetworkManager/system-connections/
```

This is the contents of the connection file `duckietown`, which describes how to connect to the duckietown wireless network:

```
[connection]
id=duckietown
uuid=e9cef1bd-f6fb-4c5b-93cf-cca837ec35f2
type=wifi
permissions=
secondaries=
timestamp=1502254646

[wifi]
mac-address-blacklist=
mac-address-randomization=Ø
mode=infrastructure
ssid=duckietown

[wifi-security]
group=
key-mgmt=wpa-psk
pairwise=
proto=
psk=quackquack

[ipv4]
dns-search=
method=auto

[ipv6]
addr-gen-mode=stable-privacy
dns-search=
ip6-privacy=Ø
method=auto
```

This is the file

```
/etc/NetworkManager/system-connections/create-5ghz-network
```

## Contents:

```
[connection]
id=create-5ghz-network
uuid=7331d1e7-2cdf-4047-b426-c170ecc16f51
type=wifi
# Put the Edimax interface name here:
interface-name=!wlx74da38c9caa0 - to change]
permissions=
secondaries=
timestamp=1502023843

[wifi]
band=a
# Put the Edimax MAC address here
mac-address=!74:DA:38:C9:CA:A0 - to change]
mac-address-blacklist=
mac-address-randomization=0
mode=ap
seen-bssids=
ssid=duckiebot-not-configured

[ipv4]
dns-search=
method=shared

[ipv6]
addr-gen-mode=stable-privacy
dns-search=
ip6-privacy=0
method=ignore
```

Note that there is an interface name and MAC address that need to be changed on each PI.

## 14.9. SSH server config

This enables the SSH server:

```
$ sudo systemctl enable ssh
```

## 14.10. Create swap Space

Do the following:

Create an empty file using the `dd` (device-to-device copy) command:



```
$ sudo dd if=/dev/zero of=/swap0 bs=1M count=512
```

This is for a 512 MB swap space.

Format the file for use as swap:



```
$ sudo mkswap /swap0
```

Add the swap file to the system configuration:



```
$ sudo vi /etc/fstab
```

Add this line to the bottom:

```
/swap0 swap swap
```

Activate the swap space:

 \$ sudo swapon -a

## 14.11. Passwordless sudo

First, make vi the default editor, using

```
$ sudo update-alternatives --config editor
```

and then choose vim.basic.

Then run:

```
$ sudo visudo
```

And then change this line:

```
%sudo ALL=(ALL:ALL) ALL
```

into this line:

```
%sudo ALL=(ALL:ALL) NOPASSWD:ALL
```

## 14.12. Ubuntu user configuration

### 1) Groups

You should make the `ubuntu` user belong to the `i2c` and `input` groups:

 \$ sudo adduser ubuntu i2c  
\$ sudo adduser ubuntu input

: forgot to add to aug20 image:

 \$ sudo adduser ubuntu video

You may need to do the following (but might be done already through `raspi-config`):

 \$ sudo udevadm trigger

### 2) Basic SSH config

Do the basic SSH config.

- The procedure is documented in Section 77.3.

**Note:** this is not in the aug10 image.

### 3) Passwordless SSH config

---

Add .authorized\_keys so that we can all do passwordless SSH.

The key is at the URL

[https://www.dropbox.com/s/pxyou3qy1p8m4d0/duckietown\\_key1.pub?dl=1](https://www.dropbox.com/s/pxyou3qy1p8m4d0/duckietown_key1.pub?dl=1)

Download to .ssh/authorized\_keys:



\$ curl -o .ssh/authorized\_keys ![URL above]

### 4) Shell prompt

---

Add the following lines to ~ubuntu/.bashrc:

```
echo ""
echo "Welcome to a duckiebot!"
echo ""
echo "Reminders:"
echo ""
echo "1) Do not use the user 'ubuntu' for development - create your own user."
echo "2) Change the name of the robot from 'duckiebot' to something else."
echo ""

export EDITOR=vim
```

## CHAPTER 15

# Installing Ubuntu on laptops

Assigned to: Andrea

Before you prepare the Duckiebot, you need to have a laptop with Ubuntu installed.

Requirements:

- A laptop with free disk space.
- Internet connection to download the Ubuntu image.
- About ??? minutes.

Results:

- A laptop ready to be used for Duckietown.

### 15.1. Install Ubuntu

Install Ubuntu 16.04.2.

→ For instructions, see for example [this online tutorial](#).

**On the choice of username:** During the installation, create a user for yourself with a username different from `ubuntu`, which is the default. Otherwise, you may get confused later.

### 15.2. Install useful software

Use `etckeeper` to keep track of the configuration in `/etc`:

 \$ sudo apt install etckeeper

Install `ssh` to login remotely and the server:

 \$ sudo apt install ssh

Use `byobu`:

 \$ sudo apt install byobu

Use `vim`:

 \$ sudo apt install vim

Use `htop` to monitor CPU usage:

 \$ sudo apt install htop

Additional utilities for `git`:

 \$ sudo apt install git git-extras

Other utilities:

 \$ sudo apt install avahi-utils cryptfs-utils

### 15.3. Install ROS

Install ROS on your laptop.

→ The procedure is given in [Section 83.1](#).

### 15.4. Other suggested software

#### 1) Redshift

This is Flux for Linux. It is an accessibility/lab safety issue: bright screens damage eyes and perturb sleep [3].

Install redshift and run it.

 \$ sudo apt install redshift-gtk

Set to “autostart” from the icon.

#### 2) Installation of the duckuments system

Optional but very encouraged: install the duckuments system. This will allow you to have a local copy of the documentation and easily submit questions and changes.

→ The procedure is documented in [Section 6.4](#).

### 15.5. Passwordless sudo

Set up passwordless sudo.

→ This procedure is described in [Section 14.11](#).

### 15.6. SSH and Git setup

#### 1) Basic SSH config

Do the basic SSH config.

→ The procedure is documented in [Section 77.3](#).

#### 2) Create key pair for ![username]

Next, create a private/public key pair for the user; call it ![username]@[robot name].

→ The procedure is documented in [Section 77.5](#).

---

### 3) Add ![username]‘s public key to Github

---

Add the public key to your Github account.

- The procedure is documented in [Section 73.3](#).

If the step is done correctly, this command should succeed:



```
$ ssh -T git@github.com
```

---

### 4) Local Git setup

---

Set up Git locally.

- The procedure is described in [Section 79.3](#).

# CHAPTER 16

## Duckiebot Initialization

Assigned to: Andrea

Prerequisites:

- An SD card of dimensions at least 32 GB.
- A computer with an internet connection, an SD card reader, and 35 GB of free space.
- A mounted Duckiebot in configuration D17-C0.

Requires: This is the result of [Chapter 13](#).

Result:

- A Duckiebot that is ready to use.

What does it mean “ready to use”?

### 16.1. Acquire and burn the image

On the laptop, download the compressed image at this URL:

<https://www.dropbox.com/s/1p4am7erdd9e53r/duckiebot-RPI3-AC-aug10.img.xz?dl=1>

The size is 2.5 GB.

You can use:

```
$ curl -o duckiebot-RPI3-AC-aug10.img.xz ![URL above]
```

Uncompress the file:

```
$ xz -d -k duckiebot-RPI3-AC-aug10.img.xz
```

This will create a file of 32 GB in size.

To make sure that the image is downloaded correctly, compute its hash using the program sha256sum:

```
$ sha256sum duckiebot-RPI3-AC-aug10.img  
2ea79b0fc6353361063c89977417fc5e8fde70611e8afa5cbf2d3a166d57e8cf duckiebot-ac-aug10.img
```

Compare the hash that you obtain with the hash above. If they are different, there was some problem in downloading the image.

Next, burn the image on disk.

- The procedure of how to burn an image is explained in [Section 74.4](#).

### 16.2. Turn on the Duckiebot

Put the SD Card in the Duckiebot.

Turn on the Duckiebot by connecting the power cable to the battery.

### 16.3. Connect the Duckiebot to a network

You can login to the Duckiebot in two ways:

1. Through an Ethernet cable.
2. Through a `duckietown` WiFi network.

In the worst case, you can use an HDMI monitor and a USB keyboard.

#### 1) Option 1: Ethernet cable

---

Connect the Duckiebot and your laptop to the same network switch.

Allow 30 s - 1 minute for the DHCP to work.

#### 2) Option 2: Duckietown network

---

The Duckiebot connects automatically to a 2.4 GHz network called “`duckietown`” and password “`quackquack`”.

Connect your laptop to the same wireless network.

### 16.4. Ping the Duckiebot

To test that the Duckiebot is connected, try to ping it.

The hostname of a freshly-installed duckiebot is `duckiebot-not-configured`:

 \$ ping `duckiebot-not-configured.local`

You should see output similar to the following:

```
PING duckiebot-not-configured.local (![X.X.X.X]): 56 data bytes  
64 bytes from ![X.X.X.X]: icmp_seq=0 ttl=64 time=2.164 ms  
64 bytes from ![X.X.X.X]: icmp_seq=1 ttl=64 time=2.303 ms  
![...]
```

### 16.5. SSH to the Duckiebot

Next, try to log in using SSH, with account `ubuntu`:

 \$ ssh `ubuntu@duckiebot-not-configured.local`

The password is `ubuntu`.

By default, the robot boots into Byobu.

Please see [Section 80.1](#) for an introduction to Byobu.

Not sure it's a good idea to boot into Byobu.

### 16.6. (For D17-C1) Configure the robot-generated network

D17-~~0+w~~ The Duckiebot in configuration D17-~~0+w~~ can create a WiFi network.

It is a 5 GHz network; this means that you need to have a 5 GHz WiFi adapter in your laptop.

First, make sure that the Edimax is correctly installed. Using `iwconfig`, you should see four interfaces:



```
$ iwconfig
wlx![AABBCCDDEEFFGG] unassociated Nickname:"rtl8822bu"
!...
lo      no wireless extensions.

enxb827eb1f81a4  no wireless extensions.

wlan1    IEEE 802.11bgn  ESSID:"duckietown"
!...
```

Make note of the name `wlx![AABBCCDDEEFFGG]`.

Look up the MAC address using the command:



```
$ ifconfig wlx![AABBCCDDEEFFGG]
wlx74da38c9caa0 Link encap:Ethernet  HWaddr ![AA:BB:CC:DD:EE:FF:GG]
```

Then, edit the connection file

```
/etc/NetworkManager/system-connections/create-5ghz-network
```

Make the following changes:

- Where it says `interface-name=![...]`, put “`wlx![AABBCCDDEEFFGG]`”.
- Where it says `mac-address=![...]`, put “`![AA:BB:CC:DD:EE:FF:GG]`”.
- Where it says `ssid=duckiebot-not-configured`, put “`ssid=![robot name]`”.

Reboot.

At this point you should see a new network being created named “`![robot name]`”.

You can connect with the laptop to that network.

If the Raspberry Pi’s network interface is connected to the `duckietown` network and to the internet, the Raspberry Pi will act as a bridge to the internet.

## 16.7. Setting up wireless network configuration

This part should not be necessary anymore

The Duckiebot is configured by default to connect to a wireless network with SSID `duckietown`. If that is not your SSID then you will need to change the configuration.

You can add a new network by editing the file:

```
/etc/wpa_supplicant/wpa_supplicant.conf
```

You will see a block like the following:

```
network={
  ssid="duckietown"
  scan_ssid=1
  psk="quackquack"
  priority=10
}
```

Add a new one with your SSID and password.

This assumes you have a roughly similar wireless network setup - if not then you might

need to change some of the other attributes.

## 16.8. Update the system

Next, we need to update to bring the system up to date.

Use these commands



```
$ sudo apt update  
$ sudo apt dist-upgrade
```

## 16.9. Give a name to the Duckiebot

It is now time to give a name to the Duckiebot.

These are the criteria:

- It should be a simple alphabetic string (no numbers or other characters like “-”, “\_”, etc.).
- It will always appear lowercase.
- It cannot be a generic name like “duckiebot”, “robot” or similar.

From here on, we will refer to this string as “[robot name]”. Every time you see ![robot name], you should substitute the name that you chose.

## 16.10. Change the hostname

We will put the robot name in configuration files.

**Note:** Files in /etc are only writable by root, so you need to use sudo to edit them. For example:



```
$ sudo vi ![filename]
```

Edit the file

```
/etc/hostname
```

and put “[robot name]” instead of duckiebot-not-configured.

Also edit the file

```
/etc/hosts
```

and put “[robot name]” where duckiebot-not-configured appears.


The first two lines of /etc/hosts should be:

```
127.0.0.1 localhost  
127.0.1.1 ![robot name]
```

**Note:** there is a command hostname that promises to change the hostname. However, the change given by that command does not persist across reboots. You need to edit the files above for the changes to persist.

**Note:** Never add other hostnames in /etc/hosts. It is a tempting fix when DNS does not work, but it will cause other problems subsequently.

Then reboot the Raspberry Pi using the command

 \$ sudo reboot

After reboot, log in again, and run the command `hostname` to check that the change has persisted:


 \$ hostname  
![robot name]

### 16.11. Create your user


You must not use the `ubuntu` user for development. Instead, you need to create a new  user.

Choose a user name, which we will refer to as `![username]`.


To create a new user:

 \$ sudo useradd -m `![username]`

Make the user an administrator by adding it to the group `sudo`:

 \$ sudo adduser `![username]` sudo

Make the user a member of the group `input` and `i2c`



```
$ sudo adduser ![username] input  
$ sudo adduser ![username] video  
$ sudo adduser ![username] i2c
```

Set the shell `bash`:

 \$ sudo chsh -s /bin/bash andrea

To set a password, use:

 \$ sudo passwd `![username]`

At this point, you should be able to login to the new user from the laptop using the password:

 \$ ssh `![username]@![robot name]`

Next, you should repeat some steps that we already described.

---

#### 1) Basic SSH config

Do the basic SSH config.

→ The procedure is documented in [Section 77.3](#).

---

#### 2) Create key pair for `![username]`

Next, create a private/public key pair for the user; call it `![username]@![robot name]`.

→ The procedure is documented in [Section 77.5](#).

### 3) Add ![username]’s public key to Github

---

Add the public key to your Github account.

- The procedure is documented in [Section 73.3](#).

If the step is done correctly, this command should succeed:

 \$ ssh -T git@github.com

### 4) Local Git configuration

---

- This procedure is in [Section 79.3](#).

### 5) Set up the laptop-Duckiebot connection

---

Make sure that you can login passwordlessly to your user from the laptop.

- The procedure is explained in [Section 77.6](#). In this case, we have: ![[local]] = laptop, ![[local-user]] = your local user on the laptop, ![[remote]] = ![[robot name]], ![[remote-user]] = ![[username]].

If the step is done correctly, you should be able to login from the laptop to the robot, without typing a password:

 \$ ssh ![[username]]@![[robot name]]

### 6) Some advice on the importance of passwordless access

---

In general, if you find yourself:

- typing an IP
- typing a password
- typing `ssh` more than once
- using a screen / USB keyboard

it means you should learn more about Linux and networks, and you are setting yourself up for failure.

Yes, you “can do without”, but with an additional 30 seconds of your time. The 30 seconds you are not saving every time are the difference between being productive roboticsists and going crazy.

Really, it is impossible to do robotics when you have to think about IPs and passwords...

## 16.12. Other customizations

If you know what you are doing, you are welcome to install and use additional shells, but please keep Bash as be the default shell. This is important for ROS installation.

For the record, our favorite shell is ZSH with `oh-my-zsh`.

## 16.13. Hardware check: camera

Check that the camera is connected using this command:



```
$ vcgencmd get_camera  
supported=1 detected=1
```

If you see `detected=0`, it means that the hardware connection is not working.

You can test the camera right away using a command-line utility called `raspistill`.

Use the `raspistill` command to capture the file `out.jpg`:



```
$ raspistill -t 1 -o out.jpg
```

Then download `out.jpg` to your computer using `scp` for inspection.

- For instructions on how to use `scp`, see Subsection 77.8.1.

## 1) Troubleshooting

---

**Symptom:** `detected=0`

**Resolution:** If you see `detected=0`, it is likely that the camera is not connected correctly.

If you see an error that starts like this:

```
mmal: Cannot read camera info, keeping the defaults for OV5647  
![...]  
mmal: Camera is not detected. Please check carefully the camera module is installed correctly.
```

then, just like it says: “Please check carefully the camera module is installed correctly.”

## CHAPTER 17

# Software setup and RC remote control

Assigned to: Andrea

Prerequisites:

- You have configured the laptop.

Requires: The procedure is documented in [Chapter 15](#).

- You have configured the Duckiebot.

Requires: The procedure is documented in [Chapter 16](#).

- You have created a Github account and configured public keys, both for the laptop and for the Duckiebot.

Requires: The procedure is documented in [Chapter 73](#).

Results:

- You can run the joystick demo.

### 17.1. Clone the Duckietown repository

Clone the repository in the directory `~/duckietown`:

 \$ git clone git@github.com:duckietown/Software.git ~/duckietown

For the above to succeed you should have a Github account already set up.

It should not ask for a password.

#### 1) Troubleshooting

---

Symptom: It asks for a password.

Resolution: You missed some of the steps described in [Chapter 73](#).

Symptom: Other weird errors.

Resolution: Probably the time is not set up correctly. Use `ntpdate` as above:

```
$ sudo ntpdate -u us.pool.ntp.org
```

### 17.2. Set up ROS environment on the Duckiebot

All the following commands should be run in the `~/duckietown` directory:

 \$ cd ~/duckietown

Now we are ready to make the workspace. First you need to source the baseline ROS environment:

 \$ source /opt/ros/kinetic/setup.bash

Then, build the workspace using:



```
$ catkin_make -C catkin_ws/
```

\* For more information about `catkin_make`, see [Subsection 83.5.3](#).

AC: I had to run it twice. The first time it complained:

```
In file included from /home/andrea/duckietown/catkin_ws/src/apriltags_ros/apriltags_ros/src/
apriltag_detector.cpp:1:0:
/home/andrea/duckietown/catkin_ws/src/apriltags_ros/apriltags_ros/include/apriltags_ros/
apriltag_detector.h:6:41: fatal error: duckietown_msgs/BoolStamped.h: No such file or directory
```

### 17.3. Add your vehicle to the machines file

On the robot edit the file

```
~/duckietown/catkin_ws/src/duckietown/machines
```

You will see something like this:

```
<launch>
  <arg name="env_script_path" default="~/duckietown/environment.sh"/>

  <machine name="![robot name]" address="![robot name].local" user="![username]"
    env-loader="$(arg env_script_path)"/>
  ...
  ...
</launch>
```

Now, duplicate a `<machine>` line between `<launch>` and `</launch>`, and replace the name and address string with the name of your vehicle.

For example, for Andrea, `![robot name]` = `emma` and `![username]` = `andrea`. So, he would add this line:

```
<machine name="emma" address="emma.local" user="andrea" env-loader="$(arg env_script_path)"/>
```

Commit and push the new machines file. ( No, don't commit the machines file.)

### 17.4. Test that the joystick is detected

Plug the joystick receiver in one of the USB port on the Raspberry Pi.

To make sure that the joystick is detected, run:



```
$ ls /dev/input/
```

and check if there is a device called `js0` on the list.

**Check before you continue**

Make sure that your user is in the group `input` and `i2c`:

```
$ groups
![username] sudo input i2c
```

If `input` and `i2c` are not in the list, you missed a step. Ohi oh! You are not following the instructions carefully!

→ Consult again [Section 16.11](#).

To test whether or not the joystick itself is working properly, run:

 \$ jstest /dev/input/js0

Move the joysticks and push the buttons. You should see the data displayed change according to your actions.

## 17.5. Run the joystick demo

SSH into the Raspberry Pi and run the following from the `duckietown` directory:

 \$ cd ~/duckietown  
\$ source environment.sh

The `environment.sh` setups the ROS environment at the terminal (so you can use commands like `rosrun` and `roslaunch`).

Now make sure the motor shield is connected.

Run the command:

 \$ roslaunch duckietown joystick.launch veh:=![robot name]

If there is no “red” output in the command line then pushing the left joystick knob controls throttle - right controls steering.

This is the expected result of the commands:

|                      |                           |
|----------------------|---------------------------|
| left joystick up     | forward                   |
| left joystick down   | backward                  |
| right joystick left  | turn left (positive yaw)  |
| right joystick right | turn right (negative yaw) |

It is possible you will have to unplug and replug the joystick or just push lots of buttons on your joystick until it wakes up. Also make sure that the mode switch on the top of your joystick is set to “X”, not “D”.

Is all of the above valid with the new joystick?

Close the program using `Ctrl-C`.

### 1) Troubleshooting

---

**Symptom:** The robot moves weirdly (e.g. forward instead of backward).

**Resolution:** The cables are not correctly inserted. Please refer to the assembly guide for pictures of the correct connections. Try swapping cables until you obtain the expected behavior.

**Resolution:** Check that the joystick has the switch set to the position “x”. And the mode light should be off.

**Symptom:** The left joystick does not work.

**Resolution:** If the green light on the right to the “mode” button is on, click the “mode” button to turn the light off. The “mode” button toggles between left joystick or the cross on the left.

**| Symptom:** The robot does not move at all.

**Resolution:** The cables are disconnected.

**Resolution:** The program assumes that the joystick is at `/dev/input/js0`. In doubt, see [Section 17.4](#).

## 17.6. The proper shutdown procedure for the Raspberry Pi

Generally speaking, you can terminate any `roslaunch` command with `Ctrl-C`.

To completely shutdown the robot, issue the following command:

 \$ sudo shutdown -h now

Then wait 30 seconds.

**Warning:** If you disconnect the power before shutting down properly using `shutdown`, the system might get corrupted.

Then, disconnect the power cable, at the **battery end**.

**Warning:** If you disconnect frequently the cable at the Raspberry Pi’s end, you might damage the port.

## CHAPTER 18

# Reading from the camera

Prerequisites:

- You have configured the Duckiebot.

**I Requires:** The procedure is documented in [Chapter 16](#).

- You know the basics of ROS (launch files, `roslaunch`, topics, `rostopic`).

Results:

- You know that the camera works under ROS.

### 18.1. Check the camera hardware

It might be useful to do a quick camera hardware check.

→ The procedure is documented in [Section 16.13](#).

### 18.2. Create two windows

On the laptop, create two Byobu windows.

→ A quick reference about Byobu commands is in [Section 80.1](#).

You will use the two windows as follows:

- In the first window, you will launch the nodes that control the camera.
- In the second window, you will launch programs to monitor the data flow.

**Note:** You could also use multiple *terminals* instead of one terminal with multiple Byobu windows. However, using Byobu is the best practice to learn.

### 18.3. First window: launch the camera nodes

In the first window, we will launch the nodes that control the camera.

Activate ROS:

 \$ source environment.sh

Run the launch file called `camera.launch`:

 \$ roslaunch duckietown camera.launch veh:=![robot name]

At this point, you should see the red LED on the camera light up continuously.

In the terminal you should not see any red message, but only happy messages like the following:

```
![...]
[INFO] [1502539383.948237]: [/![robot name]/camera_node] Initialized.
[INFO] [1502539383.951123]: [/![robot name]/camera_node] Start capturing.
[INFO] [1502539384.040615]: [/![robot name]/camera_node] Published the first image.
```

\* For more information about `roslaunch` and “launch files”, see [Section 83.3](#).

## 18.4. Second window: view published topics

Switch to the second window.

Activate the ROS environment:

 \$ source environment.sh

### 1) List topics

You can see a list of published topics with the command:

 \$ rostopic list

\* For more information about `rostopic`, see [Section 83.5](#).

You should see the following topics:

```
/![robot name]/camera_node/camera_info
/![robot name]/camera_node/image/compressed
/![robot name]/camera_node/image/raw
/rosout
/rosout_agg
```

### 2) Show topics frequency

You can use `rostopic hz` to see the statistics about the publishing frequency:

 \$ rostopic hz /![robot name]/camera\_node/image/compressed

On a Raspberry Pi 3, you should see a number close to 30 Hz:

```
average rate: 30.016
min: 0.026s max: 0.045s std dev: 0.00190s window: 841
```

### 3) Show topics data

You can view the messages in real time with the command `rostopic echo`:

 \$ rostopic echo /![robot name]/camera\_node/image/compressed

You should see a large sequence of numbers being printed to your terminal.

That’s the “image” — as seen by a machine.

If you are Neo, then this already makes sense. If you are not Neo, in [Chapter 20](#), you will learn how to visualize the image stream on the laptop using `rviz`.

use `Ctrl-C` to stop `rostopic`.

## CHAPTER 19

# RC control launched remotely

Assigned to: Andrea

Prerequisites:

- You can run the joystick demo from the Raspberry Pi.

Requires: The procedure is documented in [Chapter 17](#).

Results:

- You can run the joystick demo from your laptop.

### 19.1. Two ways to launch a program

ROS nodes can be launched in two ways:

1. “local launch”: log in to the Raspberry Pi using SSH and run the program from there.
2. “remote launch”: run the program directly from a laptop.

Which is better when is a long discussion that will be done later. Here we set up the “remote launch”.

### 19.2. Download and setup Software repository on the laptop

As you did on the Duckiebot, you should clone the Software repository in the `~/duckietown` directory.

- The procedure is documented in [Section 17.1](#).

Then, you should build the repository.

- This procedure is documented in [Section 17.2](#).

### 19.3. Edit the `machines` files on your laptop

You have to edit the `machines` files on your laptop, as you did on the Duckiebot.

- The procedure is documented in [Section 17.3](#).

### 19.4. Start the demo

Now you are ready to launch the joystick demo remotely.

#### Check before you continue

Make sure that you can login with SSH without a password. From the laptop, run:

```
💻 $ ssh ![username]@[robot name].local
```

If this doesn't work, you missed some previous steps.

Run this *on the laptop*:

```
💻 $ source environment.sh  
$ roslaunch duckietown joystick.launch veh:=![robot name]
```

You should be able to drive the vehicle with joystick just like the last example. Note that remotely launching nodes from your laptop doesn't mean that the nodes are running on your laptop. They are still running on the Raspberry Pi in this case.

\* For more information about `roslaunch`, see [Section 83.3](#).

## 19.5. Watch the program output using `rqt_console`

Also, you might have noticed that the terminal where you launch the launch file is not printing all the printouts like the previous example. This is one of the limitations of remote launch.

Don't worry though, we can still see the printouts using `rqt_console`.

On the laptop, open a new terminal window, and run:

```
💻 $ export ROS_MASTER_URI=http://![robot name].local:11311/  
$ rqt_console
```

AC: I could not see any messages in `rqt_console` - not sure what is wrong.

You should see a nice interface listing all the printouts in real time, completed with filters that can help you find that message you are looking for in a sea of messages.

You can use `Ctrl-C` at the terminal where `roslaunch` was executed to stop all the nodes launched by the launch file.

\* For more information about `rqt_console`, see [Section 83.2](#).

## 19.6. Troubleshooting

**Symptom:** `roslaunch` fails with an error similar to the following:

```
remote[![robot name].local-0]: failed to launch on ![robot name]:
```

```
Unable to establish ssh connection to ![username]@[robot name].local:22:  
Server '![robot name].local' not found in known_hosts.
```

**Resolution:** You have not followed the instructions that told you to add the `HostKeyAlgorithms` option. Delete `~/.ssh/known_hosts` and fix your configuration.

→ The procedure is documented in [Section 77.3](#).

## CHAPTER 20

# RC+camera remotely

Assigned to: Andrea

Prerequisites:

- You can run the joystick demo remotely.

Requires: The procedure is documented in [Chapter 19](#).

- You can read the camera data from ROS.

Requires: The procedure is documented in [Chapter 18](#).

- You know how to get around in Byobu.

→ You can find the Byobu tutorial in [Section 80.1](#).

Results:

- You can run the joystick demo from your laptop and see the camera image on the laptop.

### 20.1. Assumptions

We are assuming that the joystick demo in [Chapter 19](#) worked.

We are assuming that the procedure in [Chapter 18](#) succeeded.

We also assume that you terminated all instances of `roslaunch` with `Ctrl-C`, so that currently there is nothing running in any window.

### 20.2. Terminal setup

On the laptop, this time create **four** Byobu windows.

→ A quick reference about Byobu commands is in [Section 80.1](#).

You will use the four windows as follows:

- In the first window, you will run the joystick demo, as before.
- In the second window, you will launch the nodes that control the camera.
- In the third window, you will launch programs to monitor the data flow.
- In the fourth window, you will use `rviz` to see the camera image.

### 20.3. First window: launch the joystick demo

In the first window, launch the joystick remotely using the same procedure in [Section 19.4](#).



```
$ source environment.sh
$ roslaunch duckietown joystick.launch veh:=![robot name]
```

You should be able to drive the robot with the joystick at this point.

## 20.4. Second window: launch the camera nodes

In the second window, we will launch the nodes that control the camera. The launch file is called `camera.launch`:

```
 $ source environment.sh  
$ roslaunch duckietown camera.launch veh:=![robot name]
```

You should see the red led on the camera light up.

## 20.5. Third window: view data flow

Open a third terminal on the laptop.

You can see a list of topics currently on the `ROS_MASTER` with the commands:

```
 $ source environment.sh  
$ export ROS_MASTER_URI=http://![robot name].local:11311/  
$ rostopic list
```

You should see the following:

```
/diagnostics  
/![robot name]/camera_node/camera_info  
/![robot name]/camera_node/image/compressed  
/![robot name]/camera_node/image/raw  
/![robot name]/joy  
/![robot name]/wheels_driver_node/wheels_cmd  
/rosout  
/rosout_agg
```

## 20.6. Fourth window: visualize the image using `rviz`

Launch `rviz` by using these commands:

```
 $ source environment.sh  
$ source set_ros_master.sh ![robot name]  
$ rviz
```

\* For more information about `rviz`, see [Section 83.4](#).

In the `rviz` interface, click “Add” on the lower left, then the “By topic” tag, then select the “Image” topic by the name

```
/![robot name]/camera_node/image/compressed
```

Then click “ok”. You should be able to see a live stream of the image from the camera.

## 20.7. Proper shutdown procedure

To stop the nodes: You can stop the node by pressing `Ctrl-C` on the terminal where `roslaunch` was executed. In this case, you can use `Ctrl-C` in the terminal where you launched the `camera.launch`.

You should see the red light on the camera turn off in a few seconds.

Note that the `joystick.launch` is still up and running, so you can still drive the vehicle with the joystick.

# CHAPTER 21

## Interlude: Ergonomics

Assigned to: Andrea

So far, we have been spelling out all commands for you, to make sure that you understand what is going on.

Now, we will tell you about some shortcuts that you can use to save some time.

**Note:** in the future you will have to debug problems, and these problems might be harder to understand if you rely blindly on the shortcuts.

Results:

- You will know about some useful shortcuts.

### 21.1. set\_ros\_master.sh

Instead of using:

```
$ export ROS_MASTER_URI=http://![robot name].local:11311/
```

You can use the “set\_ros\_master.sh” script in the repo:

```
$ source set_ros_master.sh ![robot name]
```

Note that you need to use `source`; without that, it will not work.

### 21.2. SSH aliases

Instead of using

```
$ ssh ![username]@![robot name].local
```

You can set up SSH so that you can use:

```
$ ssh my-robot
```

To do this, create a host section in `~/.ssh/config` with the following contents:

```
Host my-robot
User ![username]
Hostname ![robot name].local
```

Here, you can choose any other string in place of “my-robot”.

Note that you **cannot** do

```
$ ping my-robot
```

You haven’t created another hostname, just an alias for SSH.

However, you can use the alias with all the tools that rely on SSH, including `rsync` and `scp`.

## CHAPTER 22

# Wheel calibration

| Assigned to: Andrea



# CHAPTER 23

## Camera calibration

## CHAPTER 24

# Taking a log

| Assigned to: Andrea



PART 4

**Operation manual - Duckietowns**

## CHAPTER 25

# Duckietown parts

| Assigned to: Jacopo



## CHAPTER 26

# Duckietown Assembly

| Assigned to: Shiying

## CHAPTER 27

# The Duckietown specification

| Assigned to: Liam?

### 27.1. Topology

1) Topology constraints

---

### 27.2. Signs placement

## CHAPTER 28

# Traffic lights

**PART 5****Operation manual - Duckiebot with LEDs**

## CHAPTER 29

### D17-1 (LEDs) parts

| Assigned to: Jacopo

## CHAPTER 30

### D17-1 (LEDs) assembly

| Assigned to: Shiying



## CHAPTER 31

### D17-1 (LEDs) setup

| Assigned to: Andrea

**PART 6**  
**Theory chapters**

These are the theory chapters.



## CHAPTER 32

# Chapter template

| Assigned to: Jacopo

## CHAPTER 33

# Linear algebra

| Assigned to: Jacopo



## CHAPTER 34

# Probability basics

| Assigned to: Liam?



## CHAPTER 35

# Dynamics

| Assigned to: Jacopo 

# CHAPTER 36

## Autonomy overview

| Assigned to: Liam

### 36.1. Perception, planning, control

## CHAPTER 37

# Autonomy architectures

| Assigned to: Andrea



# **CHAPTER 38**

## **Representations**

| Assigned to: Matt

## CHAPTER 39

# Software architectures and middlewares

| Assigned to: Andrea



# CHAPTER 40

## Modern signal processing

| Assigned to: Andrea



**CHAPTER 41**

**Basic Kinematics**

| Assigned to: Jacopo



## CHAPTER 42

# Basic Dynamics

| Assigned to: Jacopo

## CHAPTER 43

# Odometry Calibration

| Assigned to: Jacopo



## CHAPTER 44

# Computer vision basics

| Assigned to: Matt

## CHAPTER 45

# Illumination invariance

| Assigned to: Matt



## CHAPTER 46

# Line Detection

Assigned to: Matt

## CHAPTER 47

# Feature extraction

| Assigned to: Matt



## CHAPTER 48

# Place recognition

| Assigned to: Matt

**CHAPTER 49**  
**Filtering 1**

| Assigned to: Liam



## **CHAPTER 50**

# **Filtering 2**

| Assigned to: Liam

**CHAPTER 51**  
**Mission planning**

| Assigned to: ETH



## CHAPTER 52

# Planning in discrete domains

| Assigned to: ETH



CHAPTER 53

## Motion planning

| Assigned to: ETH



## **CHAPTER 54**

# **RRT**

| Assigned to: ETH

CHAPTER 55

## Feedback control

| Assigned to: Jacopo



## **CHAPTER 56**

# **PID Control**

| Assigned to: Jacopo



## CHAPTER 57

# MPC Control

| Assigned to: Jacopo



## CHAPTER 58

# Object detection

| Assigned to: Nick and David



**CHAPTER 59**

**Object classification**

| Assigned to: Nick and David



## CHAPTER 60

# Object tracking

| Assigned to: Nick and David



## CHAPTER 61

# Reacting to obstacles

| Assigned to: Jacopo



## CHAPTER 62

# Semantic segmentation

| Assigned to: Nick and David



## CHAPTER 63

### Text recognition

| Assigned to: Nick



## CHAPTER 64

# SLAM - Problem formulation

| Assigned to: Liam



**CHAPTER 65**

**SLAM - Broad categories**

| Assigned to: Liam



## **CHAPTER 66**

## **VINS**

| Assigned to: Liam

**CHAPTER 67**

**Advanced place recognition**

| Assigned to: Liam



# CHAPTER 68

## Fleet level planning (placeholder)

| Assigned to: ETH



**CHAPTER 69**

**Fleet level planning (placeholder)**

| Assigned to: ETH



# CHAPTER 70

## Bibliography

- [1] Jacopo Tani, Liam Paull, Maria Zuber, Daniela Rus, Jonathan How, John Leonard, and Andrea Censi. Duckietown: an innovative way to teach autonomy. In *EduRobotics 2016*. Athens, Greece, December 2016.  pdf
- [2] Liam Paull, Jacopo Tani, Heejin Ahn, Javier Alonso-Mora, Luca Carlone, Michal Cap, Yu Fan Chen, Changhyun Choi, Jeff Dusek, Daniel Hoehener, Shih-Yuan Liu, Michael Novitzky, Igor Franzoni Okuyama, Jason Pazis, Guy Rosman, Valerio Varricchio, Hsueh-Cheng Wang, Dmitry Yershov, Hang Zhao, Michael Benjamin, Christopher Carr, Maria Zuber, Sertac Karaman, Emilio Frazzoli, Domitilla Del Vecchio, Daniela Rus, Jonathan How, John Leonard, and Andrea Censi. Duckietown: an open, inexpensive and flexible platform for autonomy education and research. In *IEEE International Conference on Robotics and Automation (ICRA)*. Singapore, May 2017.  pdf
- [3] Tosini, G., Ferguson, I., Tsubota, K. *Effects of blue light on the circadian system and eye physiology*. Molecular Vision, 22, 61–72, 2016 (online).

## CHAPTER 71

# Exercises

These are the exercises.



## CHAPTER 72

# Line detection

## PART 7

# Software manuals

This part describes things that you should know about UNIX/Linux environments.

Please read the “background reading” section before you start, while the rest can be used as a reference.

Documentation writers: please make sure that every command used has a section in these chapters.

# CHAPTER 73

## Setup Github access

Assigned to: Andrea

This chapter describes how to create a Github account and setup SSH on the robot and on the laptop.

### 73.1. Create a Github account

Our example account is the following:

Github name: greta-p  
E-mail: greta-p@duckietown.com

Create a Github account ([Figure 23](#)).




Figure 23

Go to your inbox and verify the email.

### 73.2. Become a member of the Duckietown organization

Give the administrators your account name. They will invite you.

Accept the invitation to join the organization that you will find in your email.

### 73.3. Add a public key to Github

You will do this procedure twice: once for the public key created on the laptop, and later with the public key created on the robot.

Requires:

- A public/private keypair already created and configured.
  - This procedure is explained in [Section 77.5](#).

Result:

- You can access Github using the key provided.

Go to settings ([Figure 24](#)).




Figure 24

Add the public key that you created:



Figure 25

Figure 26

Figure 27

To check that all of this works, use the command

```
$ ssh -T git@github.com
```

The command tries to connect to Github using the private keys that you specified. This is the expected output:

```
Warning: Permanently added the RSA host key for IP address '![ip address]' to the list of known hosts.
Hi ![username]! You've successfully authenticated, but GitHub does not provide shell access.
```

If you don't see the greeting, stop.

Repeat what you just did for the Duckiebot on the laptop as well, making sure to change the name of the file containing the private key.

## CHAPTER 74

# Linux

Assigned to: Andrea

### 74.1. Background reading

- UNIX
- Linux
- free software; open source software.

### 74.2. Ubuntu packaging

1) apt install

---

2) apt update

---

3) apt dist-upgrade

---

### 74.3. Measuring resource usage

1) pgrep

---

2) Testing SD Card and disk speed

---

Test SD Card (or any disk) speed using the following commands, which write to a file called ![filename].

```
$ dd if=/dev/zero of=![filename] bs=500K count=1024  
$ sync  
$ echo 3 | sudo tee /proc/sys/vm/drop_caches  
$ dd if=![filename] of=/dev/null bs=500K count=1024  
$ rm ![filename]
```

Note the sync and the echo command are very important.

Example results:

```
524288000 bytes (524 MB, 500 MiB) copied, 30.2087 s, 17.4 MB/s  
524288000 bytes (524 MB, 500 MiB) copied, 23.3568 s, 22.4 MB/s
```

That is write 17.4 MB/s, read 22 MB/s.

### 3) Measuring CPU usage using htop

---

You can use htop to monitor CPU usage.

```
$ sudo apt install htop
```

### 4) Measuring I/O usage using iotop

---

```
$ sudo apt install iotop
```

## 74.4. How to burn an image to an SD card

Requires:

- A blank SD card.
- An image file to burn.
- An Ubuntu computer with an SD reader.

Results:

- A burned image.

### 1) Finding your device name for the SD card

---

First, find out what is the device name for the SD card.

Insert the SD Card in the slot.

Run the command:

```
$ sudo fdisk -l
```

Find your device name, by looking at the sizes.

For example, the output might contain:

```
Disk /dev/mmcblk0: 14.9 GiB, 15931539456 bytes, 31116288 sectors
Units: sectors of 1 * 512 = 512 bytes
Sector size (logical/physical): 512 bytes / 512 bytes
I/O size (minimum/optimal): 512 bytes / 512 bytes
```

In this case, the device is `/dev/mmcblk0`. That will be the `![device]` in the next commands.

You may see `/dev/mmcblk0px` or a couple of similar entries for each partition on the card, where `x` is the partition number. If you don't see anything like that, take out the SD card and run the command again and see what disappeared.

### 2) Unmount partitions

---

Before proceeding, unmount all partitions.

Run `df -h`. If there are partitions like `/dev/mmcblk0p![n]`, then unmount each of them. For example:

```
sudo umount /dev/mmcblk0p1
sudo umount /dev/mmcblk0p2
```

### 3) Burn the image

---

Now that you know that the device is ![device], you can burn the image to disk.

Let the image file be ![image file].

Burn the image using the command dd:



```
$ sudo dd of=![device] if=![image file] status=progress bs=4M
```

**Note:** Use the name of the device, without partitions. i.e., /dev/mmcblk0, not /dev/mmcblk0pX.

## CHAPTER 75

# Networking tools

Assigned to: Andrea

Preliminary reading:

- Basics of networking, including
  - what are IP addresses
  - what are subnets
  - how DNS works
  - how .local names work
  - ...

→ (ref to find).

Make sure that you know:

### 75.1. Visualizing information about the network

1) `ping`: are you there?

---

2) `ifconfig`

---

`$ ifconfig`

### 75.2. Wireless networks

1) `iwlist`

---

What wireless networks do I have around?

`$ sudo iwlist ![interface] scan | grep SSID`

Does the interface support 5 GHz channels?

`$ sudo iwlist ![interface] freq`

Example output:

```
wlx74da38c9caa0 20 channels in total; available frequencies :  
Channel 01 : 2.412 GHz  
Channel 02 : 2.417 GHz  
Channel 03 : 2.422 GHz  
Channel 04 : 2.427 GHz  
Channel 05 : 2.432 GHz  
Channel 06 : 2.437 GHz  
Channel 07 : 2.442 GHz  
Channel 08 : 2.447 GHz  
Channel 09 : 2.452 GHz  
Channel 10 : 2.457 GHz  
Channel 11 : 2.462 GHz  
Channel 36 : 5.18 GHz  
Channel 40 : 5.2 GHz  
Channel 44 : 5.22 GHz  
Channel 48 : 5.24 GHz  
Channel 149 : 5.745 GHz  
Channel 153 : 5.765 GHz  
Channel 157 : 5.785 GHz  
Channel 161 : 5.805 GHz  
Channel 165 : 5.825 GHz  
Current Frequency:2.437 GHz (Channel 6)
```

Note that in this example only *some* 5Ghz channels are supported (36, 40, 44, 48, 149, 153, 157, 161, 165); for example, channel 38, 42, 50 are not supported. This means that you need to set up the router not to use those channels.

## CHAPTER 76

# Compilers

| Assigned to: Andrea



# CHAPTER 77

## Accessing computers using SSH

Assigned to: Andrea

### 77.1. Background reading

- Encryption
- Public key authentication

### 77.2. Installation of SSH

This installs the client:

```
$ sudo apt install ssh
```

This installs the server:

This enables the server:

### 77.3. Local configuration

The SSH configuration as a client is in the file

```
~/.ssh/config
```

Create the directory with the right permissions:

```
$ mkdir ~/.ssh  
$ chmod 0700 ~/.ssh
```

Then add the following lines:

```
HostKeyAlgorithms ssh-rsa
```

The reason is that Paramiko, used by roslaunch, [does not support the ECDSA keys](#).

### 77.4. How to login with SSH and a password

To log in to a remote computer ![remote] with user ![remote-user], use:

```
$ ssh ![remote-user]@[!][remote]
```

#### 1) Troubleshooting

Symptom: “Offending key error”.

If you get something like this:

```
Warning: the ECDSA host key for ![...] differs from the key for the IP address '! [...] '
Offending key for IP in /home/![user]/.ssh/known_hosts:! [line]
```

then remove line ! [line] in ~/.ssh/known\_hosts.

## 77.5. Creating an SSH keypair

This is a step that you will repeat twice: once on the Duckiebot, and once on your laptop.

The program will prompt you for the filename on which to save the file.

Use the convention

```
/home/![username]/.ssh/![username]@! [host name]
/home/![username]/.ssh/![username]@! [host name].pub
```

where:

- ! [username] is the current user name that you are using (ubuntu or your chosen one);
- ! [host name] is the name of the host (the Duckiebot or laptop);

An SSH key can be generated with the command:

```
$ ssh-keygen -h
```

The session output will look something like this:

```
Generating public/private rsa key pair.
Enter file in which to save the key (/home/![username]/.ssh/id_rsa):
```

At this point, tell it to choose this file:

```
/home/![username]/.ssh/![username]@! [host name]
```

Then:

```
Enter passphrase (empty for no passphrase):
```

Press enter; you want an empty passphrase.

```
Enter same passphrase again:
```

Press enter.

```
Your identification has been saved in /home/![username]/.ssh/![username]@![host name]
Your public key has been saved in /home/![username]/.ssh/![username]@![host name].pub
The key fingerprint is:
![:XX:XX:XX:XX:XX:XX:XX:XX:XX:XX:XX:XX:XX:XX:XX] !:[username]@![host name]
The key's randomart image is:
+--[ RSA 2048]----+
|          .   |
|         o o . |
|        o = o . o |
|       B . . * o |
|       S o     0 |
|       o o   . E |
|       o o o   |
|       o +   |
|       ...  |
+-----+
```

Note that the program created two files.

The file that contains the private key is

```
/home/![username]/.ssh/![username]@![host name]
```

The file that contains the public key has extension .pub:

```
/home/![username]/.ssh/![username]@![host name].pub
```

Next, tell SSH that you want to use this key.

Make sure that the file ~/.ssh/config exists:

```
$ touch ~/.ssh/config
```

Add a line containing

```
IdentityFile ![PRIVATE_KEY_FILE]
```

(using the filename for the private key).

Check that the config file is correct:

```
$ cat ~/.ssh/config
!...
IdentityFile ![PRIVATE_KEY_FILE]
!...
```

## 77.6. How to login without a password

Assumptions:

- You have two computers, called “[local]” and “[remote]”, with users “[local-user]” and “[remote-user]”.
- The two computers are on the same network.
- You have created a keypair for “[local-user]” on “[local]”.

→ This procedure is described in [Section 77.5](#).

Results:

- From the “[local]” computer, “[local-user]” will be able to log in to “[remote]” com-

puter without a password.

First, connect the two computers to the same network, and make sure that you can ping ![remote] from ![local]:

```
![local] $ ping ![remote].local
```

Do not continue if you cannot do this successfully.

If you have created a keypair for ![local-user], you will have a public key in this file on the ![local] computer:

```
/home/![local-user]/.ssh/![local-user]@![local].pub
```

This file is in the form:

```
ssh-rsa ![long list of letters and numbers] ![local-user]@![local]
```

You will have to copy the contents of this file on the ![remote] computer, to tell it that this key is authorized.

On the ![remote] computer, edit or create the file:

```
/home/![remote-user]/.ssh/authorized_keys
```

and add the entire line as above containing the public key.

Now, from the ![local] computer, try to log in into the ![remote] one:

```
![local] $ ssh ![remote-user]@![remote]
```

This should succeed, and you should not be asked for a password.

## 77.7. Fixing SSH Permissions

Sometimes, SSH does not work because you have the wrong permissions on some files.

In doubt, these lines fix the permissions for your .ssh directory.

```
$ chmod 0700 ~/.ssh  
$ chmod 0700 ~/.ssh/*
```

## 77.8. SCP

1) Download a file with SCP

---

## 77.9. RSync

# CHAPTER 78

## Editors

Assigned to: Andrea

### 78.1. VIM

To do quick changes to files, especially when logged remotely, we suggest you use the VI editor, or more precisely, VIM (“VI iMproved”).

→ [A VIM tutorial.](#)

#### 1) Installation

---

Install like this:

```
$ sudo apt install vim
```

#### 2) Suggested configuration

---

Suggested `~/.vimrc`:

```
syntax on
set number
filetype plugin indent on
highlight Comment ctermfg=Gray
autocmd FileType python set complete isk+=.,(
```

#### 3) Visual mode

---

#### 4) Indenting using VIM

---

Use the `>` command to indent.

To indent 5 lines, use `5 > >`.

To mark a block of lines and indent it, use `V >`.

For example, use `V J J >` to indent 3 lines.

Use `<` to dedent.

### 78.2. Atom

### 78.3. Eclipse

## CHAPTER 79

# Source code control with Git

Assigned to: Andrea

### 79.1. Background reading

- Git
- GitFlow

### 79.2. Installation

The basic Git program is installed using

```
$ sudo apt install git
```

Additional utilities for git are installed using:

```
$ sudo apt install git-extras
```

This include the `git-ignore` utility.

### 79.3. Setting up global configurations for Git

This should be done twice, once on the laptop, and later, on the robot.

These options tell Git who you are:

```
$ git config --global user.email "[email]"  
$ git config --global user.name "[full name]"
```

Also do this, and it doesn't matter if you don't know what it is:

```
$ git config --global push.default simple
```

### 79.4. Git tips

#### 1) Shallow clone

---

You can clone without history with the command:

```
$ git clone --depth 1 ![repository URL]
```

### 79.5. Git troubleshooting

---

### 1) Problem 1: https instead of ssh:

The symptom is:

```
$ git push  
Username for 'https://github.com':
```

Diagnosis: the `remote` is not correct.

If you do `git remote` you get entries with `https`:

```
$ git remote -v  
origin  https://github.com/duckietown/Software.git (fetch)  
origin  https://github.com/duckietown/Software.git (push)
```

Expectation:

```
$ git remote -v  
origin  git@github.com:duckietown/Software.git (fetch)  
origin  git@github.com:duckietown/Software.git (push)
```

Solution:

```
$ git remote remove origin  
$ git remote add origin git@github.com:duckietown/Software.git
```

---

### 2) Problem 1: `git push` complains about upstream

The symptom is:

```
fatal: The current branch ![branch name] has no upstream branch.
```

Solution:

```
$ git push --set-upstream origin ![branch name]
```

## CHAPTER 80

# Shells

Assigned to: Andrea

### 80.1. Byobu

You need to learn to use Byobu. It will save you much time later.

\* See the screencast on the website <http://byobu.co/>.

---

#### 1) Advantages of using Byobu

---

#### 2) Installation

On Ubuntu, install using:

```
$ sudo apt install byobu
```

---

#### 3) Quick command reference

You can change the escape sequence from **[Ctrl]-[A]** to something else by using the configuration tool that appears when you type **[F9]**.

Commands to use windows:

**TABLE 1. WINDOWS**

|                   | Using function keys | Using escape sequences          |
|-------------------|---------------------|---------------------------------|
| Create new window | <b>F2</b>           | <b>[Ctrl]-[A]</b> then <b>C</b> |
| Previous window   | <b>F3</b>           |                                 |
| Next window       | <b>F4</b>           |                                 |
| Switch to window  |                     | <b>[Ctrl]-[A]</b> then a number |
| Close window      | <b>F6</b>           | <b>[Ctrl]-[A]</b> then <b>Q</b> |
| Rename window     |                     | <b>[Ctrl]-[A]</b> then <b>R</b> |

Commands to use panes (windows split in two or more):

**TABLE 1. COMMANDS FOR PANES**

|                          | Using function keys | Using escape sequences                     |
|--------------------------|---------------------|--|
| Split horizontally       | <b>Shift-[F2]</b>   | <b>[Ctrl]-[A]</b> then <b>I</b>            |
| Split vertically         | <b>Ctrl-[F2]</b>    | <b>[Ctrl]-[A]</b> then <b>%</b>            |
| Switch focus among panes | <b>Ctrl-[↑↓↔]</b>   | <b>[Ctrl]-[A]</b> then one of <b>[↑↓↔]</b> |
| Break pane               |                     | <b>[Ctrl]-[A]</b> then <b>I</b>            |

Other commands:

**TABLE 1. OTHER**

|        | Using function keys | Using escape sequences          |
|--------|---------------------|---------------------------------|
| Help   |                     | <b>[Ctrl]-[A]</b> then <b>?</b> |
| Detach |                     | <b>[Ctrl]-[A]</b> then <b>D</b> |

#### 4) OS X

---

Scroll up and down using `[fn] [option] ↑` and `[fn] [option] ↓`.

Highlight using `[alt]`.

#### 5) Alternatives

---

[GNU Screen](#) is fine as well.

## CHAPTER 81

### Other things to know

| Assigned to: Andrea

#### 81.1. Markdown

## PART 8

# Software development guide

This part is about how to develop software for the Duckiebot.

## CHAPTER 82

# Python

### 82.1. Background reading

- Python
- Python tutorial

### 82.2. Python virtual environments

Install using:

```
$ sudo apt install virtualenv
```

### 82.3. Useful libraries

```
matplotlib  
seaborn  
numpy  
panda  
scipy  
opencv  
...
```

# CHAPTER 83

## Introduction to ROS

Assigned to: Liam

### 83.1. Install ROS

This part installs ROS. You will run this twice, once on the laptop, once on the robot. The first commands are copied from [this page](#).

Tell Ubuntu where to find ROS:

```
$ sudo sh -c 'echo "deb http://packages.ros.org/ros/ubuntu $(lsb_release -sc) main" > /etc/apt/sources.list.d/ros-latest.list'
```

Tell Ubuntu that you trust the ROS people (they are nice folks):

```
$ sudo apt-key adv --keyserver hkp://ha.pool.sks-keyservers.net:80 --recv-key 421C365BD9FF1F717815A3895523BAEEB01FA116
```

Fetch the ROS repo:

```
$ sudo apt update
```

Now install the mega-package `ros-kinetic-desktop-full`.

```
$ sudo apt install ros-kinetic-desktop-full
```

There's more to install:

```
$ sudo apt install  
ros-kinetic-{tf-conversions,cv-bridge,image-transport,camera-info-manager,thor-audio-transport,joy,image-
```

**Note:** Do not install packages by the name of `ros-X`, only those by the name of `ros-kinetic-X`. The packages `ros-X` are from another version of ROS.

: not done in aug20 image:

Initialize ROS:

```
$ sudo rosdep init  
$ rosdep update
```

### 83.2. `rqt_console`

### 83.3. `roslaunch`

### 83.4. `rviz`

### 83.5. rostopic

1) rostopic hz

---

2) rostopic echo

---

3) catkin\_make

---

4) Troubleshooting

---

**Symptom:** ! [computer] is not in your SSH known\_hosts file

See [this thread](#). Remove the known\_hosts file and make sure you have followed the instructions in [Section 77.3](#).

## CHAPTER 84

# What the duck!

`what-the-duck` is a program that tests *dozens* of configuration inconsistencies that can happen on a Duckiebot.

To use it, first compile the repository, and then run:

```
$ ./what-the-duck
```

### 84.1. Adding more tests to `what-the-duck`

The idea is to add to `what-the-duck` all the tests that can be automated.

The documentation about to do that is not ready yet.

The current tests are available in the file:

```
./catkin_ws/src/f23-LED/led_detection/include/what_the_duck/list_of_checks.py
```

### 84.2. Tests already added

Here's the list of tests already added:

```
✓ Camera is detected
✓ Scipy is installed
✓ sklearn is installed
✓ Date is set correctly
✓ Not running as root
✓ Not running as ubuntu
✓ Member of group sudo
✓ Member of group input
✓ Member of group video
✓ Member of group i2c
✓ ~/.ssh exists
✓ ~/.ssh permissions
✓ ~/.ssh/config exists
✓ SSH option HostKeyAlgorithms is set
✓ At least one key is configured.
✓ ~/.ssh/authorized_keys exists
✓ Git configured
✓ Git email set
✓ Git name set
✓ Git push policy set
✓ Edimax detected
✓ The hostname is configured
✓ /etc/hosts is sane
✓ Correct kernel version
✓ Messages are compiled
✓ Shell is bash
✓ Working internet connection
✓ Github configured
✓ Joystick detected
✓ Environment variable DUCKIETOWN_ROOT
✓ ${DUCKIETOWN_ROOT} exists
✓ Wifi network configured
```

### 84.3. List of tests to add

Please add below any configuration test that can be automated:

- Check that all the `rosX` command resolve to a file `/opt/ros/kinetic/bin/rosX`.
- Make sure that packages such as `python-roslaunch` are not installed. (The user is invited to install it when `roslaunch` is not found!)
- Repository remote is not `https`.
- Editor is set to `vim`.
- They put the right MAC address in the network configuration

# CHAPTER 85

## How to create a ROS package

### 85.1. Conforming ROS package checklist

- The name of the package is package\_! [handle]
- The directory is in ...
- The messages are called ....
- there is a readme file
- there is the first launch file

**CHAPTER 86**

**Integrate package in the architecture**

## CHAPTER 87

# Creating unit tests

## PART 9

# Fall 2017

This is the first time that a class is taught jointly across 3 continents!

There are 4 universities involved in the joint teaching for the term:

- ETH Zürich (ETHZ), with instructors Emilio Frazzoli, Andrea Censi, Jacopo Tani.
- University of Montreal (UdeM), with instructor Liam Paull.
- TTI Chicago (TTI), with instructor Matthew Walter.
- National C T University (NCTU), with instructor Nick Wang.

This part of the Duckiebook describes all the information that is needed by the students of the four institutions.

## CHAPTER 88

# General remarks

Assigned to: Andrea

### 88.1. The rules of Duckietown

#### The first rule of Duckietown

The first rule of Duckietown is: you don't talk about Duckietown, *using email*.

Instead, we use a communication platform called Slack.

There is one exception: inquiries about "meta" level issues, such as course enrollment and other official bureaucratic issues can be communicated via email.

#### The second rule of Duckietown

The second rule of Duckietown is: be kind and respectful, and have fun.

#### The third rule of Duckietown

The third rule of Duckietown is: read the instructions carefully.

Do not blindly copy and paste.

Only run a command if you know what it does.

### 88.2. Synchronization between classes

At ETHZ, UdeM, TTIC, the class will be more-or-less synchronized. The materials are the same; there is some slight variation in the ordering.

Moreover, there will be some common groups for the projects.

The NCTU class is undergraduate level. Students will learn slightly simplified materials. They will not collaborate directly with the classes.

### 88.3. Accounts for students

To participate in Duckietown, students must use two accounts: Slack and Github.

#### 1) Slack

---

You need a Slack account, for team discussion and organization.

#### 2) Github

- 
- A Github account;
  - Membership in the Duckietown organization.

### 88.4. Accounts for all instructors and TAs

As an instructor/TA for the Fall 2017 class, in addition to the accounts above, these are two more accounts that you need.

---

**1) Twist**

Twist is used for class organization (such as TAs, logistics);

TODO:

---

**2) Google docs**

Google Docs is used to maintain TODOs and other coordination materials.

In particular:

- This is the schedule: XXX
- This is the calendar in which to annotate everything: XXX

# CHAPTER 89

## Additional information for ETH Zürich students

Assigned to: Andrea

This section describes information specific for ETH Zürich students.

### 1) Website

---

All really important information, such as deadlines, is in the authoritative website:

### 2) Duckiebox distribution

---

### 3) Lab access

---

### 4) The local TAs

---

**CHAPTER 90****Additional information for UdeM students**

| Assigned to: Liam



## CHAPTER 91

# Additional information for TTIC students

| Assigned to: Matt

## CHAPTER 92

### Additional information for NCTU students

| Assigned to: Nick



CHAPTER 93

## Milestone: ROS node working

**CHAPTER 94**

**Homework: Take and process a log**

CHAPTER 95

Milestone: Calibrated robot

**CHAPTER 96**  
**Homework: Camera geometry**

CHAPTER 97

Milestone: Illumination invariance

CHAPTER 98

## Homework: Place recognition

CHAPTER 99

Milestone: Lane following

CHAPTER 100  
Homework: localization



CHAPTER 101

Milestone: Navigation

**CHAPTER 102****Homework: group forming**

CHAPTER 103

**Milestone: Ducks in a row**

CHAPTER 104

## Homework: Comparison of PID

CHAPTER 105  
**Homework: RRT**

CHAPTER 106  
Caffe tutorial

CHAPTER 107

Milestone: Object Detection

CHAPTER 108  
Homework: Object Detection

CHAPTER 109  
Milestone: Semantic perception

**CHAPTER 110****Homework: Semantic perception**

CHAPTER 111

Milestone: Reacting to obstacles

**CHAPTER 112****Homework: Reacting to obstacles**

CHAPTER 113  
**Milestone: SLAM demo**

CHAPTER 114  
Homework: SLAM

CHAPTER 115

**Milestone: fleet demo**

CHAPTER 116  
Homework: fleet

CHAPTER 117

Project proposals

## CHAPTER 118

# Template of a project

### 118.1. Checklist for students

- Have a Github account. See [Chapter 73](#). See name conventions (TODO).
- Be part of the Duckietown Github organization. You are sure only when you commit and push one change to one of our repositories.
- Be part of the Duckietown Slack. See name conventions (TODO).

### 118.2. Checklist for TAs

- Be signed up on

PART 10

Drafts or pieces to remove

## CHAPTER 119

# Laptop setup

### 119.1. Setup passwordless SSH to log in using the `ubuntu` user

On each Duckiebot it is possible to log in as the `ubuntu` user using a common key.

Now, let's set up passwordless SSH, so that you don't need to type a password.

On the laptop, create the `.ssh` directory:

```
 $ mkdir -p ~/.ssh
```

The key `duckietown_key1` is found at the URL:

```
https://www.dropbox.com/s/q23qptu01u7ur3y/duckietown_key1?dl=1
```

Download the file and call it `~/ssh/duckietown_key1`

```
 $ curl -o ~/ssh/duckietown_key1 ![URL above]
```

Edit the permission of the file. SSH wants the key file to be not readable or writable from other users or groups.

```
 $ chmod 600 ~/ssh/duckietown_key1
```

Regenerate the public key according to:

```
 $ ssh-keygen -f ~/ssh/duckietown_key1 -y > ~/ssh/duckietown_key1.pub
```

On the laptop, now edit `~/.ssh/config` and add the following lines:

```
Host ![robot name]
  Hostname ![robot name].local
  User ![user name]
  IdentityFile ~/ssh/duckietown_key1
  HostKeyAlgorithms ssh-rsa
```

Now you should be able to connect without using a password.

The following command should connect without a password being asked:

```
 $ ssh ubuntu@[robot name]
```

#### 1) Troubleshooting

---

**Symptom:** “Scheme missing”

**Resolution:** If there are issues such as “scheme missing” and the file `duckietown_key1` does not exist in the `~/.ssh/` folder, but instead downloaded a file named `duckietown_key1?dl=1` in the current folder, simply rename `duckietown_key1?dl=1` to `duckietown_key1` and copy it over to the directory `~/.ssh/`.

Page left blank