

# **Syscheck**

## **Mysql replication for redundancy and fail over**

Henrik Andreasson

[kinneh@users.sourceforge.net](mailto:kinneh@users.sourceforge.net)

2010-11-09

Version 1.3

## **Table of Contents**

1 System preparation for database replication .....	3
1.1 Prerequisites .....	3
1.2 Configure master- and slave-hosts ipaddresses.....	3
1.3 Copy config from node1 to node2 .....	3
1.4 Configure database users and ipaddresses for nodes.....	4
1.5 Create mysql-user access rules on node1.....	4
1.6 Create mysql-user access rules on node2.....	5
1.7 Create mysql-replication-user on node1.....	6
1.8 Create an empty db on node2 .....	6
1.9 Configure mysql server for replication on node1.....	7
1.10 Configure mysql server for replication on node2.....	7
1.11 Configure the virtual IP.....	8
2 Production interrupting steps to sync db from node1 to node2.....	10
2.1 Stop jboss application server.....	10

2.2 Restart mysql server to make replication options take effect.....	10
2.3 Lock the database .....	11
2.4 Make a database backup .....	11
2.5 Transfer the database-backup to node2 .....	12
2.6 Restore mysql database on node2 .....	12
2.7 Make node1 master .....	12
2.8 Make node 2 slave .....	13
2.9 Unlock master database tables .....	14
2.10 Verify replication .....	14
2.11 Write to the test table and verify both servers answers the same number .....	16
2.12 Change datasource config in jboss.....	16
2.13 Start Jboss application server .....	17
2.14 Activate CA:s.....	17
3 Fail over and fail back .....	17
3.1 Fail over, make the slave master .....	17
3.2 Fail-back, make the old master master again .....	20
4 Verification and Troubleshooting .....	27
4.1 Check the log file: .....	27
4.2 Write to the test table and verify both servers answers the same number .....	27
4.3 Use the show master and show slave scripts .....	28

# 1 System preparation for database replication

## 1.1 Prerequisites

Master node must be installed and running.

## 1.2 Configure master- and slave-hosts ipaddresses

Set THIS\_NODE to NODE1(master) or NODE2(slave) and IP-addresses to node1 and node2  
#IP address or hostname to primary and secondary cluster nodes.

```
THIS_NODE=NODE1

# master node

HOSTNAME_NODE1=192.168.31.140

# slave node

HOSTNAME_NODE2=192.168.31.142
```

## 1.3 Copy config from node1 to node2

Run the backup of key config and keystore files

*Optionally configure extra files to be copied:*

```
username@smartcard20-node1:/usr/local/syscheck/> sudo vi config/921.conf
```

on node1 run:

```
root@smartcard20-node1:/usr/local/syscheck/related-enabled # ./921_copy_htmf_conf.sh -s
```

Screenonly output:

```
Copying file: /usr/local/certificate-services/htmf/hardtokenmgmt.properties to:localhost dir:/tmp/backup_htmf_conf/
remotreuser:jboss sshkey: /home/jboss/.ssh/id_rsa
```

Screenonly output:

```
Copying file: /usr/local/certificate-services/htmf/autogenerated_hardtokenmgmt.properties to:localhost
dir:/tmp/backup_htmf_conf/ remotreuser:jboss sshkey: /home/jboss/.ssh/id_rsa
```

Screenonly output:

```
Copying file: /usr/local/certificate-services/htmf/src/resources/globalsettings/global.properties to:localhost
dir:/tmp/backup_htmf_conf/ remotreuser:jboss sshkey: /home/jboss/.ssh/id_rsa
```

Screenonly output:

```
Copying file: /usr/local/certificate-services/htmf/jarsigner.jks to:localhost dir:/tmp/backup_htmf_conf/ remotreuser:jboss sshkey:
```

```
/home/jboss/.ssh/id_rsa
```

Screenonly output:

```
Copying file: /usr/local/certificate-services/ejbca/conf/ejbca.properties to:localhost dir:/tmp/backup_htmf_conf/ remotreuser:jboss  
sshkey: /home/jboss/.ssh/id_rsa
```

Screenonly output:

```
Copying file: /usr/local/certificate-services/ejbca/conf/database.properties to:localhost dir:/tmp/backup_htmf_conf/  
remotreuser:jboss sshkey: /home/jboss/.ssh/id_rsa
```

Screenonly output:

```
Copying file: /usr/local/certificate-services/jboss/server/default/conf/keystore/keystore.jks to:localhost dir:/tmp/backup_htmf_conf/  
remotreuser:jboss sshkey: /home/jboss/.ssh/id_rsa
```

Screenonly output:

```
Copying file: /usr/local/certificate-services/jboss/server/default/conf/keystore/truststore.jks to:localhost  
dir:/tmp/backup_htmf_conf/ remotreuser:jboss sshkey: /home/jboss/.ssh/id_rsa
```

Screenonly output:

```
Copying file: /usr/local/certificate-services/jboss/server/default/deploy/jboss-web.deployer/server.xml  
to:localhost dir:/tmp/backup_htmf_conf/ remotreuser:jboss sshkey: /home/jboss/.ssh/id_rsa
```

## ***1.4 Configure database users and ipaddresses for nodes***

Verify that the database name, username, and password to access the database is correct

```
smartcard20-node1:/usr/local/syscheck # vi config/common.conf (was resources.sh )
```

```
DB_NAME=ejbca
```

```
DB_USER=ejbca
```

```
DB_PASSWORD="foo123"
```

Enter new information about replication user into syscheck config/common.sh (you need to make up the username and password, the scripts later on will create the user based on that information)

```
# Database replication user and password
```

```
DBREP_USER=ejbcarep
```

```
DBREP_PASSWORD="foo123"
```

## ***1.5 Create mysql-user access rules on node1***

on node1 run:

```
smartcard20-node1:/usr/local/syscheck/database-replication # ./802-create-mysql-ejbca-user-db-user.sh
```

Will now insert these sql:

```
GRANT ALL ON ejbca.* to 'ejbca'@'10.1.1.10' IDENTIFIED BY 'foo123';
```

```
GRANT ALL ON ejbca.* to 'ejbca'@'10.1.1.11' IDENTIFIED BY 'foo123';
```

```
GRANT ALL ON ejbca.* to 'ejbca'@'10.1.1.12' IDENTIFIED BY 'foo123';
```

```
select * from user where user like '%ejbca%'
```

```
Host User Password Select_priv Insert_priv Update_priv Delete_priv Create_priv Drop_priv Reload_priv Shutdown_priv
Process_priv File_priv Grant_priv References_priv Index_priv Alter_priv Show_db_priv Super_priv Create_tmp_table_priv
Lock_tables_priv Execute_priv Repl_slave_priv Repl_client_priv Create_view_priv Show_view_priv Create_routine_priv
Alter_routine_priv Create_user_priv ssl_type ssl_cipher x509_issuer x509_subject max_questions max_updates max_connections
max_user_connections
```

```
10.1.1.10 ejbca *1618E643E43E4921AC458E23C5E7728892CCF1A6 N N N N N N N N N N N N N N N N N N N N N N N N N N
N N 0 0 0 0
```

```
10.1.1.11 ejbca *1618E643E43E4921AC458E23C5E7728892CCF1A6 N N N N N N N N N N N N N N N N N N N N N N N N N N
N N 0 0 0 0
```

```
localhost ejbca *77805DB3940553564EF23E5EB2231A1BEB02EFC3 N N N N N N N N N N N N N N N N N N N N N N N N N N
N N 0 0 0 0
```

```
10.1.1.12 ejbca *1618E643E43E4921AC458E23C5E7728892CCF1A6 N N N N N N N N N N N N N N N N N N N N N N N N N N
N N 0 0 0 0
```

```
I-8021-PKI 20090311 15:57:53 smartcard20-node1: INFO - access rules inserted into mysql db ok
```

## 1.6 Create mysql-user access rules on node2

on node2 run:

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./802-create-mysql-ejbca-user-db-user.sh
```

Will now insert these sql:

```
GRANT ALL ON ejbca.* to 'ejbca'@'10.1.1.10' IDENTIFIED BY 'foo123';
```

```
GRANT ALL ON ejbca.* to 'ejbca'@'10.1.1.11' IDENTIFIED BY 'foo123';
```

```
GRANT ALL ON ejbca.* to 'ejbca'@'10.1.1.12' IDENTIFIED BY 'foo123';
```

```
select * from user where user like '%ejbca%'
```

```
Host User Password Select_priv Insert_priv Update_priv Delete_priv Create_priv Drop_priv Reload_priv Shutdown_priv
Process_priv File_priv Grant_priv References_priv Index_priv Alter_priv Show_db_priv Super_priv Create_tmp_table_priv
Lock_tables_priv Execute_priv Repl_slave_priv Repl_client_priv Create_view_priv Show_view_priv Create_routine_priv
Alter_routine_priv Create_user_priv ssl_type ssl_cipher x509_issuer x509_subject max_questions max_updates max_connections
max_user_connections
```

```
10.1.1.10 ejbca *1618E643E43E4921AC458E23C5E7728892CCF1A6 N N N N N N N N N N N N N N N N N N N N N N N N N N
N N 0 0 0 0
```

```
10.1.1.11 ejbca *1618E643E43E4921AC458E23C5E7728892CCF1A6 N N N N N N N N N N N N N N N N N N N N N N N N N N
```

```
N N O O O O  
  
localhost ejbca *77805DB3940553564EF23E5EB2231A1BEB02EFC3 N N N N N N N N N N N N N N N N N N N N N N N N  
N N O O O O  
  
10.1.1.12 ejbca *1618E643E43E4921AC458E23C5E7728892CCF1A6 N N N N N N N N N N N N N N N N N N N N N N N N  
N N O O O O  
  
I-8021-PKI 20090311 15:57:53 smartcard20-node1: INFO - access rules inserted into mysql db ok
```

*on node1 run:*

```
Host User Password Select_priv Insert_priv Update_priv Delete_priv Create_priv Drop_priv Reload_priv Shutdown_priv
Process_priv File_priv Grant_priv References_priv Index_priv Alter_priv Show_db_priv Super_priv Create_tmp_table_priv
Lock_tables_priv Execute_priv Repl_slave_priv Repl_client_priv Create_view_priv Show_view_priv Create_routine_priv
Alter_routine_priv Create_user_priv ssl_type ssl_cipher x509_issuer x509_subject max_questions max_updates max_connections
max_user_connections

10.1.1.10 ejbcarep *1618E643E43E4921AC458E23C5E7728892CCF1A6 N N N N N N N N N N N N N N N N N N Y N N N
N N N 0 0 0 0

10.1.1.11 ejbcarep *1618E643E43E4921AC458E23C5E7728892CCF1A6 N N N N N N N N N N N N N N N N N N Y N N N
N N N 0 0 0 0

I-8031-PKI 20090311 15:57:58 smartcard20-node1: INFO - Replication access rules inserted into mysql db ok
```

- If you got a db (from a previous install/testrun) do drop it then create a empty ejbca db!
- If yo dont got a db, ie this is a clean install, you can skip this step, and goto the creation of the empty db.
- If you are uncertain if there is a db, there is no harm in trying to do this step, it will tell you there was nothing to drop!

```
username@smartcard20-node2:/usr/local/syscheck/database-replication> ./801-drop-existing-ejbca-db.sh
```

are you really sure you want to drop and replace the ejbca db on this host?

enter 'im-really-sure' (without the '-') to continue or ctrl-c to abort

**im really sure**

```
I-9041-PKI 20090309 14:44:11 smartcard20-node1: INFO - Backed up db ok (file:/backup/mysql/ejbca/backup-2009-03-09_14.44.10.sql.gz)
```

Dropping the database is potentially a very bad thing to do.

Any data stored in the database will be destroyed.

Do you really want to drop the 'ejbca' database [y/N] **y**

Database "ejbca" dropped

```
I-8011-PKI 20090309 14:44:13 smartcard20-node1: INFO - Dropped the db ok
```

## **And create an empty one:**

*on node2 run:*

```
username@smartcard20-node2:/usr/local/syscheck/database-replication> sudo ./800-create-mysql-ejbca-db.sh
```

```
I-8001-PKI 20090309 14:44:18 smartcard20-node2: INFO - Created the db ok
```

## ***1.9 Configure mysql server for replication on node1***

Edit /etc/my.cnf and set the following options:

*on node1 edit:*

```
# Replication Master Server (default)

# binary logging is required for replication

log-bin=mysql-bin

# required unique id between 1 and 2^32 - 1

# defaults to 1 if master-host is not set

# but will not function as a master if omitted

server-id = 1
```

## ***1.10 Configure mysql server for replication on node2***

Edit /etc/my.cnf and set the following options:

*on node2 edit:*

```
# Replication Master Server (default)

# binary logging is required for replication
```

```
log-bin=mysql-bin
```

But do set server-id = 2

```
# required unique id between 1 and 2^32 - 1
```

```
# defaults to 1 if master-host is not set
```

```
# but will not function as a master if omitted
```

```
server-id = 2
```

## **1.11 Configure the virtual IP**

Verify the VIP configuration in config/common.conf

Check the interface name of the host:s ipaddress

```
# ifconfig
```

```
eth0 Link encap:Ethernet HWaddr 00:0c:29:c2:1d:f9
```

```
inet addr:192.168.31.146 Bcast:192.168.31.255 Mask:255.255.255.0
```

```
inet6 addr: fe80::20c:29ff:fec2:1df9/64 Scope:Link
```

```
UP BROADCAST RUNNING MULTICAST MTU:1500 Metric:1
```

```
RX packets:39796 errors:0 dropped:0 overruns:0 frame:0
```

```
TX packets:58761 errors:0 dropped:0 overruns:0 carrier:0
```

```
collisions:0 txqueuelen:1000
```

```
RX bytes:2834743 (2.7 MiB) TX bytes:41442017 (39.5 MiB)
```

```
Interrupt:19 Base address:0x2000
```

Verify the interface set in config/common.conf

```
IF_VIRTUAL="eth0:0"
```

test the activate / deactivate scripts

remove VIP from node1

```
smartcard20-node1:/usr/local/syscheck/related-enabled# ./912_deactivate_VIP.sh -s
```

```
I-9123-PKI 20100615 17:42:05 smartcard20-node1: INFO - While deactivating, the VIP was already NOT active on this host
```

Activate VIP on node1 again

```
smartcard20-node1:/usr/local/certificate-services/syscheck/related-enabled# ./911_activate_VIP.sh -s
```



Check if the VIP is configured that the alias interface is showing up (eth0:0) and has the correct ip, if the VIP should NOT be activated, the interface shall not be shown in ifconfig.

```
# ifconfig
```

```
eth0    Link encap:Ethernet  HWaddr 00:0c:29:c2:1d:f9

        inet addr:192.168.31.146  Bcast:192.168.31.255  Mask:255.255.255.0

        inet6 addr: fe80::20c:29ff:fec2:1df9/64 Scope:Link

        UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1

        RX packets:39796 errors:0 dropped:0 overruns:0 frame:0

        TX packets:58761 errors:0 dropped:0 overruns:0 carrier:0

        collisions:0 txqueuelen:1000

        RX bytes:2834743 (2.7 MiB)  TX bytes:41442017 (39.5 MiB)

        Interrupt:19 Base address:0x2000
```

```
eth0:0  Link encap:Ethernet  HWaddr 00:0c:29:c2:1d:f9

        inet addr:192.168.0.10  Bcast:192.168.0.255  Mask:255.255.255.0

        UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1

        Interrupt:19 Base address:0x2000
```

## 2 Production interrupting steps to sync db from node1 to node2

### 2.1 Stop jboss application server

**NOTE:** from this step the service is unavailable!

Stop jboss on node1 and node2

on node1 run:

```
smartcard20-node1:/usr/local/certificate-services/syscheck/related-enabled# /etc/init.d/jboss stop
```

```
Stopping JBoss: ..... done
```

on node2 run:

```
smartcard20-node2:/usr/local/certificate-services/syscheck/related-enabled# /etc/init.d/jboss stop
```

```
Stopping JBoss: .....done
```

### 2.2 Restart mysql server to make replication options take effect

**NOTE:** this step is only needed if changes has been done to configuration of mysql-server (/etc/my.cnf)

Restart mysql on both nodes

on node1 run:

```
smartcard20-node1:/usr/local/syscheck/database-replication # /etc/init.d/mysql restart
```

```
Restarting service MySQL
```

```
Shutting down service MySQL done
```

```
Starting service MySQL done
```

on node2 run:

```
smartcard20-node1:/usr/local/syscheck/database-replication # /etc/init.d/mysql restart
```

```
Restarting service MySQL
```

```
Shutting down service MySQL done
```

```
Starting service MySQL done
```

## 2.3 Lock the database

Now we lock the tables from writes, read statements will still work.

**NOTE: This console will be occupied with this command until the steps below are done so you need screen or two terminals.** This is because the *LOCK TABLES* command will only last while the session is active, so if you exits the mysql-console the lock is automaticly unlocked, dont do that !

on node1 run:

```
smartcard20-node1:/usr/local/syscheck/database-replication # ./811-master-node-flush-tables-with-read-lock.sh
```

Connecting to localhost, run this on master only!

Enter manually:

```
FLUSH TABLES WITH READ LOCK;
```

keep the console open until the last step is done

then enter:

```
UNLOCK TABLES
```

Welcome to the MySQL monitor. Commands end with ; or \g.

Your MySQL connection id is 26

Server version: 5.0.67 SUSE MySQL RPM

Type 'help;' or '\h' for help. Type '\c' to clear the buffer.

```
mysql> FLUSH TABLES WITH READ LOCK;
```

Query OK, 0 rows affected (0.00 sec)

```
mysql>
```

*keep this console running, until instructed to exit or run the unlock tables command.*

## 2.4 Make a database backup

on node1 run:

```
smartcard20-node1:/usr/local/syscheck-1.4.3b3-cluster/related-enabled # ./904_make_mysql_db_backup.sh -s
```

```
I-9041-PKI 20090309 13:48:14 smartcard20-node1: INFO - Backed up db ok (file:/backup/mysql/ejbcabackup-2009-03-09_13.48.13.sql.gz)
```

Write down the name of this database backup in your protocol as the last db backup before this change. If anything would go wrong this is the backup to revert to!!!

## 2.5 Transfer the database-backup to node2

Transfer it to node2:

on node1 run:

```
jboss@smartcard20-node1:~> scp /backup/mysql/ejbcabackup-2009-03-09_13.44.55.sql.gz smartcard20-node2:
```

```
ejbcabackup-2009-03-09_13.44.55.sql.gz 100% 1459KB 1.4MB/s 00:00
```

OR use ./906\_ssh-copy-to-remote-machine.sh

on node1 run:

```
smartcard20:/usr/local/certificate-services/syscheck/related-enabled# ./906_ssh-copy-to-remote-machine.sh --help
```

```
smartcard20:/usr/local/certificate-services/syscheck/related-enabled# ./906_ssh-copy-to-remote-machine.sh -s  
/backup/mysql/default/ejbcabackup-2010-06-15_16.03.18.sql.gz node2-hostname /tmp jboss /home/jboss/.ssh/id_rsa
```

```
I-9061-PKI 20100615 16:05:30 smartcard20.demo: INFO - file transfered ok
```

## 2.6 Restore mysql database on node2

**NOTE: Upto and including version 1.5.15 of syscheck 920\_restore\_mysql\_db\_from\_backup.sh don't handle the case that there is no database very good, so be sure to create a empty one first as a work around until this is fixed**

on node2 run:

```
root@smartcard20-node2:/usr/local/syscheck/related-enabled # ./920_restore_mysql_db_from_backup.sh -s  
/home/jboss/ejbcabackup-2009-03-09_13.44.55.sql.gz
```

now we'll backup the current database before we restore the one you specified

```
I-9041-PKI 20090309 14:51:51 smartcard20-node2: INFO - Backed up db ok (file:/backup/mysql/ejbcabackup-2009-03-09_14.51.50.sql.gz)
```

restoring the db from /home/jboss/ejbcabackup-2009-03-09\_13.44.55.sql.gz

```
I-9202-PKI 20090309 14:51:55 smartcard20-node2: INFO - Restored the db from file (/home/jboss/ejbcabackup-2009-03-09_13.44.55.sql.gz)
```

## 2.7 Make node1 master

**Now make node1 take the role of mysql master!!**

on node1 run:

```
smartcard20-node1:/usr/local/syscheck/database-replication # ./804-make-mysql-server-act-as-master.sh
```

Are you sure you want to make this mysql server act as mysql master?

enter 'im-really-sure' (without the '-') to continue or ctrl-c to abort

**im really sure**

I-8041-PKI 20090312 16:34:20 smartcard20-node1: INFO - Mysql server made to act as a master

**Run the show master status command and note the log: “File” and “position”, you will need them in the next step.**

*on node1 run:*

```
smartcard20-node1:/usr/local/syscheck/database-replication # ./810-show-mysql-master-status.sh
```

```
File Position Binlog_Do_DB Binlog_Ignore_DB
```

**mysql-bin.000001 98**

I-8101-PKI 20090311 15:26:32 smartcard20-node1: INFO - Master status shown

```
***** 1. row *****
```

```
Id: 3
```

```
User: root
```

```
Host: localhost
```

```
db: mysql
```

```
Command: Query
```

```
Time: 0
```

```
State: NULL
```

```
Info: SHOW PROCESSLIST
```

I-8101-PKI 20090311 15:26:32 smartcard20-node1: INFO - Master status shown

I-8101-PKI 20090311 15:26:32 smartcard20-node1: INFO - Master status shown

## **2.8 Make node 2 slave**

**Now it's time to start the slave**

*on node2 run:*

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./805-make-mysql-server-act-as-slave.sh
```

Are you sure you want to make this mysql server act as mysql slave?

Press enter to continue, ctrl-c to abort

now you need to run 810-show-mysql-master-status.sh on the master node

For a first time setup (master has never had a slave) default file="" and pos=4 is the values to use

then enter File and Position

Enter Log File default:[]>

**mysql-bin.000001**

Enter Log Pos default:[4]>

**98**

I-8051-PKI 20090312 16:48:09 smartcard20-node2: INFO - Mysql server made to act as a slave

## **2.9 Unlock master database tables**

In the console used to lock the tables in previous step enter the following commands:

on node1 run:

```
mysql> UNLOCK TABLES;
```

Query OK, 0 rows affected (0.00 sec)

```
mysql>
```

## **2.10 Verify replication**

on node1 run:

```
smartcard20-node1:/usr/local/syscheck/database-replication # ./810-show-mysql-master-status.sh
```

File Position Binlog\_Do\_DB Binlog\_Ignore\_DB

**mysql-bin.000001 4439**

I-8101-PKI 20090311 16:02:33 smartcard20-node1: INFO - Master status shown

\*\*\*\*\* 1. row \*\*\*\*\*

Id: 73

User: ejbcarep

Host: 10.15.251.247:6265

db: NULL

Command: Binlog Dump

Time: 1015

**State: Has sent all binlog to slave; waiting for binlog to be updated**

Info: NULL

Here one or more connections can be described, but those are from other clients than the replication client so they are not important at this step.

\*\*\*\*\* 2. row \*\*\*\*\*

Id: 88

User: ejbca

Host: localhost:24797

db: ejbca

Command: Sleep

Time: 306

State:

Info: NULL

Info: SHOW PROCESSLIST

I-8101-PKI 20090311 16:02:33 smartcard20-node1: INFO - Master status shown

I-8101-PKI 20090311 16:02:33 smartcard20-node1: INFO - Master status shown

## Check the slave

*on node2 run:*

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./809-show-mysql-slave-status.sh
```

Slave_IO_State	Master_Host	Master_User	Master_Port	Connect_Retry	Master_Log_File	Read_Master_Log_Pos	Relay_Log_File	Relay_Log_Pos	Relay_Master_Log_File	Slave_IO_Running	Slave_SQL_Running	Replicate_Do_DB	Replicate_Ignore_DB	Replicate_Do_Table	Replicate_Ignore_Table	Replicate_Wild_Do_Table	Replicate_Wild_Ignore_Table	Last_Errno	Last_Error	Skip_Counter	Exec_Master_Log_Pos	Relay_Log_Space	Until_Condition	Until_Log_File	Until_Log_Pos	Master_SSL_Allowed	Master_SSL_CA_File	Master_SSL_CA_Path	Master_SSL_Cert	Master_SSL_Cipher	Master_SSL_Key
----------------	-------------	-------------	-------------	---------------	-----------------	---------------------	----------------	---------------	-----------------------	------------------	-------------------	-----------------	---------------------	--------------------	------------------------	-------------------------	-----------------------------	------------	------------	--------------	---------------------	-----------------	-----------------	----------------	---------------	--------------------	--------------------	--------------------	-----------------	-------------------	----------------

Seconds\_Behind\_Master

**Waiting for master to send event 10.15.251.246 ejbcarep 3306 60 mysql-bin.000001 4439 smartcard20-node2-relay-bin.000003 2057 mysql-bin.000001 Yes Yes 0 0**

4439 2057 None 0 No 0

I-8091-PKI 20090311 16:02:25 smartcard20-node2: INFO - Slave status shown

## **2.11 Write to the test table and verify both servers answers the same number**

**NOTE: this command will use localhost as master so never run this on the slave-host then the replication of the test table will stop!**

on node1(master-node) run:

smartcard20-node1:/usr/local/syscheck/database-replication # **./807-test-table-create-table.sh**

creating the test table:

smartcard20-node1:/usr/local/syscheck/database-replication # **./808-test-table-update-and-check-master-and-slave.sh**

cleaning and inserting new val: **1236784263**

values from 10.15.251.246

value

**1236784263**

values from 10.15.251.247

value

**1236784263**

## **2.12 Change datasource config in jboss**

Set jboss datasource on node1

on node1 run:

smartcard20-node1:/usr/local/certificate-services/syscheck/database-replication# **./806-change-active-mysql-server-in-jboss-datasource.sh node1**

ejbca-ds.xml in jboss switched host to 10.1.1.10

remember to restart jboss when you want the change to take effect

Set jboss datasource on node2

on node2 run:



```
smartcard20-node2:/usr/local/certificate-services/syscheck/database-replication# ./806-change-active-mysql-server-in-jboss-datasource.sh node1
```

ejbca-ds.xml in jboss switched host to 10.1.1.10

remember to restart jboss when you want the change to take effect

## 2.13 Start Jboss application server

Start jboss on node1

on node1 run:

```
smartcard20-node1:/usr/local/certificate-services/syscheck/related-enabled# /etc/init.d/jboss start
```

Starting JBoss using Java from /usr/local/certificate-services/java: Waiting for jboss server to start:.....done

Start jboss on node2

on node2 run:

```
smartcard20-node2:/usr/local/certificate-services/syscheck/related-enabled# /etc/init.d/jboss start
```

Starting JBoss using Java from /usr/local/certificate-services/java: Waiting for jboss server to start:.....done

## 2.14 Activate CA:s

Either activate CA:s in EJBCA / The Admin Console or with Syscheck

With syscheck you need to config PIN-codes into config/common.conf

on node1 run:

```
smartcard20-node1:/usr/local/certificate-services/syscheck/related-enabled# ./909_activate_CAs.sh -s
```

Screenonly output:

Activating CA : eIDCA (./bin/ejbca.sh ca activateca eIDCA 1111)

Using JBoss JNDI provider...

I-9091-PKI 20100615 17:27:04 smartcard20.demo: INFO - Activate CA:s run successfully

[...]

**NOTE: from this step on the service is again available!**

# 3 Fail over and fail back

## 3.1 Fail over, make the slave master

Master has problems, thus we need to make the slave accept updates i.e. make it mysql master

To simulate master problems just shut it down

```
smartcard20-node1:/usr/local/syscheck/database-replication # /etc/init.d/mysql stop
```

Also shut down jboss on both nodes

```
smartcard20-node1:/usr/local/syscheck/database-replication # /etc/init.d/jboss stop
```

```
smartcard20-node2:/usr/local/syscheck/database-replication # /etc/init.d/jboss stop
```

Slave now shows it can't connect to master:

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./809-show-mysql-slave-status.sh
```

Slave_IO_State	Master_Host	Master_User	Master_Port	Connect_Retry	Master_Log_File	Read_Master_Log_Pos	Relay_Log_File	Relay_Log_Pos	Relay_Master_Log_File	Slave_IO_Running	Slave_SQL_Running	Replicate_Do_DB	Replicate_Ignore_DB	Replicate_Do_Table	Replicate_Ignore_Table	Replicate_Wild_Do_Table	Replicate_Wild_Ignore_Table	Last_Errno	Last_Error	Skip_Counter	Exec_Master_Log_Pos	Relay_Log_Space	Until_Condition	Until_Log_File	Until_Log_Pos
----------------	-------------	-------------	-------------	---------------	-----------------	---------------------	----------------	---------------	-----------------------	------------------	-------------------	-----------------	---------------------	--------------------	------------------------	-------------------------	-----------------------------	------------	------------	--------------	---------------------	-----------------	-----------------	----------------	---------------

Master_SSL_Allowed	Master_SSL_CA_File	Master_SSL_CA_Path	Master_SSL_Cert	Master_SSL_Cipher	Master_SSL_Key	Seconds_Behind_Master
--------------------	--------------------	--------------------	-----------------	-------------------	----------------	-----------------------

**Reconnecting after a failed master event read 10.15.251.246** ejbcarep 3306 60 mysql-bin.000001 822 smartcard20-node2-relay-bin.000002 235 mysql-bin.000001 No Yes 0

0 822 235 None 0 No NULL

I-8091-PKI 20090312 16:33:15 smartcard20-node2: INFO - Slave status shown

**Now make this node take the role of mysql master**

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./804-make-mysql-server-act-as-master.sh
```

Are you sure you want to make this mysql server act as mysql master?

Press enter to continue, ctrl-c to abort

I-8041-PKI 20090312 16:34:20 smartcard20-node2: INFO - Mysql server made to act as a master

*Check the master status*

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./810-show-mysql-master-status.sh
```

File Position Binlog\_Do\_DB Binlog\_Ignore\_DB

**mysql-bin.000001 98**

I-8101-PKI 20090312 16:34:35 smartcard20-node2: INFO - Master status shown

\*\*\*\*\* 1. row \*\*\*\*\*

Id: 64

User: ejbca

Host: smartcard20-node2.demo:23152

db: ejbca

Command: Sleep

Time: 313

State:

Info: NULL

Here one or more connections can be described, but those are from other clients than the replication client so they are not important at this step.

\*\*\*\*\* 2. row \*\*\*\*\*

Id: 65

User: ejbca

Host: smartcard20-node2.demo:23153

db: ejbca

Command: Sleep

Time: 313

State:

Info: NULL

I-8101-PKI 20090312 16:34:35 smartcard20-node2: INFO - Master status shown

I-8101-PKI 20090312 16:34:35 smartcard20-node2: INFO - Master status shown

**Since there is no slave we wont see that process in the list!**

Failover VIP , remove VIP from node1

```
smartcard20-node1:/usr/local/syscheck/related-enabled # ./912_deactivate_VIP.sh -s
```

```
I-9123-PKI 20100615 17:42:05 smartcard20.demo: INFO - While deactivating, the VIP was already NOT active on this host
```

Activate VIP on node2

```
smartcard20:/usr/local/certificate-services/syscheck/related-enabled# ./911_activate_VIP.sh -s
```

```
I-9111-PKI 20100615 17:44:22 smartcard20.demo: INFO - Activate VIP run successfully
```

Failover jboss datasource configuration on node2

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./806-change-active-mysql-server-in-jboss-datasource.sh node2
```

ejbca-ds.xml in jboss switched host to 10.1.1.11

remember to restart jboss when you want the change to take effect

todo: start jboss and verify functionality

start jboss on node2

```
smartcard20-node2:/usr/local/syscheck/related-enabled # /etc/init.d/jboss start
```

activate CA:s

issue a CRL for each CA and optionally issue a test certificate to verify node 2 is working.

## ***3.2 Fail-back, make the old master master again***

First we need to lock the tables from writes on node2

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./811-master-node-flush-tables-with-read-lock.sh
```

Connecting to localhost, run this on master only!

Enter manually:

FLUSH TABLES WITH READ LOCK;

keep the console open until the last step is done

then enter:

UNLOCK TABLES

Welcome to the MySQL monitor. Commands end with ; or \g.

Your MySQL connection id is 26

Server version: 5.0.67 SUSE MySQL RPM

Type 'help;' or '\h' for help. Type '\c' to clear the buffer.

```
mysql> FLUSH TABLES WITH READ LOCK;
```

Query OK, 0 rows affected (0.00 sec)

```
mysql>
```

*keep this console running, until instructed to exit or run the unlock tables command.*

Shutdown jboss on node1

```
smartcard20-node1:/usr/local/syscheck/related-enabled # /etc/init.d/jboss stop
```

Shutdown jboss on node2

```
smartcard20-node2:/usr/local/syscheck/related-enabled # /etc/init.d/jboss stop
```

Make a backup of the data at node2

```
smartcard20-node2:/usr/local/syscheck/related-enabled # ./904_make_mysql_db_backup.sh -s
```

```
I-9041-PKI 20090312 16:44:14 smartcard20-node2: INFO - Backed up db ok (file:/backup/mysql/ejbcabackup-2009-03-12_16.44.14.sql.gz)
```

transfer backup it to node1

```
smartcard20-node2:/usr/local/syscheck/related-enabled # ./906_ssh-copy-to-remote-machine.sh -s /backup/mysql/ejbcabackup-2009-03-12_16.44.14.sql.gz smartcard20-node1 /home/jboss jboss /home/jboss/.ssh/id_rsa
```

```
I-9061-PKI 20090312 16:44:39 smartcard20-node2: INFO - file transfered ok
```

At node1 start the database server (if it was off during recovering the server)

```
username@smartcard20-node1:/usr/local/syscheck-1_5_0/related-enabled> sudo /etc/init.d/mysql start
```

At node1 restore the database

```
username@smartcard20-node1:/usr/local/syscheck-1_5_0/related-enabled> sudo ./920_restore_mysql_db_from_backup.sh -s /home/jboss/ejbcabackup-2009-03-27_11.09.08.sql.gz
```

enter 'im-really-sure' (without the '-') to continue or ctrl-c to abort

**im really sure**

now we'll backup the current database before we restore the one you specified

I-9041-PKI 20090327 11:09:46 sles20sp2-2: INFO - Backed up db ok (file:/backup/mysql/ejbcabackup-2009-03-27\_11.09.46.sql.gz)

restoring the db from /backup/mysql/ejbcabackup-2009-03-27\_11.09.08.sql.gz

I-9202-PKI 20090327 11:09:47 sles20sp2-2: INFO - Restored the db from file (/backup/mysql/ejbcabackup-2009-03-27\_11.09.08.sql.gz)

## Now lets make the old master master again

smartcard20-node1:/usr/local/syscheck/database-replication # **./804-make-mysql-server-act-as-master.sh**

Are you sure you want to make this mysql server act as mysql master?

enter 'im-really-sure' (without the '-') to continue or ctrl-c to abort

**im really sure**

I-8041-PKI 20090312 16:47:00 smartcard20-node1: INFO - Mysql server made to act as a master

## Check mysql master status

smartcard20-node1:/usr/local/syscheck/database-replication # **./810-show-mysql-master-status.sh**

File Position Binlog\_Do\_DB Binlog\_Ignore\_DB

**mysql-bin.000001 98**

I-8101-PKI 20090312 16:47:08 smartcard20-node1: INFO - Master status shown

\*\*\*\*\* 1. row \*\*\*\*\*

Id: 5

User: root

Host: localhost

db: mysql

Command: Query

Time: 0

State: NULL

Info: SHOW PROCESSLIST

I-8101-PKI 20090312 16:47:08 smartcard20-node1: INFO - Master status shown

I-8101-PKI 20090312 16:47:08 smartcard20-node1: INFO - Master status shown

## Make the old slave slave again, enter YOUR values from the last commnd!

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./805-make-mysql-server-act-as-slave.sh
```

Are you sure you want to make this mysql server act as mysql slave?

enter 'im-really-sure' (without the '-') to continue or ctrl-c to abort

**im really sure**

now you need to run 810-show-mysql-master-status.sh on the master node

For a first time setup (master has never had a slave) default file="" and pos=4 is the values to use

then enter File and Position

Enter Log File default:[]>

**mysql-bin.000001**

Enter Log Pos default:[4]>

**98**

I-8051-PKI 20090312 16:48:09 smartcard20-node2: INFO - Mysql server made to act as a slave

Time to release lock on node2, go back to the console used to lock the tables and enter:

```
mysql> UNLOCK TABLES;
```

Query OK, 0 rows affected (0.00 sec)

```
mysql>
```

Failback VIP - deactivate on node2

```
sc20fmv-node2:/usr/local/certificate-services/syscheck/related-enabled # ./912_deactivate_VIP.sh -s
```

I-9121-PKI 20100610 13:21:00 sc20fmv-node2: INFO - Deactivate VIP run successfully

Failback VIP - activate on node1

```
sc20fmv-node1:/usr/local/certificate-services/syscheck/related-enabled # ./911_activate_VIP.sh -s
```

I-9111-PKI 20100610 13:21:06 sc20fmv-node1: INFO - Activate VIP run successfully

Failback jboss datasource configuration

Change to node1 to use as datasource

```
smartcard20-node1:/usr/local/syscheck/database-replication # ./806-change-active-mysql-server-in-jboss-datasource.sh node1  
ejbca-ds.xml in jboss switched host to 192.168.31.140  
remember to restart jboss when you want the change to take effect
```

Change to node2 to use as datasource

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./806-change-active-mysql-server-in-jboss-datasource.sh node1  
ejbca-ds.xml in jboss switched host to 192.168.31.140  
remember to restart jboss when you want the change to take effect
```

Verify replication with the simple test tool

All three values MUST be the same

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./808-test-table-update-and-check-master-and-slave.sh
```

cleaning and inserting new val: **1276170492**

values from 192.168.31.140

value

**1276170492**

values from 192.168.31.142

value

**1276170492**

start jboss on node1

```
smartcard20-node1:/usr/local/syscheck/related-available # /etc/init.d/jboss start
```

Starting JBoss application server: Waiting for jboss server to start:

.....JBoss server is up and running.

start jboss on node2

```
smartcard20-node2:/usr/local/syscheck/related-available # /etc/init.d/jboss start
```

Starting JBoss application server: Waiting for jboss server to start:

.....JBoss server is up and running.



Verify replication status – The position shall be updated from the initial “98”

```
smartcard20-node1:/usr/local/syscheck/database-replication # ./810-show-mysql-master-status.sh
```

File	Position	Binlog_Do_DB	Binlog_Ignore_DB
------	----------	--------------	------------------

<b>mysql-bin.000001</b>	<b>19528</b>		
-------------------------	--------------	--	--

I-8101-PKI 20080504 18:09:18 sc20fmv-node1: INFO - Master status shown

\*\*\*\*\* 1. row \*\*\*\*\*

Id: 12

User: ejbcarep

Host: 192.168.31.142:35185

db: NULL

Command: Binlog Dump

Time: 2018

**State: Has sent all binlog to slave; waiting for binlog to be updated**

Info: NULL

\*\*\*\*\* 2. row \*\*\*\*\*

<...>

I-8101-PKI 20090312 16:50:51 smartcard20-node1: INFO - Master status shown

I-8101-PKI 20090312 16:50:51 smartcard20-node1: INFO - Master status shown

show slave status, the slave must have the same file and position (or larger value on replica)

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./809-show-mysql-slave-status.sh
```

\*\*\*\*\* 1. row \*\*\*\*\*

Slave\_IO\_State: Waiting for master to send event

Master\_Host: 192.168.31.140

Master\_User: ejbcarep

Master\_Port: 3306

Connect\_Retry: 60

**Master\_Log\_File: mysql-bin.000001**

**Read\_Master\_Log\_Pos: 19528**

Relay\_Log\_File: sc20fmv-node2-relay-bin.000002

Relay\_Log\_Pos: 19665

Relay\_Master\_Log\_File: mysql-bin.000001

Slave\_IO\_Running: Yes

Slave\_SQL\_Running: Yes

Replicate\_Do\_DB:

Replicate\_Ignore\_DB:

Replicate\_Do\_Table:

Replicate\_Ignore\_Table:

Replicate\_Wild\_Do\_Table:

Replicate\_Wild\_Ignore\_Table:

Last\_Errno: 0

Last\_Error:

Skip\_Counter: 0

Exec\_Master\_Log\_Pos: 19528

Relay\_Log\_Space: 19665

Until\_Condition: None

Until\_Log\_File:

Until\_Log\_Pos: 0

Master\_SSL\_Allowed: No

Master\_SSL\_CA\_File:

Master\_SSL\_CA\_Path:

Master\_SSL\_Cert:

Master\_SSL\_Cipher:

Master\_SSL\_Key:

Seconds\_Behind\_Master: 0

I-8091-PKI 20100610 13:50:09 sc20fmv-node2: INFO - Slave status shown

# 4 Verification and Troubleshooting

## 4.1 Check the log file:

on node2 run:

```
smartcard20-node2:/usr/local/syscheck/database-replication # less /var/log/mysqld.log

090311 15:45:37 mysqld ended

090311 15:45:37 mysqld started

090311 15:45:38 InnoDB: Started; log sequence number 0 43665

090311 15:45:38 [Warning] Neither --relay-log nor --relay-log-index were used; so replication may break when this MySQL server acts as a slave and has his hostname changed!! Please use '--relay-log=smartcard20-node2-relay-bin' to avoid this problem.

090311 15:45:38 [Note] /usr/sbin/mysqld: ready for connections.

Version: '5.0.26' socket: '/var/lib/mysql/mysql.sock' port: 3306 SUSE MySQL RPM

090311 15:45:38 [Note] Slave SQL thread initialized, starting replication in log 'mysql-bin.000001' at position 2617, relay log './smartcard20-node2-relay-bin.000001' position: 98

090311 15:45:38 [Note] Slave I/O thread: connected to master 'ejbcarep@10.15.251.246:3306', replication started in log 'mysql-bin.000001' at position 2617
```

## 4.2 Write to the test table and verify both servers answers the same number

on node1 run:

```
smartcard20-node1:/usr/local/syscheck/database-replication # ./807-test-table-create-table.sh

creating the test table:

smartcard20-node1:/usr/local/syscheck/database-replication # ./808-test-table-update-and-check-master-and-slave.sh

cleaning and inserting new val: 1236784263
```

values from 10.15.251.246

value

**1236784263**

values from 10.15.251.247

value

**1236784263**

### ***4.3 Use the show master and show slave scripts***

**Run this script on the master!**

*on master-host run: (since this can change back an forth, you need to know which host is master)*

```
smartcard20-node1:/usr/local/syscheck/database-replication # ./810-show-mysql-master-status.sh
```

```
File Position Binlog_Do_DB Binlog_Ignore_DB
```

```
mysql-bin.000001 6106
```

```
I-8101-PKI 20090311 16:22:44 smartcard20-node1: INFO - Master status shown
```

```
***** 1. row *****
```

```
Id: 73
```

```
User: ejbcarep
```

```
Host: 10.15.251.247:6265
```

```
db: NULL
```

```
Command: Binlog Dump
```

```
Time: 2226
```

```
State: Has sent all binlog to slave; waiting for binlog to be updated
```

```
Info: NULL
```

```
***** 2. row *****
```

Id: 141

User: ejbca

Host: localhost:27370

db: ejbca

Command: Sleep

Time: 317

State:

Info: NULL

\*\*\*\*\* 3. row \*\*\*\*\*

Id: 142

User: ejbca

Host: localhost:27371

db: ejbca

Command: Sleep

Time: 317

State:

Info: NULL

\*\*\*\*\* 4. row \*\*\*\*\*

Id: 143

User: ejbca

Host: localhost:27372

db: ejbca

Command: Sleep

Time: 167

State:

Info: NULL

\*\*\*\*\* 5. row \*\*\*\*\*

Id: 144

User: ejbca

Host: localhost:27373

db: ejbca

Command: Sleep

Time: 167

State:

Info: NULL

\*\*\*\*\* 6. row \*\*\*\*\*

Id: 145

User: ejbca

Host: localhost:27374

db: ejbca

Command: Sleep

Time: 167

State:

Info: NULL

\*\*\*\*\* 7. row \*\*\*\*\*

Id: 148

User: root

Host: localhost

db: mysql

Command: Query

Time: 0

State: NULL

Info: SHOW PROCESSLIST

I-8101-PKI 20090311 16:22:44 smartcard20-node1: INFO - Master status shown

I-8101-PKI 20090311 16:22:44 smartcard20-node1: INFO - Master status shown

**It's important the master show status says:**

**State: Has sent all binlog to slave; waiting for binlog to be updated**

**And then compare the logfilename and log\_pos with slave show status**

**Run this script on the slave!**

*on slave-host run:*

```
smartcard20-node2:/usr/local/syscheck/database-replication # ./809-show-mysql-slave-status.sh
```

```
Slave_IO_State Master_Host Master_User Master_Port Connect_Retry Master_Log_File Read_Master_Log_Pos
Relay_Log_File Relay_Log_Pos Relay_Master_Log_File Slave_IO_Running Slave_SQL_Running Replicate_Do_DB
Replicate_Ignore_DB Replicate_Do_Table Replicate_Ignore_Table Replicate_Wild_Do_Table Replicate_Wild_Ignore_Table
Last_Errno Last_Error Skip_Counter Exec_Master_Log_Pos Relay_Log_Space Until_Condition Until_Log_File Until_Log_Pos
```

```
Master_SSL_Allowed Master_SSL_CA_File Master_SSL_CA_Path Master_SSL_Cert Master_SSL_Cipher Master_SSL_Key
Seconds_Behind_Master
```

```
Waiting for master to send event 10.15.251.246 ejbcarep 3306 60 mysql-bin.000001 6106 smartcard20-node2-relay-bin.000003
3724 mysql-bin.000001 Yes Yes 0 0
```

```
6106 3724 None 0 No 0
```

I-8091-PKI 20090311 16:23:24 smartcard20-node2: INFO - Slave status shown

Here it's important the slave states it waits for master to send updates, has the right ip to the master and the same Logfilename and log\_pos is the same as master show status shows.