



Date: December 17, 2019

To: Bristol, Jhecelle R. EN No.: EN69-0702

No. of Offence: 1st offence

From: Human Resources and Administrative Dept.

Re: As stated

Based on incident reported on November 25, 2019. You hereby allegedly violated:

One Source Code of Discipline Section:

3.2. Use of Company Property (3.2.14 Not following company standards, operating procedures, work instruction and practices which may or may not result to damage of company property.)

In line with the violation, this memorandum will serve as your

() Written Warning	() 10-days Suspension
W1-day Suspension	() 15-days Suspension
() 2-days Suspension	() 30-days Suspension
() 3-days Suspension	() Warning to Dismissal Depending to gravity of offense
() 5-days Suspension	() Dismissal Effective
) 7-days Suspension	() For record purposes only

For your reference. Thank you

Best Regards,

Received by: JAECEUE

BRISTOL SIGNITURE OVER PRINTED NAME

RECOMMENDATION FORM JHECELLE BRISH En le9 Not Following)N) 01-27-2020 01-28-2020 * TRETURN SHIFT-拍-(0998)977-4625 | |SHIFT/SCHEDULE: PDS-Paalala: Iwanan ang ID sa Coordinator bago ang suspension date at sa muling pagpasok galing sa suspension kuhanin ang ID sa

Coordinator bago mag 8am

/f			Massage on Company	NC	TICE	TO EXPL	AIN		entrement general proportion in the latest the desirate (a desirate de desta de desirate de desirate de desirate de desirate de desirate d
		Bristol Jho	ecelly.	the good and the control of the cont		PROJECT:	FURLIKAWA		
ME:		DEC- 20-			-	EMP NO:	En 69-0207		ASSOCIATE
(ON:		PRODUCTO	on of	PERAIDR		SUPERIOR:	-		
our immedi ne One Source [Cite Code of Di	Specialized	Services Inc. Code	on notice of Discipl	that based on prelir ine; see attached In	minary inve cident Repo	stigations, you a ort (HRF004-00).	llegedly violated the	e following	provision in
on [date/time] a	at [location,	if applicable].			***************************************				Net/Premiserous/servicemproproprostobuleen
For this reason,	One Source	is considering the	following	disciplinary action	against you	negatives and an experience of the second se			
Pre	ovision/Pol	licy		rdinal No. of Offe n the prescriptive	100,000	Discipli	nary Action Per Co	de of Disc	ipline
		and dissertance of the first				10	day Suspension)	
Employee's Expl	anation:	ve (5) days upon re ove should not be	taken aga	his Notice of your wainst you.	ritten expla	HIVDI	, and justifications a		е
								NU0	
<u> </u>	CONTRACTOR CONTRACTOR CONTRACTOR	9.0.P		PACSULAT	76	WIRE	LENGHT	St ki	2DD
	Huanan	Contraction of Descriptor and Associate Contraction Co	Fleo Y	NAGMAMA		DAHI	Po 1	2000	
***************************************	ARA		ngyl	AKO AY	MARI	aminc i	UIRE AT	Do wu	1mx
Note: You may use	NADIV	THE RESIDENCE OF THE PROPERTY						Comment desired and the comment of t	Martin Salah serinda Advoping yada salah s
Note. You may use	un extru sne	et as needed.				/	LIMPIOYEE SIE		2-20-201
for standiller alle tilpitoler opt vettangen ave fillerand van ve		emper of every of Children by treatmen or where	(To	be filled up by One	Source HR	only.)	on the besidence are springing for symmetry sign speakers who some	tion on original by represe as	species to modern on names on almose
Superior's Reco	mmendati	on:							
As your immediation writing, we find				that after a thorou				mants mad	e by you
For this reason, C	ne Source h	nas decided to imp	ose on yo	u the following disc	iplinary act	ion/sanction:			
1.0	itten War	nsion	[]	15-day Suspensio Dismissal Dismissal	on and Wa	arning of	For f	Records O	nly
	day Suspe	ension		For Further Inver	ntigation		981		
~ 1	Ausaho			8		Noted by:			
Juey	8-	ALTECHE	The same of the sa				Manager, HR & A	dmin. Depa	artment
Immediate Sup	erior (Signa	ture over Printed	Name)						
1. Proper way for	erasures		Walter Street Mannier van Jacob in derhand			2. Standard wa	y of writing date.		
12335	Corre	ection signature					14 (year-month-day)		

Form Number: HRF005-00

I ALERT WRITTEN EXPLANATION

FAS	MDHII		Control No: +ALP 18 1910 . 2005
PKIMT	OTHERS: ONESWALCE		Gantalparadon Audited By: Noted By:
Name: Position: ID Number: Batch No.: Car Model/Line: Audit Find Details:	Bristol. Thecelle Associate ENG9. 6702 270 Subam Instial ings: Not following ate did not conduct meanting of five	No of Offense: Superior Name:	The sum 1 ? Ds B october 25.2019 08:50 151 Oftense M. Marana
	tristing frouse	wie wight	und Fith Hangin after
		EXPLANATION	
	INCO 26 FO-K Sc	THE PAGE THE PER PAY DOL	HIND! PG WIRE AKOY NAG MA MA - UNTIME AT MARAM!
COUNTER MEA IN SU KAHIT I	***************************************		one mas (usyka)
W	Remarks itten - Isue fonalty	/ Evaluation:	DD11. 11.
	Issue forom of	vou pan	I NOT ITALK WAL

Signature of Employee
Date: #- C& -[7]

R-Ivaranc Jestaff Date: 11-0-19

Milescorez

Staff
Date: 11-04-19

Supervisor Date: 1121/9

Haly Managar Date: ∭ 27



All Models

TWISTING PROCESS (Primary

FALP-WI-ENG-TW-050 DOCUMENT NO. WORK INSTRUCTION APPROVAL Verified by: REVISION NO.

PAGE NO.: 1

EFFECTIVITY DA May-28-2018

Checked by

Approved by

ENG 146 Twisting Working Record (System Generated), MEI-045F1 Daily Inspection Record of Single Wire Twisting Machine Kanban, Shikakari, Tape (refer to kanban) MATERIALS To serve as a guide for twisting process using primary machine Twisting Machine(Primary), Multi-twisting Machine (Primary), Convex SCOPE OSM-10CB213 A, OSM-10CB213 Annex 1, OSM-10CB124 Annex 3, OSM-20CC802 Prepared by:

Initial Process


Jr. Staff

Supervisor

Asst. Manager

Dept. Manager / Div. Mar


Input the number of rotation into a rotation up switch based on kanhan. Check paint: *Set up rotation number is correct



3. Fit this wire's along the golde. Set 1 pair of wire for single twisting machine and 2 to 3 pairs of wire for mulit-twisting machine and trade sure that the terminal tijns touched the board.

•Nowaig prioritize setting of female terminal with of without gonissen on running side of the machine.
•If body male terminal, set the male terminal without gonusien on running side of the machine.
•Lach wine should be at the center of each clamp and both sides are tocked.
•The advanced *The distance of wire clamp is 110mm from stop plate for long guide of wire in movement part.

In case that there is twist wire difference in Kanbeh, arrange the terminal tips of rotation haad side and fix it. Set sige by side in order that the wires are not piled up when it clamped.



4.1 Check the position of terminal wire in the center of each fixed damp of the rotation hzad side and the movement side.
Note:

Applicable only if there is "Tysisting both ands leips fining" indication on kanban, "Tabing "Indication on kanban, "Tabing rounds; Laf epunds "Tabing rounds; Laf epunds on the Use "Refer to kantian for tabe kind to be use."



Wires should not be sagged and tightened.
 (Refer OSN-20CC802)

Do fit taping on to the sides of twisted wife: 4.2 Put tape on the taping lig then close the safety car Note:



5.2 Release the twisted wire on the moving side without releasing on the running side.


5.3 On the moving side, set the next pairs of wire then release the twisted wire on the running side and set the other pair of wires. Press the start button near the running side.

Importance: This procedure is to avoid MUDA of walking.



6.1 Loosen the clamp on both sides.

First movement side then running side.
 Fold the twisted wire beside the fiding clamp at the movement side, and carefully remove the twisted wire.



Call the attention of concerned personnel and report any

abnormality in machine or process.

65mm-80mm -

Check vissually the wire and terminal appearance of twisted wire. (Refer to OSM-10CB124 Annex 3)

Measure the twisted wire length and confirm its kanban standard (Refer to OSM-10CB213 Annex 1)

Measure the pitch of twisted wire and confirm if it is within the standard (Refer to OSM-IOCB213 Annex 1).


Measure the fixing position of twisted wire on both sides (Rusin OSM-10CBZ13 A).

The consist proof terminal - the distance between the end of the flacts; tope and the end of ruber seal is form to 80 nm. I stope and the end of ruber seal is form to 80 nm. I stope and the end of terminal the distance between the end of trining tope and the end of terminal (insulation adds) is

Note:

• Measure the first product per kanban combination

Measure the first product per kanban combinatio



(3) Close the safety cover before proceeding to twisting process

(3) Always turn off the machine when not in use

			Surfey vir sa ann i recon af em dethy.
DR/CN No.	Revision No.	Effectivity Date	Details of change
PE-ENG-L3a-1805-006	7	May-28-2018	Add details for the use of taping lig understep 4.2; Delete fix taping on both sides of twisted wire instead, refer to kanban for the tape kind to be used; Add warning for safety reminders.
PE-ENG-L3a-1710-001	6	Oct-06-2017	Add multi-twikting machine operation under step 3 and 5; change picture 3 and 5; updata reference document under step 11; add multi-twikting machine on devices/equipment used.
PE-ENG-L3a-1708-002	5	Aug-17-2017	Change picture and additional checkpoine under step 3; Update reference documents.
PE-ENG-L3a-1706-011	4	Jun-17-2017	Change scope from: First and Secondary Focess, to: Initial Process; Additional note for the kind of tape to be used under step 6; Change document references; Additional safety reminder; Additional form ENC-1.46 Twisting Working Record
* A3a-1609-046	3	Oct-03-2016	Additional defails in procedure 1, 3, 4, 6, 30, 11; add reference for procedure 4 and 11; change pictures 1, 7 and 10
A3a-1606-002	2	Jun-11-2016	Removed checking of length of wire before twisting process, include checking of fix taping indication in Kanban comment (Step 6)
1 A3a-1503-007	1	Mar-22-2015	Additional defails in procedure 8.1 and manges in reference for procedure 9.1 8.10.1
A3a-050	0	Apr-01-2013	First Issue per ISO 9001 2008 Quality Madisagnment System

EFF