

fakeBash

One or more commands on a line describe the actions of the script.

Every command is in `[...]` brackets, and must contain at least the function name and may contain additional comma-seperated parameters.

Comments are possible if the first char in a line is a #.

The first line without a `#` is treated as the `bashProfile` string, which can be plain text or html.

Every command can have a class, indicated with `:className`; eg `[autotype:greenBg, "this text is green"]`

After every line, a `[br]` command is inserted, except if the class of the command is `:nobr`

The **EXIT** command stops parsing the file at this location. Good for testing.

All possible commands function names & options

- `[bashProfile]` - prints a the bashProfile, defined in the first line in this document
- `[autotype, "text", 500]` - prints `text` at once, after a delay of `500ms`
- `[autotype:green, "text"]` - prints `text` at once but green without a delay
- `[forceType, "text"]` - user input is forced to type `text`, next command starts when enter is pressed. If the `text` starts with `sudo`, a third parameter is allowed for how to deal with the credentials, see below params for `[credentials]`.
- `[credentials]` - prints password verification. If the password contains `s`, it `s`ucceeds and goes on; if it contains `f`, it `f`ails and commands on the same line with credentials are then ignored.
- `[credentials, true]` - prints password verification - always succeeds on first try
- `[credentials, false]` - prints password verification - always fails (three times)
- `[credentials, 2]` - prints password verification - succeeds on `2`nd try (1-3)
- `[br]` - prints an additional line break
- `[wait]` - waits for the user to press any key
- `[waitForEnter]` - waits for the user to press enter
- `[sleep, 1000]` - waits 1000ms
- `[javascript, "parent.show('elementOnDesktop')"]` - does anything
- `[goto, 4]` - jump to command index `4`; `0` for begin of script
- `[clear]` - clears the screen. Use `[clear] [goto:nobr, 0]` to clear the screen, start from scratch and get the white space correct.
- `[resetProfile]` - reset the path in the bash profile to its initial state.
- `[loader, "Loading: \[" , "█", "░", "\]", 30, 2000, 0, 100, "Progress: ", "%"]` - Shows a loading animation with the char `█` max repeated `30` times; `2000ms` total duration; goes from `0` to `100`; and looks like this:

Loading: [██████████░░░░░░░░░░░░░░░░] Progress: 17%

- `[freeText]` - With `freeText`, you can type whatever. `fakeBash` tries to interpret the typed string. If the command start with the following, *default scripts* get executed: `ls`, `ls -l`, `ls -l -a`, `clear`, `top`, `cd ~`, `cd folderName`, `cd ...`. If the command starts with `sudo`, eg. `sudo ls`, password credentials are asked first, then `ls` gets executed.

NOTE: If you want to have `[ or ]` anywhere in text, use `\[` or `\]`

NOTE: User interaction is only available when `freeText`, `forceType`, `credentials` or `wait` is being used.

`forceType` & *default scripts*

All the *default scripts* above can be used as well within `forceType`:

- `[forceType, "ls"]`
- `[forceType, "ls -l"]`
- `[forceType, "ls -l -a"]`
- `[forceType, "clear"]`
- `[forceType, "top"]`
- `[forceType, "cd ~"]`
- `[forceType, "cd folder"]`
- `[forceType, "cd .."]`
- `[forceType, "sudo ls -l -a", true]`

NOTE: if you use `sudo` in `forcetype`, there is no need for an additional `[credentials]` command, as `sudo` already triggers that.

NOTE: Also, there is a *third* parameter for `sudo` in `forceType`: Same functionality as in the `[credentials]` command; true/false or no third parameter.

NOTE: A *third* parameter string asteriks (eg., `[forceType, "ls -l -a", "*"]`) does inhibit a default script. The example leads to the "ls -l -a" default script to not trigger, eg. nothing happens and you can echo any file list, for example.

Example

```
# ----- setup
# bashProfileName
<span class='green'>admin</span>@<span class='red'>localhost</span>:
<span class='grey'>~</span> $
# -----
[bashProfile] [forceType, "reboot now"]
[autoType:grey, "Reboot sequence initiated.", 500]
[autoType:grey, "Commence graceful shutdown and reboot..", 1500]
[autoType:grey, "Rebooting now.. Thanks for having me!", 2500]
[sleep, 1000]
[bashProfile] [autoType, "Start again?", 0] [wait]
[clear] [goto:nobr, 0]
```