

fakeBash

URL parameters

```
scene          folder name in "/data/"
script         file name in "/data/{script}/{script}.fakeBash". If not
               set, defaults to "script". If script is "freetext" (independent of scene) it
               loads a basic freetext-bash console with all the defaultScripts available.
```

Description

One or more commands on a line describe the actions of the script.

Every command is in `[...]` brackets, and must contain at least the function name and may contain additional comma-separated parameters.

Comments are possible if the first char in a line is a `#`.

The first line without a `#` is treated as the `bashProfile` string, which can be plain text or html.

Some commands can have multiple classes, indicated with `:className`; eg `[autoType:greenBg, "this text is green"]` or, for multiple separated by semicolon:

`[autoType:greenBg;maxWidth;paddingY2:centerText, "this text is green, centered and padded"]`

After every line, a `[br]` command is inserted, except if the class of the command is `:nobr`

The `EXIT` command stops parsing the file at this location. Good for testing.

All possible commands function names & options

Command name	Example	Explanation
autoType	<code>[autoType, "text", 500]</code>	prints <code>text</code> at once, after a delay of <code>500ms</code>
	<code>[autoType:green, "text"]</code>	prints <code>text</code> at once but green without a delay
	<code>[autoType, "javascript:printThisText('aaaaa')"]</code>	prints return value of <code>printThisText</code>
bashProfile	<code>[bashProfile]</code>	prints a the <code>bashProfile</code> , defined in the first line in this document
br	<code>[br]</code>	prints an additional line break
clear	<code>[clear]</code>	clears the screen content. Script commences from here. Use <code>[clear]</code> <code>[goto:nobr, 0]</code> to clear the screen without losing memory, start from scratch and get the white space correct. To reset the whole scene, check out <code>[reset]</code>

Command name	Example	Explanation
credentials	[credentials]	prints password verification. If the password contains s , it s ucceeds and goes on; if it contains f , it f ails and commands on the same line with credentials are then ignored.
	[credentials, true]	prints password verification; always succeeds on first try
	[credentials, false]	prints password verification; always fails (three times)
	[credentials, 2]	prints password verification; succeeds on 2nd try (1-3)
forceType	[forceType, "text"]	user input is forced to type text , next command starts when enter is pressed. If the text starts with sudo , a third parameter is allowed for how to deal with the credentials, see below params for [credentials].
freeText	[freeText]	With freeText, you can type whatever. fakeBash tries to interpret the typed string. If the command start with the following, <i>default scripts</i> get executed: ls, ls -l, ls -l -a, clear, top, cd ~, cd folderName, cd ... If the command starts with sudo , eg. sudo ls , password credentials are asked first, then ls gets executed.
garbageCollection	[garbageCollection, 50]	removes first 50 lines from body to preserve data
goto	[goto, 4]	jump to command index 4 ; 0 for begin of script
javascript	[javascript, "parent.show('elementOnDesktop')"]	does anything
loader	[loader, "Loading: \[" , "█", "░", "\]", 30, 2000, 0, 100, "Progress: ", "%"]	Shows a loading animation with the char █ max repeated 30 times; 2000 ms total duration; goes from 0 to 100 ; and looks like this: Loading: Progress: 17%
say	[say, "This is spoken out loud", "en", "voice"]	Says the text in a bad, browser-dependend computer voice. Specify lang , defaults to en . Dont specify voice as this is different on all OS and Browsers. Also prints the text to the screen like autoType .
sleep	[sleep, 1000]	waits 1000ms

Command name	Example	Explanation
reset	[reset]	hard reloads everything from scratch; clears the screen. Checkout [clear] for only clearing the screen.
resetProfile	[resetProfile]	reset the path in the bash profile to its initial state.
wait	[wait]	waits for the user to press any key
waitForEnter	[waitForEnter]	waits for the user to press enter

NOTE: If you want to have [or] anywhere in text, use \[or \]

NOTE: User interaction is only available when `freeText`, `forceType`, `credentials` or `wait` is being used.

NOTE: `[goto:nobr, 0]` does somehow wait for an input even if the command at index 1 is `Autotpye`. To resolve this, remove the `:nobr` class. Will make a `<br>` too much but it loops correctly.

ATTENTION: There's no automatic garbage collection. The document will get bigger and bigger. Use `[garbageCollection, 50]` on and off again.

forceType & default scripts

All the *default scripts* above can be used as well within `forceType`:

- `[forceType, "ls"]`
- `[forceType, "ls -l"]`
- `[forceType, "ls -l -a"]`
- `[forceType, "clear"]`
- `[forceType, "top"]`
- `[forceType, "cd ~"]`
- `[forceType, "cd folder"]`
- `[forceType, "cd .."]`
- `[forceType, "sudo ls -l -a", true]`

NOTE: if you use `sudo` in `forcetype`, there is no need for an additional `[credentials]` command, as `sudo` already triggers that.

NOTE: Also, there is a *third* parameter for `sudo` in `forceType`: Same functionality as in the `[credentials]` command; `true/false` or no third parameter.

NOTE: A *third* parameter string asteriks (eg., `[forceType, "ls -l -a", "*"]`) does inhibit a default script. The example leads to the `"ls -l -a"` default script to not trigger, eg. nothing happens and you can echo any file list, for example.

Example

```
# ----- setup
# bashProfileName
<span class='green'>admin</span>@<span class='red'>localhost</span>:<span class='grey'>~</span> $
# -----
[bashProfile] [forceType, "reboot now"]
[autoType:grey, "Reboot sequence initiated.", 500]
[autoType:grey, "Commence graceful shutdown and reboot..", 1500]
[autoType:grey, "Rebooting now.. Thanks for having me!", 2500]
```

```
[sleep, 1000]  
[bashProfile] [autoType, "Start again?", 0] [wait]  
[clear] [goto:nobr, 0]
```