

fakeBash

URL parameters

```
scene                folder name in "/data/"
script               file name in "/data/{script}/{script}.fakeBash".
If not set, defaults to "script". If script is "freetext" (independent
of scene) it loads a basic freetext-bash console with all the
defaultScripts available.
```

Descriptions

One or more commands on a line describe the actions of the script.

Every command is in `[..]` brackets, and must contain at least the function name and may contain additional comma-separated parameters.

Comments are possible if the first char in a line is a `#`.

The first line without a `#` is treated as the `bashProfile` string, which can be plain text or html.

Every command can have a class, indicated with `:className`; eg `[autotype:greenBg, "this text is green"]`

After every line, a `[br]` command is inserted, except if the class of the command is `:nobr`

The `EXIT` command stops parsing the file at this location. Good for testing.

All possible commands function names & options

- `[bashProfile]` - prints a the `bashProfile`, defined in the first line in this document
- `[autotype, "text", 500]` - prints `text` at once, after a delay of `500ms`
- `[autotype:green, "text"]` - prints `text` at once but green without a delay
- `[forceType, "text"]` - user input is forced to type `text`, next command starts when enter is pressed. If the `text` starts with `sudo`, a third parameter is allowed for how to deal with the credentials, see below params for `[credentials]`.
- `[credentials]` - prints password verification. If the password contains `s`, it `s`ucceeds and goes on; if it contains `f`, it `f`ails and commands on the same line with credentials are then ignored.
- `[credentials, true]` - prints password verification - always succeeds on first try
- `[credentials, false]` - prints password verification - always fails (three times)
- `[credentials, 2]` - prints password verification - succeeds on `2`nd try (1-3)
- `[br]` - prints an additional line break
- `[wait]` - waits for the user to press any key
- `[waitForEnter]` - waits for the user to press enter
- `[sleep, 1000]` - waits `1000ms`
- `[javascript, "parent.show('elementOnDesktop')"]` - does anything

default script. The example leads to the "ls -l -a" default script to not trigger, eg. nothing happens and you can echo any file list, for example.

Example

```
# ----- setup
# bashProfileName
admin@localhost:
~/ $
# -----
[bashProfile] [forceType, "reboot now"]
[autoType:grey, "Reboot sequence initiated.", 500]
[autoType:grey, "Commence graceful shutdown and reboot..", 1500]
[autoType:grey, "Rebooting now.. Thanks for having me!", 2500]
[sleep, 1000]
[bashProfile] [autoType, "Start again?", 0] [wait]
[clear] [goto:nobr, 0]
```