



Global Knowledge®

In-company training QNH Module 5 Angular Services

Peter Kassenaar –
info@kassenaar.com

WORLDWIDE LOCATIONS

BELGIUM CANADA COLOMBIA DENMARK EGYPT FRANCE IRELAND JAPAN KOREA MALAYSIA MEXICO NETHERLANDS NORWAY QATAR
SAUDI ARABIA SINGAPORE SPAIN SWEDEN UNITED ARAB EMIRATES UNITED KINGDOM UNITED STATES OF AMERICA

Waarom Services?


Doel – datafunctionality herbruikbaar maken voor verschillende componenten

- Data retrieval
- Data caching
- Data Storage,
- ...


Angular 2 : één optie

- `export class myDataService { ... }`

Data flow



Bij multiple components



Services in Angular 2

Data services in Angular 1:

```
angular.module( 'myApp' )  
  .service(...)  
  .factory(...)  
  .provider(...)
```

Data services in Angular 2:


```
import {Injectable} from '@angular/core';  
  
@Injectable()  
export class CityService{  
  //....  
}
```

De rol van @Injectable

Why? – Dependency Injection (DI) en metadata!

“TypeScript sees the @Injectable() decorator and emits metadata about our service, metadata that Angular may need to inject other dependencies into this service.”

<https://angular.io/docs/ts/latest/tutorial/toh-pt4.html>



“Our service doesn't have any dependencies at the moment. Add the decorator anyway.

It is a best practice to apply the `@Injectable()` decorator from the start both for consistency and for future-proofing”

Stap 1 – service maken (static data)

```
import { Injectable } from '@angular/core';
import { City } from './city.model'

@Injectable()
export class CityService {
  cities:City[] = [
    new City(1, 'Groningen', 'Groningen'),
    ...
  ];

  // retourner alle cities
  getCities() {
    return this.cities
  }

  // retourner city op basis van ID
  getCity(id:number) {
    return this.cities.find(c => c.id === id);
  }
}
```


Stap 2 – Service consumeren/injecten

```
...
import {CityService} from "../city.service";

@Component({
  selector    : 'hello-world',
  templateUrl: 'app/app.html',
})

export class AppComponent implements OnInit {
  // Properties voor de component/class
  currentCity: City;
  cities: City[];
  cityPhoto: string;

  constructor(private cityService: CityService) {

  }

  ngOnInit() {
    this.cities = this.cityService.getCities();
  }

  getCity(city: City) {
    this.currentCity = this.cityService.getCity(city.id);
    this.cityPhoto   = `img/${this.currentCity.name}.jpg`;
    console.log('City opgehaald:', this.currentCity);
  }
}
```


local
variables

DI in Constructor: shorthand
voor nieuwe private variable +
instantiëring!

Detailgegevens voor
city bij (click) event

“No provider for CityService”

Solution: inject in `app.module.ts`



Service injecteren in Module

Alleen de *referentie* naar CityService is niet voldoende.

Angular moet de service *injecteren* in de module

Gebruik de annotatie `providers: [...]`

```
// Module declaration
```

```
@NgModule({  
  imports      : [BrowserModule],  
  declarations: [AppComponent],  
  bootstrap   : [AppComponent],  
  providers    : [CityService] // DI voor service  
})  
  
export class AppModule {  
}
```



Array met
Service-
dependencies

Singleton?

Services zijn (in principe) singletons

- Maar: afhankelijk van de plek waar ze geïntanceerd worden!
- Ze zijn een singleton voor de Component/Module en alle child components.
- Module/Site-wide gebruiken? (aanbevolen) → Instantieer service in `app.module.ts`

Checkpoint

Elke service in Angular 2 is een `class`

Services worden geannoteerd met `@Injectable()`

Service importeren in de component die hem gebruikt

Instantiëren in `constructor()`

Service invoegen in de Module bij `providers: []`

Oefening 5a) + 5b)

Voorbeeld: `\200-services-static`

Oefening....

