Neovim Setup Guide & Reference Sheet

Kickstart.nvim Fork | Neovim 0.12+ (`vim.pack`) | Minimalist UI

1 General & Core UX

`<Leader>`	Space key
`<Esc>`	Clear search highlights
`<leader>q`	Open diagnostic [Q]uickfix (location) list
`<leader>f`	[F]ormat buffer (`conform`; Lua: stylua)
`<leader>z`	Toggle [Z]en Mode (`zen-mode`)
`gcc` / `gc`	Comment line (Normal / Visual), built-in
`u` / `CTRL-r`	[u]ndo / [r]edo change
`.`	Repeat last edit or command
`<Esc><Esc>`	Exit builtin terminal mode

2 File Explorer & Buffers

`-`	Open [Oil.nvim] parent directory
`_`	[Oil]: Open working dir (CWD)
`<BS>` / `h`	[Oil]: Go up one directory
`l`	[Oil]: Open file / enter folder
`g.`	[Oil]: Toggle hidden files
`<leader>bd`	Smart [B]uffer [D]elete (to Oil)
`:bd[!]` / `:bdelete[!]`	Aliased to `:Bd[!] [N|name]`
`<C-h,j,k,l>`	Focus window (L/D/U/R)

3 Vim Text Motions

`h, j, k, l`	Move Left, Down, Up, Right
`w` / `b`	Move [w]ord forward / [b]ackward
`e` / `ge`	End of word / End of previous word
`0` / `$`	Beginning / End of line
`^` / `g_`	First / Last non-blank character
`{` / `}`	Previous / Next paragraph
`%`	Jump to matching pair `()[]{}`
`gg` / `G`	Top / Bottom of buffer
`M, H, L`	[M]iddle, [H]igh, [L]ow of screen
`CTRL-u / d`	Scroll half-page [u]p / [d]own
`f/t <char>`	Find / Till next char on line
`F/T <char>`	Find / Till previous char on line
`; / ,`	Repeat last find/till (fwd / rev)
`* / #`	Search word under cursor (fwd / rev)

4 AI & Security Plugins

`<Tab>`	Accept Supermaven AI suggestion
`<C-j>`	Accept next word of AI suggestion
`<C-]>`	Clear AI suggestion
`:SupermavenUseFree`	Choose free tier (first run)
`:SupermavenUsePro`	Link a Pro account
`<leader>tc`	[T]oggle [C]loak masking
`<leader>cp`	[C]loak: [P]review current line
Cloak.nvim:	Masks `.env*`, `secrets.*`, PEM
Wakatime:	Coding metrics tracking.

5 Search & Fuzzy Finder (Telescope)

`<leader>sf`	[S]earch [F]iles (including hidden)
`<leader>sg`	[S]earch by [G]rep (live grep)
`<leader>sw`	[S]earch current [W]ord
`<leader>sd`	[S]earch [D]iagnostics
`<leader>sh`	[S]earch [H]elp tags
`<leader>sk`	[S]earch [K]eymaps
`<leader>ss`	[S]earch [S]elect Telescope builtin
`<leader>sr`	[S]earch [R]esume last search
`<leader>s.`	[S]earch Recent Files
`<leader>sc`	[S]earch [C]ommands
`<leader><leader>`	Search existing open buffers
`<leader>/`	Fuzzily search in current buffer
`<leader>s/`	Live Grep across open buffers
`<leader>sn`	[S]earch [N]eovim config files

6 LSP & Language Intelligence

`grd`	[G]oto [D]efinition
`grr`	[G]oto [R]eferences
`gri`	[G]oto [I]mplementation
`grt`	[G]oto [T]ype Definition
`grD`	[G]oto [D]eclaration
`grn`	[R]e[n]ame symbol
`gra`	Code [A]ction
`gO`	Document Symbols
`gW`	Workspace Symbols
`<leader>th`	[T]oggle Inlay [H]ints
`:Mason`	Manage LSP/fmt/lint tools
Format/Completion:	`conform.nvim`, `blink.cmp`
LSP enabled:	`lua_ls` only
Treesitter:	bash, c, html, lua, markdown, vim (+ auto-install on open)

7 Git Integration (Gitsigns)

`]c` / `[c`	Next / Previous Git change hunk
`<leader>hs`	Stage hunk (Normal & Visual)
`<leader>hr`	Reset hunk (Normal & Visual)
`<leader>hS`	Stage entire buffer
`<leader>hR`	Reset entire buffer
`<leader>hp`	Preview hunk
`<leader>hi`	Preview hunk inline
`<leader>hb`	Blame current line
`<leader>hd`	Diff against index
`<leader>hD`	Diff against last commit
`<leader>hq` / `hQ`	Hunks to quickfix (file / repo)
`<leader>tb`	[T]oggle line blame
`<leader>tw`	[T]oggle intra-line word diff
`ih`	Text object: inside hunk (o/x)

8 Text Objects & Mini Plugins

`va)`	[V]isually select [A]round [)]paren
`ci"`	[C]hange [I]nside ["]quotes
`cii"`	Change inside *next* quotes
`aa`	Around *next* (was `an`)
`saiw)`	[S]urround [A]dd [I]nner [W]ord [)]
`sd'`	[S]urround [D]elete [']quote
`sr)'`	[S]urround [R]eplace [)] with [']
Mini Modules:	`mini.ai`, `mini.surround`, `mini.statusline`, `mini.icons`

9 Assembly Viewer (C/C++/Rust)

`<leader>a`	[A]sm: function under cursor
`<leader>a` (visual)	[A]sm: selected lines (`:Asm`)
`+` / `-`	In window: raise / lower `-O` level
`R`	In window: recompile
`q` / `<Esc>`	In window: close

10 Jumplist, Marks & Macros

`CTRL-o`	Jump to older position in jumplist
`CTRL-i`	Jump to newer position (same key as `<Tab>`)
`m[a-z]`	Set local [m]ark
`'[a-z]`	Jump to mark line
`` `[a-z] ``	Jump to exact mark position
`q[a-z]`	Record macro into register
`q`	Stop macro recording
`@[a-z]`	Play macro from register
`@@`	Repeat last executed macro