

Machine Learning - SS 2021

Exercise 3: Synthetic Data

Federico Ambrogi, e1449911@student.tuwien.ac.at
Adam Höfler, e11847620@student.tuwien.ac.at
Matteo Panzeri 12039996@student.tuwien.ac.at
TU Wien

July 25, 2021

Contents

1	Data Sets Description	1
1.1	Income Data Set	2
1.2	Titanic Data Set	4
1.3	Social Data Set	5
2	Workflow Overview and Code Structure	6
3	Data Exploration and Pre-processing	6
3.1	Data Overview	6
4	Generation of Synthetic Data	7
5	Model Implementation and Evaluation	7
6	Confusion Matrices	7
7	Conclusion	7

Introduction

In this document we describe the results of the implementation of synthesizing algorithms to create synthetic replicas of three different data sets. We test them for their ability to create replicas of the original data set.

1 Data Sets Description

Here we briefly introduce our datasets, analyze the distributions of the input data and check for significant correlations between variables.

1.1 Income Data Set

The data set [1] provides us information about people, like: age, workclass, education, marital-status, occupation, capital-gain, ecc...

Our purpose is to determine if a person income is lower or greater than a given value specifically the threshold is 50000 Dollars per year. The distribution of a selection of relevant features, as well as a scatter plot to highlight pair-wise correlations are shown in Fig. 5, while a more general view on the correlations including all features are shown in Fig. 6.




Figure 1: Distributions and pair-wise correlation for the features of the "income" data set.




Figure 2: Correlation matrix for the "income" data set.

1.2 Titanic Data Set

The Titanic data set [2] contains informations about the Titanic's passengers. Given the observations we want to determine if a given person, represented by an observation, will survive on the Titanic. Some features of the dataset are: Name, sex, age, Passenger class, ticket fare, where the passenger embarked, etc.




Figure 3: Distributions and pair-wise correlation for the features of the "social" data set.




Figure 4: Correlation matrix for the "social" data set.

1.3 Social Data Set

The Social network ads data set [3] collects information about social network users in particular age,sex and income. Our objective is to understand if an user will buy the advised good.




Figure 5: Distributions and pair-wise correlation for the features of the "Titanic" data set.




Figure 6: Correlation matrix for the "Titanic" data set.

2 Workflow Overview and Code Structure

Here we outline the structure of the code. The Project is build using the *python3.8* language and various standard libraries such as *pandas* and *numpy* (for basic data import and analysis), *sklearn* (sci-kit learn for model training and evaluation), (for the creation of the synthetic data sets), *matplotlib* and *seaborn* for data visualization.

The project includes five different scripts that perform different tasks:

- *clean_dataset.py*: module for the loading and cleaning of the input data sets. It reads the input data sets as *pandas* data frames, which are the main format handled by the library for model training. Among the cleaning of the data, we find the outlier removals and data rescaling;
- *generate_data.py*: module for the creating of synthetic data, based on the *SDV* library;
- *classifier.py*: main module of the project, contains the main functionalities to perform all the steps from data loading, cleaning, generation of synthetic data, model training and comparison of results;
- *utils.py*: module containing utilities e.g. for data plotting;

In addition, a directory named "input_data" is used to contain the input data sets as well as their respective cleaned version. To run the entire project it is sufficient to first call the *clean_dataset.py* module e.g.

```
python3.8 clean_dataset.py
```

This step will produce the cleaned data set inside the same "input_data" directory as well as some control plots to show the distributions and correlation of the data.

In the second step it is required to run with

```
python3.8 classifier.py
```

that follows the following procedure:

1. splitting of the original cleaned dataset into *train* and *test* sets, using a ratio of 70% – 30% respectively;
2. training and evaluation of the original dataset using the chosen classifier (random forest);
3. creation of the synthetic data sets, using the training set from the previous splitting of the original dataset, for the three models GaussianCopula, CTGAN and Copula GAN (see 4);
4. evaluate the models trained with the original and the synthetic dataset with the test set, obtained from the original model.

3 Data Exploration and Pre-processing

In this section we describe the necessary preliminary steps to import and prepare the data to make them suitable for the learning algorithms.

The steps are handled by the script *data_preparation.py* which includes dedicated function to pre-process each data set.

3.1 Data Overview

Here we provide an overview of the original data.

Missing Value The

Normalization The

Labelling In all datasets were present not numeric features. In order to synthetize them was necessary to change the strings into numeric values. In order to do so we used the `cat.code` method in this way for every not numeric features all the possible values where labelled using a different value. Using the labelling we had the possibility to use the three models.

4 Generation of Synthetic Data

In order to generate the synthetic data we relied on three different generation models. The models are defined in the *SDV* library. The three models aim to generate a synthetic data set whose properties are the same as in the original dataset. The three models we used are: GaussianCopula model, CTGAN model, CopulaGAN model. We now describe the idea behind these three models as reported on the SDV library user guide.

GaussianCopula The Gaussian copula model [4] is based on copulas which are distributions on $[0;1]^d$ which is constructed from a multivariate normal distribution over \mathbb{R}^d by using the probability integral transform. Intuitively, a copula is a mathematical function that allows us to describe the joint distribution of multiple random variables by analyzing the dependencies between their marginal distributions.

CTGAN model The `sdv.tabular.CTGAN` model [5] is based on the GAN-based Deep Learning data synthesizer which was presented at the NeurIPS 2020 conference by the paper titled "Modeling Tabular data using Conditional GAN".

Copula GAN The `sdv.tabular.CopulaGAN` model [6] is a variation of the CTGAN Model which takes advantage of the CDF based transformation that the GaussianCopulas apply to make the underlying CTGAN model task of learning the data easier.

5 Model Implementation and Evaluation

To train our model, we used the *sci-kit learn* implementation of a random forest algorithm *RandomForestClassifier()* with default parameters. We did not try to optimize the classification algorithm since we were more interested in comparing the results using the original and synthetic data sets.

As outlined in the previous section, we classified both the original and synthetic data set and create the corresponding confusion matrices. Each entry i, j corresponds to the number of observations in group i , but predicted to be in group j . We normalize the entries according to the sum of each row. Since it is a binary classification, the matrix reduces to the number of true negatives (TN), false positives (FP), false negatives (FN) and true positives (TP). We then analyzed the performance of the implementation using precision (P) and recall (R), defined as :

$$P = \frac{TP}{TP + FP} \quad R = \frac{TP}{TP + FN} \quad A = \frac{TP + TN}{all} \quad (1)$$

6 Confusion Matrices

In this section we present the results of the confusion matrices, obtained after training our random forest classifier on the original data set and on the three different synthetic data sets. Results for the titanic, income and social data sets are shown respectively in Figures 7, 8 and 9.

7 Conclusion




Figure 7: Correlation matrices for the "Titanic" data set: original dataset (top-left panel), Gaussian Copula synthetic data set (top-right panel), GAN synthetic data set (bottom-left panel) and GAN Copula synthetic data set (bottom-right panel).




Figure 8: Correlation matrices for the "Income" data set: original dataset (top-left panel), Gaussian Copula synthetic data set (top-right panel), GAN synthetic data set (bottom-left panel) and GAN Copula synthetic data set (bottom-right panel).




Figure 9: Correlation matrices for the "Social" data set: original dataset (top-left panel), Gaussian Copula synthetic data set (top-right panel), GAN synthetic data set (bottom-left panel) and GAN Copula synthetic data set (bottom-right panel).

References

- [1] Ronny Kohavi and Barry Becker. Uci - adult data set. <https://archive.ics.uci.edu/ml/datasets/Adult>. Accessed: 11.07.2021.
- [2] Kaggle - titanic, machine learning from disaster. <https://www.kaggle.com/c/titanic/data>. Accessed: 11.07.2021.
- [3] Kaggle - social network ads. <https://www.kaggle.com/rakeshrau/social-network-ads>. Accessed: 11.07.2021.
- [4] Sdv. https://sdv.dev/SDV/user_guides/single_table/gaussian_copula.html#what-is-gaussiancopula. Accessed: 11.07.2021.
- [5] Sdv. https://sdv.dev/SDV/user_guides/single_table/ctgan.html#what-is-ctgan. Accessed: 11.07.2021.
- [6] Sdv. https://sdv.dev/SDV/user_guides/single_table/copulagan.html. Accessed: 11.07.2021.