

# Application Security Alert Report

**Customer Name**

## **Confidential**

This document is SENSITIVE AND CONFIDENTIAL, and is intended for distribution only to the named recipient. Its contents may not be copied, posted, disclosed or used by third parties in any way not expressly authorized by COMPANYNAME. The reception and use of this document by the recipient, explicitly implies acceptance of these terms.

# Multiple X-Frame-Options Header Entries

## Description

X-Frame-Options (XFO) headers were found, a response with multiple XFO header entries may not be predictably treated by all user-agents.

## Risk

Medium

## Reliability

Medium

## URLs

1-<https://stage.thumbsignin.com/terms>

Parameters: X-Frame-Options

2-<https://stage.thumbsignin.com/privacy>

Parameters: X-Frame-Options

3-<https://stage.thumbsignin.com/pricing>

Parameters: X-Frame-Options

4-<https://stage.thumbsignin.com/partners>

Parameters: X-Frame-Options

5-<https://stage.thumbsignin.com/login>

Parameters: X-Frame-Options

6-<https://stage.thumbsignin.com/features>

Parameters: X-Frame-Options

7-<https://stage.thumbsignin.com/documentation/windows>

Parameters: X-Frame-Options

8-<https://stage.thumbsignin.com/documentation/web>

Parameters: X-Frame-Options

9-<https://stage.thumbsignin.com/documentation/ios>

Parameters: X-Frame-Options

10-<https://stage.thumbsignin.com/documentation/azure>

Parameters: X-Frame-Options

11-<https://stage.thumbsignin.com/documentation/android>

Parameters: X-Frame-Options

12-<https://stage.thumbsignin.com/blockchain>

Parameters: X-Frame-Options

13-<https://stage.thumbsignin.com/>

Parameters: X-Frame-Options

## **Solution**

Ensure only a single X-Frame-Options header is present in the response.

## **References**

<https://tools.ietf.org/html/rfc7034>

# HTTP Parameter Override

## Description

Unspecified form action: HTTP parameter override attack potentially possible. This is a known problem with Java Servlets but other platforms may also be vulnerable.

## Risk

Medium

## Reliability

Low

## URLs

1-<https://stage.thumbsignin.com/pricing>

Evidence: <form>

2-<https://stage.thumbsignin.com/>

Evidence: <form>

## Solution

All forms must specify the action URL.

## References

<http://download.oracle.com/javaee-archive/servlet-spec.java.net/jsr340-experts/att-0317/OnParameterPollutionAttacks.pdf>

# Absence of Anti-CSRF Tokens

## Description

No Anti-CSRF tokens were found in a HTML submission form.

A cross-site request forgery is an attack that involves forcing a victim to send an HTTP request to a target destination without their knowledge or intent in order to perform an action as the victim. The underlying cause is application functionality using predictable URL/form actions in a repeatable way. The nature of the attack is that CSRF exploits the trust that a web site has for a user. By contrast, cross-site scripting (XSS) exploits the trust that a user has for a web site. Like XSS, CSRF attacks are not necessarily cross-site, but they can be. Cross-site request forgery is also known as CSRF, XSRF, one-click attack, session riding, confused deputy, and sea surf.

CSRF attacks are effective in a number of situations, including:

- \* The victim has an active session on the target site.
- \* The victim is authenticated via HTTP auth on the target site.
- \* The victim is on the same local network as the target site.

CSRF has primarily been used to perform an action against a target site using the victim's privileges, but recent techniques have been discovered to disclose information by gaining access to the response. The risk of information disclosure is dramatically increased when the target site is vulnerable to XSS, because XSS can be used as a platform for CSRF, allowing the attack to operate within the bounds of the same-origin policy.

## Risk

Low

## Reliability

Medium

## URLs

1-<https://stage.thumbsignin.com/pricing>

Evidence: <form>

Other Information: No known Anti-CSRF token [anticsrf, CSRFToken, \_\_RequestVerificationToken, csrfmiddlewaretoken, authenticity\_token, OWASP\_CSRFTOKEN, anoncsrf] was found in the following HTML form: [Form 1: "Enter Your Work Email Address.." ].

2-<https://stage.thumbsignin.com/blog/sample-page/>

Evidence: <form role="search" method="get" class="search-form" action="https://stage.thumbsignin.com/blog/">

Other Information: No known Anti-CSRF token [anticsrf, CSRFToken, \_\_RequestVerificationToken, csrfmiddlewaretoken, authenticity\_token, OWASP\_CSRFTOKEN, anoncsrf] was found in the following HTML form: [Form 1: "s" ].

3-<https://stage.thumbsignin.com/blog/category/uncategorized/>

Evidence: <form role="search" method="get" class="search-form" action="https://stage.thumbsignin.com/blog/">

Other Information: No known Anti-CSRF token [anticsrf, CSRFToken, \_\_RequestVerificationToken, csrfmiddlewaretoken, authenticity\_token, OWASP\_CSRFTOKEN, anoncsrf] was found in the following HTML form: [Form 1: "s" ].

4-<https://stage.thumbsignin.com/blog/blog/>

Evidence: <form role="search" method="get" class="search-form" action="https://stage.thumbsignin.com/blog/">

Other Information: No known Anti-CSRF token [anticsrf, CSRFToken, \_\_RequestVerificationToken, csrfmiddlewaretoken, authenticity\_token, OWASP\_CSRFTOKEN, anoncsrf] was found in the following HTML form: [Form 1: "s" ].

5-<https://stage.thumbsignin.com/blog/2018/07/16/hello-world/>

Evidence: <form role="search" method="get" class="search-form" action="https://stage.thumbsignin.com/blog/">

Other Information: No known Anti-CSRF token [anticsrf, CSRFToken, \_\_RequestVerificationToken, csrfmiddlewaretoken, authenticity\_token, OWASP\_CSRFTOKEN, anoncsrf] was found in the following HTML form: [Form 2: "s" ].

6-<https://stage.thumbsignin.com/blog/2018/07/16/hello-world/>

Evidence: <form action="https://stage.thumbsignin.com/blog/wp-comments-post.php" method="post" id="commentform" class="comment-form" novalidate>

Other Information: No known Anti-CSRF token [anticsrf, CSRFToken, \_\_RequestVerificationToken, csrfmiddlewaretoken, authenticity\_token, OWASP\_CSRFTOKEN, anoncsrf] was found in the following HTML form: [Form 1: "author" "email" "url" "submit" "comment\_post\_ID" "comment\_parent" ].

7-<https://stage.thumbsignin.com/blog/2018/07/>

Evidence: <form role="search" method="get" class="search-form" action="https://stage.thumbsignin.com/blog/">

Other Information: No known Anti-CSRF token [anticsrf, CSRFToken, \_\_RequestVerificationToken, csrfmiddlewaretoken, authenticity\_token, OWASP\_CSRFTOKEN, anoncsrf] was found in the following HTML form: [Form 1: "s" ].

8-<https://stage.thumbsignin.com/blog/>

Evidence: <form role="search" method="get" class="search-form" action="https://stage.thumbsignin.com/blog/">

Other Information: No known Anti-CSRF token [anticsrf, CSRFToken, \_\_RequestVerificationToken, csrfmiddlewaretoken, authenticity\_token, OWASP\_CSRFTOKEN, anoncsrf] was found in the following HTML form: [Form 1: "s" ].

9-<https://stage.thumbsignin.com/>

Evidence: <form>

Other Information: No known Anti-CSRF token [anticsrf, CSRFToken, \_\_RequestVerificationToken, csrfmiddlewaretoken, authenticity\_token, OWASP\_CSRFTOKEN, anoncsrf] was found in the following HTML form: [Form 1: "Enter Your Work Email Address.." ].

## **Solution**

Phase: Architecture and Design

Use a vetted library or framework that does not allow this weakness to occur or provides constructs that make this weakness easier to avoid.

For example, use anti-CSRF packages such as the OWASP CSRFGuard.

Phase: Implementation

Ensure that your application is free of cross-site scripting issues, because most CSRF defenses can be bypassed using attacker-controlled script.

Phase: Architecture and Design

Generate a unique nonce for each form, place the nonce into the form, and verify the nonce upon receipt of the form. Be sure that the nonce is not predictable (CWE-330).

Note that this can be bypassed using XSS.

Identify especially dangerous operations. When the user performs a dangerous operation, send a separate confirmation request to ensure that the user intended to perform that operation.

Note that this can be bypassed using XSS.

Use the ESAPI Session Management control.

This control includes a component for CSRF.

Do not use the GET method for any request that triggers a state change.

Phase: Implementation

Check the HTTP Referer header to see if the request originated from an expected page. This could break legitimate functionality, because users or proxies may have disabled sending the Referer for privacy reasons.

## **References**

<http://projects.webappsec.org/Cross-Site-Request-Forgery>

<http://cwe.mitre.org/data/definitions/352.html>

# Cross-Domain JavaScript Source File Inclusion

## Description

The page includes one or more script files from a third-party domain.

## Risk

Low

## Reliability

Medium

## URLs

1-<https://stage.thumbsignin.com/terms>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`

2-<https://stage.thumbsignin.com/privacy>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`

3-<https://stage.thumbsignin.com/pricing>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`

4-<https://stage.thumbsignin.com/partners>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`

5-<https://stage.thumbsignin.com/login>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`

6-<https://stage.thumbsignin.com/features>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`



7-<https://stage.thumbsignin.com/documentation/windows>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`

8-<https://stage.thumbsignin.com/documentation/web>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`

9-<https://stage.thumbsignin.com/documentation/ios>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`

10-<https://stage.thumbsignin.com/documentation/azure>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`

11-<https://stage.thumbsignin.com/documentation/android>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`

12-<https://stage.thumbsignin.com/blockchain>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`

13-<https://stage.thumbsignin.com/>

Parameters: <https://www.googletagmanager.com/gtag/js?id>

Attack: UA-124590242-1

Evidence: `<script async="" src="https://www.googletagmanager.com/gtag/js?id=UA-124590242-1"></script>`

## Solution

Ensure JavaScript source files are loaded from only trusted sources, and the sources can't be controlled by end users of the application.

# Cookie Without Secure Flag

## Description

A cookie has been set without the secure flag, which means that the cookie can be accessed via unencrypted connections.

## Risk

Low

## Reliability

Medium

## URLs

1-<https://stage.thumbsignin.com/blogs>

Parameters: PHPSESSID

Evidence: Set-Cookie: PHPSESSID

## Solution

Whenever a cookie contains sensitive information or is a session token, then it should always be passed using an encrypted channel. Ensure that the secure flag is set for cookies containing such sensitive information.

## References

[http://www.owasp.org/index.php/Testing\\_for\\_cookies\\_attributes\\_\(OWASP-SM-002\)](http://www.owasp.org/index.php/Testing_for_cookies_attributes_(OWASP-SM-002))

# Cookie No HttpOnly Flag

## Description

A cookie has been set without the HttpOnly flag, which means that the cookie can be accessed by JavaScript. If a malicious script can be run on this page then the cookie will be accessible and can be transmitted to another site. If this is a session cookie then session hijacking may be possible.

## Risk

Low

## Reliability

Medium

## URLs

1-<https://stage.thumbsignin.com/blogs>

Parameters: PHPSESSID

Evidence: Set-Cookie: PHPSESSID

## Solution

Ensure that the HttpOnly flag is set for all cookies.

## References

<http://www.owasp.org/index.php/HttpOnly>

# Information Disclosure - Suspicious Comments

## Description

The response appears to contain suspicious comments which may help an attacker.

## Risk

Informational

## Reliability

Medium

## URLs

1-[https://stage.thumbsignin.com/thumbsign\\_widget.js](https://stage.thumbsignin.com/thumbsign_widget.js)

Other Information: 'USER\_BLOCKED': 'User is blocked from Registration',

'DEVICE\_BLOCKED': 'Device is blocked from Login',

//TODO: hard refresh, reset to get new configs updated

```
elem: '<div class="tsmodal-footer"><p class="more-info more-info2" >' + config.sms.smsTitle +
'</p><div class="more-info"><div class="d-box"><p id="sms_result" class="more-info"></p><div
class="db-b"><input type="text" placeholder="123 456 7890" id="phone" maxlength="10"><img
class="d-arrow-b" src="" + url + '/styles/img/icons-8-sent-filled.png"/></div></div></div></div>',
style: '.more-info{margin:0 auto;max-width:248px}.db-b
img.d-arrow-b{position:absolute;right:50px;padding:10px 5px;cursor:pointer}'
```

2-<https://stage.thumbsignin.com/terms>

Other Information:

```
<script>window.App={"apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":f
alse,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isErro
r":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError
":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}}</script>
```

3-<https://stage.thumbsignin.com/privacy>

Other Information:

```
<script>window.App={"apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":f
alse,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isErro
r":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError
":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}}</script>
```

4-<https://stage.thumbsignin.com/pricing>

Other Information:

```
<script>window.App={"apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":f
alse,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isErro
r":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError
```

":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}}</script>

5-<https://stage.thumbssignin.com/partners>

Other Information:

```
<script>window.App={"apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":false,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isError":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}}</script>
```

6-<https://stage.thumbssignin.com/login>

Other Information:

```
<script>window.App={"apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":false,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isError":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}}</script>
```

7-<https://stage.thumbssignin.com/features>

Other Information:

```
<script>window.App={"apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":false,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isError":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}}</script>
```

8-<https://stage.thumbssignin.com/documentation/windows>

Other Information:

```
<script>window.App={"apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":false,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isError":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}}</script>
```

9-<https://stage.thumbssignin.com/documentation/web>

Other Information:

```
<script>window.App={"apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":false,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isError":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}}</script>
```

10-<https://stage.thumbssignin.com/documentation/ios>

Other Information:

```
<script>window.App={"apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":false,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isError":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}}</script>
```

11-<https://stage.thumbsignin.com/documentation/azure>

Other Information:

```
<script>window.App={ "apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":false,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isError":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}} </script>
```

12-<https://stage.thumbsignin.com/documentation/android>

Other Information:

```
<script>window.App={ "apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":false,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isError":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}} </script>
```

13-<https://stage.thumbsignin.com/blockchain>

Other Information:

```
<script>window.App={ "apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":false,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isError":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}} </script>
```

14-<https://stage.thumbsignin.com/assets/vendor.js>

Other Information: // bind timers to global for call from export context

```
var $from = function from(source /* , mapfn, thisArg */) {
  // TODO: add validation descriptor w/o calling accessors
  return $from.call(TypedArray, data);
  // `ws` module bug, temporarily remove validation length for Uint8Array
  return $from.call(TypedArray, data);
  from: $from,
  // Thrash, waste and sodomy: IE GC bug
  // getting tag from 19.1.3.6 Object.prototype.toString()
  // https://bugs.chromium.org/p/v8/issues/detail?id=4118
  // https://bugs.chromium.org/p/v8/issues/detail?id=3056
  // https://bugs.chromium.org/p/v8/issues/detail?id=3056
  var from;
  from = Object(arguments[s]);
  for (var key in from) {
    if (hasOwnProperty.call(from, key)) {
      to[key] = from[key];
    }
  }
  symbols = getOwnPropertySymbols(from);
  if (propIsEnumerable.call(from, symbols[i])) {
    to[symbols[i]] = from[symbols[i]];
  }
}
```

```

Array.from(riter, function () { throw 2; });
$export($export.S, COLLECTION, { from: function from(source /* , mapFn, thisArg */) {
// IE 8- don't enum bug keys
// Old FF bug
// Tor Browser bug
// strange IE + webpack dev server bug - use .call(global)
// iOS Safari 7.x bug
// fail the render phase where it didn't fail before. So we log it.
invariant(typeof typeSpecs[typeSpecName] === 'function', '%s: %s type `%s` is invalid; it must be a
function, usually from ' + 'the `prop-types` package, but received `%s`.', componentName || 'React class',
location, typeSpecName, typeof typeSpecs[typeSpecName]);
* If the function has been minified and NODE_ENV !== 'production', warn the user.
// TODO: If another transition starts while we're still confirming
// Return false from a transition hook to cancel the transition.
__WEBPACK_IMPORTED_MODULE_0_warning___default()(!nextProps.location &&
!this.props.location), '<Route> elements should not change from uncontrolled to controlled (or vice versa). You
initially used no "location" prop and then provided one on a subsequent render.');
```

\_\_WEBPACK\_IMPORTED\_MODULE\_0\_warning\_\_\_default()(!nextProps.location &&
this.props.location), '<Route> elements should not change from controlled to uncontrolled (or vice versa). You
provided a "location" prop initially but omitted it on a subsequent render.');

```

computedMatch: __WEBPACK_IMPORTED_MODULE_3_prop_types___default.a.object, // private, from
<Switch>
// TODO: If another transition starts while we're still confirming
// Return false from a transition hook to cancel the transition.
try { // Avoid failures from read-only properties
// Don't enum bug & hidden keys
// should work with symbols and should have deterministic property order (V8 bug)
var from = toAbsoluteIndex(start, len);
var count = Math.min((end === undefined ? len : toAbsoluteIndex(end, len)) - from, len - to);
if (from < to && to < from + count) {
from += count - 1;
if (from in O) O[to] = O[from];
from += inc;
var from = __webpack_require__(149);
return from(this);
compute new props from state, props, and dispatch. For example:
// If this component received store from props, its subscription should be transparent
// to any descendants receiving store+subscription from context; it passes along
// To handle the case where a child component may have triggered a state change by
// dispatching an action in its componentWillMount, we have to re-run the select and maybe
// parentSub's source should match where store came from: props vs. context. A component
// connected to the store via props shouldn't use subscription from context, or vice versa.
// `notifyNestedSubs` is duplicated to handle the case where the component is unmounted in
```

```

    // the middle of the notification loop, where `this.subscription` will then be null. An
    // instance, preventing the instance from being garbage collected, and that would be bad
* to hydrate the state from the server in universal apps, or to restore a
* previously serialized user session.
* You may call `dispatch()` from a change listener, with the following
* a good idea to keep actions serializable so you can record and replay user
    * be used to unsubscribe the observable from the store, and prevent further
    * emission of values from the observable.
* Composes single-argument functions from right to left. The rightmost
* from right to left. For example, compose(f, g, h) is identical to doing
// A length of one signals that mapToProps does not depend on props from the parent component.
* if you have asynchronously-loaded routes, so reading from and relying on
    // TODO: We could probably make this more reliable by
var from = arguments.length > 1 && arguments[1] !== undefined ? arguments[1] : "";
var fromParts = from && from.split('/') || [];
var isFromAbs = from && isAbsolute(from);
* Returns true if the HTML5 history API is supported. Taken from Modernizr.
* The public API for prompting the user before navigating away
* from a screen with a component.
from: __WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.string,
* Returns true if the HTML5 history API is supported. Taken from Modernizr.
    __WEBPACK_IMPORTED_MODULE_2_warning___default()(!(nextProps.location &&
!this.props.location), '<Switch> elements should not change from uncontrolled to controlled (or vice versa).
You initially used no "location" prop and then provided one on a subsequent render.');
```

```

    __WEBPACK_IMPORTED_MODULE_2_warning___default()(!(nextProps.location &&
this.props.location), '<Switch> elements should not change from controlled to uncontrolled (or vice versa). You
provided a "location" prop initially but omitted it on a subsequent render.');
```

```

    from = _element$props.from;
    var path = pathProp || from;
// V8 bug: https://code.google.com/p/v8/issues/detail?id=3509
// Tor Browser bug: Math.acosh(Infinity) -> NaN
// Tor Browser bug: Math.asinh(0) -> -0
// Tor Browser bug: Math.atanh(-0) -> 0
$export($export.S + $export.F * !__webpack_require__(63)(function (iter) { Array.from(iter); })), 'Array', {
    // 22.1.2.1 Array.from(arrayLike, mapfn = undefined, thisArg = undefined)
    from: function from(arrayLike /* , mapfn = undefined, thisArg = undefined */) {
        // V8 bug
        // v8 6.6 (Node 10 and Chrome 66) have a bug with resolving custom thenables
        // https://bugs.chromium.org/p/chromium/issues/detail?id=830565
        // FF Nightly sets third argument as `new.target`, but does not create `this` from it
        // https://tc39.github.io/proposal-setmap-offrom/#sec-map.from
        // https://tc39.github.io/proposal-setmap-offrom/#sec-set.from
        // https://tc39.github.io/proposal-setmap-offrom/#sec-weakmap.from

```



```
// https://tc39.github.io/proposal-setmap-offrom/#sec-weakset.from
var from = __webpack_require__(149);
return pKeys.length ? oKeys.length ? from(new Set(oKeys.concat(pKeys))) : pKeys : oKeys;
from: function from(x) {
  CSSRuleList: true, // TODO: Not spec compliant, should be false.
  MediaList: true, // TODO: Not spec compliant, should be false.
  StyleSheetList: true, // TODO: Not spec compliant, should be false.
  // Returning this object from the innerFn has the same effect as
    // only option is to throw it from the await expression, and
    // Avoid propagating failures to Promises returned by later
    // If an exception is thrown from innerFn, we leave state ===
  // result, either by returning a { value, done } result from the
    // If maybeInvokeDelegate(context) changed context.method from
  // object to not be returned from this call. This ensures that doesn't happen.
    // or a finally block) gives us a place to store values thrown from
    // locations where there is no enclosing try statement.
  // TODO: this is special because it gets imported during build.
  // Experimental error-boundary API that can recover from errors within a single
  * Forked from fbjs/warning:
    warning(false, "Can't call %s on a component that is not yet mounted. " + "This is a no-op, but it might
  indicate a bug in your application. ' + 'Instead, assign to `this.state` directly or define a `state = {}`; ' + 'class
  property with the desired state in the %s component.', callerName, componentName);
    * properties which is confusing. TODO: Expose pendingState or don't use it
    * from this.* because your function may be called after receiveProps but before
    * @param {*} self A *temporary* helper to detect places where `this` is
    * different from the `owner` when React.createElement is called, so that we
    // the validation flag non-enumerable (where possible, which should
    // equal for testing purposes and therefore we hide it from enumeration.
    // Silently steal the ref from the parent.
    * TODO: Test that a single child and an array with one item have the same key
    childOwner = ' It was passed a child from ' + getComponentName(element._owner) + '.';
    // but now we print a separate warning for them later.
    info += ' You likely forgot to export your component from the file ' + "it's defined in, or you might have
  mixed up default and named imports.";
    // TODO: Drop this when these are no longer allowed as the type argument.
    // TODO: remove in React 17.0.
  // TODO: decide on the top-level export form.
  // "Pause on exceptions" behavior. Because React wraps all user-provided
  // invokeGuardedCallback uses a try-catch, all user exceptions are treated
  // unintuitive, though, because even though React has caught the error, from
  // DOM node, and call the user-provided callback from inside an event handler
    !(typeof document !== 'undefined') ? invariant(false, 'The `document` global was defined when React was
  initialized, but is not defined anymore. This can happen in a test environment if a component schedules an
```

```

update from an asynchronous callback, but the test has already finished running. To solve this, you can either
unmount the component at the end of your test (and ensure that any asynchronous operations get canceled in
`componentWillUnmount`), or you can change the test itself to be asynchronous.') : void 0;
    // Keeps track of whether the user-provided callback threw an error. We
    // call the user-provided callback.
    // We immediately remove the callback from event listeners so that
    // Synchronously dispatch our fake event. If the user-provided function
    * it in a global so it can be rethrown by `rethrowCaughtError` later.
    * TODO: See if `_caughtError` and `_rethrowError` can be unified.
    invariant(false, 'clearCaughtError was called but no error was captured. This error is likely caused by a bug
in React. Please file an issue.');
```

- \* Injectable mapping from names to event plugin modules.
- \* Mapping from event name to dispatch config
- \* Mapping from registration name to plugin module
- \* Mapping from registration name to event name
- \* Mapping from lowercase registration names to the properly cased version,
- \* to be decoupled from injection of the actual plugins so that ordering is
- \* @param {object} injectedNamesToPlugins Map from names to plugin modules.

```

return tag === 'button' || tag === 'input' || tag === 'select' || tag === 'textarea';
    * @param {object} injectedNamesToPlugins Map from names to plugin modules.
    // TODO: shouldPreventMouseEvent is DOM-specific and definitely should not
    * Allows registered plugins an opportunity to extract events from top-level
    // TODO: If this is a HostRoot we might want to bail out.
function traverseEnterLeave(from, to, fn, argFrom, argTo) {
    var common = from && to ? getLowestCommonAncestor(from, to) : null;
    if (!from) {
    if (from === common) {
        var alternate = from.alternate;
        pathFrom.push(from);
        from = getParent(from);
    * propagation strategies from actually executing the dispatches, since we
function accumulateEnterLeaveDispatches(leave, enter, from, to) {
    traverseEnterLeave(from, to, accumulateDispatches, leave, enter);
// Instead use constants exported from DOMTopLevelEventTypes in ReactDOM.
    // to check if the un-prefixed events are usable, and if not remove them from the map.
    * The rest of ReactDOM code should import top level types from this file.
    * Identify the node where selection currently begins, then observe
    * (cut, copy, select-all, etc.) even though no character is inserted.
    // Inject data generated from fallback path into the synthetic event.
    * @param {TopLevelType} topLevelType Number from `TopLevelType`.
    * @param {number} topLevelType Number from `TopLevelEventTypes`.
    // try to extract the composed characters from the fallback object.
    // IE fires the `keypress` event when a user types an emoji via
```

```

!(fiberHostComponent && typeof fiberHostComponent.restoreControlledState === 'function') ?
invariant(false, 'Fiber needs to be injected to handle a fiber target for controlled events. This error is likely
caused by a bug in React. Please file an issue.'): void 0;
* Gets the target node from a native browser event by accounting for
* `reset`, `load`, `error`, and `select`.
* Borrows from Modernizr.
// but it triggers a bug in IE11 and Edge 14/15.
// TODO: Once it's just Fiber we can move this to node._wrapperState
// TODO: This prevents the assignment of defaultValue to regular
// This is a mapping from React prop names to the attribute names.
// Note: there is a special case that prevents it from being written to the DOM
// Note: `option.selected` is not updated if `select.multiple` is
// TODO: direct imports like some-package/src/* are bad. Fix me.
* If `checked` or `value` are not supplied (or null/undefined), user actions
  warning(false, 'A component is changing an uncontrolled input of type %s to be controlled. ' + 'Input
elements should not switch from uncontrolled to controlled (or vice versa). ' + 'Decide between using a
controlled or uncontrolled input ' + 'element for the lifetime of the component. More info:
https://fb.me/react-controlled-components%s', props.type, getCurrentFiberStackAddendum());
  warning(false, 'A component is changing a controlled input of type %s to be uncontrolled. ' + 'Input
elements should not switch from controlled to uncontrolled (or vice versa). ' + 'Decide between using a
controlled or uncontrolled input ' + 'element for the lifetime of the component. More info:
https://fb.me/react-controlled-components%s', props.type, getCurrentFiberStackAddendum());
  // Do not assign value if it is already set. This prevents user text input
  // from being lost during SSR hydration.
  // potentially avoids a DOM write and prevents Firefox (~60.0.1) from
  // value must be assigned before defaultValue. This fixes an issue where the
  // Normally, we'd just do `node.checked = node.checked` upon initial mount, less this bug
  // this is needed to work around a chrome bug where setting defaultChecked
  // Reference: https://bugs.chromium.org/p/chromium/issues/detail?id=608416
  // when the user is inputting text
  return nodeName === 'select' || nodeName === 'input' && elem.type === 'file';
* and override the value property so that we can distinguish user events from
* (For IE <=9) Removes the event listeners from the currently-tracked element,
  // is changed from JS so we redefine a setter for `.value` that updates
  // propertychange on the first input event after setting `value` from a
  // keystroke if user does a key repeat (it'll be a little delayed: right
* - select
* Translation from modifier key to the associated property in the event.
* browser from outside will not fire a `mouseout` event. In this case, we use
  // TODO: Figure out why `ownerDocument` is sometimes undefined in IE8.
var from = void 0;
  from = targetInst;
  // Moving to a node from outside the window.

```

```

    from = null;
    if (from === to) {
    var fromNode = from == null ? win : getNodeFromInstance$1(from);
    var leave = eventInterface.getPooled(leaveEventType, from, nativeEvent, nativeEventTarget);
    accumulateEnterLeaveDispatches(leave, enter, from, to);
    * `ReactInstanceMap` maintains a mapping from a public facing stateful
    * methods to accept the user facing instance as an argument and map them back
    // TODO: Check if this was a nested HostRoot when used with
    !instance._warnedAboutRefsInRender ? warning(false, '%s is accessing isMounted inside its render()
function. ' + 'render() should be a pure function of props and state. It should ' + 'never access something that
requires stale data from the previous ' + 'render, such as refs. Move this logic to componentDidMount and ' +
'componentDidUpdate instead.', getComponentName(ownerFiber) || 'A component') : void 0;
    !didFindChild ? invariant(false, 'Child was not found in either parent set. This indicates a bug in React
related to the return pointer. Please file an issue.') : void 0;
    !(a.alternate === b) ? invariant(false, 'Return fibers should always be each others\' alternates. This error is
likely caused by a bug in React. Please file an issue.') : void 0;
    * Translation from legacy `keyCode` to HTML5 `key`
    // While user keyboard layout determines the actual meaning of each
    // Due to this, it is left to the user to implement at this time.
    // Browsers without "deltaMode" is reporting in raw wheel delta where one
    // TODO: Disabled elements should not respond to mouse events
    warning(false, 'SimpleEventPlugin: Unhandled event type, `%s`. This warning ' + 'is likely caused by a
bug in React. Please file an issue.', topLevelType);
    // TODO: It may be a good idea to cache this to prevent unnecessary DOM
    // TODO: can we stop exporting these?
    * @param {number} topLevelType Number from `TopLevelEventTypes`.
    * @param {number} topLevelType Number from `TopLevelEventTypes`.
    * @param {object} mountAt Container where to mount the listener
    // We set the flag for a single dependency later in this function,
    * Returns {start, end} where `start` is the character/codepoint index of
    // Moving from `node` to its first child `next`.
    // Moving from `node` to its next sibling `next`.
    * but modified to be suitable for react and has a couple of bug fixes (doesn't
    * from https://html.spec.whatwg.org/#do-not-apply, looking at `selectionStart`
    * -@offsets Object of same form that is returned from get*
    select: {
    // Ensure we have the right element, and that the user is not dragging a
    // selection (this matches native `select` event behavior). In HTML5, select
    var syntheticEvent = SyntheticEvent$1.getPooled(eventTypes$3.select, activeElementInst$1, nativeEvent,
nativeEventTarget);
    syntheticEvent.type = 'select';
    * This plugin creates an `onSelect` event that normalizes select events
    * This differs from native browser implementations in the following ways:

```

```

* - Fires after user input.
  // Don't fire the event while the user is dragging. This matches the
  // semantics of the native select event.
* Current TODO items:
  * Handles the case where a callback errors:
    // always remove it from linked list
  // TODO: this would be more efficient if deferred callbacks are stored in
  // where the nextSoonestTimeoutTime was set wrong.
  // callUnsafely will remove it from the head of the linked list
  // Schedule another animation callback so we retry later.
  // If we get lower than that, it is probably a bug.
  // TODO: If this rAF doesn't materialize because the browser throttles, we
  // TODO (yungsters): Remove support for `selected` in <option>.
  warning(false, 'Use the `defaultValue` or `value` props on <select> instead of ' + 'setting `selected` on
<option>');
// TODO: direct imports like some-package/src/* are bad. Fix me.
ReactControlledValuePropTypes.checkPropTypes('select', props, getCurrentFiberStackAddendum$3);
  warning(false, 'The `%s` prop supplied to <select> must be an array if ' + '`multiple` is true.%s', propName,
getDeclarationErrorAddendum());
  warning(false, 'The `%s` prop supplied to <select> must be a scalar ' + 'value if `multiple` is false.%s',
propName, getDeclarationErrorAddendum());
  // Do not set `select.value` as exact behavior isn't consistent across all
* Implements a <select> host component that allows optionally setting the
* If `value` is not supplied (or null/undefined), user actions that change the
* update in response to user actions. Instead, the `value` prop must change in
  warning(false, 'Select elements must be either controlled or uncontrolled ' + '(specify either the value prop,
or the defaultValue prop, but not ' + 'both). Decide between using a controlled or uncontrolled select ' +
'element and remove one of these props. More info: ' + 'https://fb.me/react-controlled-components');
  // Revert the select back to its default unselected state.
// TODO: direct imports like some-package/src/* are bad. Fix me.
* `defaultValue`. This differs from the traditional DOM API because value is
* If `value` is not supplied (or null/undefined), user actions that affect the
  // to only set the value if/when the value differs from the node value (which would
  // completely solve this IE9 bug), but Sebastian+Sophie seemed to like this
  // TODO (yungsters): Remove support for children content in <textarea>.
  // initial value. In IE10/IE11 there is a bug where the placeholder attribute
  // the markup. If you provide unsafe user data here they can inject
  !(props.style == null || typeof props.style === 'object') ? invariant(false, 'The `style` prop expects a mapping
from style properties to values, not a string. For example, style={{ marginRight: spacing + `em` }} when using
JSX.%s', getStack()) : void 0;
  from: 'from',
  if (type !== 'input' && type !== 'textarea' && type !== 'select') {
    if (type === 'select' && props.multiple) {

```

warning(false, 'React does not recognize the `%s` prop on a DOM element. If you '+' intentionally want it to appear in the DOM as a custom '+' attribute, spell it as lowercase `%s` instead. '+' 'If you accidentally passed it from a parent component, remove '+' 'it from the DOM element.%s', name, lowerCasedName, getStackAddendum\$2());

warning(false, 'Invalid value for prop %s on <%s> tag. Either remove it from the element, '+' 'or pass a string or number value to keep it in the DOM. '+' 'For details, see <https://fb.me/react-attribute-behavior%s>', unknownPropString, type, getStackAddendum\$2());

warning(false, 'Invalid values for props %s on <%s> tag. Either remove them from the element, '+' 'or pass a string or number value to keep them in the DOM. '+' 'For details, see <https://fb.me/react-attribute-behavior%s>', unknownPropString, type, getStackAddendum\$2());

// TODO: direct imports like some-package/src/\* are bad. Fix me.

warning(false, 'Extra attributes from the server: %s', names);

// fire. The workaround for this bug involves attaching an empty click

// TODO: Only do this for the relevant Safaris maybe?

// TODO: Handle wasCustomComponentTag

// Separate else branch instead of using `props.is || undefined` above because of a Firefox bug.

// TODO: Make sure that we check isMounted before firing any of these events.

case 'select':

// TODO: Make sure we check if this is still unmounted or do any clean

// TODO: Make sure we check if this is still unmounted or do any clean

case 'select':

// TODO: This cast may not be sound for SVG, MathML or custom elements.

case 'select':

// TODO: This cast may not be sound for SVG, MathML or custom elements.

// TODO: It might be too late to clear this if we have children

// TODO: Ensure that an update gets scheduled if any of the special props

// raise warnings and prevent the new value from being assigned.

case 'select':

// <select> value update needs to occur after <option> children

// TODO: Make sure that we check isMounted before firing any of these events.

case 'select':

// TODO: Only ignore them on controlled tags.

// TODO: Warn if there is more than a single textNode as a child.

// TODO: Should we use domElement.firstChild.nodeValue to compare?

// TODO: Only ignore them on controlled tags.

// be successfully parsed from HTML, but will produce a mismatch

// TODO: Make sure we check if this is still unmounted or do any clean

// TODO: Make sure we check if this is still unmounted or do any clean

case 'select':

// post mount to force it to diverge from attributes. However, for

// option and select we don't quite do the same thing and select

// TODO: Consider not doing this for input and textarea.

// TODO: This cast may not be sound for SVG, MathML or custom elements.

```

    // TODO: Remove this special case if we can just avoid inserting empty
    case 'select':
// TODO: direct imports like some-package/src/* are bad. Fix me.
    // for cases where the parser will give a parse tree differing from what React
    // <p> tags where the beginning of the second element implicitly closes the
    var specialTags = ['address', 'applet', 'area', 'article', 'aside', 'base', 'basefont', 'bgsound', 'blockquote', 'body', 'br',
'button', 'caption', 'center', 'col', 'colgroup', 'dd', 'details', 'dir', 'div', 'dl', 'dt', 'embed', 'fieldset', 'figcaption',
'figure', 'footer', 'form', 'frame', 'frameset', 'h1', 'h2', 'h3', 'h4', 'h5', 'h6', 'head', 'header', 'hgroup', 'hr', 'html',
'iframe', 'img', 'input', 'isindex', 'li', 'link', 'listing', 'main', 'marquee', 'menu', 'menuitem', 'meta', 'nav', 'noembed',
'noframes', 'noscript', 'object', 'ol', 'p', 'param', 'plaintext', 'pre', 'script', 'section', 'select', 'source', 'style',
'summary', 'table', 'tbody', 'td', 'template', 'textarea', 'tfoot', 'th', 'thead', 'title', 'tr', 'track', 'ul', 'wbr', 'xmp'];
    // TODO: Distinguish by namespace here -- for <title>, including it here
    case 'select':
        // Strictly speaking, seeing an <option> doesn't mean we're in a <select>
        // where the parsing rules cause implicit opens or closes to be added.
// TODO: turn this into a named export
// can re-export everything from this module.
    invariant(false, 'The current renderer does not support persistence. This error is likely caused by a bug in
React. Please file an issue.');
```

```

    case 'select':
        // TODO: take namespace into account when validating.
        // TODO: Possibly defer this until the commit phase where all the events
// Experimental error-boundary API that can recover from errors within a single
// TODO: this looks the same as nextUnitOfWork in scheduler. Can we unify them?
// If we're in the middle of user code, which fiber and method is it?
// Reusing `currentFiber` would be confusing for this because user code fiber
// if we continue in a later deferred loop from the same unit of work.
// If we pause, this is the fiber to unwind from.
// If we pause, its parent is the fiber to unwind from.
// If we pause, its parent is the fiber to unwind from.
    !(contextStackCursor.current === emptyObject) ? invariant(false, 'Unexpected context found on stack. This
error is likely caused by a bug in React. Please file an issue.') : void 0;
    // TODO (bvaughn) Replace this behavior with an invariant() in the future.
    warning(false, '%s.childContextTypes is specified but there is no getChildContext() method ' + 'on the
instance. You can either define getChildContext() on %s or remove ' + 'childContextTypes from it.',
componentName, componentName);
    // context from the parent component instance. The stack will be missing
    // and replace it on the stack later when invalidating the context.
    // Remember the parent context so we can merge with it later.
    !instance ? invariant(false, 'Expected to have an instance by this point. This error is likely caused by a bug in
React. Please file an issue.') : void 0;
    !(isFiberMounted(fiber) && fiber.tag === ClassComponent) ? invariant(false, 'Expected subtree parent to be a
mounted class component. This error is likely caused by a bug in React. Please file an issue.') : void 0;

```

```

!parent ? invariant(false, 'Found unexpected detached subtree parent. This error is likely caused by a bug in
React. Please file an issue.'): void 0;
// TODO: Use an opaque type once ESLint et al support the syntax
// TODO: we can remove these if Rollup fixes the bug.
// TODO: Consider warning about bad polyfills
// 4) We can easily go from a constructor to a createFiber object literal if that
// This prevents time from endlessly accumulating in new commits.
info += ' You likely forgot to export your component from the file ' + "it's defined in, or you might have
mixed up default and " + 'named imports.';
// TODO: This should be lifted into the renderer.
* Forked from fbjs/warning:
warning(false, 'Expected to find a StrictMode component in a strict mode tree. ' + 'This error is likely caused
by a bug in React. Please file an issue.');
```

```

warning(false, 'Expected to find a StrictMode component in a strict mode tree. ' + 'This error is likely caused
by a bug in React. Please file an issue.');
```

```

// TODO: Offscreen updates
// The earliest remaining level is later than all the suspended work. That
// TODO: What if a promise suspends and pings before the root completes?
// -progress render restarts by cloning from current. Similarly, if we only add
// priority, it remains in the queue to be processed later, during a lower
// where the number indicates the priority, and the update is applied to the
// TODO: With resuming, if we bail out and reuse the child tree, we should
warning(false, 'An update (setState, replaceState, or forceUpdate) was scheduled ' + 'from inside an update
function. Update functions should be pure, ' + 'with zero side-effects. Consider using componentDidUpdate or a
' + 'callback.');
```

```

// TODO: I put this here rather than createWorkInProgress so that we don't
!(c !== NO_CONTEXT) ? invariant(false, 'Expected host context to exist. This error is likely caused by a bug
in React. Please file an issue.'): void 0;
warning(false, 'Cannot start base timer that is already running. ' + 'This error is likely caused by a bug in
React. ' + 'Please file an issue.');
```

```

warning(false, '%s(...): No `render` method found on the returned component ' + 'instance: did you
accidentally return an object from the constructor?', name);
!(typeof child._store === 'object') ? invariant(false, 'React Component in warnForMissingKey should have a
_store. This error is likely caused by a bug in React. Please file an issue.'): void 0;
warning(false, 'A string ref, "%s", has been found within a strict mode tree. ' + 'String refs are a source of
potential bugs and should be avoided. ' + 'We recommend using createRef() instead.' + '\n%s' + '\n\nLearn more
about using refs safely here:' + '\nhttps://fb.me/react-strict-mode-string-ref', mixedRef,
getStackAddendumByWorkInProgressFiber(returnFiber));
!inst ? invariant(false, 'Missing owner for string ref %s. This error is likely caused by a bug in React. Please
file an issue.', mixedRef): void 0;
var currentComponentErrorInfo = 'Functions are not valid as a React child. This may happen if ' + 'you return
a Component instead of <Component /> from render. ' + 'Or maybe you meant to call this function rather than
return it.' + (getCurrentFiberStackAddendum$7() || '');

```



```

warning(false, 'Functions are not valid as a React child. This may happen if ' + 'you return a Component
instead of <Component /> from render. ' + 'Or maybe you meant to call this function rather than return it.%s',
getCurrentFiberStackAddendum$7() || '');
// TODO: For the shouldClone case, this could be micro-optimized a bit by
// This algorithm can't optimize by searching from boths ends since we
// add it later.
// where there are few changes and brute force the comparison instead of
// TODO: This breaks on empty slots like null children. That's
// TODO: Move out of the loop. This only happens for the first run.
// TODO: Defer siblings if we're not at the right index for this slot.
// TODO: Move out of the loop. This only happens for the first run.
// it from the child list so that we don't add it to the deletion
!(typeof iteratorFn === 'function') ? invariant(false, 'An object is not an iterable. This error is likely caused
by a bug in React. Please file an issue.') : void 0;
// We'll get a different iterator later for the main pass.
// TODO: This breaks on empty slots like null children. That's
// TODO: Move out of the loop. This only happens for the first run.
// TODO: Defer siblings if we're not at the right index for this slot.
// TODO: Move out of the loop. This only happens for the first run.
// it from the child list so that we don't add it to the deletion
// TODO: If key === null and child.key === null, then this only applies to
// TODO: If key === null and child.key === null, then this only applies to
invariant(false, '%s(...): Nothing was returned from render. This usually means a return statement is
missing. Or, to render nothing, return null.', Component.displayName || Component.name || 'Component');
invariant(false, 'Expected prepareToHydrateHostInstance() to never be called. This error is likely caused by a
bug in React. Please file an issue.');
```

// TODO: Type this specific to this type of component.

```

invariant(false, 'Expected prepareToHydrateHostTextInstance() to never be called. This error is likely caused
by a bug in React. Please file an issue.');
```

// We assume that prepareToHydrateHostTextInstance is called in a context where the

```

// TODO: Better heuristic.
// TODO: Remove this and use reconcileChildrenAtExpirationTime directly.
// TODO: consider bringing fn.shouldComponentUpdate() back.
// TODO: Warn in a future release.
// If we're recovering from an error, reconcile twice: first to delete
// TODO: Restructure so we never read values from the instance.
// TODO: Delete this when we delete isMounted and findDOMNode.
// If we're switching from a direct text child to a normal child, or to
// Bailout and come back to this fiber later.
!(current === null) ? invariant(false, 'An indeterminate component should never have mounted. This error is
likely caused by a bug in React. Please file an issue.') : void 0;
// TODO: Consider unifying this with how the root works.
// consumer, we'll continue scanning from that point. This way the
```

```

// TODO: We should ideally be able to bail out early if the children have no
// TODO: Handle HostComponent tags here as well and call pushHostContext()?
// TODO: What if this is currently in progress?
// TODO: Delete memoizeProps/State and move to reconcile/bailout instead
    invariant(false, 'Unknown unit of work tag. This error is likely caused by a bug in React. Please file an
issue.');
```

// down its children. Instead, we'll get insertions from each child in
 // TODO: Type this specific to this type of component.
 // down its children. Instead, we'll get insertions from each child in
 // TODO: Delete this when we delete isMounted and findDOMNode.
 // TODO: Split the update API as separate for the props vs. children.
 // TODO: Experiencing an error where oldProps is null. Suggests a host
 !(workInProgress.stateNode !== null) ? invariant(false, 'We must have new props for new mounts. This
error is likely caused by a bug in React. Please file an issue.') : void 0;
 // TODO: Move createInstance to beginWork and keep it on a context
 // TODO: Move this and createInstance step into the beginPhase
 // Make sure such renderers get scheduled for later work.
 !(workInProgress.stateNode !== null) ? invariant(false, 'We must have new props for new mounts. This
error is likely caused by a bug in React. Please file an issue.') : void 0;
 invariant(false, 'An indeterminate component should have become determinate before completing. This
error is likely caused by a bug in React. Please file an issue.');

invariant(false, 'Unknown unit of work tag. This error is likely caused by a bug in React. Please file an
issue.');

errorBoundaryMessage = 'React will try to recreate this component tree from scratch ' + ('using the error
boundary you provided, ' + errorBoundaryName + ');
 errorBoundaryMessage = 'This error was initially handled by the error boundary ' + errorBoundaryName +
'.\\n' + 'Recreating the tree from scratch failed so React will unmount the tree.';
 invariant(false, 'This unit of work tag should not have side-effects. This error is likely caused by a bug in
React. Please file an issue.');

invariant(false, 'This unit of work tag should not have side-effects. This error is likely caused by a bug in
React. Please file an issue.');

// User-originating errors (lifecycles and refs) should not interrupt
 // TODO: this is recursive.
 // composites before this host node is removed from the tree. Therefore
 // Cut off the return pointers to disconnect it from the tree. Ideally, we
 invariant(false, 'This unit of work tag should not have side-effects. This error is likely caused by a bug in
React. Please file an issue.');

invariant(false, 'Expected to find a host parent. This error is likely caused by a bug in React. Please file an
issue.');

invariant(false, 'Invalid host parent fiber. This error is likely caused by a bug in React. Please file an issue.');

// Clear ContentReset from the effect tag
 // down its children. Instead, we'll get insertions from each child in
 !(parent !== null) ? invariant(false, 'Expected to find a host parent. This error is likely caused by a bug in

```

React. Please file an issue.') : void 0;
  // node from the tree.
  // When we go into a portal, it becomes the parent to remove from.
  // Recursively delete all host nodes from the parent.
    // TODO: Type the updateQueue to be specific to host components.
    !(finishedWork.stateNode !== null) ? invariant(false, 'This should have a text node initialized. This error is
likely caused by a bug in React. Please file an issue.') : void 0;
    invariant(false, 'This unit of work tag should not have side-effects. This error is likely caused by a bug in
React. Please file an issue.');
```

// TODO: Warn in strict mode if getDerivedStateFromCatch is  
 // TODO: Alternatively, we could store the earliest timeout on the context  
 // TODO: Need to figure out a different strategy if/when we add  
 warning(false, 'Could not replay rendering after an error. This is likely a bug in React. ' + 'Please file an
issue.');

// possible bitmap value, we remove the secondary effects from the  
 // Clear the "placement" from effect tag so that we know that this is inserted, before  
 // TODO: findDOMNode doesn't rely on this any more but isMounted  
 // Clear the "placement" from effect tag so that we know that this is inserted, before  
 !(root.current !== finishedWork) ? invariant(false, 'Cannot commit the same tree as before. This is probably a
bug related to the return field. This error is likely caused by a bug in React. Please file an issue.') : void 0;  
 !(committedExpirationTime !== NoWork) ? invariant(false, 'Cannot commit an incomplete root. This error is
likely caused by a bug in React. Please file an issue.') : void 0;  
 !(nextEffect !== null) ? invariant(false, 'Should have next effect. This error is likely caused by a bug in
React. Please file an issue.') : void 0;  
 // This enables them to be grouped later.  
 !(nextEffect !== null) ? invariant(false, 'Should have next effect. This error is likely caused by a bug in
React. Please file an issue.') : void 0;  
 !(nextEffect !== null) ? invariant(false, 'Should have next effect. This error is likely caused by a bug in
React. Please file an issue.') : void 0;  
 // TODO: Calls need to visit stateNode  
 // from the effect tag.  
 // TODO Remove the above while(true) loop  
 !!isWorking ? invariant(false, 'renderRoot was called recursively. This error is likely caused by a bug in React.
Please file an issue.') : void 0;  
 // Check if we're starting from a fresh stack, or if we're resuming from  
 // Reset the stack and start working from the root.  
 // TODO: we already know this isn't true in some cases.  
 !(nextUnitOfWork !== null) ? invariant(false, 'Failed to replay rendering after an error. This is likely
caused by a bug in React. Please file an issue with a reproducing case to help us find it.') : void 0;  
 !!nextRenderIsExpired ? invariant(false, 'Expired work should have completed. This error is likely caused
by a bug in React. Please file an issue.') : void 0;  
 // TODO: Rename this to scheduleTimeout or something  
 // TODO: Everything below this is written as if it has been lifted to the

```

// TODO: Get rid of Sync and use current time?
// This root no longer has work. Remove it from the scheduler.
// TODO: This check is redundant, but Flow is confused by the branch
// below where we set lastScheduledRoot to null, even though we break
// from the loop right after.
!(previousScheduledRoot !== null && lastScheduledRoot !== null) ? invariant(false, 'Should have a
previous and last root. This error is likely caused by a bug in React. Please file an issue.') : void 0;
!!isRendering ? invariant(false, 'work.commit(): Cannot commit while already rendering. This likely means
you attempted to commit from inside a lifecycle method.') : void 0;
!!isRendering ? invariant(false, 'performWorkOnRoot was called recursively. This error is likely caused by a
bug in React. Please file an issue.') : void 0;
// back and commit it later.
// This root is blocked from committing by a batch. Unschedule it until
!(nextFlushedRoot !== null) ? invariant(false, 'Should be working on a root. This error is likely caused by a
bug in React. Please file an issue.') : void 0;
!(nextFlushedRoot !== null) ? invariant(false, 'Should be working on a root. This error is likely caused by a
bug in React. Please file an issue.') : void 0;
// TODO: Batching should be implemented at the renderer level, not inside
// TODO: Batching should be implemented at the renderer level, not inside
// TODO: Batching should be implemented at the renderer level, not within
!!isRendering ? invariant(false, 'flushSync was called from inside a lifecycle method. It cannot be called when
React is already rendering.') : void 0;
// Might add PROFILE later.
warning(false, 'Render methods should be a pure function of props and state; ' + 'triggering nested
component updates from render is not allowed. ' + 'If necessary, trigger nested updates in
componentDidUpdate.\n\n' + 'Check the render method of %s.',
getComponentName(ReactDebugCurrentFiber.current) || 'Unknown');
// TODO: If this is a nested container, this won't be the root.
// TODO: figure out the API for cross-renderer implementation.
// TODO: this is special because it gets imported during build.
// TODO: This type is shared between the reconciler and ReactDOM, but will
// TODO: This forces a restart. Should we print a warning?
// Remove the batch from the list.
// Pop the batch from the list.
// TODO: Error handling.
// TODO: Avoid need to bind by replacing callbacks in the update queue with
// TODO: Error handling.
// TODO: Ensure all entry points contain this check
// TODO: Without `any` type, Flow says "Property cannot be accessed on any
// TODO: pass ReactDOM portal implementation as third argument
!warnedAboutRefsInRender ? warning(false, '%s is accessing findDOMNode inside its render(). ' +
'render() should be a pure function of props and state. It should ' + 'never access something that requires stale
data from the previous ' + 'render, such as refs. Move this logic to componentDidMount and ' +

```

```

'componentDidUpdate instead.', getComponentName(owner) || 'A component') : void 0;
  // TODO: throw or warn if we couldn't hydrate?
  // TODO: remove in React 17.
// TODO: decide on the top-level export form.
  // Test for A's keys different from B.
// https://github.com/sindresorhus/query-string/issues/47
// https://github.com/sindresorhus/query-string/pull/37
query: parse(extract(str), opts)
  // We need to check all keys in case some are required but missing from
  // the current/next pattern is copied from redux's createStore code.
  // TODO: refactor+expose that code to be reusable here?
selectorFactory returns a final props selector from its mapStateToProps,
  // used to compute Connect's displayName from the wrapped component's displayName.
* @param {*} value The value to query.
/* WEBPACK VAR INJECTION */(function(global) {/** Detect free variable `global` from Node.js. */
* @param {*} value The value to query.
  throw new Error('bindActionCreators expected an object or a function, instead received ' + (actionCreators
=== null ? 'null' : typeof actionCreators) + '. ' + 'Did you write "importActionCreators from" instead of "import
* asActionCreators from"?');
// TODO: Add more comments
* Location changes flow from history to the store. An enhanced history is
  // Remember where we are
  // Let user unsubscribe later
function _toConsumableArray(arr) { if (Array.isArray(arr)) { for (var i = 0, arr2 = Array(arr.length); i <
arr.length; i++) { arr2[i] = arr[i]; } return arr2; } else { return Array.from(arr); } }
* provided history object. This will prevent these actions from reaching your
/* WEBPACK VAR INJECTION */(function(global) {!function(e,t){true?t(exports):"function"===typeof
define&&define.amd?define(["exports"],t):(t(e.reduxLogger=e.reduxLogger||{}))(this,function(e){"use
strict";function
t(e,t){e.super_=t,e.prototype=Object.create(t.prototype,{constructor:{value:e,enumerable:!1,writable:!0,configu
rable:!0}})}function
r(e,t){Object.defineProperty(this,"kind",{value:e,enumerable:!0}),t&&t.length&&Object.defineProperty(this,"p
ath",{value:t,enumerable:!0})}function
n(e,t,r){n.super_.call(this,"E",e),Object.defineProperty(this,"lhs",{value:t,enumerable:!0}),Object.definePropert
y(this,"rhs",{value:r,enumerable:!0})}function
o(e,t){o.super_.call(this,"N",e),Object.defineProperty(this,"rhs",{value:t,enumerable:!0})}function
i(e,t){i.super_.call(this,"D",e),Object.defineProperty(this,"lhs",{value:t,enumerable:!0})}function
a(e,t,r){a.super_.call(this,"A",e),Object.defineProperty(this,"index",{value:t,enumerable:!0}),Object.defineProp
erty(this,"item",{value:r,enumerable:!0})}function f(e,t,r){var n=e.slice((r||t)+1||e.length);return
e.length=t<0?e.length+t:t,e.push.apply(e,n),e}function u(e){var t="undefined"===typeof
e?"undefined":N(e);return"object"!==t?t:e===Math?"math":null===e?"null":Array.isArray(e?"array":["object
Date"]===Object.prototype.toString.call(e?"date":"function"===typeof
e.toString&&/^\.\.*\/.test(e.toString())?"regexp":"object"})}function l(e,t,r,c,s,d,p){s=s||[],p=p||[];var

```

```

g=s.slice(0);if("undefined"!==typeof d){if(c){if("function"===typeof
c&& c(g,d))return;if("object"===("undefined"===typeof
c?"undefined":N(c)))if(c.prefilter&&c.prefilter(g,d))return;if(c.normalize){var
h=c.normalize(g,d,e,t);h&&(e=h[0],t=h[1])}}g.push(d)}"regexp"===u(e)&&"regexp"===u(t)&&(e=e.toString
(),t=t.toString());var y="undefined"===typeof e?"undefined":N(e),v="undefined"===typeof
t?"undefined":N(t),b="undefined"!==y||p&&p[p.length-1].lhs&&p[p.length-1].lhs.hasOwnProperty(d),m="und
efined"!==v||p&&p[p.length-1].rhs&&p[p.length-1].rhs.hasOwnProperty(d);if(!b&&m)r(new o(g,t));else
if(!m&&b)r(new i(g,e));else if(u(e)!==u(t))r(new n(g,e,t));else if("date"===u(e)&&e-t!==0)r(new n(g,e,t));else
if("object"===y&&null!==e&&null!==t)if(p.filter(function(t){return t.lhs===e}).length)e!==t&&r(new
n(g,e,t));else{if(p.push({lhs:e,rhs:t}),Array.isArray(e)){var
w;e.length;for(w=0;w<e.length;w++)w>=t.length?r(new a(g,w,new i(void
0,e[w]))):l(e[w],t[w],r,c,g,w,p);for(;w<t.length;r(new a(g,w,new o(void 0,t[w++]))))}else{var
x=Object.keys(e),S=Object.keys(t);x.forEach(function(n,o){var
i=S.indexOf(n);i>=0?(l(e[n],t[n],r,c,g,n,p),S=f(S,i)):l(e[n],void 0,r,c,g,n,p)},S.forEach(function(e){l(void
0,t[e],r,c,g,e,p)}))p.length=p.length-1}else e!==t&&("number"===y&&isNaN(e)&&isNaN(t)||r(new
n(g,e,t)))}function c(e,t,r,n){return n=n||[],l(e,t,function(e){e&&n.push(e)},r),n.length?n:void 0}function
s(e,t,r){if(r.path&&r.path.length){var
n,o=e[t],i=r.path.length-1;for(n=0;n<i;n++)o=o[r.path[n]];switch(r.kind){case"A":s(o[r.path[n]],r.index,r.item);
break;case"D":delete o[r.path[n]];break;case"E":case"N":o[r.path[n]]=r.rhs} }else
switch(r.kind){case"A":s(e[t],r.index,r.item);break;case"D":e=f(e,t);break;case"E":case"N":e[t]=r.rhs}return
e}function d(e,t,r){if(e&&t&&r&&r.kind){for(var
n=e,o=-1,i=r.path?r.path.length-1:0;++o<i;) "undefined"===typeof
n[r.path[o]]&&(n[r.path[o]]="number"===typeof
r.path[o]?[]:{}),n=n[r.path[o]];switch(r.kind){case"A":s(r.path?n[r.path[o]]:n,r.index,r.item);break;case"D":dele
te n[r.path[o]];break;case"E":case"N":n[r.path[o]]=r.rhs} }}function p(e,t,r){if(r.path&&r.path.length){var
n,o=e[t],i=r.path.length-1;for(n=0;n<i;n++)o=o[r.path[n]];switch(r.kind){case"A":p(o[r.path[n]],r.index,r.item);
break;case"D":o[r.path[n]]=r.lhs;break;case"E":o[r.path[n]]=r.lhs;break;case"N":delete o[r.path[n]]} }else
switch(r.kind){case"A":p(e[t],r.index,r.item);break;case"D":e[t]=r.lhs;break;case"E":e[t]=r.lhs;break;case"N":e
=f(e,t)}return e}function g(e,t,r){if(e&&t&&r&&r.kind){var
n,o,i=e;for(o=r.path.length-1,n=0;n<o;n++) "undefined"===typeof
i[r.path[n]]&&(i[r.path[n]]={}),i=i[r.path[n]];switch(r.kind){case"A":p(i[r.path[n]],r.index,r.item);break;case"D
":i[r.path[n]]=r.lhs;break;case"E":i[r.path[n]]=r.lhs;break;case"N":delete i[r.path[n]]} }}function
h(e,t,r){if(e&&t){var n=function(n){r&&!r(e,t,n)||d(e,t,n)};l(e,t,n)}function y(e){return"color: "+F[e].color+";
font-weight: bold"}function v(e){var
pÿ t = e . k i n d , r = e . p a t h , n = e . l h s , o = e . r h s , i = e . i n d e x , a = e . i t e m ; s w i t c h ( t ) { c a s e " E "
[r.join("."),o];case"D":return[r.join(".")];case"A":return[r.join(".")+"["+i+"]",a];default:return[]} }function
b(e,t,r,n){var
o=c(e,t);try{n?r.groupCollapsed("diff"):r.group("diff")}catch(e){r.log("diff")}o?o.forEach(function(e){var
pÿ t = e . k i n d , n = v ( e ) ; r . l o g . a p p l y ( r , [ " % c " + F [ t ] . t e x t , y ( t ) ] . c o n c a t ( P ( n ) ) ) : r . l o
g ( " " ) ; t r y { r . g r o u p E n d ( ) } c a t c h ( e ) { r . l o g ( " d i f f e n d " ) } } function m(e,t,r
e?"undefined":N(e)){case"object":return"function"===typeof e[n]?e[n].apply(e,P(r)):e[n];case"function":return
e(t);default:return e} }function w(e){var t=e.timestamp,r=e.duration;return function(e,n,o){var
i=["action"];return i.push("%c"+String(e.type)),t&&i.push("%c@ "+n),r&&i.push("%c(in "+o.toFixed(2)+")"}

```

```
ms)),i.join(" "))}function x(e,t){var r=t.logger,n=t.actionTransformer,o=t.titleFormatter,i=void
0===o?w(t):o,a=t.collapsed,f=t.colors,u=t.level,l=t.diff,c="undefined"===typeof
t.titleFormatter;e.forEach(function(o,s){var
d=o.started,p=o.startedTime,g=o.action,h=o.prevState,y=o.error,v=o.took,w=o.nextState,x=e[s+1];x&&(w=x.p
revState,v=x.started-d);var S=n(g),k="function"===typeof a?a(function(){return
w},g,o):a,j=D(p),E=f.title?"color: "+f.title(S)+" ":"",A=["color: gray; font-weight:
lighter;"];A.push(E),t.timestamp&&A.push("color: gray; font-weight: lighter;"),t.duration&&A.push("color:
gray; font-weight: lighter;");var O=i(S,j,v);try{k?f.title&&c?r.groupCollapsed.apply(r,["%c
"+O].concat(A)):r.groupCollapsed(O):f.title&&c?r.group.apply(r,["%c
"+O].concat(A)):r.group(O)}catch(e){r.log(O)}var
N=m(u,S,[h],"prevState"),P=m(u,S,[S],"action"),C=m(u,S,[y,h],"error"),F=m(u,S,[w],"nextState");if(N)if(f.prev
State){var L="color: "+f.prevState(h)+" ";font-weight: bold";r[N]("%c prev state",L,h)}else r[N]("prev
state",h);if(P)if(f.action){var T="color: "+f.action(S)+" ";font-weight: bold";r[P]("%c action ",T,S)}else
r[P]("action ",S);if(y&&C)if(f.error){var M="color: "+f.error(y,h)+" ";font-weight: bold";r[C]("%c error
",M,y)}else r[C]("error ",y);if(F)if(f.nextState){var _="color: "+f.nextState(w)+" ";font-weight:
bÿ bold ";r[F]("%c next state",_,w)}else r[F]("next state",w);l&&b(h,w,r,k)
bÿ log end ")}))}function S(){var e=arguments.length>0&&void
0!=arguments[0]?arguments[0]:{ },t=Object.assign({ },L,e),r=t.logger,n=t.stateTransformer,o=t.errorTransform
er,i=t.predicate,a=t.logErrors,f=t.diffPredicate;if("undefined"===typeof r)return function(){return
function(e){return function(t){return e(t)}}};if(e.getState&&e.dispatch)return console.error("[redux-logger]
redux-logger not installed. Make sure to pass logger instance as middleware:\n// Logger with default
options\nimport { logger } from 'redux-logger'\nconst store = createStore(\n reducer,\n
applyMiddleware(logger)\n)\n// Or you can create your own logger with custom options
http://bit.ly/redux-logger-options\nimport createLogger from 'redux-logger'\nconst logger = createLogger({\n //
...options\n});\nconst store = createStore(\n reducer,\n applyMiddleware(logger)\n)\n"),function(){return
function(e){return function(t){return e(t)}};var u=[];return function(e){var r=e.getState;return
function(e){return function(l){if("function"===typeof i&&!i(r,l))return e(l);var
c={ };u.push(c),c.started=O.now(),c.startedTime=new Date,c.prevState=n(r()),c.action=l;var s=void
0;if(a)try{s=e(l)}catch(e){c.error=o(e)}else s=e(l);c.took=O.now()-c.started,c.nextState=n(r());var
d=t.diff&&"function"===typeof f?f(r,l):t.diff;if(x(u,Object.assign({ },t,{diff:d})),u.length=0,c.error)throw
c.error;return s}}}}var k,j,E=function(e,t){return new Array(t+1).join(e)},A=function(e,t){return
E("0",t-e.toString().length)+e},D=function(e){return
A(e.getHours(),2)+":"+A(e.getMinutes(),2)+":"+A(e.getSeconds(),2)+"."+A(e.getMilliseconds(),3)},O="undefi
ned"!==typeof performance&&null!==performance&&"function"===typeof
performance.now?performance.Date,N="function"===typeof Symbol&&"symbol"===typeof
Symbol.iterator?function(e){return typeof e}:function(e){return e&&"function"===typeof
Symbol&&e.constructor===Symbol&&e!==Symbol.prototype?"symbol":typeof
e},P=function(e){if(Array.isArray(e)){for(var t=0,r=Array(e.length);t<e.length;t++)r[t]=e[t];return r}return
Array.from(e)},C=[];k="object"===("undefined"===typeof
global?"undefined":N(global))&&global?global:"undefined"!==typeof
window?window:{ },j=k.DeepDiff,j&&C.push(function(){ "undefined"!==typeof
j&&k.DeepDiff===c&&(k.DeepDiff=j,j=void
0)),t(n,r),t(o,r),t(i,r),t(a,r),Object.defineProperties(c,{diff:{value:c,enumerable:!0},observableDiff:{value:l,enu
```

```
merable:!0},applyDiff:{value:h,enumerable:!0},applyChange:{value:d,enumerable:!0},revertChange:{value:g,enumerable:!0},isConflict:{value:function(){return"undefined"!==typeof j},enumerable:!0},noConflict:{value:function(){return C&&(C.forEach(function(e){e()}),C=null),c},enumerable:!0}});var F={E:{color:"#2196F3",text:"CHANGED:"},N:{color:"#4CAF50",text:"ADDED:"},D:{color:"#F44336",text:"DELETED:"},A:{color:"#2196F3",text:"ARRAY:"}},L={level:"log",logger:console,logErrors:!0,collapsed:void 0,predicate:void 0,duration:!1,timestamp:!0,stateTransformer:function(e){return e},actionTransformer:function(e){return e},errorTransformer:function(e){return e},colors:{title:function(){return"inherit"},prevState:function(){return"#9E9E9E"},action:function(){return"#03A9F4"},nextState:function(){return"#4CAF50"},error:function(){return"#F20404"}},diff:!1,diffPredicate:void 0,transformer:void 0},T=function(){var e=arguments.length>0&&void 0!==arguments[0]?arguments[0]:{}t=e.dispatch,r=e.getState;return"function"===typeof t||"function"===typeof r?S()({dispatch:t,getState:r}):void console.error("\n[redux-logger v3] BREAKING CHANGE\n[redux-logger v3] Since 3.0.0 redux-logger exports by default logger with default settings.\n[redux-logger v3] Change\n[redux-logger v3] import createLogger from 'redux-logger'\n[redux-logger v3] to\n[redux-logger v3] import { createLogger } from 'redux-logger'\n"));e.defaults=L,e.createLogger=S,e.logger=T,e.default=T,Object.defineProperty(e,"__esModule",{value:!0}));
```

// TODO: We could probably make this more reliable by

// This allows the user to escape special characters that won't transform.

\* Get the flags for a regexp from the options.

\* Pull out keys from a regexp.

\* Create a path regexp from string input.

// in non-ending mode, where "/test/" shouldn't match "/test//route".

\* placeholder key descriptions. For example, using `/user/:id`, `keys` will

// TODO: We could probably make this more reliable by

// TODO: We could probably make this more reliable by

```
var source = req.headers['user-agent'] || '';
```

// If the UA does not start with Mozilla guess the user agent.

15-[https://stage.thumbsignin.com/assets/terms\\_m.chunk.js](https://stage.thumbsignin.com/assets/terms_m.chunk.js)

Other Information: 'PLEASE READ THESE TERMS CAREFULLY. BY ACCESSING OR USING ANY SERVICES, YOU AGREE TO BE BOUND BY THESE TERMS, AS THEY MAY BE MODIFIED OR AMENDED FROM TIME TO TIME BY ThumbSignIn IN ITS DISCRETION. ANY SUCH AMENDMENTS TO THESE TERMS BECOME EFFECTIVE AT THE TIME THEY ARE POSTED TO THE SITE, AND EACH TIME YOU ACCESS OR USE ANY SERVICES, YOU AGREE TO BE BOUND BY THESE TERMS AS AMENDED. IF YOU DO NOT AGREE, YOU SHOULD DISCONTINUE USE OF THE SITE AND ALL OTHER SERVICES IMMEDIATELY.'

'Fraudulently inducing the purchase of goods or services or disclosure of information by any user;'

'Deceiving any user regarding the identity of you or your organization, the origin of your content, or the nature or quality of any products or services promoted by you; or'

'As between the parties, ThumbSignIn owns all right, title, and interest in the Services,



ThumbSignIn trademarks, and any technology or tools used by us to generate, distribute or display Your Content within the Services (collectively the "ThumbSignIn IP"). You agree not to rent, lease, sublicense, distribute, transfer, copy, reproduce, download, display, modify or timeshare the ThumbSignIn IP or any portion thereof, or use such ThumbSignIn IP as a component of or a base for goods or services prepared for commercial sale, sublicense, lease, access or distribution. You are prohibited from creating any derivative work based on the ThumbSignIn IP. You agree not to translate, reverse engineer, decompile or disassemble the ThumbSignIn IP.'

'The Services are protected by U.S. copyright laws and international treaty provisions. You may not use, copy, modify, or distribute the Services (electronically or otherwise) or ThumbSignIn IP, including the source code for any portion of the Services, or any copy, adaptation, transcription, or merged portion thereof, except as expressly authorized by us in writing. You may not modify, reverse engineer, disassemble, decompile, translate, create derivative works from, or otherwise alter the Services. You may not transfer, lease, assign, rent, or sublicense the rights granted to you under these Terms, or make the Services available for the use of others through your User ID. You may not use any portion of the Services or any standalone utility provided for use with the Services for any purpose other than its intended purpose.'

'We assume no responsibility or make any representation or warranty with respect to websites or services owned and operated independently by third parties (including but not limited to our partners or affiliates) which may be accessed by you or users through links on the Site interfaces or otherwise from the Services.'

'description of where the infringing content is located on this website'

'You agree to indemnify and hold harmless ThumbSignIn, its subsidiaries, affiliates, directors, officers and employees, from and against any and all liabilities, damages, losses, costs or expenses (including reasonable attorneys' fees) arising from or relating to any third party claim, action or demand asserted against any of the foregoing parties based on: (a) any breach of these Terms by you or anyone accessing the Services using your login credentials; (b) any violation of law, regulation or third party rights in connection with your use of the Services; (c) any complaint by any User with respect to Your Content; or (d) any claim arising out our publication of Your Content, including but not limited to any claims for false advertising, defamation, infringement or personal injury.'

'You acknowledge that your breach of any of the provisions of these Terms may cause immediate and irreparable harm to ThumbSignIn for which we may not have an adequate remedy in money or damages. We will therefore be entitled to obtain an injunction against such breach or threatened breach from any court of competent jurisdiction, without the necessity of posting a bond, and will be entitled to recover from you the costs incurred in seeking such an injunction. Our right to obtain injunctive relief will not limit our right to seek or obtain further remedies.'

```
// this implementation is not 100% perfect for weird media query combinations
// Adapted from convert-source-map (MIT)
* // Remove it from the DOM
// bind timers to global for call from export context
// Thrash, waste and sodomy: IE GC bug
// IE 8- don't enum bug keys
// Don't enum bug & hidden keys
// getting tag from 19.1.3.6 Object.prototype.toString()
```

16-<https://stage.thumbsignin.com/assets/terms.chunk.js>

Other Information: 'PLEASE READ THESE TERMS CAREFULLY. BY ACCESSING OR USING ANY SERVICES, YOU AGREE TO BE BOUND BY THESE TERMS, AS THEY MAY BE MODIFIED OR AMENDED FROM TIME TO TIME BY ThumbSignIn IN ITS DISCRETION. ANY SUCH AMENDMENTS TO THESE TERMS BECOME EFFECTIVE AT THE TIME THEY ARE POSTED TO THE SITE, AND EACH TIME YOU ACCESS OR USE ANY SERVICES, YOU AGREE TO BE BOUND BY THESE TERMS AS AMENDED. IF YOU DO NOT AGREE, YOU SHOULD DISCONTINUE USE OF THE SITE AND ALL OTHER SERVICES IMMEDIATELY.'

'Fraudulently inducing the purchase of goods or services or disclosure of information by any user;'

'Deceiving any user regarding the identity of you or your organization, the origin of your content, or the nature or quality of any products or services promoted by you; or'

'As between the parties, ThumbSignIn owns all right, title, and interest in the Services, ThumbSignIn trademarks, and any technology or tools used by us to generate, distribute or display Your Content within the Services (collectively the "ThumbSignIn IP"). You agree not to rent, lease, sublicense, distribute, transfer, copy, reproduce, download, display, modify or timeshare the ThumbSignIn IP or any portion thereof, or use such ThumbSignIn IP as a component of or a base for goods or services prepared for commercial sale, sublicense, lease, access or distribution. You are prohibited from creating any derivative work based on the ThumbSignIn IP. You agree not to translate, reverse engineer, decompile or disassemble the ThumbSignIn IP.'

'The Services are protected by U.S. copyright laws and international treaty provisions. You may not use, copy, modify, or distribute the Services (electronically or otherwise) or ThumbSignIn IP, including the source code for any portion of the Services, or any copy, adaptation, transcription, or merged portion thereof, except as expressly authorized by us in writing. You may not modify, reverse engineer, disassemble, decompile, translate, create derivative works from, or otherwise alter the Services. You may not transfer, lease, assign, rent, or sublicense the rights granted to you under these Terms, or make the Services available for the use of others through your User ID. You may not use any portion of the Services or any standalone utility provided for use with the Services for any purpose other than its intended purpose.'

'We assume no responsibility or make any representation or warranty with respect to websites or services owned and operated independently by third parties (including but not limited to our partners or affiliates) which may be accessed by you or users through links on the Site interfaces or otherwise from the Services.'

'description of where the infringing content is located on this website'

'You agree to indemnify and hold harmless ThumbSignIn, its subsidiaries, affiliates, directors, officers and employees, from and against any and all liabilities, damages, losses, costs or expenses (including reasonable attorneys' fees) arising from or relating to any third party claim, action or demand asserted against any of the foregoing parties based on: (a) any breach of these Terms by you or anyone accessing the Services using your login credentials; (b) any violation of law, regulation or third party rights in connection with your use of the Services; (c) any complaint by any User with respect to Your Content; or (d) any claim arising out of our publication of Your Content, including but not limited to any claims for false advertising, defamation, infringement or personal injury.'

'You acknowledge that your breach of any of the provisions of these Terms may cause immediate and irreparable harm to ThumbSignIn for which we may not have an adequate remedy in money or damages.'

We will therefore be entitled to obtain an injunction against such breach or threatened breach from any court of competent jurisdiction, without the necessity of posting a bond, and will be entitled to recover from you the costs incurred in seeking such an injunction. Our right to obtain injunctive relief will not limit our right to seek or obtain further remedies.'

```
    query: '{\n      user {\n        isLogedin\n      } \n    }'\n    { query: data, __source: {\n      // this implementation is not 100% perfect for weird media query combinations\n    }\n  }\n  // Adapted from convert-source-map (MIT)\n  * // Remove it from the DOM\n  // bind timers to global for call from export context\n  // Thrash, waste and sodomy: IE GC bug\n  // IE 8- don't enum bug keys\n  err = new Error('You provided a `'+ propFullNameSafe + '` to the '+ componentNameSafe + '\n  ' that was ' + ('not within the range from \'' + min + ' - ' + max + '\'. `'+ propFullNameSafe + `': ' + value + '));\n  // Don't enum bug & hidden keys\n  // getting tag from 19.1.3.6 Object.prototype.toString()\n  return fetch('/api/user').then(function (response) {\n    return fetch('/api/user', { method: "POST", body: userInfo }).then(function (response) {\n  // import { Provider } from '../Modal'\n  query: __WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.object.isRequired\n  exports.push([module.i, "/*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css */\n\n  Document\n\n  =====\n\n  /*\n  1. Correct the line height in all browsers.\n  2. Prevent adjustments of font size after orientation\n  changes in\n  IE on Windows Phone and in iOS.\n  */\n  html {\n    line-height: 1.15;\n  }\n  *\n  -ms-text-size-adjust: 100%;\n  * 2\n  -webkit-text-size-adjust: 100%;\n  * 2\n  }*\n\n  Sections\n\n  =====\n\n  /*\n  Remove the margin in all browsers (opinionated).\n  */\n  body {\n    margin: 0;\n  }\n\n  /*\n  Add the correct display in IE 9-.\n  */\n  article,\n  aside,\n  footer,\n  header,\n  nav,\n  section {\n    display:\n    block;\n  }\n\n  /*\n  Correct the font size and margin on `h1` elements within `section` and `article`\n  contexts in Chrome, Firefox, and Safari.\n  */\n  h1 {\n    font-size: 2em;\n    margin: 0.67em 0;\n  }\n\n  /*\n  Grouping\n  content\n\n  =====\n\n  /*\n  Add the correct display in IE 9-.\n  */\n  1. Add the correct display in IE.\n\n  figure,\n  figure,\n  main {\n    /* 1\n    display: block;\n  }\n\n  /*\n  Add the correct margin in IE 8.\n\n  figure {\n    margin: 1em 40px;\n  }\n\n  /*\n  1. Add the correct box sizing in Firefox.\n  2. Show the\n  overflow in Edge and IE.\n  */\n  hr {\n    -webkit-box-sizing: content-box;\n    box-sizing: content-box;\n  }\n\n  /*\n  1\n  height: 0;\n  /* 1\n  overflow: visible;\n  /* 2\n  */\n\n  /*\n  1. Correct the inheritance and scaling of font\n  size in all browsers.\n  2. Correct the odd `em` font sizing in all browsers.\n  */\n  pre {\n    font-family:\n    monospace, monospace;\n  }\n  /* 1\n  font-size: 1em;\n  /* 2\n  }*\n\n  Text-level semantics\n\n  =====\n\n  /*\n  1. Remove the gray background on active links in IE 10.\n  2. Remove gaps in links underline in\n  iOS 8+ and Safari 8+.\n  */\n  a {\n    background-color: transparent;\n  }\n  /* 1\n  -webkit-text-decoration-skip:
```

objects; /\* 2 \*/\n}\n\n/\*\*\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*/\n\nabbr[title] {\n border-bottom: none;\n \* 1 \*\n text-decoration: underline; /\* 2 \*\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*\n}\n\n/\*\*\n \* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n \*/\n\nb, \bstrong {\n font-weight: inherit;\n}\n\n/\*\*\n \* Add the correct font weight in Chrome, Edge, and Safari.\n \*/\n\nb, \bstrong {\n font-weight: bolder;\n}\n\n/\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\ncode, \nkbd, \nsamp {\n font-family: monospace, monospace; /\* 1 \*\n font-size: 1em; /\* 2 \*\n}\n\n/\*\*\n \* Add the correct font style in Android 4.3-.\n \*/\n\ni, \ndfn {\n font-style: italic;\n}\n\n/\*\*\n \* Add the correct background and color in IE 9-.\n \*/\n\nmark {\n background-color: #ff0;\n color: #000;\n}\n\n/\*\*\n \* Add the correct font size in all browsers.\n \*/\n\nsmall {\n font-size: 80%;\n}\n\n/\*\*\n \* Prevent `sub` and `sup` elements from affecting the line height in\n \* all browsers.\n \*/\n\nsub, \nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded content\n

=====  
\*\n\n/\*\*\n \* Add the correct display in IE 9-.\n \*/\n\naudio, \nvideo {\n display: inline-block;\n}\n\n/\*\*\n \* Add the correct display in iOS 4-7.\n \*/\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n/\*\*\n \* Remove the border on images inside links in IE 10-.\n \*/\n\nimg {\n border-style: none;\n}\n\n/\*\*\n \* Hide the overflow in IE.\n \*/\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\*\n\n/\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n \*/\n\nbutton, \ninput, \noptgroup, \nselect, \ntextarea {\n font-family: sans-serif; /\* 1 \*\n font-size: 100%; /\* 1 \*\n line-height: 1.15; /\* 1 \*\n margin: 0; /\* 2 \*\n}\n\n/\*\*\n \* Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n \*/\n\nbutton, \ninput {\n \* 1 \*\n overflow: visible;\n}\n\n/\*\*\n \* Remove the inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n \*/\n\nbutton, \nselect {\n \* 1 \*\n text-transform: none;\n}\n\n/\*\*\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable types in iOS and Safari.\n \*/\n\nbutton, \nhtml [type="button"], /\* 1 \*\n [type="reset"], \n [type="submit"] {\n -webkit-appearance: button; /\* 2 \*\n}\n\n/\*\*\n \* Remove the inner border and padding in Firefox.\n \*/\n\nbutton::-moz-focus-inner, \n [type="button"]::-moz-focus-inner, \n [type="reset"]::-moz-focus-inner, \n [type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n/\*\*\n \* Restore the focus styles unset by the previous rule.\n \*/\n\nbutton:-moz-focusing, \n [type="button"]:-moz-focusing, \n [type="reset"]:-moz-focusing, \n [type="submit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n\n/\*\*\n \* Correct the padding in Firefox.\n \*/\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n/\*\*\n \* 1. Correct the text wrapping in Edge and IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers are not caught out when they zero out\n \* `fieldset` elements in all browsers.\n \*/\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*\n color: inherit; /\* 2 \*\n display: table; /\* 1 \*\n max-width: 100%; /\* 1 \*\n padding: 0; /\* 3 \*\n white-space: normal; /\* 1 \*\n}\n\n/\*\*\n \* 1. Add the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*/\n\nprogress {\n display: inline-block; /\* 1 \*\n vertical-align: baseline; /\* 2 \*\n}\n\n/\*\*\n \* Remove the default vertical scrollbar in IE.\n \*/\n\ntextarea {\n overflow: auto;\n}\n\n/\*\*\n \* 1. Add the correct box sizing in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*/\n\n [type="checkbox"], \n [type="radio"] {\n

-webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n padding: 0; /\* 2 \*/\n}\n\n\*\*\n \*

Correct the cursor style of increment and decrement buttons in Chrome.\n

\*\n\n[type=\\\"number\\\"]::-webkit-inner-spin-button,\n[type=\\\"number\\\"]::-webkit-outer-spin-button {\n height: auto;\n}\n\n\*\*\n \* 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in

Safari.\n \*\n\n[type=\\\"search\\\"] {\n -webkit-appearance: textfield; /\* 1 \*/\n outline-offset: -2px; /\* 2

\*\n}\n\n\*\*\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n

\*\n\n[type=\\\"search\\\"]::-webkit-search-cancel-button,\n[type=\\\"search\\\"]::-webkit-search-decoration {\n -webkit-appearance: none;\n}\n\n\*\*\n \* 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2.

Change font properties to `inherit` in Safari.\n \*\n\n::-webkit-file-upload-button {\n -webkit-appearance: button; /\* 1 \*/\n font: inherit; /\* 2 \*/\n}\n\n/\* Interactive\n

=====  
\*\n\n/\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in Edge, IE, and Firefox.\n

\*\n\n\ndetails, /\* 1 \*/\n\nmenu {\n display: block;\n}\n\n/\*\n \* Add the correct display in all browsers.\n

\*\n\n\nsummary {\n display: list-item;\n}\n\n/\* Scripting\n

=====  
\*\n\n\*\*\n \* Add the correct display in IE 9-.\n \*\n\n\ncanvas {\n display: inline-block;\n}\n\n\*\*\n \* Add the correct display in IE.\n \*\n\n\ntemplate {\n display: none;\n}\n\n/\* Hidden\n

=====  
\*\n\n\*\*\n \* Add the correct display in IE 10-.\n \*\n\n\n[hidden] {\n display: none;\n}\n\n", "",  
{ "version": 3, "sources": ["/home/ubuntu/ReactThumbSignIn/node\_modules/normalize.css/normalize.css"], "names": [], "mappings": "AAAA,4EAA4E;;AAE5E;gFACgF;;AAEhF;;;GAIG;;AAEH;EACE,kBAaKB,CAAC,OA  
AO;EAC1B,2BAA2B,CAAC,OAAO;EACnC,+BAA+B,CAAC,OAAO;CACxC;;AAED;gFACgF;;AAEhF;;G  
AEG;;AAEH;EACE,UAAU;CACX;;AAED;;GAEG;;AAEH;;;;;EAME,eAAe;CACHB;;AAED;;;GAGG;;AAE  
H;EACE,eAAe;EACf,iBAaIB;CACIB;;AAED;gFACgF;;AAEhF;;;GAGG;;AAEH;;OAE0,OAAO;EACZ,eA  
Ae;CACHB;;AAED;;GAEG;;AAEH;EACE,iBAaIB;CACIB;;AAED;;;GAGG;;AAEH;EACE,gCAAgC;UACx  
B,wBAawB,CAAC,OAAO;EACxC,UAAU,CAAC,OAAO;EAC1B,kBAaKB,CAAC,OAAO;CAC3B;;AAED;;  
;GAGG;;AAEH;EACE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED;gFACgF;;AA  
EhF;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,sCAAsC,CAAC,OAAO;CAC/C;;AAED;;;GAG  
G;;AAEH;EACE,oBAaOB,CAAC,OAAO;EAC5B,2BAA2B,CAAC,OAAO;EACnC,0CAA0C;UACIC,kCAA  
kC,CAAC,OAAO;CACnD;;AAED;;GAEG;;AAEH;;EAEe,qBAaQB;CACtB;;AAED;;GAEG;;AAEH;;EAEe,  
oBAaOB;CACrB;;AAED;;;GAGG;;AAEH;;EAGE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;C  
ACxB;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;;GAEG;;AAEH;EACE,uBAaUB;EACvB,Y  
AAY;CACb;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EAEe,eAAe;EACf,eAA  
e;EACf,mBAaMB;EACnB,yBAaYB;CAC1B;;AAED;EACE,gBAaGB;CACjB;;AAED;EACE,YAAY;CACb;;  
AAED;gFACgF;;AAEhF;;GAEG;;AAEH;;EAEe,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;EA  
Cd,UAAU;CACX;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;;GAEG;;AAEH;EACE,iBAaIB  
;CACIB;;AAED;gFACgF;;AAEhF;;;GAGG;;AAEH;;;;;EAKE,wBAawB,CAAC,OAAO;EACHC,gBAaGB,CA  
AC,OAAO;EACxB,kBAaKB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;;GAGG;;AAEH  
;QACQ,OAAO;EACb,kBAaKB;CACnB;;AAED;;;GAGG;;AAEH;SACS,OAAO;EACd,qBAaQB;CACtB;;A  
AED;;;;;GAIG;;AAEH;;;;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;;;;EAIE,mBAaMB;  
EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;;;;EAIE,+BAA+B;CACHC;;AAED;;GAEG;;AAEH;EACE,+  
BAA+B;CACHC;;AAED;;;;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAaUB,CAAC,OAAO;EACvC,eAAe,  
CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAaGB,CAAC,OAAO;EACxB,WAAW,CAAC,OAA

O;EACnB,oBAAoB,CAAC,OAAO;CAC7B;;AAED;;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,yBAAyB,CAAC,OAAO;CAClC;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EAEe,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AAEH;;EAEe,aAAa;CACd;;AAED;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAAqB,CAAC,OAAO;CAC9B;;AAED;;GAEG;;AAEH;;EAEe,yBAAyB;CAC1B;;AAED;;;GAGG;;AAEH;EACE,2BAA2B,C AAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;EAEe,eAAe;CACHB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;gFACgF;;AAEHf;;GAEG;;AAEH;EACE,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED;gFACgF;;AAEHf;;GAEG;;AAEH;EACE,cAAc;CACf","file":"normalize.css","sourcesContent":["/\*! normalize.css v7.0.0 | MIT License |  
github.com/necolas/normalize.css \*/\n\n/\* Document\n

vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded content\n

=====  
\*\n\n\*\*\n \* Add the correct display in IE 9-.\n \*\n\naudio,\nvideo {\n display: inline-block;\n}\n\n\*\*\n \* Add the correct display in iOS 4-7.\n \*\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n\*\*\n \* Remove the border on images inside links in IE 10-.\n \*\n\nimg {\n border-style: none;\n}\n\n\*\*\n \* Hide the overflow in IE.\n \*\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\*\n\n\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n \*\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*\n font-size: 100%; /\* 1 \*\n line-height: 1.15; /\* 1 \*\n margin: 0; /\* 2 \*\n}\n\n\*\*\n \* Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n \*\n\nbutton,\ninput {\n /\* 1 \*\n overflow: visible;\n}\n\n\*\*\n \* Remove the inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n \*\n\nbutton,\nselect {\n /\* 1 \*\n text-transform: none;\n}\n\n\*\*\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable types in iOS and Safari.\n \*\n\nbutton,\nhtml [type="button"], /\* 1 \*\n[type="reset"],\n[type="submit"] {\n -webkit-appearance: button; /\* 2 \*\n}\n\n\*\*\n \* Remove the inner border and padding in Firefox.\n \*\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n\*\*\n \* Restore the focus styles unset by the previous rule.\n

\*\n\nbutton:-moz-focusing,\n[type="button"]:-moz-focusing,\n[type="reset"]:-moz-focusing,\n[type="submit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n\n\*\*\n \* Correct the padding in Firefox.\n \*\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n\*\*\n \* 1. Correct the text wrapping in Edge and IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers are not caught out when they zero out `fieldset` elements in all browsers.\n \*\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*\n color: inherit; /\* 2 \*\n display: table; /\* 1 \*\n max-width: 100%; /\* 1 \*\n padding: 0; /\* 3 \*\n white-space: normal; /\* 1 \*\n}\n\n\*\*\n \* 1. Add the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*\n\nprogress {\n display: inline-block; /\* 1 \*\n vertical-align: baseline; /\* 2 \*\n}\n\n\*\*\n \* Remove the default vertical scrollbar in IE.\n \*\n\ntextarea {\n overflow: auto;\n}\n\n\*\*\n \* 1. Add the correct box sizing in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*\n\n[type="checkbox"],\n[type="radio"] {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*\n padding: 0; /\* 2 \*\n}\n\n\*\*\n \* Correct the cursor style of increment and decrement buttons in Chrome.\n

\*\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n height: auto;\n}\n\n\*\*\n \* 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in Safari.\n \*\n\n[type="search"] {\n -webkit-appearance: textfield; /\* 1 \*\n outline-offset: -2px; /\* 2 \*\n}\n\n\*\*\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n \*\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n -webkit-appearance: none;\n}\n\n\*\*\n \* 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2. Change font properties to `inherit` in Safari.\n \*\n\n::-webkit-file-upload-button {\n -webkit-appearance: button; /\* 1 \*\n font: inherit; /\* 2 \*\n}\n\n/\* Interactive\n

=====  
\*\n\n\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in Edge, IE, and Firefox.\n

```

*^n\ndetails, /* 1 *^nmenu {\n display: block;\n}\n\n/*^n * Add the correct display in all browsers.\n
*^n\nsummary {\n display: list-item;\n}\n\n/* Scripting\n

```

```

=====
*^n\n/**^n * Add the correct display in IE 9-.\n *^n\ncanvas {\n display: inline-block;\n}\n\n/**^n * Add the
correct display in IE.\n *^n\ntemplate {\n display: none;\n}\n\n/* Hidden\n
=====

```

```

*^n\n/**^n * Add the correct display in IE 10-.\n *^n\n[hidden] {\n display: none;\n}\n\n", "sourceRoot": "" }]);
    user = _props.user,
    user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
    user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
    user.isLoggedin ? __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
user: {

```

```

    isLoggedin: !userInfo.isLoading ? userInfo.data.isLoggedin : ownProps.query.user.isLoggedin,
* `Indeterminate`, and `Query Indeterminate`.

```

```

* A `Query Indeterminate` linear progress bar is used when you are combining
* as a query indeterminate progress bar by adding the prop `query={true}` to the
* component. Until a progress value is given, it will display the query linear
* progress animation. Afterwards, it will start the determinate animation of where

```

```

    query = _props.query,
    props = _objectWithoutProperties(_props, ['className', 'progressClassName', 'progressStyle', 'value',
'query', 'centered']);

```

```

    'md-progress--linear-query': query,
* region until it is finished loading. It is not possible for the user to alter the value of a progressbar
* Boolean if this should be a query indeterminate progress bar.

```

```

query: _propTypes2.default.bool,
query: false

```

```

* region until it is finished loading. It is not possible for the user to alter the value of a progressbar

```

17-<https://stage.thumbsignin.com/assets/signup.chunk.js>

Other Information:           var user = this.props.user;  
                               'Simpler User Experience'  
                               'Strongly resistant to phishing, MITM and replay attacks. Built in anti-databreach  
 and user secret protection capabilities.'

```

    query: '{\n    ...userInfo    \n    }\n    ' +
__WEBPACK_IMPORTED_MODULE_3__v2_data_fragments__["a" /* default */]
    throw new Error('Failed to fetch user data');
    { query: data, __source: {

```

```

// this implementation is not 100% perfect for weird media query combinations

```

```

// Adapted from convert-source-map (MIT)

```

```

* // Remove it from the DOM

```

```

// bind timers to global for call from export context

```

```

// Thrash, waste and sodomy: IE GC bug

```

```

// IE 8- don't enum bug keys

```



```

err = new Error('You provided a ` ` + propFullNameSafe + ` ` + location + ` to the ` + componentNameSafe +
` that was ` + ('not within the range from ` + min + ` - ` + max + `'. ` + propFullNameSafe + `: ` + value + `'));
// Don't enum bug & hidden keys
// getting tag from 19.1.3.6 Object.prototype.toString()
return fetch('/api/user').then(function (response) {
return fetch('/api/user', { method: "POST", body: userInfo }).then(function (response) {
// import { Provider } from '../Modal'
query: __WEBPACK_IMPORTED_MODULE_1_prop_types__default.a.isRequired
exports.push([module.i, "/*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css */\n\n/*
Document\n
=====
*\n\n**\n * 1. Correct the line height in all browsers.\n * 2. Prevent adjustments of font size after orientation
changes in\n * IE on Windows Phone and in iOS.\n */\n\nhtml {\n line-height: 1.15; /* 1 *\n
-ms-text-size-adjust: 100%; /* 2 *\n -webkit-text-size-adjust: 100%; /* 2 *\n}\n\n/* Sections\n
=====
*\n\n**\n * Remove the margin in all browsers (opinionated).\n */\n\nbody {\n margin: 0;\n}\n\n**\n * Add
the correct display in IE 9-.\n */\n\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display:
block;\n}\n\n**\n * Correct the font size and margin on `h1` elements within `section` and\n * `article`
contexts in Chrome, Firefox, and Safari.\n */\n\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/* Grouping
content\n
=====
*\n\n**\n * Add the correct display in IE 9-.\n * 1. Add the correct display in IE.\n
*\n\nfigcaption,\nfigure,\nmain { /* 1 *\n display: block;\n}\n\n**\n * Add the correct margin in IE 8.\n
*\n\nfigure {\n margin: 1em 40px;\n}\n\n**\n * 1. Add the correct box sizing in Firefox.\n * 2. Show the
overflow in Edge and IE.\n */\n\nhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /* 1
*\n height: 0; /* 1 *\n overflow: visible; /* 2 *\n}\n\n**\n * 1. Correct the inheritance and scaling of font
size in all browsers.\n * 2. Correct the odd `em` font sizing in all browsers.\n */\n\npre {\n font-family:
monospace, monospace; /* 1 *\n font-size: 1em; /* 2 *\n}\n\n/* Text-level semantics\n
=====
*\n\n**\n * 1. Remove the gray background on active links in IE 10.\n * 2. Remove gaps in links underline in
iOS 8+ and Safari 8+.\n */\n\na {\n background-color: transparent; /* 1 *\n -webkit-text-decoration-skip:
objects; /* 2 *\n}\n\n**\n * 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n * 2. Add the
correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n */\n\nabbr[title] {\n border-bottom: none; /*
1 *\n text-decoration: underline; /* 2 *\n -webkit-text-decoration: underline dotted;\n text-decoration:
underline dotted; /* 2 *\n}\n\n**\n * Prevent the duplicate application of `bolder` by the next rule in Safari
6.\n */\n\nb,\nstrong {\n font-weight: inherit;\n}\n\n**\n * Add the correct font weight in Chrome, Edge, and
Safari.\n */\n\nb,\nstrong {\n font-weight: bolder;\n}\n\n**\n * 1. Correct the inheritance and scaling of font
size in all browsers.\n * 2. Correct the odd `em` font sizing in all browsers.\n */\n\ncode,\nkbd,\nsamp {\n
font-family: monospace, monospace; /* 1 *\n font-size: 1em; /* 2 *\n}\n\n**\n * Add the correct font style in
Android 4.3-.\n */\n\ni,\ndfn {\n font-style: italic;\n}\n\n**\n * Add the correct background and color in IE 9-.\n
*\n\nmark {\n background-color: #ff0;\n color: #000;\n}\n\n**\n * Add the correct font size in all
browsers.\n */\n\nsmall {\n font-size: 80%;\n}\n\n**\n * Prevent `sub` and `sup` elements from affecting the
line height in\n * all browsers.\n */\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n

```

vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded content\n

=====  
\*\n\n\*\*\n \* Add the correct display in IE 9-.\n \*\n\naudio,\nvideo {\n display: inline-block;\n}\n\n\*\*\n \* Add the correct display in iOS 4-7.\n \*\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n\*\*\n \* Remove the border on images inside links in IE 10-.\n \*\n\nimg {\n border-style: none;\n}\n\n\*\*\n \* Hide the overflow in IE.\n \*\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\*\n\n\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n \*\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*\n font-size: 100%; /\* 1 \*\n line-height: 1.15; /\* 1 \*\n margin: 0; /\* 2 \*\n}\n\n\*\*\n \* Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n \*\n\nbutton,\ninput {\n /\* 1 \*\n overflow: visible;\n}\n\n\*\*\n \* Remove the inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n \*\n\nbutton,\nselect {\n /\* 1 \*\n text-transform: none;\n}\n\n\*\*\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable types in iOS and Safari.\n \*\n\nbutton,\nhtml [type="button"], /\* 1 \*\n[type="reset"],\n[type="submit"] {\n -webkit-appearance: button; /\* 2 \*\n}\n\n\*\*\n \* Remove the inner border and padding in Firefox.\n \*\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n\*\*\n \* Restore the focus styles unset by the previous rule.\n

\*\n\nbutton:-moz-focusing,\n[type="button"]:-moz-focusing,\n[type="reset"]:-moz-focusing,\n[type="submit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n\n\*\*\n \* Correct the padding in Firefox.\n \*\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n\*\*\n \* 1. Correct the text wrapping in Edge and IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers are not caught out when they zero out `fieldset` elements in all browsers.\n \*\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*\n color: inherit; /\* 2 \*\n display: table; /\* 1 \*\n max-width: 100%; /\* 1 \*\n padding: 0; /\* 3 \*\n white-space: normal; /\* 1 \*\n}\n\n\*\*\n \* 1. Add the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*\n\nprogress {\n display: inline-block; /\* 1 \*\n vertical-align: baseline; /\* 2 \*\n}\n\n\*\*\n \* Remove the default vertical scrollbar in IE.\n \*\n\ntextarea {\n overflow: auto;\n}\n\n\*\*\n \* 1. Add the correct box sizing in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*\n\n[type="checkbox"],\n[type="radio"] {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*\n padding: 0; /\* 2 \*\n}\n\n\*\*\n \* Correct the cursor style of increment and decrement buttons in Chrome.\n

\*\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n height: auto;\n}\n\n\*\*\n \* 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in Safari.\n \*\n\n[type="search"] {\n -webkit-appearance: textfield; /\* 1 \*\n outline-offset: -2px; /\* 2 \*\n}\n\n\*\*\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n \*\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n -webkit-appearance: none;\n}\n\n\*\*\n \* 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2. Change font properties to `inherit` in Safari.\n \*\n\n::-webkit-file-upload-button {\n -webkit-appearance: button; /\* 1 \*\n font: inherit; /\* 2 \*\n}\n\n/\* Interactive\n

=====  
\*\n\n\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in Edge, IE, and Firefox.\n

\*\n\ndetails, /\* 1 \*\nmenu {\n display: block;\n}\n\n/\*\n \* Add the correct display in all browsers.\n\n\*\n\nsummary {\n display: list-item;\n}\n\n/\* Scripting\n

=====  
\*\n\n\*\*\n \* Add the correct display in IE 9-.\n\n\*\n\nncanvas {\n display: inline-block;\n}\n\n\*\*\n \* Add the correct display in IE.\n\n\*\n\nntemplate {\n display: none;\n}\n\n/\* Hidden\n

=====  
\*\n\n\*\*\n \* Add the correct display in IE 10-.\n\n\*\n\n[hidden] {\n display: none;\n}\n", "",  
{ "version":3,"sources":["/home/ubuntu/ReactThumbSignIn/node\_modules/normalize.css/normalize.css"],"names":[],"mappings":"AAAA,4EAA4E;;AAE5E:gFACgF;;AAEhF;;;GAIG;;AAEH;EACE,kBAAkB,CAAC,OA  
AO;EAC1B,2BAA2B,CAAC,OAAO;EACnC,+BAA+B,CAAC,OAAO;CACxC;;AAED:gFACgF;;AAEhF;;G  
AEG;;AAEH;EACE,UAAU;CACX;;AAED;;GAEG;;AAEH;;;;;EAME,eAAe;CACHB;;AAED;;;GAGG;;AAE  
H;EACE,eAAe;EACf,iBAAiB;CACIB;;AAED:gFACgF;;AAEhF;;;GAGG;;AAEH;;OAE0,OAAO;EACZ,eA  
Ae;CACHB;;AAED;;GAEG;;AAEH;EACE,iBAAiB;CACIB;;AAED;;;GAGG;;AAEH;EACE,gCAAgC;UACx  
B,wBAAwB,CAAC,OAAO;EACxC,UAAU,CAAC,OAAO;EACIB,kBAAkB,CAAC,OAAO;CAC3B;;AAED;;  
;GAGG;;AAEH;EACE,kCAAkC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED:gFACgF;;AA  
EhF;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,sCAAsC,CAAC,OAAO;CAC/C;;AAED;;;GAG  
G;;AAEH;EACE,oBAAoB,CAAC,OAAO;EAC5B,2BAA2B,CAAC,OAAO;EACnC,0CAA0C;UACIC,kCAA  
kC,CAAC,OAAO;CACnD;;AAED;;GAEG;;AAEH;;EAEe,qBAAqB;CACtB;;AAED;;GAEG;;AAEH;;EAEe,  
oBAAoB;CACrB;;AAED;;;GAGG;;AAEH;;EAGE,kCAAkC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;C  
ACxB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,uBAAuB;EACvB,Y  
AAY;CACb;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EAEe,eAAe;EACf,eAA  
e;EACf,mBAAmB;EACnB,yBAAyB;CAC1B;;AAED;EACE,gBAAgB;CACjB;;AAED;EACE,YAAY;CACb;;  
AAED:gFACgF;;AAEhF;;GAEG;;AAEH;;EAEe,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;EA  
Cd,UAAU;CACX;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,iBAAiB  
;CACIB;;AAED:gFACgF;;AAEhF;;;GAGG;;AAEH;;;;;EAKE,wBAAwB,CAAC,OAAO;EACChC,gBAAgB,CA  
AC,OAAO;EACxB,kBAAkB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;;GAGG;;AAEH  
;QACQ,OAAO;EACb,kBAAkB;CACnB;;AAED;;;GAGG;;AAEH;SACS,OAAO;EACd,qBAAqB;CACtB;;A  
AED;;;GAIG;;AAEH;;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;;EAIE,mBAAmB;  
EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;;EAIE,+BAA+B;CACHC;;AAED;;GAEG;;AAEH;EACE,+  
BAA+B;CACHC;;AAED;;;;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,eAAe,  
CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAAgB,CAAC,OAAO;EACxB,WAAW,CAAC,OAA  
O;EACnB,oBAAoB,CAAC,OAAO;CAC7B;;AAED;;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,  
yBAAyB,CAAC,OAAO;CACIC;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EA  
EE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AA  
EH;;EAEe,aAAa;CACd;;AAED;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAAqB,CAAC,O  
AAO;CAC9B;;AAED;;GAEG;;AAEH;;EAEe,yBAAyB;CAC1B;;AAED;;;GAGG;;AAEH;EACE,2BAA2B,C  
AAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED:gFACgF;;AAEhF;;;GAGG;;AAEH;;EAEe,eAAe;  
CACHB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED:gFACgF;;AAEhF;;GAEG;;AAEH;EACE,  
sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED:gFACgF;;AAEhF;;GAEG;;AAEH;EAC  
E,cAAc;CACf","file":"normalize.css","sourcesContent":["/\*! normalize.css v7.0.0 | MIT License |  
github.com/necolas/normalize.css \*/\n\n/\* Document\n

=====  
\*\n\n\*\*\n \* 1. Correct the line height in all browsers.\n\n \* 2. Prevent adjustments of font size after orientation

changes in\n \* IE on Windows Phone and in iOS.\n \*/\n\nhtml {\n line-height: 1.15; /\* 1 \*/\n -ms-text-size-adjust: 100%; /\* 2 \*/\n -webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n

=====  
\n\n\*\*\n \* Remove the margin in all browsers (opinionated).\n \*/\n\nbody {\n margin: 0;\n}\n\n\*\*\n \* Add the correct display in IE 9-.\n \*/\n\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display: block;\n}\n\n\*\*\n \* Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.\n \*/\n\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping content\n

=====  
\n\n\*\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in IE.\n \*/\n\nfigcaption,\nfigure,\nmain { /\* 1 \*/\n display: block;\n}\n\n\*\*\n \* Add the correct margin in IE 8.\n \*/\n\nfigure {\n margin: 1em 40px;\n}\n\n\*\*\n \* 1. Add the correct box sizing in Firefox.\n \* 2. Show the overflow in Edge and IE.\n \*/\n\nhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /\* 1 \*/\n height: 0; /\* 1 \*/\n overflow: visible; /\* 2 \*/\n}\n\n\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\npre {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\* Text-level semantics\n

=====  
\n\n\*\*\n \* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in iOS 8+ and Safari 8+.\n \*/\n\na {\n background-color: transparent; /\* 1 \*/\n -webkit-text-decoration-skip: objects; /\* 2 \*/\n}\n\n\*\*\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*/\n\nabbr[title] {\n border-bottom: none; /\* 1 \*/\n text-decoration: underline; /\* 2 \*/\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*/\n}\n\n\*\*\n \* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n \*/\n\nb,\nstrong {\n font-weight: inherit;\n}\n\n\*\*\n \* Add the correct font weight in Chrome, Edge, and Safari.\n \*/\n\nb,\nstrong {\n font-weight: bolder;\n}\n\n\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\ncode,\nkbd,\nsamp {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n\*\*\n \* Add the correct font style in Android 4.3-.\n \*/\n\ndfn {\n font-style: italic;\n}\n\n\*\*\n \* Add the correct background and color in IE 9-.\n \*/\n\nmark {\n background-color: #ff0;\n color: #000;\n}\n\n\*\*\n \* Add the correct font size in all browsers.\n \*/\n\nsmall {\n font-size: 80%;\n}\n\n\*\*\n \* Prevent `sub` and `sup` elements from affecting the line height in all browsers.\n \*/\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded content\n

=====  
\n\n\*\*\n \* Add the correct display in IE 9-.\n \*/\n\naudio,\nvideo {\n display: inline-block;\n}\n\n\*\*\n \* Add the correct display in iOS 4-7.\n \*/\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n\*\*\n \* Remove the border on images inside links in IE 10-.\n \*/\n\nimg {\n border-style: none;\n}\n\n\*\*\n \* Hide the overflow in IE.\n \*/\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\n\n\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n \*/\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*/\n font-size: 100%; /\* 1 \*/\n line-height: 1.15; /\* 1 \*/\n margin: 0; /\* 2 \*/\n}\n\n\*\*\n \* Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n \*/\n\nbutton,\ninput { /\* 1 \*/\n overflow: visible;\n}\n\n\*\*\n \* Remove the



```

    isLogedin: !userInfo.isLoading ? userInfo.data.isLogedin : ownProps.query.user.isLogedin,
    * `Indeterminate`, and `Query Indeterminate`.
    * A `Query Indeterminate` linear progress bar is used when you are combining
    * as a query indeterminate progress bar by adding the prop `query={true}` to the
    * component. Until a progress value is given, it will display the query linear
    * progress animation. Afterwards, it will start the determinate animation of where
      query = _props.query,
      props = _objectWithoutProperties(_props, ['className', 'progressClassName', 'progressStyle', 'value',
'query', 'centered']);
      'md-progress--linear-query': query,
    * region until it is finished loading. It is not possible for the user to alter the value of a progressbar
    * Boolean if this should be a query indeterminate progress bar.
    query: _propTypes2.default.bool,
    query: false
    * region until it is finished loading. It is not possible for the user to alter the value of a progressbar
var userInfoFragment = "fragment userInfo on Root{\n  user {\n    isLogedin\n    isNewUser\n    userId\n    admin\n  }\n}";

```

18-[https://stage.thumbsignin.com/assets/privacy\\_m.chunk.js](https://stage.thumbsignin.com/assets/privacy_m.chunk.js)

Other Information: 'We are very delighted that you have shown interest in our enterprise. Data protection is of a particularly high priority for the management of the ThumbSignIn. The use of the Internet pages of the ThumbSignIn is possible without any indication of personal data; however, if a data subject wants to use special enterprise services via our website, processing of personal data could become necessary. If the processing of personal data is necessary and there is no statutory basis for such processing, we generally obtain consent from the data subject.'

'Controller or controller responsible for the processing is the natural or legal person, public authority, agency or other body which, alone or jointly with others, determines the purposes and means of the processing of personal data; where the purposes and means of such processing are determined by Union or Member State law, the controller or the specific criteria for its nomination may be provided for by Union or Member State law.'

'The website of the ThumbSignIn collects a series of general data and information when a data subject or automated system calls up the website. This general data and information are stored in the server log files. Collected may be (1) the browser types and versions used, (2) the operating system used by the accessing system, (3) the website from which an accessing system reaches our website (so-called referrers), (4) the sub-websites, (5) the date and time of access to the Internet site, (6) an Internet protocol address (IP address), (7) the Internet service provider of the accessing system, and (8) any other similar data and information that may be used in the event of attacks on our information technology systems.'

'When using these general data and information, the ThumbSignIn does not draw any conclusions about the data subject. Rather, this information is needed to (1) deliver the content of our website correctly, (2) optimize the content of our website as well as its advertisement, (3) ensure the long-term viability of our information technology systems and website technology, and (4) provide law enforcement authorities with the information necessary for criminal prosecution in case of a cyber-attack. Therefore, the ThumbSignIn analyzes anonymously collected data and information statistically, with the aim of increasing the data

protection and data security of our enterprise, and to ensure an optimal level of protection for the personal data we process. The anonymous data of the server log files are stored separately from all personal data provided by a data subject. ThumbSignin makes use of OS provided biometric mechanism for authentication purposes and never stores any biometric related information in the backend.'

'No location information of the device/user is collected.No cookies is created/saved by ThumbSignIn platform. Device name & device OS (Device Information) is collected & this data is used to show the number of devices you have registered along with the device name & OS version to you and your app creator.'

'Only data shared with your app creator (web & app). No data is shared with any third party. Your app creator is the owner/admin of the website/mobile app you use and has integrated with ThumbSignIn platform.'

'The registration of the data subject, with the voluntary indication of personal data, is intended to enable the controller to offer the data subject contents or services that may only be offered to registered users due to the nature of the matter in question. Registered persons are free to change the personal data specified during the registration at any time, or to have them completely deleted from the data stock of the controller.'

'On the website of the ThumbSignIn, users are given the opportunity to subscribe to our enterprise\'s newsletter. The input mask used for this purpose determines what personal data are transmitted, as well as when the newsletter is ordered from the controller.'

'During the registration for the newsletter, we also store the IP address of the computer system assigned by the Internet service provider (ISP) and used by the data subject at the time of the registration, as well as the date and time of the registration. The collection of this data is necessary in order to understand the (possible) misuse of the e-mail address of a data subject at a later date, and it therefore serves the aim of the legal protection of the controller.'

'The personal data collected as part of a registration for the newsletter will only be used to send our newsletter. In addition, subscribers to the newsletter may be informed by e-mail, as long as this is necessary for the operation of the newsletter service or a registration in question, as this could be the case in the event of modifications to the newsletter offer, or in the event of a change in technical circumstances. There will be no transfer of personal data collected by the newsletter service to third parties. The subscription to our newsletter may be terminated by the data subject at any time. The consent to the storage of personal data, which the data subject has given for shipping the newsletter, may be revoked at any time. For the purpose of revocation of consent, a corresponding link is found in each newsletter. It is also possible to unsubscribe from the newsletter at any time directly on the website of the controller or to communicate this to the controller in a different way.'

'Such personal data collected in the tracking pixels contained in the newsletters are stored and analyzed by the controller in order to optimize the shipping of the newsletter, as well as to adapt the content of future newsletters even better to the interests of the data subject. These personal data will not be passed on to third parties. Data subjects are at any time entitled to revoke the respective separate declaration of consent issued by means of the double-opt-in procedure. After a revocation, these personal data will be deleted by the controller. The ThumbSignIn automatically regards a withdrawal from the receipt of the newsletter as a revocation.'

'Each data subject shall have the right to obtain from the controller the confirmation as to whether or not personal data concerning him or her are being processed.'

'Each data subject shall have the right to obtain from the controller-free information

about his or her personal data stored at any time and a copy of this information. Furthermore, the European directives and regulations grant the data subject access to the following information:'

'where possible, the envisaged period for which the personal data will be stored, or, if not possible, the criteria used to determine that period;',

'the existence of the right to request from the controller rectification or erasure of personal data, or restriction of processing of personal data concerning the data subject, or to object to such processing;',

'where the personal data are not collected from the data subject, any available information as to their source;',

'Furthermore, the data subject shall have a right to obtain information as to whether personal data are transferred to a third country or to an international organization. Where this is the case, the data subject shall have the right to be informed of the appropriate safeguards relating to the transfer.'

'Each data subject shall have the right granted by the European legislator to obtain from the controller without undue delay the rectification of inaccurate personal data concerning him or her. Taking into account the purposes of the processing, the data subject shall have the right to have incomplete personal data completed, including by means of providing a supplementary statement.'

'Each data subject shall have the right granted by the European legislator to obtain from the controller the erasure of personal data concerning him or her without undue delay, and the controller shall have the obligation to erase personal data without undue delay where one of the following grounds applies, as long as the processing is not necessary:'

'The data subject withdraws consent to which the processing is based according to the point (a) of Article 6(1) of the GDPR, or point (a) of Article 9(2) of the GDPR, and where there is no other legal ground for the processing.',

'Where the controller has made personal data public and is obliged pursuant to Article 17(1) to erase the personal data, the controller, taking account of available technology and the cost of implementation, shall take reasonable steps, including technical measures, to inform other controllers processing the personal data that the data subject has requested erasure by such controllers of any links to, or copy or replication of, those personal data, as far as processing is not required. An employee of the ThumbSignIn will arrange the necessary measures in individual cases.'

'Each data subject shall have the right granted by the European legislator to obtain from the controller restriction of processing where one of the following applies:'

'Each data subject shall have the right granted by the European legislator, to receive the personal data concerning him or her, which was provided to a controller, in a structured, commonly used and machine-readable format. He or she shall have the right to transmit those data to another controller without hindrance from the controller to which the personal data have been provided, as long as the processing is based on consent pursuant to point (a) of Article 6(1) of the GDPR or point (a) of Article 9(2) of the GDPR, or on a contract pursuant to point (b) of Article 6(1) of the GDPR, and the processing is carried out by automated means, as long as the processing is not necessary for the performance of a task carried out in the public interest or in the exercise of official authority vested in the controller.'

'Furthermore, in exercising his or her right to data portability pursuant to Article 20(1) of the GDPR, the data subject shall have the right to have personal data transmitted directly from one controller to another, where technically feasible and when doing so does not adversely affect the rights and freedoms of others.'



'On this website, the controller has integrated the component of Google Analytics (with the anonymizer function). Google Analytics is a web analytics service. Web analytics is the collection, gathering, and analysis of data about the behavior of visitors to websites. A web analysis service collects, inter alia, data about the website from which a person has come (the so-called referrer), which sub-pages were visited, or how often and for what duration a sub-page was viewed. Web analytics are mainly used for the optimization of a website and in order to carry out a cost-benefit analysis of Internet advertising.'

'For the web analytics through Google Analytics the controller uses the application "\_gat.\_anonymizeIp". By means of this application, the IP address of the Internet connection of the data subject is abridged by Google and anonymized when accessing our websites from a Member State of the European Union or another Contracting State to the Agreement on the European Economic Area.'

'The cookie is used to store personal information, such as the access time, the location from which the access was made, and the frequency of visits to our website by the data subject. With each visit to our Internet site, such personal data, including the IP address of the Internet access used by the data subject, will be transmitted to Google in the United States of America. These personal data are stored by Google in the United States of America. Google may pass these personal data collected through the technical procedure to third parties.'

'The data subject may, as stated above, prevent the setting of cookies through our website at any time by means of a corresponding adjustment of the web browser used and thus permanently deny the setting of cookies. Such an adjustment to the Internet browser used would also prevent Google Analytics from setting a cookie on the information technology system of the data subject. In addition, cookies already in use by Google Analytics may be deleted at any time via a web browser or other software programs.'

' and install it. This browser add-on tells Google Analytics through a JavaScript, that any data and information about the visits of Internet pages may not be transmitted to Google Analytics. The installation of the browser add-ons is considered an objection by Google. If the information technology system of the data subject is later deleted, formatted, or newly installed, then the data subject must reinstall the browser add-ons to disable Google Analytics. If the browser add-on was uninstalled by the data subject or any other person who is attributable to their sphere of competence or is disabled, it is possible to execute the reinstallation or reactivation of the browser add-ons.'

'If the data subject is logged in at the same time on LinkedIn, LinkedIn detects with every call-up to our website by the data subject\u2014and for the entire duration of their stay on our Internet site\u2014which specific sub-page of our Internet page was visited by the data subject. This information is collected through the LinkedIn component and associated with the respective LinkedIn account of the data subject. If the data subject clicks on one of the LinkedIn buttons integrated on our website, then LinkedIn assigns this information to the personal LinkedIn user account of the data subject and stores the personal data.'

'LinkedIn receives information via the LinkedIn component that the data subject has visited our website, provided that the data subject is logged in at LinkedIn at the time of the call-up to our website. This occurs regardless of whether the person clicks on the LinkedIn button or not. If such a transmission of information to LinkedIn is not desirable for the data subject, then he or she may prevent this by logging off from their LinkedIn account before a call-up to our website is made.'

' the possibility to unsubscribe from e-mail messages, SMS messages and targeted ads, as well as the ability to manage ad settings. LinkedIn also uses affiliates such as Eire, Google Analytics, BlueKai, DoubleClick, Nielsen, Comscore, Eloqua, and Lotame. The setting of such cookies may be denied under '

'On this website, the controller has integrated components of Twitter. Twitter is a multilingual,

publicly-accessible microblogging service on which users may publish and spread so-called tweets, e.g. short messages, which are limited to 280 characters. These short messages are available for everyone, including those who are not logged on to Twitter. The tweets are also displayed to so-called followers of the respective user. Followers are other Twitter users who follow a user's tweets. Furthermore, Twitter allows you to address a wide audience via hashtags, links or retweets.'

'If the data subject is logged in at the same time on Twitter, Twitter detects with every call-up to our website by the data subject and for the entire duration of their stay on our Internet site which specific sub-page of our Internet page was visited by the data subject. This information is collected through the Twitter component and associated with the respective Twitter account of the data subject. If the data subject clicks on one of the Twitter buttons integrated on our website, then Twitter assigns this information to the personal Twitter user account of the data subject and stores the personal data.'

'Twitter receives information via the Twitter component that the data subject has visited our website, provided that the data subject is logged in on Twitter at the time of the call-up to our website. This occurs regardless of whether the person clicks on the Twitter component or not. If such a transmission of information to Twitter is not desirable for the data subject, then he or she may prevent this by logging off from their Twitter account before a call-up to our website is made.'

'YouTube and Google will receive information through the YouTube component that the data subject has visited our website if the data subject at the time of the call to our website is logged in on YouTube; this occurs regardless of whether the person clicks on a YouTube video or not. If such a transmission of this information to YouTube and Google is not desirable for the data subject, the delivery may be prevented if the data subject logs off from their own YouTube account before a call-up to our website is made.'

'Art. 6(1) lit. a GDPR serves as the legal basis for processing operations for which we obtain consent for a specific processing purpose. If the processing of personal data is necessary for the performance of a contract to which the data subject is party, as is the case, for example, when processing operations are necessary for the supply of goods or to provide any other service, the processing is based on Article 6(1) lit. b GDPR. The same applies to such processing operations which are necessary for carrying out pre-contractual measures, for example in the case of inquiries concerning our products or services. Is our company subject to a legal obligation by which processing of personal data is required, such as for the fulfillment of tax obligations, the processing is based on Art. 6(1) lit. c GDPR. In rare cases, the processing of personal data may be necessary to protect the vital interests of the data subject or of another natural person. This would be the case, for example, if a visitor were injured in our company and his name, age, health insurance data or other vital information would have to be passed on to a doctor, hospital or other third party. Then the processing would be based on Art. 6(1) lit. d GDPR. Finally, processing operations could be based on Article 6(1) lit. f GDPR. This legal basis is used for processing operations which are not covered by any of the abovementioned legal grounds, if processing is necessary for the purposes of the legitimate interests pursued by our company or by a third party, except where such interests are overridden by the interests or fundamental rights and freedoms of the data subject which require protection of personal data. Such processing operations are particularly permissible because they have been specifically mentioned by the European legislator. It is considered that a legitimate interest could be assumed if the data subject is a client of the controller (Recital 47 Sentence 2 GDPR).'

'Where the processing of personal data is based on Article 6(1) lit. f GDPR our legitimate interest is to carry out our business in favor of the well-being of all our employees and the shareholders.'

'We clarify that the provision of personal data is partly required by law (e.g. tax regulations) or can also result from contractual provisions (e.g. information on the contractual partner). Sometimes it may be

necessary to conclude a contract that the data subject provides us with personal data, which must subsequently be processed by us. The data subject is, for example, obliged to provide us with personal data when our company signs a contract with him or her. The non-provision of the personal data would have the consequence that the contract with the data subject could not be concluded. Before personal data is provided by the data subject, the data subject must contact any employee. The employee clarifies to the data subject whether the provision of the personal data is required by law or contract or is necessary for the conclusion of the contract, whether there is an obligation to provide the personal data and the consequences of non-provision of the personal data.'

'Thumbsignin reserves the right to modify or update our Privacy Policy at any time without notice, so we encourage you to review this policy from time to time.'

```
// this implementation is not 100% perfect for weird media query combinations
// Adapted from convert-source-map (MIT)
* // Remove it from the DOM
// bind timers to global for call from export context
// Thrash, waste and sodomy: IE GC bug
// IE 8- don't enum bug keys
// Don't enum bug & hidden keys
// getting tag from 19.1.3.6 Object.prototype.toString()
```

19-<https://stage.thumbsignin.com/assets/privacy.chunk.js>

Other Information: 'We are very delighted that you have shown interest in our enterprise. Data protection is of a particularly high priority for the management of the ThumbSignIn. The use of the Internet pages of the ThumbSignIn is possible without any indication of personal data; however, if a data subject wants to use special enterprise services via our website, processing of personal data could become necessary. If the processing of personal data is necessary and there is no statutory basis for such processing, we generally obtain consent from the data subject.'

'Controller or controller responsible for the processing is the natural or legal person, public authority, agency or other body which, alone or jointly with others, determines the purposes and means of the processing of personal data; where the purposes and means of such processing are determined by Union or Member State law, the controller or the specific criteria for its nomination may be provided for by Union or Member State law.'

'The website of the ThumbSignIn collects a series of general data and information when a data subject or automated system calls up the website. This general data and information are stored in the server log files. Collected may be (1) the browser types and versions used, (2) the operating system used by the accessing system, (3) the website from which an accessing system reaches our website (so-called referrers), (4) the sub-websites, (5) the date and time of access to the Internet site, (6) an Internet protocol address (IP address), (7) the Internet service provider of the accessing system, and (8) any other similar data and information that may be used in the event of attacks on our information technology systems.'

'When using these general data and information, the ThumbSignIn does not draw any conclusions about the data subject. Rather, this information is needed to (1) deliver the content of our website correctly, (2) optimize the content of our website as well as its advertisement, (3) ensure the long-term viability of our information technology systems and website technology, and (4) provide law enforcement authorities with the information necessary for criminal prosecution in case of a cyber-attack. Therefore, the ThumbSignIn

analyzes anonymously collected data and information statistically, with the aim of increasing the data protection and data security of our enterprise, and to ensure an optimal level of protection for the personal data we process. The anonymous data of the server log files are stored separately from all personal data provided by a data subject. ThumbSignin makes use of OS provided biometric mechanism for authentication purposes and never stores any biometric related information in the backend.'

'No location information of the device/user is collected.No cookies is created/saved by ThumbSignIn platform. Device name & device OS (Device Information) is collected & this data is used to show the number of devices you have registered along with the device name & OS version to you and your app creator.'

'Only data shared with your app creator (web & app). No data is shared with any third party. Your app creator is the owner/admin of the website/mobile app you use and has integrated with ThumbSignIn platform.'

'The registration of the data subject, with the voluntary indication of personal data, is intended to enable the controller to offer the data subject contents or services that may only be offered to registered users due to the nature of the matter in question. Registered persons are free to change the personal data specified during the registration at any time, or to have them completely deleted from the data stock of the controller.'

'On the website of the ThumbSignIn, users are given the opportunity to subscribe to our enterprise\'s newsletter. The input mask used for this purpose determines what personal data are transmitted, as well as when the newsletter is ordered from the controller.'

'During the registration for the newsletter, we also store the IP address of the computer system assigned by the Internet service provider (ISP) and used by the data subject at the time of the registration, as well as the date and time of the registration. The collection of this data is necessary in order to understand the (possible) misuse of the e-mail address of a data subject at a later date, and it therefore serves the aim of the legal protection of the controller.'

'The personal data collected as part of a registration for the newsletter will only be used to send our newsletter. In addition, subscribers to the newsletter may be informed by e-mail, as long as this is necessary for the operation of the newsletter service or a registration in question, as this could be the case in the event of modifications to the newsletter offer, or in the event of a change in technical circumstances. There will be no transfer of personal data collected by the newsletter service to third parties. The subscription to our newsletter may be terminated by the data subject at any time. The consent to the storage of personal data, which the data subject has given for shipping the newsletter, may be revoked at any time. For the purpose of revocation of consent, a corresponding link is found in each newsletter. It is also possible to unsubscribe from the newsletter at any time directly on the website of the controller or to communicate this to the controller in a different way.'

'Such personal data collected in the tracking pixels contained in the newsletters are stored and analyzed by the controller in order to optimize the shipping of the newsletter, as well as to adapt the content of future newsletters even better to the interests of the data subject. These personal data will not be passed on to third parties. Data subjects are at any time entitled to revoke the respective separate declaration of consent issued by means of the double-opt-in procedure. After a revocation, these personal data will be deleted by the controller. The ThumbSignIn automatically regards a withdrawal from the receipt of the newsletter as a revocation.'

'Each data subject shall have the right to obtain from the controller the confirmation as to whether or not personal data concerning him or her are being processed.'

'Each data subject shall have the right to obtain from the controller free information about his or her personal data stored at any time and a copy of this information. Furthermore, the European directives and regulations grant the data subject access to the following information:'

'where possible, the envisaged period for which the personal data will be stored, or, if not possible, the criteria used to determine that period;',

'the existence of the right to request from the controller rectification or erasure of personal data, or restriction of processing of personal data concerning the data subject, or to object to such processing;',

'where the personal data are not collected from the data subject, any available information as to their source;',

'Furthermore, the data subject shall have a right to obtain information as to whether personal data are transferred to a third country or to an international organization. Where this is the case, the data subject shall have the right to be informed of the appropriate safeguards relating to the transfer.'

'Each data subject shall have the right granted by the European legislator to obtain from the controller without undue delay the rectification of inaccurate personal data concerning him or her. Taking into account the purposes of the processing, the data subject shall have the right to have incomplete personal data completed, including by means of providing a supplementary statement.'

'Each data subject shall have the right granted by the European legislator to obtain from the controller the erasure of personal data concerning him or her without undue delay, and the controller shall have the obligation to erase personal data without undue delay where one of the following grounds applies, as long as the processing is not necessary:'

'The data subject withdraws consent to which the processing is based according to the point (a) of Article 6(1) of the GDPR, or point (a) of Article 9(2) of the GDPR, and where there is no other legal ground for the processing.',

'Where the controller has made personal data public and is obliged pursuant to Article 17(1) to erase the personal data, the controller, taking account of available technology and the cost of implementation, shall take reasonable steps, including technical measures, to inform other controllers processing the personal data that the data subject has requested erasure by such controllers of any links to, or copy or replication of, those personal data, as far as processing is not required. An employee of the ThumbSignIn will arrange the necessary measures in individual cases.'

'Each data subject shall have the right granted by the European legislator to obtain from the controller restriction of processing where one of the following applies:'

'Each data subject shall have the right granted by the European legislator, to receive the personal data concerning him or her, which was provided to a controller, in a structured, commonly used and machine-readable format. He or she shall have the right to transmit those data to another controller without hindrance from the controller to which the personal data have been provided, as long as the processing is based on consent pursuant to point (a) of Article 6(1) of the GDPR or point (a) of Article 9(2) of the GDPR, or on a contract pursuant to point (b) of Article 6(1) of the GDPR, and the processing is carried out by automated means, as long as the processing is not necessary for the performance of a task carried out in the public interest or in the exercise of official authority vested in the controller.'

'Furthermore, in exercising his or her right to data portability pursuant to Article 20(1) of the GDPR, the data subject shall have the right to have personal data transmitted directly from one controller to another, where technically feasible and when doing so does not adversely affect the rights and freedoms of

others.'

'On this website, the controller has integrated the component of Google Analytics (with the anonymizer function). Google Analytics is a web analytics service. Web analytics is the collection, gathering, and analysis of data about the behavior of visitors to websites. A web analysis service collects, inter alia, data about the website from which a person has come (the so-called referrer), which sub-pages were visited, or how often and for what duration a sub-page was viewed. Web analytics are mainly used for the optimization of a website and in order to carry out a cost-benefit analysis of Internet advertising.'

'For the web analytics through Google Analytics the controller uses the application "\_gat.\_anonymizeIp". By means of this application, the IP address of the Internet connection of the data subject is abridged by Google and anonymized when accessing our websites from a Member State of the European Union or another Contracting State to the Agreement on the European Economic Area.'

'The cookie is used to store personal information, such as the access time, the location from which the access was made, and the frequency of visits to our website by the data subject. With each visit to our Internet site, such personal data, including the IP address of the Internet access used by the data subject, will be transmitted to Google in the United States of America. These personal data are stored by Google in the United States of America. Google may pass these personal data collected through the technical procedure to third parties.'

'The data subject may, as stated above, prevent the setting of cookies through our website at any time by means of a corresponding adjustment of the web browser used and thus permanently deny the setting of cookies. Such an adjustment to the Internet browser used would also prevent Google Analytics from setting a cookie on the information technology system of the data subject. In addition, cookies already in use by Google Analytics may be deleted at any time via a web browser or other software programs.'

'and install it. This browser add-on tells Google Analytics through a JavaScript, that any data and information about the visits of Internet pages may not be transmitted to Google Analytics. The installation of the browser add-ons is considered an objection by Google. If the information technology system of the data subject is later deleted, formatted, or newly installed, then the data subject must reinstall the browser add-ons to disable Google Analytics. If the browser add-on was uninstalled by the data subject or any other person who is attributable to their sphere of competence or is disabled, it is possible to execute the reinstallation or reactivation of the browser add-ons.'

'If the data subject is logged in at the same time on LinkedIn, LinkedIn detects with every call-up to our website by the data subject\u2014and for the entire duration of their stay on our Internet site\u2014which specific sub-page of our Internet page was visited by the data subject. This information is collected through the LinkedIn component and associated with the respective LinkedIn account of the data subject. If the data subject clicks on one of the LinkedIn buttons integrated on our website, then LinkedIn assigns this information to the personal LinkedIn user account of the data subject and stores the personal data.'

'LinkedIn receives information via the LinkedIn component that the data subject has visited our website, provided that the data subject is logged in at LinkedIn at the time of the call-up to our website. This occurs regardless of whether the person clicks on the LinkedIn button or not. If such a transmission of information to LinkedIn is not desirable for the data subject, then he or she may prevent this by logging off from their LinkedIn account before a call-up to our website is made.'

'the possibility to unsubscribe from e-mail messages, SMS messages and targeted ads, as well as the ability to manage ad settings. LinkedIn also uses affiliates such as Eire, Google Analytics, BlueKai, DoubleClick, Nielsen, Comscore, Eloqua, and Lotame. The setting of such cookies may be denied under '

'On this website, the controller has integrated components of Twitter. Twitter is a multilingual, publicly-accessible microblogging service on which users may publish and spread so-called tweets, e.g. short messages, which are limited to 280 characters. These short messages are available for everyone, including those who are not logged on to Twitter. The tweets are also displayed to so-called followers of the respective user. Followers are other Twitter users who follow a user's tweets. Furthermore, Twitter allows you to address a wide audience via hashtags, links or retweets.'

'If the data subject is logged in at the same time on Twitter, Twitter detects with every call-up to our website by the data subject and for the entire duration of their stay on our Internet site which specific sub-page of our Internet page was visited by the data subject. This information is collected through the Twitter component and associated with the respective Twitter account of the data subject. If the data subject clicks on one of the Twitter buttons integrated on our website, then Twitter assigns this information to the personal Twitter user account of the data subject and stores the personal data.'

'Twitter receives information via the Twitter component that the data subject has visited our website, provided that the data subject is logged in on Twitter at the time of the call-up to our website. This occurs regardless of whether the person clicks on the Twitter component or not. If such a transmission of information to Twitter is not desirable for the data subject, then he or she may prevent this by logging off from their Twitter account before a call-up to our website is made.'

'YouTube and Google will receive information through the YouTube component that the data subject has visited our website if the data subject at the time of the call to our website is logged in on YouTube; this occurs regardless of whether the person clicks on a YouTube video or not. If such a transmission of this information to YouTube and Google is not desirable for the data subject, the delivery may be prevented if the data subject logs off from their own YouTube account before a call-up to our website is made.'

'Art. 6(1) lit. a GDPR serves as the legal basis for processing operations for which we obtain consent for a specific processing purpose. If the processing of personal data is necessary for the performance of a contract to which the data subject is party, as is the case, for example, when processing operations are necessary for the supply of goods or to provide any other service, the processing is based on Article 6(1) lit. b GDPR. The same applies to such processing operations which are necessary for carrying out pre-contractual measures, for example in the case of inquiries concerning our products or services. Is our company subject to a legal obligation by which processing of personal data is required, such as for the fulfillment of tax obligations, the processing is based on Art. 6(1) lit. c GDPR. In rare cases, the processing of personal data may be necessary to protect the vital interests of the data subject or of another natural person. This would be the case, for example, if a visitor were injured in our company and his name, age, health insurance data or other vital information would have to be passed on to a doctor, hospital or other third party. Then the processing would be based on Art. 6(1) lit. d GDPR. Finally, processing operations could be based on Article 6(1) lit. f GDPR. This legal basis is used for processing operations which are not covered by any of the abovementioned legal grounds, if processing is necessary for the purposes of the legitimate interests pursued by our company or by a third party, except where such interests are overridden by the interests or fundamental rights and freedoms of the data subject which require protection of personal data. Such processing operations are particularly permissible because they have been specifically mentioned by the European legislator. It is considered that a legitimate interest could be assumed if the data subject is a client of the controller (Recital 47 Sentence 2 GDPR).'

'Where the processing of personal data is based on Article 6(1) lit. f GDPR our legitimate interest is to carry out our business in favor of the well-being of all our employees and the shareholders.'

'We clarify that the provision of personal data is partly required by law (e.g. tax regulations)

or can also result from contractual provisions (e.g. information on the contractual partner). Sometimes it may be necessary to conclude a contract that the data subject provides us with personal data, which must subsequently be processed by us. The data subject is, for example, obliged to provide us with personal data when our company signs a contract with him or her. The non-provision of the personal data would have the consequence that the contract with the data subject could not be concluded. Before personal data is provided by the data subject, the data subject must contact any employee. The employee clarifies to the data subject whether the provision of the personal data is required by law or contract or is necessary for the conclusion of the contract, whether there is an obligation to provide the personal data and the consequences of non-provision of the personal data.'

'Thumbsignin reserves the right to modify or update our Privacy Policy at any time without notice, so we encourage you to review this policy from time to time.'

```
query: '{\n      user {\n        isLogedin\n      } \n    }'
```

```
{ query: data, __source: {
```

```
// this implementation is not 100% perfect for weird media query combinations
```

```
// Adapted from convert-source-map (MIT)
```

```
* // Remove it from the DOM
```

```
// bind timers to global for call from export context
```

```
// Thrash, waste and sodomy: IE GC bug
```

```
// IE 8- don't enum bug keys
```

```
err = new Error('You provided a `` + propFullNameSafe + ``' + location + ' to the ' + componentNameSafe +  
' that was ' + (not within the range from `` + min + ' - ' + max + ``'. `` + propFullNameSafe + ``: ' + value + '));
```

```
// Don't enum bug & hidden keys
```

```
// getting tag from 19.1.3.6 Object.prototype.toString()
```

```
return fetch('/api/user').then(function (response) {
```

```
return fetch('/api/user', { method: "POST", body: userInfo }).then(function (response) {
```

```
// import { Provider } from '../Modal'
```

```
query: __WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.isRequired
```

```
exports.push([module.i, "/*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css */\n\n/*
```

```
Document\n
```

```
*/\n\n**\n * 1. Correct the line height in all browsers.\n * 2. Prevent adjustments of font size after orientation  
changes in\n * IE on Windows Phone and in iOS.\n */\nhtml {\n  line-height: 1.15; /* 1 */\n  -ms-text-size-adjust: 100%; /* 2 */\n  -webkit-text-size-adjust: 100%; /* 2 */\n}\n\n/* Sections\n
```

```
*/\n\n**\n * Remove the margin in all browsers (opinionated).\n */\nbody {\n  margin: 0;\n}\n\n**\n * Add the correct display in IE 9-.\n */\narticle, aside, footer, header, nav, section {\n  display:  
block;\n}\n\n**\n * Correct the font size and margin on `h1` elements within `section` and\n * `article`  
contexts in Chrome, Firefox, and Safari.\n */\nh1 {\n  font-size: 2em;\n  margin: 0.67em 0;\n}\n\n/* Grouping  
content\n
```

```
*/\n\n**\n * Add the correct display in IE 9-.\n * 1. Add the correct display in IE.\n
```

```
*/\nfigcaption, figure, main { /* 1 */\n  display: block;\n}\n\n**\n * Add the correct margin in IE 8.\n
```

```
*/\nfigure {\n  margin: 1em 40px;\n}\n\n**\n * 1. Add the correct box sizing in Firefox.\n * 2. Show the
```



overflow in Edge and IE.\n \*^\\n\\nhr {\\n -webkit-box-sizing: content-box;\\n box-sizing: content-box; /\* 1  
\*^\\n height: 0; /\* 1 \*^\\n overflow: visible; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* 1. Correct the inheritance and scaling of font  
size in all browsers.\\n \* 2. Correct the odd `em` font sizing in all browsers.\\n \*^\\n\\npre {\\n font-family:  
monospace, monospace; /\* 1 \*^\\n font-size: 1em; /\* 2 \*^\\n}\\n\\n/\* Text-level semantics\\n

=====

\*^\\n\\n/\*\*\\n \* 1. Remove the gray background on active links in IE 10.\\n \* 2. Remove gaps in links underline in  
iOS 8+ and Safari 8+.\\n \*^\\n\\na {\\n background-color: transparent; /\* 1 \*^\\n -webkit-text-decoration-skip:  
objects; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\\n \* 2. Add the  
correct text decoration in Chrome, Edge, IE, Opera, and Safari.\\n \*^\\n\\nabbr[title] {\\n border-bottom: none; /\*  
1 \*^\\n text-decoration: underline; /\* 2 \*^\\n -webkit-text-decoration: underline dotted;\\n text-decoration:  
underline dotted; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Prevent the duplicate application of `bolder` by the next rule in Safari  
6.\\n \*^\\n\\nb,\\nstrong {\\n font-weight: inherit;\\n}\\n\\n/\*\*\\n \* Add the correct font weight in Chrome, Edge, and  
Safari.\\n \*^\\n\\nb,\\nstrong {\\n font-weight: bolder;\\n}\\n\\n/\*\*\\n \* 1. Correct the inheritance and scaling of font  
size in all browsers.\\n \* 2. Correct the odd `em` font sizing in all browsers.\\n \*^\\n\\ncode,\\nkbd,\\nsamp {\\n  
font-family: monospace, monospace; /\* 1 \*^\\n font-size: 1em; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Add the correct font style in  
Android 4.3-.\\n \*^\\n\\ndfn {\\n font-style: italic;\\n}\\n\\n/\*\*\\n \* Add the correct background and color in IE 9-.\\n  
\*^\\n\\nmark {\\n background-color: #ff0;\\n color: #000;\\n}\\n\\n/\*\*\\n \* Add the correct font size in all  
browsers.\\n \*^\\n\\nsmall {\\n font-size: 80%;\\n}\\n\\n/\*\*\\n \* Prevent `sub` and `sup` elements from affecting the  
line height in\\n \* all browsers.\\n \*^\\n\\nsub,\\nsup {\\n font-size: 75%;\\n line-height: 0;\\n position: relative;\\n  
vertical-align: baseline;\\n}\\n\\nsub {\\n bottom: -0.25em;\\n}\\n\\nsup {\\n top: -0.5em;\\n}\\n\\n/\* Embedded  
content\\n

=====

\*^\\n\\n/\*\*\\n \* Add the correct display in IE 9-.\\n \*^\\n\\naudio,\\nvideo {\\n display: inline-block;\\n}\\n\\n/\*\*\\n \*  
Add the correct display in iOS 4-7.\\n \*^\\n\\naudio:not([controls]) {\\n display: none;\\n height: 0;\\n}\\n\\n/\*\*\\n \*  
Remove the border on images inside links in IE 10-.\\n \*^\\n\\nimg {\\n border-style: none;\\n}\\n\\n/\*\*\\n \* Hide the  
overflow in IE.\\n \*^\\n\\nsvg:not(:root) {\\n overflow: hidden;\\n}\\n\\n/\* Forms\\n

=====

\*^\\n\\n/\*\*\\n \* 1. Change the font styles in all browsers (opinionated).\\n \* 2. Remove the margin in Firefox and  
Safari.\\n \*^\\n\\nbutton,\\ninput,\\noptgroup,\\nselect,\\ntextarea {\\n font-family: sans-serif; /\* 1 \*^\\n font-size:  
100%; /\* 1 \*^\\n line-height: 1.15; /\* 1 \*^\\n margin: 0; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Show the overflow in IE.\\n \* 1.  
Show the overflow in Edge.\\n \*^\\n\\nbutton,\\ninput { /\* 1 \*^\\n overflow: visible;\\n}\\n\\n/\*\*\\n \* Remove the  
inheritance of text transform in Edge, Firefox, and IE.\\n \* 1. Remove the inheritance of text transform in  
Firefox.\\n \*^\\n\\nbutton,\\nselect { /\* 1 \*^\\n text-transform: none;\\n}\\n\\n/\*\*\\n \* 1. Prevent a WebKit bug where  
(2) destroys native `audio` and `video`\\n \* controls in Android 4.\\n \* 2. Correct the inability to style clickable  
types in iOS and Safari.\\n \*^\\n\\nbutton,\\nhtml [type="button"], /\* 1 \*^\\n [type="reset"],\\n [type="submit"]  
{\\n -webkit-appearance: button; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Remove the inner border and padding in Firefox.\\n  
\*^\\n\\nbutton::-moz-focus-inner,\\n [type="button"]::-moz-focus-inner,\\n [type="reset"]::-moz-focus-inner,\\n [ty  
pe="submit"]::-moz-focus-inner {\\n border-style: none;\\n padding: 0;\\n}\\n\\n/\*\*\\n \* Restore the focus styles  
unset by the previous rule.\\n  
\*^\\n\\nbutton:-moz-focusing,\\n [type="button"]:-moz-focusing,\\n [type="reset"]:-moz-focusing,\\n [type="su  
bmit"]:-moz-focusing {\\n outline: 1px dotted ButtonText;\\n}\\n\\n/\*\*\\n \* Correct the padding in Firefox.\\n  
\*^\\n\\nfieldset {\\n padding: 0.35em 0.75em 0.625em;\\n}\\n\\n/\*\*\\n \* 1. Correct the text wrapping in Edge and  
IE.\\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\\n \* 3. Remove the padding so developers



;CACIB;;AAED;gFACgF;;AAEHF;;;GAGG;;AAEH;;;EAKE,wBAAwB,CAAC,OAAO;EACbC,gBAAgB,CAAC,OAAO;EACxB,kBAAkB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;;GAGG;;AAEH;QACQ,OAAO;EACb,kBAAkB;CACnB;;AAED;;;GAGG;;AAEH;SACS,OAAO;EACd,qBAAqB;CACtB;;AAED;;;GAIG;;AAEH;;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;;EAIE,mBAAmB;EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;;EAIE,+BAA+B;CACbC;;AAED;;GAEG;;AAEH;EACE,+BAA+B;CACbC;;AAED;;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,eAAe,CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAAgB,CAAC,OAAO;EACxB,WAAW,CAAC,OAAO;EACnB,oBAAoB,CAAC,OAAO;CAC7B;;AAED;;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,yBAAyB,CAAC,OAAO;CACiC;;AAED;;GAEG;;AAEH;EACE,eAAe;CACbB;;AAED;;;GAGG;;AAEH;EAEE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AAEH;EAEE,aAAa;CACd;;AAED;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAAqB,CAAC,OAAO;CAC9B;;AAED;;GAEG;;AAEH;EAEE,yBAAyB;CAC1B;;AAED;;;GAGG;;AAEH;EACE,2BAA2B,CAAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED;gFACgF;;AAEHF;;;GAGG;;AAEH;EAEE,eAAe;CACbB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;gFACgF;;AAEHF;;GAEG;;AAEH;EACE,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED;gFACgF;;AAEHF;;GAEG;;AAEH;EACE,cAAc;CACf","file":"normalize.css","sourcesContent":["/\*! normalize.css v7.0.0 | MIT License |  
github.com/necolas/normalize.css \*/\n\n/\* Document\n\n=====\n\n\*/\n\n/\* 1. Correct the line height in all browsers.\n \* 2. Prevent adjustments of font size after orientation changes in IE on Windows Phone and in iOS.\n \*/\n\nhtml {\n line-height: 1.15; /\* 1 \*/\n -ms-text-size-adjust: 100%; /\* 2 \*/\n -webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n\n=====\n\n\*/\n\n/\* Remove the margin in all browsers (opinionated).\n \*/\n\nbody {\n margin: 0;\n}\n\n/\* Add the correct display in IE 9-.\n \*/\n\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display: block;\n}\n\n/\* Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.\n \*/\n\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping content\n\n=====\n\n\*/\n\n/\* Add the correct display in IE 9-.\n \*/\n\n1. Add the correct display in IE.\n\nfigurecaption,\nfigure,\nmain { /\* 1 \*/\n display: block;\n}\n\n/\* Add the correct margin in IE 8.\n \*/\n\nfigure {\n margin: 1em 40px;\n}\n\n/\* 1. Add the correct box sizing in Firefox.\n \* 2. Show the overflow in Edge and IE.\n \*/\n\nhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /\* 1 \*/\n height: 0; /\* 1 \*/\n overflow: visible; /\* 2 \*/\n}\n\n/\* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\npre {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\* Text-level semantics\n\n=====\n\n\*/\n\n/\* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in iOS 8+ and Safari 8+.\n \*/\n\na {\n background-color: transparent; /\* 1 \*/\n -webkit-text-decoration-skip: objects; /\* 2 \*/\n}\n\n/\* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*/\n\nabbr[title] {\n border-bottom: none; /\* 1 \*/\n text-decoration: underline; /\* 2 \*/\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*/\n}\n\n/\* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n \*/\n\nb,\nstrong {\n font-weight: inherit;\n}\n\n/\* Add the correct font weight in Chrome, Edge, and

Safari.\n \*^\\nb,\\nstrong {\\n font-weight: bolder;\\n}\\n\\n/\*\*\\n \* 1. Correct the inheritance and scaling of font size in all browsers.\\n \* 2. Correct the odd `em` font sizing in all browsers.\\n \*^\\n\\ncode,\\nkbd,\\nsamp {\\n font-family: monospace, monospace; /\* 1 \*^\\n font-size: 1em; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Add the correct font style in Android 4.3-.\\n \*^\\n\\nfn {\\n font-style: italic;\\n}\\n\\n/\*\*\\n \* Add the correct background and color in IE 9-.\\n \*^\\n\\nmark {\\n background-color: #ff0;\\n color: #000;\\n}\\n\\n/\*\*\\n \* Add the correct font size in all browsers.\\n \*^\\n\\nsmall {\\n font-size: 80%;\\n}\\n\\n/\*\*\\n \* Prevent `sub` and `sup` elements from affecting the line height in\\n \* all browsers.\\n \*^\\n\\nsub,\\nsup {\\n font-size: 75%;\\n line-height: 0;\\n position: relative;\\n vertical-align: baseline;\\n}\\n\\nsub {\\n bottom: -0.25em;\\n}\\n\\nsup {\\n top: -0.5em;\\n}\\n\\n/\* Embedded content\\n

=====  
\*^\\n\\n/\*\*\\n \* Add the correct display in IE 9-.\\n \*^\\n\\naudio,\\nvideo {\\n display: inline-block;\\n}\\n\\n/\*\*\\n \* Add the correct display in iOS 4-7.\\n \*^\\n\\naudio:not([controls]) {\\n display: none;\\n height: 0;\\n}\\n\\n/\*\*\\n \* Remove the border on images inside links in IE 10-.\\n \*^\\n\\nimg {\\n border-style: none;\\n}\\n\\n/\*\*\\n \* Hide the overflow in IE.\\n \*^\\n\\nsvg:not(:root) {\\n overflow: hidden;\\n}\\n\\n/\* Forms\\n

=====  
\*^\\n\\n/\*\*\\n \* 1. Change the font styles in all browsers (opinionated).\\n \* 2. Remove the margin in Firefox and Safari.\\n \*^\\n\\nbutton,\\ninput,\\noptgroup,\\nselect,\\ntextarea {\\n font-family: sans-serif; /\* 1 \*^\\n font-size: 100%; /\* 1 \*^\\n line-height: 1.15; /\* 1 \*^\\n margin: 0; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Show the overflow in IE.\\n \* 1. Show the overflow in Edge.\\n \*^\\n\\nbutton,\\ninput { /\* 1 \*^\\n overflow: visible;\\n}\\n\\n/\*\*\\n \* Remove the inheritance of text transform in Edge, Firefox, and IE.\\n \* 1. Remove the inheritance of text transform in Firefox.\\n \*^\\n\\nbutton,\\nselect { /\* 1 \*^\\n text-transform: none;\\n}\\n\\n/\*\*\\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video`\\n \* controls in Android 4.\\n \* 2. Correct the inability to style clickable types in iOS and Safari.\\n \*^\\n\\nbutton,\\nhtml [type=\\\"button\\\"], /\* 1 \*^\\n[type=\\\"reset\\\"],\\n[type=\\\"submit\\\"] {\\n -webkit-appearance: button; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Remove the inner border and padding in Firefox.\\n \*^\\n\\nbutton::-moz-focus-inner,\\n[type=\\\"button\\\"]::-moz-focus-inner,\\n[type=\\\"reset\\\"]::-moz-focus-inner,\\n[type=\\\"submit\\\"]::-moz-focus-inner {\\n border-style: none;\\n padding: 0;\\n}\\n\\n/\*\*\\n \* Restore the focus styles unset by the previous rule.\\n \*^\\n\\nbutton:-moz-focusing,\\n[type=\\\"button\\\"]:-moz-focusing,\\n[type=\\\"reset\\\"]:-moz-focusing,\\n[type=\\\"submit\\\"]:-moz-focusing {\\n outline: 1px dotted ButtonText;\\n}\\n\\n/\*\*\\n \* Correct the padding in Firefox.\\n \*^\\n\\nfieldset {\\n padding: 0.35em 0.75em 0.625em;\\n}\\n\\n/\*\*\\n \* 1. Correct the text wrapping in Edge and IE.\\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\\n \* 3. Remove the padding so developers are not caught out when they zero out\\n \* `fieldset` elements in all browsers.\\n \*^\\n\\nlegend {\\n -webkit-box-sizing: border-box;\\n box-sizing: border-box; /\* 1 \*^\\n color: inherit; /\* 2 \*^\\n display: table; /\* 1 \*^\\n max-width: 100%; /\* 1 \*^\\n padding: 0; /\* 3 \*^\\n white-space: normal; /\* 1 \*^\\n}\\n\\n/\*\*\\n \* 1. Add the correct display in IE 9-.\\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\\n \*^\\n\\nprogress {\\n display: inline-block; /\* 1 \*^\\n vertical-align: baseline; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Remove the default vertical scrollbar in IE.\\n \*^\\n\\ntextarea {\\n overflow: auto;\\n}\\n\\n/\*\*\\n \* 1. Add the correct box sizing in IE 10-.\\n \* 2. Remove the padding in IE 10-.\\n \*^\\n\\n[type=\\\"checkbox\\\"],\\n[type=\\\"radio\\\"] {\\n -webkit-box-sizing: border-box;\\n box-sizing: border-box; /\* 1 \*^\\n padding: 0; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Correct the cursor style of increment and decrement buttons in Chrome.\\n \*^\\n\\n[type=\\\"number\\\"]::-webkit-inner-spin-button,\\n[type=\\\"number\\\"]::-webkit-outer-spin-button {\\n height: auto;\\n}\\n\\n/\*\*\\n \* 1. Correct the odd appearance in Chrome and Safari.\\n \* 2. Correct the outline style in Safari.\\n \*^\\n\\n[type=\\\"search\\\"] {\\n -webkit-appearance: textfield; /\* 1 \*^\\n outline-offset: -2px; /\* 2

```

/*\n}\n\n/**\n * Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n *\n *\n\n[ type="search" ]::-webkit-search-cancel-button,\n[ type="search" ]::-webkit-search-decoration {\n  -webkit-appearance: none;\n}\n\n/**\n * 1. Correct the inability to style clickable types in iOS and Safari.\n * 2. Change font properties to `inherit` in Safari.\n *\n\n::-webkit-file-upload-button {\n  -webkit-appearance: button;\n  /* 1 */\n  font: inherit;\n  /* 2 */\n}\n\n/* Interactive\n
```

```

*^n^n/*^n * Add the correct display in IE 9-.\n * 1. Add the correct display in Edge, IE, and Firefox.\n
*^n^ndetails, /* 1 *^nmenu {\n  display: block;\n}\n^n/*^n * Add the correct display in all browsers.\n
*^n^nsummary {\n  display: list-item;\n}\n^n/* Scripting\n

```

\*\n/n/\*\*\n \* Add the correct display in IE 9-.\n \*\n canvas {\n display: inline-block;\n }\n/n/\*\*\n \* Add the  
correct display in IE.\n \*\n template {\n display: none;\n }\n/n/\* Hidden\n

\*\n\n\*\*\n \* Add the correct display in IE 10-.\n \*\n\n[hidden] {\n display: none;\n}\n\n"},"sourceRoot":""});

```
isLoggedin: !userInfo.isLoading ? userInfo.data.isLoggedin : ownProps.query.user.isLoggedin,
```

- \* A `Query Indeterminate` linear progress bar is used when you are combining
- \* as a query indeterminate progress bar by adding the prop `query={true}` to the
- \* component. Until a progress value is given, it will display the query linear
- \* progress animation. Afterwards, it will start the determinate animation of where

'md-progress--linear-query': query,

\* Boolean if this should be a query indeterminate progress bar.

query: false

20-<https://stage.thumbsignin.com/assets/partners.chunk.js>

```

    _this.from = __WEBPACK_IMPORTED_MODULE_0_react___default.a.createRef();
    var results = { firstName: null, lastName: null, from: null, contactNo: null, message: null };
    var isError = { firstName: false, lastName: false, message: false, from: false, contactNo: false };
    if (!this.from.current.field.state.error) {
        var value3 = this.from.current.field.value.trim();
        isError.from = !new

```

```
RegExp(/^(^<>()\[\]\.,:;s@""]+(\.^[^<>()\[\]\.,:;s@""]+)*)(".+")@((\[[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\])|((\[[a-zA-Z]{0-9}+\.[a-zA-Z]{2,}\])$)).test(value3);
```

```
!isError.from && value3.length > 0 ? results.from = value3 : isError.from = true;
```

```
name: "from",
```

```
ref: this.from,
```

```
error: this.state.errorFlag.from,
```

```
// from https://github.com/d3/d3-ease/blob/master/src/linear.js
```

```
// Apapted from https://github.com/d3/d3-transition/blob/master/src/transition/schedule.js
```

```
// removes this transition from the pending list!
```

```
var user = this.props.user;
```

'According to Gartner, the worldwide security market will hit \$93 billion in 2018, and that\u2019s an emerging opportunity for the security services industry. Thumbsignin\u2019s authentication solutions are built to be user-friendly, technically robust, versatile, standards-compliant, and future-proof. Partner with us.'

```
query: '{\n      user {\n        isLogedin\n      } \n    }'
```

```
{ query: data, __source: {
```

```
__WEBPACK_IMPORTED_MODULE_0_react__default.a.createElement(__WEBPACK_IMPORTED_MODULE_2__Partners__[\"a\" /* default */], { query: data, __source: {
```

```
// this implementation is not 100% perfect for weird media query combinations
```

```
// Adapted from convert-source-map (MIT)
```

```
* // Remove it from the DOM
```

```
// bind timers to global for call from export context
```

```
// Thrash, waste and sodomy: IE GC bug
```

```
// IE 8- don't enum bug keys
```

```
* @param {string=} field - the field to extract a value from. Defaults to 'value'.
```

```
err = new Error('You provided a `'+ propFullNameSafe + '` to the '+ componentNameSafe + ' that was ' + ('not within the range from \'' + min + ' - ' + max + '\'. `'+ propFullNameSafe + `: ' + value + `'));
```

```
// Don't enum bug & hidden keys
```

```
// getting tag from 19.1.3.6 Object.prototype.toString()
```

```
return fetch('/api/user').then(function (response) {
```

```
return fetch('/api/user', { method: "POST", body: userInfo }).then(function (response) {
```

```
* where the component should be switched to something else for valid html.
```

```
// import { Provider } from '../Modal'
```

```
query: __WEBPACK_IMPORTED_MODULE_1_prop_types__default.a.object.isRequired
```

```
exports.push([module.i, "/*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css *\n\nDocument\n
```

```
*/\n\n**\n\n * 1. Correct the line height in all browsers.\n * 2. Prevent adjustments of font size after orientation changes in\n * IE on Windows Phone and in iOS.\n */\nhtml {\n  line-height: 1.15; /* 1 *\n  -ms-text-size-adjust: 100%; /* 2 *\n  -webkit-text-size-adjust: 100%; /* 2 *\n}\n\n/* Sections\n
```

```
*/\n\n**\n\n * Remove the margin in all browsers (opinionated).\n */\nbody {\n  margin: 0;\n}\n\n**\n\n * Add
```

the correct display in IE 9-.  
block;  
Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.  
h1 {  
font-size: 2em;  
margin: 0.67em 0;  
}  
Grouping content

=====

1. Add the correct display in IE.  
figcaption, figure, main {  
display: block;  
}  
figure {  
margin: 1em 40px;  
}  
1. Add the correct box sizing in Firefox.  
2. Show the overflow in Edge and IE.  
hr {  
-webkit-box-sizing: content-box;  
box-sizing: content-box;  
height: 0;  
overflow: visible;  
}  
1. Correct the inheritance and scaling of font size in all browsers.  
2. Correct the odd `em` font sizing in all browsers.  
pre {  
font-family: monospace, monospace;  
font-size: 1em;  
}  
Text-level semantics

=====

1. Remove the gray background on active links in IE 10.  
2. Remove gaps in links underline in iOS 8+ and Safari 8+.  
a {  
background-color: transparent;  
-webkit-text-decoration-skip: objects;  
}  
1. Remove the bottom border in Chrome 57- and Firefox 39-.  
2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.  
abbr[title] {  
border-bottom: none;  
text-decoration: underline;  
-webkit-text-decoration: underline dotted;  
text-decoration: underline dotted;  
}  
Prevent the duplicate application of `bolder` by the next rule in Safari 6.  
b, strong {  
font-weight: inherit;  
}  
Add the correct font weight in Chrome, Edge, and Safari.  
b, strong {  
font-weight: bolder;  
}  
1. Correct the inheritance and scaling of font size in all browsers.  
2. Correct the odd `em` font sizing in all browsers.  
code, kbd, samp {  
font-family: monospace, monospace;  
font-size: 1em;  
}  
Add the correct font style in Android 4.3-.  
dfn {  
font-style: italic;  
}  
Add the correct background and color in IE 9-.  
mark {  
background-color: #ff0;  
color: #000;  
}  
Add the correct font size in all browsers.  
small {  
font-size: 80%;  
}  
Prevent `sub` and `sup` elements from affecting the line height in all browsers.  
sub, sup {  
font-size: 75%;  
line-height: 0;  
position: relative;  
vertical-align: baseline;  
}  
sub {  
bottom: -0.25em;  
}  
sup {  
top: -0.5em;  
}  
Embedded content

=====

Add the correct display in IE 9-.  
audio, video {  
display: inline-block;  
}  
Add the correct display in iOS 4-7.  
audio:not([controls]) {  
display: none;  
height: 0;  
}  
Remove the border on images inside links in IE 10-.  
img {  
border-style: none;  
}  
Hide the overflow in IE.  
svg:not(:root) {  
overflow: hidden;  
}  
Forms

=====

1. Change the font styles in all browsers (opinionated).  
2. Remove the margin in Firefox and Safari.  
button, input, optgroup, select, textarea {  
font-family: sans-serif;  
font-size: 100%;  
line-height: 1.15;  
margin: 0;  
}  
Show the overflow in IE.  
1. Show the overflow in Edge.  
button, input {  
overflow: visible;  
}  
Remove the inheritance of text transform in Edge, Firefox, and IE.  
1. Remove the inheritance of text transform in Firefox.  
button, select {  
text-transform: none;  
}  
1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.  
2. Correct the inability to style clickable types in iOS and Safari.  
button, html [type="button"], [type="reset"], [type="submit"]

{\n -webkit-appearance: button; /\* 2 \*/\n}\n\n/\*\n \* Remove the inner border and padding in Firefox.\n \*/\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n/\*\n \* Restore the focus styles\n unset by the previous rule.\n \*/\n\nbutton:-moz-focusing,\n[type="button"]:-moz-focusing,\n[type="reset"]:-moz-focusing,\n[type="submit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n\n/\*\n \* Correct the padding in Firefox.\n \*/\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n/\*\n \* 1. Correct the text wrapping in Edge and\n IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers\n are not caught out when they zero out\n `fieldset` elements in all browsers.\n \*/\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n color: inherit; /\* 2 \*/\n display: table;\n /\* 1 \*/\n max-width: 100%; /\* 1 \*/\n padding: 0; /\* 3 \*/\n white-space: normal; /\* 1 \*/\n}\n\n/\*\n \* 1. Add\n the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*/\n\nprogress {\n display: inline-block; /\* 1 \*/\n vertical-align: baseline; /\* 2 \*/\n}\n\n/\*\n \* Remove the\n default vertical scrollbar in IE.\n \*/\n\ntextarea {\n overflow: auto;\n}\n\n/\*\n \* 1. Add the correct box sizing\n in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*/\n\n[type="checkbox"],\n[type="radio"] {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n padding: 0; /\* 2 \*/\n}\n\n/\*\n \* Correct the cursor style of increment and decrement buttons in Chrome.\n \*/\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n height: auto;\n}\n\n/\*\n \* 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in\n Safari.\n \*/\n\n[type="search"] {\n -webkit-appearance: textfield; /\* 1 \*/\n outline-offset: -2px; /\* 2 \*/\n}\n\n/\*\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n \*/\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n -webkit-appearance: none;\n}\n\n/\*\n \* 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2.\n Change font properties to `inherit` in Safari.\n \*/\n\n::-webkit-file-upload-button {\n -webkit-appearance: button; /\* 1 \*/\n font: inherit; /\* 2 \*/\n}\n\n/\* Interactive\n

=====  
\*\n\n/\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in Edge, IE, and Firefox.\n \*/\n\n\ndetails, /\* 1 \*/\n\nmenu {\n display: block;\n}\n\n/\*\n \* Add the correct display in all browsers.\n \*/\n\n\nsummary {\n display: list-item;\n}\n\n/\* Scripting\n

=====  
\*\n\n/\*\n \* Add the correct display in IE 9-.\n \*/\n\n\ncanvas {\n display: inline-block;\n}\n\n/\*\n \* Add the\n correct display in IE.\n \*/\n\n\ntemplate {\n display: none;\n}\n\n/\* Hidden\n

=====  
\*\n\n/\*\n \* Add the correct display in IE 10-.\n \*/\n\n\n[hidden] {\n display: none;\n}\n\n", "",\n{\n "version": 3,\n "sources": ["/home/ubuntu/ReactThumbSignIn/node\_modules/normalize.css/normalize.css"],\n "names": [],\n "mappings": "AAAA,4EAA4E;;AAE5E;gFACgF;;AAEHf;;;GAIG;;AAEH;EACE,kBAaKB,CAAC,OA\nAO;EAC1B,2BAA2B,CAAC,OAAO;EACnC,+BAA+B,CAAC,OAAO;CACxC;;AAED;gFACgF;;AAEHf;;G\nAEG;;AAEH;EACE,UAAU;CACX;;AAED;;GAEG;;AAEH;;;;;EAME,eAAe;CACHB;;AAED;;;GAGG;;AAE\nH;EACE,eAAe;EACf,iBAaIB;CACIB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;OAE0,OAAO;EACZ,eA\nAe;CACHB;;AAED;;GAEG;;AAEH;EACE,iBAaIB;CACIB;;AAED;;;GAGG;;AAEH;EACE,gCAAgC;UACx\nB,wBAAwB,CAAC,OAAO;EACxC,UAAU,CAAC,OAAO;EACIB,kBAaKB,CAAC,OAAO;CAC3B;;AAED;;\n;GAGG;;AAEH;EACE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED;gFACgF;;AA\nEHf;;;GAGG;;AAEH;EACE,8BAa8B,CAAC,OAAO;EACtC,sCAAsC,CAAC,OAAO;CAC/C;;AAED;;;GAG



G;;AAEH;EACE,oBAAoB,CAAC,OAAO;EAC5B,2BAA2B,CAAC,OAAO;EACnC,0CAA0C;UACIC,kCAA  
kC,CAAC,OAAO;CACnD;;AAED;;GAEG;;AAEH;;EAEe,qBAAqB;CACtB;;AAED;;GAEG;;AAEH;;EAEe,  
oBAAoB;CACrB;;AAED;;;GAGG;;AAEH;;;EAGE,kCAAkC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;C  
ACxB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,uBAAuB;EACvB,Y  
AAY;CACb;;AAED;;GAEG;;AAEH;EACE,eAAe;CACbB;;AAED;;;GAGG;;AAEH;;EAEe,eAAe;EACf,eAA  
e;EACf,mBAAmB;EACnB,yBAAyB;CAC1B;;AAED;EACE,gBAAgB;CACjB;;AAED;EACE,YAAY;CACb;;  
AAED;gFACgF;;AAEHf;;GAEG;;AAEH;;EAEe,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;EA  
Cd,UAAU;CACX;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,iBAAiB  
;CACIB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;;EAKE,wBAAwB,CAAC,OAAO;EACbC,gBAAgB,CA  
AC,OAAO;EACxB,kBAAkB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;;GAGG;;AAEH  
;QACQ,OAAO;EACb,kBAAkB;CACnB;;AAED;;;GAGG;;AAEH;SACS,OAAO;EACd,qBAAqB;CACtB;;A  
AED;;;GAIG;;AAEH;;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;;EAIE,mBAAmB;  
EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;;EAIE,+BAA+B;CACbC;;AAED;;GAEG;;AAEH;EACE,+  
BAA+B;CACbC;;AAED;;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,eAAe,  
CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAAgB,CAAC,OAAO;EACxB,WAAW,CAAC,OAA  
O;EACnB,oBAAoB,CAAC,OAAO;CAC7B;;AAED;;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,  
yBAAyB,CAAC,OAAO;CACIC;;AAED;;GAEG;;AAEH;EACE,eAAe;CACbB;;AAED;;;GAGG;;AAEH;;EA  
EE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AA  
EH;;EAEe,aAAa;CACd;;AAED;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAAqB,CAAC,O  
AAO;CAC9B;;AAED;;GAEG;;AAEH;;EAEe,yBAAyB;CAC1B;;AAED;;;GAGG;;AAEH;EACE,2BAA2B,C  
AAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;EAEe,eAAe;  
CACbB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;gFACgF;;AAEHf;;GAEG;;AAEH;EACE,  
sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED;gFACgF;;AAEHf;;GAEG;;AAEH;EAC  
E,cAAc;CACf","file":"normalize.css","sourcesContent":["/\*! normalize.css v7.0.0 | MIT License |  
github.com/necolas/normalize.css \*/\n\n/\* Document\n\n=====\n\n\*/\n\n/\* 1. Correct the line height in all browsers.\n \* 2. Prevent adjustments of font size after orientation  
changes in\n \* IE on Windows Phone and in iOS.\n \*/\nhtml {\n line-height: 1.15; /\* 1 \*/\n -ms-text-size-adjust: 100%; /\* 2 \*/\n -webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n\n=====\n\n\*/\n\n/\* Remove the margin in all browsers (opinionated).\n \*/\nbody {\n margin: 0;\n}\n\n/\* Add the correct display in IE 9-.\n \*/\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display: block;\n}\n\n/\* Correct the font size and margin on `h1` elements within `section` and `article`  
contexts in Chrome, Firefox, and Safari.\n \*/\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping content\n\n=====\n\n\*/\n\n/\* Add the correct display in IE 9-.\n \*/\n1. Add the correct display in IE.\n\nfigurecaption,\nfigure,\nmain {\n /\* 1 \*/\n display: block;\n}\n\n/\* Add the correct margin in IE 8.\n \*/\nfigure {\n margin: 1em 40px;\n}\n\n/\* 1. Add the correct box sizing in Firefox.\n \* 2. Show the overflow in Edge and IE.\n \*/\nhhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /\* 1 \*/\n height: 0; /\* 1 \*/\n overflow: visible; /\* 2 \*/\n}\n\n/\* 1. Correct the inheritance and scaling of font  
size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\npre {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\* Text-level semantics\n\n=====

=====  
\*/\n\n/\* 1. Correct the line height in all browsers.\n \* 2. Prevent adjustments of font size after orientation  
changes in\n \* IE on Windows Phone and in iOS.\n \*/\nhtml {\n line-height: 1.15; /\* 1 \*/\n -ms-text-size-adjust: 100%; /\* 2 \*/\n -webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n\n=====  
\*/\n\n/\* Remove the margin in all browsers (opinionated).\n \*/\nbody {\n margin: 0;\n}\n\n/\* Add the correct display in IE 9-.\n \*/\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display: block;\n}\n\n/\* Correct the font size and margin on `h1` elements within `section` and `article`  
contexts in Chrome, Firefox, and Safari.\n \*/\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping content\n\n=====  
\*/\n\n/\* Add the correct display in IE 9-.\n \*/\n1. Add the correct display in IE.\n\nfigurecaption,\nfigure,\nmain {\n /\* 1 \*/\n display: block;\n}\n\n/\* Add the correct margin in IE 8.\n \*/\nfigure {\n margin: 1em 40px;\n}\n\n/\* 1. Add the correct box sizing in Firefox.\n \* 2. Show the overflow in Edge and IE.\n \*/\nhhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /\* 1 \*/\n height: 0; /\* 1 \*/\n overflow: visible; /\* 2 \*/\n}\n\n/\* 1. Correct the inheritance and scaling of font  
size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\npre {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\* Text-level semantics\n\n=====

=====

\*\n\n/\*\*\n \* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in iOS 8+ and Safari 8+.\n \*\n\na {\n background-color: transparent; /\* 1 \*\n -webkit-text-decoration-skip: objects; /\* 2 \*\n}\n\n/\*\*\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*\n\nabbr[title] {\n border-bottom: none; /\* 1 \*\n text-decoration: underline; /\* 2 \*\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*\n}\n\n/\*\*\n \* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n \*\n\nb,\nstrong {\n font-weight: inherit;\n}\n\n/\*\*\n \* Add the correct font weight in Chrome, Edge, and Safari.\n \*\n\nb,\nstrong {\n font-weight: bolder;\n}\n\n/\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*\n\ncode,\nkbd,\nsamp {\n font-family: monospace, monospace; /\* 1 \*\n font-size: 1em; /\* 2 \*\n}\n\n/\*\*\n \* Add the correct font style in Android 4.3-.\n \*\n\ni {\n font-style: italic;\n}\n\n/\*\*\n \* Add the correct background and color in IE 9-.\n \*\n\nmark {\n background-color: #ff0;\n color: #000;\n}\n\n/\*\*\n \* Add the correct font size in all browsers.\n \*\n\nsmall {\n font-size: 80%;\n}\n\n/\*\*\n \* Prevent `sub` and `sup` elements from affecting the line height in\n \* all browsers.\n \*\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded content\n

=====

\*\n\n/\*\*\n \* Add the correct display in IE 9-.\n \*\n\naudio,\nvideo {\n display: inline-block;\n}\n\n/\*\*\n \* Add the correct display in iOS 4-7.\n \*\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n/\*\*\n \* Remove the border on images inside links in IE 10-.\n \*\n\nimg {\n border-style: none;\n}\n\n/\*\*\n \* Hide the overflow in IE.\n \*\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====

\*\n\n/\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n \*\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*\n font-size: 100%; /\* 1 \*\n line-height: 1.15; /\* 1 \*\n margin: 0; /\* 2 \*\n}\n\n/\*\*\n \* Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n \*\n\nbutton,\ninput { /\* 1 \*\n overflow: visible;\n}\n\n/\*\*\n \* Remove the inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n \*\n\nbutton,\nselect { /\* 1 \*\n text-transform: none;\n}\n\n/\*\*\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable types in iOS and Safari.\n \*\n\nbutton,\nhtml [type="button"], /\* 1 \*\n[type="reset"],\n[type="submit"] {\n -webkit-appearance: button; /\* 2 \*\n}\n\n/\*\*\n \* Remove the inner border and padding in Firefox.\n \*\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n/\*\*\n \* Restore the focus styles unset by the previous rule.\n \*\n\nbutton:-moz-focusing,\n[type="button"]:-moz-focusing,\n[type="reset"]:-moz-focusing,\n[type="submit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n\n/\*\*\n \* Correct the padding in Firefox.\n \*\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n/\*\*\n \* 1. Correct the text wrapping in Edge and IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers are not caught out when they zero out\n \* `fieldset` elements in all browsers.\n \*\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*\n color: inherit; /\* 2 \*\n display: table; /\* 1 \*\n max-width: 100%; /\* 1 \*\n padding: 0; /\* 3 \*\n white-space: normal; /\* 1 \*\n}\n\n/\*\*\n \* 1. Add the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n

```

/*\n\nprogress {\n  display: inline-block; /* 1 *\n  vertical-align: baseline; /* 2 *\n}\n\n/**\n * Remove the
default vertical scrollbar in IE.\n *\n\ntextarea {\n  overflow: auto;\n}\n\n/**\n * 1. Add the correct box sizing
in IE 10-.\n * 2. Remove the padding in IE 10-.\n *\n\n[type=\\"checkbox\\"],\n[type=\\"radio\\""] {\n
-webkit-box-sizing: border-box;\n      box-sizing: border-box; /* 1 *\n  padding: 0; /* 2 *\n}\n\n/**\n *
Correct the cursor style of increment and decrement buttons in Chrome.\n
*\n\n[type=\\"number\\""]::-webkit-inner-spin-button,\n[type=\\"number\\""]::-webkit-outer-spin-button {\n  height:
auto;\n}\n\n/**\n * 1. Correct the odd appearance in Chrome and Safari.\n * 2. Correct the outline style in
Safari.\n *\n\n[type=\\"search\\""] {\n  -webkit-appearance: textfield; /* 1 *\n  outline-offset: -2px; /* 2
*\n}\n\n/**\n * Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n
*\n\n[type=\\"search\\""]::-webkit-search-cancel-button,\n[type=\\"search\\""]::-webkit-search-decoration {\n
-webkit-appearance: none;\n}\n\n/**\n * 1. Correct the inability to style clickable types in iOS and Safari.\n * 2.
Change font properties to `inherit` in Safari.\n *\n\n::-webkit-file-upload-button {\n  -webkit-appearance:
button; /* 1 *\n  font: inherit; /* 2 *\n}\n\n/* Interactive\n

```

```

====
*\n\n/*\n * Add the correct display in IE 9-.\n * 1. Add the correct display in Edge, IE, and Firefox.\n
*\n\ndetails, /* 1 *\n\nmenu {\n  display: block;\n}\n\n/*\n * Add the correct display in all browsers.\n
*\n\nsummary {\n  display: list-item;\n}\n\n/* Scripting\n

```

```

====
*\n\n/**\n * Add the correct display in IE 9-.\n *\n\ncanvas {\n  display: inline-block;\n}\n\n/**\n * Add the
correct display in IE.\n *\n\ntemplate {\n  display: none;\n}\n\n/* Hidden\n

```

```

====
*\n\n/**\n * Add the correct display in IE 10-.\n *\n\n[hidden] {\n  display: none;\n}\n\n"},"sourceRoot":""}}]);

```

```

    user = _props.user,
    user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
      user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
        user.isLoggedin ? __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
          user: {
            isLoggedin: !userInfo.isLoading ? userInfo.data.isLoggedin : ownProps.query.user.isLoggedin,
            * `Indeterminate`, and `Query Indeterminate`.
            * A `Query Indeterminate` linear progress bar is used when you are combining
            * as a query indeterminate progress bar by adding the prop `query={true}` to the
            * component. Until a progress value is given, it will display the query linear
            * progress animation. Afterwards, it will start the determinate animation of where
            query = _props.query,
            props = _objectWithoutProperties(_props, ['className', 'progressClassName', 'progressStyle', 'value',
            'query', 'centered']);
            'md-progress--linear-query': query,
            * region until it is finished loading. It is not possible for the user to alter the value of a progressbar
            * Boolean if this should be a query indeterminate progress bar.
            query: _propTypes2.default.bool,
            query: false
            * region until it is finished loading. It is not possible for the user to alter the value of a progressbar
            * Removes observer from observers list.

```

- \* Updates every observer from observers list and notifies them of queued
  - // has the "ownerDocument" property from which we can retrieve a
  - // Return the local global object if it's not possible extract one from
- \* Extracts borders size from provided styles.
- \* Extracts paddings sizes from provided styles.
- \* from the corresponding properties of the last observed content rectangle.
- \* instances collected from active resize observations.
  - \* Gets the current value from the text field. This is used when you have an uncontrolled
  - \* text field and simply need the value from a ref callback.
- \* floating labels and remove the text divider from the component.
- \* this will only be visible when there is no value and the user focused the text field.
- \* Boolean if the text field is required. If the user blurs the text field while there is
- \* The direction that the underline should appear from.
- \* required and the user blurs the text field with no value.
- \* The ink when there is an injectInk above the text field. Used from the SelectField.

```

text = Array.from(Array(value.length)).reduce(function (s) {
  className: (0, _classnames2.default)('md-divider--text-field md-divider--expand-from-' + lineDirection, {

```

21-<https://stage.thumbsignin.com/assets/login.chunk.js>

Other Information:            var user = this.props.user;  
                               'Simpler User Experience'  
                               'Strongly resistant to phishing, MITM and replay attacks. Built in anti-databreach  
 and user secret protection capabilities.'

```

    query: '{\n      user {\n        isLogedin\n      } \n    }'
    throw new Error('Failed to fetch user data');
    { query: data, __source: {
// this implementation is not 100% perfect for weird media query combinations
// Adapted from convert-source-map (MIT)
* // Remove it from the DOM
// bind timers to global for call from export context
// Thrash, waste and sodomy: IE GC bug
// IE 8- don't enum bug keys
err = new Error('You provided a `` + propFullNameSafe + ``' + location + ' to the ' + componentNameSafe +
' that was ' + ('not within the range from \'' + min + ' - ' + max + '\'. ``' + propFullNameSafe + `:`' + value + '));
// Don't enum bug & hidden keys
// getting tag from 19.1.3.6 Object.prototype.toString()
return fetch('/api/user').then(function (response) {
return fetch('/api/user', { method: "POST", body: userInfo }).then(function (response) {
// import { Provider } from '../Modal'
query: __WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.object.isRequired
exports.push([module.i, "/*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css *\n\n/*
Document\n
=====

```

```
*/\n\n/**\n * 1. Correct the line height in all browsers.\n * 2. Prevent adjustments of font size after orientation
changes in\n * IE on Windows Phone and in iOS.\n */\n\nhtml {\n  line-height: 1.15; /* 1 */\n  -ms-text-size-adjust: 100%; /* 2 */\n  -webkit-text-size-adjust: 100%; /* 2 */\n}\n\n/* Sections\n
=====

*/\n\n/**\n * Remove the margin in all browsers (opinionated).\n */\n\nbody {\n  margin: 0;\n}\n\n/**\n * Add
the correct display in IE 9-.\n */\n\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n  display:
block;\n}\n\n/**\n * Correct the font size and margin on `h1` elements within `section` and `article`
contexts in Chrome, Firefox, and Safari.\n */\n\nh1 {\n  font-size: 2em;\n  margin: 0.67em 0;\n}\n\n/* Grouping
content\n
=====

*/\n\n/**\n * Add the correct display in IE 9-.\n * 1. Add the correct display in IE.\n
*/\n\nfigcaption,\nfigure,\nmain { /* 1 */\n  display: block;\n}\n\n/**\n * Add the correct margin in IE 8.\n
*/\n\nfigure {\n  margin: 1em 40px;\n}\n\n/**\n * 1. Add the correct box sizing in Firefox.\n * 2. Show the
overflow in Edge and IE.\n */\n\nhr {\n  -webkit-box-sizing: content-box;\n      box-sizing: content-box; /* 1
*/\n  height: 0; /* 1 */\n  overflow: visible; /* 2 */\n}\n\n/**\n * 1. Correct the inheritance and scaling of font
size in all browsers.\n * 2. Correct the odd `em` font sizing in all browsers.\n */\n\npre {\n  font-family:
monospace, monospace; /* 1 */\n  font-size: 1em; /* 2 */\n}\n\n/* Text-level semantics\n
=====

*/\n\n/**\n * 1. Remove the gray background on active links in IE 10.\n * 2. Remove gaps in links underline in
iOS 8+ and Safari 8+.\n */\n\na {\n  background-color: transparent; /* 1 */\n  -webkit-text-decoration-skip:
objects; /* 2 */\n}\n\n/**\n * 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n * 2. Add the
correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n */\n\nabbr[title] {\n  border-bottom: none; /*
1 */\n  text-decoration: underline; /* 2 */\n  -webkit-text-decoration: underline dotted;\n      text-decoration:
underline dotted; /* 2 */\n}\n\n/**\n * Prevent the duplicate application of `bolder` by the next rule in Safari
6.\n */\n\nb,\nstrong {\n  font-weight: inherit;\n}\n\n/**\n * Add the correct font weight in Chrome, Edge, and
Safari.\n */\n\nb,\nstrong {\n  font-weight: bolder;\n}\n\n/**\n * 1. Correct the inheritance and scaling of font
size in all browsers.\n * 2. Correct the odd `em` font sizing in all browsers.\n */\n\ncode,\nkbd,\nsamp {\n
font-family: monospace, monospace; /* 1 */\n  font-size: 1em; /* 2 */\n}\n\n/**\n * Add the correct font style in
Android 4.3-.\n */\n\ni,\ndfn {\n  font-style: italic;\n}\n\n/**\n * Add the correct background and color in IE 9-.\n
*/\n\nmark {\n  background-color: #ff0;\n  color: #000;\n}\n\n/**\n * Add the correct font size in all
browsers.\n */\n\nsmall {\n  font-size: 80%;\n}\n\n/**\n * Prevent `sub` and `sup` elements from affecting the
line height in\n * all browsers.\n */\n\nsub,\nsup {\n  font-size: 75%;\n  line-height: 0;\n  position: relative;\n
vertical-align: baseline;\n}\n\nsub {\n  bottom: -0.25em;\n}\n\nsup {\n  top: -0.5em;\n}\n\n/* Embedded
content\n
=====

*/\n\n/**\n * Add the correct display in IE 9-.\n */\n\naudio,\nvideo {\n  display: inline-block;\n}\n\n/**\n *
Add the correct display in iOS 4-7.\n */\n\naudio:not([controls]) {\n  display: none;\n  height: 0;\n}\n\n/**\n *
Remove the border on images inside links in IE 10-.\n */\n\nimg {\n  border-style: none;\n}\n\n/**\n * Hide the
overflow in IE.\n */\n\nsvg:not(:root) {\n  overflow: hidden;\n}\n\n/* Forms\n
=====

*/\n\n/**\n * 1. Change the font styles in all browsers (opinionated).\n * 2. Remove the margin in Firefox and
Safari.\n */\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n  font-family: sans-serif; /* 1 */\n  font-size:
100%; /* 1 */\n  line-height: 1.15; /* 1 */\n  margin: 0; /* 2 */\n}\n\n/**\n * Show the overflow in IE.\n * 1.
```

Show the overflow in Edge.\n \*^\\n\\nbutton,\\ninput { /\* 1 \*/ overflow: visible;\\n}\\n\\n/\*\*\n \* Remove the inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n \*^\\n\\nbutton,\\nselect { /\* 1 \*/ text-transform: none;\\n}\\n\\n/\*\*\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable types in iOS and Safari.\n \*^\\n\\nbutton,\\nhtml [type=\\\"button\\\"], /\* 1 \*/ [type=\\\"reset\\\"], [type=\\\"submit\\\"] {\\n -webkit-appearance: button; /\* 2 \*/}\\n\\n/\*\*\n \* Remove the inner border and padding in Firefox.\n \*^\\n\\nbutton::-moz-focus-inner, [type=\\\"button\\\"]::-moz-focus-inner, [type=\\\"reset\\\"]::-moz-focus-inner, [type=\\\"submit\\\"]::-moz-focus-inner {\\n border-style: none;\\n padding: 0;\\n}\\n\\n/\*\*\n \* Restore the focus styles unset by the previous rule.\n \*^\\n\\nbutton:-moz-focusing, [type=\\\"button\\\"]:-moz-focusing, [type=\\\"reset\\\"]:-moz-focusing, [type=\\\"submit\\\"]:-moz-focusing {\\n outline: 1px dotted ButtonText;\\n}\\n\\n/\*\*\n \* Correct the padding in Firefox.\n \*^\\n\\nfieldset {\\n padding: 0.35em 0.75em 0.625em;\\n}\\n\\n/\*\*\n \* 1. Correct the text wrapping in Edge and IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers are not caught out when they zero out `fieldset` elements in all browsers.\n \*^\\n\\nlegend {\\n -webkit-box-sizing: border-box;\\n box-sizing: border-box; /\* 1 \*/ color: inherit; /\* 2 \*/ display: table; /\* 1 \*/ max-width: 100%; /\* 1 \*/ padding: 0; /\* 3 \*/ white-space: normal; /\* 1 \*/}\\n\\n/\*\*\n \* 1. Add the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*^\\n\\nprogress {\\n display: inline-block; /\* 1 \*/ vertical-align: baseline; /\* 2 \*/}\\n\\n/\*\*\n \* Remove the default vertical scrollbar in IE.\n \*^\\n\\ntextarea {\\n overflow: auto;\\n}\\n\\n/\*\*\n \* 1. Add the correct box sizing in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*^\\n\\n[type=\\\"checkbox\\\"], [type=\\\"radio\\\"] {\\n -webkit-box-sizing: border-box;\\n box-sizing: border-box; /\* 1 \*/ padding: 0; /\* 2 \*/}\\n\\n/\*\*\n \* Correct the cursor style of increment and decrement buttons in Chrome.\n \*^\\n\\n[type=\\\"number\\\"]::-webkit-inner-spin-button, [type=\\\"number\\\"]::-webkit-outer-spin-button {\\n height: auto;\\n}\\n\\n/\*\*\n \* 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in Safari.\n \*^\\n\\n[type=\\\"search\\\"] {\\n -webkit-appearance: textfield; /\* 1 \*/ outline-offset: -2px; /\* 2 \*/}\\n\\n/\*\*\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n \*^\\n\\n[type=\\\"search\\\"]::-webkit-search-cancel-button, [type=\\\"search\\\"]::-webkit-search-decoration {\\n -webkit-appearance: none;\\n}\\n\\n/\*\*\n \* 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2. Change font properties to `inherit` in Safari.\n \*^\\n\\n::-webkit-file-upload-button {\\n -webkit-appearance: button; /\* 1 \*/ font: inherit; /\* 2 \*/}\\n\\n/\* Interactive\\n

=====  
\*^\\n\\n/\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in Edge, IE, and Firefox.\n \*^\\n\\ndetails, /\* 1 \*/\n \*^\\n\\nmenu {\\n display: block;\\n}\\n\\n/\*\n \* Add the correct display in all browsers.\n \*^\\n\\nsummary {\\n display: list-item;\\n}\\n\\n/\* Scripting\\n

=====  
\*^\\n\\n/\*\*\n \* Add the correct display in IE 9-.\n \*^\\n\\ncanvas {\\n display: inline-block;\\n}\\n\\n/\*\*\n \* Add the correct display in IE.\n \*^\\n\\ntemplate {\\n display: none;\\n}\\n\\n/\* Hidden\\n

=====  
\*^\\n\\n/\*\*\n \* Add the correct display in IE 10-.\n \*^\\n\\n[hidden] {\\n display: none;\\n}\\n", "",  
{ "version": 3, "sources": ["/home/ubuntu/ReactThumbSignIn/node\_modules/normalize.css/normalize.css"], "names": [], "mappings": "AAAA,4EAA4E;;AAE5E;gFACgF;;AAEhF;;;GAIG;;AAEH;EACE,kBAaKB,CAAC,OA  
AO;EAC1B,2BAA2B,CAAC,OAAO;EACnC,+BAA+B,CAAC,OAAO;CACxC;;AAED;gFACgF;;AAEhF;;G  
AEG;;AAEH;EACE,UAAU;CACX;;AAED;;GAEG;;AAEH;;;EAME,eAAe;CACHB;;AAED;;;GAGG;;AAE

H;EACE,eAAe;EACf,iBAaIB;CACIB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;OAE0,OAAO;EACZ,eAAe;CACHB;;AAED;;GAEG;;AAEH;EACE,iBAaIB;CACIB;;AAED;;;GAGG;;AAEH;EACE,gCAAgC;UACxB,wBAAwB,CAAC,OAAO;EACxC,UAAU,CAAC,OAAO;EACIB,kBAaKB,CAAC,OAAO;CAC3B;;AAED;;;GAGG;;AAEH;EACE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,sCAAsC,CAAC,OAAO;CAC/C;;AAED;;;GAGG;;AAEH;EACE,oBAAoB,CAAC,OAAO;EAC5B,2BAA2B,CAAC,OAAO;EACnC,0CAA0C;UAC1C,kCAaKC,CAAC,OAAO;CACnD;;AAED;;GAEG;;AAEH;;EAEe,qBAaQB;CACtB;;AAED;;GAEG;;AAEH;;EAEe,oBAAoB;CACrB;;AAED;;;GAGG;;AAEH;;EAGE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,uBAAuB;EACvB,YAAY;CACb;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EAEe,eAAe;EACf,eAAe;EACf,mBAAmB;EACnB,yBAaYB;CAC1B;;AAED;EACE,gBAAgB;CACjB;;AAED;EACE,YAAY;CACb;;AAED;gFACgF;;AAEHf;;GAEG;;AAEH;;EAEe,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;EACd,UAAU;CACX;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,iBAaIB;CACIB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;;EAKE,wBAAwB,CAAC,OAAO;EACHC,gBAAgB,CAAC,OAAO;EACxB,kBAaKB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;;GAGG;;AAEH;QACQ,OAAO;EACb,kBAaKB;CACnB;;AAED;;;GAGG;;AAEH;SACS,OAAO;EACd,qBAaQB;CACtB;;AAED;;;GAIG;;AAEH;;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;;EAIE,mBAAmB;EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;;EAIE,+BAA+B;CACHC;;AAED;;GAEG;;AAEH;EACE,+BAA+B;CACHC;;AAED;;;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,eAAe,CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAAgB,CAAC,OAAO;EACxB,WAAW,CAAC,OAAO;EACnB,oBAAoB,CAAC,OAAO;CAC7B;;AAED;;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,yBAaYB,CAAC,OAAO;CAC1C;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EAEe,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AAEH;;EAEe,aAAa;CACd;;AAED;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAaQB,CAAC,OAAO;CAC9B;;AAED;;GAEG;;AAEH;;EAEe,yBAaYB;CAC1B;;AAED;;;GAGG;;AAEH;EACE,2BAA2B,CAAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;EAEe,eAAe;CACHB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;gFACgF;;AAEHf;;GAEG;;AAEH;EACE,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED;gFACgF;;AAEHf;;GAEG;;AAEH;EACE,cAAc;CACf", "file": "normalize.css", "sourcesContent": ["/\*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css \*/\n\n/\* Document\n\n=====\n\n\*/\n\n/\* 1. Correct the line height in all browsers.\n\n 2. Prevent adjustments of font size after orientation changes in\n IE on Windows Phone and in iOS.\n\n\*/\n\nhtml { line-height: 1.15; /\* 1 \*/\n\n-ms-text-size-adjust: 100%; /\* 2 \*/\n-webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n\n=====\n\n\*/\n\n/\* Remove the margin in all browsers (opinionated).\n\n\*/\n\nbody { margin: 0;\n\n}\n\n/\* Add the correct display in IE 9-.\n\n\*/\n\narticle, aside, footer, header, nav, section { display: block;\n\n}\n\n/\* Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.\n\n\*/\n\nh1 { font-size: 2em;\n\nmargin: 0.67em 0;\n\n}\n\n/\* Grouping content\n\n=====\n\n\*/\n\n/\* Add the correct display in IE 9-.\n\n 1. Add the correct display in IE.\n\n\*/\n\nfigure, figure, main { /\* 1 \*/ display: block;\n\n}\n\n/\* Add the correct margin in IE 8.\n\n\*/

/\* 1. Correct the line height in all browsers.\n\n 2. Prevent adjustments of font size after orientation changes in\n IE on Windows Phone and in iOS.\n\n\*/\n\nhtml { line-height: 1.15; /\* 1 \*/\n\n-ms-text-size-adjust: 100%; /\* 2 \*/\n-webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n\n=====\n\n\*/\n\n/\* Remove the margin in all browsers (opinionated).\n\n\*/\n\nbody { margin: 0;\n\n}\n\n/\* Add the correct display in IE 9-.\n\n\*/\n\narticle, aside, footer, header, nav, section { display: block;\n\n}\n\n/\* Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.\n\n\*/\n\nh1 { font-size: 2em;\n\nmargin: 0.67em 0;\n\n}\n\n/\* Grouping content\n\n=====\n\n\*/\n\n/\* Add the correct display in IE 9-.\n\n 1. Add the correct display in IE.\n\n\*/\n\nfigure, figure, main { /\* 1 \*/ display: block;\n\n}\n\n/\* Add the correct margin in IE 8.\n\n\*/

\*\n\nfigure {\n margin: 1em 40px;\n}\n\n/\*\*\n \* 1. Add the correct box sizing in Firefox.\n \* 2. Show the overflow in Edge and IE.\n \*\n\nhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /\* 1 \*\n height: 0; /\* 1 \*\n overflow: visible; /\* 2 \*\n}\n\n/\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*\n\npre {\n font-family: monospace, monospace; /\* 1 \*\n font-size: 1em; /\* 2 \*\n}\n\n/\* Text-level semantics\n

=====  
\*\n\n/\*\*\n \* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in iOS 8+ and Safari 8+.\n \*\n\na {\n background-color: transparent; /\* 1 \*\n -webkit-text-decoration-skip: objects; /\* 2 \*\n}\n\n/\*\*\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*\n\nabbr[title] {\n border-bottom: none; /\* 1 \*\n text-decoration: underline; /\* 2 \*\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*\n}\n\n/\*\*\n \* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n \*\n\nb,\nstrong {\n font-weight: inherit;\n}\n\n/\*\*\n \* Add the correct font weight in Chrome, Edge, and Safari.\n \*\n\nb,\nstrong {\n font-weight: bolder;\n}\n\n/\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*\n\ncode,\nkbd,\nsamp {\n font-family: monospace, monospace; /\* 1 \*\n font-size: 1em; /\* 2 \*\n}\n\n/\*\*\n \* Add the correct font style in Android 4.3-.\n \*\n\ndfn {\n font-style: italic;\n}\n\n/\*\*\n \* Add the correct background and color in IE 9-.\n \*\n\nmark {\n background-color: #ff0;\n color: #000;\n}\n\n/\*\*\n \* Add the correct font size in all browsers.\n \*\n\nsmall {\n font-size: 80%;\n}\n\n/\*\*\n \* Prevent `sub` and `sup` elements from affecting the line height in\n \* all browsers.\n \*\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded content\n

=====  
\*\n\n/\*\*\n \* Add the correct display in IE 9-.\n \*\n\naudio,\nvideo {\n display: inline-block;\n}\n\n/\*\*\n \* Add the correct display in iOS 4-7.\n \*\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n/\*\*\n \* Remove the border on images inside links in IE 10-.\n \*\n\nimg {\n border-style: none;\n}\n\n/\*\*\n \* Hide the overflow in IE.\n \*\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\*\n\n/\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n \*\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*\n font-size: 100%; /\* 1 \*\n line-height: 1.15; /\* 1 \*\n margin: 0; /\* 2 \*\n}\n\n/\*\*\n \* Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n \*\n\nbutton,\ninput { /\* 1 \*\n overflow: visible;\n}\n\n/\*\*\n \* Remove the inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n \*\n\nbutton,\nselect { /\* 1 \*\n text-transform: none;\n}\n\n/\*\*\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable types in iOS and Safari.\n \*\n\nbutton,\nhtml [type="button"], /\* 1 \*\n[type="reset"],\n[type="submit"] {\n -webkit-appearance: button; /\* 2 \*\n}\n\n/\*\*\n \* Remove the inner border and padding in Firefox.\n \*\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n/\*\*\n \* Restore the focus styles unset by the previous rule.\n \*\n\nbutton:-moz-focusing,\n[type="button"]:-moz-focusing,\n[type="reset"]:-moz-focusing,\n[type="submit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n\n/\*\*\n \* Correct the padding in Firefox.\n \*\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n/\*\*\n \* 1. Correct the text wrapping in Edge and



IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers are not caught out when they zero out\n \* `fieldset` elements in all browsers.\n \*/\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n color: inherit; /\* 2 \*/\n display: table; /\* 1 \*/\n max-width: 100%; /\* 1 \*/\n padding: 0; /\* 3 \*/\n white-space: normal; /\* 1 \*/\n}\n\n\*\*\n \* 1. Add the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*/\n\nprogress {\n display: inline-block; /\* 1 \*/\n vertical-align: baseline; /\* 2 \*/\n}\n\n\*\*\n \* Remove the default vertical scrollbar in IE.\n \*/\n\ntextarea {\n overflow: auto;\n}\n\n\*\*\n \* 1. Add the correct box sizing in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*/\n\n[type="checkbox"],\n[type="radio"] {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n padding: 0; /\* 2 \*/\n}\n\n\*\*\n \* Correct the cursor style of increment and decrement buttons in Chrome.\n \*/\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n height: auto;\n}\n\n\*\*\n \* 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in Safari.\n \*/\n\n[type="search"] {\n -webkit-appearance: textfield; /\* 1 \*/\n outline-offset: -2px; /\* 2 \*/\n}\n\n\*\*\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n \*/\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n -webkit-appearance: none;\n}\n\n\*\*\n \* 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2. Change font properties to `inherit` in Safari.\n \*/\n\n::-webkit-file-upload-button {\n -webkit-appearance: button; /\* 1 \*/\n font: inherit; /\* 2 \*/\n}\n\n/\* Interactive\n

\* Boolean if this should be a query indeterminate progress bar.

query: \_propTypes2.default.bool,

query: false

\* region until it is finished loading. It is not possible for the user to alter the value of a progressbar

22-[https://stage.thumbssignin.com/assets/docs\\_windows.chunk.js](https://stage.thumbssignin.com/assets/docs_windows.chunk.js)

Other Information: \* Gets the easing type from the smooth prop within options.

```
var from = match.index + (lookbehind ? match[1].length : 0),
    // Move the index i to the element in strarr that is closest to from
    if (from >= p) {
var from = match.index + lookbehindLength,
    to = from + match.length,
    before = str.slice(0, from),
// Copy of the full string this token was created from
'keyword':
/\b(?:as|async|await|break|case|catch|class|const|continue|debugger|default|delete|do|else|enum|export|extends|finally|for|from|function|get|if|implements|import|in|instanceof|interface|let|new|null|of|package|private|protected|public|return|set|static|super|switch|this|throw|try|typeof|var|void|while|with|yield)\b/,
//import PropTypes from 'prop-types';
/** Detect free variable `global` from Node.js. */
// accelerating from zero velocity
// accelerating from zero velocity
// accelerating from zero velocity
// accelerating from zero velocity
// Remove `parentBindings` from props
'ThumbSignin provides an additional security layer to protect windows computers. The
administrator of an organisation as to download and install the Thumbssignin Connector app in the windows PC.'
'Thereafter whenever the account holders tries to log in to their computer, a QR code is
displayed as a second factor authentication once they provide the windows username and password. Scanning
the QR code using the ThumbSignin mobile app and authenticating with their fingerprint will let the user to
login into the computer.'
'This can significantly enhance the additional security of an enterprise computer and protect
critical data from unauthorized access.'
'Operating System: Windows 10 or later.'
'Operating System: Windows Server 2008 R2 Standard or later.'
'ThumbSignin also requires .NET Framework 4.0 or later. If the correct .NET version is not
present on your system then the setup prompts you to install the .NET Framework.'
'Windows user must have password to login to the computer even though they have
enabled ThumbSignin as second factor authentication.'
'User can bypass ThumbSignin second factor authentication by restarting Windows in
Safe mode.'
'AD / Azure AD / LDAP: Admin can reset the user authentication mobile device.'
'ThumbSigninConnector.msi requires an admin access to install / uninstall.'
```

'Login to Administrator account and then download ThumbSigninConnector.msi and install it on the required client machines.'

'Once the QR code is scanned, mobile app will ask the user to authenticate using the fingerprint.'

'After the successful fingerprint authentication, second factor authentication is enabled for the user.'

'The user submit the Windows credentials.'

'ThumbSignin QR code appears after the user successfully submit the Windows credentials. By scanning the QR code and authenticating the fingerprint user will be able to login into windows.'

'The Admin manages the second factor authentication for the domain users by creating a group called 2FA. Adding a user to this group will enable 2FA and removing the user from the group will disable 2FA.'

'Active Directory User list'

'Add user to 2FA group'

'To enable second-factor authentication for an user, admin can add the user to 2FA group.'

'Remove user from 2FA group'

'To disable second-factor authentication for an user, admin can simply remove the user from 2FA group.'

'Remove user access'

'To stop the user accessing the Windows pc delete the user account from the server or add to \u201CACCESS\_DENIED\u201D group. So that the user won\u2019t even be able to login to the windows machine.'

'Windows Removed user account'

'Usually windows will take some time to sync, if the user has been removed from the organisation domain. ThumbSignin solution will take effect immediately whenever admin make changes.'

```
query: '{\n    user {\n        isLogedin\n    } \n    }'
```

```
name: 'Active Directory User list',
```

```
name: 'Add user to 2FA group',
```

```
name: 'Remove user from 2FA group',
```

```
name: 'Remove user access',
```

```
name: 'Windows Removed user account',
```

```
{ query: data, __source: {
```

```
// this implementation is not 100% perfect for weird media query combinations
```

```
// Adapted from convert-source-map (MIT)
```

```
* // Remove it from the DOM
```

```
// bind timers to global for call from export context
```

```
// Thrash, waste and sodomy: IE GC bug
```

```
// IE 8- don't enum bug keys
```

```
err = new Error('You provided a `'+ propFullNameSafe + '` ' + location + ' to the ' + componentNameSafe +  
' that was ' + ('not within the range from \'' + min + ' - ' + max + '\'. `'+ propFullNameSafe + `': ' + value + '));
```

```
// Don't enum bug & hidden keys
```

```
// getting tag from 19.1.3.6 Object.prototype.toString()
```

```
// callbacks from appending listeners
    return fetch('/api/user').then(function (response) {
      return fetch('/api/user', { method: "POST", body: userInfo }).then(function (response) {
// cached from whatever global is present so that test runners that stub it
// import { Provider } from '../Modal'
    query: __WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.object.isRequired
exports.push([module.i, "/*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css *\n\n/*
Document\n
```

```

*^/n/n/**\n * 1. Correct the line height in all browsers.\n * 2. Prevent adjustments of font size after orientation
changes in\n * IE on Windows Phone and in iOS.\n *^/n/nhtml {\n line-height: 1.15; /* 1 */^/n
-ms-text-size-adjust: 100%; /* 2 */^/n -webkit-text-size-adjust: 100%; /* 2 */^/n }^/n/n/* Sections\n

```

```

* Remove the margin in all browsers (opinionated).
body {
  margin: 0;
}

* Add the correct display in IE 9-.
article, aside, footer, header, nav, section {
  display: block;
}

* Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.
h1 {
  font-size: 2em;
  margin: 0.67em 0;
}

Grouping content

```

```

*\n/n/**\n * Add the correct display in IE 9-.\n * 1. Add the correct display in IE.\n
*\n/nfigcaption,\nfigure,\nmain { /* 1 *\n  display: block;\n}\n/n/**\n * Add the correct margin in IE 8.\n
*\n/n/figure {\n  margin: 1em 40px;\n}\n/n/**\n * 1. Add the correct box sizing in Firefox.\n * 2. Show the
overflow in Edge and IE.\n *\n/n/nhr {\n  -webkit-box-sizing: content-box;\n          box-sizing: content-box; /* 1
*\n  height: 0; /* 1 *\n  overflow: visible; /* 2 *\n}\n/n/**\n * 1. Correct the inheritance and scaling of font
size in all browsers.\n * 2. Correct the odd `em` font sizing in all browsers.\n *\n/n/npre {\n  font-family:
monospace, monospace; /* 1 *\n  font-size: 1em; /* 2 *\n}\n/n/* Text-level semantics\n

```

\*\n\n/\*\*\n \* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in iOS 8+ and Safari 8+.\n \*/\n\n\na {\n background-color: transparent; /\* 1 \*\n -webkit-text-decoration-skip: objects; /\* 2 \*\n }\n\n/\*\*\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*/\n\nabbr[title] {\n border-bottom: none; /\* 1 \*\n text-decoration: underline; /\* 2 \*\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*\n }\n\n/\*\*\n \* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n \*/\n\nb,\nstrong {\n font-weight: inherit;\n }\n\n/\*\*\n \* Add the correct font weight in Chrome, Edge, and Safari.\n \*/\n\nb,\nstrong {\n font-weight: bolder;\n }\n\n/\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\ncode,\nkbd,\nsamp {\n font-family: monospace, monospace; /\* 1 \*\n font-size: 1em; /\* 2 \*\n }\n\n/\*\*\n \* Add the correct font style in Android 4.3-.\n \*/\n\nndfn {\n font-style: italic;\n }\n\n/\*\*\n \* Add the correct background and color in IE 9-.\n \*/\n\nmark {\n background-color: #ff0;\n color: #000;\n }\n\n/\*\*\n \* Add the correct font size in all browsers.\n \*/\n\nsmall {\n font-size: 80%;\n }\n\n/\*\*\n \* Prevent `sub` and `sup` elements from affecting the line height in\n \* all browsers.\n \*/\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n }\n\nsub {\n bottom: -0.25em;\n }\n\nsup {\n top: -0.5em;\n }\n\n/\* Embedded content\n

=====  
\*/n/n/\*\*/n \* Add the correct display in IE 9-. \n \*/n/naudio,\nvideo {\n display: inline-block;\n}\n/n/\*\*/n \*  
Add the correct display in iOS 4-7. \n \*/n/naudio:not([controls]) {\n display: none;\n height: 0;\n}\n/n/\*\*/n \*  
Remove the border on images inside links in IE 10-. \n \*/n/nimg {\n border-style: none;\n}\n/n/\*\*/n \* Hide the  
overflow in IE. \n \*/n/nsvg:not(:root) {\n overflow: hidden;\n}\n/n/\* Forms\n

=====  
\*/n/n/\*\*/n \* 1. Change the font styles in all browsers (opinionated). \n \* 2. Remove the margin in Firefox and  
Safari. \n \*/n/nbutton,\nininput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*/ \n font-size:  
100%; /\* 1 \*/ \n line-height: 1.15; /\* 1 \*/ \n margin: 0; /\* 2 \*/ }\n/n/\*\*/n \* Show the overflow in IE. \n \* 1.  
Show the overflow in Edge. \n \*/n/nbutton,\nininput { /\* 1 \*/ \n overflow: visible;\n}\n/n/\*\*/n \* Remove the  
inheritance of text transform in Edge, Firefox, and IE. \n \* 1. Remove the inheritance of text transform in  
Firefox. \n \*/n/nbutton,\nselect { /\* 1 \*/ \n text-transform: none;\n}\n/n/\*\*/n \* 1. Prevent a WebKit bug where  
(2) destroys native `audio` and `video` \n \* controls in Android 4. \n \* 2. Correct the inability to style clickable  
types in iOS and Safari. \n \*/n/nbutton,\nhtml [type="button"], /\* 1 \*/ \n[type="reset"],\n[type="submit"]  
{\n -webkit-appearance: button; /\* 2 \*/ }\n/n/\*\*/n \* Remove the inner border and padding in Firefox. \n  
\*/n/nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[ty  
pe="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n/n/\*\*/n \* Restore the focus styles  
unset by the previous rule. \n  
\*/n/nbutton:-moz-focusing,\n[type="button"]:-moz-focusing,\n[type="reset"]:-moz-focusing,\n[type="su  
bmit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n/n/\*\*/n \* Correct the padding in Firefox. \n  
\*/n/nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n/n/\*\*/n \* 1. Correct the text wrapping in Edge and  
IE. \n \* 2. Correct the color inheritance from `fieldset` elements in IE. \n \* 3. Remove the padding so developers  
are not caught out when they zero out \n \* `fieldset` elements in all browsers. \n \*/n/nlegend {\n  
-webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/ \n color: inherit; /\* 2 \*/ \n display: table;  
/\* 1 \*/ \n max-width: 100%; /\* 1 \*/ \n padding: 0; /\* 3 \*/ \n white-space: normal; /\* 1 \*/ }\n/n/\*\*/n \* 1. Add  
the correct display in IE 9-. \n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera. \n  
\*/n/nprogress {\n display: inline-block; /\* 1 \*/ \n vertical-align: baseline; /\* 2 \*/ }\n/n/\*\*/n \* Remove the  
default vertical scrollbar in IE. \n \*/n/ntextarea {\n overflow: auto;\n}\n/n/\*\*/n \* 1. Add the correct box sizing  
in IE 10-. \n \* 2. Remove the padding in IE 10-. \n \*/n/n[type="checkbox"],\n[type="radio"] {\n  
-webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/ \n padding: 0; /\* 2 \*/ }\n/n/\*\*/n \*  
Correct the cursor style of increment and decrement buttons in Chrome. \n  
\*/n/n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n height:  
auto;\n}\n/n/\*\*/n \* 1. Correct the odd appearance in Chrome and Safari. \n \* 2. Correct the outline style in  
Safari. \n \*/n/n[type="search"] {\n -webkit-appearance: textfield; /\* 1 \*/ \n outline-offset: -2px; /\* 2  
\*/ }\n/n/\*\*/n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS. \n  
\*/n/n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n  
-webkit-appearance: none;\n}\n/n/\*\*/n \* 1. Correct the inability to style clickable types in iOS and Safari. \n \* 2.  
Change font properties to `inherit` in Safari. \n \*/n/n::-webkit-file-upload-button {\n -webkit-appearance:  
button; /\* 1 \*/ \n font: inherit; /\* 2 \*/ }\n/n/\* Interactive\n

=====  
\*/n/n/\* \n \* Add the correct display in IE 9-. \n \* 1. Add the correct display in Edge, IE, and Firefox. \n  
\*/n/ndetails, /\* 1 \*/ \nmenu {\n display: block;\n}\n/n/\* \n \* Add the correct display in all browsers. \n  
\*/n/nsummary {\n display: list-item;\n}\n/n/\* Scripting\n

=====

\*\n\n\*\*\n \* Add the correct display in IE 9-.\n \*\n\nncanvas {\n display: inline-block;\n}\n\n/\*\*\n \* Add the correct display in IE.\n \*\n\nntemplate {\n display: none;\n}\n\n/\* Hidden\n

=====

\*\n\n\*\*\n \* Add the correct display in IE 10-.\n \*\n\n[hidden] {\n display: none;\n}\n\n", "",  
{ "version":3,"sources":["/home/ubuntu/ReactThumbSignIn/node\_modules/normalize.css/normalize.css"],"names":["mappings":"AAAA,4EAA4E;;AAE5E;gFACgF;;AAEhF;;;GAIG;;AAEH;EACE,kBAaKB,CAAC,OA  
AO;EAC1B,2BAA2B,CAAC,OAAO;EACnC,+BAA+B,CAAC,OAAO;CACxC;;AAED;gFACgF;;AAEhF;;G  
AEG;;AAEH;EACE,UAAU;CACX;;AAED;;GAEG;;AAEH;;;;;EAME,eAAe;CACHB;;AAED;;;GAGG;;AAE  
H;EACE,eAAe;EACf,iBAaIB;CACIB;;AAED;gFACgF;;AAEhF;;;GAGG;;AAEH;;OAE0,OAAO;EACZ,eA  
Ae;CACHB;;AAED;;GAEG;;AAEH;EACE,iBAaIB;CACIB;;AAED;;;GAGG;;AAEH;EACE,gCAAgC;UACx  
B,wBAawB,CAAC,OAAO;EACxC,UAAU,CAAC,OAAO;EACIB,kBAaKB,CAAC,OAAO;CAC3B;;AAED;;  
;GAGG;;AAEH;EACE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED;gFACgF;;AA  
EhF;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,sCAAsC,CAAC,OAAO;CAC/C;;AAED;;;GAG  
G;;AAEH;EACE,oBAaOB,CAAC,OAAO;EAC5B,2BAA2B,CAAC,OAAO;EACnC,0CAA0C;UACIC,kCAA  
kC,CAAC,OAAO;CACnD;;AAED;;GAEG;;AAEH;;EAEe,qBAaQB;CACtB;;AAED;;GAEG;;AAEH;;EAEe,  
oBAaOB;CACrB;;AAED;;;GAGG;;AAEH;;EAGE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;C  
ACxB;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;;GAEG;;AAEH;EACE,uBAaUB;EACvB,Y  
AAY;CACb;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EAEe,eAAe;EACf,eAA  
e;EACf,mBAaMB;EACnB,yBAaYB;CAC1B;;AAED;EACE,gBAaGB;CACjB;;AAED;EACE,YAAY;CACb;;  
AAED;gFACgF;;AAEhF;;GAEG;;AAEH;;EAEe,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;EA  
Cd,UAAU;CACX;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;;GAEG;;AAEH;EACE,iBAaIB  
;CACIB;;AAED;gFACgF;;AAEhF;;;GAGG;;AAEH;;;;;EAKE,wBAawB,CAAC,OAAO;EACbC,gBAaGB,CA  
AC,OAAO;EACxB,kBAaKB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;;GAGG;;AAEH  
;QACQ,OAAO;EACb,kBAaKB;CACnB;;AAED;;;GAGG;;AAEH;SACS,OAAO;EACd,qBAaQB;CACtB;;A  
AED;;;GAIG;;AAEH;;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;;EAIE,mBAaMB;  
EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;;EAIE,+BAA+B;CACHC;;AAED;;GAEG;;AAEH;EACE,+  
BAA+B;CACHC;;AAED;;;;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAaUB,CAAC,OAAO;EACvC,eAAe,  
CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAaGB,CAAC,OAAO;EACxB,WAAW,CAAC,OAA  
O;EACnB,oBAaOB,CAAC,OAAO;CAC7B;;AAED;;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,  
yBAaYB,CAAC,OAAO;CACIC;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EA  
EE,+BAA+B;UACvB,uBAaUB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AA  
EH;;EAEe,aAAa;CACd;;AAED;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAaQB,CAAC,O  
AAO;CAC9B;;AAED;;GAEG;;AAEH;;EAEe,yBAaYB;CAC1B;;AAED;;;GAGG;;AAEH;EACE,2BAA2B,C  
AAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED;gFACgF;;AAEhF;;;GAGG;;AAEH;;EAEe,eAAe;  
CACHB;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;gFACgF;;AAEhF;;GAEG;;AAEH;EACE,  
sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED;gFACgF;;AAEhF;;GAEG;;AAEH;EAC  
E,cAAc;CACf","file":"normalize.css","sourcesContent":["/\*! normalize.css v7.0.0 | MIT License |  
github.com/necolas/normalize.css \*/\n\n/\* Document\n

=====

\*\n\n\*\*\n \* 1. Correct the line height in all browsers.\n \* 2. Prevent adjustments of font size after orientation  
changes in\n \* IE on Windows Phone and in iOS.\n \*\n\nhtml {\n line-height: 1.15; /\* 1 \*\n-ms-text-size-adjust: 100%; /\* 2 \*\n-webkit-text-size-adjust: 100%; /\* 2 \*\n}\n\n/\* Sections\n

=====  
\*/\n\n\*\*\n \* Remove the margin in all browsers (opinionated).\n \*/\n\nbody {\n margin: 0;\n}\n\n\*\*\n \* Add the correct display in IE 9-.\n \*/\n\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display: block;\n}\n\n\*\*\n \* Correct the font size and margin on `h1` elements within `section` and\n \* `article` contexts in Chrome, Firefox, and Safari.\n \*/\n\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping content\n

=====  
\*/\n\n\*\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in IE.\n\n\*/\n\nfigcaption,\nfigure,\nmain { /\* 1 \*/\n display: block;\n}\n\n\*\*\n \* Add the correct margin in IE 8.\n\n\*/\n\nfigure {\n margin: 1em 40px;\n}\n\n\*\*\n \* 1. Add the correct box sizing in Firefox.\n \* 2. Show the overflow in Edge and IE.\n \*/\n\nhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /\* 1 \*/\n height: 0; /\* 1 \*/\n overflow: visible; /\* 2 \*/\n}\n\n\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\npre {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\* Text-level semantics\n

=====  
\*/\n\n\*\*\n \* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in iOS 8+ and Safari 8+.\n \*/\n\na {\n background-color: transparent; /\* 1 \*/\n -webkit-text-decoration-skip: objects; /\* 2 \*/\n}\n\n\*\*\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*/\n\nabbr[title] {\n border-bottom: none; /\* 1 \*/\n text-decoration: underline; /\* 2 \*/\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*/\n}\n\n\*\*\n \* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n \*/\n\nb,\nstrong {\n font-weight: inherit;\n}\n\n\*\*\n \* Add the correct font weight in Chrome, Edge, and Safari.\n \*/\n\nb,\nstrong {\n font-weight: bolder;\n}\n\n\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\ncode,\nkbd,\nsamp {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n\*\*\n \* Add the correct font style in Android 4.3-.\n \*/\n\ni,\ndfn {\n font-style: italic;\n}\n\n\*\*\n \* Add the correct background and color in IE 9-.\n \*/\n\nmark {\n background-color: #ff0;\n color: #000;\n}\n\n\*\*\n \* Add the correct font size in all browsers.\n \*/\n\nsmall {\n font-size: 80%;\n}\n\n\*\*\n \* Prevent `sub` and `sup` elements from affecting the line height in\n \* all browsers.\n \*/\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded content\n

=====  
\*/\n\n\*\*\n \* Add the correct display in IE 9-.\n \*/\n\naudio,\nvideo {\n display: inline-block;\n}\n\n\*\*\n \* Add the correct display in iOS 4-7.\n \*/\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n\*\*\n \* Remove the border on images inside links in IE 10-.\n \*/\n\nimg {\n border-style: none;\n}\n\n\*\*\n \* Hide the overflow in IE.\n \*/\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\*/\n\n\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n \*/\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*/\n font-size: 100%; /\* 1 \*/\n line-height: 1.15; /\* 1 \*/\n margin: 0; /\* 2 \*/\n}\n\n\*\*\n \* Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n \*/\n\nbutton,\ninput {\n overflow: visible; /\* 1 \*/\n}\n\n\*\*\n \* Remove the inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n \*/\n\nbutton,\nselect { /\* 1 \*/\n text-transform: none;\n}\n\n\*\*\n \* 1. Prevent a WebKit bug where

(2) destroys native `audio` and `video` controls in Android 4.  
2. Correct the inability to style clickable types in iOS and Safari.  
`<button>`, `<html [type="button"]>`, `<[type="reset"]>`, `<[type="submit"]>`  
`{<br> -webkit-appearance: button; }>`  
2. Remove the inner border and padding in Firefox.  
`<[type="button"]>`, `<[type="button"]>`, `<[type="reset"]>`, `<[type="submit"]>`  
`{<br> border-style: none;<br> padding: 0; }>`  
Restore the focus styles unset by the previous rule.

`<[type="button"]>`, `<[type="button"]>`, `<[type="reset"]>`, `<[type="submit"]>`  
`{<br> outline: 1px dotted ButtonText; }>`  
Correct the padding in Firefox.

`<fieldset>`  
`{<br> padding: 0.35em 0.75em 0.625em; }>`  
1. Correct the text wrapping in Edge and IE.  
2. Correct the color inheritance from `fieldset` elements in IE.  
3. Remove the padding so developers are not caught out when they zero out `fieldset` elements in all browsers.

`<legend>`  
`{<br> -webkit-box-sizing: border-box;<br> box-sizing: border-box; }>`  
1. `color: inherit;`  
2. `display: table;`  
1. `max-width: 100%;`  
1. `padding: 0;`  
3. `white-space: normal;`  
1. Add the correct display in IE 9-.

2. Add the correct vertical alignment in Chrome, Firefox, and Opera.  
`<progress>`  
`{<br> display: inline-block; }>`  
1. `vertical-align: baseline;`  
2. Remove the default vertical scrollbar in IE.  
`<textarea>`  
`{<br> overflow: auto; }>`  
1. Add the correct box sizing in IE 10-.

2. Remove the padding in IE 10-.

`<[type="checkbox"]>`, `<[type="radio"]>`  
`{<br> -webkit-box-sizing: border-box;<br> box-sizing: border-box; }>`  
1. `padding: 0;`  
2. Correct the cursor style of increment and decrement buttons in Chrome.

`<[type="number"]>`, `<[type="number"]>`, `<[type="number"]>`  
`{<br> height: auto; }>`  
1. Correct the odd appearance in Chrome and Safari.  
2. Correct the outline style in Safari.

`<[type="search"]>`  
`{<br> -webkit-appearance: textfield; }>`  
1. `outline-offset: -2px;`  
2. Remove the inner padding and cancel buttons in Chrome and Safari on macOS.

`<[type="search"]>`, `<[type="search"]>`, `<[type="search"]>`  
`{<br> -webkit-appearance: none; }>`  
1. Correct the inability to style clickable types in iOS and Safari.  
2. Change font properties to `inherit` in Safari.

`<[type="file-upload-button"]>`  
`{<br> -webkit-appearance: button; }>`  
1. `font: inherit;`  
2. Interactive

`<[type="details"]>`  
1. Add the correct display in IE 9-.

`<[type="menu"]>`  
`{<br> display: block; }>`  
1. Add the correct display in all browsers.

`<[type="summary"]>`  
`{<br> display: list-item; }>`  
Scripting

`<[type="canvas"]>`  
`{<br> display: inline-block; }>`  
1. Add the correct display in IE 9-.

`<[type="template"]>`  
`{<br> display: none; }>`  
Hidden

`<[type="hidden"]>`  
`{<br> display: none; }>`, `"sourceRoot": ""`);

user = \_props.user,

user.isLoggedin && \_\_WEBPACK\_IMPORTED\_MODULE\_0\_react\_\_default.a.createElement(

user.isLoggedin && \_\_WEBPACK\_IMPORTED\_MODULE\_0\_react\_\_default.a.createElement(

user.isLoggedin ? \_\_WEBPACK\_IMPORTED\_MODULE\_0\_react\_\_default.a.createElement(

user: {

isLoggedin: !userInfo.isLoading ? userInfo.data.isLoggedin : ownProps.query.user.isLoggedin,

\* `Indeterminate`, and `Query Indeterminate`.



- \* A `Query Indeterminate` linear progress bar is used when you are combining
- \* as a query indeterminate progress bar by adding the prop `query={true}` to the
- \* component. Until a progress value is given, it will display the query linear
- \* progress animation. Afterwards, it will start the determinate animation of where

```

    query = _props.query,
    props = _objectWithoutProperties(_props, ['className', 'progressClassName', 'progressStyle', 'value',
'query', 'centered']);

```

```

    'md-progress--linear-query': query,

```

- \* region until it is finished loading. It is not possible for the user to alter the value of a progressbar

- \* Boolean if this should be a query indeterminate progress bar.

```

query: _propTypes2.default.bool,

```

```

query: false

```

- \* region until it is finished loading. It is not possible for the user to alter the value of a progressbar

23-[https://stage.thumbsignin.com/assets/docs\\_web.chunk.js](https://stage.thumbsignin.com/assets/docs_web.chunk.js)

Other Information:                query: '{\n        user {\n        isLogedin\n        } \n    }'

```

    { query: data, __source: {

```

```

    // this implementation is not 100% perfect for weird media query combinations

```

```

// Adapted from convert-source-map (MIT)

```

- \* // Remove it from the DOM

```

    // bind timers to global for call from export context

```

```

    // Thrash, waste and sodomy: IE GC bug

```

```

// IE 8- don't enum bug keys

```

- \* @param {string=} field - the field to extract a value from. Defaults to 'value'.

```

    err = new Error('You provided a `` + propFullNameSafe + `` ' + location + ' to the ' + componentNameSafe +
' that was ' + ('not within the range from \'' + min + ' - ' + max + '\'. `` + propFullNameSafe + `': ' + value + '));

```

```

    // Don't enum bug & hidden keys

```

```

// getting tag from 19.1.3.6 Object.prototype.toString()

```

```

    // TODO: we could get rid of the need for the wrapper node

```

```

    // factoryChild is not different from child.

```

- \* An ink from `injectInk`.

- \* A tooltip from `injectTooltip`

```

    return new Error('Only one material design button type may be specified in the `` + component + `` but `` +
len + `` ' + 'were given. Select only one of `flat`, `raised`, `icon`, or `floating`.');

```

```

    // callbacks from appending listeners

```

```

    return fetch('/api/user').then(function (response) {

```

```

    return fetch('/api/user', { method: "POST", body: userInfo }).then(function (response) {

```

```

// cached from whatever global is present so that test runners that stub it

```

- \* where the component should be switched to something else for valid html.

```

// import { Provider } from '../Modal'

```

```

    query: __WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.isRequired

```

```

exports.push([module.i, "/*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css */\n\n/*

```

```

Document\n

```

=====

\*\n\n/\*\*\n \* 1. Correct the line height in all browsers.\n \* 2. Prevent adjustments of font size after orientation changes in\n \* IE on Windows Phone and in iOS.\n \*/\n\nhtml {\n line-height: 1.15; /\* 1 \*\n -ms-text-size-adjust: 100%; /\* 2 \*\n -webkit-text-size-adjust: 100%; /\* 2 \*\n }\n\n/\* Sections\n

=====

\*\n\n/\*\*\n \* Remove the margin in all browsers (opinionated).\n \*/\n\nbody {\n margin: 0;\n}\n\n/\*\*\n \* Add the correct display in IE 9-.\n \*/\n\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display: block;\n}\n\n/\*\*\n \* Correct the font size and margin on `h1` elements within `section` and\n \* `article` contexts in Chrome, Firefox, and Safari.\n \*/\n\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping content\n

=====

\*\n\n/\*\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in IE.\n \*/\n\nfigcaption,\nfigure,\nmain { /\* 1 \*\n display: block;\n}\n\n/\*\*\n \* Add the correct margin in IE 8.\n \*/\n\nfigure {\n margin: 1em 40px;\n}\n\n/\*\*\n \* 1. Add the correct box sizing in Firefox.\n \* 2. Show the overflow in Edge and IE.\n \*/\n\nhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /\* 1 \*\n height: 0; /\* 1 \*\n overflow: visible; /\* 2 \*\n}\n\n/\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\npre {\n font-family: monospace, monospace; /\* 1 \*\n font-size: 1em; /\* 2 \*\n}\n\n/\* Text-level semantics\n

=====

\*\n\n/\*\*\n \* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in iOS 8+ and Safari 8+.\n \*/\n\na {\n background-color: transparent; /\* 1 \*\n -webkit-text-decoration-skip: objects; /\* 2 \*\n}\n\n/\*\*\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*/\n\nabbr[title] {\n border-bottom: none; /\* 1 \*\n text-decoration: underline; /\* 2 \*\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*\n}\n\n/\*\*\n \* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n \*/\n\nb,\nstrong {\n font-weight: inherit;\n}\n\n/\*\*\n \* Add the correct font weight in Chrome, Edge, and Safari.\n \*/\n\nb,\nstrong {\n font-weight: bolder;\n}\n\n/\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\ncode,\nkbd,\nsamp {\n font-family: monospace, monospace; /\* 1 \*\n font-size: 1em; /\* 2 \*\n}\n\n/\*\*\n \* Add the correct font style in Android 4.3-.\n \*/\n\ndfn {\n font-style: italic;\n}\n\n/\*\*\n \* Add the correct background and color in IE 9-.\n \*/\n\nmark {\n background-color: #ff0;\n color: #000;\n}\n\n/\*\*\n \* Add the correct font size in all browsers.\n \*/\n\nsmall {\n font-size: 80%;\n}\n\n/\*\*\n \* Prevent `sub` and `sup` elements from affecting the line height in\n \* all browsers.\n \*/\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded content\n

=====

\*\n\n/\*\*\n \* Add the correct display in IE 9-.\n \*/\n\naudio,\nvideo {\n display: inline-block;\n}\n\n/\*\*\n \* Add the correct display in iOS 4-7.\n \*/\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n/\*\*\n \* Remove the border on images inside links in IE 10-.\n \*/\n\nimg {\n border-style: none;\n}\n\n/\*\*\n \* Hide the overflow in IE.\n \*/\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====

\*\n\n/\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n \*/\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*\n font-size:

100%; /\* 1 \*/ line-height: 1.15; /\* 1 \*/ margin: 0; /\* 2 \*/ } } } Show the overflow in IE. /\* 1. Show the overflow in Edge. \*/ button, input { /\* 1 \*/ overflow: visible; } } } Remove the inheritance of text transform in Edge, Firefox, and IE. /\* 1. Remove the inheritance of text transform in Firefox. \*/ button, select { /\* 1 \*/ text-transform: none; } } } 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4. /\* 2. Correct the inability to style clickable types in iOS and Safari. \*/ button, html [type="button"], /\* 1 \*/ [type="reset"], [type="submit"] { -webkit-appearance: button; /\* 2 \*/ } } } Remove the inner border and padding in Firefox. \*/ button::-moz-focus-inner, [type="button"]::-moz-focus-inner, [type="reset"]::-moz-focus-inner, [type="submit"]::-moz-focus-inner { border-style: none; padding: 0; } } } Restore the focus styles unset by the previous rule. \*/ button:-moz-focusring, [type="button"]:-moz-focusring, [type="reset"]:-moz-focusring, [type="submit"]:-moz-focusring { outline: 1px dotted ButtonText; } } } Correct the padding in Firefox. \*/ fieldset { padding: 0.35em 0.75em 0.625em; } } } 1. Correct the text wrapping in Edge and IE. /\* 2. Correct the color inheritance from `fieldset` elements in IE. /\* 3. Remove the padding so developers are not caught out when they zero out `fieldset` elements in all browsers. \*/ legend { -webkit-box-sizing: border-box; box-sizing: border-box; /\* 1 \*/ color: inherit; /\* 2 \*/ display: table; /\* 1 \*/ max-width: 100%; /\* 1 \*/ padding: 0; /\* 3 \*/ white-space: normal; /\* 1 \*/ } } } 1. Add the correct display in IE 9. /\* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera. \*/ progress { display: inline-block; /\* 1 \*/ vertical-align: baseline; /\* 2 \*/ } } } Remove the default vertical scrollbar in IE. \*/ textarea { overflow: auto; } } } 1. Add the correct box sizing in IE 10. /\* 2. Remove the padding in IE 10. \*/ [type="checkbox"], [type="radio"] { -webkit-box-sizing: border-box; box-sizing: border-box; /\* 1 \*/ padding: 0; /\* 2 \*/ } } } Correct the cursor style of increment and decrement buttons in Chrome. \*/ [type="number"]::-webkit-inner-spin-button, [type="number"]::-webkit-outer-spin-button { height: auto; } } } 1. Correct the odd appearance in Chrome and Safari. /\* 2. Correct the outline style in Safari. \*/ [type="search"] { -webkit-appearance: textfield; /\* 1 \*/ outline-offset: -2px; /\* 2 \*/ } } } Remove the inner padding and cancel buttons in Chrome and Safari on macOS. \*/ [type="search"]::-webkit-search-cancel-button, [type="search"]::-webkit-search-decoration { -webkit-appearance: none; } } } 1. Correct the inability to style clickable types in iOS and Safari. /\* 2. Change font properties to `inherit` in Safari. \*/ ::-webkit-file-upload-button { -webkit-appearance: button; /\* 1 \*/ font: inherit; /\* 2 \*/ } } } Interactive

\*/ } } } Add the correct display in IE 9. /\* 1. Add the correct display in Edge, IE, and Firefox. \*/ details, /\* 1 \*/ menu { display: block; } } } Add the correct display in all browsers. \*/ summary { display: list-item; } } } Scripting

\*/ } } } Add the correct display in IE 9. \*/ canvas { display: inline-block; } } } Add the correct display in IE. \*/ template { display: none; } } } Hidden

\*/ } } } Add the correct display in IE 10. \*/ [hidden] { display: none; } } } , "" , {"version":3,"sources":["/home/ubuntu/ReactThumbSignIn/node\_modules/normalize.css/normalize.css"],"names":[],"mappings":"AAAA,4EAA4E;;AAE5E;gFACgF;;AAEhF;;;GAIG;;AAEH;EACE,kBAaKb,CAAC,OA AO;EAC1B,2BAA2B,CAAC,OAAO;EACnC,+BAA+B,CAAC,OAAO;CACxC;;AAED;gFACgF;;AAEhF;;G

AEG;;AAEH;EACE,UAAU;CACX;;AAED;;GAEG;;AAEH;;;;;EAME,eAAe;CACHB;;AAED;;;GAGG;;AAEH;EACE,eAAe;EACf,iBAaIB;CACIB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;OAE0,OAAO;EACZ,eAAe;CACHB;;AAED;;GAEG;;AAEH;EACE,iBAaIB;CACIB;;AAED;;;GAGG;;AAEH;EACE,gCAAgC;UACxB,wBAAwB,CAAC,OAAO;EACxC,UAAU,CAAC,OAAO;EACIB,kBAaKB,CAAC,OAAO;CAC3B;;AAED;;;GAGG;;AAEH;EACE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,sCAAsC,CAAC,OAAO;CAC/C;;AAED;;;GAGG;;AAEH;EACE,oBAAoB,CAAC,OAAO;EAC5B,2BAA2B,CAAC,OAAO;EACnC,0CAA0C;UAC1C,kCAaKC,CAAC,OAAO;CACnD;;AAED;;GAEG;;AAEH;;EAEe,qBAaQB;CACtB;;AAED;;GAEG;;AAEH;;EAEe,oBAAoB;CACrB;;AAED;;;GAGG;;AAEH;;EAGE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;;GAEG;;AAEH;EACE,uBAaUB;EACvB,YAAY;CACb;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EAEe,eAAe;EACf,eAAe;EACf,mBAaMB;EACnB,yBAaYB;CAC1B;;AAED;EACE,gBAaGB;CACjB;;AAED;EACE,YAAY;CACb;;AAED;gFACgF;;AAEHf;;GAEG;;AAEH;;EAEe,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;EACd,UAAU;CACX;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;;GAEG;;AAEH;EACE,iBAaIB;CACIB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;;;;EAKE,wBAAwB,CAAC,OAAO;EACbC,gBAaGB,CAAC,OAAO;EACxB,kBAaKB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;;GAGG;;AAEH;QACQ,OAAO;EACb,kBAaKB;CACnB;;AAED;;;GAGG;;AAEH;SACS,OAAO;EACd,qBAaQB;CACtB;;AAED;;;GAIG;;AAEH;;;;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;;;;EAIE,mBAaMB;EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;;;;EAIE,+BAA+B;CACHC;;AAED;;GAEG;;AAEH;EACE,+BAA+B;CACHC;;AAED;;;;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAaUB,CAAC,OAAO;EACvC,eAAe,CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAaGB,CAAC,OAAO;EACxB,WAAW,CAAC,OAAO;EACnB,oBAAoB,CAAC,OAAO;CAC7B;;AAED;;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,yBAaYB,CAAC,OAAO;CAC1C;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EAEe,+BAA+B;UACvB,uBAaUB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AAEH;;EAEe,aAAa;CACd;;AAED;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAaQB,CAAC,OAAO;CAC9B;;AAED;;GAEG;;AAEH;;EAEe,yBAaYB;CAC1B;;AAED;;;GAGG;;AAEH;EACE,2BAA2B,CAAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;EAEe,eAAe;CACHB;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;gFACgF;;AAEHf;;GAEG;;AAEH;EACE,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED;gFACgF;;AAEHf;;GAEG;;AAEH;EACE,cAAc;CACf","file":"normalize.css","sourcesContent":["/\*! normalize.css v7.0.0 | MIT License |  
github.com/necolas/normalize.css \*/\n\n/\* Document\n\n=====\n\n\*/\n\n/\* 1. Correct the line height in all browsers.\n\n2. Prevent adjustments of font size after orientation changes in IE on Windows Phone and in iOS.\n\n\*/\n\nhtml {\n line-height: 1.15; /\* 1 \*/\n -ms-text-size-adjust: 100%; /\* 2 \*/\n -webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n\n=====\n\n\*/\n\n/\* Remove the margin in all browsers (opinionated).\n\n\*/\n\nbody {\n margin: 0;\n}\n\n/\* Add the correct display in IE 9-.\n\narticle,\naside,\nfooter,\nheader,\nav,\nsection {\n display: block;\n}\n\n/\* Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.\n\n\*/\n\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping content\n\n=====\n\n\*/\n\n/\* Add the correct display in IE 9-.\n\n1. Add the correct display in IE.\n\n\*/

\*/\n\n/\* 1. Correct the line height in all browsers.\n\n2. Prevent adjustments of font size after orientation changes in IE on Windows Phone and in iOS.\n\n\*/\n\nhtml {\n line-height: 1.15; /\* 1 \*/\n -ms-text-size-adjust: 100%; /\* 2 \*/\n -webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n\n=====\n\n\*/\n\n/\* Remove the margin in all browsers (opinionated).\n\n\*/\n\nbody {\n margin: 0;\n}\n\n/\* Add the correct display in IE 9-.\n\narticle,\naside,\nfooter,\nheader,\nav,\nsection {\n display: block;\n}\n\n/\* Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.\n\n\*/\n\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping content\n\n=====\n\n\*/\n\n/\* Add the correct display in IE 9-.\n\n1. Add the correct display in IE.\n\n\*/

\*\n\nfigcaption,\nfigure,\nmain { /\* 1 \*\n display: block;\n}\n\n\*\*\n \* Add the correct margin in IE 8.\n\*\n\nfigure {\n margin: 1em 40px;\n}\n\n\*\*\n \* 1. Add the correct box sizing in Firefox.\n \* 2. Show the overflow in Edge and IE.\n\*\n\nhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /\* 1 \*\n height: 0; /\* 1 \*\n overflow: visible; /\* 2 \*\n}\n\n\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n\*\n\npre {\n font-family: monospace, monospace; /\* 1 \*\n font-size: 1em; /\* 2 \*\n}\n\n/\* Text-level semantics\n

=====  
\*\n\n\*\*\n \* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in iOS 8+ and Safari 8+.\n\*\n\na {\n background-color: transparent; /\* 1 \*\n -webkit-text-decoration-skip: objects; /\* 2 \*\n}\n\n\*\*\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n\*\n\nabbr[title] {\n border-bottom: none; /\* 1 \*\n text-decoration: underline; /\* 2 \*\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*\n}\n\n\*\*\n \* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n\*\n\nb,\nstrong {\n font-weight: inherit;\n}\n\n\*\*\n \* Add the correct font weight in Chrome, Edge, and Safari.\n\*\n\nb,\nstrong {\n font-weight: bolder;\n}\n\n\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n\*\n\ncode,\nkbd,\nsamp {\n font-family: monospace, monospace; /\* 1 \*\n font-size: 1em; /\* 2 \*\n}\n\n\*\*\n \* Add the correct font style in Android 4.3-.\n\*\n\ni {\n font-style: italic;\n}\n\n\*\*\n \* Add the correct background and color in IE 9-.\n\*\n\nmark {\n background-color: #ff0;\n color: #000;\n}\n\n\*\*\n \* Add the correct font size in all browsers.\n\*\n\nsmall {\n font-size: 80%;\n}\n\n\*\*\n \* Prevent `sub` and `sup` elements from affecting the line height in\n \* all browsers.\n\*\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded content\n

=====  
\*\n\n\*\*\n \* Add the correct display in IE 9-.\n\*\n\naudio,\nvideo {\n display: inline-block;\n}\n\n\*\*\n \* Add the correct display in iOS 4-7.\n\*\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n\*\*\n \* Remove the border on images inside links in IE 10-.\n\*\n\nimg {\n border-style: none;\n}\n\n\*\*\n \* Hide the overflow in IE.\n\*\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\*\n\n\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n\*\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*\n font-size: 100%; /\* 1 \*\n line-height: 1.15; /\* 1 \*\n margin: 0; /\* 2 \*\n}\n\n\*\*\n \* Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n\*\n\nbutton,\ninput {\n /\* 1 \*\n overflow: visible;\n}\n\n\*\*\n \* Remove the inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n\*\n\nbutton,\nselect {\n /\* 1 \*\n text-transform: none;\n}\n\n\*\*\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable types in iOS and Safari.\n\*\n\nbutton,\nhtml [type="button"], /\* 1 \*\n [type="reset"],\n [type="submit"] {\n -webkit-appearance: button; /\* 2 \*\n}\n\n\*\*\n \* Remove the inner border and padding in Firefox.\n\*\n\nbutton::-moz-focus-inner,\n [type="button"]::-moz-focus-inner,\n [type="reset"]::-moz-focus-inner,\n [type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n\*\*\n \* Restore the focus styles unset by the previous rule.\n\*\n\nbutton:-moz-focusing,\n [type="button"]:-moz-focusing,\n [type="reset"]:-moz-focusing,\n [type="submit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n\n\*\*\n \* Correct the padding in Firefox.\n

```

*^\\n\\nfieldset {\\n  padding: 0.35em 0.75em 0.625em;\\n}\\n\\n/**\\n * 1. Correct the text wrapping in Edge and
IE.\\n * 2. Correct the color inheritance from `fieldset` elements in IE.\\n * 3. Remove the padding so developers
are not caught out when they zero out\\n *   `fieldset` elements in all browsers.\\n */^\\n\\nlegend {\\n
-webkit-box-sizing: border-box;\\n      box-sizing: border-box; /* 1 */\\n  color: inherit; /* 2 */\\n  display: table;
/* 1 */\\n  max-width: 100%; /* 1 */\\n  padding: 0; /* 3 */\\n  white-space: normal; /* 1 */\\n}\\n\\n/**\\n * 1. Add
the correct display in IE 9-.\\n * 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\\n
*/^\\n\\nprogress {\\n  display: inline-block; /* 1 */\\n  vertical-align: baseline; /* 2 */\\n}\\n\\n/**\\n * Remove the
default vertical scrollbar in IE.\\n */^\\n\\ntextarea {\\n  overflow: auto;\\n}\\n\\n/**\\n * 1. Add the correct box sizing
in IE 10-.\\n * 2. Remove the padding in IE 10-.\\n */^\\n\\n[type=\\\"checkbox\\\"],\\n[type=\\\"radio\\\"] {\\n
-webkit-box-sizing: border-box;\\n      box-sizing: border-box; /* 1 */\\n  padding: 0; /* 2 */\\n}\\n\\n/**\\n *
Correct the cursor style of increment and decrement buttons in Chrome.\\n
*/^\\n\\n[type=\\\"number\\\"]::-webkit-inner-spin-button,\\n[type=\\\"number\\\"]::-webkit-outer-spin-button {\\n  height:
auto;\\n}\\n\\n/**\\n * 1. Correct the odd appearance in Chrome and Safari.\\n * 2. Correct the outline style in
Safari.\\n */^\\n\\n[type=\\\"search\\\"] {\\n  -webkit-appearance: textfield; /* 1 */\\n  outline-offset: -2px; /* 2
*/\\n}\\n\\n/**\\n * Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\\n
*/^\\n\\n[type=\\\"search\\\"]::-webkit-search-cancel-button,\\n[type=\\\"search\\\"]::-webkit-search-decoration {\\n
-webkit-appearance: none;\\n}\\n\\n/**\\n * 1. Correct the inability to style clickable types in iOS and Safari.\\n * 2.
Change font properties to `inherit` in Safari.\\n */^\\n\\n::-webkit-file-upload-button {\\n  -webkit-appearance:
button; /* 1 */\\n  font: inherit; /* 2 */\\n}\\n\\n/* Interactive\\n

```

```

=====
*^\\n\\n/*\\n * Add the correct display in IE 9-.\\n * 1. Add the correct display in Edge, IE, and Firefox.\\n
*/^\\n\\ndetails, /* 1 */^\\n\\nmenu {\\n  display: block;\\n}\\n\\n/*\\n * Add the correct display in all browsers.\\n
*/^\\n\\nsummary {\\n  display: list-item;\\n}\\n\\n/* Scripting\\n

```

```

=====
*^\\n\\n/**\\n * Add the correct display in IE 9-.\\n */^\\n\\ncanvas {\\n  display: inline-block;\\n}\\n\\n/**\\n * Add the
correct display in IE.\\n */^\\n\\ntemplate {\\n  display: none;\\n}\\n\\n/* Hidden\\n

```

```

=====
*^\\n\\n/**\\n * Add the correct display in IE 10-.\\n */^\\n\\n[hidden] {\\n  display: none;\\n}\\n\\n\"],\"sourceRoot\":\"\"});

```

```

    user = _props.user,

```

```

    user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react__default.a.createElement(

```

```

    user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react__default.a.createElement(

```

```

    user.isLoggedin ? __WEBPACK_IMPORTED_MODULE_0_react__default.a.createElement(

```

```

    user: {

```

```

      isLoggedin: !userInfo.isLoading ? userInfo.data.isLoggedin : ownProps.query.user.isLoggedin,

```

```

* `Indeterminate`, and `Query Indeterminate`.

```

```

* A `Query Indeterminate` linear progress bar is used when you are combining

```

```

* as a query indeterminate progress bar by adding the prop `query={true}` to the

```

```

* component. Until a progress value is given, it will display the query linear

```

```

* progress animation. Afterwards, it will start the determinate animation of where

```

```

    query = _props.query,

```

```

    props = _objectWithoutProperties(_props, ['className', 'progressClassName', 'progressStyle', 'value',

```

```

'query', 'centered']);

```

```

    'md-progress--linear-query': query,

```

- \* region until it is finished loading. It is not possible for the user to alter the value of a progressbar
- \* Boolean if this should be a query indeterminate progress bar.

```
query: _propTypes2.default.bool,
query: false
```

- \* region until it is finished loading. It is not possible for the user to alter the value of a progressbar
- \* The list's z-depth for applying box shadow. This should be a number from 0 to 5.
- \* closing when a list item has been clicked, or the user presses escape.
- \* Removes observer from observers list.
- \* Updates every observer from observers list and notifies them of queued
 

```
// has the "ownerDocument" property from which we can retrieve a
// Return the local global object if it's not possible extract one from
```
- \* Extracts borders size from provided styles.
- \* Extracts paddings sizes from provided styles.
- \* from the corresponding properties of the last observed content rectangle.
- \* instances collected from active resize observations.
- \* `type="submit"`, the `ComposedComponent` is in a form, and the user hits the `enter` key
  - \* The ink can either be created by using the `pageX` and `pageY` from a click/touch event
  - \* use case where `Switches` needed the ink disabled only when using a mouse.
- \* The layover will appear by transitioning from the top left and expand
- \* The layover will appear by transitioning from the top right and expand
- \* The layover will appear by transitioning from the bottom left and expand
- \* The layover will appear by transitioning from the bottom right and expand
- \* The layover will appear by just transitioning downwards from the bottom
- \* This is used for some lists where only a parent contains the icon.
- \* The nested items will be visible once the user clicks on the `ListItem`.
 

```
// We need to check all keys in case some are required but missing from
// fail the render phase where it didn't fail before. So we log it.
    'it must be a function, usually from the `prop-types` package, but received `' + typeof
typeSpecs[typeSpecName] + `.'
```
- \* @param {object} prev prev children as returned from
- \* @param {object} next next children as returned from
 

```
// TODO: when config is {a: 10} and dest is {a: 10} do we raf once and
// changed from 0 to 400 to spring(0) again, the async currentStyle is still
// TODO: when config is {a: 10} and dest is {a: 10} do we raf once and
// changed from 0 to 400 to spring(0) again, the async currentStyle is still
// Array<TransitionPlainStyle>, where each TransitionPlainStyle is of the format
// turn current (interpolating) style from {a, b} into {a?, b, c}
// TODO: key search code
// TODO: when config is {a: 10} and dest is {a: 10} do we raf once and
// TODO: key search code
// that you've unmounted but that's still animating. This is where it lives
// changed from 0 to 400 to spring(0) again, the async currentStyle is still
// this reduces to merging two partially ordered lists (e.g. lists where not
```

```

// merge in keys that the user desires to kill
// a period where rootNode briefly equals null.
// can leave a period where rootNode briefly equals null.
* This is useful when you want to prohibit the user from changing slides.
* This will allow the user to perform the relevant swipe actions with a mouse.
* should user swipe to switch slide.
* component when the shown slide change after a swipe made by the user.
* triggered when the user presses enter anywhere in the form.
* Creates an ink from pageX and pageY coordinates. These values should either come
* from the `changedTouches` or just the base event (if clicked). These coordinates
* are used to position the ink correctly in the container from touch/click point.
* If either value is undefined, an ink will be created from the center of the
* Creates an ink from pageX and pageY coordinates. These values should either come
* from the `changedTouches` or just the base event (if clicked). These coordinates
* are used to position the ink correctly in the container from touch/click point.
* If either value is undefined, an ink will be created from the center of the
* Removes an ink from the container.
* Sets the ink container and the main container from the ref callback. When the component
* Boolean if the layover should fill the height of the viewport from the current calculated `top`. This will just
* iOS does not subtract the soft keyboard from the viewport's size so the list will still extend to the bottom
* This is the position that the children should animate from. It directly ties into
* This is really only helpful in cases where the layover can't calculate things correctly due to
  // The init function can be called again if the user quickly toggles the layover. If that
* @param {Object} el - The element to get a scroll value from.
* where a `false` value will mean it is out of the viewport for that
* The `AccessibleFakeButton` allows the user to tab focus the element, use the
* An optional onClick function to call when the user clicks the
* The ink when coming from the AccessibleFakeInkedButton
* the `children` from each tab, and render them in a swipeable container. However,
* @see https://github.com/oliviertassinari/react-swipeable-views#user-content-swipeableviews-
* @see https://github.com/oliviertassinari/react-swipeable-views#user-content-swipeableviews-
* `label` and `children` from a custom `Tab` component.
* An id for a `TabPanel` that holds the children from this tab. This is required for all y.
* Gets the easing type from the smooth prop within options.
  var from = match.index + (lookbehind ? match[1].length : 0),
  // Move the index i to the element in strarr that is closest to from
  if (from >= p) {
  var from = match.index + lookbehindLength,
    to = from + match.length,
    before = str.slice(0, from),
  // Copy of the full string this token was created from
  'keyword':
  /\b(?:as|async|await|break|case|catch|class|const|continue|debugger|default|delete|do|else|enum|export|extends|fin

```





```

\n          </a>\n          </p>\n          </div>\n          </div>\n          \n          style:\n`.ts-logo-wrapper span{font-weight:500;font-family:Montserrat-Bold;color:#19b2e6}\n          .ts-logo-wrapper
p{font-family:Montserrat-Medium;font-size:12px;color:#1a1a39}`\n    }\n}\n}, function (dom, config) {\n/*\n*
"this" holds the widget scope, from where you can get the the DOM.\n* "dom" param has the module dom
element that has been compiled from \n* the above template\n* "config" param holds the widget config in
which "logo"(module-name) holds\n* the module specific config created above \n* ( ex : playStoreURL
accessed via "config.logo.playStoreURL" )\n*/\n    this.DOM.find("#module-wrapper").append(dom);\n}\n)',
        code: '/*\n* param_1: "tsModal" , the name of the module\n* Param_2: "config"
holds the module constants , \n*\t\t\t\t\t "getElem" should return object with \'elem\'(DOM) template and
\'style\'\n*\n* Param_3: function callback with \'dom\' (compiled template) and
config\n*/\nthumbSignIn.addModule(\'tsModal\', {\n    config: {\n        \'modalTitle\': \'Scan the QR Code\',\n
    },\n    getElem: function (config, url) {\n        return {\n            elem: \n            `<button id="tsModalBtn">Open
Modal</button>\n            <div id="tsModal" class="modal">\n                <div class="modal-content">\n                    <h4
class="text-center">\${config.tsModal.modalTitle}</h4>\n                    <span class="close">&times;</span>\n
<div class="modal-content-wrapper"></div>\n                </div>\n            </div>`, \n            style:\n            `#tsModal{display:none;position:fixed;z-index:1000;\n                left:0;top:0;width:100%;height:100%;\n
overflow:hidden;background-color:rgba(0,0,0,.4)}\n            #tsModal
.modal-content{background-color:#fefefe;margin:10% auto;\n                padding:20px;box-shadow:0 3px 6px
rgba(0,0,0,.16),0 3px 6px rgba(0,0,0,.23);\n                border:1px solid #888;width:450px}\n            #tsModal
.close{color:#aaa;float:right;font-size:28px;font-weight:700}\n            #tsModal .close:focus,\n            #tsModal
.close:hover{color:#000;text-decoration:none;cursor:pointer}`\n        }\n    }\n}\n}, function (dom, config) {\n/*\n*
"this" holds the widget scope, from where you can get the the DOM.\n* "dom" param has the module dom
element that has been compiled from \n* the above template\n* "config" param holds the widget config in
which "tsModal"(module-name) holds\n* the module specific config created above \n* ( ex : modalTitle
accessed via "config.tsModal.modalTitle" )\n*/\n    var widgetObj = this;\n    $(\'body\').append(dom);\n    var
modal = $(\'#tsModal\');\n    modal.find(\'#modal-content-wrapper\').empty().append(this.DOM.detach());\n    $(\'#tsModalBtn\').click(function () {\n        modal.show();\n        widgetObj.open();\n    });\n    $(\'#tsModal
.close\').click(function () {\n        widgetObj.close();\n        modal.hide();\n    });\n\n    window.onclick =
function (event) {\n        if (event.target == modal[0]) {\n            widgetObj.close();\n            modal.hide();\n
        }\n    }\n}\n}\n}',

```

'Called by the widget to get the QR code for authenticating a user.'

'Provides the list of the registered devices for that user.'

'user-agent'

```
': "% Your user agent%"
```

'Query String'

```
': "%Username or such unique id of the user%"
```

'user-agent'

```
' : "% Your user agent%"'
```

'Query String'

It is important to note that all calls to the ThumbSignIn SaaS API must be HMAC signed using the application id and the secret key. The secret key should be downloaded from the app dashboard and stored on your server. This will be used to sign the requests made from your server to the ThumbSignIn SaaS

server.'

'Transaction created and waiting for user action'

'Started user action like scanned QR code \'failureReason\': This will contain text value which describe reason of transaction failure, this field can have values listed below'

'User has already registered device for this application,'

'will happen when the user tries to enable the same device again'

'User tries to login without registering device'

'Transaction timed out without user\'s action'

'This will happen in events like user didn\'t add fingerprints and not enabled pin/pattern locking'

'User click on cancel from ThumbSignin App'

```
code: 'import axios from \'axios\';\nimport HmacSigner from \'../hmac/sign\';\n\nlet timer = 180,\n  giveProperResponse = false;\n\nconst tsServer = "https://api.thumbsignin.com";\nconst tsServerPath = tsServer + "/ts/secure";\n\n// Insert your application Id and Secret key below\nconst tsCredential = {\n  accessKeyId: "<<Your Application Id>>\",\n  secretKey: "<<Your Secret Key>>\",\n};\n\n// Handle GET requests to register and Authenticate\nrouter.get(\'/tsAuth/:action(register|authenticate)\', (req, res) => {\n  let session = req.session;\n  let action = req.params.action;\n\n  // If trying to register when the user is not logged in\n  if (action === \'register\' && !session.loginInfo) {\n    res.status(401).json({ status: "401", message: "Unauthorized" });\n    return\n  }\n\n  let request = {\n    method: \'get\',\n    headers: {}\n  };\n\n  // Handle a registration request\n  // Get the username from a previously saved login session\n  if (action === \'register\') {\n    request.url = tsServerPath + \'/register?userId=\' + session.loginInfo.username;\n  } else {\n    let queryString = session.loginInfo && session.loginInfo.username ? \'?userId=\' + session.loginInfo.username : \';\n    request.url = tsServerPath + \'/authenticate\' + queryString;\n  }\n\n  // Sign the request first\n  HmacSigner.sign(request, tsCredential);\n\n  // And then send it to api.thumbsignin.com\n  axios(request).then((response) => {\n    res.status(200).json(response.data)\n  }).catch((error) => {\n    res.status(401).json({\n      status: "SERVER_ERROR",\n      message: error.toString()\n    });\n  });\n\n  // If authentication is successful, alter the session to log the user in\n\n  function loginAndSendSuccess(req, res, data) {\n    let request = {\n      method: \'get\',\n      url: tsServerPath + \'/getUser\' + data.transactionId,\n      headers: {}\n    };\n\n    HmacSigner.sign(request, tsCredential);\n    axios(request).then((response) => {\n      Account.findOne({ username: response.data.userId }, (err, account) => {\n        if (err || !account) {\n          res.status(401).json({\n            status: "INTERNAL_ERROR",\n            message: err ? err : "Unable to login"\n          });\n        } else {\n          // ALTER SESSION\n          if (!account.fingerprint) {\n            account.fingerprint = true;\n            account.save()\n          }\n          let session = req.session;\n          session.loginInfo = account.sessionInfo();\n          data.redirectUrl = "/";\n          res.status(200).json(data);\n        }\n      }).catch((error) => {\n        res.status(401).json({\n          status: "SERVER_ERROR",\n          message: error.toString()\n        });\n      });\n\n      // Handle GET request for checking transaction status\n      router.get(\'/txnStatus/:id\', (req, res) => {\n        let q = req.query.cancelled?"cancelled=true":'';\n        let request = {\n          method: \'get\',\n          url: tsServerPath + \'/txn-status\' + req.params.id + q,\n          headers: {}\n        };\n        HmacSigner.sign(request, tsCredential);\n        axios(request).then((response) => {\n          if (response.data.status === \'COMPLETED_SUCCESSFUL\') {\n            loginAndSendSuccess(req, res, response.data)\n          } else {\n            res.status(200).json(response.data)\n          }\n        }).catch((error) => {\n          res.status(401).json({\n            status: "SERVER_ERROR",\n            message: error.toString()\n          })\n        })\n      })\n    })\n  })\n})
```

```
});\n}));',
```

24-[https://stage.thumbsignin.com/assets/docs\\_ios.chunk.js](https://stage.thumbsignin.com/assets/docs_ios.chunk.js)

Other Information: \* Gets the easing type from the smooth prop within options.

```
var from = match.index + (lookbehind ? match[1].length : 0),
// Move the index i to the element in strarr that is closest to from
if (from >= p) {
var from = match.index + lookbehindLength,
to = from + match.length,
before = str.slice(0, from),
// Copy of the full string this token was created from
'keyword':
/\b(?:as|async|await|break|case|catch|class|const|continue|debugger|default|delete|do|else|enum|export|extends|finally|for|from|function|get|if|implements|import|in|instanceof|interface|let|new|null|of|package|private|protected|public|return|set|static|super|switch|this|throw|try|typeof|var|void|while|with|yield)\b/,
//import PropTypes from 'prop-types';
/** Detect free variable `global` from Node.js. */
// accelerating from zero velocity
// accelerating from zero velocity
// accelerating from zero velocity
// accelerating from zero velocity
// Remove `parentBindings` from props
'Download the iOS/Android ThumbSignin SDK from your dashboard.'
'From the ThumbSignIn Dashboard, download ',
'Select ',
' and select ',
'From the ThumbSignIn Dashboard, inside a newly created application, Click on iOS
section.'
'method to check whether a user registration is available.'
'This function is to register the user for passwordless authentication
mechanism using ThumbSignIn.This function can be triggered after legacy login flow or via a setting once user
logged in the app (For eg: After Username & Password login).'
': identifier of the user (',
': userIdentifier can be an internal mapping to the user provided to
ThumbSignIn, not necessarily be the actual username or user id in your platform)'
code: 'NSString *status; /*Transaction status of the operation*/\nNSString
*userId; /*User identity*/\nNSString *transactionId; /*The Transaction ID*/',
'Use this model object to retrieve the transaction details of the registered
user.',
'to display the corresponding error message to the user.'
'This function is to authenticate the user using TouchID via ThumbSignIn.
Only successfully registered user can use this Authenticator.'
'This function is to authenticate the transaction for a user.'
```

' : description of the transaction that needs to be displayed to the user during TouchID prompt.'

'This function is used to deregister the user from ThumbSignIn server. After the successful deregistration, the user will no longer be able to use the Thumbsignin Authenticator unless he registers again.'

' : QRContent scanned from the QR code shown on the vendor's website'

'When a user opens a ThumbSignIn enabled web page in the mobile browser on the same phone as the one that has the authenticator app, there is obviously no way to scan the QR code using the camera. Mobile App Deep Linking enables strong authentication in this scenario by invoking the authenticator app when the user taps on a link on the web page.'

' : the dictionary received from branch.io'

' : url you receive from -(BOOL)application:(UIApplication \*)app openURL delegate function'

'Use the Deregistration API functionality available in the Mobile integration section above to deregister the user.'

'This section should answer \u201C Where in the iOS app should we add the code?\u201D. Developers could invoke at instances where passwordless mechanisms are required using the above mentioned 4 methods. They could handle the success/failure scenarios in respective callbacks.'

' API to register users at any point after legacy login flow (existing login process of the application e.g. username/password)'

' API from the legacy login screen by displaying it as the alternative option to log in. The authentication API should be triggered only after the user has successfully completed the registration step'

' - Enable the deregister functionality for the user if he/she wants to opt out of passwordless login. This API can be made available in settings of the App.'

```
code: 'typedef NS_ENUM(NSInteger, TSErrorsEnum)\n{\n    /*UAF protocol failure*\n    TS_TECHNICAL_ERROR=8001,\n    /* User cancelled the transaction when touchID is prompted*\n    TS_USER_CANCELLED=8002,\n    /*TouchID is not available or setup*\n    TS_NO_SUITABLE_AUTHENTICATOR=8003,\n    /*If the APPID configured in the plist failed during\n    configuration check with the ThumbSignIn server*\n    TS_APPID_VALIDATION_FAILED=8004,\n    /*If\n    the device is jailbroken*\n    TS_DEVICE_JAILBROKEN=8005,\n    /*If the operation failed due to untrusted\n    bundle identifier. \n    The bundle identifier configured in the ThumbSignIn Dashboard does \n    not match\n    with the one in the project*\n    TSERROR_UNTRUSTED_FACETID=8006,\n    /*IF the SDK version is\n    unsupported*\n    TSERROR_UNSUPPORTED_VERSION=8007,\n    /*If the operation failed due to some\n    unknown reason*\n    TSERROR_UNKNOWN=8008,\n    /*Internet connectivity error*\n    TSERROR_NETWORK=8009,\n    TSERROR_REGISTRATION_NOT_AVAILABLE=8010,\n    TSERROR_SAME_USER_ALREADY_REGISTERED=8011,\n    TSERROR_INVALID_ERROR_QRCODE=8012,\n    TSERROR_TIMED_OUT=8013,\n    /*Default\n    Enum*\n    TSERROR_NULL=8999\n}', __source: {
```

```
    query: '{\n        user {\n            isLogedin\n        } \n    }'
```

```
    { query: data, __source: {
```

```
        // this implementation is not 100% perfect for weird media query combinations
```

```
// Adapted from convert-source-map (MIT)
```

```
* // Remove it from the DOM
```

```

// bind timers to global for call from export context
// Thrash, waste and sodomy: IE GC bug
// IE 8- don't enum bug keys
err = new Error('You provided a ` ` + propFullNameSafe + ` ` + location + ` ` to the ` ` + componentNameSafe +
` that was ` + (not within the range from ` + min + ` ` - ` + max + ` `.` + propFullNameSafe + ` `: ` + value + `.`));
// Don't enum bug & hidden keys
// getting tag from 19.1.3.6 Object.prototype.toString()
// callbacks from appending listeners
return fetch('/api/user').then(function (response) {
return fetch('/api/user', { method: "POST", body: userInfo }).then(function (response) {
// cached from whatever global is present so that test runners that stub it
// import { Provider } from '../Modal'
query: __WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.isRequired
exports.push([module.i, "/*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css */\n\n/*
Document\n
=====
*/\n\n/*\n * 1. Correct the line height in all browsers.\n * 2. Prevent adjustments of font size after orientation
changes in\n * IE on Windows Phone and in iOS.\n */\n\nhtml {\n line-height: 1.15; /* 1 */\n
-ms-text-size-adjust: 100%; /* 2 */\n -webkit-text-size-adjust: 100%; /* 2 */\n}\n\n/* Sections\n
=====
*/\n\n/*\n * Remove the margin in all browsers (opinionated).\n */\n\nbody {\n margin: 0;\n}\n\n/*\n * Add
the correct display in IE 9-.\n */\n\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display:
block;\n}\n\n/*\n * Correct the font size and margin on `h1` elements within `section` and\n * `article`
contexts in Chrome, Firefox, and Safari.\n */\n\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/* Grouping
content\n
=====
*/\n\n/*\n * Add the correct display in IE 9-.\n * 1. Add the correct display in IE.\n
*/\n\nfigcaption,\nfigure,\nmain { /* 1 */\n display: block;\n}\n\n/*\n * Add the correct margin in IE 8.\n
*/\n\nfigure {\n margin: 1em 40px;\n}\n\n/*\n * 1. Add the correct box sizing in Firefox.\n * 2. Show the
overflow in Edge and IE.\n */\n\nhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /* 1
*/\n height: 0; /* 1 */\n overflow: visible; /* 2 */\n}\n\n/*\n * 1. Correct the inheritance and scaling of font
size in all browsers.\n * 2. Correct the odd `em` font sizing in all browsers.\n */\n\npre {\n font-family:
monospace, monospace; /* 1 */\n font-size: 1em; /* 2 */\n}\n\n/* Text-level semantics\n
=====
*/\n\n/*\n * 1. Remove the gray background on active links in IE 10.\n * 2. Remove gaps in links underline in
iOS 8+ and Safari 8+.\n */\n\na {\n background-color: transparent; /* 1 */\n -webkit-text-decoration-skip:
objects; /* 2 */\n}\n\n/*\n * 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n * 2. Add the
correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n */\n\nabbr[title] {\n border-bottom: none; /*
1 */\n text-decoration: underline; /* 2 */\n -webkit-text-decoration: underline dotted;\n text-decoration:
underline dotted; /* 2 */\n}\n\n/*\n * Prevent the duplicate application of `bolder` by the next rule in Safari
6.\n */\n\nb,\nstrong {\n font-weight: inherit;\n}\n\n/*\n * Add the correct font weight in Chrome, Edge, and
Safari.\n */\n\nb,\nstrong {\n font-weight: bolder;\n}\n\n/*\n * 1. Correct the inheritance and scaling of font
size in all browsers.\n * 2. Correct the odd `em` font sizing in all browsers.\n */\n\ncode,\nkbd,\nsamp {\n

```

font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\*\n \* Add the correct font style in  
Android 4.3-.\n \*/\n\nndfn {\n font-style: italic;\n}\n\n/\*\n \* Add the correct background and color in IE 9-.\n \*/\n\nmark {\n background-color: #fff;\n color: #000;\n}\n\n/\*\n \* Add the correct font size in all  
browsers.\n \*/\n\nsmall {\n font-size: 80%;\n}\n\n/\*\n \* Prevent `sub` and `sup` elements from affecting the  
line height in\n \* all browsers.\n \*/\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded  
content\n

=====  
\*\n\n/\*\n \* Add the correct display in IE 9-.\n \*/\n\naudio,\nvideo {\n display: inline-block;\n}\n\n/\*\n \* Add the correct display in iOS 4-7.\n \*/\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n/\*\n \* Remove the border on images inside links in IE 10-.\n \*/\n\nimg {\n border-style: none;\n}\n\n/\*\n \* Hide the  
overflow in IE.\n \*/\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\*\n\n/\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and  
Safari.\n \*/\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*/\n font-size:  
100%; /\* 1 \*/\n line-height: 1.15; /\* 1 \*/\n margin: 0; /\* 2 \*/\n}\n\n/\*\n \* Show the overflow in IE.\n \* 1.  
Show the overflow in Edge.\n \*/\n\nbutton,\ninput { /\* 1 \*/\n overflow: visible;\n}\n\n/\*\n \* Remove the  
inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in  
Firefox.\n \*/\n\nbutton,\nselect { /\* 1 \*/\n text-transform: none;\n}\n\n/\*\n \* 1. Prevent a WebKit bug where  
(2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable  
types in iOS and Safari.\n \*/\n\nbutton,\nhtml [type="button"], /\* 1 \*/\n[type="reset"],\n[type="submit"] {\n -webkit-appearance: button; /\* 2 \*/\n}\n\n/\*\n \* Remove the inner border and padding in Firefox.\n \*/\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[ty  
pe="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n/\*\n \* Restore the focus styles  
unset by the previous rule.\n \*/\n\nbutton:-moz-focusing,\n[type="button"]:-moz-focusing,\n[type="reset"]:-moz-focusing,\n[ty  
pe="submit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n\n/\*\n \* Correct the padding in Firefox.\n \*/\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n/\*\n \* 1. Correct the text wrapping in Edge and  
IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers  
are not caught out when they zero out\n \* `fieldset` elements in all browsers.\n \*/\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n color: inherit; /\* 2 \*/\n display: table;  
/\* 1 \*/\n max-width: 100%; /\* 1 \*/\n padding: 0; /\* 3 \*/\n white-space: normal; /\* 1 \*/\n}\n\n/\*\n \* Add  
the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*/\n\nprogress {\n display: inline-block; /\* 1 \*/\n vertical-align: baseline; /\* 2 \*/\n}\n\n/\*\n \* Remove the  
default vertical scrollbar in IE.\n \*/\n\ntextarea {\n overflow: auto;\n}\n\n/\*\n \* 1. Add the correct box sizing  
in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*/\n\n[type="checkbox"],\n[type="radio"] {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n padding: 0; /\* 2 \*/\n}\n\n/\*\n \* Correct the cursor style of increment and decrement buttons in Chrome.\n \*/\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n height:  
auto;\n}\n\n/\*\n \* 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in  
Safari.\n \*/\n\n[type="search"] {\n -webkit-appearance: textfield; /\* 1 \*/\n outline-offset: -2px; /\* 2  
\*\n \*/\n}\n\n/\*\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n \*/\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n

-webkit-appearance: none;\n}\n\n/\*\n \* 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2. Change font properties to `inherit` in Safari.\n \*/\n\n:-webkit-file-upload-button {\n -webkit-appearance: button; /\* 1 \*/\n font: inherit; /\* 2 \*/\n}\n\n/\* Interactive\n

=====  
\*\n\n/\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in Edge, IE, and Firefox.\n \* 2. Add the correct display in all browsers.\n \*/\n\nsummary {\n display: list-item;\n}\n\n/\* Scripting\n

=====  
\*\n\n/\*\n \* Add the correct display in IE 9-.\n \*/\n\nncanvas {\n display: inline-block;\n}\n\n/\*\n \* Add the correct display in IE.\n \*/\n\ntemplate {\n display: none;\n}\n\n/\* Hidden\n

=====  
\*\n\n/\*\n \* Add the correct display in IE 10-.\n \*/\n\n[hidden] {\n display: none;\n}\n\n", "",  
{ "version":3,"sources":["/home/ubuntu/ReactThumbSignIn/node\_modules/normalize.css/normalize.css"],"names":[],"mappings":"AAAA,4EAA4E;;AAE5E:gFACgF;;AAEhF;;;GAIG;;AAEH;EACE,kBAaAkB,CAAC,OA  
AO;EAC1B,2BAA2B,CAAC,OAAO;EACnC,+BAA+B,CAAC,OAAO;CACxC;;AAED:gFACgF;;AAEhF;;G  
AEG;;AAEH;EACE,UAAU;CACX;;AAED;;GAEG;;AAEH;;;EAME,eAAe;CACHB;;AAED;;GAGG;;AAE  
H;EACE,eAAe;EACf,iBAaIB;CACIB;;AAED:gFACgF;;AAEhF;;GAGG;;AAEH;;OAE0,OAAO;EACZ,eA  
Ae;CACHB;;AAED;;GAEG;;AAEH;EACE,iBAaIB;CACIB;;AAED;;GAGG;;AAEH;EACE,gCAAgC;UACx  
B,wBAawB,CAAC,OAAO;EACxC,UAAU,CAAC,OAAO;EAC1B,kBAaAkB,CAAC,OAAO;CAC3B;;AAED;;  
;GAGG;;AAEH;EACE,kCAaKc,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED:gFACgF;;AA  
EhF;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,sCAAsC,CAAC,OAAO;CAC/C;;AAED;;GAG  
G;;AAEH;EACE,oBAaOB,CAAC,OAAO;EAC5B,2BAA2B,CAAC,OAAO;EACnC,0CAA0C;UAC1C,kCAA  
kC,CAAC,OAAO;CACnD;;AAED;;GAEG;;AAEH;;EAEe,qBAaQB;CACtB;;AAED;;GAEG;;AAEH;;EAEe,  
oBAaOB;CACrB;;AAED;;GAGG;;AAEH;;EAGE,kCAaKc,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;C  
ACxB;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;;GAEG;;AAEH;EACE,uBAaUB;EACvB,Y  
AAY;CACb;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;GAGG;;AAEH;;EAEe,eAAe;EACf,eAA  
e;EACf,mBAaMB;EACnB,yBAaYB;CAC1B;;AAED;EACE,gBAaGB;CACjB;;AAED;EACE,YAAY;CACb;;  
AAED:gFACgF;;AAEhF;;GAEG;;AAEH;;EAEe,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;EA  
Cd,UAAU;CACX;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;;GAEG;;AAEH;EACE,iBAaIB  
;CACIB;;AAED:gFACgF;;AAEhF;;GAGG;;AAEH;;;EAKE,wBAawB,CAAC,OAAO;EACHC,gBAaGB,CA  
AC,OAAO;EACxB,kBAaAkB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;GAGG;;AAEH  
;QACQ,OAAO;EACb,kBAaAkB;CACnB;;AAED;;GAGG;;AAEH;SACS,OAAO;EACd,qBAaQB;CACtB;;A  
AED;;;GAIG;;AAEH;;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;;EAIE,mBAaMB;  
EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;;EAIE,+BAA+B;CACHC;;AAED;;GAEG;;AAEH;EACE,+  
BAA+B;CACHC;;AAED;;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAaUB,CAAC,OAAO;EACvC,eAAe,  
CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAaGB,CAAC,OAAO;EACxB,WAAW,CAAC,OAA  
O;EACnB,oBAaOB,CAAC,OAAO;CAC7B;;AAED;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,  
yBAaYB,CAAC,OAAO;CACIC;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;GAGG;;AAEH;;EA  
EE,+BAA+B;UACvB,uBAaUB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AA  
EH;;EAEe,aAAa;CACd;;AAED;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAaQB,CAAC,O  
AAO;CAC9B;;AAED;;GAEG;;AAEH;;EAEe,yBAaYB;CAC1B;;AAED;;GAGG;;AAEH;EACE,2BAA2B,C  
AAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED:gFACgF;;AAEhF;;GAGG;;AAEH;;EAEe,eAAe;  
CACHB;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED:gFACgF;;AAEhF;;GAEG;;AAEH;EACE,



sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED;gFACgF;;AAEhF;;GAEG;;AAEH;EAC  
E,cAAc;CACf","file":"normalize.css","sourcesContent":["/\*! normalize.css v7.0.0 | MIT License |  
github.com/necolas/normalize.css \*/\n\n/\* Document\n

=====  
\*\n\n/\*\*\n \* 1. Correct the line height in all browsers.\n \* 2. Prevent adjustments of font size after orientation  
changes in\n \* IE on Windows Phone and in iOS.\n \*/\nhtml {\n line-height: 1.15; /\* 1 \*/\n -ms-text-size-adjust: 100%; /\* 2 \*/\n -webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n

=====  
\*\n\n/\*\*\n \* Remove the margin in all browsers (opinionated).\n \*/\nbody {\n margin: 0;\n}\n\n/\*\*\n \* Add the correct display in IE 9-.\n \*/\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display:  
block;\n}\n\n/\*\*\n \* Correct the font size and margin on `h1` elements within `section` and `article`  
contexts in Chrome, Firefox, and Safari.\n \*/\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping  
content\n

=====  
\*\n\n/\*\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in IE.\n \*/\nfigcaption,\nfigure,\nmain { /\* 1 \*/\n display: block;\n}\n\n/\*\*\n \* Add the correct margin in IE 8.\n \*/\nfigure {\n margin: 1em 40px;\n}\n\n/\*\*\n \* 1. Add the correct box sizing in Firefox.\n \* 2. Show the  
overflow in Edge and IE.\n \*/\nhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /\* 1 \*/\n height: 0; /\* 1 \*/\n overflow: visible; /\* 2 \*/\n}\n\n/\*\*\n \* 1. Correct the inheritance and scaling of font  
size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\npre {\n font-family:  
monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\* Text-level semantics\n

=====  
\*\n\n/\*\*\n \* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in  
iOS 8+ and Safari 8+.\n \*/\na {\n background-color: transparent; /\* 1 \*/\n -webkit-text-decoration-skip:  
objects; /\* 2 \*/\n}\n\n/\*\*\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the  
correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*/\nabbr[title] {\n border-bottom: none; /\*  
1 \*/\n text-decoration: underline; /\* 2 \*/\n -webkit-text-decoration: underline dotted;\n text-decoration:  
underline dotted; /\* 2 \*/\n}\n\n/\*\*\n \* Prevent the duplicate application of `bolder` by the next rule in Safari  
6.\n \*/\nb,\nstrong {\n font-weight: inherit;\n}\n\n/\*\*\n \* Add the correct font weight in Chrome, Edge, and  
Safari.\n \*/\nb,\nstrong {\n font-weight: bolder;\n}\n\n/\*\*\n \* 1. Correct the inheritance and scaling of font  
size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\ncode,\nkbd,\nsamp {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\*\*\n \* Add the correct font style in  
Android 4.3-.\n \*/\ndfn {\n font-style: italic;\n}\n\n/\*\*\n \* Add the correct background and color in IE 9-.\n \*/\nmark {\n background-color: #ff0;\n color: #000;\n}\n\n/\*\*\n \* Add the correct font size in all  
browsers.\n \*/\nsmall {\n font-size: 80%;\n}\n\n/\*\*\n \* Prevent `sub` and `sup` elements from affecting the  
line height in\n \* all browsers.\n \*/\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded  
content\n

=====  
\*\n\n/\*\*\n \* Add the correct display in IE 9-.\n \*/\naudio,\nvideo {\n display: inline-block;\n}\n\n/\*\*\n \* Add the correct display in iOS 4-7.\n \*/\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n/\*\*\n \* Remove the border on images inside links in IE 10-.\n \*/\nimg {\n border-style: none;\n}\n\n/\*\*\n \* Hide the  
overflow in IE.\n \*/\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n



```

    user = _props.user,
    user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
    user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
    user.isLoggedin ? __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
user: {
    isLoggedin: !userInfo.isLoading ? userInfo.data.isLoggedin : ownProps.query.user.isLoggedin,
* `Indeterminate`, and `Query Indeterminate`.
* A `Query Indeterminate` linear progress bar is used when you are combining
* as a query indeterminate progress bar by adding the prop `query={true}` to the
* component. Until a progress value is given, it will display the query linear
* progress animation. Afterwards, it will start the determinate animation of where
    query = _props.query,
    props = _objectWithoutProperties(_props, ['className', 'progressClassName', 'progressStyle', 'value',
'query', 'centered']);
    'md-progress--linear-query': query,
* region until it is finished loading. It is not possible for the user to alter the value of a progressbar
* Boolean if this should be a query indeterminate progress bar.
query: _propTypes2.default.bool,
query: false
* region until it is finished loading. It is not possible for the user to alter the value of a progressbar

```

25-[https://stage.thumbsignin.com/assets/docs\\_azure.chunk.js](https://stage.thumbsignin.com/assets/docs_azure.chunk.js)

Other Information: \* Gets the easing type from the smooth prop within options.

```

    var from = match.index + (lookbehind ? match[1].length : 0),
    // Move the index i to the element in strarr that is closest to from
    if (from >= p) {
    var from = match.index + lookbehindLength,
        to = from + match.length,
        before = str.slice(0, from),
    // Copy of the full string this token was created from
    'keyword':
    /\b(?:as|async|await|break|case|catch|class|const|continue|debugger|default|delete|do|else|enum|export|extends|fin
ally|for|from|function|get|if|implements|import|in|instanceof|interface|let|new|null|of|package|private|protected|pu
blic|return|set|static|super|switch|this|throw|try|typeof|var|void|while|with|yield)\b/,
    //import PropTypes from 'prop-types';
    /** Detect free variable `global` from Node.js. */
    // accelerating from zero velocity
    // accelerating from zero velocity
    // accelerating from zero velocity
    // accelerating from zero velocity
    // Remove `parentBindings` from props
    '(From TS)'
    'Make calls to Azure for getting access token, user profiles.'

```

'Accept calls from the client app and forward to Connector App'

'The client application already uses the Azure AD services for user authentication.'

'In order to perform & receive the status of Registration & Authentication from ThumbsignIn server, the backend should expose APIs to the client widget.'

'Backend also should take care of talking with Azure AD for getting the `access token` and API calls to fetching the user profiles during successful authentication from ThumbsignIn server.'

'Download the code from '

```
query: '{\n    user {\n        isLogedin\n    } \n    }'\n{ query: data, __source: {
```

// this implementation is not 100% perfect for weird media query combinations

// Adapted from convert-source-map (MIT)

\* // Remove it from the DOM

// bind timers to global for call from export context

// Thrash, waste and sodomy: IE GC bug

// IE 8- don't enum bug keys

```
err = new Error('You provided a `'+ propFullNameSafe + '` to the '+ componentNameSafe +  
' that was ' + (not within the range from `'+ min + '` - `'+ max + '`.' + propFullNameSafe + `': ' + value + '));
```

// Don't enum bug & hidden keys

// getting tag from 19.1.3.6 Object.prototype.toString()

// callbacks from appending listeners

```
return fetch('/api/user').then(function (response) {
```

```
return fetch('/api/user', { method: "POST", body: userInfo }).then(function (response) {
```

// cached from whatever global is present so that test runners that stub it

// import { Provider } from '../Modal'

```
query: __WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.isRequired
```

```
exports.push([module.i, "/*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css */\n\n/*
```

```
Document\n
```

```
*/\n\n/* 1. Correct the line height in all browsers.\n * 2. Prevent adjustments of font size after orientation changes in\n * IE on Windows Phone and in iOS.\n */\nhtml {\n  line-height: 1.15; /* 1 */\n  -ms-text-size-adjust: 100%; /* 2 */\n  -webkit-text-size-adjust: 100%; /* 2 */\n}\n\n/* Sections\n
```

```
*/\n\n/* Remove the margin in all browsers (opinionated).\n */\nbody {\n  margin: 0;\n}\n\n/* Add the correct display in IE 9-.\n */\narticle,\naside,\nfooter,\nheader,\nav,\nsection {\n  display: block;\n}\n\n/* Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.\n */\nh1 {\n  font-size: 2em;\n  margin: 0.67em 0;\n}\n\n/* Grouping content\n
```

```
*/\n\n/* Add the correct display in IE 9-.\n * 1. Add the correct display in IE.\n
```

```
*/\nfigure,\nmain { /* 1 */\n  display: block;\n}\n\n/* Add the correct margin in IE 8.\n
```

```
*/\nfigure {\n  margin: 1em 40px;\n}\n\n/* 1. Add the correct box sizing in Firefox.\n * 2. Show the overflow in Edge and IE.\n */\nhr {\n  -webkit-box-sizing: content-box;\n  box-sizing: content-box; /* 1
```

```
*/\n  height: 0; /* 1 */\n  overflow: visible; /* 2 */\n}\n\n/* 1. Correct the inheritance and scaling of font
```

size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\npre {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\* Text-level semantics\n

=====  
\*\n\n\*\*\n \* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in iOS 8+ and Safari 8+.\n \*/\n\na {\n background-color: transparent; /\* 1 \*/\n -webkit-text-decoration-skip: objects; /\* 2 \*/\n}\n\n\*\*\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*/\n\nabbr[title] {\n border-bottom: none; /\* 1 \*/\n text-decoration: underline; /\* 2 \*/\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*/\n}\n\n\*\*\n \* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n \*/\n\nb,\nstrong {\n font-weight: inherit;\n}\n\n\*\*\n \* Add the correct font weight in Chrome, Edge, and Safari.\n \*/\n\nb,\nstrong {\n font-weight: bolder;\n}\n\n\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\ncode,\nkbd,\nsamp {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n\*\*\n \* Add the correct font style in Android 4.3-.\n \*/\n\ni,\ndfn {\n font-style: italic;\n}\n\n\*\*\n \* Add the correct background and color in IE 9-.\n \*/\n\nmark {\n background-color: #ff0;\n color: #000;\n}\n\n\*\*\n \* Add the correct font size in all browsers.\n \*/\n\nsmall {\n font-size: 80%;\n}\n\n\*\*\n \* Prevent `sub` and `sup` elements from affecting the line height in\n \* all browsers.\n \*/\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded content\n

=====  
\*\n\n\*\*\n \* Add the correct display in IE 9-.\n \*/\n\naudio,\nvideo {\n display: inline-block;\n}\n\n\*\*\n \* Add the correct display in iOS 4-7.\n \*/\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n\*\*\n \* Remove the border on images inside links in IE 10-.\n \*/\n\nimg {\n border-style: none;\n}\n\n\*\*\n \* Hide the overflow in IE.\n \*/\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\*\n\n\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n \*/\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*/\n font-size: 100%; /\* 1 \*/\n line-height: 1.15; /\* 1 \*/\n margin: 0; /\* 2 \*/\n}\n\n\*\*\n \* Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n \*/\n\nbutton,\ninput {\n /\* 1 \*/\n overflow: visible;\n}\n\n\*\*\n \* Remove the inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n \*/\n\nbutton,\nselect {\n /\* 1 \*/\n text-transform: none;\n}\n\n\*\*\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable types in iOS and Safari.\n \*/\n\nbutton,\nhtml [type="button"], /\* 1 \*/\n[type="reset"],\n[type="submit"] {\n -webkit-appearance: button; /\* 2 \*/\n}\n\n\*\*\n \* Remove the inner border and padding in Firefox.\n \*/\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n\*\*\n \* Restore the focus styles unset by the previous rule.\n \*/\n\nbutton:-moz-focusing,\n[type="button"]:-moz-focusing,\n[type="reset"]:-moz-focusing,\n[type="submit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n\n\*\*\n \* Correct the padding in Firefox.\n \*/\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n\*\*\n \* 1. Correct the text wrapping in Edge and IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers are not caught out when they zero out\n \* `fieldset` elements in all browsers.\n \*/\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n color: inherit; /\* 2 \*/\n display: table;\n

/\* 1 \*/\n max-width: 100%; /\* 1 \*/\n padding: 0; /\* 3 \*/\n white-space: normal; /\* 1 \*/\n}\n\n/\*\*\n \* 1. Add the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*/\n\nprogress {\n display: inline-block; /\* 1 \*/\n vertical-align: baseline; /\* 2 \*/\n}\n\n/\*\*\n \* Remove the default vertical scrollbar in IE.\n \*/\n\ntextarea {\n overflow: auto;\n}\n\n/\*\*\n \* 1. Add the correct box sizing in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*/\n\n[type=\\"checkbox\"],\n[type=\\"radio\"] {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n padding: 0; /\* 2 \*/\n}\n\n/\*\*\n \* Correct the cursor style of increment and decrement buttons in Chrome.\n \*/\n\n[type=\\"number\"]::-webkit-inner-spin-button,\n[type=\\"number\"]::-webkit-outer-spin-button {\n height: auto;\n}\n\n/\*\*\n \* 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in Safari.\n \*/\n\n[type=\\"search\"] {\n -webkit-appearance: textfield; /\* 1 \*/\n outline-offset: -2px; /\* 2 \*/\n}\n\n/\*\*\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n \*/\n\n[type=\\"search\"]::-webkit-search-cancel-button,\n[type=\\"search\"]::-webkit-search-decoration {\n -webkit-appearance: none;\n}\n\n/\*\*\n \* 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2. Change font properties to `inherit` in Safari.\n \*/\n\n::-webkit-file-upload-button {\n -webkit-appearance: button; /\* 1 \*/\n font: inherit; /\* 2 \*/\n}\n\n/\* Interactive\n

\*/\n\n/\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in Edge, IE, and Firefox.\n \*/\n\ndetails, /\* 1 \*/\nmenu {\n display: block;\n}\n\n/\*\n \* Add the correct display in all browsers.\n \*/\n\nsummary {\n display: list-item;\n}\n\n/\* Scripting\n

\*/\n\n/\*\*\n \* Add the correct display in IE 9-.\n \*/\n\ncanvas {\n display: inline-block;\n}\n\n/\*\*\n \* Add the correct display in IE.\n \*/\n\ntemplate {\n display: none;\n}\n\n/\* Hidden\n

\*/\n\n/\*\*\n \* Add the correct display in IE 10-.\n \*/\n\n[hidden] {\n display: none;\n}\n\n", "", {\n "version":3,"sources":["/home/ubuntu/ReactThumbSignIn/node\_modules/normalize.css/normalize.css"],"names":[],"mappings":"AAAA,4EAA4E;;AAE5E;gFACgF;;AAEHf;;;GAIG;;AAEH;EACE,kBAAkB,CAAC,OA AO;EAC1B,2BAA2B,CAAC,OAAO;EACnC,+BAA+B,CAAC,OAAO;CACxC;;AAED;gFACgF;;AAEHf;;GA EG;;AAEH;EACE,UAAU;CACX;;AAED;;GAEG;;AAEH;;;;;EAME,eAAe;CACHB;;AAED;;;GAGG;;AAE H;EACE,eAAe;EACf,iBAAiB;CACIB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;OAE0,OAAO;EACZ,eA Ae;CACHB;;AAED;;GAEG;;AAEH;EACE,iBAAiB;CACIB;;AAED;;;GAGG;;AAEH;EACE,gCAAgC;UACx B,wBAAwB,CAAC,OAAO;EACxC,UAAU,CAAC,OAAO;EAC1B,kBAAkB,CAAC,OAAO;CAC3B;;AAED;; ;GAGG;;AAEH;EACE,kCAAkC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED;gFACgF;;AA EHf;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,sCAAsC,CAAC,OAAO;CAC/C;;AAED;;;GAG G;;AAEH;EACE,oBAAoB,CAAC,OAAO;EAC5B,2BAA2B,CAAC,OAAO;EACnC,0CAA0C;UACIC,kCAA kC,CAAC,OAAO;CACnD;;AAED;;GAEG;;AAEH;;EAEe,qBAAqB;CACtB;;AAED;;GAEG;;AAEH;;EAEe, oBAAoB;CACrB;;AAED;;;GAGG;;AAEH;;;EAGE,kCAAkC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;C ACxB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,uBAAuB;EACvB,Y AAY;CACb;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EAEe,eAAe;EACf,eAA e;EACf,mBAAmB;EACnB,yBAAyB;CAC1B;;AAED;EACE,gBAAgB;CACjB;;AAED;EACE,YAAY;CACb;; AAED;gFACgF;;AAEHf;;GAEG;;AAEH;;EAEe,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;EA Cd,UAAU;CACX;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,iBAAiB ;CACIB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;;;;EAKE,wBAAwB,CAAC,OAAO;EACHC,gBAAgB,CA AC,OAAO;EACxB,kBAAkB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;;GAGG;;AAEH

;QACQ,OAAO;EACb,kBAAkB;CACnB;;AAED;;;GAGG;;AAEH;SACS,OAAO;EACd,qBAAqB;CACtB;;AAED;;;GAIG;;AAEH;;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;;EAIE,mBAAmB;EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;;EAIE,+BAA+B;CACHc;;AAED;;GAEG;;AAEH;EACE,+BAA+B;CACHc;;AAED;;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,eAAe,CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAAgB,CAAC,OAAO;EACxB,WAAW,CAAC,OAAO;EACnB,oBAAoB,CAAC,OAAO;CAC7B;;AAED;;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,yBAAyB,CAAC,OAAO;CACiC;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHb;;AAED;;;GAGG;;AAEH;EAEE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AAEH;EAEE,aAAa;CACd;;AAED;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAAqB,CAAC,OAAO;CAC9B;;AAED;;GAEG;;AAEH;EAEE,yBAAyB;CAC1B;;AAED;;;GAGG;;AAEH;EACE,2BAA2B,CAAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED;gFACgF;;AAEhF;;;GAGG;;AAEH;EAEE,eAAe;CACHb;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;gFACgF;;AAEhF;;GAEG;;AAEH;EACE,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED;gFACgF;;AAEhF;;GAEG;;AAEH;EACE,cAAc;CACf","file":"normalize.css","sourcesContent":["/\*! normalize.css v7.0.0 | MIT License |  
github.com/necolas/normalize.css \*/\n\n/\* Document\n\n=====\n\n\*/\n\n/\* 1. Correct the line height in all browsers.\n \* 2. Prevent adjustments of font size after orientation changes in IE on Windows Phone and in iOS.\n \*/\n\nhtml {\n line-height: 1.15; /\* 1 \*/\n -ms-text-size-adjust: 100%; /\* 2 \*/\n -webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n\n=====\n\n\*/\n\n/\* Remove the margin in all browsers (opinionated).\n \*/\n\nbody {\n margin: 0;\n}\n\n/\* Add the correct display in IE 9-.\n \*/\n\narticle,aside,footer,header,nav,section {\n display: block;\n}\n\n/\* Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.\n \*/\n\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping content\n\n=====\n\n\*/\n\n/\* Add the correct display in IE 9-.\n \*/\n\n1. Add the correct display in IE.\n\nfigurecaption,figure,main { /\* 1 \*/\n display: block;\n}\n\n/\* Add the correct margin in IE 8.\n \*/\n\nfigure {\n margin: 1em 40px;\n}\n\n/\* 1. Add the correct box sizing in Firefox.\n \* 2. Show the overflow in Edge and IE.\n \*/\n\nhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /\* 1 \*/\n height: 0; /\* 1 \*/\n overflow: visible; /\* 2 \*/\n}\n\n/\* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\npre {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\* Text-level semantics\n\n=====\n\n\*/\n\n/\* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in iOS 8+ and Safari 8+.\n \*/\n\na {\n background-color: transparent; /\* 1 \*/\n -webkit-text-decoration-skip: objects; /\* 2 \*/\n}\n\n/\* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*/\n\nabbr[title] {\n border-bottom: none; /\* 1 \*/\n text-decoration: underline; /\* 2 \*/\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*/\n}\n\n/\* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n \*/\n\nb,strong {\n font-weight: inherit;\n}\n\n/\* Add the correct font weight in Chrome, Edge, and Safari.\n \*/\n\nb,strong {\n font-weight: bolder;\n}\n\n/\* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\ncode,kbd,samp {\n

font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\*\n \* Add the correct font style in  
Android 4.3-.\n \*/\n\nndfn {\n font-style: italic;\n}\n\n/\*\n \* Add the correct background and color in IE 9-.\n \*/\n\nmark {\n background-color: #fff;\n color: #000;\n}\n\n/\*\n \* Add the correct font size in all  
browsers.\n \*/\n\nsmall {\n font-size: 80%;\n}\n\n/\*\n \* Prevent `sub` and `sup` elements from affecting the  
line height in\n \* all browsers.\n \*/\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded  
content\n

=====  
\*\n\n/\*\n \* Add the correct display in IE 9-.\n \*/\n\naudio,\nvideo {\n display: inline-block;\n}\n\n/\*\n \* Add the correct display in iOS 4-7.\n \*/\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n/\*\n \* Remove the border on images inside links in IE 10-.\n \*/\n\nimg {\n border-style: none;\n}\n\n/\*\n \* Hide the  
overflow in IE.\n \*/\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\*\n\n/\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and  
Safari.\n \*/\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*/\n font-size:  
100%; /\* 1 \*/\n line-height: 1.15; /\* 1 \*/\n margin: 0; /\* 2 \*/\n}\n\n/\*\n \* Show the overflow in IE.\n \* 1.  
Show the overflow in Edge.\n \*/\n\nbutton,\ninput { /\* 1 \*/\n overflow: visible;\n}\n\n/\*\n \* Remove the  
inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in  
Firefox.\n \*/\n\nbutton,\nselect { /\* 1 \*/\n text-transform: none;\n}\n\n/\*\n \* 1. Prevent a WebKit bug where  
(2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable  
types in iOS and Safari.\n \*/\n\nbutton,\nhtml [type="button"], /\* 1 \*/\n[type="reset"],\n[type="submit"] {\n -webkit-appearance: button; /\* 2 \*/\n}\n\n/\*\n \* Remove the inner border and padding in Firefox.\n \*/\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n/\*\n \* Restore the focus styles  
unset by the previous rule.\n \*/\n\nbutton:-moz-focusing,\n[type="button"]:-moz-focusing,\n[type="reset"]:-moz-focusing,\n[type="submit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n\n/\*\n \* Correct the padding in Firefox.\n \*/\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n/\*\n \* 1. Correct the text wrapping in Edge and  
IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers  
are not caught out when they zero out\n \* `fieldset` elements in all browsers.\n \*/\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n color: inherit; /\* 2 \*/\n display: table;\n /\* 1 \*/\n max-width: 100%; /\* 1 \*/\n padding: 0; /\* 3 \*/\n white-space: normal; /\* 1 \*/\n}\n\n/\*\n \* Add  
the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*/\n\nprogress {\n display: inline-block; /\* 1 \*/\n vertical-align: baseline; /\* 2 \*/\n}\n\n/\*\n \* Remove the  
default vertical scrollbar in IE.\n \*/\n\ntextarea {\n overflow: auto;\n}\n\n/\*\n \* 1. Add the correct box sizing  
in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*/\n\n[type="checkbox"],\n[type="radio"] {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n padding: 0; /\* 2 \*/\n}\n\n/\*\n \* Correct the cursor style of increment and decrement buttons in Chrome.\n \*/\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n height:  
auto;\n}\n\n/\*\n \* 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in  
Safari.\n \*/\n\n[type="search"] {\n -webkit-appearance: textfield; /\* 1 \*/\n outline-offset: -2px; /\* 2  
\*\n\n/\*\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n \*/\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n



-webkit-appearance: none;\n}\n\n/\*\*\n \* 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2. Change font properties to `inherit` in Safari.\n \*/\n\n::-webkit-file-upload-button {\n -webkit-appearance: button; /\* 1 \*/\n font: inherit; /\* 2 \*/\n}\n\n/\* Interactive\n

=====  
\*\n\n/\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in Edge, IE, and Firefox.\n \* 2. Add the correct display in all browsers.\n \*/\n\nndetails, /\* 1 \*/\n\nmenu {\n display: block;\n}\n\n/\*\n \* Add the correct display in all browsers.\n \*/\n\nsummary {\n display: list-item;\n}\n\n/\* Scripting\n

=====  
\*\n\n/\*\*\n \* Add the correct display in IE 9-.\n \*/\n\nncanvas {\n display: inline-block;\n}\n\n/\*\*\n \* Add the correct display in IE.\n \*/\n\nntemplate {\n display: none;\n}\n\n/\* Hidden\n

=====  
\*\n\n/\*\*\n \* Add the correct display in IE 10-.\n \*/\n\n[hidden] {\n display: none;\n}\n\n", "sourceRoot": "" }]);

```
    user = _props.user,
    user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
      user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
        user.isLoggedin ? __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
          user: {
            isLoggedin: !userInfo.isLoading ? userInfo.data.isLoggedin : ownProps.query.user.isLoggedin,
            * `Indeterminate`, and `Query Indeterminate`.
            * A `Query Indeterminate` linear progress bar is used when you are combining
            * as a query indeterminate progress bar by adding the prop `query={true}` to the
            * component. Until a progress value is given, it will display the query linear
            * progress animation. Afterwards, it will start the determinate animation of where
            query = _props.query,
            props = _objectWithoutProperties(_props, ['className', 'progressClassName', 'progressStyle', 'value',
            'query', 'centered']));
```

```
    'md-progress--linear-query': query,
    * region until it is finished loading. It is not possible for the user to alter the value of a progressbar
    * Boolean if this should be a query indeterminate progress bar.
    query: _propTypes2.default.bool,
    query: false
    * region until it is finished loading. It is not possible for the user to alter the value of a progressbar
```

26-[https://stage.thumbsignin.com/assets/docs\\_android.chunk.js](https://stage.thumbsignin.com/assets/docs_android.chunk.js)

Other Information: \* Gets the easing type from the smooth prop within options.

```
var from = match.index + (lookbehind ? match[1].length : 0),
// Move the index i to the element in strarr that is closest to from
if (from >= p) {
var from = match.index + lookbehindLength,
to = from + match.length,
before = str.slice(0, from),
// Copy of the full string this token was created from
'keyword':
```

```

\b(?:as|async|await|break|case|catch|class|const|continue|debugger|default|delete|do|else|enum|export|extends|finally|for|from|function|get|if|implements|import|in|instanceof|interface|let|new|null|of|package|private|protected|public|return|set|static|super|switch|this|throw|try|typeof|var|void|while|with|yield)\b/,
//import PropTypes from 'prop-types';
/** Detect free variable `global` from Node.js. */
// accelerating from zero velocity
// accelerating from zero velocity
// accelerating from zero velocity
// accelerating from zero velocity
// Remove `parentBindings` from props
    'From the ThumbSignIn Dashboard, download ',
    'From the ThumbSignIn Dashboard, inside a newly created application, click on Android
section.'
```

'This function is to register the user for strong authentication using ThumbSignIn. It should be triggered after legacy login flow or via a setting once user logged in the app e.g. after username and password login.'

```

code: /**\n* Register a user,\n* @param username identifier of the user
(Note: userIdentifier can be an internal mapping to the user provided to ThumbSignIn, not necessarily be the
actual username or user id in your platform)\n* @param callback\n*\npublic static void register (String
username, Callback callback) {\n}',
```

'This function is to authenticate the user using fingerprint/pin via ThumbSignIn. Only successfully registered user can use this authenticator.'

```

code: /**\n* Authenticate a user\n* @param username\n* @param
callback\n*\npublic static void authenticate(String username, Callback callback) {\n}',
```

```

code: /**\n* In addition to authentication show transaction text to user as
well\n* @param username\n* @param transaction description of the transaction that needs to be displayed to
user during fingerprint-authentication\n* @param callback\n*\npublic static void transact(String username,
String transaction, Callback callback) {\n}',
```

'This function is used to deregister the user from ThumbSignIn server. After the successful deregistration, the user will no longer be able to use ThumbsignIn authenticator unless he registers again.'

```

code: /**\n* This is a model class for final response received from
FAAS. It is used in success callback to\n* return transaction info to app. The developer can use these
information in various format.\n*\npublic class TSResponse {\n    private boolean success;           //
Transaction status of the operation\n    private String userId;           // User identity\n    private String
transactionId;           // Transaction ID\n    private String token;           // Optional! JWT web token(used for IoT
Requirement)\n}',
```

```

code: /**\n* Authenticates an IoT device\n*\n* @param username\n*
@param callback\n*\npublic static void authenticateIoT(String username, Callback callback) {\n}',
```

'After, successful legacy-login(existing login process of the application eg: username, password) to vendor's website, a user can start FIDO registration process. The user can scan ThumbSignIn generated QR code and forward the scanned raw text data to FIDO sdk'

'Once, a user is FIDO-registered with ThumbSignIn, he can login directly to

website by scanning QR displayed on vendor's homepage.'

```
code: '/**\n* FacetID MUST be a URI derived from the Base64 encoding SHA-1
hash of the APK signing certificate.\n* [APK-Signing]:
android:apk-key-hash:<base64_encoded_sha1_hash-of-apk-signing-cert>\n*\n* TODO: check and match if
apk-hash string can be renamed to "pramati-fido-key" string.\n* @return FacetID\n*/\npublic static String
getFacetID() {\n    Context context = ThumbSignIn.getContext();\n    try {\n        PackageInfo
paramPackageInfo = context.getPackageManager().getPackageInfo(context.getApplicationContext().\ngetPackageName(), context.getPackageManager().GET_SIGNATURES);\n        ByteArrayInputStream
byteArrayInputStream = new ByteArrayInputStream(paramPackageInfo.signatures[0].toByteArray());\n        Certificate certificate = CertificateFactory.getInstance("X509").generateCertificate(byteArrayInputStream);\n        MessageDigest messageDigest = MessageDigest.getInstance("SHA1");\n\n        String facetID = "android:apk-key-hash:" +
Base64.encodeToString(messageDigest.digest(certificate.getEncoded()), 3);\n        return facetID;\n    } catch
(Exception e) {\n        Log.e ("FACET-ID", "Can't fetch facet-ID", e);\n    }\n    return null;\n}
```

'The four different API methods need to be invoked at different points during the app user experience and the success/failure scenarios handled during the respective callbacks.'

'For Registration, the developers could initiate registration API for the user after legacy login flow(existing login process of the application. eg: username, password) to relying-party application. See the illustration below for a sample implementation:'

'Now, users can be prompted to register for FIDO, If he agrees for FIDO registration, then invoke the ThumbSignIn#registration API, otherwise proceed with user logged-in screen.'

'Now, after successful fingerprint/pin verification, the user will be registered with ThumbSignIn.'

'For Authentication, the developers can trigger an authentication API from the legacy login screen by displaying it as the alternative option to login. The authentication API needs to be triggered only after the user successfully registered with ThumbSignIn. See the illustration below for a sample implementation.'

' functionality for the user if he/she wants to opt out of passwordless login. This API can be triggered by any settings section of the App.'

```
query: '{\n    user {\n        isLogedin\n    } \n    }'\n{ query: data, __source: {
```

// this implementation is not 100% perfect for weird media query combinations

// Adapted from convert-source-map (MIT)

\* // Remove it from the DOM

// bind timers to global for call from export context

// Thrash, waste and sodomy: IE GC bug

// IE 8- don't enum bug keys

```
err = new Error('You provided a `'+ propFullNameSafe + '` + location + ' to the ' + componentNameSafe +
' that was ' + ('not within the range from \'' + min + ' - ' + max + '\'. `'+ propFullNameSafe + `': ' + value + '));
```

// Don't enum bug & hidden keys

// getting tag from 19.1.3.6 Object.prototype.toString()

// callbacks from appending listeners

```
return fetch('/api/user').then(function (response) {
```

```

    return fetch('/api/user', { method: "POST", body: userInfo }).then(function (response) {
// cached from whatever global is present so that test runners that stub it
// import { Provider } from '../Modal'
    query: __WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.isRequired
exports.push([module.i, "/*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css */\n\n/*
Document\n
=====
*\n\n**\n * 1. Correct the line height in all browsers.\n * 2. Prevent adjustments of font size after orientation
changes in\n *   IE on Windows Phone and in iOS.\n */\n\nhtml {\n  line-height: 1.15; /* 1 *\n
-ms-text-size-adjust: 100%; /* 2 *\n  -webkit-text-size-adjust: 100%; /* 2 *\n}\n\n/* Sections\n
=====
*\n\n**\n * Remove the margin in all browsers (opinionated).\n */\n\nbody {\n  margin: 0;\n}\n\n**\n * Add
the correct display in IE 9-.\n */\n\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n  display:
block;\n}\n\n**\n * Correct the font size and margin on `h1` elements within `section` and\n * `article`
contexts in Chrome, Firefox, and Safari.\n */\n\nh1 {\n  font-size: 2em;\n  margin: 0.67em 0;\n}\n\n/* Grouping
content\n
=====
*\n\n**\n * Add the correct display in IE 9-.\n * 1. Add the correct display in IE.\n
*\n\nfigcaption,\nfigure,\nmain { /* 1 *\n  display: block;\n}\n\n**\n * Add the correct margin in IE 8.\n
*\n\nfigure {\n  margin: 1em 40px;\n}\n\n**\n * 1. Add the correct box sizing in Firefox.\n * 2. Show the
overflow in Edge and IE.\n */\n\nhr {\n  -webkit-box-sizing: content-box;\n      box-sizing: content-box; /* 1
*\n  height: 0; /* 1 *\n  overflow: visible; /* 2 *\n}\n\n**\n * 1. Correct the inheritance and scaling of font
size in all browsers.\n * 2. Correct the odd `em` font sizing in all browsers.\n */\n\npre {\n  font-family:
monospace, monospace; /* 1 *\n  font-size: 1em; /* 2 *\n}\n\n/* Text-level semantics\n
=====
*\n\n**\n * 1. Remove the gray background on active links in IE 10.\n * 2. Remove gaps in links underline in
iOS 8+ and Safari 8+.\n */\n\na {\n  background-color: transparent; /* 1 *\n  -webkit-text-decoration-skip:
objects; /* 2 *\n}\n\n**\n * 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n * 2. Add the
correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n */\n\nabbr[title] {\n  border-bottom: none; /*
1 *\n  text-decoration: underline; /* 2 *\n  -webkit-text-decoration: underline dotted;\n      text-decoration:
underline dotted; /* 2 *\n}\n\n**\n * Prevent the duplicate application of `bolder` by the next rule in Safari
6.\n */\n\nb,\nstrong {\n  font-weight: inherit;\n}\n\n**\n * Add the correct font weight in Chrome, Edge, and
Safari.\n */\n\nb,\nstrong {\n  font-weight: bolder;\n}\n\n**\n * 1. Correct the inheritance and scaling of font
size in all browsers.\n * 2. Correct the odd `em` font sizing in all browsers.\n */\n\ncode,\nkbd,\nsamp {\n
font-family: monospace, monospace; /* 1 *\n  font-size: 1em; /* 2 *\n}\n\n**\n * Add the correct font style in
Android 4.3-.\n */\n\ni,\ndfn {\n  font-style: italic;\n}\n\n**\n * Add the correct background and color in IE 9-.\n
*\n\nmark {\n  background-color: #ff0;\n  color: #000;\n}\n\n**\n * Add the correct font size in all
browsers.\n */\n\nsmall {\n  font-size: 80%;\n}\n\n**\n * Prevent `sub` and `sup` elements from affecting the
line height in\n * all browsers.\n */\n\nsub,\nsup {\n  font-size: 75%;\n  line-height: 0;\n  position: relative;\n
vertical-align: baseline;\n}\n\nsub {\n  bottom: -0.25em;\n}\n\nsup {\n  top: -0.5em;\n}\n\n/* Embedded
content\n
=====
*\n\n**\n * Add the correct display in IE 9-.\n */\n\naudio,\nvideo {\n  display: inline-block;\n}\n\n**\n *

```

Add the correct display in iOS 4-7.\n \*/\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n\*\*\n \*\n Remove the border on images inside links in IE 10-.\n \*/\n\nimg {\n border-style: none;\n}\n\n\*\*\n \*\n Hide the overflow in IE.\n \*/\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\*\n\n\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n \*/\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*\n font-size: 100%; /\* 1 \*\n line-height: 1.15; /\* 1 \*\n margin: 0; /\* 2 \*\n}\n\n\*\*\n \*\n Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n \*/\n\nbutton,\ninput {\n /\* 1 \*\n overflow: visible;\n}\n\n\*\*\n \*\n Remove the inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n \*/\n\nbutton,\nselect {\n /\* 1 \*\n text-transform: none;\n}\n\n\*\*\n \*\n 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable types in iOS and Safari.\n \*/\n\nbutton,\nhtml [type="button"], /\* 1 \*\n[type="reset"],\n[type="submit"] {\n -webkit-appearance: button; /\* 2 \*\n}\n\n\*\*\n \*\n Remove the inner border and padding in Firefox.\n \*/\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n\*\*\n \*\n Restore the focus styles unset by the previous rule.\n \*/\n\nbutton:-moz-focusring,\n[type="button"]:-moz-focusring,\n[type="reset"]:-moz-focusring,\n[type="submit"]:-moz-focusring {\n outline: 1px dotted ButtonText;\n}\n\n\*\*\n \*\n Correct the padding in Firefox.\n \*/\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n\*\*\n \*\n 1. Correct the text wrapping in Edge and IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers are not caught out when they zero out `fieldset` elements in all browsers.\n \*/\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*\n color: inherit; /\* 2 \*\n display: table; /\* 1 \*\n max-width: 100%; /\* 1 \*\n padding: 0; /\* 3 \*\n white-space: normal; /\* 1 \*\n}\n\n\*\*\n \*\n 1. Add the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*/\n\nprogress {\n display: inline-block; /\* 1 \*\n vertical-align: baseline; /\* 2 \*\n}\n\n\*\*\n \*\n Remove the default vertical scrollbar in IE.\n \*/\n\ntextarea {\n overflow: auto;\n}\n\n\*\*\n \*\n 1. Add the correct box sizing in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*/\n\n[type="checkbox"],\n[type="radio"] {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*\n padding: 0; /\* 2 \*\n}\n\n\*\*\n \*\n Correct the cursor style of increment and decrement buttons in Chrome.\n \*/\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n height: auto;\n}\n\n\*\*\n \*\n 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in Safari.\n \*/\n\n[type="search"] {\n -webkit-appearance: textfield; /\* 1 \*\n outline-offset: -2px; /\* 2 \*\n}\n\n\*\*\n \*\n Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n \*/\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n -webkit-appearance: none;\n}\n\n\*\*\n \*\n 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2. Change font properties to `inherit` in Safari.\n \*/\n\n::-webkit-file-upload-button {\n -webkit-appearance: button; /\* 1 \*\n font: inherit; /\* 2 \*\n}\n\n/\* Interactive\n

=====  
\*\n\n\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in Edge, IE, and Firefox.\n \*/\n\ndetails, /\* 1 \*\nmenu {\n display: block;\n}\n\n\*\*\n \*\n Add the correct display in all browsers.\n \*/\n\nsummary {\n display: list-item;\n}\n\n/\* Scripting\n

=====  
\*\n\n\*\*\n \* Add the correct display in IE 9-.\n \*/\n\ncanvas {\n display: inline-block;\n}\n\n\*\*\n \* Add the

correct display in IE.\n \*\n\ntemplate {\n display: none;\n}\n\n/\* Hidden\n

```
=====  
*\n\n/**\n * Add the correct display in IE 10-.\n *\n\n[hidden] {\n display: none;\n}\n", "",  
{ "version":3,"sources":["/home/ubuntu/ReactThumbSignIn/node_modules/normalize.css/normalize.css"],"names":[], "mappings": "AAAA,4EAA4E;;AAE5E;gFACgF;;AAEhF;;;GAIG;;AAEH;EACE,kBAaKB,CAAC,OA  
AO;EAC1B,2BAA2B,CAAC,OAAO;EACnC,+BAA+B,CAAC,OAAO;CACxC;;AAED;gFACgF;;AAEhF;;G  
AEG;;AAEH;EACE,UAAU;CACX;;AAED;;GAEG;;AAEH;;;;;EAME,eAAe;CACHB;;AAED;;;GAGG;;AAE  
H;EACE,eAAe;EACf,iBAaIB;CACIB;;AAED;gFACgF;;AAEhF;;;GAGG;;AAEH;;OAE0,OAAO;EACZ,eA  
Ae;CACHB;;AAED;;GAEG;;AAEH;EACE,iBAaIB;CACIB;;AAED;;;GAGG;;AAEH;EACE,gCAAgC;UACx  
B,wBAawB,CAAC,OAAO;EACxC,UAAU,CAAC,OAAO;EACIB,kBAaKB,CAAC,OAAO;CAC3B;;AAED;;  
;GAGG;;AAEH;EACE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED;gFACgF;;AA  
EhF;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,sCAAsC,CAAC,OAAO;CAC/C;;AAED;;;GAG  
G;;AAEH;EACE,oBAaOB,CAAC,OAAO;EAC5B,2BAA2B,CAAC,OAAO;EACnC,0CAA0C;UACIC,kCAA  
kC,CAAC,OAAO;CACnD;;AAED;;GAEG;;AAEH;;EAEe,qBAaQB;CACtB;;AAED;;GAEG;;AAEH;;EAEe,  
oBAaOB;CACrB;;AAED;;;GAGG;;AAEH;;EAGE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;C  
ACxB;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;;GAEG;;AAEH;EACE,uBAaUB;EACvB,Y  
AAY;CACb;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EAEe,eAAe;EACf,eAA  
e;EACf,mBAaMB;EACnB,yBAaYB;CAC1B;;AAED;EACE,gBAaGB;CACjB;;AAED;EACE,YAAY;CACb;;  
AAED;gFACgF;;AAEhF;;GAEG;;AAEH;;EAEe,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;EA  
Cd,UAAU;CACX;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;;GAEG;;AAEH;EACE,iBAaIB  
;CACIB;;AAED;gFACgF;;AAEhF;;;GAGG;;AAEH;;;;;EAKE,wBAawB,CAAC,OAAO;EACbC,gBAaGB,CA  
AC,OAAO;EACxB,kBAaKB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;;GAGG;;AAEH  
;QACQ,OAAO;EACb,kBAaKB;CACnB;;AAED;;;GAGG;;AAEH;SACS,OAAO;EACd,qBAaQB;CACtB;;A  
AED;;;GAIG;;AAEH;;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;;EAIE,mBAaMB;  
EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;;EAIE,+BAA+B;CACHC;;AAED;;GAEG;;AAEH;EACE,+  
BAA+B;CACHC;;AAED;;;;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAaUB,CAAC,OAAO;EACvC,eAAe,  
CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAaGB,CAAC,OAAO;EACxB,WAAW,CAAC,OAA  
O;EACnB,oBAaOB,CAAC,OAAO;CAC7B;;AAED;;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,  
yBAaYB,CAAC,OAAO;CACIC;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;;GAGG;;AAEH;;EA  
EE,+BAA+B;UACvB,uBAaUB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AA  
EH;;EAEe,aAAa;CACd;;AAED;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAaQB,CAAC,O  
AAO;CAC9B;;AAED;;GAEG;;AAEH;;EAEe,yBAaYB;CAC1B;;AAED;;;GAGG;;AAEH;EACE,2BAA2B,C  
AAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED;gFACgF;;AAEhF;;;GAGG;;AAEH;;EAEe,eAAe;  
CACHB;;AAED;;GAEG;;AAEH;EACE,mBAaMB;CACpB;;AAED;gFACgF;;AAEhF;;GAEG;;AAEH;EACE,  
sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED;gFACgF;;AAEhF;;GAEG;;AAEH;EAC  
E,cAAc;CACf","file":"normalize.css","sourcesContent":["/*! normalize.css v7.0.0 | MIT License |  
github.com/necolas/normalize.css */\n\n/* Document\n
```

```
=====  
*\n\n/**\n * 1. Correct the line height in all browsers.\n * 2. Prevent adjustments of font size after orientation  
changes in\n * IE on Windows Phone and in iOS.\n *\n\nhtml {\n line-height: 1.15; /* 1 *\n -ms-text-size-adjust: 100%; /* 2 *\n -webkit-text-size-adjust: 100%; /* 2 *\n}\n\n/* Sections\n
```

```
=====  
*\n\n/**\n * Remove the margin in all browsers (opinionated).\n *\n\nbody {\n margin: 0;\n}\n\n/* Add
```

the correct display in IE 9-.  
block;  
Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.  
h1 {  
font-size: 2em;  
margin: 0.67em 0;  
}  
Grouping content

=====

1. Add the correct display in IE.  
figcaption, figure, main {  
display: block;  
}  
figure {  
margin: 1em 40px;  
}  
1. Add the correct box sizing in Firefox.  
2. Show the overflow in Edge and IE.  
hr {  
-webkit-box-sizing: content-box;  
box-sizing: content-box;  
height: 0;  
overflow: visible;  
}  
1. Correct the inheritance and scaling of font size in all browsers.  
2. Correct the odd `em` font sizing in all browsers.  
pre {  
font-family: monospace, monospace;  
font-size: 1em;  
}  
Text-level semantics

=====

1. Remove the gray background on active links in IE 10.  
2. Remove gaps in links underline in iOS 8+ and Safari 8+.  
a {  
background-color: transparent;  
-webkit-text-decoration-skip: objects;  
}  
1. Remove the bottom border in Chrome 57- and Firefox 39-.  
2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.  
abbr[title] {  
border-bottom: none;  
text-decoration: underline;  
-webkit-text-decoration: underline dotted;  
text-decoration: underline dotted;  
}  
Prevent the duplicate application of `bolder` by the next rule in Safari 6.  
b, strong {  
font-weight: inherit;  
}  
Add the correct font weight in Chrome, Edge, and Safari.  
b, strong {  
font-weight: bolder;  
}  
1. Correct the inheritance and scaling of font size in all browsers.  
2. Correct the odd `em` font sizing in all browsers.  
code, kbd, samp {  
font-family: monospace, monospace;  
font-size: 1em;  
}  
Add the correct font style in Android 4.3-.  
dfn {  
font-style: italic;  
}  
Add the correct background and color in IE 9-.  
mark {  
background-color: #ff0;  
color: #000;  
}  
Add the correct font size in all browsers.  
small {  
font-size: 80%;  
}  
Prevent `sub` and `sup` elements from affecting the line height in all browsers.  
sub, sup {  
font-size: 75%;  
line-height: 0;  
position: relative;  
vertical-align: baseline;  
}  
sub {  
bottom: -0.25em;  
}  
sup {  
top: -0.5em;  
}  
Embedded content

=====

1. Add the correct display in IE 9-.  
audio, video {  
display: inline-block;  
}  
Add the correct display in iOS 4-7.  
audio:not([controls]) {  
display: none;  
height: 0;  
}  
Remove the border on images inside links in IE 10-.  
img {  
border-style: none;  
}  
Hide the overflow in IE.  
svg:not(:root) {  
overflow: hidden;  
}  
Forms

=====

1. Change the font styles in all browsers (opinionated).  
2. Remove the margin in Firefox and Safari.  
button, input, optgroup, select, textarea {  
font-family: sans-serif;  
font-size: 100%;  
line-height: 1.15;  
margin: 0;  
}  
Show the overflow in IE.  
1. Show the overflow in Edge.  
button, input {  
overflow: visible;  
}  
Remove the inheritance of text transform in Edge, Firefox, and IE.  
1. Remove the inheritance of text transform in Firefox.  
button, select {  
text-transform: none;  
}  
1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.  
2. Correct the inability to style clickable types in iOS and Safari.  
button, html [type="button"], [type="reset"], [type="submit"]

```
{\n  -webkit-appearance: button; /* 2 */\n}\n\n/**\n * Remove the inner border and padding in Firefox.\n */\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[type="submit"]::-moz-focus-inner {\n  border-style: none;\n  padding: 0;\n}\n\n/**\n * Restore the focus styles\n * unset by the previous rule.\n */\n\nbutton:-moz-focusing,\n[type="button"]:-moz-focusing,\n[type="reset"]:-moz-focusing,\n[type="submit"]:-moz-focusing {\n  outline: 1px dotted ButtonText;\n}\n\n/**\n * Correct the padding in Firefox.\n */\n\nfieldset {\n  padding: 0.35em 0.75em 0.625em;\n}\n\n/**\n * 1. Correct the text wrapping in Edge and IE.\n * 2. Correct the color inheritance from `fieldset` elements in IE.\n * 3. Remove the padding so developers\n *    are not caught out when they zero out\n *    `fieldset` elements in all browsers.\n */\n\nlegend {\n  -webkit-box-sizing: border-box;\n  box-sizing: border-box; /* 1 */\n  color: inherit; /* 2 */\n  display: table;\n  /* 1 */\n  max-width: 100%; /* 1 */\n  padding: 0; /* 3 */\n  white-space: normal; /* 1 */\n}\n\n/**\n * 1. Add the correct display in IE 9-.\n * 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n */\n\nprogress {\n  display: inline-block; /* 1 */\n  vertical-align: baseline; /* 2 */\n}\n\n/**\n * Remove the default vertical scrollbar in IE.\n */\n\ntextarea {\n  overflow: auto;\n}\n\n/**\n * 1. Add the correct box sizing in IE 10-.\n * 2. Remove the padding in IE 10-.\n */\n\n[type="checkbox"],\n[type="radio"] {\n  -webkit-box-sizing: border-box;\n  box-sizing: border-box; /* 1 */\n  padding: 0; /* 2 */\n}\n\n/**\n * Correct the cursor style of increment and decrement buttons in Chrome.\n */\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n  height: auto;\n}\n\n/**\n * 1. Correct the odd appearance in Chrome and Safari.\n * 2. Correct the outline style in Safari.\n */\n\n[type="search"] {\n  -webkit-appearance: textfield; /* 1 */\n  outline-offset: -2px; /* 2 */\n}\n\n/**\n * Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n */\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n  -webkit-appearance: none;\n}\n\n/**\n * 1. Correct the inability to style clickable types in iOS and Safari.\n * 2. Change font properties to `inherit` in Safari.\n */\n\n::-webkit-file-upload-button {\n  -webkit-appearance: button; /* 1 */\n  font: inherit; /* 2 */\n}\n\n/* Interactive\n
```

```
=====\n\n/**\n * Add the correct display in IE 9-.\n * 1. Add the correct display in Edge, IE, and Firefox.\n */\n\ndetails, /* 1 */\nmenu {\n  display: block;\n}\n\n/**\n * Add the correct display in all browsers.\n */\n\nsummary {\n  display: list-item;\n}\n\n/* Scripting\n
```

```
=====\n\n/**\n * Add the correct display in IE 9-.\n */\n\ncanvas {\n  display: inline-block;\n}\n\n/**\n * Add the correct display in IE.\n */\n\ntemplate {\n  display: none;\n}\n\n/* Hidden\n
```

```
=====\n\n/**\n * Add the correct display in IE 10-.\n */\n\n[hidden] {\n  display: none;\n}\n\n", "sourceRoot": "" }));
```

```
  user = _props.user,
```

```
    user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react__default.a.createElement(\n      user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react__default.a.createElement(\n        user.isLoggedin ? __WEBPACK_IMPORTED_MODULE_0_react__default.a.createElement(\n
```

```
      user: {
```

```
        isLoggedin: !userInfo.isLoading ? userInfo.data.isLoggedin : ownProps.query.user.isLoggedin,
```

```
        * `Indeterminate`, and `Query Indeterminate`.
```

```
        * A `Query Indeterminate` linear progress bar is used when you are combining
```

```
        * as a query indeterminate progress bar by adding the prop `query={true}` to the
```



- \* component. Until a progress value is given, it will display the query linear
- \* progress animation. Afterwards, it will start the determinate animation of where

```

    query = _props.query,
    props = _objectWithoutProperties(_props, ['className', 'progressClassName', 'progressStyle', 'value',
'query', 'centered']);
    'md-progress--linear-query': query,

```

- \* region until it is finished loading. It is not possible for the user to alter the value of a progressbar
- \* Boolean if this should be a query indeterminate progress bar.

```

query: _propTypes2.default.bool,
query: false

```

- \* region until it is finished loading. It is not possible for the user to alter the value of a progressbar

27-<https://stage.thumbsignin.com/assets/client.js>

Other Information:                      if (!(activeRoute.doAuthenticate &&  
componentObject.component.props.query.user.isLoggedin === false)) {  
                    // TODO: no match route resolver and component object;  
//import actions from './v2/actions/userAction';  
\* that can be accessed from all the child components.  
    return props.query.user.isLoggedin ? '/' : false;  
    return !props.query.user.userId || props.query.user.isLoggedin ? '/' : false;  
    return props.query.user.isNewUser ? '/welcome' : false;  
//THIS IS STILL IN DEVLOPMENT MODE => USE THIS TO DO NESTED ROUTE ANY WHERE IN AN  
COMPONENT

28-<https://stage.thumbsignin.com/assets/blockchain.chunk.js>

Other Information: /\* From FvD 13.37, CSS Color Module Level 3 \*/  
    \_this.from = \_\_WEBPACK\_IMPORTED\_MODULE\_0\_react\_\_\_default.a.createRef();  
    var results = { firstName: null, lastName: null, from: null, contactNo: null, message: null };  
    var isError = { firstName: false, lastName: false, message: false, from: false, contactNo: false };  
    if (!this.from.current.field.state.error) {  
        var value3 = this.from.current.field.value.trim();  
        isError.from = !new  
RegExp(/^(^<>()\[\]\.,;\s@""]+(\.^[^<>()\[\]\.,;\s@""]+)\*)(".+")@((\[[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\.[0-9]{1,3}\])|((\[[a-zA-Z-0-9]+\.[a-zA-Z]{2,})\$/.test(value3);  
        !isError.from && value3.length > 0 ? results.from = value3 : isError.from = true;  
        name: "from",  
        ref: this.from,  
        error: this.state.errorFlag.from,  
// from <https://github.com/d3/d3-ease/blob/master/src/linear.js>  
// Apapted from <https://github.com/d3/d3-transition/blob/master/src/transition/schedule.js>  
// removes this transition from the pending list!  
var user = this.props.user;

'Blockchain is all about decentralisation, so there is no single point of control. Identity



-ms-text-size-adjust: 100%; /\* 2 \*/ -webkit-text-size-adjust: 100%; /\* 2 \*/ } Sections

/\* Remove the margin in all browsers (opinionated).  
body { margin: 0; }  
/\* Add the correct display in IE 9-  
article, aside, footer, header, nav, section { display: block; }  
/\* Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.  
h1 { font-size: 2em; margin: 0.67em 0; }  
/\* Grouping content

/\* Add the correct display in IE 9-  
1. Add the correct display in IE.  
figcaption, figure, main { /\* 1 \*/ display: block; }  
/\* Add the correct margin in IE 8.  
figure { margin: 1em 40px; }  
/\* 1. Add the correct box sizing in Firefox.  
2. Show the overflow in Edge and IE.  
hr { -webkit-box-sizing: content-box; box-sizing: content-box; /\* 1 \*/ height: 0; /\* 1 \*/ overflow: visible; /\* 2 \*/ }  
/\* 1. Correct the inheritance and scaling of font size in all browsers.  
2. Correct the odd `em` font sizing in all browsers.  
pre { font-family: monospace, monospace; /\* 1 \*/ font-size: 1em; /\* 2 \*/ }  
/\* Text-level semantics

1. Remove the gray background on active links in IE 10.  
2. Remove gaps in links underline in iOS 8+ and Safari 8+.  
a { background-color: transparent; /\* 1 \*/ -webkit-text-decoration-skip: objects; /\* 2 \*/ }  
/\* 1. Remove the bottom border in Chrome 57- and Firefox 39-  
2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.  
abbr[title] { border-bottom: none; /\* 1 \*/ text-decoration: underline; /\* 2 \*/ -webkit-text-decoration: underline dotted; text-decoration: underline dotted; /\* 2 \*/ }  
/\* Prevent the duplicate application of `bolder` by the next rule in Safari 6.  
b, strong { font-weight: inherit; }  
/\* Add the correct font weight in Chrome, Edge, and Safari.  
b, strong { font-weight: bolder; }  
/\* 1. Correct the inheritance and scaling of font size in all browsers.  
2. Correct the odd `em` font sizing in all browsers.  
code, kbd, samp { font-family: monospace, monospace; /\* 1 \*/ font-size: 1em; /\* 2 \*/ }  
/\* Add the correct font style in Android 4.3-  
dfn { font-style: italic; }  
/\* Add the correct background and color in IE 9-  
mark { background-color: #ff0; color: #000; }  
/\* Add the correct font size in all browsers.  
small { font-size: 80%; }  
/\* Prevent `sub` and `sup` elements from affecting the line height in  
\* all browsers.  
sub, sup { font-size: 75%; line-height: 0; position: relative; vertical-align: baseline; }  
sub { bottom: -0.25em; }  
sup { top: -0.5em; }  
/\* Embedded content

/\* Add the correct display in IE 9-  
audio, video { display: inline-block; }  
/\* Add the correct display in iOS 4-7  
audio:not([controls]) { display: none; height: 0; }  
/\* Remove the border on images inside links in IE 10-  
img { border-style: none; }  
/\* Hide the overflow in IE.  
svg:not(:root) { overflow: hidden; }  
/\* Forms

1. Change the font styles in all browsers (opinionated).  
2. Remove the margin in Firefox and Safari.  
button, input, optgroup, select, textarea { font-family: sans-serif; /\* 1 \*/ font-size: 100%; /\* 1 \*/ line-height: 1.15; /\* 1 \*/ margin: 0; /\* 2 \*/ }  
/\* Show the overflow in IE.  
1. Show the overflow in Edge.  
button, input { /\* 1 \*/ overflow: visible; }  
/\* Remove the inheritance of text transform in Edge, Firefox, and IE.  
1. Remove the inheritance of text transform in

Firefox.\n \*^\\n\\nbutton,\\nselect { /\* 1 \*^\\n text-transform: none;\\n}\\n\\n/\*\*\\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video`\\n \* controls in Android 4.\\n \* 2. Correct the inability to style clickable types in iOS and Safari.\\n \*^\\n\\nbutton,\\nhtml [type=\\\"button\\\"], /\* 1 \*^\\n[type=\\\"reset\\\"],\\n[type=\\\"submit\\\"] {\\n -webkit-appearance: button; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Remove the inner border and padding in Firefox.\\n \*^\\n\\nbutton::-moz-focus-inner,\\n[type=\\\"button\\\"]::-moz-focus-inner,\\n[type=\\\"reset\\\"]::-moz-focus-inner,\\n[type=\\\"submit\\\"]::-moz-focus-inner {\\n border-style: none;\\n padding: 0;\\n}\\n\\n/\*\*\\n \* Restore the focus styles unset by the previous rule.\\n \*^\\n\\nbutton:-moz-focusing,\\n[type=\\\"button\\\"]:-moz-focusing,\\n[type=\\\"reset\\\"]:-moz-focusing,\\n[type=\\\"submit\\\"]:-moz-focusing {\\n outline: 1px dotted ButtonText;\\n}\\n\\n/\*\*\\n \* Correct the padding in Firefox.\\n \*^\\n\\nfieldset {\\n padding: 0.35em 0.75em 0.625em;\\n}\\n\\n/\*\*\\n \* 1. Correct the text wrapping in Edge and IE.\\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\\n \* 3. Remove the padding so developers are not caught out when they zero out\\n \* `fieldset` elements in all browsers.\\n \*^\\n\\nlegend {\\n -webkit-box-sizing: border-box;\\n box-sizing: border-box; /\* 1 \*^\\n color: inherit; /\* 2 \*^\\n display: table; /\* 1 \*^\\n max-width: 100%; /\* 1 \*^\\n padding: 0; /\* 3 \*^\\n white-space: normal; /\* 1 \*^\\n}\\n\\n/\*\*\\n \* 1. Add the correct display in IE 9.\\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\\n \*^\\n\\nprogress {\\n display: inline-block; /\* 1 \*^\\n vertical-align: baseline; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Remove the default vertical scrollbar in IE.\\n \*^\\n\\ntextarea {\\n overflow: auto;\\n}\\n\\n/\*\*\\n \* 1. Add the correct box sizing in IE 10-.\\n \* 2. Remove the padding in IE 10.\\n \*^\\n\\n[type=\\\"checkbox\\\"],\\n[type=\\\"radio\\\"] {\\n -webkit-box-sizing: border-box;\\n box-sizing: border-box; /\* 1 \*^\\n padding: 0; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Correct the cursor style of increment and decrement buttons in Chrome.\\n \*^\\n\\n[type=\\\"number\\\"]::-webkit-inner-spin-button,\\n[type=\\\"number\\\"]::-webkit-outer-spin-button {\\n height: auto;\\n}\\n\\n/\*\*\\n \* 1. Correct the odd appearance in Chrome and Safari.\\n \* 2. Correct the outline style in Safari.\\n \*^\\n\\n[type=\\\"search\\\"] {\\n -webkit-appearance: textfield; /\* 1 \*^\\n outline-offset: -2px; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\\n \*^\\n\\n[type=\\\"search\\\"]::-webkit-search-cancel-button,\\n[type=\\\"search\\\"]::-webkit-search-decoration {\\n -webkit-appearance: none;\\n}\\n\\n/\*\*\\n \* 1. Correct the inability to style clickable types in iOS and Safari.\\n \* 2. Change font properties to `inherit` in Safari.\\n \*^\\n\\n::-webkit-file-upload-button {\\n -webkit-appearance: button; /\* 1 \*^\\n font: inherit; /\* 2 \*^\\n}\\n\\n/\* Interactive\\n

=====

\*^\\n\\n/\*^\\n \* Add the correct display in IE 9-.\\n \* 1. Add the correct display in Edge, IE, and Firefox.\\n \*^\\n\\ndetails, /\* 1 \*^\\nmenu {\\n display: block;\\n}\\n\\n/\*^\\n \* Add the correct display in all browsers.\\n \*^\\n\\nsummary {\\n display: list-item;\\n}\\n\\n/\* Scripting\\n

=====

\*^\\n\\n/\*\*\\n \* Add the correct display in IE 9-.\\n \*^\\n\\ncanvas {\\n display: inline-block;\\n}\\n\\n/\*\*\\n \* Add the correct display in IE.\\n \*^\\n\\ntemplate {\\n display: none;\\n}\\n\\n/\* Hidden\\n

=====

\*^\\n\\n/\*\*\\n \* Add the correct display in IE 10-.\\n \*^\\n\\n[hidden] {\\n display: none;\\n}\\n\\n", "", { "version": 3, "sources": ["/home/ubuntu/ReactThumbSignIn/node\_modules/normalize.css/normalize.css"], "names": [], "mappings": "AAAA,4EAA4E;;AAE5E;gFACgF;;AAEhF;;;GAIG;;AAEH;EACE,kBAaKB,CAAC,OA AO;EAC1B,2BAA2B,CAAC,OAAO;EACnC,+BAA+B,CAAC,OAAO;CACxC;;AAED;gFACgF;;AAEhF;;G AEG;;AAEH;EACE,UAAU;CACX;;AAED;;GAEG;;AAEH;;;;;EAME,eAAe;CACHB;;AAED;;;GAGG;;AAE H;EACE,eAAe;EACf,iBAAiB;CACIB;;AAED;gFACgF;;AAEhF;;;GAGG;;AAEH;;OAE0,OAAO;EACZ,eA Ae;CACHB;;AAED;;GAEG;;AAEH;EACE,iBAAiB;CACIB;;AAED;;;GAGG;;AAEH;EACE,gCAAgC;UACx

B,wBAAwB,CAAC,OAAO;EACxC,UAAU,CAAC,OAAO;EACIB,kBAaKB,CAAC,OAAO;CAC3B;;AAED;;  
;GAGG;;AAEH;EACE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED;gFACgF;;AA  
EhF;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,sCAAsC,CAAC,OAAO;CAC/C;;AAED;;;GAG  
G;;AAEH;EACE,oBAAoB,CAAC,OAAO;EAC5B,2BAA2B,CAAC,OAAO;EACnC,0CAA0C;UACIC,kCAA  
kC,CAAC,OAAO;CACnD;;AAED;;GAEG;;AAEH;;EAEE,qBAAqB;CACtB;;AAED;;GAEG;;AAEH;;EAEE,  
oBAAoB;CACrB;;AAED;;;GAGG;;AAEH;;;EAGE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;C  
ACxB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,uBAAuB;EACvB,Y  
AAY;CACb;;AAED;;GAEG;;AAEH;EACE,eAAe;CACbB;;AAED;;;GAGG;;AAEH;;EAEE,eAAe;EACf,eAA  
e;EACf,mBAAmB;EACnB,yBAAyB;CAC1B;;AAED;EACE,gBAAgB;CACjB;;AAED;EACE,YAAY;CACb;;  
AAED;gFACgF;;AAEHF;;GAEG;;AAEH;;EAEE,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;EA  
Cd,UAAU;CACX;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,iBAAiB  
;CACIB;;AAED;gFACgF;;AAEHF;;;GAGG;;AAEH;;;EAKE,wBAAwB,CAAC,OAAO;EACbC,gBAAgB,CA  
AC,OAAO;EACxB,kBAaKB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;;GAGG;;AAEH  
;QACQ,OAAO;EACb,kBAaKB;CACnB;;AAED;;;GAGG;;AAEH;SACS,OAAO;EACd,qBAAqB;CACtB;;A  
AED;;;GAIG;;AAEH;;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;;EAIE,mBAAmB;  
EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;;EAIE,+BAA+B;CACbC;;AAED;;GAEG;;AAEH;EACE,+  
BAA+B;CACbC;;AAED;;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,eAAe,  
CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAAgB,CAAC,OAAO;EACxB,WAAW,CAAC,OAA  
O;EACnB,oBAAoB,CAAC,OAAO;CAC7B;;AAED;;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,  
yBAAyB,CAAC,OAAO;CACIC;;AAED;;GAEG;;AAEH;EACE,eAAe;CACbB;;AAED;;;GAGG;;AAEH;;EA  
EE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AA  
EH;;EAEE,aAAa;CACd;;AAED;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAAqB,CAAC,O  
AAO;CAC9B;;AAED;;GAEG;;AAEH;;EAEE,yBAAyB;CAC1B;;AAED;;;GAGG;;AAEH;EACE,2BAA2B,C  
AAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED;gFACgF;;AAEHF;;;GAGG;;AAEH;;EAEE,eAAe;  
CACbB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;gFACgF;;AAEHF;;GAEG;;AAEH;EACE,  
sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED;gFACgF;;AAEHF;;GAEG;;AAEH;EAC  
E,cAAc;CACf","file":"normalize.css","sourcesContent":["/\*! normalize.css v7.0.0 | MIT License |  
github.com/necolas/normalize.css \*/\n\n/\* Document\n\n=====

\*/\n\n\*\*\n\n \* 1. Correct the line height in all browsers.\n \* 2. Prevent adjustments of font size after orientation  
changes in\n \* IE on Windows Phone and in iOS.\n \*/\n\nhtml {\n line-height: 1.15; /\* 1 \*/\n -ms-text-size-adjust: 100%; /\* 2 \*/\n -webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n\n=====

\*/\n\n\*\*\n\n \* Remove the margin in all browsers (opinionated).\n \*/\n\nbody {\n margin: 0;\n}\n\n\*\*\n\n \* Add the correct display in IE 9-.\n \*/\n\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display: block;\n}\n\n\*\*\n\n \* Correct the font size and margin on `h1` elements within `section` and\n \* `article` contexts in Chrome, Firefox, and Safari.\n \*/\n\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping content\n\n=====

\*/\n\n\*\*\n\n \* Add the correct display in IE 9-.\n\n \* 1. Add the correct display in IE.\n\n \*/\n\nfigure,\nfigcaption,\nfigure,\nmain {\n /\* 1 \*/\n display: block;\n}\n\n\*\*\n\n \* Add the correct margin in IE 8.\n\n \*/\n\nfigure {\n margin: 1em 40px;\n}\n\n\*\*\n\n \* 1. Add the correct box sizing in Firefox.\n \* 2. Show the overflow in Edge and IE.\n \*/\n\nhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /\* 1

\*/\n height: 0; /\* 1 \*/\n overflow: visible; /\* 2 \*/\n}\n\n/\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\npre {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\* Text-level semantics\n

=====  
\*/\n\n/\*\*\n \* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in iOS 8+ and Safari 8+.\n \*/\n\na {\n background-color: transparent; /\* 1 \*/\n -webkit-text-decoration-skip: objects; /\* 2 \*/\n}\n\n/\*\*\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*/\n\nabbr[title] {\n border-bottom: none; /\* 1 \*/\n text-decoration: underline; /\* 2 \*/\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*/\n}\n\n/\*\*\n \* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n \*/\n\nb,\nstrong {\n font-weight: inherit;\n}\n\n/\*\*\n \* Add the correct font weight in Chrome, Edge, and Safari.\n \*/\n\nb,\nstrong {\n font-weight: bolder;\n}\n\n/\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\ncode,\nkbd,\nsamp {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\*\*\n \* Add the correct font style in Android 4.3-.\n \*/\n\ndfn {\n font-style: italic;\n}\n\n/\*\*\n \* Add the correct background and color in IE 9-.\n \*/\n\nmark {\n background-color: #ff0;\n color: #000;\n}\n\n/\*\*\n \* Add the correct font size in all browsers.\n \*/\n\nsmall {\n font-size: 80%;\n}\n\n/\*\*\n \* Prevent `sub` and `sup` elements from affecting the line height in\n \* all browsers.\n \*/\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded content\n

=====  
\*/\n\n/\*\*\n \* Add the correct display in IE 9-.\n \*/\n\naudio,\nvideo {\n display: inline-block;\n}\n\n/\*\*\n \* Add the correct display in iOS 4-7.\n \*/\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n/\*\*\n \* Remove the border on images inside links in IE 10-.\n \*/\n\nimg {\n border-style: none;\n}\n\n/\*\*\n \* Hide the overflow in IE.\n \*/\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\*/\n\n/\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n \*/\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*/\n font-size: 100%; /\* 1 \*/\n line-height: 1.15; /\* 1 \*/\n margin: 0; /\* 2 \*/\n}\n\n/\*\*\n \* Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n \*/\n\nbutton,\ninput {\n /\* 1 \*/\n overflow: visible;\n}\n\n/\*\*\n \* Remove the inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n \*/\n\nbutton,\nselect {\n /\* 1 \*/\n text-transform: none;\n}\n\n/\*\*\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable types in iOS and Safari.\n \*/\n\nbutton,\nhtml [type="button"], /\* 1 \*/\n[type="reset"],\n[type="submit"] {\n -webkit-appearance: button; /\* 2 \*/\n}\n\n/\*\*\n \* Remove the inner border and padding in Firefox.\n \*/\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n/\*\*\n \* Restore the focus styles unset by the previous rule.\n \*/\n\nbutton:-moz-focusing,\n[type="button"]:-moz-focusing,\n[type="reset"]:-moz-focusing,\n[type="submit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n\n/\*\*\n \* Correct the padding in Firefox.\n \*/\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n/\*\*\n \* 1. Correct the text wrapping in Edge and IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers are not caught out when they zero out\n \* `fieldset` elements in all browsers.\n \*/\n\nlegend {\n

```

-webkit-box-sizing: border-box;\n      box-sizing: border-box; /* 1 */\n color: inherit; /* 2 */\n display: table;\n/* 1 */\n max-width: 100%; /* 1 */\n padding: 0; /* 3 */\n white-space: normal; /* 1 */\n}\n\n**\n * 1. Add the correct display in IE 9.\n * 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n */\n\nprogress {\n display: inline-block; /* 1 */\n vertical-align: baseline; /* 2 */\n}\n\n**\n * Remove the default vertical scrollbar in IE.\n */\n\ntextarea {\n overflow: auto;\n}\n\n**\n * 1. Add the correct box sizing in IE 10-.\n * 2. Remove the padding in IE 10-.\n */\n\n[type="checkbox"],\n[type="radio"] {\n -webkit-box-sizing: border-box;\n      box-sizing: border-box; /* 1 */\n padding: 0; /* 2 */\n}\n\n**\n * Correct the cursor style of increment and decrement buttons in Chrome.\n */\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n height: auto;\n}\n\n**\n * 1. Correct the odd appearance in Chrome and Safari.\n * 2. Correct the outline style in Safari.\n */\n\n[type="search"] {\n -webkit-appearance: textfield; /* 1 */\n outline-offset: -2px; /* 2 */\n}\n\n**\n * Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n */\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n -webkit-appearance: none;\n}\n\n**\n * 1. Correct the inability to style clickable types in iOS and Safari.\n * 2. Change font properties to `inherit` in Safari.\n */\n\n::-webkit-file-upload-button {\n -webkit-appearance: button; /* 1 */\n font: inherit; /* 2 */\n}\n\n/* Interactive\n

```

```

**\n\n * Add the correct display in IE 9-.\n * 1. Add the correct display in Edge, IE, and Firefox.\n */\n\ndetails, /* 1 */\nmenu {\n display: block;\n}\n\n**\n * Add the correct display in all browsers.\n */\n\nsummary {\n display: list-item;\n}\n\n/* Scripting\n

```

```

**\n\n * Add the correct display in IE 9-.\n */\n\ncanvas {\n display: inline-block;\n}\n\n**\n * Add the correct display in IE.\n */\n\ntemplate {\n display: none;\n}\n\n/* Hidden\n

```

```

**\n\n * Add the correct display in IE 10-.\n */\n\n[hidden] {\n display: none;\n}\n\n", "sourceRoot": "" }]);

user = _props.user,
  user.isLogedin && __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
    user.isLogedin && __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
      user.isLogedin ? __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
        user: {
          isLogedin: !userInfo.isLoading ? userInfo.data.isLogedin : ownProps.query.user.isLogedin,
* `Indeterminate`, and `Query Indeterminate`.
* A `Query Indeterminate` linear progress bar is used when you are combining
* as a query indeterminate progress bar by adding the prop `query={true}` to the
* component. Until a progress value is given, it will display the query linear
* progress animation. Afterwards, it will start the determinate animation of where
  query = _props.query,
  props = _objectWithoutProperties(_props, ['className', 'progressClassName', 'progressStyle', 'value',
'query', 'centered']);
  'md-progress--linear-query': query,
* region until it is finished loading. It is not possible for the user to alter the value of a progressbar
* Boolean if this should be a query indeterminate progress bar.
query: _propTypes2.default.bool,

```

query: false

- \* region until it is finished loading. It is not possible for the user to alter the value of a progressbar

- \* Removes observer from observers list.

- \* Updates every observer from observers list and notifies them of queued

  - // has the "ownerDocument" property from which we can retrieve a

  - // Return the local global object if it's not possible extract one from

- \* Extracts borders size from provided styles.

- \* Extracts paddings sizes from provided styles.

- \* from the corresponding properties of the last observed content rectangle.

- \* instances collected from active resize observations.

  - \* Gets the current value from the text field. This is used when you have an uncontrolled

  - \* text field and simply need the value from a ref callback.

- \* floating labels and remove the text divider from the component.

- \* this will only be visible when there is no value and the user focused the text field.

- \* Boolean if the text field is required. If the user blurs the text field while there is

- \* The direction that the underline should appear from.

- \* required and the user blurs the text field with no value.

- \* The ink when there is an injectInk above the text field. Used from the SelectField.

  - text = Array.from(Array(value.length)).reduce(function (s) {

  - className: (0, \_classnames2.default)('md-divider--text-field md-divider--expand-from-' + lineDirection, {

29-<https://stage.thumbsignin.com/>

Other Information:

```
<script>window.App={ "apiUrl":"","state":{"userInfo":{"data":{"isLoggedin":false,"admin":false},"isLoading":false,"isVerificationExpired":false,"isError":false},"appInfo":{"data":null,"isLoading":false,"status":null,"isError":false},"contactUs":{"data":null,"isError":false},"adminDashDevices":{"data":null,"isLoading":false,"isError":false},"adminDashBoard":{"data":null,"isLoading":false,"isError":false}}} </script>
```

30-<https://stage.thumbsignin.com/assets/pricing.chunk.js>

Other Information:                    query: '{\n            user {\n            isLoggedin\n            } \n            }'

   { query: data, \_\_source: {

\_\_WEBPACK\_IMPORTED\_MODULE\_0\_react\_\_\_default.a.createElement(\_\_WEBPACK\_IMPORTED\_MODULE\_3\_\_Pricing\_\_[ "a" /\* default \*/], { query: data, \_\_source: {

- \* @param {string=} field - the field to extract a value from. Defaults to 'value'.

  - // this implementation is not 100% perfect for weird media query combinations

// Adapted from convert-source-map (MIT)

- \* // Remove it from the DOM

  - // bind timers to global for call from export context

- \* An ink from `injectInk`.

- \* A tooltip from `injectTooltip`

return new Error('Only one material design button type may be specified in the `'+ component + '` but `'+ len + '` were given. Select only one of `flat`, `raised`, `icon`, or `floating`.');



- \* where the component should be switched to something else for valid html.

```
// Thrash, waste and sodomy: IE GC bug
```

```
// IE 8- don't enum bug keys
```

- \* @param {string=} field - the field to extract a value from. Defaults to 'value'.
- \* The list's z-depth for applying box shadow. This should be a number from 0 to 5.
- \* closing when a list item has been clicked, or the user presses escape.
- \* Gets the current value from the text field. This is used when you have an uncontrolled
- \* text field and simply need the value from a ref callback.
- \* floating labels and remove the text divider from the component.
- \* this will only be visible when there is no value and the user focused the text field.
- \* Boolean if the text field is required. If the user blurs the text field while there is
- \* The direction that the underline should appear from.
- \* required and the user blurs the text field with no value.
- \* The ink when there is an injectInk above the text field. Used from the SelectField.

```
text = Array.from(Array(value.length)).reduce(function (s) {
```

- \* Prevents a second warning from appearing when using the deprecated or a11y required
- \* Gets the current checked value from the selection control. This is used when you have
- \* an uncontrolled selection control and simply need the checked state from a ref callback.
- \* in `[]` so that the value can be found from `document.querySelector('input[name="someName[]"]').value`.

```
'md-table-column--select-field': selectColumnHeader
```

- \* additional styling to the column to position with the select field.

```
err = new Error('You provided a ` ` + propFullNameSafe + ` ` + location + ` ` to the ` ` + componentNameSafe + ` ` that was ` ` + (not within the range from ` ` + min + ` ` - ` ` + max + ` `. ` ` + propFullNameSafe + ` `: ` ` + value + ` `));
```

```
// Don't enum bug & hidden keys
```

```
// getting tag from 19.1.3.6 Object.prototype.toString()
```

```
// TODO: we could get rid of the need for the wrapper node
```

```
// factoryChild is not different from child.
```

- \* The `AccessibleFakeButton` allows the user to tab focus the element, use the
- \* An optional onClick function to call when the user clicks the
- \* The ink when coming from the AccessibleFakeInkedButton

```
err = new Error('You provided a ` ` + propFullNameSafe + ` ` + location + ` ` to the ` ` + componentNameSafe + ` ` that was ` ` + (not within the range from ` ` + min + ` ` - ` ` + max + ` `. ` ` + propFullNameSafe + ` `: ` ` + value + ` `));
```

- \* An ink from `injectInk`.
- \* A tooltip from `injectTooltip`

```
return new Error('Only one material design button type may be specified in the ` ` + component + ` ` but ` ` + len + ` ` + `were given. Select only one of `flat`, `raised`, `icon`, or `floating`.');
```

- \* @param {Object} obj - The object to omit keys from.
- \* This is used for some lists where only a parent contains the icon.
- \* The nested items will be visible once the user clicks on the `ListItem`.

```
// callbacks from appending listeners
```

- \* Boolean if the layover should fill the height of the viewport from the current calculated `top`. This will just
- \* iOS does not subtract the soft keyboard from the viewport's size so the list will still extend to the bottom
- \* This is the position that the children should animate from. It directly ties into

- \* This is really only helpful in cases where the layover can't calculate things correctly due to
  - // The init function can be called again if the user quickly toggles the layover. If that
- \* Attempts to find the base table component from an element in the table.
- \* @param {Object} el - The element to traverse from
  - return fetch('/api/user').then(function (response) {
  - return fetch('/api/user', { method: "POST", body: userInfo }).then(function (response) {
- // cached from whatever global is present so that test runners that stub it
  - \* where the component should be switched to something else for valid html.
- \* `type="submit"`, the `ComposedComponent` is in a form, and the user hits the `enter` key
  - \* The ink can either be created by using the `pageX` and `pageY` from a click/touch event
  - \* use case where `Switches` needed the ink disabled only when using a mouse.
- this.\_field = this.\_container.querySelector('.md-select-field');
- \* Gets the current value from the select field. This is used when you have an uncontrolled
  - \* text field and simply need the value from a ref callback.
- \* @return {String} the select field's value
  - className: \_\_WEBPACK\_IMPORTED\_MODULE\_3\_classnames\_\_\_default()('md-menu--select-field',
  - className),
- \* An id to give the select field. This is required for accessibility.
- \* An optional name to give to the select field.
- \* An optional id to provide to the select field's menu. If this is omitted,
- \* An optional id to provide to the select field's list.
- \* An optional style to apply to the select field's container (the menu).
- \* An optional className to apply to the select field's container (the menu).
- \* An optional style to apply to the select field's toggle.
- \* An optional className to apply to the select field's toggle.
- \* for the select field.
- \* for the select field.
- \* Boolean if the select field should have the menu's list visible by default.
- \* Boolean if the select field should have the menu's list visible. This will make
  - \* the select field controlled and require the `onVisibilityChange` prop to be defined,
- \* An optional function to call when the select field's menu has its visibility changed. The callback
  - \* while typing. Since a user can select items by typing multiple letters in a row,
- \* - User types `g`
- \* - User delays 200ms and types `u`
- \* - User delays 1000ms and types `a`.
- \* The default value to use for the select field. If this is set, it should either match
- \* The value to use for the select field. If this is defined, it becomes a controlled component
- \* An optional function to call when the select field's value has been changed either when the user
  - \* has click/touched/keyboard selected a value in the list, or the user has selected a value by typing
  - \* in the select field while the menu's list is closed.
- \* triggered the change, and the id, name, and value of the select field.
- \* An optional label to use with the select field. This will be a floating label as seen on the text field.
- \* An optional placeholder to use in the select field. This will only appear when no value has been selected.

- \* Boolean if the select field should be disabled.
- \* Boolean if the select field is required. This will update the label and placeholder to include a `\*` suffix.
- \* Boolean if the select field is considered to be in an `error` state.
- \* An optional text to display when the text select field is in an error state.
- \* An optional text to display below the select field to provide input help to the user.
- \* This will only be displayed if the select field is not in an error state.
- \* An optional function to call when any element in the select field has been clicked.
- \* select field.
- \* An optional function to call when the select field's toggle has gained focus.
- \* An optional function to call when the select field's toggle has been blurred. This
- \* will be triggered if the user hits the up or down arrow keys to traverse the list
- \* Boolean if the select field is in a toolbar. This should automatically be injected by the `Toolbar`
- \* Boolean if the currently active item should be removed from the list of available `menuItems`.
- \* new item `_drop_` into the select field's input location.
- \* This is how the menu's `List` gets anchored to the select field.
- \* The list's z-depth for applying box shadow. This should be a number from 0 to 5.
- \* any unnecessary props from the `ListItem` itself. This is where you
- \* The direction that the underline should appear from.

floatingLabel:

```
__WEBPACK_IMPORTED_MODULE_4__react_prop_types_lib_deprecated___default()(__WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.bool, 'A select field can only have floating labels now. Only provide the `label` prop'),
```

noAutoAdjust:

```
__WEBPACK_IMPORTED_MODULE_4__react_prop_types_lib_deprecated___default()(__WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.bool, 'No longer valid to use since select fields are no longer text fields'),
```

adjustMinWidth:

```
__WEBPACK_IMPORTED_MODULE_4__react_prop_types_lib_deprecated___default()(__WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.bool, 'No longer valid to use since select fields are no longer text fields')
```

```
// If the select field is positioned below and there is no value, need to increment the last index
```

```
// by one since this select field removes the active item. Need to account for that here when there
```

```
* correctly add the `id` and `fixedTo` props if they are omitted from the child component's props.
```

```
// need to apply the _fixedTo for the select field
```

```
* An optional function to call when the `visible` prop is changed from `false` to `true`.
```

```
* the dialog should appear from.
```

```
* the dialog should appear from.
```

```
* Boolean if the Dialog should no longer try to prevent the parent container from scrolling while visible.
```

```
* dialog, it will attempt to prevent the parent dialog from scrolling.
```

```
* from state to state.
```

```
// import { Provider } from '../Modal'
```

```
query: __WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.object.isRequired
```

```
exports.push([module.i, "/*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css */\n\n/*
```

\* 1. Correct the line height in all browsers. 2. Prevent adjustments of font size after orientation changes in IE on Windows Phone and in iOS.

```
html {
  line-height: 1.15;
}
* 1
-ms-text-size-adjust: 100%;
* 2
-webkit-text-size-adjust: 100%;
* 2
```

Remove the margin in all browsers (opinionated).

```
body {
  margin: 0;
}
* 1
Add the correct display in IE 9.
```

```
article, aside, footer, header, nav, section {
  display: block;
}
* 1
Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.
```

```
h1 {
  font-size: 2em;
  margin: 0.67em 0;
}
* 1
Grouping content
```

Add the correct display in IE 9.

```
1. Add the correct display in IE.
figure, figure, main {
  display: block;
}
* 1
Add the correct margin in IE 8.
```

```
figure {
  margin: 1em 40px;
}
* 1
Add the correct box sizing in Firefox. 2. Show the overflow in Edge and IE.
```

```
hr {
  -webkit-box-sizing: content-box;
  box-sizing: content-box;
}
* 1
height: 0;
* 1
overflow: visible;
* 2
* 1
Correct the inheritance and scaling of font size in all browsers. 2. Correct the odd `em` font sizing in all browsers.
```

```
pre {
  font-family: monospace, monospace;
}
* 1
font-size: 1em;
* 2
```

1. Remove the gray background on active links in IE 10. 2. Remove gaps in links underline in iOS 8+ and Safari 8+.

```
na {
  background-color: transparent;
}
* 1
-webkit-text-decoration-skip: objects;
* 2
* 1
Remove the bottom border in Chrome 57- and Firefox 39-. 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.
```

```
abbr[title] {
  border-bottom: none;
}
* 1
text-decoration: underline;
* 2
-webkit-text-decoration: underline dotted;
text-decoration: underline dotted;
* 2
* 1
Prevent the duplicate application of `bolder` by the next rule in Safari 6.
```

```
nb, nstrong {
  font-weight: inherit;
}
* 1
Add the correct font weight in Chrome, Edge, and Safari.
```

```
nb, nstrong {
  font-weight: bolder;
}
* 1
Correct the inheritance and scaling of font size in all browsers. 2. Correct the odd `em` font sizing in all browsers.
```

```
ncode, nkbd, nsamp {
  font-family: monospace, monospace;
}
* 1
font-size: 1em;
* 2
* 1
Add the correct font style in Android 4.3-.
```

```
ndfn {
  font-style: italic;
}
* 1
Add the correct background and color in IE 9-.
```

```
nmark {
  background-color: #fff;
  color: #000;
}
* 1
Add the correct font size in all browsers.
```

```
nsmall {
  font-size: 80%;
}
* 1
Prevent `sub` and `sup` elements from affecting the line height in all browsers.
```

```
nsub, nsup {
  font-size: 75%;
  line-height: 0;
  position: relative;
  vertical-align: baseline;
}
nsub {
  bottom: -0.25em;
}
nsup {
  top: -0.5em;
}
* 1
Embedded content
```

Add the correct display in IE 9-.

```
audio, video {
  display: inline-block;
}
* 1
Add the correct display in iOS 4-7.
```

```
audio:not([controls]) {
  display: none;
  height: 0;
}
* 1
Remove the border on images inside links in IE 10-.
```

```
nimg {
  border-style: none;
}
* 1
Hide the overflow in IE.
```

```
nsvg:not(:root) {
  overflow: hidden;
}
* 1
Forms
```

1. Change the font styles in all browsers (opinionated). 2. Remove the margin in Firefox and

Safari.\n \*/\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*/\n font-size: 100%; /\* 1 \*/\n line-height: 1.15; /\* 1 \*/\n margin: 0; /\* 2 \*/\n}\n\n\*\*\n \* Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n \*/\n\nbutton,\ninput { /\* 1 \*/\n overflow: visible;\n}\n\n\*\*\n \* Remove the inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n \*/\n\nbutton,\nselect { /\* 1 \*/\n text-transform: none;\n}\n\n\*\*\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` \n \* controls in Android 4.\n \* 2. Correct the inability to style clickable types in iOS and Safari.\n \*/\n\nbutton,\nhtml [type="button"], /\* 1 \*/\n[type="reset"],\n[type="submit"] {\n -webkit-appearance: button; /\* 2 \*/\n}\n\n\*\*\n \* Remove the inner border and padding in Firefox.\n \*/\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n\*\*\n \* Restore the focus styles unset by the previous rule.\n \*/\n\nbutton:-moz-focusing,\n[type="button"]:-moz-focusing,\n[type="reset"]:-moz-focusing,\n[type="submit"]:-moz-focusing {\n outline: 1px dotted ButtonText;\n}\n\n\*\*\n \* Correct the padding in Firefox.\n \*/\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n\*\*\n \* 1. Correct the text wrapping in Edge and IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers are not caught out when they zero out \n \* `fieldset` elements in all browsers.\n \*/\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n color: inherit; /\* 2 \*/\n display: table; /\* 1 \*/\n max-width: 100%; /\* 1 \*/\n padding: 0; /\* 3 \*/\n white-space: normal; /\* 1 \*/\n}\n\n\*\*\n \* 1. Add the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*/\n\nprogress {\n display: inline-block; /\* 1 \*/\n vertical-align: baseline; /\* 2 \*/\n}\n\n\*\*\n \* Remove the default vertical scrollbar in IE.\n \*/\n\ntextarea {\n overflow: auto;\n}\n\n\*\*\n \* 1. Add the correct box sizing in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*/\n\n[type="checkbox"],\n[type="radio"] {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n padding: 0; /\* 2 \*/\n}\n\n\*\*\n \* Correct the cursor style of increment and decrement buttons in Chrome.\n \*/\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n height: auto;\n}\n\n\*\*\n \* 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in Safari.\n \*/\n\n[type="search"] {\n -webkit-appearance: textfield; /\* 1 \*/\n outline-offset: -2px; /\* 2 \*/\n}\n\n\*\*\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n \*/\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n -webkit-appearance: none;\n}\n\n\*\*\n \* 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2. Change font properties to `inherit` in Safari.\n \*/\n\n::-webkit-file-upload-button {\n -webkit-appearance: button; /\* 1 \*/\n font: inherit; /\* 2 \*/\n}\n\n/\* Interactive\n

=====  
\*\n\n\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in Edge, IE, and Firefox.\n \*/\n\n\*\n\n\*\n \* Add the correct display in all browsers.\n \*/\n\n\*\n\n\*\n \* Scripting\n

=====  
\*\n\n\*\*\n \* Add the correct display in IE 9-.\n \*/\n\n\*\n\n\*\n \* Add the correct display in IE.\n \*/\n\n\*\n\n\*\n \* Hidden\n

=====  
\*\n\n\*\*\n \* Add the correct display in IE 10-.\n \*/\n\n\*\n\n\*\n [hidden] {\n display: none;\n}\n\n", "",  
{ "version": 3, "sources": ["/home/ubuntu/ReactThumbSignIn/node\_modules/normalize.css/normalize.css"], "names": [], "mappings": "AAAA,4EAA4E;;AAE5E;gFACgF;;AAEhF;;;GAIG;;AAEH;EACE,kBAaKB,CAAC,OA

AO;EAC1B,2BAA2B,CAAC,OAAO;EACnC,+BAA+B,CAAC,OAAO;CACxC;;AAED;gFACgF;;AAEhF;;G  
AEG;;AAEH;EACE,UAAU;CACX;;AAED;;GAEG;;AAEH;;EAME,eAAe;CACHB;;AAED;;GAGG;;AAE  
H;EACE,eAAe;EACf,iBAAiB;CACIB;;AAED;gFACgF;;AAEhF;;GAGG;;AAEH;;OAE0,OAAO;EACZ,eA  
Ae;CACHB;;AAED;;GAEG;;AAEH;EACE,iBAAiB;CACIB;;AAED;;GAGG;;AAEH;EACE,gCAAgC;UACx  
B,wBAAwB,CAAC,OAAO;EACxC,UAAU,CAAC,OAAO;EACIB,kBAAkB,CAAC,OAAO;CAC3B;;AAED;;  
;GAGG;;AAEH;EACE,kCAAkC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED;gFACgF;;AA  
EhF;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,sCAAsC,CAAC,OAAO;CAC/C;;AAED;;GAG  
G;;AAEH;EACE,oBAAoB,CAAC,OAAO;EAC5B,2BAA2B,CAAC,OAAO;EACnC,0CAA0C;UACIC,kCAA  
kC,CAAC,OAAO;CACnD;;AAED;;GAEG;;AAEH;;EAEe,qBAAqB;CActB;;AAED;;GAEG;;AAEH;;EAEe,  
oBAAoB;CACrB;;AAED;;GAGG;;AAEH;;EAGE,kCAAkC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;C  
ACxB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,uBAAuB;EACvB,Y  
AAY;CACb;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;GAGG;;AAEH;;EAEe,eAAe;EACf,eAA  
e;EACf,mBAAmB;EACnB,yBAAyB;CAC1B;;AAED;EACE,gBAAgB;CACjB;;AAED;EACE,YAAY;CACb;;  
AAED;gFACgF;;AAEhF;;GAEG;;AAEH;;EAEe,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;EA  
Cd,UAAU;CACX;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,iBAAiB  
;CACIB;;AAED;gFACgF;;AAEhF;;GAGG;;AAEH;;EAKE,wBAAwB,CAAC,OAAO;EACHC,gBAAgB,CA  
AC,OAAO;EACxB,kBAAkB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;GAGG;;AAEH  
;QACQ,OAAO;EACb,kBAAkB;CACnB;;AAED;;GAGG;;AAEH;SACS,OAAO;EACd,qBAAqB;CActB;;A  
AED;;GAIG;;AAEH;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;EAIE,mBAAmB;  
EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;EAIE,+BAA+B;CACHC;;AAED;;GAEG;;AAEH;EACE,+  
BAA+B;CACHC;;AAED;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,eAAe,  
CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAAgB,CAAC,OAAO;EACxB,WAAW,CAAC,OAA  
O;EACnB,oBAAoB,CAAC,OAAO;CAC7B;;AAED;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,  
yBAAyB,CAAC,OAAO;CACIC;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHB;;AAED;;GAGG;;AAEH;;EA  
EE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AA  
EH;;EAEe,aAAa;CACd;;AAED;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAAqB,CAAC,O  
AAO;CAC9B;;AAED;;GAEG;;AAEH;;EAEe,yBAAyB;CAC1B;;AAED;;GAGG;;AAEH;EACE,2BAA2B,C  
AAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED;gFACgF;;AAEhF;;GAGG;;AAEH;;EAEe,eAAe;  
CACHB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;gFACgF;;AAEhF;;GAEG;;AAEH;EACE,  
sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED;gFACgF;;AAEhF;;GAEG;;AAEH;EAC  
E,cAAc;CACf","file":"normalize.css","sourcesContent":["/\*! normalize.css v7.0.0 | MIT License |  
github.com/necolas/normalize.css \*/\n\n/\* Document\n\n=====

\*\n\n\*\*\n \* 1. Correct the line height in all browsers.\n \* 2. Prevent adjustments of font size after orientation  
changes in\n \* IE on Windows Phone and in iOS.\n \*\nhtml {\n line-height: 1.15; /\* 1 \*\n-ms-text-size-adjust: 100%; /\* 2 \*\n-webkit-text-size-adjust: 100%; /\* 2 \*\n}\n\n/\* Sections\n\n=====

\*\n\n\*\*\n \* Remove the margin in all browsers (opinionated).\n \*\nbody {\n margin: 0;\n}\n\n\*\*\n \* Add  
the correct display in IE 9-.\n \*\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display:  
block;\n}\n\n\*\*\n \* Correct the font size and margin on `h1` elements within `section` and\n \* `article`  
contexts in Chrome, Firefox, and Safari.\n \*\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping  
content\n\n=====

```

*^n/n/**^n * Add the correct display in IE 9-.^n * 1. Add the correct display in IE.^n
*^n/nfigcaption,^nfigure,^nmain { /* 1 *^n display: block;^n}^n/n/**^n * Add the correct margin in IE 8.^n
*^n/nfigure {^n margin: 1em 40px;^n}^n/n/**^n * 1. Add the correct box sizing in Firefox.^n * 2. Show the
overflow in Edge and IE.^n *^n/n/hr {^n -webkit-box-sizing: content-box;^n box-sizing: content-box; /* 1
*^n height: 0; /* 1 *^n overflow: visible; /* 2 *^n}^n/n/**^n * 1. Correct the inheritance and scaling of font
size in all browsers.^n * 2. Correct the odd `em` font sizing in all browsers.^n *^n/n/pre {^n font-family:
monospace, monospace; /* 1 *^n font-size: 1em; /* 2 *^n}^n/n/* Text-level semantics^n
=====

*^n/n/**^n * 1. Remove the gray background on active links in IE 10.^n * 2. Remove gaps in links underline in
iOS 8+ and Safari 8+.^n *^n/n/a {^n background-color: transparent; /* 1 *^n -webkit-text-decoration-skip:
objects; /* 2 *^n}^n/n/**^n * 1. Remove the bottom border in Chrome 57- and Firefox 39-.^n * 2. Add the
correct text decoration in Chrome, Edge, IE, Opera, and Safari.^n *^n/n/abbr[title] {^n border-bottom: none; /*
1 *^n text-decoration: underline; /* 2 *^n -webkit-text-decoration: underline dotted;^n text-decoration:
underline dotted; /* 2 *^n}^n/n/**^n * Prevent the duplicate application of `bolder` by the next rule in Safari
6.^n *^n/n/b,^nstrong {^n font-weight: inherit;^n}^n/n/**^n * Add the correct font weight in Chrome, Edge, and
Safari.^n *^n/n/b,^nstrong {^n font-weight: bolder;^n}^n/n/**^n * 1. Correct the inheritance and scaling of font
size in all browsers.^n * 2. Correct the odd `em` font sizing in all browsers.^n *^n/n/code,^nkbd,^nsamp {^n
font-family: monospace, monospace; /* 1 *^n font-size: 1em; /* 2 *^n}^n/n/**^n * Add the correct font style in
Android 4.3-.^n *^n/n/dfn {^n font-style: italic;^n}^n/n/**^n * Add the correct background and color in IE 9-.^n
*^n/n/mark {^n background-color: #ff0;^n color: #000;^n}^n/n/**^n * Add the correct font size in all
browsers.^n *^n/n/small {^n font-size: 80%;^n}^n/n/**^n * Prevent `sub` and `sup` elements from affecting the
line height in^n * all browsers.^n *^n/n/sub,^nsup {^n font-size: 75%;^n line-height: 0;^n position: relative;^n
vertical-align: baseline;^n}^n/n/sub {^n bottom: -0.25em;^n}^n/n/sup {^n top: -0.5em;^n}^n/n/* Embedded
content^n
=====

*^n/n/**^n * Add the correct display in IE 9-.^n *^n/n/audio,^nvideo {^n display: inline-block;^n}^n/n/**^n *
Add the correct display in iOS 4-7.^n *^n/n/audio:not([controls]) {^n display: none;^n height: 0;^n}^n/n/**^n *
Remove the border on images inside links in IE 10-.^n *^n/n/img {^n border-style: none;^n}^n/n/**^n * Hide the
overflow in IE.^n *^n/n/svg:not(:root) {^n overflow: hidden;^n}^n/n/* Forms^n
=====

*^n/n/**^n * 1. Change the font styles in all browsers (opinionated).^n * 2. Remove the margin in Firefox and
Safari.^n *^n/n/button,^ninput,^noptgroup,^nselect,^ntextarea {^n font-family: sans-serif; /* 1 *^n font-size:
100%; /* 1 *^n line-height: 1.15; /* 1 *^n margin: 0; /* 2 *^n}^n/n/**^n * Show the overflow in IE.^n * 1.
Show the overflow in Edge.^n *^n/n/button,^ninput { /* 1 *^n overflow: visible;^n}^n/n/**^n * Remove the
inheritance of text transform in Edge, Firefox, and IE.^n * 1. Remove the inheritance of text transform in
Firefox.^n *^n/n/button,^nselect { /* 1 *^n text-transform: none;^n}^n/n/**^n * 1. Prevent a WebKit bug where
(2) destroys native `audio` and `video`^n * controls in Android 4.^n * 2. Correct the inability to style clickable
types in iOS and Safari.^n *^n/n/button,^nhtml [type="button"], /* 1 *^n[type="reset"],^n[type="submit"]
{^n -webkit-appearance: button; /* 2 *^n}^n/n/**^n * Remove the inner border and padding in Firefox.^n
*^n/n/button::-moz-focus-inner,^n[type="button"]::-moz-focus-inner,^n[type="reset"]::-moz-focus-inner,^n[ty
pe="submit"]::-moz-focus-inner {^n border-style: none;^n padding: 0;^n}^n/n/**^n * Restore the focus styles
unset by the previous rule.^n
*^n/n/button:-moz-focusing,^n[type="button"]:-moz-focusing,^n[type="reset"]:-moz-focusing,^n[type="su

```

```
bmit\"):moz-focusing {\n  outline: 1px dotted ButtonText;\n}\n\n/**\n * Correct the padding in Firefox.\n */\n\nfieldset {\n  padding: 0.35em 0.75em 0.625em;\n}\n\n/**\n * 1. Correct the text wrapping in Edge and IE.\n * 2. Correct the color inheritance from `fieldset` elements in IE.\n * 3. Remove the padding so developers are not caught out when they zero out\n *    `fieldset` elements in all browsers.\n */\n\nlegend {\n  -webkit-box-sizing: border-box;\n  box-sizing: border-box; /* 1 */\n  color: inherit; /* 2 */\n  display: table;\n  /* 1 */\n  max-width: 100%; /* 1 */\n  padding: 0; /* 3 */\n  white-space: normal; /* 1 */\n}\n\n/**\n * 1. Add the correct display in IE 9-.\n * 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n */\n\nprogress {\n  display: inline-block; /* 1 */\n  vertical-align: baseline; /* 2 */\n}\n\n/**\n * Remove the default vertical scrollbar in IE.\n */\n\ntextarea {\n  overflow: auto;\n}\n\n/**\n * 1. Add the correct box sizing in IE 10-.\n * 2. Remove the padding in IE 10-.\n */\n\n[type="checkbox"],\n[type="radio"] {\n  -webkit-box-sizing: border-box;\n  box-sizing: border-box; /* 1 */\n  padding: 0; /* 2 */\n}\n\n/**\n * Correct the cursor style of increment and decrement buttons in Chrome.\n */\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n  height: auto;\n}\n\n/**\n * 1. Correct the odd appearance in Chrome and Safari.\n * 2. Correct the outline style in Safari.\n */\n\n[type="search"] {\n  -webkit-appearance: textfield; /* 1 */\n  outline-offset: -2px; /* 2 */\n}\n\n/**\n * Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n */\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n  -webkit-appearance: none;\n}\n\n/**\n * 1. Correct the inability to style clickable types in iOS and Safari.\n * 2. Change font properties to `inherit` in Safari.\n */\n\n::-webkit-file-upload-button {\n  -webkit-appearance: button; /* 1 */\n  font: inherit; /* 2 */\n}\n\n/* Interactive\n
```

```
=====\n\n\n/*\n * Add the correct display in IE 9-.\n * 1. Add the correct display in Edge, IE, and Firefox.\n */\n\ndetails, /* 1 */\nmenu {\n  display: block;\n}\n\n/*\n * Add the correct display in all browsers.\n */\n\nsummary {\n  display: list-item;\n}\n\n/* Scripting\n
```

```
=====\n\n\n/*\n * Add the correct display in IE 9-.\n */\n\ncanvas {\n  display: inline-block;\n}\n\n/**\n * Add the correct display in IE.\n */\n\ntemplate {\n  display: none;\n}\n\n/* Hidden\n
```

```
=====\n\n\n/*\n * Add the correct display in IE 10-.\n */\n\n[hidden] {\n  display: none;\n}\n\n", "sourceRoot": "" }));
```

```
  user = _props.user,
```

```
    user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
```

```
    user.isLoggedin && __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
```

```
    user.isLoggedin ? __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(
```

```
  user: {
```

```
    isLoggedIn: !userInfo.isLoading ? userInfo.data.isLoggedIn : ownProps.query.isLoggedIn,
```

```
    * `Indeterminate`, and `Query Indeterminate`.
```

```
    * A `Query Indeterminate` linear progress bar is used when you are combining
```

```
    * as a query indeterminate progress bar by adding the prop `query={true}` to the
```

```
    * component. Until a progress value is given, it will display the query linear
```

```
    * progress animation. Afterwards, it will start the determinate animation of where
```

```
    query = _props.query,
```

```
    props = _objectWithoutProperties(_props, ['className', 'progressClassName', 'progressStyle', 'value',
```

```
    'query', 'centered']));
```



```

    'md-progress--linear-query': query,
    * region until it is finished loading. It is not possible for the user to alter the value of a progressbar
    * Boolean if this should be a query indeterminate progress bar.
query: _propTypes2.default.bool,
query: false
    * region until it is finished loading. It is not possible for the user to alter the value of a progressbar
    * Removes observer from observers list.
    * Updates every observer from observers list and notifies them of queued
      // has the "ownerDocument" property from which we can retrieve a
      // Return the local global object if it's not possible extract one from
    * Extracts borders size from provided styles.
    * Extracts paddings sizes from provided styles.
    * from the corresponding properties of the last observed content rectangle.
    * instances collected from active resize observations.
    * The layover will appear by transitioning from the top left and expand
    * The layover will appear by transitioning from the top right and expand
    * The layover will appear by transitioning from the bottom left and expand
    * The layover will appear by transitioning from the bottom right and expand
    * The layover will appear by just transitioning downwards from the bottom
    * where a `false` value will mean it is out of the viewport for that
      className: __WEBPACK_IMPORTED_MODULE_2_classnames___default()('md-divider--text-field
md-divider--expand-from-' + lineDirection, {
var FOCUSABLE_QUERY = ['button', 'textarea', 'select'].reduce(function (queryString, element) {
    throw new Error('You specified that the `FocusContainer` should focus an element on mount, ' + 'but a
focusable element was not found in the children. This could be because ' + 'the `initialFocus` prop is an invalid
id or query selector, or the children ' + ('do not contain a valid focusable element.' + debugError));
    * An optional id string or a query selector string to use for the initial focus.
    * that appears from the side of a screen.
    * Simply does a `window.matchMedia(query)` where the query gets defined as a min width
    * @param {number} min - The min width for the media query.
    * @param {number=} max - An optional max width to include for the media query.
    * media query.
    * The min-width to use for the mobile media query.
    * media query.
    * The min-width to use for the tablet media query.
    * query.
    * The `$md-drawer-transition-time` value from sass.
    * the drawer will close when a user clicks anywhere on the page except in the drawer.
    * the page to get the main focus on the drawer. When the user touches the overlay or
      // I honestly don't remember why this was implemented, but it was copied from the Button
    * Boolean if the theming should be swapped from text to background or vice-versa.
    * be triggered when the user selects a new file or cancels the new file selection.
    * `input` tag, the user will not be able to select the same file multiple times unless

```

- \* > NOTE: If the user hits cancel, null will be given for a single file input.

label: 'Select a file',

- \* Boolean if all the gutters and spacing should be removed from the grid.

className: \_\_WEBPACK\_IMPORTED\_MODULE\_2\_classnames\_\_\_default()('md-title md-title--toolbar md-select-field--toolbar', {

- \* `type="submit"`, the `ComposedComponent` is in a form, and the user hits the `enter` key
  - \* The ink can either be created by using the `pageX` and `pageY` from a click/touch event
  - \* use case where `Switches` needed the ink disabled only when using a mouse.

// Inject from injectTooltip

// We need to check all keys in case some are required but missing from

// fail the render phase where it didn't fail before. So we log it.

'it must be a function, usually from the `prop-types` package, but received `' + typeof

typeSpecs[typeSpecName] + `.`'

- \* @param {object} prev prev children as returned from
- \* @param {object} next next children as returned from
  - // TODO: when config is {a: 10} and dest is {a: 10} do we raf once and
  - // changed from 0 to 400 to spring(0) again, the async currentStyle is still
  - // TODO: when config is {a: 10} and dest is {a: 10} do we raf once and
  - // changed from 0 to 400 to spring(0) again, the async currentStyle is still
  - // Array<TransitionPlainStyle>, where each TransitionPlainStyle is of the format
  - // turn current (interpolating) style from {a, b} into {a?, b, c}
  - // TODO: key search code
  - // TODO: when config is {a: 10} and dest is {a: 10} do we raf once and
  - // TODO: key search code
- // that you've unmounted but that's still animating. This is where it lives
- // changed from 0 to 400 to spring(0) again, the async currentStyle is still
- // this reduces to merging two partially ordered lists (e.g. lists where not
  - // merge in keys that the user desires to kill
  - // a period where rootNode briefly equals null.
  - // can leave a period where rootNode briefly equals null.
- \* This is useful when you want to prohibit the user from changing slides.
- \* This will allow the user to perform the relevant swipe actions with a mouse.
- \* should user swipe to switch slide.
- \* component when the shown slide change after a swipe made by the user.
- \* Gets the current value from the text field. This is used when you have an uncontrolled
- \* text field and simply need the value from a ref callback.
- \* A single key or an array of keys to delete from your data object before passing
- \* This will be triggered when the window is clicked or when a user tabs away from
- \* The list's z-depth for applying box shadow. This should be a number from 0 to 5.
- \* triggered when the user presses enter anywhere in the form.
  - \* Creates an ink from pageX and pageY coordinates. These values should either come
  - \* from the `changedTouches` or just the base event (if clicked). These coordinates
  - \* are used to position the ink correctly in the container from touch/click point.

- \* If either value is undefined, an ink will be created from the center of the
  - \* Creates an ink from pageX and pageY coordinates. These values should either come
  - \* from the `changedTouches` or just the base event (if clicked). These coordinates
  - \* are used to position the ink correctly in the container from touch/click point.
  - \* If either value is undefined, an ink will be created from the center of the
  - \* Removes an ink from the container.
  - \* Sets the ink container and the main container from the ref callback. When the component
  - \* @param {Object} el - The element to get a scroll value from.
  - \* Boolean if the bottom navigation should dynamically appear based on scrolling. When the user
  - \* The distance a user must scroll before the bottom navigation appears or disappears when it is `dynamic`.
  - \* to the `checkedCheckboxIcon` prop from the `SelectionControl`.
  - \* to the `uncheckedCheckboxIcon` prop from the `SelectionControl`.
  - \* so that when a user scrolls to the right, they will always be able to use the
- inputClassName:

\_\_WEBPACK\_IMPORTED\_MODULE\_2\_classnames\_\_default()('md-select-field--pagination',  
selectFieldInputClassName),

- \* An optional id to provide to the select field. If this is omitted, it will be
  - \* An optional style to apply to the select field.
  - \* An optional className to apply to the select field.
  - \* An optional style to apply to the select field's input.
  - \* An optional className to apply to the select field's input.
  - \* Boolean if the select field should use the simplified menu logic.
  - \* A function to call when a user clicks the increment or decrement pagination
  - \* The current value for the select field holding the number of rows per page.
  - \* Pages start from 1 instead of 0.
  - \* The default page to start from for the pagination. Pages start from 1 instead of 0.
  - \* display and determine if the user can increment/decrement again.
- { style: style, className:

\_\_WEBPACK\_IMPORTED\_MODULE\_2\_classnames\_\_default()('md-select-field\_\_toggle', className) },  
className: 'md-divider--select-field'

className: \_\_WEBPACK\_IMPORTED\_MODULE\_2\_classnames\_\_default()('md-select-field',  
Object(\_\_WEBPACK\_IMPORTED\_MODULE\_4\_utils\_themeColors\_\_["a" /\* default \*/])(  
'md-select-field--text-field': !below,  
'md-select-field--btn': below

- \* An optional function to call when the "Ok" button has been clicked, the user presses enter
- \* on \* the text field or when the `okOnOutsideClick` prop has been enabled and the user clicks
- \* An optional function to call when a user clicks out of the text field.
- \* Boolean if the edit dialog should be closed if the user clicks somewhere else on the page
- \* See the [SelectField](/components/select-fields?tab=1#select-field-proptypes) for remaining prop descriptions.

className: \_\_WEBPACK\_IMPORTED\_MODULE\_2\_classnames\_\_default()('md-select-field-column',  
className),

- \* An optional id to use for the select field in the column. If this is omitted, it's value will be

- \* ``${rowId}-${cellIndex}-select-field``
- \* The is the optional style to apply to the select field's menu container.
- \* The is the optional class name to apply to the select field's menu container.
- \* This is how the select field should be fixed within the table. When this is omitted,
- \* it will automatically use the responsive table as the fixture so that the select field
- \* Boolean if the select field should span the entire width of the column.
- \* The position for the select field.

```
/* unused harmony default export */ var _unused_webpack_default_export =
(Object(__WEBPACK_IMPORTED_MODULE_7__withTableFixes__["a" /* default */])(SelectFieldColumn,
'select-field'));
```

- \* This is how the select field should be fixed within the table. When this is omitted,
- \* it will automatically use the responsive table as the fixture so that the select field
- \* This is how the select field should be fixed within the table. When this is omitted,
- \* it will automatically use the responsive table as the fixture so that the select field
- \* a user selects a row.
- \* contextual header once the user has selected a row or multiple rows.
- \* @param {string|Object=} selector - An optional query selector string to use to select an element.
  - // Hopefully a nice warning about fixing the missing props injected from ExpansionList
  - console.error('The `ExpansionPanel` component expects the `columnWidths` prop to be injected from the '
 + `ExpansionList` component. It could be missing because:' + '\n - you have a wrapper component with extra
 functionality' + '\n - the `ExpansionPanel` is not a direct child of the `ExpansionList` component' + '\n\nYou can
 fix this by making sure to pass `this.props.focused` and `this.props.columnWidths` ' + 'within your wrapper
 component and making the `ExpansionPanel` a direct child of `ExpansionList`.');
- \* can also be toggled from the `ExpansionList` component if all `ExpansionPanel` in the list
- \* So if the size changes from 80 -> 120 -> 160 -> 140. It will only update on the third resize (160)
- \* file that is uploading. Unreliable for multi-select.
- \* Boolean if all the gutters and spacing should be removed from the grid.
- \* The min width to use for a mobile media query. This prop should match the `md-mobile-min-width`
- \* The media query for a mobile device will be:
- \* The min width to use for a tablet media query. This prop should match the `md-tablet-min-width`
- \* The media query for a tablet device will be:
- \* The min width to use for a desktop media query. This prop should match the `md-desktop-min-width`
- \* The media query for a tablet device will be:
- \* A boolean if the mini drawer's list should be generated from the `navItems` prop. When building
- \* the list, it will extract the `leftIcon` or `leftAvatar` from the `navItem` and then create a
- \* An optional select field menu to display in the main toolbar. Either the `toolbarTitle` or the
 ``toolbarTitleMenu``
- \* The label to use for a keyboard accessibility link that jumps all the navigation and allows a user to focus

- \* import { DatePicker } from 'react-md/lib/Pickers';
- \* import DatePicker from 'react-md/lib/Pickers/DatePickerContainer';
- \* Gets the current value from the date picker as a formatted string.
- \* A function to format the dates since it should be formatted to the user's
- \* the user's language in the browser or `en-US` when server rendering.

- \* Boolean if the date should automatically be selected when a user clicks
- \* The direction that the text field divider expands from when the text field
- \* Boolean if the dialog should be able to close if a keyboard user presses the escape key.
- \* Boolean if the DatePicker should be read only. This will prevent the user from opening the picker
- \* True if dates from adjacent months should be shown in calendar.
- \* Boolean if the dates from adjacent months should be disabled. This will only
- \* clickable until the user switches to that month.
- \* An optional className to apply to a date from an adjacent month in calendar. This will be applied
- \* True if dates from adjacent months should be shown in calendar.
- \* An optional className to apply to a date from an adjacent month in calendar.
- \* current year and the current date. It allows the user to switch
- \* True if dates from adjacent months should be shown.
- \* An optional className to apply to a date from an adjacent month.
- \* A function to call that will select a new date.
- \* True if dates from adjacent months should be shown.
- \* An optional className to apply to a date from an adjacent month.
- \* Removes all the time parts (hours, minutes, seconds, milliseconds) from a date.
- \* will display a list of years to select from within the given range.
  - \* @param {Object} props - The current props to extract the year range from.
- \* import { TimePicker } from 'react-md/lib/Pickers';
- \* import TimePicker from 'react-md/lib/Pickers/TimePickerContainer';
  - \* A function to format the dates since it should be formatted to the user's
  - \* the user's language in the browser or `en-US` when server rendering.
  - \* Boolean if the date should automatically be selected when a user clicks
  - \* The direction that the text field divider expands from when the text field
  - \* Boolean if the dialog should be able to close if a keyboard user presses the escape key.
  - \* Boolean if the TimePicker should be read only. This will prevent the user from opening the picker
- 'aria-label': 'Select a time',
- \* Extracts the hours, minutes, and optional time period from
- \* @param {Date} time the time to extract from.
  - \* A function that will switch the state from hour to minute.
  - \* the user selects ok. This function will be given a new Date object
  - \* A string that is a representation of the hours in the user's locale.
  - \* A string that is a representation of the minutes in the user's locale.
  - \* A string that is a representation of the seconds in the user's locale.
  - \* An optional time period if a user's locale uses it.
- \* Takes a point from a mouse or touch event and a center point of a circle to determine
  - className: \_\_WEBPACK\_IMPORTED\_MODULE\_2\_classnames\_\_\_default()('md-clock-time
- md-text-no-select md-pointer--none', {
  - \* A formatted hours string for the user's locale. This
  - \* A formatted minutes string for the user's locale.
  - \* A formatted seconds string for the user's locale.
  - \* region until it is finished loading. It is not possible for the user to alter the value of a progressbar

- \* `Indeterminate`, and `Query Indeterminate`.
- \* A `Query Indeterminate` linear progress bar is used when you are combining
- \* as a query indeterminate progress bar by adding the prop `query={true}` to the
- \* component. Until a progress value is given, it will display the query linear
- \* progress animation. Afterwards, it will start the determinate animation of where
 

```

      query = _props.query,
      props = _objectWithoutProperties(_props, ['className', 'progressClassName', 'progressStyle', 'value',
'query', 'centered']);
      'md-progress--linear-query': query,
      
```
- \* region until it is finished loading. It is not possible for the user to alter the value of a progressbar
- \* Boolean if this should be a query indeterminate progress bar.

query: \_\_WEBPACK\_IMPORTED\_MODULE\_1\_prop\_types\_\_\_default.a.bool,  
 query: false

- \* The `SelectionControl` will inherit any inheritable props from the `SelectionControlGroup`.
- \* The `Checkbox` component is used for the selection of multiple options from a set.
  - \* value can be found from `document.querySelector('input[name="someName[]"]').value`.
- \* The `Radio` component is used for the selection of a single option from a set. Unfortunately
- \* The `Slider` component is used to let users select a value from a continuous
- \* When the user has finished dragging the Slider or increments the value by using
  - \* - The user does a quick jump
  - \* - The user stops dragging with the mouse
  - \* - The user drops dragging with touch
- \* @param {Object} e - The current event to extract an x location from
- \* This will either allow a user to start dragging the slider or quickly
- \* This will set the active state of the slider to false if the user
- \* where the event can either be:
  - \* This is only called when the user is dragging the slider with either
  - \* The incremental amount when the user hits left or right with the
  - \* keyboard arrows, or the user hits the up or down buttons in the
- \* This calculates the distance from a screen x location to a position in some element
- \* @return {Number} the distance from the element's left position to the page x
- \* The `Snackbar` component is used for displaying a concise and small message to the user about
  - \* The snackbar will always display the first toast in this list. When the user has
 

```

          return new Error('Invalid ' + location + '`' + propFullNameSafe + ` supplied to ` + componentNameSafe +
`, expected a ' + 'ref to a floating `Button` component. This should not be a DOMElement from
`findDOMNode` but instead ' + 'the React ref object.');
```
- // Only style we really want from the .md-snackbar
- \* height, separated by white space and/or a comma, which specify a rectangle in user
- \* `viewBox="0 0 25 20"`, the coordinates inside the SVG will go from the top left corner
- \* the `children` from each tab, and render them in a swipeable container. However,
  - \* @see <https://github.com/oliviertassinari/react-swipeable-views#user-content-swipeableviews->
  - \* @see <https://github.com/oliviertassinari/react-swipeable-views#user-content-swipeableviews->
  - \* `label` and `children` from a custom `Tab` component.

- \* An id for a `TabPanel` that holds the children from this tab. This is required for all.
- \* Gets the current value from the text field. This is used when you have an uncontrolled text field and simply need the value from a ref callback.
- \* floating labels and remove the text divider from the component.
- \* this will only be visible when there is no value and the user focused the text field.
- \* Boolean if the text field is required. If the user blurs the text field while there is
- \* The direction that the underline should appear from.
- \* required and the user blurs the text field with no value.
- \* The ink when there is an injectInk above the text field. Used from the SelectField.  
`text = Array.from(Array(value.length)).reduce(function (s) {  
 className: (0, _classnames2.default)('md-divider--text-field md-divider--expand-from-' + lineDirection, {`
- \* triggered when the user presses enter anywhere in the form.
- \* Creates an ink from pageX and pageY coordinates. These values should either come
- \* from the `changedTouches` or just the base event (if clicked). These coordinates
- \* are used to position the ink correctly in the container from touch/click point.
- \* If either value is undefined, an ink will be created from the center of the
- \* Creates an ink from pageX and pageY coordinates. These values should either come
- \* from the `changedTouches` or just the base event (if clicked). These coordinates
- \* are used to position the ink correctly in the container from touch/click point.
- \* If either value is undefined, an ink will be created from the center of the
- \* Removes an ink from the container.
- \* Sets the ink container and the main container from the ref callback. When the component  
`var user = this.props.user;  
 return !user.isLoggedin ? __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(  
 user: {  
 name: !userInfo.isLoading ? userInfo.data.name : ownProps.query.user.name,  
 isLoggedin: !userInfo.isLoading ? userInfo.data.isLoggedin : ownProps.query.user.isLoggedin,  
 var user = this.props.user;  
 'Price/User/Month'  
 !user.isLoggedin ? __WEBPACK_IMPORTED_MODULE_0_react___default.a.createElement(  
 user: {  
 name: !userInfo.isLoading ? userInfo.data.name : ownProps.query.user.name,  
 isLoggedin: !userInfo.isLoading ? userInfo.data.isLoggedin : ownProps.query.user.isLoggedin,`

31-<https://stage.thumbsignin.com/assets/features.chunk.js>

Other Information: `query: '{\n user {\n isLoggedin\n } \n }'`  
`{ query: data, __source: {`

- \* @param {string=} field - the field to extract a value from. Defaults to 'value'.  
 // this implementation is not 100% perfect for weird media query combinations
- // Adapted from convert-source-map (MIT)
- \* // Remove it from the DOM
- // bind timers to global for call from export context
- \* An ink from `injectInk`.

- \* A tooltip from `injectTooltip`  
return new Error('Only one material design button type may be specified in the ` ` + component + ` ` but ` ` + len + ` ` + `were given. Select only one of `flat`, `raised`, `icon`, or `floating`.');
- \* where the component should be switched to something else for valid html.
- // Thrash, waste and sodomy: IE GC bug
- // IE 8- don't enum bug keys
- \* The list's z-depth for applying box shadow. This should be a number from 0 to 5.
- \* closing when a list item has been clicked, or the user presses escape.
- \* Gets the current value from the text field. This is used when you have an uncontrolled
- \* text field and simply need the value from a ref callback.
- \* floating labels and remove the text divider from the component.
- \* this will only be visible when there is no value and the user focused the text field.
- \* Boolean if the text field is required. If the user blurs the text field while there is
- \* The direction that the underline should appear from.
- \* required and the user blurs the text field with no value.
- \* The ink when there is an injectInk above the text field. Used from the SelectField.  
text = Array.from(Array(value.length)).reduce(function (s) {
- \* Prevents a second warning from appearing when using the deprecated or allly required
- \* Gets the current checked value from the selection control. This is used when you have
- \* an uncontrolled selection control and simply need the checked state from a ref callback.
- \* in `[]` so that the value can be found from `document.querySelector('input[name="someName[]"]').value`.
- 'md-table-column--select-field': selectColumnHeader
- \* additional styling to the column to position with the select field.  
err = new Error('You provided a ` ` + propFullNameSafe + ` ` + location + ` ` to the ` ` + componentNameSafe + ` ` that was ` ` + (not within the range from ` ` + min + ` ` - ` ` + max + ` `. ` ` + propFullNameSafe + ` `: ` ` + value + ` `));
- // Don't enum bug & hidden keys
- // getting tag from 19.1.3.6 Object.prototype.toString()
- // TODO: we could get rid of the need for the wrapper node
- // factoryChild is not different from child.
- \* The `AccessibleFakeButton` allows the user to tab focus the element, use the
- \* An optional onClick function to call when the user clicks the
- \* The ink when coming from the AccessibleFakeInkedButton  
err = new Error('You provided a ` ` + propFullNameSafe + ` ` + location + ` ` to the ` ` + componentNameSafe + ` ` that was ` ` + (not within the range from ` ` + min + ` ` - ` ` + max + ` `. ` ` + propFullNameSafe + ` `: ` ` + value + ` `));
- \* @param {Object} obj - The object to omit keys from.
- \* This is used for some lists where only a parent contains the icon.
- \* The nested items will be visible once the user clicks on the `ListItem`.  
// callbacks from appending listeners
- \* Boolean if the layover should fill the height of the viewport from the current calculated `top`. This will just
- \* iOS does not subtract the soft keyboard from the viewport's size so the list will still extend to the bottom
- \* This is the position that the children should animate from. It directly ties into
- \* This is really only helpful in cases where the layover can't calculate things correctly due to  
// The init function can be called again if the user quickly toggles the layover. If that



- \* Attempts to find the base table component from an element in the table.
- \* @param {Object} el - The element to traverse from
 

```

      return fetch('/api/user').then(function (response) {
        return fetch('/api/user', { method: "POST", body: userInfo }).then(function (response) {

```
- // cached from whatever global is present so that test runners that stub it
- \* `type="submit"`, the `ComposedComponent` is in a form, and the user hits the `enter` key
  - \* The ink can either be created by using the `pageX` and `pageY` from a click/touch event
  - \* use case where `Switches` needed the ink disabled only when using a mouse.
- this.\_field = this.\_container.querySelector('.md-select-field');
- \* Gets the current value from the select field. This is used when you have an uncontrolled
- \* text field and simply need the value from a ref callback.
- \* @return {String} the select field's value
 

```

      className: __WEBPACK_IMPORTED_MODULE_3_classnames___default()('md-menu--select-field',
className),

```
- \* An id to give the select field. This is required for accessibility.
- \* An optional name to give to the select field.
- \* An optional id to provide to the select field's menu. If this is omitted,
- \* An optional id to provide to the select field's list.
- \* An optional style to apply to the select field's container (the menu).
- \* An optional className to apply to the select field's container (the menu).
- \* An optional style to apply to the select field's toggle.
- \* An optional className to apply to the select field's toggle.
- \* for the select field.
- \* for the select field.
- \* Boolean if the select field should have the menu's list visible by default.
- \* Boolean if the select field should have the menu's list visible. This will make
- \* the select field controlled and require the `onVisibilityChange` prop to be defined,
- \* An optional function to call when the select field's menu has its visibility changed. The callback
- \* while typing. Since a user can select items by typing multiple letters in a row,
- \* - User types `g`
- \* - User delays 200ms and types `u`
- \* - User delays 1000ms and types `a`.
- \* The default value to use for the select field. If this is set, it should either match
- \* The value to use for the select field. If this is defined, it becomes a controlled component
- \* An optional function to call when the select field's value has been changed either when the user
- \* has click/touched/keyboard selected a value in the list, or the user has selected a value by typing
- \* in the select field while the menu's list is closed.
- \* triggered the change, and the id, name, and value of the select field.
- \* An optional label to use with the select field. This will be a floating label as seen on the text field.
- \* An optional placeholder to use in the select field. This will only appear when no value has been selected.
- \* Boolean if the select field should be disabled.
- \* Boolean if the select field is required. This will update the label and placeholder to include a `\*` suffix.
- \* Boolean if the select field is considered to be in an `error` state.

- \* An optional text to display when the text select field is in an error state.
- \* An optional text to display below the select field to provide input help to the user.
- \* This will only be displayed if the select field is not in an error state.
- \* An optional function to call when any element in the select field has been clicked.
- \* select field.
- \* An optional function to call when the select field's toggle has gained focus.
- \* An optional function to call when the select field's toggle has been blurred. This
- \* will be triggered if the user hits the up or down arrow keys to traverse the list
- \* Boolean if the select field is in a toolbar. This should automatically be injected by the `Toolbar`
- \* Boolean if the currently active item should be removed from the list of available `menuItems`.
- \* new item `_drop_` into the select field's input location.
- \* This is how the menu's `List` gets anchored to the select field.
- \* The list's z-depth for applying box shadow. This should be a number from 0 to 5.
- \* any unnecessary props from the `ListItem` itself. This is where you
- \* The direction that the underline should appear from.

floatingLabel:

```
__WEBPACK_IMPORTED_MODULE_4__react_prop_types_lib_deprecated___default()(__WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.bool, 'A select field can only have floating labels now. Only provide the `label` prop'),
```

noAutoAdjust:

```
__WEBPACK_IMPORTED_MODULE_4__react_prop_types_lib_deprecated___default()(__WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.bool, 'No longer valid to use since select fields are no longer text fields'),
```

adjustMinWidth:

```
__WEBPACK_IMPORTED_MODULE_4__react_prop_types_lib_deprecated___default()(__WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.bool, 'No longer valid to use since select fields are no longer text fields')
```

```
// If the select field is positioned below and there is no value, need to increment the last index
```

```
// by one since this select field removes the active item. Need to account for that here when there
```

```
* correctly add the `id` and `fixedTo` props if they are omitted from the child component's props.
```

```
// need to apply the _fixedTo for the select field
```

```
* An optional function to call when the `visible` prop is changed from `false` to `true`.
```

```
* the dialog should appear from.
```

```
* the dialog should appear from.
```

```
* Boolean if the Dialog should no longer try to prevent the parent container from scrolling while visible.
```

```
* dialog, it will attempt to prevent the parent dialog from scrolling.
```

```
* from state to state.
```

```
// import { Provider } from '../Modal'
```

```
query: __WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.object.isRequired
```

```
exports.push([module.i, "/*! normalize.css v7.0.0 | MIT License | github.com/necolas/normalize.css *\n\n/* Document\n
```

```
=====
```

```
*\n\n**\n * 1. Correct the line height in all browsers.\n * 2. Prevent adjustments of font size after orientation
```

changes in\n \* IE on Windows Phone and in iOS.\n \*/\n\nhtml {\n line-height: 1.15; /\* 1 \*/\n -ms-text-size-adjust: 100%; /\* 2 \*/\n -webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n

=====  
\n\n\*\*\n \* Remove the margin in all browsers (opinionated).\n \*/\n\nbody {\n margin: 0;\n}\n\n\*\*\n \* Add the correct display in IE 9-.\n \*/\n\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display: block;\n}\n\n\*\*\n \* Correct the font size and margin on `h1` elements within `section` and `article` contexts in Chrome, Firefox, and Safari.\n \*/\n\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping content\n

=====  
\n\n\*\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in IE.\n \*/\n\nfigcaption,\nfigure,\nmain { /\* 1 \*/\n display: block;\n}\n\n\*\*\n \* Add the correct margin in IE 8.\n \*/\n\nfigure {\n margin: 1em 40px;\n}\n\n\*\*\n \* 1. Add the correct box sizing in Firefox.\n \* 2. Show the overflow in Edge and IE.\n \*/\n\nhr {\n -webkit-box-sizing: content-box;\n box-sizing: content-box; /\* 1 \*/\n height: 0; /\* 1 \*/\n overflow: visible; /\* 2 \*/\n}\n\n\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\npre {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n/\* Text-level semantics\n

=====  
\n\n\*\*\n \* 1. Remove the gray background on active links in IE 10.\n \* 2. Remove gaps in links underline in iOS 8+ and Safari 8+.\n \*/\n\na {\n background-color: transparent; /\* 1 \*/\n -webkit-text-decoration-skip: objects; /\* 2 \*/\n}\n\n\*\*\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\n \* 2. Add the correct text decoration in Chrome, Edge, IE, Opera, and Safari.\n \*/\n\nabbr[title] {\n border-bottom: none; /\* 1 \*/\n text-decoration: underline; /\* 2 \*/\n -webkit-text-decoration: underline dotted;\n text-decoration: underline dotted; /\* 2 \*/\n}\n\n\*\*\n \* Prevent the duplicate application of `bolder` by the next rule in Safari 6.\n \*/\n\nb,\nstrong {\n font-weight: inherit;\n}\n\n\*\*\n \* Add the correct font weight in Chrome, Edge, and Safari.\n \*/\n\nb,\nstrong {\n font-weight: bolder;\n}\n\n\*\*\n \* 1. Correct the inheritance and scaling of font size in all browsers.\n \* 2. Correct the odd `em` font sizing in all browsers.\n \*/\n\ncode,\nkbd,\nsamp {\n font-family: monospace, monospace; /\* 1 \*/\n font-size: 1em; /\* 2 \*/\n}\n\n\*\*\n \* Add the correct font style in Android 4.3-.\n \*/\n\ni,\ndfn {\n font-style: italic;\n}\n\n\*\*\n \* Add the correct background and color in IE 9-.\n \*/\n\nmark {\n background-color: #ff0;\n color: #000;\n}\n\n\*\*\n \* Add the correct font size in all browsers.\n \*/\n\nsmall {\n font-size: 80%;\n}\n\n\*\*\n \* Prevent `sub` and `sup` elements from affecting the line height in all browsers.\n \*/\n\nsub,\nsup {\n font-size: 75%;\n line-height: 0;\n position: relative;\n vertical-align: baseline;\n}\n\nsub {\n bottom: -0.25em;\n}\n\nsup {\n top: -0.5em;\n}\n\n/\* Embedded content\n

=====  
\n\n\*\*\n \* Add the correct display in IE 9-.\n \*/\n\naudio,\nvideo {\n display: inline-block;\n}\n\n\*\*\n \* Add the correct display in iOS 4-7.\n \*/\n\naudio:not([controls]) {\n display: none;\n height: 0;\n}\n\n\*\*\n \* Remove the border on images inside links in IE 10-.\n \*/\n\nimg {\n border-style: none;\n}\n\n\*\*\n \* Hide the overflow in IE.\n \*/\n\nsvg:not(:root) {\n overflow: hidden;\n}\n\n/\* Forms\n

=====  
\n\n\*\*\n \* 1. Change the font styles in all browsers (opinionated).\n \* 2. Remove the margin in Firefox and Safari.\n \*/\n\nbutton,\ninput,\noptgroup,\nselect,\ntextarea {\n font-family: sans-serif; /\* 1 \*/\n font-size: 100%; /\* 1 \*/\n line-height: 1.15; /\* 1 \*/\n margin: 0; /\* 2 \*/\n}\n\n\*\*\n \* Show the overflow in IE.\n \* 1. Show the overflow in Edge.\n \*/\n\nbutton,\ninput { /\* 1 \*/\n overflow: visible;\n}\n\n\*\*\n \* Remove the

inheritance of text transform in Edge, Firefox, and IE.\n \* 1. Remove the inheritance of text transform in Firefox.\n \*/\n\nbutton,\nselect { /\* 1 \*/\n text-transform: none;\n}\n\n/\*\*\n \* 1. Prevent a WebKit bug where (2) destroys native `audio` and `video` controls in Android 4.\n \* 2. Correct the inability to style clickable types in iOS and Safari.\n \*/\n\nbutton,\nhtml [type="button"], /\* 1 \*/\n[type="reset"],\n[type="submit"] {\n -webkit-appearance: button; /\* 2 \*/\n}\n\n/\*\*\n \* Remove the inner border and padding in Firefox.\n \*/\n\nbutton::-moz-focus-inner,\n[type="button"]::-moz-focus-inner,\n[type="reset"]::-moz-focus-inner,\n[type="submit"]::-moz-focus-inner {\n border-style: none;\n padding: 0;\n}\n\n/\*\*\n \* Restore the focus styles unset by the previous rule.\n \*/\n\nbutton:-moz-focusring,\n[type="button"]:-moz-focusring,\n[type="reset"]:-moz-focusring,\n[type="submit"]:-moz-focusring {\n outline: 1px dotted ButtonText;\n}\n\n/\*\*\n \* Correct the padding in Firefox.\n \*/\n\nfieldset {\n padding: 0.35em 0.75em 0.625em;\n}\n\n/\*\*\n \* 1. Correct the text wrapping in Edge and IE.\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\n \* 3. Remove the padding so developers are not caught out when they zero out `fieldset` elements in all browsers.\n \*/\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n color: inherit; /\* 2 \*/\n display: table; /\* 1 \*/\n max-width: 100%; /\* 1 \*/\n padding: 0; /\* 3 \*/\n white-space: normal; /\* 1 \*/\n}\n\n/\*\*\n \* 1. Add the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*/\n\nprogress {\n display: inline-block; /\* 1 \*/\n vertical-align: baseline; /\* 2 \*/\n}\n\n/\*\*\n \* Remove the default vertical scrollbar in IE.\n \*/\n\ntextarea {\n overflow: auto;\n}\n\n/\*\*\n \* 1. Add the correct box sizing in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*/\n\n[type="checkbox"],\n[type="radio"] {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n padding: 0; /\* 2 \*/\n}\n\n/\*\*\n \* Correct the cursor style of increment and decrement buttons in Chrome.\n \*/\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n height: auto;\n}\n\n/\*\*\n \* 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in Safari.\n \*/\n\n[type="search"] {\n -webkit-appearance: textfield; /\* 1 \*/\n outline-offset: -2px; /\* 2 \*/\n}\n\n/\*\*\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n \*/\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n -webkit-appearance: none;\n}\n\n/\*\*\n \* 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2. Change font properties to `inherit` in Safari.\n \*/\n\n::-webkit-file-upload-button {\n -webkit-appearance: button; /\* 1 \*/\n font: inherit; /\* 2 \*/\n}\n\n/\* Interactive\n

=====  
\*/\n\n/\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in Edge, IE, and Firefox.\n \*/\n\ndetails, /\* 1 \*/\nmenu {\n display: block;\n}\n\n/\*\n \* Add the correct display in all browsers.\n \*/\n\nsummary {\n display: list-item;\n}\n\n/\* Scripting\n

=====  
\*/\n\n/\*\*\n \* Add the correct display in IE 9-.\n \*/\n\ncanvas {\n display: inline-block;\n}\n\n/\*\*\n \* Add the correct display in IE.\n \*/\n\ntemplate {\n display: none;\n}\n\n/\* Hidden\n

=====  
\*/\n\n/\*\*\n \* Add the correct display in IE 10-.\n \*/\n\n[hidden] {\n display: none;\n}\n\n", "",\n{"version":3,"sources":["/home/ubuntu/ReactThumbSignIn/node\_modules/normalize.css/normalize.css"],"names":[],"mappings":"AAAA,4EAA4E;;AAE5E;gFACgF;;AAEHf;;;GAIG;;AAEH;EACE,kBAAkB,CAAC,OA AO;EAC1B,2BAA2B,CAAC,OAAO;EACnC,+BAA+B,CAAC,OAAO;CACxC;;AAED;gFACgF;;AAEHf;;GA EG;;AAEH;EACE,UAAU;CACX;;AAED;;GAEG;;AAEH;;;;;EAME,eAAe;CACHB;;AAED;;;GAGG;;AAE H;EACE,eAAe;EACf,iBAaIB;CACIB;;AAED;gFACgF;;AAEHf;;;GAGG;;AAEH;;OAEO,OAAO;EACZ,eA

Ae;CACHb;;AAED;;GAEG;;AAEH;EACE,iBAaIB;CACIB;;AAED;;;GAGG;;AAEH;EACE,gCAAgC;UACx  
B,wBAAwB,CAAC,OAAO;EACxC,UAAU,CAAC,OAAO;EACIB,kBAaKB,CAAC,OAAO;CAC3B;;AAED;;  
;GAGG;;AAEH;EACE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;CACxB;;AAED;gFACgF;;AA  
EhF;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,sCAAsC,CAAC,OAAO;CAC/C;;AAED;;;GAG  
G;;AAEH;EACE,oBAAoB,CAAC,OAAO;EAC5B,2BAA2B,CAAC,OAAO;EACnC,0CAA0C;UACIC,kCAA  
kC,CAAC,OAAO;CACnD;;AAED;;GAEG;;AAEH;;EAEe,qBAAqB;CACtB;;AAED;;GAEG;;AAEH;;EAEe,  
oBAAoB;CACrB;;AAED;;;GAGG;;AAEH;;;EAGE,kCAaKC,CAAC,OAAO;EAC1C,eAAe,CAAC,OAAO;C  
ACxB;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,uBAAuB;EACvB,Y  
AAY;CACb;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHb;;AAED;;;GAGG;;AAEH;;EAEe,eAAe;EACf,eAA  
e;EACf,mBAAmB;EACnB,yBAAyB;CAC1B;;AAED;EACE,gBAAgB;CACjB;;AAED;EACE,YAAY;CACb;;  
AAED;gFACgF;;AAEhF;;GAEG;;AAEH;;EAEe,sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;EA  
Cd,UAAU;CACX;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;;GAEG;;AAEH;EACE,iBAaIB  
;CACIB;;AAED;gFACgF;;AAEhF;;;GAGG;;AAEH;;;EAKE,wBAAwB,CAAC,OAAO;EACHC,gBAAgB,CA  
AC,OAAO;EACxB,kBAaKB,CAAC,OAAO;EAC1B,UAAU,CAAC,OAAO;CACnB;;AAED;;;GAGG;;AAEH  
;QACQ,OAAO;EACb,kBAaKB;CACnB;;AAED;;;GAGG;;AAEH;SACS,OAAO;EACd,qBAAqB;CACtB;;A  
AED;;;GAIG;;AAEH;;;EAIE,2BAA2B,CAAC,OAAO;CACpC;;AAED;;GAEG;;AAEH;;;EAIE,mBAAmB;  
EACnB,WAAW;CACZ;;AAED;;GAEG;;AAEH;;;EAIE,+BAA+B;CACHC;;AAED;;GAEG;;AAEH;EACE,+  
BAA+B;CACHC;;AAED;;;GAKG;;AAEH;EACE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,eAAe,  
CAAC,OAAO;EACvB,eAAe,CAAC,OAAO;EACvB,gBAAgB,CAAC,OAAO;EACxB,WAAW,CAAC,OAA  
O;EACnB,oBAAoB,CAAC,OAAO;CAC7B;;AAED;;;GAGG;;AAEH;EACE,sBAAsB,CAAC,OAAO;EAC9B,  
yBAAyB,CAAC,OAAO;CACIC;;AAED;;GAEG;;AAEH;EACE,eAAe;CACHb;;AAED;;;GAGG;;AAEH;;EA  
EE,+BAA+B;UACvB,uBAAuB,CAAC,OAAO;EACvC,WAAW,CAAC,OAAO;CACpB;;AAED;;GAEG;;AA  
EH;;EAEe,aAAa;CACd;;AAED;;;GAGG;;AAEH;EACE,8BAA8B,CAAC,OAAO;EACtC,qBAAqB,CAAC,O  
AAO;CAC9B;;AAED;;GAEG;;AAEH;;EAEe,yBAAyB;CAC1B;;AAED;;;GAGG;;AAEH;EACE,2BAA2B,C  
AAC,OAAO;EACnC,cAAc,CAAC,OAAO;CACvB;;AAED;gFACgF;;AAEhF;;;GAGG;;AAEH;;EAEe,eAAe;  
CACHb;;AAED;;GAEG;;AAEH;EACE,mBAAmB;CACpB;;AAED;gFACgF;;AAEhF;;GAEG;;AAEH;EACE,  
sBAAsB;CACvB;;AAED;;GAEG;;AAEH;EACE,cAAc;CACf;;AAED;gFACgF;;AAEhF;;GAEG;;AAEH;EAC  
E,cAAc;CACf","file":"normalize.css","sourcesContent":["/\*! normalize.css v7.0.0 | MIT License |  
github.com/necolas/normalize.css \*/\n\n/\* Document\n\n=====

\*/\n\n\*\*\n \* 1. Correct the line height in all browsers.\n \* 2. Prevent adjustments of font size after orientation  
changes in\n \* IE on Windows Phone and in iOS.\n \*/\nhtml {\n line-height: 1.15; /\* 1 \*/\n -ms-text-size-adjust: 100%; /\* 2 \*/\n -webkit-text-size-adjust: 100%; /\* 2 \*/\n}\n\n/\* Sections\n\n=====

\*/\n\n\*\*\n \* Remove the margin in all browsers (opinionated).\n \*/\nbody {\n margin: 0;\n}\n\n\*\*\n \* Add the correct display in IE 9-.\n \*/\narticle,\naside,\nfooter,\nheader,\nnav,\nsection {\n display: block;\n}\n\n\*\*\n \* Correct the font size and margin on `h1` elements within `section` and `article`  
contexts in Chrome, Firefox, and Safari.\n \*/\nh1 {\n font-size: 2em;\n margin: 0.67em 0;\n}\n\n/\* Grouping content\n\n=====

\*/\n\n\*\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in IE.\n \*/\nfigcaption,\nfigure,\nmain {\n /\* 1 \*/\n display: block;\n}\n\n\*\*\n \* Add the correct margin in IE 8.\n \*/\nfigure {\n margin: 1em 40px;\n}\n\n\*\*\n \* 1. Add the correct box sizing in Firefox.\n \* 2. Show the

overflow in Edge and IE.\n \*^\\n\\nhr {\\n -webkit-box-sizing: content-box;\\n box-sizing: content-box; /\* 1  
\*^\\n height: 0; /\* 1 \*^\\n overflow: visible; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* 1. Correct the inheritance and scaling of font  
size in all browsers.\\n \* 2. Correct the odd `em` font sizing in all browsers.\\n \*^\\n\\npre {\\n font-family:  
monospace, monospace; /\* 1 \*^\\n font-size: 1em; /\* 2 \*^\\n}\\n\\n/\* Text-level semantics\\n

=====

\*^\\n\\n/\*\*\\n \* 1. Remove the gray background on active links in IE 10.\\n \* 2. Remove gaps in links underline in  
iOS 8+ and Safari 8+.\\n \*^\\n\\na {\\n background-color: transparent; /\* 1 \*^\\n -webkit-text-decoration-skip:  
objects; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* 1. Remove the bottom border in Chrome 57- and Firefox 39-.\\n \* 2. Add the  
correct text decoration in Chrome, Edge, IE, Opera, and Safari.\\n \*^\\n\\nabbr[title] {\\n border-bottom: none; /\*  
1 \*^\\n text-decoration: underline; /\* 2 \*^\\n -webkit-text-decoration: underline dotted;\\n text-decoration:  
underline dotted; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Prevent the duplicate application of `bolder` by the next rule in Safari  
6.\\n \*^\\n\\nb,\\nstrong {\\n font-weight: inherit;\\n}\\n\\n/\*\*\\n \* Add the correct font weight in Chrome, Edge, and  
Safari.\\n \*^\\n\\nb,\\nstrong {\\n font-weight: bolder;\\n}\\n\\n/\*\*\\n \* 1. Correct the inheritance and scaling of font  
size in all browsers.\\n \* 2. Correct the odd `em` font sizing in all browsers.\\n \*^\\n\\ncode,\\nkbd,\\nsamp {\\n  
font-family: monospace, monospace; /\* 1 \*^\\n font-size: 1em; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Add the correct font style in  
Android 4.3-.\\n \*^\\n\\ndfn {\\n font-style: italic;\\n}\\n\\n/\*\*\\n \* Add the correct background and color in IE 9-.\\n  
\*^\\n\\nmark {\\n background-color: #ff0;\\n color: #000;\\n}\\n\\n/\*\*\\n \* Add the correct font size in all  
browsers.\\n \*^\\n\\nsmall {\\n font-size: 80%;\\n}\\n\\n/\*\*\\n \* Prevent `sub` and `sup` elements from affecting the  
line height in\\n \* all browsers.\\n \*^\\n\\nsub,\\nsup {\\n font-size: 75%;\\n line-height: 0;\\n position: relative;\\n  
vertical-align: baseline;\\n}\\n\\nsub {\\n bottom: -0.25em;\\n}\\n\\nsup {\\n top: -0.5em;\\n}\\n\\n/\* Embedded  
content\\n

=====

\*^\\n\\n/\*\*\\n \* Add the correct display in IE 9-.\\n \*^\\n\\naudio,\\nvideo {\\n display: inline-block;\\n}\\n\\n/\*\*\\n \*  
Add the correct display in iOS 4-7.\\n \*^\\n\\naudio:not([controls]) {\\n display: none;\\n height: 0;\\n}\\n\\n/\*\*\\n \*  
Remove the border on images inside links in IE 10-.\\n \*^\\n\\nimg {\\n border-style: none;\\n}\\n\\n/\*\*\\n \* Hide the  
overflow in IE.\\n \*^\\n\\nsvg:not(:root) {\\n overflow: hidden;\\n}\\n\\n/\* Forms\\n

=====

\*^\\n\\n/\*\*\\n \* 1. Change the font styles in all browsers (opinionated).\\n \* 2. Remove the margin in Firefox and  
Safari.\\n \*^\\n\\nbbutton,\\ninput,\\noptgroup,\\nselect,\\ntextarea {\\n font-family: sans-serif; /\* 1 \*^\\n font-size:  
100%; /\* 1 \*^\\n line-height: 1.15; /\* 1 \*^\\n margin: 0; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Show the overflow in IE.\\n \* 1.  
Show the overflow in Edge.\\n \*^\\n\\nbbutton,\\ninput { /\* 1 \*^\\n overflow: visible;\\n}\\n\\n/\*\*\\n \* Remove the  
inheritance of text transform in Edge, Firefox, and IE.\\n \* 1. Remove the inheritance of text transform in  
Firefox.\\n \*^\\n\\nbbutton,\\nselect { /\* 1 \*^\\n text-transform: none;\\n}\\n\\n/\*\*\\n \* 1. Prevent a WebKit bug where  
(2) destroys native `audio` and `video`\\n \* controls in Android 4.\\n \* 2. Correct the inability to style clickable  
types in iOS and Safari.\\n \*^\\n\\nbbutton,\\nhtml [type="button"], /\* 1 \*^\\n[type="reset"],\\n[type="submit"]  
{\\n -webkit-appearance: button; /\* 2 \*^\\n}\\n\\n/\*\*\\n \* Remove the inner border and padding in Firefox.\\n  
\*^\\n\\nbbutton::-moz-focus-inner,\\n[type="button"]::-moz-focus-inner,\\n[type="reset"]::-moz-focus-inner,\\n[ty  
pe="submit"]::-moz-focus-inner {\\n border-style: none;\\n padding: 0;\\n}\\n\\n/\*\*\\n \* Restore the focus styles  
unset by the previous rule.\\n  
\*^\\n\\nbbutton:-moz-focusing,\\n[type="button"]:-moz-focusing,\\n[type="reset"]:-moz-focusing,\\n[type="su  
bmit"]:-moz-focusing {\\n outline: 1px dotted ButtonText;\\n}\\n\\n/\*\*\\n \* Correct the padding in Firefox.\\n  
\*^\\n\\nfieldset {\\n padding: 0.35em 0.75em 0.625em;\\n}\\n\\n/\*\*\\n \* 1. Correct the text wrapping in Edge and  
IE.\\n \* 2. Correct the color inheritance from `fieldset` elements in IE.\\n \* 3. Remove the padding so developers

are not caught out when they zero out\n \* `fieldset` elements in all browsers.\n \*/\n\nlegend {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n color: inherit; /\* 2 \*/\n display: table;\n /\* 1 \*/\n max-width: 100%; /\* 1 \*/\n padding: 0; /\* 3 \*/\n white-space: normal; /\* 1 \*/\n}\n\n\*\*\n \* 1. Add the correct display in IE 9-.\n \* 2. Add the correct vertical alignment in Chrome, Firefox, and Opera.\n \*/\n\nprogress {\n display: inline-block; /\* 1 \*/\n vertical-align: baseline; /\* 2 \*/\n}\n\n\*\*\n \* Remove the default vertical scrollbar in IE.\n \*/\n\ntextarea {\n overflow: auto;\n}\n\n\*\*\n \* 1. Add the correct box sizing in IE 10-.\n \* 2. Remove the padding in IE 10-.\n \*/\n\n[type="checkbox"],\n[type="radio"] {\n -webkit-box-sizing: border-box;\n box-sizing: border-box; /\* 1 \*/\n padding: 0; /\* 2 \*/\n}\n\n\*\*\n \* Correct the cursor style of increment and decrement buttons in Chrome.\n \*/\n\n[type="number"]::-webkit-inner-spin-button,\n[type="number"]::-webkit-outer-spin-button {\n height: auto;\n}\n\n\*\*\n \* 1. Correct the odd appearance in Chrome and Safari.\n \* 2. Correct the outline style in Safari.\n \*/\n\n[type="search"] {\n -webkit-appearance: textfield; /\* 1 \*/\n outline-offset: -2px; /\* 2 \*/\n}\n\n\*\*\n \* Remove the inner padding and cancel buttons in Chrome and Safari on macOS.\n \*/\n\n[type="search"]::-webkit-search-cancel-button,\n[type="search"]::-webkit-search-decoration {\n -webkit-appearance: none;\n}\n\n\*\*\n \* 1. Correct the inability to style clickable types in iOS and Safari.\n \* 2. Change font properties to `inherit` in Safari.\n \*/\n\n::-webkit-file-upload-button {\n -webkit-appearance: button; /\* 1 \*/\n font: inherit; /\* 2 \*/\n}\n\n/\* Interactive\n

=====  
 \*/\n\n\*\*\n \* Add the correct display in IE 9-.\n \* 1. Add the correct display in Edge, IE, and Firefox.\n \*/\n\n\*{\n details, /\* 1 \*/\n menu {\n display: block;\n}\n\n\*\*\n \* Add the correct display in all browsers.\n \*/\n\nsummary {\n display: list-item;\n}\n\n/\* Scripting\n

=====  
 \*/\n\n\*\*\n \* Add the correct display in IE 9-.\n \*/\n\n\*{\n canvas {\n display: inline-block;\n}\n\n\*\*\n \* Add the correct display in IE.\n \*/\n\n\*{\n template {\n display: none;\n}\n\n/\* Hidden\n

=====  
 \*/\n\n\*\*\n \* Add the correct display in IE 10-.\n \*/\n\n\*{\n [hidden] {\n display: none;\n}\n\n"}\n","sourceRoot":""}});\n\nuser = \_props.user,\n\nuser.isLoggedin && \_\_WEBPACK\_IMPORTED\_MODULE\_0\_react\_\_default.a.createElement(\nuser.isLoggedin && \_\_WEBPACK\_IMPORTED\_MODULE\_0\_react\_\_default.a.createElement(\nuser.isLoggedin ? \_\_WEBPACK\_IMPORTED\_MODULE\_0\_react\_\_default.a.createElement(\nuser: {\n\nisLoggedin: !userInfo.isLoading ? userInfo.data.isLoggedin : ownProps.query.user.isLoggedin,\n\n\* `Indeterminate`, and `Query Indeterminate`.\n\n\* A `Query Indeterminate` linear progress bar is used when you are combining\n\n\* as a query indeterminate progress bar by adding the prop `query={true}` to the\n\n\* component. Until a progress value is given, it will display the query linear\n\n\* progress animation. Afterwards, it will start the determinate animation of where\n\nquery = \_props.query,\n\nprops = \_objectWithoutProperties(\_props, ['className', 'progressClassName', 'progressStyle', 'value', 'query', 'centered']);\n\n'md-progress--linear-query': query,\n\n\* region until it is finished loading. It is not possible for the user to alter the value of a progressbar\n\n\* Boolean if this should be a query indeterminate progress bar.\n

query: \_propTypes2.default.bool,

query: false

\* region until it is finished loading. It is not possible for the user to alter the value of a progressbar

\* Removes observer from observers list.

\* Updates every observer from observers list and notifies them of queued

// has the "ownerDocument" property from which we can retrieve a

// Return the local global object if it's not possible extract one from

\* Extracts borders size from provided styles.

\* Extracts paddings sizes from provided styles.

\* from the corresponding properties of the last observed content rectangle.

\* instances collected from active resize observations.

\* The layover will appear by transitioning from the top left and expand

\* The layover will appear by transitioning from the top right and expand

\* The layover will appear by transitioning from the bottom left and expand

\* The layover will appear by transitioning from the bottom right and expand

\* The layover will appear by just transitioning downwards from the bottom

\* where a `false` value will mean it is out of the viewport for that

className: \_\_WEBPACK\_IMPORTED\_MODULE\_2\_classnames\_\_\_default()('md-divider--text-field  
md-divider--expand-from-' + lineDirection, {

var FOCUSABLE\_QUERY = ['button', 'textarea', 'select'].reduce(function (queryString, element) {

throw new Error('You specified that the `FocusContainer` should focus an element on mount, ' + 'but a  
focusable element was not found in the children. This could be because ' + 'the `initialFocus` prop is an invalid  
id or query selector, or the children ' + ('do not contain a valid focusable element.' + debugError));

\* An optional id string or a query selector string to use for the initial focus.

\* that appears from the side of a screen.

\* Simply does a `window.matchMedia(query)` where the query gets defined as a min width

\* @param {number} min - The min width for the media query.

\* @param {number=} max - An optional max width to include for the media query.

\* media query.

\* The min-width to use for the mobile media query.

\* media query.

\* The min-width to use for the tablet media query.

\* query.

\* The `\$md-drawer-transition-time` value from sass.

\* the drawer will close when a user clicks anywhere on the page except in the drawer.

\* the page to get the main focus on the drawer. When the user touches the overlay or

// I honestly don't remember why this was implemented, but it was copied from the Button

\* Boolean if the theming should be swapped from text to background or vice-versa.

\* be triggered when the user selects a new file or cancels the new file selection.

\* `input` tag, the user will not be able to select the same file multiple times unless

\* > NOTE: If the user hits cancel, null will be given for a single file input.

label: 'Select a file',

\* Boolean if all the gutters and spacing should be removed from the grid.



```

    className: __WEBPACK_IMPORTED_MODULE_2_classnames___default()('md-title md-title--toolbar
md-select-field--toolbar', {
    // We need to check all keys in case some are required but missing from
    // fail the render phase where it didn't fail before. So we log it.
    'it must be a function, usually from the `prop-types` package, but received `' + typeof
typeSpecs[typeSpecName] + `.'
* @param {object} prev prev children as returned from
* @param {object} next next children as returned from
    // TODO: when config is {a: 10} and dest is {a: 10} do we raf once and
    // changed from 0 to 400 to spring(0) again, the async currentStyle is still
    // TODO: when config is {a: 10} and dest is {a: 10} do we raf once and
    // changed from 0 to 400 to spring(0) again, the async currentStyle is still
    // Array<TransitionPlainStyle>, where each TransitionPlainStyle is of the format
    // turn current (interpolating) style from {a, b} into {a?, b, c}
    // TODO: key search code
    // TODO: when config is {a: 10} and dest is {a: 10} do we raf once and
    // TODO: key search code
    // that you've unmounted but that's still animating. This is where it lives
    // changed from 0 to 400 to spring(0) again, the async currentStyle is still
    // this reduces to merging two partially ordered lists (e.g. lists where not
    // merge in keys that the user desires to kill
    // a period where rootNode briefly equals null.
    // can leave a period where rootNode briefly equals null.
* This is useful when you want to prohibit the user from changing slides.
* This will allow the user to perform the relevant swipe actions with a mouse.
* should user swipe to switch slide.
* component when the shown slide change after a swipe made by the user.
* Gets the current value from the text field. This is used when you have an uncontrolled
* text field and simply need the value from a ref callback.
* A single key or an array of keys to delete from your data object before passing
* This will be triggered when the window is clicked or when a user tabs away from
* The list's z-depth for applying box shadow. This should be a number from 0 to 5.
* triggered when the user presses enter anywhere in the form.
* Creates an ink from pageX and pageY coordinates. These values should either come
* from the `changedTouches` or just the base event (if clicked). These coordinates
* are used to position the ink correctly in the container from touch/click point.
* If either value is undefined, an ink will be created from the center of the
* Creates an ink from pageX and pageY coordinates. These values should either come
* from the `changedTouches` or just the base event (if clicked). These coordinates
* are used to position the ink correctly in the container from touch/click point.
* If either value is undefined, an ink will be created from the center of the
* Removes an ink from the container.
* Sets the ink container and the main container from the ref callback. When the component

```

- \* @param {Object} el - The element to get a scroll value from.
- \* Boolean if the bottom navigation should dynamically appear based on scrolling. When the user
- \* The distance a user must scroll before the bottom navigation appears or disappears when it is `dynamic`.
- \* to the `checkedCheckboxIcon` prop from the `SelectionControl`.
- \* to the `uncheckedCheckboxIcon` prop from the `SelectionControl`.
- \* so that when a user scrolls to the right, they will always be able to use the

inputClassName:

```
__WEBPACK_IMPORTED_MODULE_2_classnames___default()('md-select-field--pagination',
selectFieldInputClassName),
```

- \* An optional id to provide to the select field. If this is omitted, it will be
- \* An optional style to apply to the select field.
- \* An optional className to apply to the select field.
- \* An optional style to apply to the select field's input.
- \* An optional className to apply to the select field's input.
- \* Boolean if the select field should use the simplified menu logic.
- \* A function to call when a user clicks the increment or decrement pagination
- \* The current value for the select field holding the number of rows per page.
- \* Pages start from 1 instead of 0.
- \* The default page to start from for the pagination. Pages start from 1 instead of 0.
- \* display and determine if the user can increment/decrement again.

```
{ style: style, className:
```

```
__WEBPACK_IMPORTED_MODULE_2_classnames___default()('md-select-field__toggle', className) },
  className: 'md-divider--select-field'
```

```
className: __WEBPACK_IMPORTED_MODULE_2_classnames___default()('md-select-field',
```

```
Object(__WEBPACK_IMPORTED_MODULE_4__utils_themeColors__["a" /* default */])( {
  'md-select-field--text-field': !below,
  'md-select-field--btn': below
```

- \* An optional function to call when the "Ok" button has been clicked, the user presses enter
- \* on \* the text field or when the `okOnOutsideClick` prop has been enabled and the user clicks
- \* An optional function to call when a user clicks out of the text field.
- \* Boolean if the edit dialog should be closed if the user clicks somewhere else on the page
- \* See the [SelectField](/components/select-fields?tab=1#select-field-proptypes) for remaining prop descriptions.

```
className: __WEBPACK_IMPORTED_MODULE_2_classnames___default()('md-select-field-column',
className),
```

- \* An optional id to use for the select field in the column. If this is omitted, it's value will be
- \* `\${rowId}-\${cellIndex}-select-field`
- \* The is the optional style to apply to the select field's menu container.
- \* The is the optional class name to apply to the select field's menu container.
- \* This is how the select field should be fixed within the table. When this is omitted,
- \* it will automatically use the responsive table as the fixture so that the select field
- \* Boolean if the select field should span the entire width of the column.
- \* The position for the select field.

```

/* unused harmony default export */ var _unused_webpack_default_export =
(Object(__WEBPACK_IMPORTED_MODULE_7__withTableFixes__["a" /* default */])(SelectFieldColumn,
'select-field'));
  * This is how the select field should be fixed within the table. When this is omitted,
  * it will automatically use the responsive table as the fixture so that the select field
  * This is how the select field should be fixed within the table. When this is omitted,
  * it will automatically use the responsive table as the fixture so that the select field
  * a user selects a row.
  * contextual header once the user has selected a row or multiple rows.
  * @param {string|Object=} selector - An optional query selector string to use to select an element.
    // Hopefully a nice warning about fixing the missing props injected from ExpansionList
    console.error("The `ExpansionPanel` component expects the `columnWidths` prop to be injected from the '
+ `ExpansionList` component. It could be missing because:' + '\n - you have a wrapper component with extra
functionality' + '\n - the `ExpansionPanel` is not a direct child of the `ExpansionList` component' + '\n\nYou can
fix this by making sure to pass `this.props.focused` and `this.props.columnWidths` ' + 'within your wrapper
component and making the `ExpansionPanel` a direct child of `ExpansionList`.');
  * can also be toggled from the `ExpansionList` component if all `ExpansionPanel` in the list
  * So if the size changes from 80 -> 120 -> 160 -> 140. It will only update on the third resize (160)
  * file that is uploading. Unreliable for multi-select.
  * Boolean if all the gutters and spacing should be removed from the grid.
  * The min width to use for a mobile media query. This prop should match the `md-mobile-min-width`
  * The media query for a mobile device will be:
  * The min width to use for a tablet media query. This prop should match the `md-tablet-min-width`
  * The media query for a tablet device will be:
  * The min width to use for a desktop media query. This prop should match the `md-desktop-min-width`
  * The media query for a tablet device will be:
  * A boolean if the mini drawer's list should be generated from the `navItems` prop. When building
  * the list, it will extract the `leftIcon` or `leftAvatar` from the `navItem` and then create a
  * An optional select field menu to display in the main toolbar. Either the `toolbarTitle` or the
`toolbarTitleMenu`
  * The label to use for a keyboard accessibility link that jumps all the navigation and allows a user to focus
  * import { DatePicker } from 'react-md/lib/Pickers';
  * import DatePicker from 'react-md/lib/Pickers/DatePickerContainer';
  * Gets the current value from the date picker as a formatted string.
  * A function to format the dates since it should be formatted to the user's
  * the user's language in the browser or `en-US` when server rendering.
  * Boolean if the date should automatically be selected when a user clicks
  * The direction that the text field divider expands from when the text field
  * Boolean if the dialog should be able to close if a keyboard user presses the escape key.
  * Boolean if the DatePicker should be read only. This will prevent the user from opening the picker
  * True if dates from adjacent months should be shown in calendar.
  * Boolean if the dates from adjacent months should be disabled. This will only
  * clickable until the user switches to that month.

```

- \* An optional className to apply to a date from an adjacent month in calendar. This will be applied
- \* True if dates from adjacent months should be shown in calendar.
- \* An optional className to apply to a date from an adjacent month in calendar.
- \* current year and the current date. It allows the user to switch
- \* True if dates from adjacent months should be shown.
- \* An optional className to apply to a date from an adjacent month.
- \* A function to call that will select a new date.
- \* True if dates from adjacent months should be shown.
- \* An optional className to apply to a date from an adjacent month.
- \* Removes all the time parts (hours, minutes, seconds, milliseconds) from a date.
- \* will display a list of years to select from within the given range.
  - \* @param {Object} props - The current props to extract the year range from.
- \* import { TimePicker } from 'react-md/lib/Pickers';
- \* import TimePicker from 'react-md/lib/Pickers/TimePickerContainer';
  - \* A function to format the dates since it should be formatted to the user's
  - \* the user's language in the browser or `en-US` when server rendering.
  - \* Boolean if the date should automatically be selected when a user clicks
  - \* The direction that the text field divider expands from when the text field
  - \* Boolean if the dialog should be able to close if a keyboard user presses the escape key.
  - \* Boolean if the TimePicker should be read only. This will prevent the user from opening the picker
- 'aria-label': 'Select a time',
- \* Extracts the hours, minutes, and optional time period from
- \* @param {Date} time the time to extract from.
  - \* A function that will switch the state from hour to minute.
  - \* the user selects ok. This function will be given a new Date object
  - \* A string that is a representation of the hours in the user's locale.
  - \* A string that is a representation of the minutes in the user's locale.
  - \* A string that is a representation of the seconds in the user's locale.
  - \* An optional time period if a user's locale uses it.
- \* Takes a point from a mouse or touch event and a center point of a circle to determine
  - className: \_\_WEBPACK\_IMPORTED\_MODULE\_2\_classnames\_\_\_default()('md-clock-time
- md-text-no-select md-pointer--none', {
  - \* A formatted hours string for the user's locale. This
  - \* A formatted minutes string for the user's locale.
  - \* A formatted seconds string for the user's locale.
  - \* region until it is finished loading. It is not possible for the user to alter the value of a progressbar
- \* `Indeterminate`, and `Query Indeterminate`.
- \* A `Query Indeterminate` linear progress bar is used when you are combining
- \* as a query indeterminate progress bar by adding the prop `query={true}` to the
- \* component. Until a progress value is given, it will display the query linear
- \* progress animation. Afterwards, it will start the determinate animation of where
  - query = \_props.query,
  - props = \_objectWithoutProperties(\_props, ['className', 'progressClassName', 'progressStyle', 'value',

```
'query', 'centered']));
```

```
  'md-progress--linear-query': query,
```

```
  * region until it is finished loading. It is not possible for the user to alter the value of a progressbar
```

```
  * Boolean if this should be a query indeterminate progress bar.
```

```
query: __WEBPACK_IMPORTED_MODULE_1_prop_types___default.a.bool,
```

```
query: false
```

```
  * The `SelectionControl` will inherit any inheritable props from the `SelectionControlGroup`.
```

```
  * The `Checkbox` component is used for the selection of multiple options from a set.
```

```
  * value can be found from `document.querySelector('input[name="someName[]"]').value`.
```

```
  * The `Radio` component is used for the selection of a single option from a set. Unfortunately
```

```
  * The `Slider` component is used to let users select a value from a continuous
```

```
  * When the user has finished dragging the Slider or increments the value by using
```

```
  * - The user does a quick jump
```

```
  * - The user stops dragging with the mouse
```

```
  * - The user drops dragging with touch
```

```
  * @param {Object} e - The current event to extract an x location from
```

```
  * This will either allow a user to start dragging the slider or quickly
```

```
  * This will set the active state of the slider to false if the user
```

```
  * where the event can either be:
```

```
  * This is only called when the user is dragging the slider with either
```

```
  * The incremental amount when the user hits left or right with the
```

```
  * keyboard arrows, or the user hits the up or down buttons in the
```

```
  * This calculates the distance from a screen x location to a position in some element
```

```
  * @return {Number} the distance from the element's left position to the page x
```

```
  * The `Snackbar` component is used for displaying a concise and small message to the user about
```

```
  * The snackbar will always display the first toast in this list. When the user has
```

```
    return new Error('Invalid ' + location + '``' + propFullNameSafe + "` supplied to `" + componentNameSafe +  
    "` , expected a ' + 'ref to a floating `Button` component. This should not be a DOMElement from  
    `findDOMNode` but instead ' + 'the React ref object.');
```

```
  // Only style we really want from the .md-snackbar
```

```
  * height, separated by white space and/or a comma, which specify a rectangle in user
```

```
  * `viewBox="0 0 25 20"`, the coordinates inside the SVG will go from the top left corner
```

```
  * the `children` from each tab, and render them in a swipeable container. However,
```

```
  * @see https://github.com/oliviertassinari/react-swipeable-views#user-content-swipeableviews-
```

```
  * @see https://github.com/oliviertassinari/react-swipeable-views#user-content-swipeableviews-
```

```
  * `label` and `children` from a custom `Tab` component.
```

```
  * An id for a `TabPanel` that holds the children from this tab. This is required for all ly.
```

```
  * @param {Object} object The object to query.
```

```
  * @param {*} value The value to query.
```

```
  * @param {Object} map The map to query.
```

```
/* WEBPACK VAR INJECTION */(function(global) {/** Detect free variable `global` from Node.js. */
```

```
  // We need to check all keys in case some are required but missing from
```

```
  // fail the render phase where it didn't fail before. So we log it.
```

'it must be a function, usually from the `prop-types` package, but received `'+ typeof typeSpecs[typeSpecName] + `.`'

- \* Removes all key-value entries from the list cache.
- \* Removes `key` and its value from the list cache.
- \* Removes all key-value entries from the stack.
- \* Removes `key` and its value from the stack.
- \* @param {\*} value The value to query.
- \* @param {Object} [object] The object to query.
- \* Removes all key-value entries from the map.
- \* Removes all key-value entries from the hash.
- \* Removes `key` and its value from the hash.
- \* Removes `key` and its value from the map.
- \* @param {Object} cache The cache to query.
- \* @param {Object} object The object to query.
- \* @param {Object} object The object to query.
- \* @param {Object} object The object to query.
- \* @param {Object} object The object to query.
- \* @param {\*} value The value to query.

/\*\* Detect free variable `process` from Node.js. \*/

- \* @param {Object} object The object to query.
- \* @param {\*} value The value to query.
- \* the DOM element or the id of the HTML element where the API will insert an <iframe>.
- \* @todo Capture event parameters.
- \* @todo Proxy all of the methods using Object.keys.
- \* @todo See TRICKY below.

// TODO: Just spread the args into the function once Babel is fixed:  
// TODO: Just spread the args into the function once Babel is fixed:

- \* TODO: add a `localStorage` variable to explicitly enable/disable colors  
// (the user may have provided their own)
- // this hackery is required for IE8/9, where
- \* when a user disables cookies/localstorage
- \* Select a color.

'It is obvious how this can help you increase user engagement and slash user drop-off rates. Not only is this approach to authentication convenient but it is also much more secure than using passwords as authentication information is never transmitted over the wire or stored on the server.'

'This method of signing in to a website is very convenient as it rids the user of having to remember and manage passwords and confirming it with an SMS based OTP. It is also way more secure as it enables multi-factor authentication by default in a single step using a simple gesture.'

'Thereafter every time they try to log in to their computer, a QR code is displayed as a second factor after they provide the username and password. Scanning the QR code using the ThumbSignIn mobile app and authenticating with their fingerprint will log the user into the computer.'

'This can significantly enhance the security of your enterprise computers and protect critical data from unauthorized access.'

'Thumbsignin brings you strong de-centralized security for your Apps. The blockchain wallet needs a stronger security after-all it has your user\'s money and a simple flaw the way your user handles the private key may compromise the security. Thumbsignin authentication platform provides blockchain-based applications with a fully interoperable solution for protecting digital assets.'

## **Solution**

Remove all comments that return information that may help an attacker and fix any underlying problems they refer to.

# Information Disclosure - Sensitive Informations in URL

## Description

The request appeared to contain sensitive information leaked in the URL. This can violate PCI and most organizational compliance policies. You can configure the list of strings for this check to add or remove values specific to your environment.

## Risk

Informational

## Reliability

Medium

## URLs

1-<https://stage.thumbsignin.com/pricing?userEmail=ZAP>

Parameters: userEmail

Evidence: ZAP

Other Information: The URL contains potentially sensitive information.

2-<https://stage.thumbsignin.com/?userEmail=ZAP>

Parameters: userEmail

Evidence: ZAP

Other Information: The URL contains potentially sensitive information.

## Solution

Do not pass sensitive information in URIs.