

12108 Extraordinarily Tired Students

When a student is too tired, he can't help sleeping in class, even if his favorite teacher is right here in front of him. Imagine you have a class of extraordinarily tired students, how long do you have to wait, before all the students are listening to you and won't sleep any more? In order to complete this task, you need to understand how students behave.

When a student is awoken, he struggles for a minutes listening to the teacher (after all, it's too bad to sleep all the time). After that, he counts the number of awoken and sleeping students (including himself). If there are strictly more sleeping students than awoken students, he sleeps for b minutes. Otherwise, he struggles for another a minutes, because he knew that when there is only very few sleeping students, there is a big chance for them to be punished! Note that a student counts the number of sleeping students only when he wants to sleep again.

Now that you understand each student could be described by two integers a and b , the length of awoken and sleeping period. If there are always more sleeping students, these two periods continue again and again. We combine an awoken period with a sleeping period after it, and call the combined period an awoken-sleeping period. For example, a student with $a = 1$ and $b = 4$ has an awoken-sleeping period of awoken-sleeping-sleeping-sleeping-sleeping. In this problem, we need another parameter c ($1 \leq c \leq a + b$) to describe a student's initial condition: the initial position in his awoken-sleeping period. The 1st and 2nd position of the period discussed above are awoken and sleeping, respectively.

Now we use a triple (a, b, c) to describe a student. Suppose there are three students $(2, 4, 1)$, $(1, 5, 5)$ and $(1, 4, 3)$, all the students will be awoken at time 18. The details are shown in the table below.

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
		😴	😴	😴	😴			😴	😴	😴	😴						
😴	😴	😴	😴	😴		😴	😴	😴	😴	😴		😴	😴	😴	😴	😴	
😴	😴	😴		😴	😴	😴	😴		😴	😴	😴	😴					

Table 1. An example

Write a program to calculate the first time when all the students are not sleeping.

Input

The input consists of several test cases. The first line of each case contains a single integer n ($1 \leq n \leq 10$), the number of students. This is followed by n lines, each describing a student. Each of these lines contains three integers a, b, c ($1 \leq a, b \leq 5$), described above. The last test case is followed by a single zero, which should not be processed.

Output

For each test case, print the case number and the first time all the students are awoken. If it'll never happen, output '-1'.

Sample Input

```
3
2 4 1
1 5 2
0
```

```
1 4 3
3
1 2 1
1 2 2
1 2 3
0
```

Sample Output

```
Case 1: 18
Case 2: -1
```