

Malicious Code Analysis

Fangtian Zhong CSCI 591

Gianforte School of Computing
Norm Asbjornson College of Engineering
E-mail: fangtian.zhong@montana.edu







>>>>

Part One

01

Export

Data Directories

```
#define IMAGE_DIRECTORY_ENTRY_EXPORT
                                           0 // Export Directory
#define IMAGE_DIRECTORY_ENTRY_IMPORT
                                           1 // Import Directory
#define IMAGE_DIRECTORY_ENTRY_RESOURCE
                                             2 // Resource Directory
#define IMAGE_DIRECTORY_ENTRY_EXCEPTION
                                             3 // Exception Directory
#define IMAGE_DIRECTORY_ENTRY_SECURITY
                                            4 // Security Directory
#define IMAGE_DIRECTORY_ENTRY_BASERELOC
                                              5 // Base Relocation Table
#define IMAGE_DIRECTORY_ENTRY_DEBUG
                                           6 // Debug Directory
    IMAGE_DIRECTORY_ENTRY_COPYRIGHT
                                           7 // (X86 usage)
#define IMAGE_DIRECTORY_ENTRY_ARCHITECTURE 7 // Architecture Specific Data
#define IMAGE_DIRECTORY_ENTRY_GLOBALPTR 8 // RVA of GP
#define IMAGE_DIRECTORY_ENTRY_TLS 9 // TLS Directory
#define IMAGE_DIRECTORY_ENTRY_LOAD_CONFIG 10 // Load Configuration Directory
#define IMAGE_DIRECTORY_ENTRY_BOUND_IMPORT 11 // Bound Import Directory in headers
#define IMAGE_DIRECTORY_ENTRY_IAT 12 // Import Address Table
#define IMAGE_DIRECTORY_ENTRY_DELAY_IMPORT 13 // Delay Load Import Descriptors
#define IMAGE_DIRECTORY_ENTRY_COM_DESCRIPTOR 14 // COM Runtime descriptor
```


Data Directories

```
typedef struct _IMAGE_DATA_DIRECTORY {
   DWORD VirtualAddress;
   DWORD Size;
} IMAGE_DATA_DIRECTORY, *PIMAGE_DATA_DIRECTORY;
```



```
typedef struct IMAGE EXPORT DIRECTORY {
  DWORD Characteristics;
                                     // Reserved, must be 0.
  DWORD TimeDateStamp;
                                     //The time and date that the export data was created.
                                     //The major version number.
  WORD
          MajorVersion;
          MinorVersion;
                                     //The minor version number.
  WORD
  DWORD Name;
                                     //The address of the ASCII string that contains the name of the DLL.
  DWORD Base;
                                     //The starting ordinal number for exports in this image.
                                     //It is usually set to 1.
  DWORD NumberOfFunctions;
                                     //The number of entries in the export address table.
  DWORD NumberOfNames;
                                     //The number of entries in the name pointer table.
  DWORD AddressOfFunctions;
                                     //The address of the export address table.
  DWORD AddressOfNames;
                                      //The address of the export name pointer table.
  DWORD AddressOfNameOrdinals; //The address of the ordinal table, relative to the image base.
} IMAGE_EXPORT_DIRECTORY, *PIMAGE_EXPORT_DIRECTORY;
```





Virtual Address== 0x90380 Size == D4DC

```
typedef struct IMAGE SECTION HEADER {
 BYTE Name[IMAGE SIZEOF SHORT NAME];
 union {
     DWORD PhysicalAddress;
     DWORD VirtualSize;
  } Misc;
 DWORD VirtualAddress;
 DWORD SizeOfRawData;
 DWORD PointerToRawData;
 DWORD PointerToRelocations;
 DWORD PointerToLinenumbers;
 WORD NumberOfRelocations;
 WORD NumberOfLinenumbers;
 DWORD Characteristics;
} IMAGE SECTION HEADER, *PIMAGE SECTION HEADER;
```





Because we don't run the program, we should convert the Virtual Address (RVA) to File Address (FOA).

00000200	UU	4 U	מט	UU	UU	ΤU	UU	w												
00000210	00	00	00	00	20	00	00	60	2E	72	64	61	14	61	00	00		`.r	data	3
00000220	BC	61	02	00	00	00	08	00	00	70	02	nn	nn	50	ПА	ΠN	1⁄4a	p	I	
00000230	00	00	00	00	00	00	00	00	00	00	00	00	40	00	00	40			0	0
00000240	2E	64	61	74	61	00	00	00	8C	0B	00	00	00	00	OB	00	.data			

- In this case, 00080000 (Section VirtualAddress) < 90380 <00080000+ 000261BC(Virtual Size).
- Therefore, it exists in .rdata section. PointerToRawData == 0x65000.
- \bigcirc FOA = 0x90380 0x80000 + 0x65000 == 0x75380






Name: starting at 13th bytes with value 0x9416A, which is a RVA. Its FOA == 7916A

```
00079160 28 06 29 06 2A 06 2B 06 2C 06 4B 45 52 4E 45 4C ( ) * + . KERNEL 00079170 33 32 2E 64 6C 6C 00 42 61 73 65 54 68 72 65 61 32.dll BaseThrea
```


```
typedef struct _IMAGE_EXPORT_DIRECTORY {
  DWORD Characteristics;
                                       // Reserved, must be 0.
  DWORD TimeDateStamp;
                                        //The time and date that the export data was created.
                                        //The major version number.
  WORD
           MajorVersion;
                                        //The minor version number.
  WORD
           MinorVersion;
  DWORD Name;
                                        //The address of the ASCII string that contains the name of the DLL.
  DWORD Base;
                                        //The starting ordinal number for exports in this image.
                                        //It is usually set to 1.
  DWORD NumberOfFunctions;
                                        //The number of entries in the export address table.
  DWORD NumberOfNames;
                                       //The number of entries in the name pointer table.
  DWORD AddressOfFunctions;
                                        //The address of the export address table.
  DWORD AddressOfNames;
                                        //The address of the export name pointer table.
  DWORD AddressOfNameOrdinals;
                                       //The address of the ordinal table, relative to the image base.
} IMAGE EXPORT_DIRECTORY, *PIMAGE_EXPORT_DIRECTORY;
```



NumberOfFunctions and NumberOfNames



- In this case, the number of all exported functions is 62d. The number of exported functions by name is 62d.
- The number of all exported functions The number of exported functions by name == the number of differences.
- That means other functions may not be exported or exported by ordinal number.




- Similarly, AddressOfFunctions FOA == 0x753A8
- AddressOfNames FOA == 0x76c5c
- AddressOfNameOrdinals FOA == 0x78510





AddressOfFunctions FOA == 0x753A8



□ In function address table, each entry is 4 bytes. The number of entries is determined by NumberOfFunctions.





For example, the RVA of the first entry is 0x0162A0.



We use the RVA of the first entry + ImageBase is the function address.

Base address	Module	Address	+Type	Symbol
00400000	merged section. exe	763762A0	export	BaseThreadInitThunk
53240,00	ucrtbased.dll	763F41A4	export	Inter lockedPushListSList
5F270000	vcruntime140d	763E1D18	export	Wow64Transition
755B0000	kernelbase.dl	763F41EE	export	AcquireSRWLockExclusive
76360000	kernel32.dll	763F4224	export	AcquireSRWLockShared
77370000	ntd11.d11	76380430	export	ActivateActCtx
		7637B780	export	ActivateActCtxWorker
		763836F0	export	AddAtomA

AddressOfNames FOA == 0x76c5c

```
00076C50
         90 34 02 00 80 1F 06 00
                                 90 E6 01 00 D6 41 09 00
                                                                     OA
         OF 42 09 00 42 42 09 00 51 41 09 00 66 42 09 00
00076060
                                                                 OB fB
         6F 42 09 00 78 42 09 00
00076C70
                                 89 42 09 00 9A 42 09 00
                                                             xB
00076080
        DF 42 09 00 05 43 09 00
                                24 43 09 00 43 43 09 00
                                                                 SC CC
00076090
        50 43 09 00 63 43 09 00 7B 43 09 00 96 43 09 00 PC
                                                             cC
00076CA0
        AB 43 09 00 C8 43 09 00 07 44 09 00 48 44 09 00 «C
00076CB
         5B 44 09 00 68 44 09 00 82 44 09 00 A0 44 09 00 [D
```

FOA = 0x941D6 - 0x80000 + 0x65000 = 0x791D6

```
      000791C0
      53 4C 69 73 74 00 57 6F
      77 36 34 54 72 61 6E 73
      SList Wow64Trans

      000791D0
      69 74 69 6F 6E 00 41 63 71 75 69 72 65 53 52 57
      ition AcquireSRW

      000791E0
      4C 6F 63 6B 45 78 63 6C 75 73 69 76 65 00 4E 54
      LockExclusive NT

      000791F0
      44 4C 4C 2E 52 74 6C 41 63 71 75 69 72 65 53 52
      DLL.RtlAcquireSR

      00079200
      57 4C 6F 63 6B 45 78 63 6C 75 73 69 76 65 00 41
      WLockExclusive A

      00079210
      63 71 75 69 72 65 53 52
      57 4C 6F 63 6B 53 68 61
      cquireSRWLockSha
```

AddressOfNameOrdinals FOA == 0x78510

	00078510															
	00078520	OB W	OC	00	OD	00	0E	00	OF	00	10	00	11	00	12	00
	00078530	13 00	14	00	15	00	16	00	17	00	18	00	19	00	1A	00
Ш	000000000	15 00		00	45	00	45	00	4-	00	00	00	~4	20	00	



Example

AddressOfFunctions	AddressOfNameOrdinals	AddressOfNames
0 0x1010 Sub	0 0x0100	0 Add
1 0x2020 Add	1 0x0000	1 Sub
2 0x3030 Div	2 0x0200	2 Div





Part Two

02

Relocation

Relocation Table



Typedef struct _IMAGE_BASE_RELOCATION{
 DWORD VirtualAddress
 DWORD SizeOfBlock
}IMAGE_BASE_RELOCATION,*PIMAGE_BASE_RELOCATION;






Na	me	Raw Addr.	Raw size	Virtual Addr.	Virtual Size	Characteristics	Ptr to Reloc.	Num. of Reloc.	Num. of Linenum
~	.text	400	1C00	1000	1AC8	60000060	0	0	0
	>	2000	^	2AC8	^	r-x			
~	.data	2000	200	3000	В0	C0000040	0	0	0
	>	2200	^	30B0	^	rw-			
>	.rdata	2200	C00	4000	B00	40000040	0	0	0
>	.pdata	2E00	400	5000	240	40000040	0	0	0
>	.xdata	3200	200	6000	1B8	40000040	0	0	0
>	.bss	0	0	7000	180	C0000080	0	0	0
>	.idata	3400	800	8000	7DC	C0000040	0	0	0
>	.CRT	3C00	200	9000	60	C0000040	0	0	0
>	.tls	3E00	200	A000	10	C0000040	0	0	0
>	.rsrc	4000	600	B000	4E8	C0000040	0	0	0
>	.reloc	4600	200	C000	80	42000040	0	0	0

Typedef struct _IMAGE_BASE_RELOCATION {
 DWORD VirtualAddress
 DWORD SizeOfBlock
 }IMAGE_BASE_RELOCATION,*PIMAGE_BASE_RELOCATION;

IMAGE_DIRECTORY_ENTRY_BASERELOC DWORD VirtualAddress:0000 C000 DWORD Size:0000 0080



Base address: VirtualAddress





	0	1	2	3	4	5	6	7	8	9	A	В	С	D	E	F				
4600	00	20	00	00	ОС	00	00	00	A8	AA	00	00	00	30	00	00				
4610	18-	00	00	00	10	ΑO	60	A0	70	ΑO	80	ΑO	90	AO	98	ΑO				
4620	AU	ΑU	υυ	υυ	00	40	00	00	4C	00	00	00	40	ΑO	60	ΑO				
4630	68	ΑO	70	ΑO	78	ΑO	70	А3	80	А3	90	А3	ΑO	А3	во	А3				
4640	CO	А3	D0	А3	ΕO	А3	FO	А3	00	Α4	10	Α4	20	Α4	30	Α4				
4650	40	A4	50	ΔΔ	60	ΔΔ	70	ΔΔ	80	ΔΔ	90	ΔΛ	ΔΩ	ΔΛ	RΛ	ΔΔ				
4660	CO	A4		20			•0	20	1//								DWOD	A O 4 O	100	0040
	_																			
4670	00	90		70			70	30	-	F	ı.	Ŀ			i XI		/ DWOR	A040	JUU	0010
4670	00	90 00	00	00	00	00	00	00	00	00	00	υυ	UV.	υυ	00	υυ	DWOR	AU4U		0010
			00	00 00	00 00	00	00 00	00 00	00 00	00	00	00	00 00	00			DWOR			0010
4680	00	00													υυ	υυ	DWOR			0010
4680 4690	00	00 00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	DWOR			0010
4680 4690 46A0	00	00 00 00	00	00	00	00	00	00	00	00	00	00	00	00	00 00 00	00 00 00	DWOR			0010
4680 4690 46A0 46B0	00 00 00 00	00 00 00	00	00 00 00	00 00 00	00 00 00	00 00 00	00 00 00	00 00 00	00	00 00 00	00 00 00	00	00 00 00	00 00 00	00 00 00	DWOR			0010



THE END

Fangtian Zhong
CSCI 591

Gianforte School of Computing
Norm Asbjornson College of Engineering
E-mail: fangtian.zhong@montana.edu

 ∇