

Game-theoretic Foundations of Multi-agent Systems

Lecture 4: Computing Solution Concepts of Normal-form Games

Seyed Majid Zahedi

UNIVERSITY OF
WATERLOO



Outline

1. Brief Overview of (Mixed Integer) Linear Programming
2. Dominated Strategies
3. Minmax and Maxmin Strategies
4. Nash Equilibrium
5. Correlated NE



Example: Reproduction of Two Paintings




- Painting 1 sells for \$30
- Painting 2 sells for \$20
- We have 16 units of blue, 8 green, 5 red
- Painting 1 requires 4 blue, 1 green, 1 red
- Painting 2 requires 2 blue, 2 green, 1 red

$$\begin{aligned} \text{max.} \quad & 3x + 2y \\ \text{s.t.} \quad & 4x + 2y \leq 16 \\ & x + 2y \leq 8 \\ & x + y \leq 5 \\ & x \geq 0 \\ & y \geq 0 \end{aligned}$$

Solving Linear Program Graphically

$$\begin{array}{ll}\text{max.} & 3x + 2y \\ \text{s.t.} & 4x + 2y \leq 16 \\ & x + 2y \leq 8 \\ & x + y \leq 5 \\ & x \geq 0 \\ & y \geq 0\end{array}$$



Modified LP

$$\text{max. } 3x + 2y$$

$$\text{s.t. } 4x + 2y \leq 16$$

$$\text{s.t. } 4x + 2y \leq 15$$

$$x + 2y \leq 8$$

$$x + y \leq 5$$

$$x \geq 0$$


$$y \geq 0$$

- Optimal solution: $x = 2.5$, $y = 2.5$
- Objective = $7.5 + 5 = 12.5$
- Can we sell half paintings?




Integer Linear Program

$$\begin{array}{ll}\max. & 3x + 2y \\ \text{s.t.} & 4x + 2y \leq 15 \\ & x + 2y \leq 8 \\ & x + y \leq 5 \\ & x \in \mathbb{N}_0 \\ & y \in \mathbb{N}_0\end{array}$$



Mixed Integer Linear Program

$$\begin{array}{ll}\max. & 3x + 2y \\ \text{s.t.} & 4x + 2y \leq 15 \\ & x + 2y \leq 8 \\ & x + y \leq 5 \\ & x \geq 0 \\ & y \in \mathbb{N}_0\end{array}$$



Solving Mixed Linear/Integer Programs

- Linear programs can be solved efficiently
 - Simplex, ellipsoid, interior point methods, etc.
- (Mixed) integer programs are **NP-hard** to solve
 - Many standard NP-complete problems can be modeled as MILP
 - Search type algorithms such as branch and bound
- Standard packages for solving these
 - Gurobi, MOSEK, GNU Linear Programming Kit, CPLEX, CVXPY, etc.
- LP relaxation of (M)ILP: remove integrality constraints
 - Gives upper bound on MILP (\sim admissible heuristic)



Exercise I: Knapsack-type Problem

- We arrive in room full of precious objects
- Can carry only 30kg out of the room
- Can carry only 20 liters out of the room
- Want to maximize our total value
- Unit of object A: 16kg, 3 liters, sells for \$11 (3 units available)
- Unit of object B: 4kg, 4 liters, sells for \$4 (4 units available)
- Unit of object C: 6kg, 3 liters, sells for \$9 (1 unit available)
- What should we take?




Exercise II: Cellphones (Set Cover)

- We want to have a working phone in every continent (besides Antarctica)
- But we want to have as few phones as possible
- Phone A works in NA, SA, Af
- Phone B works in E, Af, As
- Phone C works in NA, Au, E
- Phone D works in SA, As, E
- Phone E works in Af, As, Au
- Phone F works in NA, E



Exercise III: Hot-dog Stands

- We have two hot-dog stands to be placed in somewhere along beach
- We know where groups of people who like hot dogs are
- We also know how far each group is willing to walk
- Where do we put our stands to maximize # hot dogs sold? (price is fixed)



Outline

1. Brief Overview of (Mixed Integer) Linear Programming
2. Dominated Strategies
3. Minmax and Maxmin Strategies
4. Nash Equilibrium
5. Correlated NE



Dominance by Pure Strategy

Algorithm 1: Determine whether s_i is strictly dominated by any pure strategy

```
for all  $a_i \in A_i$  where  $a_i \neq s_i$  do  
   $dom \leftarrow true$ ;  
  forall  $a_{-i} \in A_{-i}$  do  
    if  $u_i(s_i, a_{-i}) \geq u_i(a_i, a_{-i})$  then  
       $dom \leftarrow false$ ;  
      break;  
  if  $dom = true$  then  
    return  $true$ ;  
return  $false$ ;
```



Dominance by Pure Strategy: Discussion

- Complexity of the Algorithm is $O(|A|)$, linear in the size of normal-form game
- (Recall) a_i **strictly dominates** s_i if $u_i(a_i, s_{-i}) > u_i(s_i, s_{-i}) \forall s_{-i} \in S_{-i}$
- This definition refers to mixed-strategy profile of other agents
- In Alg. (1), we do not check every mixed-strategy profile of others, why?
 - Suppose a_i does not strictly dominate s_i for all a_{-i}
 - Then, there is no s_{-i} for which a_i strictly dominates s_i
 - This holds because of the linearity of expectation



Weak Dominance by Mixed Strategy

- Checking if strategy s_i is weakly dominated by any mixed strategy

$$\begin{aligned} \text{max.} \quad & \sum_{a_{-i} \in A_{-i}} \left[\left(\sum_{a_i \in A_i} p_{a_i} u_i(a_i, a_{-i}) \right) - u_i(s_i, a_{-i}) \right] \\ \text{s.t.} \quad & \sum_{a_i \in A_i} p_{a_i} u_i(a_i, a_{-i}) \geq u_i(s_i, a_{-i}) && \forall a_{-i} \in A_{-i} \\ & \sum_{a_i \in A_i} p_{a_i} = 1 \\ & p_{a_i} \geq 0, && \forall a_i \in A_i \end{aligned}$$

- If optimal solution is strictly positive, then s_i is weakly dominated by $\{p_{a_i}\}$



Strict Dominance by Mixed Strategies

- Checking if strategy s_i is strictly dominated by any mixed strategy




$$\begin{aligned} \max. \quad & \epsilon \\ \text{s.t.} \quad & \sum_{a_i \in A_i} p_{a_i} u_i(a_i, a_{-i}) \geq u_i(s_i, a_{-i}) + \epsilon \quad \forall a_{-i} \in A_{-i} \\ & \sum_{a_i \in A_i} p_{a_i} = 1 \\ & p_{a_i} \geq 0, \quad \forall a_i \in A_i \end{aligned}$$

- If optimal solution is strictly positive, then s_i is strictly dominated by $\{p_{a_i}\}$



Path Dependency of Iterated Dominance

- Iterated weak dominance is **path-dependent**:
 - Sequence of eliminations may determine which solution we get (if any)



- Iterated strict dominance is **path-independent**:
 - Elimination process will always terminate at the same point

Computational Questions for Iterated Dominance

- Does there exist some elimination path under which s_i is eliminated?
- Does there exist maximally reduced game where each agent has exactly 1 action?
- For **strict dominance**, both can be solved in polynomial time
 - Due to path-independence
 - Check if any strategy is dominated, remove it, repeat
 - With or without dominance by mixed strategies
- For **weak dominance**, both questions are NP-hard¹
 - Even when all utilities are 0 or 1
 - With or without dominance by mixed strategies

¹[Conitzer, Sandholm 05] and weaker version proved by [Gilboa, Kalai, Zemel 93]



Outline

1. Brief Overview of (Mixed Integer) Linear Programming
2. Dominated Strategies
- 3. Minmax and Maxmin Strategies**
4. Nash Equilibrium
5. Correlated NE



Recall: Minmax and Maxmin

- **Maxmin** strategy for agent i (maxmin value for agent i)

$$\operatorname{argmax}_{s_i} \min_{s_{-i}} u_i(s_i, s_{-i})$$

- **Minmax** strategy against agent i (minmax value for agent i)

$$\operatorname{argmin}_{s_{-i}} \max_{s_i} u_i(s_i, s_{-i})$$



Maxmin Strategy and Value

- Finding maxmin strategy of agent i

$$\begin{aligned} \max. \quad & U_i \\ \text{s.t.} \quad & \sum_{a_i \in A_i} p_{a_i} u_i(a_i, a_{-i}) \geq U_i, \quad \forall a_{-i} \in A_{-i} \\ & \sum_{a_i \in A_i} p_{a_i} = 1 \\ & p_{a_i} \geq 0, \quad \forall a_i \in A_i \end{aligned}$$

- Given p_{a_i} , first constraint ensures that U_i is less than any achievable expected utility for any pure strategies of opponents
- Objective of this LP, u , is **maxmin value** of agent i



Outline

1. Brief Overview of (Mixed Integer) Linear Programming
2. Dominated Strategies
3. Minmax and Maxmin Strategies
- 4. Nash Equilibrium**
5. Correlated NE



NE of Two-player, Zero-sum Games

- Maximin value for agent 1

$$\begin{aligned} \text{max.} \quad & U_1 \\ \text{s.t.} \quad & \sum_{a_1 \in A_1} p_{a_1} u_1(a_1, a_2) \geq U_1 \quad \forall a_2 \in A_2 \\ & \sum_{a_1 \in A_1} p_{a_1} = 1 \\ & p_{a_1} \geq 0, \quad \forall a_1 \in A_1 \end{aligned}$$

- Minmax value for agent 1

$$\begin{aligned} \text{min.} \quad & U_1 \\ \text{s.t.} \quad & \sum_{a_2 \in A_2} p_{a_2} u_1(a_1, a_2) \leq U_1 \quad \forall a_1 \in A_1 \\ & \sum_{a_2 \in A_2} p_{a_2} = 1 \\ & p_{a_2} \geq 0, \quad \forall a_2 \in A_2 \end{aligned}$$

- NE is expressed as LP \Rightarrow NE can be computed in polynomial time



Maximin Strategy for General-sum Games

- Agents could still play minimax strategy in general-sum games
 - I.e., pretend that the opponent is only trying to hurt you
- But this might not be rational:

		Agent 2	
		Left	Right
Agent 1	Up	0, 0	3, 1
	Down	1, 0	2, 1

- If A2 was trying to hurt A1, she would play Left, so A1 should play Down
- In reality, A2 will play Right (strictly dominant), so A1 should play Up



Hardness of Computing NE for General-sum Games

- Complexity was open for long time
 - “together with factoring [...] the most important concrete open question on the boundary of P today” [Papadimitriou STOC'01]
- Sequence of papers showed that computing any NE is PPAD-complete (even in 2-player games) [Daskalakis, Goldberg, Papadimitriou 2006; Chen, Deng 2006]
- All known algorithms require **exponential time** (in worst case)



Hardness of Computing NE for General-Sum Games (cont.)

- What about computing NE with **specific property**?
 - NE that is not Pareto-dominated
 - NE that maximizes expected social welfare (i.e., sum of all agents' utilities)
 - NE that maximizes expected utility of given agent
 - NE that maximizes expected utility of worst-off player
 - NE in which given pure strategy is played with positive probability
 - NE in which given pure strategy is played with zero probability
 - ...
- All of these are NP-hard (and the optimization questions are inapproximable assuming $P \neq NP$), even in 2-player games

[Gilboa, Zemel 89; Conitzer & Sandholm IJCAI-03/GEB-08]



Search-based Approaches (for Two-player Games)

- We can use LP, if we know support X_i of each player i 's mixed strategy

$$\begin{aligned} \text{find } & (U_1, U_2) \\ \text{s.t. } & p_{a_i} \geq 0, & \forall i, a_i \in A_i \\ & \sum_{a_i \in A_i} p_{a_i} = 1, & \forall i \\ & p_{a_i} = 0, & \forall i, a_i \in A_i / X_i \\ & \sum_{a_{-i} \in A_{-i}} p_{a_{-i}} u_i(a_i, a_{-i}) = U_i, & \forall i, a_i \in X_i \\ & \sum_{a_{-i} \in A_{-i}} p_{a_{-i}} u_i(a_i, a_{-i}) \leq U_i, & \forall i, a_i \in A_i / X_i \end{aligned}$$

- Thus, we can search over possible supports, which is basic idea underlying methods in [Dickhaut & Kaplan 91; Porter, Nudelman, Shoham AAAI04/GEB08]



NE using MILP (for Two-player Games)

[Sandholm, Gilpin, Conitzer AAAI05]

max. whatever you like (e.g., social welfare)

s.t. $p_{a_i} \geq 0,$ $\forall i, a_i \in A_i$

$\sum_{a_i \in A_i} p_{a_i} = 1,$ $\forall i$

$\sum_{a_{-i} \in A_{-i}} p_{a_{-i}} u_i(a_i, a_{-i}) = u_{a_i},$ $\forall i, a_i \in A_i$

$u_{a_i} \leq u_i,$ $\forall i, a_i \in A_i$

$p_{a_i} \leq b_{a_i},$ $\forall i, a_i \in A_i$

$u_i - u_{a_i} \leq M(1 - b_{a_i}),$ $\forall i, a_i \in A_i$

$b_{a_i} \in \{0, 1\},$ $\forall i, a_i \in A_i$

- b_{a_i} indicates whether a_i is in support of i 's mixed strategy, and M is large number



Outline

1. Brief Overview of (Mixed Integer) Linear Programming
2. Dominated Strategies
3. Minmax and Maxmin Strategies
4. Nash Equilibrium
5. Correlated NE



Correlated Equilibrium (N-player Games!)

- Variables are now p_a for all action profiles a (i.e., outcome)

max. whatever you like (e.g., social welfare)

$$\text{s.t.} \quad \sum_{a_{-i} \in A_{-i}} p_a u_i(a) \geq \sum_{a_{-i} \in A_{-i}} p_a u_i(t_i, a_{-i}) \quad \forall i, a_i t_i \in A_i$$

$$\sum_{a \in A} p_a = 1$$

$$p_a \geq 0, \quad \forall a \in A$$



Acknowledgment

- This lecture is a slightly modified version of ones prepared by
 - Vincent Conitzer [Duke CPS 590.4]
- Xiaoliang Zhou helped with importing slides from PowerPoint to L^AT_EX

