

# Cipher

Jack and Daniel are friends.  
They want to encrypt their conversation so that they can save themselves from interception by a detective agency. So they invent a new cipher.  
Every message is encoded to its binary representation  $B$  of length  $N$ .  
Then it is written down  $K$  times, shifted by  $0, 1, \dots, K-1$  bits.  
If  $B = 1001010$  and  $K = 4$  it looks so:

```
1001010
1001010
 1001010
   1001010
```

Then calculate **XOR** in every column and write it down. This number is called  $S$ . For example, XOR-ing the numbers in the above example results in

```
1110100110
```

Then the encoded message  $S$  and  $K$  are sent to Daniel.  
  
Jack is using this encoding algorithm and asks Daniel to implement a decoding algorithm.  
Can you help Daniel implement this?

### Input Format

The first line contains two integers  $N$  and  $K$ .  
The second line contains string  $S$  of length  $N+K-1$  consisting of ones and zeros.

### Output Format

Decoded message of length  $N$ , consisting of ones and zeros.

### Constraints

$1 \leq N \leq 10^6$   
 $1 \leq K \leq 10^6$   
 $|S| = N+K-1$   
It is guaranteed that  $S$  is correct.

### Sample Input#00

```
7 4
1110100110
```

### Sample Output#00

```
1001010
```

### Sample Input#01

```
6 2
1110001
```

## Sample Output#01

```
101111
```

## Explanation

### Input#00

```
1001010
1001010
1001010
1001010
-----
1110100110
```

### Input#01

```
101111
101111
-----
1110001
```