

# Deep Generative Models

## Lecture 14

Roman Isachenko

Moscow Institute of Physics and Technology  
Yandex School of Data Analysis

2025, Autumn

# Recap of Previous Lecture

# Outline

# Discrete or Continuous Diffusion Models?

**Reminder:** Diffusion models define a forward corruption process and a reverse denoising process. Previously, we studied diffusion models with continuous states  $\mathbf{x}(t) \in \mathbb{R}^m$ .

## Continuous state space

- ▶ **Discrete time**  $t \in \{0, 1, \dots, T\} \Rightarrow$  **DDPM / NCSN**.
- ▶ **Continuous time**  $t \in [0, 1] \Rightarrow$  **Score-based SDE models**.

# Discrete or Continuous Diffusion Models?

**Reminder:** Diffusion models define a forward corruption process and a reverse denoising process. Previously, we studied diffusion models with continuous states  $\mathbf{x}(t) \in \mathbb{R}^m$ .

## Continuous state space

- ▶ **Discrete time**  $t \in \{0, 1, \dots, T\} \Rightarrow$  **DDPM / NCSN**.
- ▶ **Continuous time**  $t \in [0, 1] \Rightarrow$  **Score-based SDE models**.

Now we turn to diffusion over discrete-value states  $\mathbf{x}(t) \in \{1, \dots, K\}^m$ .

## Discrete state space

- ▶ **Discrete time**  $t \in \{0, 1, \dots, T\}$ .
- ▶ **Continuous time**  $t \in [0, 1]$ .

Let's discuss why we need discrete diffusion models.

# Why Discrete Diffusion Models?

While autoregressive (AR) models dominate discrete-data domains (e.g., text or sequences), they have fundamental limitations.

# Why Discrete Diffusion Models?

While autoregressive (AR) models dominate discrete-data domains (e.g., text or sequences), they have fundamental limitations.

## Key advantages of discrete diffusion

- ▶ **Parallel generation:** diffusion enables sampling all tokens simultaneously, unlike AR's strictly left-to-right process.

# Why Discrete Diffusion Models?

While autoregressive (AR) models dominate discrete-data domains (e.g., text or sequences), they have fundamental limitations.

## Key advantages of discrete diffusion

- ▶ **Parallel generation:** diffusion enables sampling all tokens simultaneously, unlike AR's strictly left-to-right process.
- ▶ **Flexible infilling:** diffusion can mask arbitrary parts of a sequence and reconstruct them, rather than generating only from prefix to suffix.



# Why Discrete Diffusion Models?

While autoregressive (AR) models dominate discrete-data domains (e.g., text or sequences), they have fundamental limitations.

## Key advantages of discrete diffusion

- ▶ **Parallel generation:** diffusion enables sampling all tokens simultaneously, unlike AR's strictly left-to-right process.
- ▶ **Flexible infilling:** diffusion can mask arbitrary parts of a sequence and reconstruct them, rather than generating only from prefix to suffix.
- ▶ **Robustness:** diffusion avoids the "exposure bias" caused by teacher forcing in AR training.

# Why Discrete Diffusion Models?

While autoregressive (AR) models dominate discrete-data domains (e.g., text or sequences), they have fundamental limitations.

## Key advantages of discrete diffusion

- ▶ **Parallel generation:** diffusion enables sampling all tokens simultaneously, unlike AR's strictly left-to-right process.
- ▶ **Flexible infilling:** diffusion can mask arbitrary parts of a sequence and reconstruct them, rather than generating only from prefix to suffix.
- ▶ **Robustness:** diffusion avoids the "exposure bias" caused by teacher forcing in AR training.
- ▶ **Unified framework:** diffusion generalizes naturally to discrete domains that do not suit continuous Gaussian noise.

# Forward Discrete Process

## Continuous Diffusion Markov Chain

In continuous diffusion, the forward Markov chain is defined by progressively corrupting data with Gaussian noise:

$$q(\mathbf{x}_t | \mathbf{x}_{t-1}) = \mathcal{N}(\sqrt{1 - \beta_t} \mathbf{x}_{t-1}, \beta_t \mathbf{I}).$$

# Forward Discrete Process

## Continuous Diffusion Markov Chain

In continuous diffusion, the forward Markov chain is defined by progressively corrupting data with Gaussian noise:

$$q(\mathbf{x}_t | \mathbf{x}_{t-1}) = \mathcal{N}(\sqrt{1 - \beta_t} \mathbf{x}_{t-1}, \beta_t \mathbf{I}).$$

## Discrete Diffusion Markov Chain

For discrete data, we instead define a Markov chain over categorical states:

$$q(\mathbf{x}_t | \mathbf{x}_{t-1}) = \text{Categorical}(\mathbf{Q}_t \mathbf{x}_{t-1}),$$

where  $\mathbf{Q}_t \in [0, 1]^{K \times K}$  is a **transition matrix** where each column gives transition probabilities from one state to all others, and columns sum to 1:

$$[\mathbf{Q}_t]_{ij} = q(x_t = i | x_{t-1} = j), \quad \sum_{i=1}^K [\mathbf{Q}_t]_{ij} = 1.$$

# Forward Process over Time

- ▶ The forward diffusion gradually destroys information through repeated random transitions.

# Forward Process over Time

- ▶ The forward diffusion gradually destroys information through repeated random transitions.
- ▶ Applying transitions  $t$  times yields a marginal distribution:

$$q(\mathbf{x}_t|\mathbf{x}_0) = \text{Categorical}(\mathbf{Q}_{1:t}\mathbf{x}_0), \quad \mathbf{Q}_{1:t} = \mathbf{Q}_t\mathbf{Q}_{t-1} \cdots \mathbf{Q}_1.$$

# Forward Process over Time

- ▶ The forward diffusion gradually destroys information through repeated random transitions.
- ▶ Applying transitions  $t$  times yields a marginal distribution:

$$q(\mathbf{x}_t|\mathbf{x}_0) = \text{Categorical}(\mathbf{Q}_{1:t}\mathbf{x}_0), \quad \mathbf{Q}_{1:t} = \mathbf{Q}_t\mathbf{Q}_{t-1}\cdots\mathbf{Q}_1.$$

- ▶ This process drives the data towards a stationary distribution as  $t \rightarrow T$ .

# Forward Process over Time

- ▶ The forward diffusion gradually destroys information through repeated random transitions.
- ▶ Applying transitions  $t$  times yields a marginal distribution:

$$q(\mathbf{x}_t|\mathbf{x}_0) = \text{Categorical}(\mathbf{Q}_{1:t}\mathbf{x}_0), \quad \mathbf{Q}_{1:t} = \mathbf{Q}_t\mathbf{Q}_{t-1}\cdots\mathbf{Q}_1.$$

- ▶ This process drives the data towards a stationary distribution as  $t \rightarrow T$ .
- ▶ To achieve this behavior, we design the transition matrices  $\mathbf{Q}_t$  appropriately.



# Designing the Transition Matrix $Q_t$

- ▶ The choice of  $Q_t$  determines how information is erased and what the stationary distribution becomes.

# Designing the Transition Matrix $Q_t$

- ▶ The choice of  $Q_t$  determines how information is erased and what the stationary distribution becomes.
- ▶ **Uniform diffusion**

$$Q_t = (1 - \beta_t)\mathbf{I} + \beta_t\mathbf{1}\mathbf{1}^\top.$$

Each token is replaced by a uniformly random symbol with probability  $\beta_t$ . The stationary distribution is uniform noise.

# Designing the Transition Matrix $Q_t$

- ▶ The choice of  $Q_t$  determines how information is erased and what the stationary distribution becomes.
- ▶ **Uniform diffusion**

$$Q_t = (1 - \beta_t)\mathbf{I} + \beta_t\mathbf{1}\mathbf{1}^\top.$$

Each token is replaced by a uniformly random symbol with probability  $\beta_t$ . The stationary distribution is uniform noise.

- ▶ **Absorbing diffusion**

$$Q_t = (1 - \beta_t)\mathbf{I} + \beta_t\mathbf{e}_m\mathbf{1}^\top.$$

Tokens are gradually replaced by a special mask  $m$ ; the stationary distribution is fully masked.

NOT READY

# Summary

