

FlowDroid source code analysis

FlowDroid source code analysis

- MainClass
- ITaintPropagationWrapper
- SetupApplication
 - Attributes
 - Methods
 - runInfoflow()
 - runInfoflow(sourcesAndSinks)
 - initializeSoot()
 - parseAppResources()
 - processEntryPoint
 - runAnalysis
- Result

The source code of FlowDroid is cloned from [here](#).

MainClass

The class `MainClass` of `soot.sjimple.infoflow.cmd`

In method `run()`:

- Initialize the parameters

```
initializeCommandLineOptions();
```

- Parse the command-line parameters and options

```
CommandLine cmd = parser.parse(options, args);
parseCommandLineOptions(cmd, config);
```

- Get the target `APK` s

```
File targetFile = new
File(config.getAnalysisFileConfig().getTargetAPKFile());
List<File> apksToAnalyze;
```

- Get the output files

```
outputFileStr = config.getAnalysisFileConfig().getOutputFile();
```

- Initialize the `taint wrapper`

```
ITaintPropagationWrapper taintWrapper = initializeTaintWrapper(cmd);
```

See [TaintWrapper](#) below

- Configure the analyzer for current `APK` file.

Construct the `SetupApplication` by calling `createFlowDroidInstance()`.

```
analyzer = createFlowDroidInstance(config);
analyzer.setTaintWrapper(taintWrapper);
```

- Start the dataflow analysis

```
analyzer.runInfoflow();
```

See [runInfoflow](#) below

ITaintPropagationWrapper

This **interface** declares methods to define classes and methods which should not be analyzed directly. Analysis results are instead taken from an external model containing method summaries.

This one can enhance the efficiency of analysis.

Here is the important function:

- `initializeTaintWrapper`: a function out of the interface, which initializes the taint wrapper based on the command-line parameters

```
private ITaintPropagationWrapper initializeTaintWrapper(CommandLine cmd)
throws Exception;
```

- it gets the definition files for the taint wrapper.

```
String[] definitionFiles =
cmd.getOptionValues(OPTION_TAINT_WRAPPER_FILE);
```

- get the option of taint wrapper

```
String taintWrapper = cmd.getOptionValue(OPTION_TAINT_WRAPPER);
```

- construct `ITaintPropagationWrapper`

```
result = createSummaryTaintWrapper(cmd, new
LazySummaryProvider("summariesManual"));
```

SetupApplication

The class to configure the dataflow analyzer.

Attributes

- `logger`: for logging
- `sourceSinkProvider`: to provide source and sink
- `callbackMethods`:
- `entrypoints`:
- `collectedSources`:

- `collectedSinks`:
- `taintPropagationHandler`:
- `backwardsPropagationHandler`:
- ...

Methods

`runInfoflow()`

```
public InfoflowResults runInfoflow() throws IOException, XmlPullParserException;
```

runs the dataflow analysis.

- gets `sourceSinkFile`.

```
String sourceSinkFile = config.getAnalysisFileConfig().getSourceSinkFile();
```

- gets `parser` as a `source` and `sink` set provider, based on different format of `sourceSinkFile`

```
ISourceSinkDefinitionProvider parser =  
PermissionMethodParser.fromFile(sourceSinkFile)
```

- calls another `runInfoflow`

```
return runInfoflow(parser);
```

See [another runInfoflow](#) below.

`runInfoflow(sourcesAndSinks)`

```
public InfoflowResults runInfoflow(ISourceSinkDefinitionProvider  
sourcesAndSinks);
```

runs the dataflow analysis

- resets our object state by the `config` and `sourcesAndSinks`.
 - build `collectedSources` to collect all of the sources.
 - build `collectedSinks` to collect all of the sinks.
 - build `sourceSinkProvider` to get sources and sinks.

```
this.collectedSources = config.getLogSourcesAndSinks() ? new HashSet<Stmt>()  
: null;  
this.collectedSinks = config.getLogSourcesAndSinks() ? new HashSet<Stmt>() :  
null;  
this.sourceSinkProvider = sourcesAndSinks;  
this.infoflow = null;
```

- starts a new `Soot` instance

```
// Start a new Soot instance
if (config.getSootIntegrationMode() == SootIntegrationMode.CreateNewInstance)
{
    G.reset();
    initializeSoot();
}
```

- parse the resource of the App

```
parseAppResources();
```

See [parseAppResources](#) below.

- process and analyze each entry point.

```
processEntryPoint(sourcesAndSinks, resultAggregator, -1, null);
```

See [processEntryPoint](#) below.

initializeSoot()

Initializes soot for running the soot-based phases of the application.

```
private void initializeSoot();
```

- clean up old `Soot` instance.

```
G.reset();
```

- get `androidJar` and `apkFileLocation` and set the options

```
Options.v().set_xxx
```

- call `configureCallgraph`

```
configureCallgraph();
```

which configures the callgraph options for `Soot` according to `FlowDroid`'s callgraph algorithm.

parseAppResources()

parse the app resources

- get the `apk` file to analyze

```
final File targetAPK = new
File(config.getAnalysisFileConfig().getTargetAPKFile());
```

- parse the resource file

```
this.resources.parse(targetAPK.getAbsolutePath());
```

- get the `manifest` file of the App

```
this.manifest = new ProcessManifest(targetAPK, resources);
```

- add the name of nodes of `activity`, `provider`, `service`, `receiver` into `entryPoints`

```
Set<String> entryPoints = manifest.getEntryPointClasses();
```

- add unsafe Soot Class according to the name(signature) in `entryPoints`.

```
for (String className : entryPoints) {
    SootClass sc = Scene.v().getSootClassUnsafe(className);
    if (sc != null)
        this.entrypoints.add(sc);
}
```

processEntryPoint

runs the dataflow analysis on the given entry point class.

```
protected void processEntryPoint(ISourceSinkDefinitionProvider sourcesAndSinks,
    MultiRunResultAggregator resultAggregator, int numEntryPoints, SootClass
    entrypoint);
```

- calculate callback functions

```
calculateCallbacks(sourcesAndSinks);
```

- calls `calculateCallbackMethods(lfp, entryPoint)`, to calculate the set of callback methods declared in the XML resource files or the app's source code.
 - Inside it, it calls `releaseCallgraph()`, `releasePointsToAnalysis()` and `releaseReachableMethods()` to change the configuration options.
 - It also collects the callback interfaces implemented in the app's source code.

```
jimpleClass.addCallbackFilter(new
    AlienHostComponentFilter(entrypoints));
jimpleClass.addCallbackFilter(new
    ApplicationCallbackFilter(entrypoints));
jimpleClass.addCallbackFilter(new UnreachableConstructorFilter());
jimpleClass.collectCallbackMethods();
```

- parse the layout XML files in the given `APK` file.

```
lfp.parseLayoutFile(config.getAnalysisFileConfig().getTargetAPKFile(
));
```

- Iterate:

in each loop, creates the main method based on the current callback information.

```
while(hasChanged) {
    hasChanged = false;
    createMainMethod(component);
    constructCallgraphInternal();
}
```

- create and run the dataflow tracker

```
infoflow = createInfoflow();
```

- run analysis

```
infoflow.runAnalysis(sourceSinkManager,
    entryPointCreator.getGeneratedMainMethod());
```

See [runAnalysis](#) below.

- print out the found result

runAnalysis

calls this `runAnalysis` to conduct a taint analysis on an already initialized callgraph.

```
private void runAnalysis(final ISourceSinkManager sourcesSinks, final Set<String>
    additionalSeeds);
```

- check and fix configuration of dataflow server.

```
checkAndFixConfiguration();
```

- print the configuration to log

```
config.printSummary();
```

- initialize the abstraction configuration

```
Abstraction.initialize(config);
```

- build the callgraph

```
constructCallgraph();
```

- patch the system libraries we need for callgraph construction.

```
patcher.patchLibraries();
```

- set the resolving level and phantom class for each `SootClass`

```
for (SootClass sc : Scene.v().getClasses())
    if (sc.resolvingLevel() == SootClass.DANGLING) {
        sc.setResolvingLevel(SootClass.BODIES);
        sc.setPhantomClass();
    }
```

- set the packs and build the callgraph

```
PackManager.v().getPack("wjpp").apply();
PackManager.v().getPack("cg").apply();
```

- initialize the source and sink manager(I don't know why the number of selected sources and sinks are fewer than that I put in `SourcesAndSinks.txt`)

```
sourcesSinks.initialize();
```

- dead code elimination

```
eliminateDeadCode(sourcesSinks);
```

- build `ICFG`(interprocedural control flow graph)

```
buildBiDirICFG();
```

In this method, it firstly gets the `baseCFG`, and then it gets the `icfg`.

- initialize the dataflow manager

```
manager = initializeInfoflowManager(sourcesSinks, icfg, globalTaintManager);
```

- initialize the `alias` analysis and the `backwardSolver`.

```
Abstraction zeroValue = null;
IAliasingStrategy aliasingStrategy = createAliasAnalysis(sourcesSinks, icfg,
    executor, memoryManager);
IInfoflowSolver backwardSolver = aliasingStrategy.getSolver();
if (backwardSolver != null) {
    zeroValue = backwardSolver.getTabulationProblem().createZeroValue();
    solvers.add(backwardSolver);
}
```

As we can see, it gets the `backwardSolver`, which contains `icfg`, `flowFunctions` and so on.

- initialize the aliasing infrastructure

```
Aliasing aliasing = createAliasController(aliasingStrategy);
manager.setAliasing(aliasing);
```

- initialize the dataflow problem

```
InfoflowProblem forwardProblem = new InfoflowProblem(manager, zeroValue,
    ruleManagerFactory);
```

- create the forward dataflow solver

```
IInfoflowSolver forwardSolver = createForwardSolver(executor,
forwardProblem);
```

- looking for sources and sinks

```
for (SootMethod sm : getMethodsForSeeds(icfg))
    sinkCount += scanMethodForSourcesSinks(sourcesSinks, forwardProblem, sm);
```

if it has not found a source or sink, then the solver terminates.

- create the path builder

```
final IAbstractionPathBuilder builder = new BatchPathBuilder(manager,
pathBuilderFactory.createPathBuilder(manager, resultExecutor));
```

- **run solve for forwardSolver (MARK! MARK! THIS IS THE ENTRY POINT OF IFDS ALGORITHM)**

```
forwardSolver.solve();
```

It calls `submitInitialSeeds` to schedule the processing of initial seeds to initialize the analysis.

```
submitInitialSeeds()
```

In method `submitInitialSeeds()`, `initialSeeds` means the set of `<entry_node, domain>`.

For each value in the domain of the entry node, it calls `propagate()`.

Then, it calls `addFunction()` to add the new path edge.

```
/**
 * Schedules the processing of initial seeds, initiating the analysis.
 * Clients
 * should only call this methods if performing synchronization on their
 * own.
 * Normally, {@link #solve()} should be called instead.
 */
protected void submitInitialSeeds() {
    for (Entry<N, Set<D>> seed : initialSeeds.entrySet()) {
        N startPoint = seed.getKey();
        for (D val : seed.getValue())
            propagate(zeroValue, startPoint, val, null, false);
        addFunction(new PathEdge<N, D>(zeroValue, startPoint,
zeroValue));
    }
}
```

```
propagate(D sourceVal, N target, D targetVal, N relatedCallSite, boolean
isUnbalancedReturn)
```



```

/**
 * Propagates the flow further down the exploded super graph.
 *
 * @param sourceVal      the source value of the propagated summary
edge
 * @param target        the target statement
 * @param targetVal      the target value at the target statement
 * @param relatedCallSite for call and return flows the related call
 *                        statement, <code>null</code> otherwise (this
value
 *                        is not used within this implementation but
may be
 *                        useful for subclasses of {@link IFDSSolver})
 * @param isUnbalancedReturn <code>true</code> if this edge is
propagating an
 *                        unbalanced return (this value is not used
within
 *                        this implementation but may be useful for
 *                        subclasses of {@link IFDSSolver})
 */
protected void propagate(D sourceVal, N target, D targetVal,
    /* deliberately exposed to clients */ N relatedCallSite,
    /* deliberately exposed to clients */ boolean isUnbalancedReturn)
{
    ...
    final PathEdge<N, D> edge = new PathEdge<N, D>(sourceVal, target,
targetVal);
    ...
    scheduleEdgeProcessing(edge);
}

```

In `propagate()`, it first generates a summary edge `edge` based on the `sourceVal`, `target` and `targetVal`.

Then, it calls `scheduleEdgeProcessing(edge)` to propagate the summary edge.

```

/**
 * Dispatch the processing of a given edge. It may be executed in a
different
 * thread.
 *
 * @param edge the edge to process
 */
protected void scheduleEdgeProcessing(PathEdge<N, D> edge) {
    // If the executor has been killed, there is little point
    // in submitting new tasks
    if (killFlag != null || executor.isTerminating() ||
executor.isTerminated())
        return;

    executor.execute(new PathEdgeProcessingTask(edge, solverId));
    propagationCount++;
}

```

In the method of `scheduleEdgeProcessing`, it creates a new `PathEdgeProcessingTask`, then it stores this task into the thread pool, and it runs the thread by calling `executor.execute()`. Then, it continuously calls `super.execute()` until calling `public void execute(Runnable command)` in `ThreadPoolExecutor.java`, which will execute the thread and call method `public void run()` in `IFDSSolver.java`, which is like

```
public void run() {
    if (icfg.isCallStmt(edge.getTarget())) {
        processCall(edge);
    } else {
        // note that some statements, such as "throw" may be
        // both an exit statement and a "normal" statement
        if (icfg.isExitStmt(edge.getTarget()))
            processExit(edge);
        if (!icfg.getSucessOf(edge.getTarget()).isEmpty())
            processNormalFlow(edge);
    }
}
```

As we can see, given the `icfg` as the environment and the `edge (dSource, dTarget and Target)`, we can execute the IFDS algorithm described in the paper: [Practical Extensions to the IFDS Algorithm](#). Here we see those methods below:

- **processCall(edge)**

```
private void processCall(PathEdge<N, D> edge)
```

Parameter `edge` is a tuple of $\langle d_1, n, d_2 \rangle$ which represents the edge of $\langle sp, d_1 \rangle \rightarrow \langle n, d_2 \rangle$. Here, `n` is a node representing a call site; `sp` is a node representing the start point of source; `d1` and `d2` are the corresponding dataflow facts.

This method implements the `tabulation algorithm` from line 13 to line 20, which processes call flow

```

13      case  $n \in Call_p$  :
14          foreach  $d_3 \in passArgs(\langle n, d_2 \rangle)$  do
15              Propagate  $\left( \langle s_{calledProc(n)}, d_3 \rangle \xrightarrow{0} \langle s_{calledProc(n)}, d_3 \rangle \right)$ 
15.1          Incoming  $\left[ \langle s_{calledProc(n)}, d_3 \rangle \right] \cup = \langle n, d_2 \rangle$ 
15.2          foreach  $\langle e_p, d_4 \rangle \in EndSummary \left[ \langle s_{calledProc(n)}, d_3 \rangle \right]$  do
15.3              foreach  $d_5 \in returnVal(\langle e_p, d_4 \rangle, \langle n, d_2 \rangle)$  do
15.4                  Insert  $\langle n, d_2 \rangle \rightarrow \langle returnSite(n), d_5 \rangle$  into SummaryEdge
15.5              od
15.6          od
16          od
17          foreach  $d_3$  s.t.  $\langle n, d_2 \rangle \rightarrow \langle returnSite(n), d_3 \rangle \in SummaryEdge$  do
18              Propagate  $\left( \langle s_p, d_1 \rangle \xrightarrow{n} \langle returnSite(n), d_3 \rangle \right)$ 
19          od
20      end case
```

In a figure, it is like this(`n` is a node representing a call site)

```

<Sp, d1>
  |
  <n, d2>
    \
      <Scp(n), d3>
        |
        <Ecp(n), d4>
          /
        <rs(n), d5>

```

And This is what this algorithm does

1. line 15 propagates $\langle S_{cp(n)}, d_3 \rangle \rightarrow \langle S_{cp(n)}, d_3 \rangle$.
2. line 15.1 adds $\langle n, d_2 \rangle$ as the predecessor of $\langle S_{cp(n)}, d_3 \rangle$.
3. line 15.4 adds the summary edge of $\langle n, d_2 \rangle \rightarrow \langle rs(n), d_5 \rangle$.
4. line 18 propagates $\langle n, d_2 \rangle \rightarrow \langle rs(n), d_5 \rangle$.

So the **implementation** of `processCall(edge)` is

- Firstly, it gets the possible callees

```
Collection<SootMethod> callees = icfg.getCalleesOfCallAt(n);
```

- Then, it filters the methods with concrete body

```
callees.stream().filter(m -> m.isConcrete()).forEach({
    public void accept(SootMethod sCalledProcN) {}
})
```

- For the method with a concrete body, it calls `accept()` to explore this new method and insert to summary edge(if possible).**(corresponding to line 15-15.6)**

```

// compute the call-flow function
FlowFunction<D> function = flowFunctions.getCallFlowFunction(n,
sCalledProcN);
Set<D> res = computeCallFlowFunction(function, d1, d2);

Collection<N> startPointsOf = icfg.getStartPointsOf(sCalledProcN);
// for each result node of the call-flow function
for (D d3 : res) {
    // for each callee's start point(s)
    for (N sP : startPointsOf) {
        // create initial self-loop
        propagate(d3, sP, d3, n, false); // line 15
    }
    // register the fact that <sp,d3> has an incoming edge from
    // <n,d2>
    // line 15.1 of Naeem/Lhotak/Rodriguez
    if (!addIncoming(sCalledProcN, d3, n, d1, d2))
        continue;
    // line 15.2,15.3,15.4
    applyEndSummaryOnCall(d1, n, d2, returnSiteNs, sCalledProcN, d3);

```

- It first computes the dataflow fact `d3` at the startpoint of the callee.

- Then it calls `propagate(d3, sP, d3, n, false)` to propagate `<d3, sP, d3>` (which represents $\langle s_P, d_3 \rangle \rightarrow \langle s_P, d_3 \rangle$) **(corresponding to line 15)**
- Then it calls `addIncoming(sCalledProcN, d3, n, d1, d2)` to add $\langle n, d_2 \rangle$ into `Incoming[sCalledProcN, d3 >]`. **(corresponding to line 15.1)**
- At last, it calls `applyEndSummaryOnCall(d1, n, d2, returnSiteNs, sCalledProcN, d3)` to insert the summary edge, where we have

```
D d5p = d5;
...
if (d5p != d2) {
    d5p = d5p.clone();
    d5p.setPredecessor(d2);
}
```

(corresponding to line 15.4)

- At last, it calls `propagate(d1, returnSiteN, d3, n, false)` to propagate `<d1, returnSiteN, d3>`, which represents $\langle s_P, d_1 \rangle \rightarrow \langle returnSiteN, d_3 \rangle$ **(corresponding to line 18).**

```
// line 17-19 of Naeem/Lhotak/Rodriguez
// process intra-procedural flows along call-to-return flow functions
for (N returnSiteN : returnSiteNs) {
    FlowFunction<D> callToReturnFlowFunction =
flowFunctions.getCallToReturnFlowFunction(n, returnSiteN);
    Set<D> res =
computeCallToReturnFlowFunction(callToReturnFlowFunction, d1, d2);

    if (res != null && !res.isEmpty()) {
        for (D d3 : res) {
            if (memoryManager != null)
                d3 = memoryManager.handleGeneratedMemoryObject(d2, d3);
            if (d3 != null)
                //////////////////////////////////////
                //                                line 18                                //
                //////////////////////////////////////
                propagate(d1, returnSiteN, d3, n, false);
        }
    }
}
```

• processExit(edge)

```
protected void processExit(PathEdge<N, D> edge)
```

Parameter `edge` is a tuple of `<d1, n, d2>` which represents the edge of $\langle s_P, d_1 \rangle \rightarrow \langle n, d_2 \rangle$. Here, `n` is a node representing a exit node; `sp` is a node representing the start point of source; `d1` and `d2` are the corresponding dataflow facts.


Here, the method `processExit(edge)` implements line 21-32 in the tabulation algorithm

```

21      case  $n \in e_p$  :
21.1    EndSummary [ $\langle s_p, d_1 \rangle \cup \langle e_p, d_2 \rangle$ ]
22      foreach  $\langle c, d_4 \rangle \in \text{Incoming}[\langle s_p, d_1 \rangle]$  do
23        foreach  $d_5 \in \text{returnVal}(\langle e_p, d_2 \rangle, \langle c, d_4 \rangle)$  do
24          if  $\langle c, d_4 \rangle \rightarrow \langle \text{returnSite}(c), d_5 \rangle \notin \text{SummaryEdge}$  then
25            Insert  $\langle c, d_4 \rangle \rightarrow \langle \text{returnSite}(c), d_5 \rangle$  into SummaryEdge
26            foreach  $d_3$  s.t.  $\langle s_{\text{procOf}(c)}, d_3 \rangle \rightarrow \langle c, d_4 \rangle \in \text{PathEdge}$  do
27              Propagate( $\langle s_{\text{procOf}(c)}, d_3 \rangle \xrightarrow{c} \langle \text{returnSite}(c), d_5 \rangle$ )
28            od
29          fi
30        od
31      od
32    end case

```

In a figure, it is like this(n is a node representing an exit point)



And This is what this algorithm does

1. line 21.1 adds $\langle n, d_2 \rangle$ into $\text{EndSummary}[\langle S_{p(n)}, d_1 \rangle]$.
2. line 25 adds the summary edge of $\langle c, d_4 \rangle \rightarrow \langle rs(c), d_5 \rangle$.
3. line 27 propagates $\langle S_{p(c)}, d_3 \rangle \rightarrow \langle rs(c), d_5 \rangle$.

So the **implementation** of `processCall(edge)` is

- add to `EndSummary` (corresponding to line 21.1)

```
addEndSummary(methodThatNeedsSummary, d1, n, d2);
```

- add the `SummaryEdge`

```

D d5p = d5;
switch (shorteningMode) {
    case AlwaysShorten:
        if (d5p != predVal) {
            d5p = d5p.clone();
            d5p.setPredecessor(predVal);
        }
        break;
    case ShortenIfEqual:
        if (d5.equals(predVal))
            d5p = predVal;
        break;
}

```

- propagates ??? why d4??

```
propagate(d4, retSiteC, d5p, c, false);
```

• processNormalFlow(edge)

```
private void processNormalFlow(PathEdge<N, D> edge)
```

Parameter `edge` is a tuple of $\langle d1, n, d2 \rangle$ which represents the edge of $\langle sp, d1 \rangle \rightarrow \langle n, d2 \rangle$. Here, `n` is a node except call site and return node; `sp` is a node representing the start point of source; `d1` and `d2` are the corresponding dataflow facts.

Here, the method `processExit(edge)` implements line 33-38 in the tabulation algorithm

```

33      case  $n \in (N_p - Call_p - \{e_p\})$  :
34          foreach  $m, d_3$  s.t.  $n \rightarrow m \in CFG$  and  $d_3 \in flow(\langle n, d_2 \rangle, \pi)$  do
35              Propagate( $\langle s_p, d_1 \rangle \xrightarrow{n} \langle m, d_3 \rangle$ )
36          od
37      end case

```

In a figure, it is like this(n is a node except a call node and an exit node)

```

<Sp, d1>
|
<n, d2>
|
<m, d3>

```

And This is what this algorithm does

1. line 35 propagates $\langle S_p, d_1 \rangle \rightarrow \langle m, d_3 \rangle$.

So the **implementation** of `processNormalFlow(edge)` is

- propagate

```
propagate(d1, m, d3, null, false);
```

问题：

- 1.

Result

I test `FlowDroid` on an simple `apk` file, and the result is shown below:

```

[main] INFO soot.jimple.infoflow.cmd.MainClass - Analyzing app
/home/eddie/Desktop/summer_intern/FlowDroidHacking/FlowDroid/DroidBench/apk/Gener
alJava/Clone1.apk (1 of 1)...
[main] INFO soot.jimple.infoflow.android.SetupApplication - Initializing Soot...
[main] INFO soot.jimple.infoflow.android.SetupApplication - Loading dex files...
[main] INFO soot.jimple.infoflow.android.SetupApplication - ARSC file parsing
took 0.029009645 seconds
[main] INFO soot.jimple.infoflow.memory.MemoryWarningSystem - Registered a memory
warning system for 1,177.2 MiB
[main] INFO
soot.jimple.infoflow.android.entryPointCreators.AndroidEntryPointCreator -
Creating Android entry point for 1 components...

```

```
[main] INFO soot.jimple.infoflow.android.SetupApplication - Constructing the
callgraph...
[main] INFO soot.jimple.infoflow.android.callbacks.DefaultCallbackAnalyzer -
Collecting callbacks in DEFAULT mode...
[main] INFO soot.jimple.infoflow.android.callbacks.DefaultCallbackAnalyzer -
Callback analysis done.
[main] INFO
soot.jimple.infoflow.android.entryPointCreators.AndroidEntryPointCreator -
Creating Android entry point for 1 components...
[main] INFO soot.jimple.infoflow.android.SetupApplication - Constructing the
callgraph...
[main] INFO soot.jimple.infoflow.android.callbacks.DefaultCallbackAnalyzer -
Running incremental callback analysis for 1 components...
[main] INFO soot.jimple.infoflow.android.callbacks.DefaultCallbackAnalyzer -
Incremental callback analysis done.
[main] INFO soot.jimple.infoflow.memory.MemoryWarningSystem - Shutting down the
memory warning system...
[main] INFO soot.jimple.infoflow.android.SetupApplication - Callback analysis
terminated normally
[main] INFO soot.jimple.infoflow.android.SetupApplication - Entry point
calculation done.
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match: <org.springframework.web.servlet.tags.UrlTag:
java.lang.String createUrl)> -> _SINK_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match: <org.springframework.orm.hibernate3.support.ClobStringType:
int[] sqlTypes)> -> _SINK_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match:
<org.springframework.security.config.http.CsrfBeanDefinitionParser:
org.springframework.beans.factory.config.BeanDefinition getCsrfLogoutHandler)> ->
_SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match: <java.io.File: java.io.File getAbsoluteFile)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match:
<org.springframework.security.config.http.FormLoginBeanDefinitionParser:
java.lang.String getLoginPage)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match: <com.google.auth.oauth2.UserCredentials: java.lang.String
getClientSecret)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match: <org.springframework.web.servlet.tags.UrlTag:
java.lang.String createUrl)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match: <java.io.File: java.io.File getCanonicalFile)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match: <org.apache.xmlrpc.webserver.RequestData: java.lang.String
getMethod)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match:
<org.dnfs.oauth2.client.http.requests.ResourceOwnerPasswordTokenRequest:
org.dnfs.httpclient.HttpRequestEntity requestEntity)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match:
<org.springframework.security.concurrent.DelegatingSecurityContextExecutorService
: java.util.concurrent.ExecutorService getDelegate)> -> _SOURCE_
```

```

[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match:
<org.springframework.security.config.annotation.web.builders.HttpSecurity:
org.springframework.security.config.'annotation'.web.configurers.HeadersConfigure
r headers)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match: <org.springframework.web.servlet.tags.EscapeBodyTag:
java.lang.String readBodyContent)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match:
<org.springframework.security.config.http.FormLoginBeanDefinitionParser:
java.lang.String getLoginProcessingUrl)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match:
<org.springframework.security.config.annotation.web.configurers.LogoutConfigurer:
java.util.List getLogoutHandlers)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match: <org.apache.xmlrpc.webserver.RequestData: java.lang.String
getHttpVersion)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match: <com.google.auth.oauth2.DefaultCredentialsProvider:
java.io.File getWellKnownCredentialsFile)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match: <org.apache.xmlrpc.webserver.HttpServletRequestImpl: void
parseParameters)> -> _SOURCE_
[main] WARN soot.jimple.infoflow.android.data.parsers.PermissionMethodParser -
Line does not match:
[main] INFO soot.jimple.infoflow.android.source.AccessPathBasedSourceSinkManager
- Created a SourceSinkManager with 68 sources, 194 sinks, and 1 callback methods.
[main] INFO soot.jimple.infoflow.android.SetupApplication - Collecting callbacks
and building a callgraph took 0 seconds
[main] INFO soot.jimple.infoflow.android.SetupApplication - Running data flow
analysis on
/home/eddie/Desktop/summer_intern/FlowDroidHacking/FlowDroid/DroidBench/apk/Gener
alJava/Clone1.apk with 68 sources and 194 sinks...
[main] INFO soot.jimple.infoflow.InfoflowConfiguration - Implicit flow tracking
is NOT enabled
[main] INFO soot.jimple.infoflow.InfoflowConfiguration - Exceptional flow
tracking is enabled
[main] INFO soot.jimple.infoflow.InfoflowConfiguration - Running with a maximum
access path length of 5
[main] INFO soot.jimple.infoflow.InfoflowConfiguration - Using path-agnostic
result collection
[main] INFO soot.jimple.infoflow.InfoflowConfiguration - Recursive access path
shortening is enabled
[main] INFO soot.jimple.infoflow.InfoflowConfiguration - Taint analysis enabled:
true
[main] INFO soot.jimple.infoflow.InfoflowConfiguration - Using alias algorithm
FlowSensitive
[main] INFO soot.jimple.infoflow.memory.MemoryWarningSystem - Registered a memory
warning system for 1,177.2 MiB
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow -
Callgraph construction took 0 seconds
[main] INFO
soot.jimple.infoflow.codeOptimization.InterproceduralConstantValuePropagator -
Removing side-effect free methods is disabled
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Dead
code elimination took 0.020726056 seconds

```



```
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Callgraph has 13 edges
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Starting Taint Analysis
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Using context- and flow-sensitive solver
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Using context- and flow-sensitive solver
[main] WARN soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Running with limited join point abstractions can break context-sensitive path builders
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Looking for sources and sinks...
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Source lookup done, found 1 sources and 1 sinks.
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Taint wrapper hits: 4
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Taint wrapper misses: 3
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - IFDS problem with 12 forward and 2 backward edges solved in 2 seconds, processing 0 results...
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Current memory consumption: 46 MB
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Memory consumption after cleanup: 20 MB
[main] INFO soot.jimple.infoflow.memory.MemoryWarningSystem - Shutting down the memory warning system...
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Memory consumption after path building: 19 MB
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Path reconstruction took 0 seconds
[main] WARN soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - No results found.
[main] INFO soot.jimple.infoflow.android.SetupApplication$InPlaceInfoflow - Data flow solver took 3 seconds. Maximum memory consumption: 46 MB
[main] INFO soot.jimple.infoflow.android.SetupApplication - Found 0 leaks
```