# NEXUS Language Manual

Version 2.0.0
Author: fanxcz
Repository: https://github.com/fanxcz/nexus-lang

---

## 1. Introduction

NEXUS is a compiled programming language designed for native applications, tools, and games. The reference compiler is written in C++20. Programs are compiled to native code through LLVM IR or through a small built-in native backend.

The language is intentionally small, explicit, and predictable. It does not hide control flow or memory operations. Variables are stack slots, function calls are direct, and the generated LLVM IR can be inspected and compiled with a normal C++ toolchain.

NEXUS has three major parts:

1. **Compiler** (src/) – lexer, parser, semantic analysis, and code generation.
2. **Runtime** (src/runtime/runtime.cpp) – console, files, networking, graphics, audio, input, and helper functions.
3. **Standard library** (stdlib/) – convenience wrappers written in NEXUS.
4. **Self-hosting toolchain** (selfhost/) – lexer, parser, type checker, and code generator written in NEXUS.

The LLVM backend is the recommended backend. It supports the full language. The native backend

supports only a small subset and exists for experiments and tiny programs.

---

# 2. Compilation model

A NEXUS program is compiled in several stages:

1. **Lexical analysis** converts source text into tokens.
2. **Parsing** builds an abstract syntax tree.
3. **Semantic analysis** checks types and variable usage.
4. **Code generation** emits LLVM IR or native code.
5. **External compilation** (for LLVM) compiles .ll files with a clang-compatible driver and links the runtime.

This separation makes the compiler easier to debug. The generated .ll file is ordinary text and can be inspected directly.

---

# 3. Installation and build

## 3.1 Building from source

```
cmake -S . -B build
cmake --build build -j
ctest --test-dir build
```

The compiler is produced as build/nexus (or build/nexus.exe on Windows).

## 3.2 Environment variables

- NEXUS_CXX – clang-compatible driver used by self-hosting tests and by generated program compilation.

- NEXUS_SOURCE_ROOT — source root used by the compiler (set by CMake).

### 3.3 Self-hosting environment

For self-hosting tests on Windows, NEXUS_CXX can point to build/clang++.cmd, which wraps the bundled Zig toolchain.

---

## 4. First program

Create hello.nx:

```
fn main() {
    print("Hello, NEXUS!")
}
```

Run it:

```
nexus run hello.nx --backend llvm
```

What happens:

1. The compiler reads hello.nx.
2. It generates LLVM IR.
3. The runtime is linked.
4. The resulting program prints the message.

---

## 5. Lexical structure

### 5.1 Comments

Line comments begin with // and continue to the end of the line:

```
let x = 10 // comment
```

Block comments use /* and */:

```
/* This is
   a block comment. */
```

### 5.2 Identifiers

Identifiers consist of letters, digits, and underscores. They must not begin with a digit. Identifiers are case-sensitive.

### 5.3 Keywords

Keywords are reserved and cannot be used as identifiers:

```
fn let const mut return if else while for in break
struct enum import extern unsafe as match true fals
```

### 5.4 Literals

Integer literals are written in decimal form:

```
0
42
-7
```

Floating point literals contain a decimal point:

```
3.14
1.0
0.5
```

String literals are enclosed in double quotes:

```
"hello"
```

Boolean literals are:

```
true
false
```

---

# 6. Types

NEXUS has a small, explicit type system.

| Type | Meaning |
|---|---|
| i64 | signed 64-bit integer |
| f64 | 64-bit floating point number |
| bool | boolean value |
| string | text |
| void | no value |

Types are not inferred for function parameters. Function signatures must state parameter and return types explicitly.

Type annotations are part of the function declaration:

```
fn scale(x: f64, factor: f64) -> f64 {
    return x * factor
}
```

---

# 7. Variables

## 7.1 Immutable variables

Use let to declare a variable whose value does not change:

```
let x = 10
```

After declaration, x cannot be reassigned.

### 7.2 Mutable variables

Use let mut when the value will change:

```
let mut i = 0
i = i + 1
```

### 7.3 Discarding values

Use let _ to explicitly discard a value:

```
let _ = some_function()
```

This is useful when a function returns a value that is not needed.

### 7.4 Type stability

A variable keeps its type for its entire lifetime. Reassigning a value of a different type is an error:

```
let x = 10
x = 20      // ok
x = "text"  // error
```

### 7.5 Scope

Variables are scoped to the block in which they are declared. A variable declared inside an if or while block is not visible outside that block.

---

# 8. Expressions

## 8.1 Arithmetic

```
a + b
a - b
a * b
a / b
a % b
```

Integer operations use signed 64-bit arithmetic. If either operand is f64, the operation is performed in floating point.

## 8.2 Comparisons

```
a == b
a ≠ b
a < b
a ≤ b
a > b
a ≥ b
```

Comparisons produce a bool.

## 8.3 Logical operators

```
a && b
a || b
!a
```

&& and || operate on boolean values.

## 8.4 Unary minus

```
-x
```

For i64, this computes zero minus the value. For f64, it negates the floating point value.

### 8.5 String concatenation

```
let s = "hello" + " " + "world"
```

The + operator concatenates strings when at least one operand is a string.

### 8.6 Precedence

From highest to lowest:

1. Primary expressions and function calls
2. Unary - and !
3. *, /, %
4. +, -
5. Comparisons
6. &&
7. ||

Parentheses can be used to override precedence.

---

## 9. Control flow

### 9.1 If statement

```
if condition {
    ...
} else {
    ...
}
```

The condition must be boolean. The else branch is optional.

### 9.2 While loop

```
while condition {
    ...
}
```

The condition is evaluated before each iteration.

### 9.3 Blocks

Blocks are delimited by braces. They introduce a new scope:

```
{
    let x = 1
    print(x)
}
```

---

## 10. Functions

### 10.1 Declaration

```
fn name(param: type, ...) → type {
    ...
}
```

### 10.2 Parameters

Parameters are named and typed:

```
fn add(a: i64, b: i64) → i64 {
    return a + b
}
```

### 10.3 Return

```
return value
```

A function may return early. If a function does not explicitly return, the compiler may insert a default return where supported.

### 10.4 Main function

```
fn main() {
    print("Hello")
}
```

main is the program entry point. At the LLVM level it returns i32.

### 10.5 Function calls

```
let x = add(1, 2)
print(add(x, 3))
```

### 10.6 Recursion

Functions may call themselves:

```
fn factorial(n: i64) → i64 {
    if n ≤ 1 {
        return 1
    }
    return n * factorial(n - 1)
}
```

### 10.7 Function order

Functions must be declared before they are called. The compiler processes declarations in source order.

---

# 11. Strings

## 11.1 Literals

```
let s = "hello"
```

## 11.2 Escape sequences

```
"\n"   // newline
"\t"   // tab
"\r"   // carriage return
"\\"   // backslash
"\""   // double quote
```

## 11.3 Concatenation

```
let s = "a" + " " + "b"
```

## 11.4 Printing strings

```
print("hello")
```

## 11.5 Byte-oriented operations

String operations in the standard library are byte-oriented. This keeps the implementation simple and predictable.

---

# 12. Floating point

Floating point values use the f64 type:

```
let x = 1.5
let y = 2.0
print(x + y)
print(x * y)
print(x / y)
```

Comparisons:

```
if x < y {
    print("less")
}
```

Floating point arithmetic follows IEEE-754 semantics through LLVM.

---

## 13. Modules and imports

Import a module by file name:

```
import "io.nx"
```

The standard library is located in stdlib/. Imports make the module's functions available.

---

## 14. Standard library

### 14.1 io

```
read_line(prompt: string) → string
read_i64(prompt: string) → i64
read_f64(prompt: string) → f64
```

### 14.2 fs

```
fs_read(path: string) → string
fs_write(path: string, data: string) → i64
fs_exists(path: string) → bool
```

### 14.3 string

```
len(s: string) → i64
byte_at(s: string, index: i64) → i64
byte_len(s: string) → i64
```

### 14.4 os

```
args_count() → i64
args_get(index: i64) → string
```

### 14.5 net

```
http_get_text(url: string) → string
```

### 14.6 json

```
json_field(json: string, key: string) → string
```

### 14.7 db

```
db_open(path: string) → i64
db_exec(db: i64, sql: string) → i64
db_close(db: i64)
```

### 14.8 crypto

```
hash_sha256(text: string) → string
```

### 14.9 memory

```
memory_alloc(bytes: i64) → i64
memory_free(ptr: i64)
```

---

## 15. Runtime functions

The runtime provides low-level functions used by generated code:

```
nexus_print_i64(i64)
nexus_print_f64(double)
nexus_print_bool(i1)
nexus_print_str(ptr)

nexus_str_concat(ptr, ptr) → ptr
nexus_str_equal(ptr, ptr) → i1

nexus_file_read(ptr) → ptr
nexus_file_write(ptr, ptr) → i64
nexus_file_exists(ptr) → i1

nexus_env(ptr) → ptr
nexus_system(ptr) → i64
nexus_exit(i64)
```

These functions are declared automatically in generated LLVM IR.

---

# 16. Tooling

## 16.1 Running programs

```
nexus run file.nx --backend llvm
```

## 16.2 Type checking

```
nexus check file.nx
```

## 16.3 Building

```
nexus build
```

## 16.4 REPL

```
nexus repl
```

## 16.5 Formatting

```
nexus fmt file.nx
```

## 16.6 Self-test

```
nexus self-test
```

## 16.7 Doctor

```
nexus doctor
```

### 16.8 Backends

- llvm supports the full language.
- native supports only a small subset.

Use --backend llvm for all real programs.

---

## 17. Build system

NEXUS uses CMake:

```
cmake -S . -B build
cmake --build build
ctest --test-dir build
```

The build produces the compiler, tests, and runtime tests.

---

## 18. Native backend

The native backend is intentionally small. It is useful for experiments but does not support strings, functions with full type support, or most standard library features.

For any non-trivial program, use:

```
nexus run file.nx --backend llvm
```

---

## 19. Self-hosting

The selfhost/ directory contains a compiler written in NEXUS:

- lexer_lib.nx
- parser_lib.nx
- typecheck_lib.nx

- codegen_lib.nx

The self-hosted code generator supports:

- let and let mut
- assignment
- print
- arithmetic
- comparisons
- logical operators
- unary minus
- if and else
- while
- functions and calls
- string literals
- f64

Self-hosting is considered complete only when the self-hosted compiler produces output matching the C++ compiler on the test corpus.

---

## 20. Grammar

```
program      := declaration*
declaration  := function | statement
function     := "fn" IDENT "(" params ")" ("→" typ
params       := (param ("," param)*)?
param        := IDENT ":" type
type         := "i64" | "f64" | "bool" | "string" |
block        := "{" statement* "}"
statement    := let | assign | print | if | while |
let          := "let" "mut"? IDENT "=" expression
assign       := IDENT "=" expression
print        := "print" "(" expression ")"
if           := "if" expression block ("else" block
while        := "while" expression block
return       := "return" expression?
```

---

# 21. Examples

## 21.1 Factorial

```
fn factorial(n: i64) → i64 {
    if n ≤ 1 {
        return 1
    }
    return n * factorial(n - 1)
}

fn main() {
    print(factorial(10))
}
```

## 21.2 Floating point

```
fn main() {
    let x = 1.5
    let y = 2.0
    print(x + y)
    print(x * y)
}
```

## 21.3 Strings

```
fn main() {
    print("hello")
    print("a" + " " + "b")
}
```

## 21.4 Loop and sum

```
fn main() {
    let mut i = 0
    let mut sum = 0
```

```
    while i < 5 {
        sum = sum + i
        i = i + 1
    }
    print(sum)
}
```

### 21.5 Functions

```
fn mul(a: i64, b: i64) → i64 {
    return a * b
}

fn main() {
    print(mul(6, 7))
}
```

---

## 22. Troubleshooting

### Program does not run

Use the LLVM backend:

```
nexus run file.nx --backend llvm
```

### Link errors

Ensure NEXUS_CXX points to a clang-compatible driver.

### Type errors

Run:

```
nexus check file.nx
```

### Self-hosting tests fail

Ensure a clang-compatible compiler is available and NEXUS_CXX is set.

---

## 23. Design notes

NEXUS favors explicitness over implicit behavior. Types are stated in function signatures, variables must be declared before use, and the generated LLVM IR is readable. This makes the language suitable for learning, tooling, and systems-oriented programming.

---

## 24. Notes

- Functions must be declared before use.
- Use let mut for mutable variables.
- let _ = ... discards a value.
- Native backend is limited; use LLVM backend for full programs.
- Documentation is versioned with the repository.

---

## 25. Runtime function reference

This appendix lists the runtime functions available to generated programs.

### Animation

| Function |
| --- |
| nexus_gfx_anim_create |
| nexus_gfx_anim_destroy |
| nexus_gfx_anim_draw |
| nexus_gfx_anim_frame |

| Function |
| --- |
| nexus_gfx_anim_update |

### Audio

| Function |
| --- |
| nexus_gfx_music_load |
| nexus_gfx_music_play |
| nexus_gfx_music_stop |
| nexus_gfx_music_volume |
| nexus_gfx_sound_load |
| nexus_gfx_sound_play |
| nexus_gfx_sound_playing |
| nexus_gfx_sound_stop |
| nexus_gfx_sound_tone |
| nexus_gfx_sound_unload |
| nexus_gfx_sound_volume |

### Canvas

| Function |
| --- |
| nexus_gfx_canvas_brush |
| nexus_gfx_canvas_checkpoint |
| nexus_gfx_canvas_clear |
| nexus_gfx_canvas_create |
| nexus_gfx_canvas_destroy |
| nexus_gfx_canvas_draw |
| nexus_gfx_canvas_fill |

| Function |
| --- |
| nexus_gfx_canvas_height |
| nexus_gfx_canvas_line |
| nexus_gfx_canvas_load_bmp |
| nexus_gfx_canvas_rect |
| nexus_gfx_canvas_redo |
| nexus_gfx_canvas_save_bmp |
| nexus_gfx_canvas_undo |
| nexus_gfx_canvas_width |

### Crypto

| Function |
| --- |
| nexus_sha256 |

### Database

| Function |
| --- |
| nexus_sqlite_close |
| nexus_sqlite_exec |
| nexus_sqlite_open |

### ECS

| Function |
| --- |
| nexus_ecs_alive |
| nexus_ecs_collides |
| nexus_ecs_count |
| nexus_ecs_create |

| Function |
| --- |
| nexus_ecs_destroy |
| nexus_ecs_draw |
| nexus_ecs_set_color |
| nexus_ecs_set_position |
| nexus_ecs_set_size |
| nexus_ecs_set_texture |
| nexus_ecs_set_velocity |
| nexus_ecs_update |
| nexus_ecs_x |
| nexus_ecs_y |

### Files

| Function |
| --- |
| nexus_file_exists |
| nexus_file_read |
| nexus_file_write |

### Graphics 2D

| Function |
| --- |
| nexus_gfx_audio_available |
| nexus_gfx_audio_error |
| nexus_gfx_backend |
| nexus_gfx_begin |
| nexus_gfx_camera_reset |
| nexus_gfx_camera_set |

| Function |
| --- |
| nexus_gfx_circle |
| nexus_gfx_clear |
| nexus_gfx_cursor_visible |
| nexus_gfx_dt |
| nexus_gfx_end |
| nexus_gfx_error |
| nexus_gfx_fullscreen |
| nexus_gfx_height |
| nexus_gfx_image_type |
| nexus_gfx_init |
| nexus_gfx_is_fullscreen |
| nexus_gfx_line |
| nexus_gfx_maximize |
| nexus_gfx_poll |
| nexus_gfx_rect |
| nexus_gfx_restore |
| nexus_gfx_set_title |
| nexus_gfx_set_ui_resolution |
| nexus_gfx_should_close |
| nexus_gfx_shutdown |
| nexus_gfx_vsync |
| nexus_gfx_width |

## Graphics 3D

| Function |
| --- |
| nexus_gfx3d_begin |
| nexus_gfx3d_cube |
| nexus_gfx3d_end |
| nexus_gfx3d_grid |
| nexus_gfx3d_model_draw |
| nexus_gfx3d_model_load |
| nexus_gfx3d_model_unload |

## Input

| Function |
| --- |
| nexus_gfx_event_is |
| nexus_gfx_event_key |
| nexus_gfx_event_mouse_button |
| nexus_gfx_event_type |
| nexus_gfx_event_x |
| nexus_gfx_event_y |
| nexus_gfx_key_down |
| nexus_gfx_mouse_down |
| nexus_gfx_mouse_x |
| nexus_gfx_mouse_y |
| nexus_input |
| nexus_input_f64 |
| nexus_input_i64 |

### JSON

| Function |
| --- |
| nexus_json_get |

### Lists

| Function |
| --- |
| nexus_ilist_get |
| nexus_ilist_len |
| nexus_ilist_new |
| nexus_ilist_push |
| nexus_ilist_set |
| nexus_slist_get |
| nexus_slist_len |
| nexus_slist_new |
| nexus_slist_push |

### Math

| Function |
| --- |
| nexus_sqrt |
| nexus_to_f64 |
| nexus_to_i64 |

### Memory

| Function |
| --- |
| nexus_mem_alloc |
| nexus_mem_copy |

| Function |
| --- |
| nexus_mem_free |
| nexus_mem_read |
| nexus_mem_set |

### Networking

| Function |
| --- |
| nexus_http_get |

### OS arguments

| Function |
| --- |
| nexus_os_args_count |
| nexus_os_args_get |

### Particles

| Function |
| --- |
| nexus_gfx_particle_alive |
| nexus_gfx_particle_create |
| nexus_gfx_particle_destroy |
| nexus_gfx_particles_clear |
| nexus_gfx_particles_draw |
| nexus_gfx_particles_update |

### Physics

| Function |
| --- |
| nexus_physics_aabb |

| Function |
| --- |
| nexus_physics_circle |

### Printing

| Function |
| --- |
| nexus_print_bool |
| nexus_print_f64 |
| nexus_print_i64 |
| nexus_print_str |

### Safety

| Function |
| --- |
| nexus_bounds_check |

### Scenes

| Function |
| --- |
| nexus_scene_add |
| nexus_scene_clear |
| nexus_scene_create |
| nexus_scene_destroy |
| nexus_scene_load |
| nexus_scene_save |

### Screen

| Function |
| --- |
| nexus_screen_begin |

| Function |
| --- |
| nexus_screen_clear |
| nexus_screen_end |
| nexus_screen_height |
| nexus_screen_present |
| nexus_screen_put |
| nexus_screen_set_title |
| nexus_screen_width |

### String conversion

| Function |
| --- |
| nexus_str_bool |
| nexus_str_concat |
| nexus_str_equal |
| nexus_str_f64 |
| nexus_str_i64 |

### Strings

| Function |
| --- |
| nexus_string_byte_at |
| nexus_string_contains |
| nexus_string_find |
| nexus_string_len |
| nexus_string_lower |
| nexus_string_slice |
| nexus_string_split_at |

| Function |
| --- |
| nexus_string_split_count |
| nexus_string_trim |
| nexus_string_upper |

### System

| Function |
| --- |
| nexus_beep |
| nexus_capture_output |
| nexus_clear |
| nexus_env |
| nexus_exit |
| nexus_key_pressed |
| nexus_random_i64 |
| nexus_read_key |
| nexus_sleep_ms |
| nexus_system |
| nexus_time_ms |

### Text and fonts

| Function |
| --- |
| nexus_gfx_font_default |
| nexus_gfx_font_load |
| nexus_gfx_font_style |
| nexus_gfx_font_unload |
| nexus_gfx_text |

| Function |
| --- |
| nexus_gfx_text_font |
| nexus_gfx_text_height |
| nexus_gfx_text_width |
| nexus_gfx_texture_draw |
| nexus_gfx_texture_draw_frame |
| nexus_gfx_texture_filter |
| nexus_gfx_texture_height |
| nexus_gfx_texture_load |
| nexus_gfx_texture_unload |
| nexus_gfx_texture_width |

### UI

| Function |
| --- |
| nexus_ui_button |
| nexus_ui_checkbox |
| nexus_ui_label |
| nexus_ui_panel |
| nexus_ui_progress |
| nexus_ui_slider |

---