



TM

TIBCO JasperReports® Server Community Project Source Build Guide

Software Release 7.5

Important Information

SOME TIBCO SOFTWARE EMBEDS OR BUNDLES OTHER TIBCO SOFTWARE. USE OF SUCH EMBEDDED OR BUNDLED TIBCO SOFTWARE IS SOLELY TO ENABLE THE FUNCTIONALITY (OR PROVIDE LIMITED ADD-ON FUNCTIONALITY) OF THE LICENSED TIBCO SOFTWARE. THE EMBEDDED OR BUNDLED SOFTWARE IS NOT LICENSED TO BE USED OR ACCESSED BY ANY OTHER TIBCO SOFTWARE OR FOR ANY OTHER PURPOSE.

USE OF TIBCO SOFTWARE AND THIS DOCUMENT IS SUBJECT TO THE TERMS AND CONDITIONS OF A LICENSE AGREEMENT FOUND IN EITHER A SEPARATELY EXECUTED SOFTWARE LICENSE AGREEMENT, OR, IF THERE IS NO SUCH SEPARATE AGREEMENT, THE CLICKWRAP END USER LICENSE AGREEMENT WHICH IS DISPLAYED DURING DOWNLOAD OR INSTALLATION OF THE SOFTWARE (AND WHICH IS DUPLICATED IN THE LICENSE FILE) OR IF THERE IS NO SUCH SOFTWARE LICENSE AGREEMENT OR CLICKWRAP END USER LICENSE AGREEMENT, THE LICENSE(S) LOCATED IN THE "LICENSE" FILE(S) OF THE SOFTWARE. USE OF THIS DOCUMENT IS SUBJECT TO THOSE TERMS AND CONDITIONS, AND YOUR USE HEREOF SHALL CONSTITUTE ACCEPTANCE OF AND AN AGREEMENT TO BE BOUND BY THE SAME.

ANY SOFTWARE ITEM IDENTIFIED AS THIRD PARTY LIBRARY IS AVAILABLE UNDER SEPARATE SOFTWARE LICENSE TERMS AND IS NOT PART OF A TIBCO PRODUCT. AS SUCH, THESE SOFTWARE ITEMS ARE NOT COVERED BY THE TERMS OF YOUR AGREEMENT WITH TIBCO, INCLUDING ANY TERMS CONCERNING SUPPORT, MAINTENANCE, WARRANTIES, AND INDEMNITIES. DOWNLOAD AND USE OF THESE ITEMS IS SOLELY AT YOUR OWN DISCRETION AND SUBJECT TO THE LICENSE TERMS APPLICABLE TO THEM. BY PROCEEDING TO DOWNLOAD, INSTALL OR USE ANY OF THESE ITEMS, YOU ACKNOWLEDGE THE FOREGOING DISTINCTIONS BETWEEN THESE ITEMS AND TIBCO PRODUCTS.

This document is subject to U.S. and international copyright laws and treaties. No part of this document may be reproduced in any form without the written authorization of TIBCO Software Inc.

TIBCO, the TIBCO logo, JasperSoft, JasperReports, and Visualize.js are registered trademarks of TIBCO Software Inc. in the United States and/or other countries.

Java and all Java based trademarks and logos are trademarks or registered trademarks of Oracle and/or its affiliates.

All other product and company names and marks mentioned in this document are the property of their respective owners and are mentioned for identification purposes only.

THIS DOCUMENT IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT.

THIS DOCUMENT COULD INCLUDE TECHNICAL INACCURACIES OR TYPOGRAPHICAL ERRORS. CHANGES ARE PERIODICALLY ADDED TO THE INFORMATION HEREIN; THESE CHANGES WILL BE INCORPORATED IN NEW EDITIONS OF THIS DOCUMENT. TIBCO SOFTWARE INC. MAY MAKE IMPROVEMENTS AND/OR CHANGES IN THE PRODUCT(S) AND/OR THE PROGRAM(S) DESCRIBED IN THIS DOCUMENT AT ANY TIME.

THE CONTENTS OF THIS DOCUMENT MAY BE MODIFIED AND/OR QUALIFIED, DIRECTLY OR INDIRECTLY, BY OTHER DOCUMENTATION WHICH ACCOMPANIES THIS SOFTWARE, INCLUDING BUT NOT LIMITED TO ANY RELEASE NOTES AND "README" FILES.

This and other products of TIBCO Software Inc. may be covered by registered patents. Please refer to TIBCO's Virtual Patent Marking document (<https://www.tibco.com/patents>) for details.

Copyright © 2005-2019. TIBCO Software Inc. All Rights Reserved.

TABLE OF CONTENTS

Chapter 1 Introduction	5
1.1 Supported Build Configurations	6
1.2 JasperReports Server Source Code Archives	6
Chapter 2 Components Required for Source Build	7
2.1 Check Your Java JDK	7
2.2 Check Your Maven Version	7
2.3 Check Your Application Server	8
2.4 Check Your Database Instance	8
2.5 Check Your PhantomJS Version	8
Chapter 3 Building JasperReports Server Source Code	9
3.1 Introduction to Buildomatic Source Build Scripts	9
3.2 Downloading and Unpacking JasperReports Server Source Code	9
3.2.1 Downloading the Source Archive	9
3.2.2 Unpacking the Source Archive	9
3.2.3 Source Code Package Structure	10
3.3 Check Apache Ant	10
3.4 Configuring the Buildomatic Properties	10
3.4.1 PostgreSQL	10
3.4.2 MySQL	11
3.5 Build Source Code	12
3.6 Set Java Options	13
3.6.1 Set Increased JAVA_OPTS Settings	13
3.7 Starting JasperReports Server	14
3.8 Logging into JasperReports Server	14
3.9 JasperReports Server Log Files	14
Chapter 4 Create and Load Sample Data	15
4.1 Load Sample Data	15
4.2 Generate Your Own Sample Resources	15
4.2.1 Generating Sample Resources for MySQL and PostgreSQL Databases	16
Chapter 5 Additional Buildomatic Information	17
5.1 Detailed Description of the deploy-webapp-ce Target	17

5.2 Running Ant in Debug Mode	17
5.2.1 Regenerate Your Buildomatic Property Settings	17
5.3 Using Your Own Apache Ant: Get ant-contrib.jar	18
5.4 Generated Property Files	18
5.5 Existing and Generated Database SQL Files	19
5.6 Generated WAR File Location and deploy-webapp-ce Target	19
5.7 Details on Database Load Build Targets	20
5.7.1 create-load-js-db-ce	20
5.7.2 create-load-all-dbs-ce	20
5.8 General Fresh Database Schema File	20
5.9 Older Buildomatic Commands	21
5.10 Manual Creation of Databases	21
5.10.1 Manually Creating Databases: PostgreSQL	22
5.10.2 Additional Databases	22
Chapter 6 Jaspersoft Internal Developers and Advanced Developers	23
6.1 Internal Developers and Advanced Developers	23
6.2 Additional Properties in default_master.properties	24
Appendix A Building JasperJPivot Source Code	27
Appendix B Java Options	29
B.1 Setting Java JVM Options	29
B.1.1 Tomcat and JBoss JVM Options	29
Appendix C Troubleshooting	31
C.1 Build Troubleshooting	31
C.1.1 Name Undefined Error (Old Ant Version)	31
C.2 Database Troubleshooting	32
C.3 Maven Troubleshooting	32
C.3.1 Maven Error on Linux or Mac	32
C.3.2 Clear JasperReports Server Artifacts in Maven Local Repository	32
C.3.3 Clear Entire Local Repository	33
C.3.4 Maven Warnings	33
C.3.5 Old Maven Binary	33
C.4 Other Build Troubleshooting	33
C.4.1 Error When Building Database Scripts	33

CHAPTER 1 INTRODUCTION

TIBCO JasperReports® Server builds on TIBCO JasperReports® Library as a comprehensive family of Business Intelligence (BI) products, providing robust static and interactive reporting, report server, and data analysis capabilities. These capabilities are available as either stand-alone products, or as part of an integrated end-to-end BI suite utilizing common metadata and provide shared services, such as security, a repository, and scheduling. The server exposes comprehensive public interfaces enabling seamless integration with other applications and the capability to easily add custom functionality.



This section describes functionality that can be restricted by the software license for JasperReports Server. If you don't see some of the options described in this section, your license may prohibit you from using them. To find out what you're licensed to use, or to upgrade your license, contact Jaspersoft.

The heart of the TIBCO Jaspersoft® BI Suite is the server, which provides the ability to:

- Easily create new reports based on views designed in an intuitive, web-based, drag and drop Ad Hoc Editor.
- Efficiently and securely manage many reports.
- Interact with reports, including sorting, changing formatting, entering parameters, and drilling on data.
- Schedule reports for distribution through email and storage in the repository.
- Arrange reports and web content to create appealing, data-rich Jaspersoft Dashboards that quickly convey business trends.

For users interested in multi-dimensional modeling, we offer Jaspersoft® OLAP, which runs as part of the server.

While the Ad Hoc Editor lets users create simple reports, more complex reports can be created outside of the server. You can either use Jaspersoft® Studio or manually write JRXML code to create a report that can be run in the server. We recommend that you use Jaspersoft Studio unless you have a thorough understanding of the JasperReports file structure.

You can use the following sources of information to learn about JasperReports Server:

- Our core documentation describes how to install, administer, and use JasperReports Server and Jaspersoft Studio. Core documentation is available as PDFs in the doc subdirectory of your JasperReports Server installation. You can also access PDF and HTML versions of these guides online from the [Documentation section](#) of the Jaspersoft Community website.
- Our Ultimate Guides document advanced features and configuration. They also include best practice recommendations and numerous examples. You can access PDF and HTML versions of these guides online from the [Documentation section](#) of the Jaspersoft Community website.

- Our [Online Learning Portal](#) lets you learn at your own pace, and covers topics for developers, system administrators, business users, and data integration users. The Portal is available online from the Professional Services section of our [website](#).
- Our free samples, which are installed with JasperReports Library, Jaspersoft Studio, and JasperReports Server, are available and documented online. Please visit our [GitHub repository](#).
- If you have a subscription to our professional support offerings, please contact our Technical Support team when you have questions or run into difficulties. They're available on the web at and through email at <http://support.tibco.com> and js-support@tibco.com.

JasperReports Server is a component of both a community project and commercial offerings. Each integrates the standard features such as security, scheduling, a web services interface, and much more for running and sharing reports. Commercial editions provide additional features, including Ad Hoc views and reports, advanced charts, dashboards, Domains, auditing, and a multi-organization architecture for hosting large BI deployments.

This guide assists developers in obtaining, setting up, building, and running JasperReports Server from its source files.



This document describes how to build from a command line shell in Linux or Windows. It does not address the process of building within an IDE (Integrated Development Environment) such as Eclipse or IntelliJ.

1.1 Supported Build Configurations

The following table lists the target configurations that can be built from the source:

Application Server	Database
Tomcat, JBoss or GlassFish	PostgreSQL
	MySQL

1.2 JasperReports Server Source Code Archives

The following table lists the source code archive files for JasperReports Server:

File	Description	Documented In
TIB_js-jrs-cp_7.5.0_src.zip	JasperReports Server source code	Chapter 2, “Components Required for Source Build,” on page 7 Chapter 3, “Building JasperReports Server Source Code,” on page 9
jasperpivot-5.1.0-src.zip	JasperJPivot source code	B.1, “Setting Java JVM Options,” on page 29

CHAPTER 2 COMPONENTS REQUIRED FOR SOURCE BUILD

The components and versions listed in this section are required to build and run JasperReports Server:

- **Check Your Java JDK**
- **Check Your Maven Version**
- **Check Your Application Server**
- **Check Your Database Instance**
- **Check Your PhantomJS Version**

2.1 Check Your Java JDK

You must compile the JasperReports Server source code under Java 1.8. To check the version of your JDK (Java Development Kit), run the following command:

```
javac -version
```

To download the Java JDK, follow the instructions on the Java web site:

<http://www.oracle.com/technetwork/java/javase/downloads/index.html>.

The Oracle/Sun JDK is the certified Java platform for JasperReports Server. OpenJDK 1.8 is also supported.

2.2 Check Your Maven Version

We use Apache Maven 3.3.9 to compile, build, and package the JasperReports Server source code because of its ability to manage third party dependencies via online repositories.

To download and install Maven go to: <http://maven.apache.org/download.html#installation>

To execute `mvn` from the command line, put the maven binary (`mvn` or `mvn.exe`) in your environment `PATH`. To check your Maven version, run this command:

```
mvn -version
```

For information about Maven, see “**Maven Troubleshooting**” on page 32.

2.3 Check Your Application Server

To run JasperReports Server, you need an application server on the same computer as your source code. We support the following application servers:

Application Server	Comments
Apache Tomcat	Source build can automatically deploy to this application server.
Glassfish	Source build can automatically deploy to this application server.
JBoss	Source build can automatically deploy to this application server.

2.4 Check Your Database Instance

To run JasperReports Server, you need a database instance. We support the following:

Database	Comments
PostgreSQL	Source build automatically creates the <code>jasperserver</code> database.
MySQL	Source build automatically creates the <code>jasperserver</code> database.

2.5 Check Your PhantomJS Version

To build JasperReports Server, you need to install PhantomJS and set the property `headless.browser` in `default_master.properties`. We recommend version 2.1.1 of PhantomJS. See the *JasperReports Server Community Project Administrator Guide* for more information about PhantomJS.

CHAPTER 3 BUILDING JASPERREPORTS SERVER SOURCE CODE



This document describes how to build from a command line shell in Linux or Windows. It does not address the process of building within an IDE (Integrated Development Environment) such as Eclipse or IntelliJ.

3.1 Introduction to Buildomatic Source Build Scripts

The JasperReports Server source code comes with a set of configuration and build scripts based on Apache Ant known as the buildomatic scripts. You'll find these scripts in the following directory:

`<js-src>/jasperserver/buildomatic`

The buildomatic scripts automate most aspects of configuring, building, and deploying the source code. Apache Ant is bundled into the source code distribution to simplify the setup.

3.2 Downloading and Unpacking JasperReports Server Source Code

3.2.1 Downloading the Source Archive

Download the source code package zip for JasperReports Server from [the Jaspersoft community site](http://community.jaspersoft.com) (<http://community.jaspersoft.com>):

The download package is `TIB_js-jrs-cp_7.5.0_src.zip`

3.2.2 Unpacking the Source Archive

Unpack the `TIB_js-jrs-cp_7.5.0_src.zip` file to a directory location, such as `C:\` or `/home/<user>`. The resulting location is referred to as `<js-src>` in this document.

Windows: `<js-src>` example is `C:\JasperReports-Server-cp-7.5.0-src`

Linux: `<js-src>` example is `/home/<user>/JasperReports-Server-cp-7.5.0-src`

3.2.3 Source Code Package Structure

After you've unpacked the zip file, the folder directory has the following structure:

Directory or file	Description
<js-src>/apache-ant	Bundled version of Apache Ant build tool
<js-src>/jasperserver	JasperReports Server open source code for core functionality
<js-src>/jasperserver-repo	Dependent jar files (not readily available publicly)

3.3 Check Apache Ant

The Apache Ant tool is bundled (pre-integrated) into the source code distribution package so you don't need to download or install Ant to run the buildomatic scripts. For example:

```
cd <js-src>/jasperserver/buildomatic
js-ant help    or
./js-ant help (Linux)
```

If you don't use the bundled version of Apache Ant, we recommend version 1.9.4 or later. Versions earlier than 1.8.1 are not compatible.

3.4 Configuring the Buildomatic Properties

The buildomatic scripts are found at the following location:

```
<js-src>/jasperserver/buildomatic
```

Use the buildomatic scripts to build the source code and configure settings for a supported application server and database. The file for configuring these settings is `default_master.properties`. The source distribution includes a properties file for each type of database. You'll add your specific settings to this file and rename it to:

`default_master.properties`



When specifying paths with Apache Ant and Java in Windows, a single forward slash (/) normally works the same as “escaped” double backslashes (\\).

3.4.1 PostgreSQL

1. Go to the buildomatic directory in the source distribution:

```
cd <js-src>/jasperserver/buildomatic
```

2. Copy the PostgreSQL specific file to the current directory and change its name to `default_master.properties` as shown below:

Windows: `copy sample_conf\postgresql_master.properties default_master.properties`

Linux: `cp sample_conf/postgresql_master.properties default_master.properties`

3. Edit the new default_master.properties file and set the following properties for your local environment:

Property	Examples
appServerType	appServerType=tomcat [jboss-eap-7, wildfly, skipAppServerCheck]
appServerDir	appServerDir = C:\\Program Files\\Apache Software Foundation\\Tomcat 9.0 appServerDir = /home/<user>/apache-tomcat-9.0
dbHost	dbHost=localhost
dbUsername	dbUsername=postgres
dbPassword	dbPassword=postgres
maven	maven = C:\\apache-maven-3.3.9\\bin\\mvn.cmd maven = /home/<user>/apache-maven-3.3.9/bin/mvn
js-path	js-path = C:\\JasperReports-Server-cp-7.5.0-src\\jasperserver js-path = /home/<user>/JasperReports-Server-cp-7.5.0-src/jasperserver
js-pro-path	js-pro-path = (Path must be declared, but doesn't require a value.)
repo-path	repo-path = C:\\JasperReports-Server-cp-7.5.0\\jasperserver-repo repo-path = /home/<user>/JasperReports-Server-cp-7.5.0-src/jasperserver-repo
headless.browser	c:/phantomjs-2.1.1-windows/bin/phantomjs.exe /opt/phantomjs/bin/phantomjs

3.4.2 MySQL

- Go to the buildomatic directory in the source distribution:

```
cd <js-src>/jasperserver/buildomatic
```
- Copy the MySQL specific file to the current directory and change its name to default_master.properties:

Windows: `copy sample_conf/mysql_master.properties default_master.properties`
Linux: `cp sample_conf/mysql_master.properties default_master.properties`
- Edit the new default_master.properties file and set the following properties to your local environment:

Property	Examples
appServerType	appServerType=tomcat [jboss-eap-7, wildfly, skipAppServerCheck]

Property	Examples
appServerDir	appServerDir = C:\\Program Files\\Apache Software Foundation\\Tomcat 9.0 appServerDir = /home/<user>/apache-tomcat-9.0
dbHost	dbHost = localhost
dbUsername	dbUsername = root
dbPassword	dbPassword = password
maven	maven = C:\\apache-maven-3.3.9\\bin\\mvn.cmd maven = /home/<user>/apache-3.3.9/bin/mvn
js-path	js-path = C:\\JasperReports-Server-cp-7.5.0-src\\jasperserver js-path = /home/<user>/JasperReports-Server-cp-7.5.0-src/jasperserver
js-pro-path	js-pro-path = C:\\JasperReports-Server-cp-7.5.0-src\\jasperserver-pro js-pro-path = /home/<user>/JasperReports-Server-cp-7.5.0-src/jasperserver-pro
repo-path	repo-path = C:\\JasperReports-Server-cp-7.5.0-src\\jasperserver-repo repo-path = /home/<user>/JasperReports-Server-cp-7.5.0-src/jasperserver-repo
headless.browser	c:/phantomjs-2.1.1-windows/bin/phantomjs.exe /opt/phantomjs/bin/phantomjs

3.5 Build Source Code

Now that you've set up your `default_master.properties` file, you can build the source code.



Installing JasperReports Server automatically generates encryption keys and encrypts passwords that reside on the file system. These keys are stored in a dedicated TIBCO JasperSoft keystore. Make sure this keystore is properly secured and backed up. For more information, refer to the *JasperReports Server Security Guide*.

To build JasperReports Server:

1. Set up the `default_master.properties` file for your environment (as described above).
2. Start the database server.
3. Stop the application server unless it's GlassFish, which should be running.

4. Run the commands shown below:

After executing each Ant target in [Table 3-1](#), look for the message BUILD SUCCESSFUL.

Table 3-1 Commands for Building JasperReports Server

Commands	Description
<code>cd <js-src>/jasperserver/buildomatic</code>	
<code>js-ant clean-config</code>	(Optional) Clears the buildomatic/build_conf/default directory.
<code>js-ant gen-config</code>	(Optional) Rebuilds the buildomatic/build_conf/default directory.
<code>js-ant add-jdbc-driver</code>	(Optional) Used for loading the databases
<code>js-ant build-ce</code>	Builds the community source code
<code>js-ant create-load-js-db-ce</code>	(Optional) Creates and loads the jasperserver database, imports core bootstrap data
<code>js-ant deploy-webapp-ce</code>	(Optional) Deploys the jasperserver war file to the application server

3.6 Set Java Options

JasperReports Server needs Java memory options that are larger than the standard defaults. For information about additional Java options, see please see [“Setting Java JVM Options” on page 29](#).

3.6.1 Set Increased JAVA_OPTS Settings

JasperReports Server needs greater heap settings for all functionality to operate. For testing your deployed JasperServer you should set your JAVA_OPTS to the same default values described in the *JasperReports Server Community Project Installation Guide*. The following shows the minimum recommended settings; you may need to increase these according to your usage.

JVM Options on Linux and Mac OSX (64 bit)	
Options for all app servers	<code>export JAVA_OPTS="\$JAVA_OPTS -Xms2048m -Xmx4096m -Xss2m"</code>

JVM Options on Windows (64 bit)	
Options for all app servers	set JAVA_OPTS=%JAVA_OPTS% -Xms2048m -Xmx4096m -Xss2m

You should add these settings to your application server startup script:

Apache Tomcat: <tomcat>/bin/setclasspath.sh (.bat for Windows)

JBoss: <jboss>/bin/standalone.conf (.bat for Windows)

For details on setting Java memory options, please see [“Setting Java JVM Options” on page 29](#).

3.7 Starting JasperReports Server

You can now start your application server or restart GlassFish. Your database should already be running.

3.8 Logging into JasperReports Server

You can now log into JasperReports Server through a web browser:

Enter the login URL with the default port number:

```
http://localhost:8080/jasperserver
```

Log into JasperReports Server as jasperadmin:

```
User ID: jasperadmin Password: jasperadmin
```

If you're unable to log in or have other problems, refer to [“Troubleshooting” on page 31](#), or the *JasperReports Server Community Project Installation Guide*, which provides additional troubleshooting information.

3.9 JasperReports Server Log Files

If you encounter any startup or runtime errors you can check the application server log files. For Apache Tomcat you'll find the log file here:

```
<tomcat>/logs/catalina.out
```

Also check the `jasperserver.log` file. You can increase the debug output level by editing the `log4j.properties` file.

The JasperReports Server runtime log is here:

```
<tomcat>/webapps/jasperserver/WEB-INF/logs/jasperserver.log
```

The `log4j.properties` file is here:

```
<tomcat>/webapps/jasperserver/WEB-INF/log4j.properties
```

CHAPTER 4 CREATE AND LOAD SAMPLE DATA

The procedure for [Chapter 3, “Building JasperReports Server Source Code,” on page 9](#) loads core data required to start the application, but it doesn't create sample data, such as sample reports to run and sample databases. Follow the steps below to create and load sample data.

4.1 Load Sample Data

The buildomatic scripts can load sample resources and sample databases. Note: In the procedure below, your `jasperserver` database will be deleted and re-created unless you choose ‘n’ for No when prompted.

Your `default_master.properties` should already be created.

1. Start your database server.
2. Stop your application server.
3. Run the commands shown below:

Commands	Description
<code>cd <js-src>/jasperserver/buildomatic</code>	
<code>js-ant create-load-all-dbs-ce</code>	<p>Creates and loads the <code>jasperserver</code> database</p> <p>Imports core bootstrap resources</p> <p>Creates and loads sample databases</p> <p>Imports sample resources</p> <p>(Choose ‘n’ when prompted if you do not want to recreate your <code>jasperserver</code> database.)</p>

4.2 Generate Your Own Sample Resources

This procedure generates the same resources imported and used by the released version of JasperReports Server. Your `jasperserver` database will be deleted and re-created.

Your `default_master.properties` should have already been created.

4.2.1 Generating Sample Resources for MySQL and PostgreSQL Databases

1. Make sure that the sample data has been loaded.
2. Start your database server.
3. Stop your application server.
4. Run the commands shown below:

Commands	Description
<code>cd <js-src>/jasperserver/buildomatic</code>	
<code>js-ant re-init-js-db-ce</code>	Drop, create, and initialize the <code>jasperserver</code> database.
<code>js-ant run-production-data-ce</code>	Generate sample resources using the processing logic from the production-test source code.

CHAPTER 5 ADDITIONAL BUILDOMATIC INFORMATION

The Ant-based buildomatic scripts contain support files for the setup and configuration of a number of databases and application servers. This chapter gives the locations of many of these files.

5.1 Detailed Description of the deploy-webapp-ce Target

The `deploy-webapp-ce` target performs the following actions in your application server environment:

- Deletes any existing `jasperserver` WAR file.
- Copies the JDBC driver to the appropriate application server directory.
- Copies additional JDBC drivers to the application server to support data source creation in the UI
- Adds a data source definition to the appropriate application server directory.
- Deploys the newly built `jasperserver` WAR file.
- Deletes files within the application server work directory (to clear out compiled JSP files and other cached files).
- On Tomcat, if present, deletes the old version of
`<tomcat>/conf/Catalina/Localhost/jasperserver.xml`.

5.2 Running Ant in Debug Mode

Ant can be run with a `-v` (verbose) or a `-d` (debug) option to help with troubleshooting, for example:

```
js-ant -v build-ce
```

5.2.1 Regenerate Your Buildomatic Property Settings

If you change your `default_master.properties` file, buildomatic will automatically clean and regenerate all configuration settings. If you want to explicitly clean and regenerate your settings manually you can run the following commands:

Commands	Description
<code>js-ant clean-config</code>	Clears the <code>buildomatic/build_conf/default</code> directory.
<code>js-ant gen-config</code>	Rebuilds the <code>buildomatic/build_conf/default</code> directory.



Any time you modify the `default_master.properties` file, configuration settings are automatically re-generated into the `buildomatic/build_conf/default` folder.

5.3 Using Your Own Apache Ant: Get ant-contrib.jar

If you prefer to use your own version of Apache Ant, get the file `ant-contrib-1.0b3.jar`. This JAR enables conditional logic in Ant scripts.

1. Make sure you're using Apache Ant 1.9.4 or higher.
2. Copy the file `ant-contrib-1.0b3.jar` from the `<js-src>/apache-ant/lib` folder to your `<ant-home>/lib` folder:

From:

`<js-src>/apache-ant/lib/ant-contrib.jar`

or

`<js-src>/jasperserver/buildomatic/install_resources/extra-jars/ant-contrib.jar`

To:

`<ant-home>/lib` (General example)

`C:\apache-ant-1.9.4\lib` (Windows example)

`/usr/share/java/apache-ant/lib` (Linux example)

`/usr/share/ant/lib` (Mac example)

5.4 Generated Property Files

After you set your database and application server property values, you'll run buildomatic scripts to generate the database and application server configuration files to run JasperReports Server. Generated property files are in the following directory:

`<js-src>/jasperserver/buildomatic/build_conf/default`

Some of the key configuration files are:

`js.jdbc.properties`

`maven_settings.xml` - (This is the maven settings file used by the source build)

More generated property files are in the following directory:

`<js-src>/jasperserver/buildomatic/build_conf/default/webapp`

Some of the configuration files in this directory are:

`META-INF/context.xml`

`WEB-INF/hibernate.properties`

`WEB-INF/js.quartz.properties`

Running `clean-config` removes these generated files. Running `gen-config` or any other target, regenerates these files.

5.5 Existing and Generated Database SQL Files

Buildomatic files that support various databases are located in:

```
<js-src>/jasperserver/buildomatic/install_resources/sql/<db-type>
```

The source code build procedure creates the `jasperserver` repository database schema using these files:

```
js-ce-create.ddl
```

```
js-ce-drop.ddl
```

When you run the buildomatic target `build-js-ddl-ce`, these database files are freshly generated for your specified database platform. The files are generated to the following location:

```
<js-src>/jasperserver/repository-hibernate/build-db/target/sql
```

Then the files are automatically copied into their buildomatic directory location:

```
<js-src>/jasperserver/buildomatic/install_resources/sql/<db-type>
```



These generated files also overwrite the ones already in the buildomatic directory location.

5.6 Generated WAR File Location and deploy-webapp-ce Target

The JasperReports Server source code build creates a `jasperserver` WAR file. The build assembles the WAR file into the following location:

```
<js-src>/jasperserver/jasperserver-war/target
```

When the `build-ce` target is run, buildomatic assembles the `jasperserver` WAR file, and copies the file to this location for use by subsequent buildomatic targets:

```
<js-src>/jasperserver/buildomatic/install_resources/war/jasperserver
```

Later, when you run the buildomatic target `deploy-webapp-ce`, the following actions take place, for example on Tomcat:

Files: `<js-src>/jasperserver/buildomatic/install_resources/war/jasperserver/*`

Copied to: `<tomcat>/webapps`

File: `<js-src>/jasperserver/buildomatic/build_conf/default/webapp/META-INF/context.xml`

Copied to: `<tomcat>/webapps/jasperserver/jasperserver/META-INF`

Files: `<js-src>/jasperserver/buildomatic/build_conf/default/webapp/WEB-INF/hibernate.properties`

`<js-src>/jasperserver/buildomatic/build_conf/default/webapp/WEB-INF/js.quartz.properties`

Copied to: `<tomcat>/webapps/jasperserver/WEB-INF`

File: `<js-src>/jasperserver/buildomatic/build_conf/db/postgresql/jdbc/postgresql-9.2-1002.jdbc4.jar`

Copied to: `<tomcat>/lib`

Files: `<js-src>/jasperserver/buildomatic/conf_source/db/app-srv-jdbc-drivers/*/jar`

Copied to: `<tomcat>/lib`

5.7 Details on Database Load Build Targets

The buildomatic targets shown below are used in “[Building JasperReports Server Source Code](#)” on page 9 to create and populate the databases used with JasperReports Server. These targets consolidate and simplify the handling of the `jasperserver` database and the optional sample databases:

- `create-load-js-db-ce`
- `create-load-all-dbs-ce`

5.7.1 `create-load-js-db-ce`

This buildomatic target is a consolidation of the following targets:

- `drop-js-db` (if necessary)
- `create-js-db`
- `init-js-db-ce`
- `import-minimal-ce`

Additional functionality determines whether the `jasperserver` database already exists. If so, a command line prompt asks you if you want to delete and re-create the database.

5.7.2 `create-load-all-dbs-ce`

This buildomatic target is a consolidation of the following targets:

- `drop-js-db` (if necessary)
- `create-js-db`
- `init-js-db-ce`
- `import-minimal-ce`
- `import-sample-data-ce`
- `(drop-foodmart-db, if necessary)`
- `create-foodmart-db`
- `load-foodmart-db`
- `(drop-sugarcrm-db, if necessary)`
- `create-sugarcrm-db`
- `load-sugarcrm-db`

Additional functionality determines whether the `jasperserver` database already exists. If so, a command line prompt asks you if you want to delete and re-create the database. The same logic applies for the sample databases: `foodmart` and `sugarcrm`.

5.8 General Fresh Database Schema File

The consolidated database scripts do not regenerate the database schema file. Instead the existing default database schema files are used. To regenerate the database schema files, run the following target:

```
js-ant build-js-ddl-ce
```

The files are generated to the following location:

```
<js-src>/jasperserver/repository-hibernate/build-db/target/sql
```

Then the files are automatically copied into their buildomatic directory location:

```
<js-src>/jasperserver/buildomatic/install_resources/sql/<db-type>
```

5.9 Older Buildomatic Commands

This section shows an alternate, more manual approach for building source code in JasperReports Server.



We recommend using the buildomatic scripts as described in [“Building JasperReports Server Source Code” on page 9](#). You'll have fewer commands to type.

To build JasperReports Server using older Buildomatic commands:

1. Edit the default_master.properties file for your particular environment.
2. Start the database server.
3. Stop the application server (unless it's GlassFish, which should be running).

After you execute the first build target, the buildomatic scripts automatically configure the necessary properties and store these settings in the following directory:

```
<js-src>/jasperserver/buildomatic/build_conf/default
```

4. Execute the following steps at the command line. After executing each Ant target, look for the message BUILD SUCCESSFUL.

Commands	Description
cd <js-src>/jasperserver/buildomatic js-ant add-jdbc-driver js-ant build-ce	Installs the JDBC driver to mvn local repository Builds the Community Project source code
js-ant create-js-db js-ant create-sugarcrm-db js-ant load-sugarcrm-db js-ant create-foodmart-db js-ant load-foodmart-db	If the jasperserver database already exists, first run js-ant drop-js-db Creates sample data for integration-tests Creates sample data for integration-tests Can run for 10 minutes or more
js-ant build-js-ddl-ce js-ant init-js-db-ce js-ant run-production-data-ce	Creates the database schema files for your database type Loads the schema into database Put core bootstrap and Sample data into the jasperserver db
js-ant deploy-webapp-ce	Deploys JasperReports Server to the application server

5.10 Manual Creation of Databases

JasperReports Server runs with a repository database typically named `jasperserver`. The automated buildomatic steps create the `jasperserver` database and sample databases. But you can also create your databases manually.

5.10.1 Manually Creating Databases: PostgreSQL

You can manually execute the scripts buildomatic uses to create and populate databases. Here is an example for PostgreSQL:

1. To create the `jasperserver` database, use a client tool to log into PostgreSQL:

```
cd <js-install>/buildomatic/install_resources/sql/postgresql
psql -U postgres -W
postgres=#create database jasperserver encoding='utf8';
postgres=#\c jasperserver;
postgres=#\i js-create.ddl
postgres=#\i quartz.ddl
postgres=#\q
```

2. To create the sample databases, run these commands:

```
cd <js-install>/buildomatic/install_resources/sql/postgresql
psql -U postgres -W
postgres=#create database sugarcrm encoding='utf8';
postgres=#create database foodmart encoding='utf8';
postgres=#\c sugarcrm;
postgres=#\i sugarcrm-postgresql.sql; (first make sure the file is unzipped)
postgres=#\c foodmart;
postgres=#\i foodmart-postgresql.sql; (first make sure the file is unzipped)
postgres=#\i supermart-update.sql;
postgres=#\q
```

5.10.2 Additional Databases

For information on manual setup of databases other than PostgreSQL, refer to the *JasperReports Server Community Project Installation Guide*.

CHAPTER 6 JASPERSOFT INTERNAL DEVELOPERS AND ADVANCED DEVELOPERS

This chapter is for Jaspersoft Internal Developers and for Advanced Developers who want to use some of the additional options available through the buildomatic property settings.

6.1 Internal Developers and Advanced Developers

TIBCO Jaspersoft provides a Maven repository using [Artifactory](#) to hold all third party components required to build the server's source code. It also acts as a proxy for the standard public Maven repositories such as [repo1.maven.org](#).

This internal repository is convenient for internal Jaspersoft developers because the developer can point to one location to get all dependencies resolved.

In `default_master.properties`, internal developers should comment out `maven.build.type=repo` and `repo-path=<path>`:

```
# maven.build.type=repo
# repo-path=<path>
```

External developers (customers) who download the `TIB_js-jrs-cp_7.5.0_src.zip` package from [jaspersoft.com](#) should set all the properties described in **“Configuring the Buildomatic Properties” on page 10** before building JasperReports Server.

Additional buildomatic property settings are available for advanced external developers. If you're an external developer working within an enterprise or on a project that has an internal Maven repository server, you can use the `mirror` value. The following property settings and values will enable a local Maven repository:

```
maven.build.type=mirror
mvn-mirror=<repo-url>
```

If you're an external developer with other build configurations to add, you can do this with the `maven.build.type=custom` property setting. If you set this value, the following file will be used as the template to set up the JasperReports Server build configuration:

```
<js-path>/buildomatic/conf_source/templates/maven_settings_custom.xml
```

You can edit this file to add whatever configurations you want.

When buildomatic auto-setup is complete, you can see the final maven settings file used for the JasperReports Server here:

```
<js-path>/buildomatic/build_conf/default/maven_settings_custom.xml
```

6.2 Additional Properties in default_master.properties

You can use the properties in the table below for various customizations of the JasperReports Server build:

Property Setting	Purpose
SKIP_TEST_ARG=skipTests	Enable this property to skip unit test execution. This will speed the source build.
VERBOSE_LOGGING=true	Enable this property to increase the INFO logging from the Maven package.
OFFLINE_ARG=-o	Enable this property if you want to build in "offline" mode. To run in offline mode you need to have successfully built JasperServer at least once.
SKIP_EXPORT_FILES=true	Enable this property to skip the copying of files that set up the command line import-export configuration. This saves time on file copying.
maven.build.type=repo	Use this setting for the build type if you've downloaded the source code zip package from the jaspersoft.com site, and you're building the source code as a customer (external developer) would build it. You'll also need to set the <code>repo-path</code> property. <code>maven.build.type=repo</code> is the default value used in the sample <code><dbType>_master.properties</code> files.
maven.build.type=community	Use this setting for the build type if you're building only the Community source code. This setting supports Community members who have checked out JasperReports Server source code from the Community site: <code>code.jaspersoft.com/svn/repos/jasperserver</code>
maven.build.type=mirror	If you're an external developer who has a central Maven style repository for your enterprise or project, you can use this setting to specify the local central repository. If you set this property value, you should also set the <code>mvn-mirror</code> property.

Property Setting	Purpose
<code>maven.build.type=custom</code>	<p>If you're an external developer whose build requires additional configurations, you can use this property value to support them. In this case, use the following template file:</p> <p><code><js-path>/buildomatic/conf_source/templates/maven_settings_custom.xml</code>.</p> <p>You can manually edit this file to add more configurations. The file will be processed by buildomatic and copied to its final location after executing a buildomatic command:</p> <p><code>buildomatic/build_conf/default/maven_settings_custom.xml</code></p>
<code>mvn-mirror=<repo-url></code>	<p><code>mvn-mirror=http://mvnrepo.jaspersoft.com:8081/artifactory/repo</code></p> <p>The value shown is the default repo-url used by Jaspersoft internal development.</p>
<code>repo-path=<path></code>	<p>Set a local path value for this property if you are using <code>maven.build.type=repo</code> (this is the default configuration from the source code zip download from jaspersoft.com).</p>

APPENDIX A BUILDING JASPERJPIVOT SOURCE CODE

JasperJPivot is adapted from the JPivot open source project. It provides the web interface for Jaspersoft OLAP. JasperJPivot also includes enhanced usability, navigation, configuration, and scalability.

Download the source code package:

On the Jaspersoft [technical support website](#) (login required).

Look for a file with the following name:

jasperpivot-<ver>-src.zip

Build the source code package:

Unpack the downloaded source code package zip file.

Follow the instructions in the <unpacked-src>/Building-JasperJPivot-Source.pdf.

The process of building the JasperJPivot requires Apache Maven. For more information, see “[Check Your Maven Version](#)” on page 7.

APPENDIX B JAVA OPTIONS

B.1 Setting Java JVM Options

To run properly, JasperReports Server needs more Java memory than the default settings. But for development work, the settings can be simpler than those recommended for production. For full information on recommended JAVA_OPTS settings, see the *JasperReports Server Community Project Installation Guide*.

B.1.1 Tomcat and JBoss JVM Options

Here are some typical settings for JVM options that affect JasperReports Server. For space reasons, some of the options are displayed on multiple lines; make sure you set all options. These are the minimum recommended options; you may need to increase the JVM memory assignment according to your usage.

JVM Options on Windows	
Options for all app servers	<pre>set JAVA_OPTS=%JAVA_OPTS% -Xms2048m -Xmx4096m set JAVA_OPTS=%JAVA_OPTS% -Xss2m -XX:+UseConcMarkSweepGC</pre>
Java 11	<pre>set JAVA_OPTS=%JAVA_OPTS% -Djava.locale.providers=COMPAT</pre>

JasperReports Server doesn't provide a virtual X frame buffer on Linux. If your Linux applications are graphical, set the `-Djava.awt.headless=true` to prevent Java from trying to connect to an X-Server for image processing.

JVM Options on Linux and Mac OSX	
Options for all app servers	<pre>export JAVA_OPTS="\$JAVA_OPTS -Xms2048m -Xmx4096m" export JAVA_OPTS="\$JAVA_OPTS -Xss2m" export JAVA_OPTS="\$JAVA_OPTS -XX:+UseConcMarkSweepGC"</pre>
Java 11	<pre>export JAVA_OPTS="\$JAVA_OPTS -Djava.locale.providers=COMPAT"</pre>

You can set JVM options in a number of ways. For example, you can add your `JAVA_OPTS` settings to these files:

File	Add JVM Options Below the Lines Shown Here:
<tomcat>\bin\setclasspath.bat	<code>set JAVA_ENDORSED_DIRS=%BASEDIR%\common\endorsed</code>
<tomcat>/bin/setclasspath.sh	<code>JAVA_ENDORSED_DIRS="\$BASEDIR"/common/endorsed</code>
<tomcat>/bin/setenv.bat or <tomcat>/bin/setenv.sh	JAVA_OPTS setting can go anywhere in this file.
<jboss>\bin\standalone.conf.bat <jboss>/bin/standalone.conf	<code>set JAVA_OPTS=%JAVA_OPTS% -Dprogram.name=%PROGNAME%</code> or <code>export JAVA_OPTS="\$JAVA_OPTS -Dprogram.name=\$PROGNAME"</code>



For information on recommended `JAVA_OPTS` settings for all certified application servers, please refer to the *JasperReports Server Community Project Installation Guide*.

APPENDIX C TROUBLESHOOTING

C.1 Build Troubleshooting

C.1.1 Name Undefined Error (Old Ant Version)

We recommend Apache Ant version 1.9.4 or higher.

If you're not using the version of Apache Ant included with the JasperReports Server source code package, you could get the following error when running the buildomatic scripts:

```
BUILD FAILED
c:\js-builds\jasperserver\buildomatic\install.xml:6: Problem: failed to create task or type if
Cause: The name is undefined.
Action: Check the spelling.
Action: Check that any custom tasks/types have been declared.
Action: Check that any <presetdef>/<macrodef> declarations have taken place.
```

Solution:

The buildomatic scripts require Ant version 1.8.1 or higher, and the ant-contrib.jar file needs to be included in your ant/lib directory. We recommend Ant version 1.9.4. If you're running with your own Ant version, you can copy this jar to your <ant-home>/lib directory:

From:

```
<js-src>/apache-ant/lib/ant-contrib.jar
or
<js-src>/jasperserver/buildomatic/extra-jars/ant-contrib.jar
```

To:

<ant-home>/lib	(General example)
C:\apache-ant-1.9.4\lib	(Windows example)
/usr/share/java/apache-ant/lib	(Linux example)
/usr/share/ant/lib	(Mac example)

C.2 Database Troubleshooting

The most common errors encountered when building JasperReports Server involve the database connection. For information about database connection problems, see the Troubleshooting Appendix of the *JasperReports Server Community Project Installation Guide*.

C.3 Maven Troubleshooting

C.3.1 Maven Error on Linux or Mac

If Maven is installed on Linux via rpm, apt-get, or yum (or on Mac), the Maven binary and the Maven libraries are probably in separate locations. This can potentially cause a problem with the source build.

C.3.1.1 /usr/boot Does Not Exist Error

When building under Linux or Mac, you may get an error similar to the following:

```
BUILD FAILED
/home/devuser/js-builds/jasperserver/buildomatic/bin/dev.xml:91:
/usr/boot does not exist
```

The Buildomatic scripts attempt to find the MAVEN_HOME setting and can be unsuccessful when the maven binary is installed in the /usr/bin/mvn location. The workaround is to update your default_master.properties file:

```
cd <js-src>/jasperserver/buildomatic
edit default_master.properties
```

Uncomment the maven.home line so that it looks like this:

```
maven.home = /usr/share/maven2                (Linux)
```

For Mac, the location of the Maven library files is typically slightly different:

```
maven.home = /usr/share/maven                (Mac)
```

C.3.2 Clear JasperReports Server Artifacts in Maven Local Repository

If you add new code to an existing source build environment, such as a bug fix source patch update, you can clear the JasperReports Server artifacts in your Maven local repository to ensure that the newly built artifacts contain the necessary new content. Maven updates the artifacts automatically, but if you have trouble building or pulling in the modified code, you can try deleting these artifact trees.

To clear existing JasperReports Server artifacts:

1. Go to the repository directory:

```
cd <home-dir-path>/m2/repository
```

2. Remove the old versions by deleting the following directories and their contents:

```
com/jaspersoft: Community Project artifact tree
```

```
jaspersoft: Commercial version artifact tree
```


C.3.3 Clear Entire Local Repository

If you want to completely rebuild everything, remove all of the cached jars in your Maven local repository. To do this you can delete (or rename) the entire local repository.

Then when you build JasperServer, all dependencies are re-downloaded.

```
cd <home-dir-path>/m2
rm -rf repository
```

C.3.4 Maven Warnings

Maven generates verbose warnings during the artifact validation process. For example, the following warning was generated, even though the required JAR file was downloaded successfully:

```
[WARNING] Unable to get resource from repository jasperServer (file:///C:/svn/js-buildlds/jasperserver-repo
Downloading: http://repo1.maven.org/maven2/commons-logging/commons-logging/1.0/commons-logging-1.0.pom
163b downloaded
```

C.3.5 Old Maven Binary

In general, it's best to use the most current stable version of the Maven tool. We recommend Maven version 3.0.4.

C.4 Other Build Troubleshooting

C.4.1 Error When Building Database Scripts

When compiling in the jasperserver-repository-hibernate/build-db directory, you might see an error containing the following message:

```
[ERROR] BUILD ERROR
[INFO] -----
[INFO] Error executing ant tasks
Embedded error: Source file does not exist!
```

The most likely problem is that your m2/settings.xml file doesn't point to the correct source location, and the build step didn't find the Quartz scripts. The settings.xml file should contain the path to the quartz script corresponding to your database, for example:

```
<js.quartz.script>/home/<user>/<js-src>/jasperserver/scripts/quartz/tables_<database>.sql</js.quartz.script>
```

If you use the buildomatic scripts you shouldn't get this kind of error.

