Supplementary material for

NICE: neural-initialised static condensation with equilibrium correction, with application to the thickness design of cut TPMS lattices

Supplementary Notes, Tables and Figures are numbered in the order in which they appear in this supplement. Variant labels follow the main text (Table 2). The two variants not listed there, the Uncorrected continuation and the Smoothing-trained variant, are evaluated in this supplement. The key below gives each variant's record identifier in the data archive.

R1. Variant and geometry key

Label	Numerical role	Record identifier in the data archive
Base network	Baseline variant; starting network parameters of every continuation and of the correction experiments of Section 5.5	v2L1
Uncorrected continuation	Base network continued; no correction in training or evaluation	A0_ctrl
Smoothing-trained	Base network continued and trained through eight smoothing steps	A2b_tail8
Base network + correction	Base network with NICE's correction applied at deployment, without retraining	B2grid
NICE	Principal variant, trained through the complete correction (8 / Q1(17) / 8)	A3_2grid

Cell label	Cut-severity group	Geometry identifier in the data archive
U1	Uncut	fresh_val_2000_full
U2	Uncut	fresh_val_2001_full
M1	Moderately cut	fresh_val_2003_d1_v1
H1	Heavily cut	fresh_val_2005_d1_v0
M2	Moderately cut	fresh_val_2006_d0_v1
H2	Heavily cut	fresh_val_2010_d0_v0
H3	Heavily cut	fresh_val_2002_d0_v0
L1	Lightly cut	fresh_val_2004_d0_v2

Cell label	Cut-severity group	Geometry identifier in the data archive
W1: validation cell with the largest NICE error (Tables ST08b, ST10)	Moderately cut	fresh_val_2051_d1_v1
W2 (Table ST08b)	Heavily cut	fresh_val_2045_d1_v0
W3: validation cell with the thinnest walls (Tables ST08b, ST10)	Heavily cut	fresh_val_2074_d0_v0
W4 (Table ST08b)	Heavily cut	fresh_val_2021_d1_v0
W5 (Table ST08b)	Lightly cut	fresh_val_2063_d1_v2
RU (Table ST08b)	Uncut	fresh_val_2032_full
RL (Table ST08b)	Lightly cut	fresh_val_2047_d1_v2
RM (Table ST08b)	Moderately cut	fresh_val_2078_d0_v1
RH (Table ST08b)	Heavily cut	fresh_val_2053_d1_v0

In the validation-cell identifiers, d0 and d1 give the half of $(0, \pi/4)$ that contains the cut angle ϑ, and v0, v1 and v2 give the heavily, moderately and lightly cut groups, which are defined by the remaining volume. In configuration labels such as U1/x, x and y give the neighbour configuration of Figure 9. The deployment geometries use the G1–G4 labels of Table ST13; the table below gives their identifiers in the data archive.

Benchmark label	Cut-severity group	Geometry identifier in the data archive
G1	Cut	fresh_train_0020_cover01_r2
G2	Cut	fresh_train_0020_cover01_r1
G3	Uncut	fresh_train_0020_full
G4	Uncut	fresh_train_0007_full

Table ST01. Training and evaluation settings

Variant	Training set (geometries)	Training-time validation geometries	Training steps	Evaluated training step / parameters	Evaluation correction	Evaluated orientations
Base network	305	40	40,000	30,000 / EMA	None	Identity, 17
Uncorrected continuation	591	40	15,000	15,000 / EMA	None	Identity
Smoothing-trained	591	40	15,000	15,000 / EMA	Eight-step smoothing	Identity
Base network + correction	305	40	—	30,000 / EMA	8 / Q1(17) / 8	Identity
NICE	591	40	15,000	15,000 / EMA	8 / Q1(17) / 8	Identity, 17

All variants are evaluated on the 80 validation geometries of Table ST02. Orientation 17 is one of the 48 cube-symmetry transformations of Appendix G (Eq. (G.2)), applied to the geometry and to the test displacements; orientation 0 is the identity. The training set of 591 comprises 304 of the base network's 305 geometries (one cell that behaved as a near-mechanism was removed) and 287 further training geometries. Under the geometry replacement described below, each 15,000-step continuation visits at most 153 of its 591 training geometries; the base network visited all 305 of its own over 40,000 training steps. The Uncorrected continuation, the Smoothing-trained variant and NICE use the same seed and split, so they draw their geometries in the same order.

Training settings, common to the variants of Table 2, the Uncorrected continuation and the Smoothing-trained variant:

- Batches of 16 test displacements; the geometry changes at every step. Three geometries of the training set are held on the GPU and one of them is replaced every 100 steps, so a run of N_{st} training steps visits at most $N_{\mathrm{st}}/100 + 3$ distinct training geometries.
- Nominal class weights, in the order `force`, `force_c`, `support`, `support_k`, `face`, `face_c`, `macro`, `grf`, `glued`, `adv`: $0.10, 0.10, 0.075, 0.075, 0.10, 0.10, 0.10, 0.125, 0.075, 0.15$, renormalised over the available classes and assigned by systematic quotas.
- Adam with a one-cycle learning-rate schedule: peak 3×10^{-4}, 5% warm-up, cosine decay and final division factor 100; gradient norm clipped at one.
- Model selection and evaluation use an exponential moving average (EMA) of the network parameters, with decay 0.9997 and zero-initialisation bias correction.
- Eq. (13): 10^{-12} lower clamp inside the logarithm of the energy term; the sensitivity term has unit weight.

The base network was initialised from parameters obtained in three preceding training stages. The data split comprises 691 geometries: 591 training geometries and 100 validation geometries, which include the 80 of Table ST02.

For the base network, the Uncorrected continuation, the Smoothing-trained variant and NICE, checkpoint selection uses the bias-corrected EMA parameters and both the identity orientation ($v = 0$) and orientation 17 ($v = 17$), although Table ST03 reports only the identity orientation. A geometry family consists of the geometries of the training-time validation list generated from one thickness field; an independently generated validation cell forms a family of its own. Within a family f and orientation v, let $\bar{\varepsilon}_{fv}$ be the mean energy error averaged over the selection classes and $\bar{e}_{s,fv}$ the mean relative sensitivity-vector error over the classes with sensitivity labels. Let $\varepsilon^{(90)}_{fv}$ be the class average of the 90th percentile of the energy error over the test displacements. Each class statistic is first averaged over the available geometries in that family. The selection score is

$$J_{\mathrm{sel}} = \frac{1}{2} \sum_{v \in \{0,17\}} \frac{1}{|\mathcal{F}|} \sum_{f \in \mathcal{F}} \left(\bar{\varepsilon}_{fv} + \bar{e}_{s,fv} + \tfrac{1}{2} \varepsilon^{(90)}_{fv} \right).$$

Families and the two orientations carry equal weight. The eight selection classes are `force`, `support`, `face`, `macro`, `grf`, `force_c`, `face_c` and `support_k`; absent classes are omitted and an absent sensitivity term contributes zero. Among eligible evaluations, the lowest finite score is selected.

- The base network was scored at 10,000, 20,000, 30,000 and 40,000 training steps ($J_{\mathrm{sel}} =$ 0.1057, 0.1065, 0.0905 and 0.0912); the parameters of step 30,000 were selected. Every continued variant starts from these parameters.
- The Uncorrected continuation and NICE were scored at 7,500 and 15,000 training steps (0.0944 and 0.0906; 0.00281 and 0.00237); in both cases the final parameters scored lower and were kept.
- The Smoothing-trained variant used the same evaluation schedule and orientations; its selection scores were not recorded, and the parameters of its final step, 15,000, are used.
- NICE was designated the principal variant after all variants had been compared on the 80 validation geometries and the two-cell configurations.

Twenty of the 80 validation geometries (6 uncut, 14 cut) belong to the selection list; they include all eight detailed cells of Supplementary Section R1.

Table ST02. Validation geometry domain

The 80 geometries use independently generated thickness fields, with 20 uniform, 30 affine and 30 mixed trilinear fields. The generator constrains every corner parameter to $[0.17520160, 0.69933962]$, the corner span to at most 0.47, and the maximum reference-coordinate gradient norm to at most 0.47. In each block of eight geometries, a uniform-field-equivalent centre volume fraction is drawn by stratified sampling between 0.1 and 0.4; nonuniform affine or trilinear shapes are scaled within these constraints. This centre-density parameter is a sampling coordinate and is not the material fraction after cutting.

Canonical cut normals are $(\cos\vartheta, \sin\vartheta, 0)$. The generator draws ϑ by stratified sampling over the two halves of $(0, \pi/4)$ and the remaining cell-box volume $v_{\mathcal{B}}$ over thirds of $(0, 1)$. Two of every eight validation fields are uncut and the other six cover the angle–volume combinations. Training and validation are drawn from separate random streams; the present table describes the 80-geometry validation set.

Cut-severity group	Geometries	Generation interval for $v_{\mathcal{B}}$	Observed $v_{\mathcal{B}}$	Observed corner-parameter range
Uncut	20	1	1	0.1762–0.6902
Lightly cut	20	$(2/3, 1)$	0.6765–0.9996	0.1853–0.6972
Moderately cut	20	$(1/3, 2/3)$	0.3437–0.6605	0.1867–0.6983
Heavily cut	20	$(0, 1/3)$	0.01326–0.3195	0.1768–0.6946

The cut volumes refer to the cell box before it is intersected with the TPMS material layer. No two validation geometries coincide up to a symmetry of the cube. At $n = 32$, the numbers of retained DOFs of the 80 geometries have a median of 23,604 and range from 2,679 to 45,900; the numbers of active DOFs have a median of 221,442 and range from 2,757 to 439,092. The selected spectral and assembly cases are identified in the geometry key of Supplementary Section R1; they are reported as test cases and do not form a random sample for population inference.

Table ST03. Energy error by load class (identity orientation)

Entries are mean / maximum over geometries, in percent: each geometry first contributes its mean over the test displacements, and geometries are weighted equally. The maximum is not the worst individual test displacement. "Base network + correction" denotes the base network with NICE's correction applied at deployment, without retraining. The last column restricts NICE to the 60 validation geometries that entered neither training nor checkpoint selection (the other 20 entered checkpoint selection, Table ST01). For NICE under traction loads, the 5,120 individually sampled test displacements of the 80 geometries have a 95th percentile of 0.331%, a 99th percentile of 0.693% and a maximum of 1.24%. For the 3,840 test displacements of the 60 geometries outside checkpoint selection, these values are 0.355%, 0.734% and 1.24%. Under traction loads the mean of Base network + correction is 0.0965% and that of NICE 0.0737%, a ratio of 1.31. Resampling the 80 geometries with replacement (paired, ratio of geometry-equal means, percentile interval) gives a 95% interval of 1.20–1.40.

Class	Geometries (all / outside selection)	Base network	Uncorrected continuation	Smoothing-trained	Base network + correction	NICE	NICE, outside selection
force	80 / 60	5.036 / 70.122	4.607 / 62.465	0.525 / 3.658	0.092 / 0.683	0.058 / 0.325	0.059 / 0.325
support	80 / 60	5.332 / 99.857	4.878 / 90.741	0.638 / 3.552	0.084 / 0.852	0.055 / 0.372	0.056 / 0.372
face	80 / 60	2.486 / 22.139	2.233 / 17.635	0.165 / 1.808	0.072 / 1.990	0.037 / 0.724	0.040 / 0.724
macro	80 / 60	0.842 / 2.636	0.827 / 2.584	0.203 / 0.935	0.022 / 0.165	0.015 / 0.118	0.015 / 0.118
grf	80 / 60	2.038 / 4.582	2.009 / 4.550	0.251 / 0.933	0.029 / 0.180	0.025 / 0.143	0.025 / 0.143
force_c	80 / 60	6.886 / 48.628	6.334 / 41.962	1.280 / 7.817	0.097 / 0.905	0.074 / 0.651	0.077 / 0.651
face_c	80 / 60	3.150 / 36.337	2.806 / 25.525	0.483 / 2.326	0.043 / 0.319	0.032 / 0.210	0.033 / 0.210
support_k	75 / 56	4.177 / 28.817	3.941 / 26.175	0.938 / 5.246	0.077 / 0.632	0.057 / 0.468	0.058 / 0.468
glued	75 / 60	4.593 / 38.128	4.422 / 42.030	0.953 / 4.629	0.078 / 0.555	0.060 / 0.384	0.055 / 0.384

Under traction loads, NICE's means by cut-severity group on the 60 geometries outside checkpoint selection are 0.020% (uncut), 0.054% (lightly cut), 0.105% (moderately cut) and 0.126% (heavily cut). The five largest geometry means of the 80 (0.651%, 0.540%, 0.487%, 0.303%, 0.287%) all belong to these geometries.

ST03b. Means by cut-severity group under nodal point loads and traction loads (%)

Cut-severity group	Geometries	Base network force/force_c	Uncorrected continuation force/force_c	Smoothing-trained force/force_c	Base network + correction force/force_c	NICE force/force_c
Uncut	20	0.908 / 1.142	0.879 / 1.029	0.072 / 0.242	0.034 / 0.029	0.013 / 0.016
Lightly cut (v2)	20	3.239 / 5.801	3.021 / 5.325	0.523 / 1.414	0.088 / 0.096	0.059 / 0.079
Moderately cut (v1)	20	4.720 / 7.899	4.506 / 7.823	0.723 / 1.769	0.103 / 0.105	0.070 / 0.091

Cut-severity group	Geometries	Base network force/force_c	Uncorrected continuation force/force_c	Smoothing-trained force/force_c	Base network + correction force/force_c	NICE force/force_c
Heavily cut (v0)	20	11.278 / 12.702	10.021 / 11.160	0.783 / 1.697	0.141 / 0.156	0.090 / 0.109

ST03c. Orientation dependence of NICE: identity / orientation 17 means (%)

NICE was also evaluated in orientation 17, which entered checkpoint selection (Table ST01), on all 80 geometries with the validation test displacements of Table ST03. The class with stiffness-scaled supports and the class with displacements imposed by a neighbouring cell are not part of this comparison.

Class	Identity	Orientation 17
force	0.058	0.059
support	0.055	0.056
face	0.037	0.034
macro	0.015	0.016
grf	0.025	0.026
force_c	0.074	0.083
face_c	0.032	0.034

Table ST04. Operator verification in the deployed arithmetic

Columns: the maximum relative asymmetry $\max_{i,j} |G_{ij} - G_{ji}| / \sqrt{|G_{ii} G_{jj}|}$ of $G = Q^T \widehat{S} Q$, where the columns of Q are the first eight test displacements of the cell's traction-load (force_c) validation set. The next three columns give the maximum relative difference between returned work and field energy, the deployed-versus-training field difference and the maximum rigid-body energy ratio, all over the same eight test displacements, which also normalise the rigid-body ratio. The ghost-penalty column gives the ghost-penalty fraction of the exact field energy, averaged over the test displacements (traction loads / nodal point loads). The last two columns give the mean δ and κ of Section 5.4 for the base network and for NICE under traction loads, with the Jacobi weighting $\mathsf{W} = \mathrm{diag}(0, D)$, $D = \mathrm{diag}(K_{II})$, of Appendix B.3. Over the first eight nodal-point-load test displacements, the asymmetry, the work–energy difference and the rigid-body energy ratio are at most 3×10^{-8}, 2×10^{-8} and 1×10^{-10}.

Cell	Asymmetry	Work–energy difference	Deployed vs training field	Rigid-body energy	Ghost-penalty fraction (traction loads / nodal point loads)	δ, κ: base network (traction loads)	δ, κ: NICE (traction loads)
H2	6.3e-09	4.5e-09	4.6e-09	1.7e-11	0.00048 / 0.49	0.71%, 7089	0.051%, 582
H1	5.6e-09	4.0e-09	4.2e-08	1.6e-12	7.9e-05 / 0.81	1.23%, 124	0.186%, 33

Cell	Asymmetry	Work–energy difference	Deployed vs training field	Rigid-body energy	Ghost-penalty fraction (traction loads / nodal point loads)	δ, κ: base network (traction loads)	δ, κ: NICE (traction loads)
M2	8.7e-09	3.4e-09	9.4e-08	2.4e-12	3.6e-05 / 0.66	1.15%, 294	0.156%, 163
M1	7.3e-09	4.4e-09	9.3e-08	1.4e-11	0.00012 / 0.58	1.26%, 866	0.179%, 426
U2	3.5e-09	1.8e-09	1.1e-07	2.9e-13	3.6e-05 / 0.79	0.74%, 85	0.107%, 47

Table ST05. Sensitivity and spectral diagnostics at fixed retained displacements

ST05a. Energy and sensitivity errors

Means over the test displacements (%) at fixed retained displacements. k is the number of Jacobi-preconditioned Chebyshev steps applied to the base network's field ($a = b/30$; Section 5.5, Figure 8a,b). Smoothed values are tabulated for the base network under traction loads, and — marks entries not tabulated. The first-order fraction, evaluated at $k = 0$, is the Frobenius norm of the linear error array divided by the sum of the Frobenius norms of the linear and quadratic arrays (%). Each array includes all eight corners and all evaluated test displacements in that cell and class.

Variant	Cell	Class	Energy error, $k = 0$	Energy error, $k = 8$ / 32	Sensitivity error, $k = 0$	Sensitivity error, $k = 8$ / 32	First-order fraction
Base network	U1	force_c	1.270	0.41971 / 0.27998	0.664	0.52592 / 0.45509	42.887
Base network	U1	force	0.742	—	1.018	—	55.124
Base network	U2	force_c	0.402	—	0.588	—	35.658
Base network	U2	force	0.506	—	1.008	—	71.565
Base network	M1	force_c	13.512	4.6850 / 2.9452	14.128	2.7552 / 1.6339	7.164
Base network	M1	force	7.156	—	4.822	—	23.516
Base network	H1	force_c	1.814	0.25081 / 0.059403	1.909	0.26139 / 0.14959	28.403
Base network	H1	force	1.842	—	0.923	—	35.199
Base network	M2	force_c	3.643	1.0382 / 0.61088	5.159	0.83675 / 0.5753	9.339
Base network	M2	force	2.175	—	1.103	—	41.390
Base network	H2	force_c	34.954	0.20515 / 0.0033313	75.072	0.77195 / 0.010708	0.786
Base network	H2	force	19.507	—	13.649	—	36.322
Uncorrected continuation	U1	force_c	1.165	—	0.937	—	35.750
Uncorrected continuation	U1	force	0.779	—	0.766	—	59.185
Uncorrected continuation	U2	force_c	0.397	—	0.560	—	35.988
Uncorrected continuation	U2	force	0.515	—	1.062	—	72.929

Variant	Cell	Class	Energy error, $k = 0$	Energy error, $k = 8$ / 32	Sensitivity error, $k = 0$	Sensitivity error, $k = 8$ / 32	First-order fraction
Uncorrected continuation	M1	force_c	13.009	—	13.275	—	7.456
Uncorrected continuation	M1	force	6.841	—	4.442	—	26.413
Uncorrected continuation	H1	force_c	1.699	—	1.894	—	28.046
Uncorrected continuation	H1	force	1.877	—	1.013	—	34.751
Uncorrected continuation	M2	force_c	3.988	—	5.432	—	9.548
Uncorrected continuation	M2	force	2.105	—	1.357	—	49.454

ST05b. Energy fractions in the lowest 200 generalised interior modes

Base network, mean over the traction-load test displacements; each fraction uses its own interior-energy denominator (Eq. (10)). Cumulative curves, results for nodal point loads and percentiles over the test displacements are shown in Figure 6.

Cell	Error fraction (%)	Exact-field fraction (%)
U1	24.019	8.498
M1	24.452	4.870
M2	18.399	4.620
H2	15.216	4.705

Cell	λ_1	Lower smoothing endpoint $a = b/30$	Modes below a (of the lowest 200)
U1	0.000402235	0.174937	200
M1	0.000574199	0.173294	200
M2	0.000935594	0.174182	200
H2	0.0213148	0.137632	66

Here b is the power-iteration estimate, multiplied by 1.05, of the smoothing study of Section 5.5. That study starts the power iteration from its own random vector (Appendix F.2), so its interval differs from the one used by the correction $\mathcal{W}$.

Table ST06. Interior coarse spaces

Mean energy error (%) under traction loads after eight smoothing steps, one coarse-grid correction and eight smoothing steps applied to the base network's field at fixed retained displacements. Coarse columns are those surviving the support screen of Appendix F.1 and the removal of columns whose diagonal energy is at most 10^{-12} of the largest; $V^T A V$ is formed explicitly and factorised without diagonal shift. The enriched partition-of-unity (PU) spaces carry 12 DOFs per vertex of a Q_1 grid through fields $\sum_v N_v(x)[a_v + B_v(x - x_v)]$. Their generating functions are linearly dependent, so the column count can exceed the dimension

of the spanned space, and the PU entries are numerical observations rather than verified Galerkin projections. NICE uses $Q_1(17)$.

Coarse space	Coarse columns: M1 / M2 / U1	M1	M2	U1
Q_1, 9^3 vertices	1,275 / 984 / 1,728	0.813	0.135	0.0966
Q_1, 17^3 vertices (NICE)	5,601 / 4,557 / 7,950	0.186	0.0273	0.0267
Q_1, 33^3 vertices	27,207 / 23,199 / 40,983	0.0477	0.00870	0.00784
Q_2, 17^3 nodes	7,401 / 5,751 / 10,452	0.0900	0.0170	0.0125
PU, 9^3 vertices	5,100 / 3,936 / 6,912	0.114	0.0211	0.0154
PU, 17^3 vertices	22,404 / 18,228 / 31,800	0.0365	0.00760	0.00653

Table ST07. Energy error of different starting fields under the same correction

Mean energy error (%) under traction loads (32 validation test displacements, fixed retained displacements) after the correction with k smoothing steps before and after the $Q_1(17)$ coarse-grid correction, for three starting fields and six detailed cells. The 8-step entries of M1, M2, H1, H2 and U2 are those of Table 4. Harmonic and zero starting fields receive the exact rigid-body split.

The harmonic starting field recovers the interior displacements from the deformation part of the retained displacements by graph-harmonic interpolation. The graph has the active nodes of the cell as vertices and joins every pair of the 27 nodes of each active element, with the element's material volume as weight (summed over the elements that share a pair); $L = D_W - W$ is its Laplacian. With the retained values prescribed, each displacement component is recovered separately from $L_{II}u_I = -L_{IP}q$. As for the zero field, the retained displacement is first split as $q = R_P c + (q - R_P c)$ with $c = R_P^+ q$; only the second part is recovered in this way, the rigid field Rc is added, and the retained values are restored. This recovery has no trainable parameters and uses only the element connectivity and volumes.

cell	starting field	8 steps	16 steps	32 steps	64 steps
H2	Base network	0.0117	0.00163	0.000182	3.65e-06
H2	harmonic	0.0806	0.00482	0.000614	1.22e-05
H2	zero	28.3	0.284	0.0156	0.000315
H1	Base network	0.0131	0.00487	0.0013	0.000173
H1	harmonic	1.28	0.547	0.199	0.0345

cell	starting field	8 steps	16 steps	32 steps	64 steps
H1	zero	39.9	10.7	2.92	0.437
M2	Base network	0.0273	0.0135	0.00691	0.00351
M2	harmonic	6.72	3.53	1.52	0.485
M2	zero	324	104	38.9	14.1
M1	Base network	0.186	0.12	0.0727	0.0393
M1	harmonic	17.2	8.13	4.11	1.43
M1	zero	1.1e+03	420	185	81.8
U1	Base network	0.0267	0.0176	0.0118	0.00783
U1	harmonic	4.19	2.65	1.87	1.33
U1	zero	133	47.7	22	11.9
U2	Base network	0.00424	0.00202	0.0009	0.000377
U2	harmonic	1.23	0.693	0.38	0.194
U2	zero	47.2	14	5.51	2.32

On M1, from the base network, the same cycle with 2 and 4 steps per stage gives 1.02% and 0.422%, and a coarse-grid correction followed by a single eight-step stage gives 0.230%. The $Q_1(17)$ space of M1 has 5,601 coarse columns for 165,927 interior DOFs.

Table ST08. Complete results of the two-cell assemblies with a continuous-thickness neighbour

Maximum relative errors (%) of the compliance and of the sensitivity vector over the six face loads, compared with the 3% reference. Sensitivity maxima include both cells. The test cell uses the stated learned variant, and its neighbour is exact. Cell labels abbreviate the validation identifiers (Supplementary Section R1).

Test cell	Configuration	Variant	Max. compliance error (%)	Max. sensitivity error (%)
U1	x	Base network	0.465	5.830
U1	y	Base network	0.427	5.390
U2	x	Base network	0.105	1.996
M1	x	Base network	4.384	12.153
H1	x	Base network	1.180	2.512
H1	y	Base network	1.379	1.820
M2	x	Base network	0.571	2.539
U1	x	Uncorrected continuation	0.401	4.885
U1	y	Uncorrected continuation	0.388	4.723
U2	x	Uncorrected continuation	0.104	1.781
U2	y	Uncorrected continuation	0.119	1.906
M1	x	Uncorrected continuation	4.119	11.365

Test cell	Configuration	Variant	Max. compliance error (%)	Max. sensitivity error (%)
M1	y	Uncorrected continuation	3.458	10.929
H1	x	Uncorrected continuation	1.061	2.469
H1	y	Uncorrected continuation	1.223	1.734
M2	x	Uncorrected continuation	0.593	2.874
L1	x	Uncorrected continuation	0.174	1.894
L1	y	Uncorrected continuation	0.182	1.646
U1	x	Smoothing-trained	0.112	3.155
U1	y	Smoothing-trained	0.111	3.166
U2	x	Smoothing-trained	0.031	0.508
U2	y	Smoothing-trained	0.038	0.782
M1	x	Smoothing-trained	1.363	4.432
M1	y	Smoothing-trained	1.115	3.974
H1	x	Smoothing-trained	0.144	0.636
H1	y	Smoothing-trained	0.237	0.561
M2	x	Smoothing-trained	0.189	1.428
M2	y	Smoothing-trained	0.213	2.545
H3	x	Smoothing-trained	0.106	1.290
H3	y	Smoothing-trained	0.132	0.678
U1	x	Base network + correction	0.011	0.945
U1	y	Base network + correction	0.011	0.904
U2	x	Base network + correction	0.00123	0.142
U2	y	Base network + correction	0.0014	0.158

Test cell	Configuration	Variant	Max. compliance error (%)	Max. sensitivity error (%)
M1	x	Base network + correction	0.079	0.350
M1	y	Base network + correction	0.066	0.339
H1	x	Base network + correction	0.010	0.139
H1	y	Base network + correction	0.013	0.105
M2	x	Base network + correction	0.00492	0.083
M2	y	Base network + correction	0.0034	0.075
H3	x	Base network + correction	0.00609	0.132
H3	y	Base network + correction	0.00894	0.202
L1	x	Base network + correction	0.00193	0.065
L1	y	Base network + correction	0.00181	0.087
U1	x	NICE	0.00614	0.598
U1	y	NICE	0.00681	0.669
U2	x	NICE	0.00121	0.082
U2	y	NICE	0.00159	0.073
M1	x	NICE	0.056	0.161
M1	y	NICE	0.048	0.206
H1	x	NICE	0.0076	0.098
H1	y	NICE	0.011	0.097
M2	x	NICE	0.00595	0.136
M2	y	NICE	0.00472	0.154
H3	x	NICE	0.0064	0.124
H3	y	NICE	0.010	0.196
L1	x	NICE	0.00202	0.101
L1	y	NICE	0.00197	0.078

Combinations without a row were not evaluated. All cells in this table belong to the 20 validation geometries used for checkpoint selection (Section 5.1). Table ST09 gives the responses of the same configurations under cut-surface tractions. For the base network on U1/x under the z traction on the neighbour face (circled in Figure S04(a–c)), the test cell carries 0.1274669% of the exact assembled energy and has a local energy error of 2.312168%. The product $\beta = w\varepsilon$ is 0.002947249%, the compliance error 0.002827394% and the test-cell sensitivity error 5.82992%.

ST08b. Held-out two-cell configurations (NICE)

The cells lie outside checkpoint selection: the five validation geometries with NICE's largest single-cell errors and one randomly chosen evaluable cell per cut-severity group. Entries are maximum relative errors (%), over the six face loads for the compliance and over both cells for the thickness sensitivity. As in Table ST08, the neighbour is exact and the test cell learned. Cell labels are defined in Supplementary Section R1.

Cell	Selection	Remaining volume	x: compliance	x: sensitivity	y: compliance	y: sensitivity
W1	largest error, rank 1	0.571	0.2706	1.485	0.2220	1.312
W2	largest error, rank 2	0.267	0.1982	0.815	0.1703	1.344
W3	largest error, rank 3	0.287	0.1587	1.329	0.2489	1.419
W4	largest error, rank 4	0.266	0.0827	0.526	0.0753	0.971
W5	largest error, rank 5	0.681	0.0967	0.434	0.0878	0.563
RU	random, uncut	1.000	0.0010	0.181	0.0011	0.133
RL	random, light	0.779	0.0038	0.102	0.0051	0.102
RM	random, moderate	0.661	0.0101	0.103	0.0066	0.100
RH	random, heavy	0.078	0.0050	0.136	0.0066	0.218

Table ST09. Responses under cut-surface tractions

Maximum relative errors (%) over the three cut-surface traction directions, for every variant and configuration of Table ST08 with a cut test cell. Combinations without a row were not evaluated. Sensitivity maxima include both cells. The test cell is learned and the neighbour exact. As in the comparison of cut-surface tractions in Section 5.6, values above the common 3% line are in bold.

Variant	Cell	Configuration	Compliance error (%)	Sensitivity error (%)
Base network	M1	x	2.880	**9.924**
Base network	H1	x	0.445	2.066
Base network	H1	y	0.651	1.275
Base network	M2	x	0.560	**3.155**
Uncorrected continuation	M1	x	2.768	**9.827**
Uncorrected continuation	M1	y	**6.870**	**14.053**
Uncorrected continuation	H1	x	0.399	1.825

Variant	Cell	Configuration	Compliance error (%)	Sensitivity error (%)
Uncorrected continuation	H1	y	0.613	1.200
Uncorrected continuation	M2	x	0.574	**3.252**
Uncorrected continuation	L1	x	0.355	1.660
Uncorrected continuation	L1	y	1.141	**3.702**
Smoothing-trained	M1	x	0.713	**3.228**
Smoothing-trained	M1	y	2.417	**5.191**
Smoothing-trained	H1	x	0.062	0.356
Smoothing-trained	H1	y	0.130	0.587
Smoothing-trained	M2	x	0.200	1.664
Smoothing-trained	M2	y	1.117	**3.924**
Smoothing-trained	H3	x	0.052	0.689
Smoothing-trained	H3	y	0.237	1.354
Base network + correction	M1	x	0.049	0.217
Base network + correction	M1	y	0.124	0.305
Base network + correction	H1	x	0.0044	0.096
Base network + correction	H1	y	0.00709	0.022
Base network + correction	M2	x	0.00468	0.053
Base network + correction	M2	y	0.020	0.091
Base network + correction	H3	x	0.00391	0.038
Base network + correction	H3	y	0.011	0.042
Base network + correction	L1	x	0.00479	0.039
Base network + correction	L1	y	0.011	0.069
NICE	M1	x	0.035	0.161

Variant	Cell	Configuration	Compliance error (%)	Sensitivity error (%)
NICE	M1	y	0.101	0.158
NICE	H1	x	0.00338	0.061
NICE	H1	y	0.00587	0.126
NICE	M2	x	0.00603	0.072
NICE	M2	y	0.027	0.154
NICE	H3	x	0.00313	0.125
NICE	H3	y	0.00982	0.129
NICE	L1	x	0.00435	0.087
NICE	L1	y	0.011	0.071

Supplementary Note S1. Verification of the reference and of the thickness derivative

Figure S01 and Table ST10 verify the CutFEM reference under refinement of the background grid and under changes of the ghost-penalty coefficient. Table ST10b compares the reference with a body-fitted discretisation on uncut cells. The last paragraph of this note verifies the numerical thickness derivative.

For U1, M1 and M2, the compliance at $n = 32$ differs from the finest level of Figure S01(a) by at most 0.057% and the thickness sensitivity by at most 0.11%. H1 is clamped on $x = 0$ and loaded on $y = 0$, because its remaining part has no material on its z-faces. At $n = 32$ it differs from $n = 48$ by up to 0.99% in compliance, for the load normal to the loaded face, and by 0.97% in sensitivity, but from $n = 64$ by only 0.07% and 0.08%. Between $n = 48$ and $n = 64$ the difference is 1.08%, so H1 does not converge monotonically (Figure S01(d), Table ST10). On U1, M1, M2 and H1, varying the ghost-penalty coefficient between 10^{-5} and 10^{-3} changes the compliance by at most 0.053% and the sensitivities by at most 0.12%. At $\gamma = 10^{-3}$, the penalty energy is 1.2×10^{-4} to 5.6×10^{-4} of the total. Refining the volume integration changes both quantities by at most 0.010%.

Table ST10. Refinement of the reference to $n = 64$

Single cells are clamped on one cell face and loaded on another face by unit traction loads in the three coordinate directions, and they are solved at $n = 24$ to 64 by a sparse direct solver. H2 is loaded instead by a body force with unit resultant, because its only cell face that carries material is the clamped one. Each entry gives the signed compliance deviation from $n = 64$ with the largest magnitude over the three loads, followed after the slash by the largest relative deviation of the thickness sensitivity vector, both in percent. H2 could not be meshed at $n = 56$. Elsewhere in this work, the reference solutions are computed at $n = 32$.

Cell	$n = 24$	$n = 32$	$n = 40$	$n = 48$	$n = 56$
H1	-1.05 / 1.06	+0.07 / 0.08	+0.46 / 0.44	+1.08 / 1.06	+1.40 / 1.37
H2	-1.58 / 5.60	-0.93 / 3.59	-0.52 / 2.16	-0.27 / 1.24	—

Cell	$n = 24$	$n = 32$	$n = 40$	$n = 48$	$n = 56$
Validation cell with the largest NICE error	-0.32 / 0.57	-0.14 / 0.23	+0.08 / 0.09	-0.14 / 0.15	-0.02 / 0.03
Validation cell with the thinnest walls	-0.66 / 1.02	-0.28 / 0.44	-0.16 / 0.24	-0.09 / 0.20	+0.17 / 0.16

On uncut cells, the discrete model was also compared with an independent body-fitted discretisation (Table ST10b). This discretisation meshes the same implicit geometry with quadratic tetrahedra and shares no geometry, quadrature or stabilisation code with the discrete model.

Table ST10b. Comparison with a body-fitted quadratic-tetrahedral discretisation on uncut cells

Configuration	Loads	CutFEM vs finer body-fitted mesh: max. compliance difference (%)	Body-fitted discretisation: change between its two mesh levels (%)
Four single uncut cells	Six fixture load cases	0.084–0.101	0.130–0.273
One uncut cell	Twelve local tractions on finite areas	0.253	0.502
Assemblies of uncut cells: two cells, 2×2×2, 1×1×4	Fixture load cases	0.052–0.090	0.108–0.190

Figure S01(c) reports a step-refinement study of the numerical thickness derivative on four cells. Relative to the step used in the computations, $10^{-5}\tau_c$, the sensitivity changes by at most 2.6×10^{-7} at $10^{-3}\tau_c$, 2.5×10^{-9} at $10^{-4}\tau_c$ and 1.6×10^{-10} at $10^{-6}\tau_c$. The hundredfold reduction per decade is the second-order truncation error of the central difference. It is consistent with a derivative that is smooth within $\pm10^{-3}\tau_c$ at the fixed active set on these cells. On the same cells, the central-difference stiffness derivative agrees to 4×10^{-8} with differences of the compliance recomputed at the perturbed designs. An element-level check over the partially filled elements of the eight detailed cells shows that the discrete moments do not everywhere preserve the nesting on which Eq. (H.7) relies. The element stiffness matrices are positive semidefinite to rounding. However, the exact derivative of the discrete moments at fixed clipping topology gives element derivative matrices with negative eigenvalues. In the uncut cells, the smallest ratio $\lambda_{\min}/\max|\lambda|$ is -2.3×10^{-3}. In four of the six cut cells, between 2 and 11 partially filled elements (of 762 to 6,033) have a uniform-thickening derivative whose most negative eigenvalue exceeds 10^{-6} of its largest eigenvalue in magnitude. These derivatives are indefinite, with a largest eigenvalue of at least 10^{-3} of the largest magnitude.

The central difference used in the computations agrees with this exact discrete derivative to 2×10^{-8}.

Supplementary Note S2. Ablation: Bernstein-restricted cell faces

This note gives the complete results of the ablation summarised in Section 5.7. Every cell uses its exact condensed stiffness matrix (the Schur complement), and only the representation of the retained cell-face displacements is reduced.

S2.1. Restricted Galerkin system

The restricted space uses tensor-product Bernstein polynomials of degree r on the selected cell faces of each cell. Its global map G_r respects the DOFs shared between cells. DOFs of the cut-plane elements that do not lie on the cell faces keep identity columns. With the supports applied, the Galerkin system is

$$\mathbb{K}_r = G_r^T \mathbb{K} G_r, \qquad f_r = G_r^T f_g, \qquad U_r = G_r \mathbb{K}_r^{-1} f_r. \tag{S2.1}$$

The comparison evaluates the exact condensed stiffness matrices of the cells within this restricted space of cell-face displacements. The interior is therefore exact, and every error comes from the restricted boundary. Two cases are examined: every cell face restricted, as in a lattice built entirely from such substructures, and only the shared interface restricted.

Boundary restriction and the interior correction $\mathcal{W}$ act on different displacement spaces. Exact condensation followed by the restriction $U = G_r y$ solves over a subspace of the space of retained displacements. By the principle of minimum potential energy, the compliance of this restricted solution does not decrease when the boundary space is enlarged to a space that contains it. The correction keeps every retained DOF fixed and changes the interior displacements of $u = \widehat{\Psi} B U$. Its ordering holds because the two-grid cycle that defines H does not increase the energy error (Section 3.4), although two such interior spaces need not be nested. In neither case is a norm of the local sensitivity ordered.

S2.2. Conditions

- Pairs in configuration x (Figure 9; Supplementary Note S4), each test cell with its exact neighbour of continuous thickness, for U1, M1, M2 and H1; the interface-only case was run for U1, M1 and M2.
- One cell per substructure, the fine-scale face traction loads used throughout, and no oversampling.
- Loads: the three tractions on the test-cell face and the three tractions on the neighbour face.
- The DOFs of the cut-plane elements that are not on the cell faces remain unrestricted, which favours the restricted model (controlled DOFs in Table ST11).
- The comparison concerns accuracy only and does not compare accuracy at equal cost.

Table ST11. Bernstein restriction of the cell-face displacements

Each test cell and its neighbour of continuous thickness are assembled in configuration x with exact condensed stiffness matrices. Degree r applies to the restricted cell faces; the DOFs of the cut-plane elements keep their identity representation. Controlled DOFs include these unrestricted DOFs of the cut-plane elements. All errors are maxima over the stated load set (%), relative to the solution with all retained DOFs; the sensitivity columns refer to the test-cell vector. Test-face loads are the three unit traction loads on the loaded face of the test cell, and the six-load set adds the three tractions on the neighbour face. The maxima of the two load sets need not occur under the same load.

ST11a. Every cell face restricted

Cell	r	Controlled DOFs	Test-face compliance (3 loads)	Test-face sensitivity (3 loads)	Six-load compliance (6 loads)	Six-load sensitivity (6 loads)
U1	1	24	76.998	89.056	82.609	203.566
U1	2	102	56.944	62.055	56.944	317.415
U1	3	240	38.907	47.849	38.907	398.644
U1	5	696	3.926	3.603	3.961	114.545
U1	8	1,830	0.485	1.467	0.485	24.435
M1	1	15,423	77.749	88.966	78.485	294.272
M1	2	15,498	53.133	62.622	53.133	402.365
M1	3	15,627	33.998	45.584	33.998	421.766
M1	5	16,047	3.930	4.748	3.930	138.963
M1	8	17,082	0.521	1.295	0.611	39.320
M2	1	15,648	76.234	84.796	85.269	244.968
M2	2	15,723	49.547	41.050	50.436	606.013
M2	3	15,852	29.124	19.138	33.554	747.730
M2	5	16,272	3.413	4.275	3.634	334.483
M2	8	17,307	0.505	4.458	0.586	38.693
H1	1	12,888	81.713	87.320	81.713	333.566
H1	2	12,939	37.528	29.960	41.962	188.527
H1	3	13,026	21.660	18.637	30.364	340.008
H1	5	13,308	2.784	2.890	3.860	171.306
H1	8	14,001	0.608	1.520	0.735	64.044

ST11b. Only the shared interface restricted

Cell	r	Controlled DOFs	Test-face compliance (3 loads)	Test-face sensitivity (3 loads)	Six-load compliance (6 loads)	Six-load sensitivity (6 loads)
U1	1	25,386	1.947	3.599	1.947	85.982
U1	2	25,401	0.667	4.905	0.667	29.133
U1	3	25,422	0.169	0.338	0.169	7.999
U1	5	25,482	0.010	0.328	0.036	2.194
U1	8	25,617	0.001	0.003	0.002	0.359
M1	1	37,080	9.355	10.397	9.355	81.909
M1	2	37,095	1.915	4.529	1.915	36.640
M1	3	37,116	0.440	1.106	0.440	9.954

Cell	r	Controlled DOFs	Test-face compliance (3 loads)	Test-face sensitivity (3 loads)	Six-load compliance (6 loads)	Six-load sensitivity (6 loads)
M1	5	37,176	0.073	0.335	0.073	2.174
M1	8	37,311	0.011	0.031	0.011	0.615
M2	1	35,196	4.228	8.397	4.228	88.562
M2	2	35,211	0.728	3.825	0.728	18.427
M2	3	35,232	0.261	1.058	0.261	21.216
M2	5	35,292	0.030	1.004	0.030	3.366
M2	8	35,427	0.009	0.049	0.009	1.537

With all retained DOFs and the supports applied, the systems have 28,206 (U1), 39,996 (M1), 39,120 (M2) and 32,991 (H1) free DOFs.

Supplementary Note S3. Cost records: whole-lattice direct solution and per-cell condensation

This note defines the three routes of Table 5 and records their phases (Table ST12). It also compares the per-cell cost of conventional condensation and NICE (Table ST13). The four-cell lattices are the two layers $z = 0$ and $z = 1$ of the $2 \times 2 \times 2$ block of Section 5.8, with their corner thickness parameters unchanged. Each layer holds two uncut cells and two cut cells with remaining volume fractions 0.616 and 0.252. All lattices are clamped on the face $y = \min$ and loaded on the face $y = \max$ by unit traction loads along the three Cartesian axes. Routes (a) and (b) also solve three random loads.

Route (a), the whole-lattice direct solution, assembles the full cut-cell stiffness of every cell, on its retained and interior degrees of freedom, into one global matrix. The retained degrees of freedom are numbered and coupled exactly as in the learned lattice, with the same clamp, free set and load vectors. The interior degrees of freedom of each cell follow the free retained ones. The matrix is scaled symmetrically by its diagonal and factorised by MKL PARDISO 2026.1 on the CPU. The factorisation is a symmetric positive definite Cholesky factorisation of the upper triangle (mtype 2), with nested-dissection ordering (iparm(2) = 3) and 16 threads. The PARDISO phases are called directly with explicitly set parameters, and all six loads are solved at once. Relative residuals $\|Ku - f\|/\|f\|$ are recomputed with the unscaled matrix.

Route (b), conventional exact condensation, processes the cells one at a time on the CPU with 16 threads. Cell setup and assembly are as in route (a). PARDISO's Cholesky factorisation with the Schur-complement option (iparm(36)) then gives the dense condensed matrix of the cell on its retained degrees of freedom, after which the cell is released. The condensed lattice system is solved exactly by a block Cholesky factorisation in substructuring order. For each cell, its private retained block is factorised and eliminated with dense kernels. The dense interface matrix over the retained DOFs shared by several cells is then factorised and solved, and the private DOFs are recovered by back-substitution. The condensed cell matrices are held until their elimination.

Route (c) runs one lattice analysis with sensitivities in the deployed implementation of NICE (PyTorch 2.8.0, CUDA 12.8, NVIDIA cuDSS 0.8) on an NVIDIA GeForce RTX 5090 GPU. Cell preparation comprises cell construction, stiffness and moment assembly, network

input and encoding, and a first application that prepares the correction. The lattice and $\mathbb{K}_{PP}$ are then assembled, and the preconditioner is set up (the balanced two-level action of Supplementary Note S4.1). Conjugate gradients solve the three traction loads to a recursive relative residual of 10^{-6}; the residuals reached are 9.0×10^{-7} to 9.9×10^{-7}. Finally, the sensitivities $\widetilde{s}_c$ of Eq. (17) for the three loads are obtained by reverse-mode differentiation of the moment integrals at the fixed recovered displacement fields. Route (c) uses the arithmetic of the timed route of Table 1. The network and the smoothing and coarse solve of the correction run in single precision, and the stiffness products of the condensed action in double precision (Appendix F.2). The three routes read the same generated cell geometries; geometry generation is not timed.

Whole-lattice iterative solvers (Table ST12e) use the global matrix, load vectors, clamp and numbering of route (a). These are exported once and solved with PETSc 3.26 Balay et al. (2026) with 16 MPI processes on the CPU used for routes (a) and (b). Conjugate gradients run on the unscaled system and stop on the unpreconditioned relative residual $\|Ku - f\|/\|f\| \leq 10^{-9}$. The iterate is recorded where the residual first falls below $10^{-3}, 10^{-4}, \ldots$, together with its compliance and energy-norm difference from the final iterate. GAMG (smoothed aggregation, PETSc defaults) uses block size 3 and the six rigid-body modes of the DOF positions as near-null space. BoomerAMG uses HMIS coarsening, extended+i interpolation, nodal coarsening, strong threshold 0.5 and its default relaxation. The BDDC configuration considered has exact local solvers and one subdomain per cell. The Dirichlet matrix of a cell is its stiffness on the DOFs it shares with no other cell, and its Neumann matrix is the whole cell stiffness on its free DOFs. Each is factorised once, cell after cell, with the PARDISO configuration of route (a) (symmetric Jacobi scaling, real SPD Cholesky, tuned iparm, 16 threads). The singular Neumann matrices of floating cells are shifted by 10^{-10} on the diagonal of the scaled matrix. The sum of these factorisations is a reference for the local factorisation cost of BDDC with exact local solvers in this configuration. It does not include the treatment of the primal constraints and the null space in the local Neumann problems, the coarse problem or the iterations. With MUMPS for the local and coarse problems on eight processes, BDDC with all local factors resident exceeded 90 GiB during its setup.

Table ST12. Whole-lattice direct solution, conventional exact condensation and learned route: dimensions, phases and memory

Times in s. Memory in GiB (2^{30} bytes). PARDISO memory is its permanent plus factorisation storage (iparm(16) + iparm(17)) reported by the analysis phase, with kilobytes taken as 1024 bytes. Totals, iteration counts, peak process memory and the memory of route (c) are given in Table 5.

ST12a. Lattice dimensions

Lattice	Cells (cut)	Cut-plane-element DOFs off the cell faces (fraction of free retained DOFs)
2×2×1, z=0	4 (2)	35,829 (46%)
2×2×1, z=1	4 (2)	33,327 (47%)

Lattice	Cells (cut)	Cut-plane-element DOFs off the cell faces (fraction of free retained DOFs)
2×2×2	8 (4)	69,156 (50%)
3×3×1	8 (3)	53,085 (37%)

Total and free retained DOFs: Table 5.

ST12b. Route (a), direct solution on the CPU (Cholesky, 16 threads and one thread): phases (s) and memory (GiB)

Lattice	Threads	Cells: setup + assembly	Global assembly and scaling	Analysis	Factorisation	Solution, 6 loads	Total	PARDISO memory	Max. relative residual
2×2×1, z=0	16	229.9	21.9	26.0	193.1	13.5	484.4	32.0	3.3e-10
2×2×1, z=0	1	777.3	19.8	115.8	1,500.0	12.1	2,425.0	31.4	4.0e-10
2×2×1, z=1	16	184.2	17.6	20.2	116.9	10.4	349.2	28.8	4.5e-10
2×2×1, z=1	1	685.6	18.8	106.1	1,309.4	11.3	2,131.3	28.3	5.2e-10
2×2×2	16	379.5	36.0	53.1	368.2	31.0	867.8	66.4	1.5e-10
2×2×2	1	1,402.1	39.3	254.5	4,140.3	27.7	5,863.9	65.5	1.8e-10
3×3×1	16	431.3	42.3	50.4	481.5	36.0	1,041.6	80.9	2.6e-09
3×3×1	1	1,669.9	45.4	324.4	6,059.1	32.4	8,131.0	79.8	2.8e-09

Total: sum of the phases; the 16-thread totals are those of Table 5. With 32 threads, the whole direct solution takes 378.5, 341.1, 823.4 and 955.5 s instead of 484.4, 349.2, 867.8 and 1,041.6 s, because cell setup and assembly do not speed up.

ST12c. Route (b), conventional exact condensation on the CPU (16 threads): phases (s) and memory (GiB)

Lattice	Cell preparation	Cells: Schur complement	Condensed solve	Condensed cell matrices held (GiB)	Compliance vs. (a)
2×2×1, z=0	210.6	274.3	86.8	17.8	5e-10
2×2×1, z=1	263.4	279.2	71.4	14.9	4e-10
2×2×2	393.6	392.5	133.9	32.8	2e-10
3×3×1	462.0	555.0	165.7	33.4	7e-10

Condensed solve: private elimination, interface factorisation and solution, and back-substitution for the six loads. The total of Table 5 also includes the per-cell lattice geometry, the matrix scaling and data movement between phases (17 to 35 s). Compliance vs. (a): largest relative difference over the six loads from the whole-lattice direct solution.

ST12d. Route (c), learned route: phases of one lattice analysis with sensitivities (s)

Lattice	Cell preparation	Lattice and $\mathbb{K}_{PP}$ assembly	Preconditioner setup	Conjugate-gradient solve, 3 loads	Sensitivities
2×2×1, z=0	7.50	0.08	3.78	25.63	2.12
2×2×1, z=1	6.49	0.08	3.39	25.23	1.87
2×2×2	11.82	0.17	6.57	56.37	3.80
3×3×1	12.66	0.14	7.25	80.85	4.07

Total, iterations and memory: Table 5. The phases sum to 0.2–0.5 s less than the totals; the remainder is bookkeeping between phases. GPU memory is the peak memory in use on the whole GPU (nvidia-smi, sampled every 0.1 s), which besides the tensors includes the CUDA context, the cuDSS factorisation and the memory held by the caching allocator; CPU memory is the resident set size after cell preparation. Learned substructures resident on the GPU (Supplementary Note S4.1): all cells of the four-cell lattices and four cells of each eight-cell lattice.

ST12e. Whole-lattice iterative solvers on the CPU (16 MPI processes): setup, conjugate gradients and BDDC factorisations (s)

Lattice	GAMG: setup	GAMG to 10^{-4}: iterations / time per load	GAMG to 10^{-4}, with setup: 3 loads / 6 loads	GAMG at 10^{-4}: max. compliance / energy difference	BoomerAMG: setup / iterations to 10^{-4} / time per load	BDDC factorisations: Dirichlet + Neumann
2×2×2	35.3	90–134 / 52–72	221 / 432	4.6e-10 / 2.1e-5	88.0 / indefinite preconditioner	207.9 + 241.3 = 449.2
3×3×1	39.2	98–123 / 66–84	278 / 478	1.4e-10 / 1.2e-5	96.6 / 250–260 / 405–481	245.3 + 277.9 = 523.1

Differences are relative to the iterate at a relative residual of 10^{-9}, which GAMG reaches in 235–274 (2×2×2) and 204–220 (3×3×1) iterations. Loads: three traction loads, then three random loads, as in route (a). Cell setup and assembly and the global assembly and scaling are taken from route (a) and are common to all fine-scale routes. They are not included (Table ST12b: 416 and 474 s).

Table ST13. Per-cell cost of conventional condensation and NICE

Four deployment cells, two cut and two uncut (Supplementary Section R1). Both routes read the generated cell geometry; geometry generation is not timed (as in Table 5). Cell preparation: cell setup and element moments, on the GPU, for NICE; cell setup, moment integration and stiffness assembly, on the CPU, for the conventional route. Condensation: network input, encoding and correction setup (smoothing interval and coarse factorisation) for NICE; symbolic analysis and Cholesky factorisation of the interior by MKL PARDISO (16 threads) for the conventional route. The NICE times exclude the one-time compilation and initialisation of the GPU kernels at the start of a process (about 1.5 s). Memory, in

GiB: for NICE, all GPU memory that the deployed implementation holds for the cell after the correction setup, comprising the network state, the correction and the stiffness kept as element moments (the deployed implementation does not assemble the cell stiffness matrix; the element moments take 0.03–0.09 GiB per cell); for the conventional route, PARDISO's factorisation storage (iparm(17)), with the assembled cell stiffness matrix held in addition.

Cell	DOFs / retained	Cell preparation (s): NICE / conventional	Condensation (s): NICE / conventional	Memory (GiB): NICE state / PARDISO factor
G1 (cut)	177,507 / 24,636	0.46 / 27.3	0.29 / 10.5	0.48 / 2.89
G2 (cut)	67,224 / 18,858	0.27 / 10.9	0.13 / 1.9	0.19 / 0.60
G3 (uncut)	289,494 / 17,508	0.58 / 45.0	0.52 / 27.3	0.83 / 6.18
G4 (uncut)	404,148 / 25,920	0.68 / 47.0	0.76 / 48.9	1.08 / 9.42

Supplementary Note S4. Global preconditioning, two-cell configurations and residual records

S4.1. Balanced two-level preconditioner

Let $\mathbb{A}$ be the supported assembled operator used in a run, either the exact or learned one. This notation is distinct from the local interior stiffness $A = K_{II}$. Let $\mathbb{K}_{PP} = \sum_m B_m^T K_{PP,m} B_m$ on the free retained DOFs. The stiffness-block fine action is $\mathcal{B}_f = \mathbb{K}_{PP}^{-1}$.

For a global coarse basis Z_g on the retained DOFs, the ideal coarse action is $Q_g = Z_g(Z_g^T \mathbb{A} Z_g)^{-1} Z_g^T$, after removal of dependent columns. The balanced action is

$$\mathcal{M}^{-1} = Q_g + (I - Q_g\mathbb{A})\mathcal{B}_f(I - \mathbb{A}Q_g).$$

The reported coarse basis multiplies the trilinear lattice-vertex functions by three translations and three rotations about each vertex, then restricts the resulting fields to the supported retained DOFs. This global coarse basis differs from the interior basis V used to correct the network's interior displacements in each cell. The exact and learned lattice solves of Section 5.8, the learned route (c) of Section 5.9 and the learned solves of Section 5.10 use this balanced action with the stiffness-block fine action and this coarse basis.

The coarse matrix $A_g = Z_g^T \mathbb{A} Z_g$ is symmetrised and scaled by its diagonal. Eigenvectors whose scaled eigenvalues are positive and exceed 10^{-10} times the largest are kept, and the corresponding normalised columns Y_g give $Q_g = Y_g Y_g^T$. The stored product $\mathbb{A}Y_g$ supplies the two projections.

On the GPU, $\mathbb{K}_{PP}$ is factorised once per design iteration by a sparse Cholesky factorisation with NVIDIA cuDSS. The learned substructures are held on the GPU up to a memory budget for resident learned substructures; beyond it, the state of the remaining cells is held in CPU memory and streamed from there. The resident cells or budget of each run are given in the note to Table ST12d, in Table ST16 and in the caption of Table ST20.

S4.2. Two-cell test configuration

In both configurations of Figure 9, the six face loads are traction loads along the three Cartesian axes on the loaded face of the test cell and the same three loads on the loaded face

of the neighbouring cell. The traction loads are obtained by integrating the Q2 surface shape functions. Each nodal load vector is normalised to unit resultant before support elimination, and clamped entries are then eliminated. Three traction loads on the cut surface of the test cell, normalised in the same way, are reported separately when present. The neighbouring cell is uncut. Where the cut plane of the test cell meets the shared face, the pair is therefore a test configuration and not a physically cut specimen.

The pair solves use conjugate gradients preconditioned by the Cholesky factor of the exact assembled reference stiffness, with a relative recursive-residual tolerance of 10^{-10} and at most 400 iterations.

S4.3. Residual work, gradient checks and difference quotients of the approximate compliance

The lattices of Section 5.8 and their two $2 \times 2 \times 1$ layers are solved with NICE to a recursive residual of 10^{-10}, with the correction in double precision. Three quantities are recorded at the final iterate $\bar{U}$. The first is the signed residual work $\bar{U}^T\rho$, with $\rho = f_g - y(\bar{U})$ and y the applied learned action. The second is the action–energy inconsistency $\omega = \sum_m \omega_m$, $\omega_m = \bar{q}_m^T y_m(\bar{q}_m) - \bar{u}_m^T K_m \bar{u}_m$. Here $\bar{q}_m = B_m\bar{U}$, $\bar{u}_m = \widehat{\Psi}_m\bar{q}_m$ and y_m is the applied action of cell m, so that $y(\bar{U}) = \sum_m B_m^T y_m(\bar{q}_m)$ and ω is the quantity of Appendix C.2. The third is the dual-norm bound on $|\bar{U}^T\rho|$ of Appendix C.2, with $\rho^T\mathbb{K}^{-1}\rho$ computed with the exact assembled operator. All quantities are relative to the exact compliance. The recomputed relative residual $\|f_g - \widehat{\mathbb{K}}\bar{U}\|/\|f_g\|$ stagnates at 3.6×10^{-4} (block) and 3.2×10^{-3} (layer). Running the correction in single instead of double precision changes this residual of the block by less than 1%. It changes the compliance errors of the block by less than 3×10^{-9} and those of the layer by less than 4×10^{-8}, and the gradient errors of both by less than 10^{-6}.

The gradient metrics compare the sensitivities from NICE with the exact ones after aggregation over the shared lattice vertices, that is, after summing the cells' thickness sensitivity components at each vertex. The aggregated vector is the gradient that an optimiser with shared thickness variables receives; loads are held fixed. For the complete derivative of the approximate compliance, every cell's condensed stiffness was rebuilt at $\tau \pm h\tau_c e_c$ for each corner. The rebuilt stiffness was applied to the solved retained displacements at fixed $\widehat{q}$, which gives the action-energy difference quotient D_{act}. A rebuild counts as switched when, relative to the unperturbed build, it changes any of the following: a binary node indicator; the set of weak-region element or face stencils (stencils containing a weakly connected node, Appendix G.1); the active element set; or the diagonal shift of the coarse factorisation (Appendix F.1).

Table ST14. Residual work, dual-norm bound, gradient and difference quotients of the approximate compliance

Face = the three face traction loads; random = the three random loads. Gradient error: $\|\widetilde{\boldsymbol{s}}_g - \boldsymbol{s}_g\|/\|\boldsymbol{s}_g\|$ over the shared vertex parameters, in percent; cosine over all six loads. D_{act}: relative error against the exact vertex gradient under the face loads at step h (in units of τ_c), in percent. Switched rebuilds: number of the 49 rebuilds per cell (three steps, both signs and eight corners, plus one unperturbed) that change a discrete choice, range over cells.

Lattice	$\max\lvert\bar{U}^T\rho\rvert/C$	Dual-norm bound / C	$\max\lvert\omega\rvert/C$	Gradient error, face / random (%)	Smallest cosine	D_{act} at $h = 3\times10^{-3}$ / 10^{-3} / 3×10^{-4} (%)	Switched rebuilds per cell
$2\times2\times1$, $z=0$	2.3×10^{-8}	6.8×10^{-6}	5.0×10^{-9}	0.022–0.048 / 0.22–0.27	0.9999998	0.29 / 0.65 / 1.53	31–48
$2\times2\times1$, $z=1$	5.3×10^{-8}	7.9×10^{-6}	9.5×10^{-9}	0.067–0.130 / 0.29–0.35	0.9999993	0.21 / 0.27 / 0.35	32–47
$2\times2\times2$	2.9×10^{-9}	4.7×10^{-6}	2.4×10^{-9}	0.052–0.069 / 0.24–0.27	0.9999996	0.18 / 0.29 / 0.59	31–48
$3\times3\times1$	2.5×10^{-8}	1.4×10^{-5}	7.0×10^{-9}	0.041–0.088 / 0.22–0.28	0.9999996	0.19 / 0.23 / 0.35	21–48

On the lattices, D_{act} grows as the step decreases, so the difference quotient does not resolve the complete derivative of the approximate compliance. The same records were made on the fourteen two-cell configurations of the selection cells (Section 5.6). They give $|\bar{U}^T\rho|/C \le 1.8\times10^{-8}$, a dual-norm bound of at most 2.0×10^{-5}, $|\omega|/C \le 1.7\times10^{-8}$, thickness-sensitivity errors of 0.07–0.67% with cosines of at least 0.999998, and D_{act} errors of 0.05–0.27% at $h = 10^{-3}$ that likewise do not decrease with the step.

The accuracy of the two eight-cell lattices in these runs is reported in Section 5.8. The values below are given for the $2\times2\times2$ block / the $3\times3\times1$ layer. The compliance errors under the three face loads are 0.0137, 0.0110 and 0.0094% / 0.0147, 0.0134 and 0.0103%, and at most 0.069% / 0.056% under the random loads. The largest thickness-sensitivity error over all cells is 0.144% / 0.144% under the face loads and 0.454% / 0.426% under the random loads. The relative Euclidean difference between the learned and exact assembled retained solutions over all six loads is 0.130% / 0.123%. The cell energy errors ε_m at the exact retained displacements are 0.0061–0.026% / 0.0051–0.052% under the face loads and 0.027–0.123% / 0.023–0.077% under the random loads. The excess of β (Eq. (15)) over the lattice compliance error is 0.13–0.28% / 0.21–0.33% of that error under the face loads and 4.4–5.1% / 4.2–5.0% under the random loads. The exact references, assembled from the dense exact condensed matrices, reach recomputed relative residuals of 9.1×10^{-11} / 1.3×10^{-10}. The corner parameters of the block range from 0.2516 to 0.5350.

One-corner sweeps test the smoothness of the approximate compliance across these switches. In the two-cell configurations M1/x and U1/y, one corner parameter of the test cell was varied over up to ±10% of its value; this was the corner with the largest or the median sensitivity. Every design had its own regenerated geometry and learned substructure. The compliance change between neighbouring designs was compared with the change predicted by the trapezoidal rule from the sensitivities at both ends. The same comparison was made for the exact discrete model at every tenth design. Every interval on M1/x and 24 of the 26 intervals on U1/y change at least one discrete choice. Most of these changes concern the active elements, ghost faces and retained DOFs, which belong to the discrete model itself. On these intervals the approximate compliance departs from the predicted change by up to 0.25% (M1/x), 0.17% and 0.085% (U1/y) of the compliance, and the exact model departs by the same amount. On M1/x the departures are 0.230, 0.252 and 0.228% against 0.228, 0.249 and 0.225%; on U1/y they are identical to three significant digits. On the two U1/y intervals without a switch the departure is 7×10^{-8}. At the reference designs the error of the approximate compliance stays at its bound β (6.0×10^{-4} on M1/x, 7.2×10^{-5} on U1/y). On the checked intervals the dominant departure of the approximate objective is therefore

also present in the exact discrete model, which an optimiser driven by exact condensation meets in the same way.

Supplementary Note S5. Network settings and parameter counts

Table ST15 complements Appendix G with the coefficient-bound groups, the initialisation and the parameter count of every block.

Table ST15. Coefficient bounds, initialisation and parameter counts

Item	Setting
Coefficient bounds $a_{\max}$	Fixed per group: gather and scatter role of each of the 8 element, 12 face and 4 weak-region layers (48 groups), and restriction and prolongation of each of the 3 levels (6 groups), plus the knee k_b: 55 stored values, part of the stored model state (definition in Appendix G)
Initialisation	Channel maps $W_{\ell h}$: $0.5\mathcal{N}(0,1)/\sqrt{32}$; W_{in}: $\mathcal{N}(0,1)/\sqrt{3}$; W_{out}: $0.1\mathcal{N}(0,1)/\sqrt{32}$; convolution kernels: $0.5\mathcal{N}(0,1)/\sqrt{27 \cdot 32}$; position-embedding tables: $0.1\mathcal{N}(0,1)$; $\sigma_\ell = 1$; $\lambda_{\text{mix}} = 0$; affine layers: PyTorch default. The base network is initialised from the parameters of three preceding training stages (notes to Table ST01), the first of which uses the random initialisation above; the continuations start from the base network's selected parameters
Parameter counts, geometry branch	Element encoder 12,288; node encoder 9,024; message passing 49,664; face encoder 12,608; position-embedding tables 432; element, face and weak-region coefficient heads 12,928, 15,008 and 10,848; restriction/prolongation heads 12,870; convolution-coefficient heads 37,440. Total 173,110
Parameter counts, displacement branch	Element channel maps 32,768; face channel maps 49,152; weak-region element channel maps 16,384; convolution kernels 331,776; W_{in} and W_{out} 96 each; skip scalars 3; λ_{mix} 24. Total 430,299
Stored values	603,409 trainable parameters and 55 fixed bound values: 603,464 in total
Training settings	Notes to Supplementary Table ST01; seed 0 for every run

Supplementary Note S6. Design optimisation records

This note gives the settings (S6.1, Table ST16) and the records of the thickness optimisations of Section 5.10. All NICE runs use one GPU. Compliance is given in the units of Section 5.1 ($E_Y = 1$, unit cell) and memory in GiB (2^{30} bytes). Times are wall-clock times of complete design iterations and include geometry generation, except at iteration 0, whose geometry was generated beforehand.

S6.1. Optimiser and constraints

Table ST16 lists the settings. The method of moving asymptotes builds one convex separable approximation per analysis from the estimated gradient. It never tests the decrease of $\widehat{C}$ along a search direction, where the inconsistency discussed in Section 4.2 would matter. Neither the gradient norm nor a KKT residual is used for stopping, since the estimate is not the gradient of $\widehat{C}$ and $\widehat{C}$ changes its discrete model between iterations (S6.4). A design iteration differs from an analysis of Table 5 in that it regenerates every cell's geometry and solves for one load instead of three. For case A, a NICE design iteration takes 74 s on average (Table ST17c), against 79 s for the analysis of the same block in Table 5, which needs no geometry generation but solves for three loads.

Table ST16. Optimiser, constraints and analysis settings

Item	Setting
Design variables	Corner thickness parameters at the lattice vertices $\boldsymbol{\tau}_g$; $\boldsymbol{\tau}_m = \boldsymbol{\tau}_m(\boldsymbol{\tau}_g)$ copies the vertex values to the corners of every cell meeting there. Case A: 27 vertices, 18 free; plate: 74 vertices, 64 free
Fixed vertices	The vertices in the plane of the loaded face (9 in case A, 10 in the plate), so that the nodal load obtained by consistent integration of the traction load does not change with the design (Appendix H: no load-derivative term)
Objective	Compliance $\widehat{C}$ under one face traction load of unit resultant, evaluated as the work $f_g^T \bar{U}$ of the final conjugate-gradient iterate and divided by its value at the first iteration
Gradient	Sensitivity estimate of Section 5.10, from one reverse-mode pass through the moment integrals at the fixed recovered displacement field; the complete derivative of the approximate compliance, Eq. (18), is not used. Exact twin: exact sensitivities from the exact displacement field with the moment derivatives of Eq. (H.3)

Item	Setting
Volume constraint	$V/V^* - 1 \leq 0$; V = sum of the zeroth element moments of all cells (material volume of the discrete model), its derivative from the same reverse pass (exact twin: Eq. (H.3)). $V^* = 0.8\,V(\boldsymbol{\tau}^0)$: 1.03558 (case A), 3.65526 (plate)
Corner-span constraint	$(\tau_a - \tau_b)/0.45 - 1 \leq 0$ for every ordered pair of distinct corner vertices of every cell (316 ordered pairs, 276 of them involving a free vertex, in case A; 938 and 896 in the plate); pairs of two fixed vertices are constant and are not passed to the optimiser; training limit 0.47 (Table ST02)
Gradient-norm constraint	$\lvert\nabla\tau\rvert^2/0.45^2 - 1 \leq 0$ at every corner of every cell, from the three edge differences (64 corner stencils in case A, 192 in the plate, each with a free vertex); for a trilinear field the largest gradient norm over the cell is attained at a corner; training limit 0.47
Bounds	$0.18 \leq \tau \leq 0.69$; training range [0.1752, 0.6993] (Table ST02)
Optimiser	Method of moving asymptotes Svanberg (1987), one update per analysis, no line search and without the conservativeness test of its globally convergent variant GCMMA; subproblem solved by the primal–dual interior-point method of Svanberg (2007, Section 5), the barrier parameter reduced tenfold from 1 to 10^{-7} (at each value, Newton steps until the largest residual is below 0.9 of it, at most 200); constants of the standard MMA problem form: $a_0 = 1$, $a_i = 0$, $c_i = 1000$, $d_i = 1$
Asymptotes	Initially $x \pm 0.5(x_{\max} - x_{\min})$ (first two iterations), then widened by 1.2 where consecutive steps have the same sign and narrowed by 0.7 where they alternate, kept between 0.01 and 10 variable ranges from x; subproblem bounds at 0.1 of the distance to the asymptotes
Move limit	0.05 of the variable range, 0.0255 per iteration
Stopping rule	$\max\lvert\Delta\tau\rvert < 10^{-3}$, or relative objective change below 10^{-4} in three consecutive iterations, or 60 iterations

Item	Setting
Geometry	Every iteration regenerates the geometry of every cell from its current corner parameters with the geometry generator used for all cells of this study, in parallel processes on the CPU (8 for case A, 12 for the plate), and rebuilds every learned substructure
Lattice solve	Preconditioned conjugate gradients with the balanced two-level preconditioner of Supplementary Note S4.1 to a recursive relative residual of 10^{-6} (at most 3,000 iterations), in the arithmetic of the timed route of Table 5, with the coarse-factor pivot rule of Appendix F.1; a run stops if a solve reaches 3,000 iterations or a recomputed relative residual above 10^{-2}. Exact twin: dense exact condensed matrices of every cell, assembled solve to 10^{-10}
Warm start	From the previous iteration's solution, matched DOF by DOF on absolute grid position, displacement component and the private flag of the cut-plane elements; unmatched DOFs start at zero; the start is scaled by the energy-optimal factor $f_g^T X_0/(X_0^T \widehat{\mathbb{K}} X_0)$; the stopping criterion, relative to $\|f_g\|$, is unchanged. At iteration 0 of every run the solve started from zero. Exact twin: cold start
GPU memory budget for resident learned substructures (Supplementary Note S4.1)	Case A: all cells resident; plate: cells resident while the allocated GPU memory stays below 22 GiB; scale study: 4 GiB (Table ST20)
Geometry-generation fallback	If generation fails for some cells, the free vertices of those cells are multiplied by $1+\epsilon$, $\epsilon =$ $10^{-4}, -10^{-4}, 10^{-3}, -10^{-3}, 3\times10^{-3}, -3\times10^{-3}$ in turn (clipped to the bounds), every cell sharing them is regenerated, and the perturbed design is analysed and continued from. Applied four times over all runs (Table ST19a)

The designs analysed on the fine scale are all iterations of the runs of Tables ST17 and ST18 and the homogenisation design. Over these designs, the largest corner span is 0.4500, the largest gradient norm 0.4518 and the corner parameters lie in [0.1800, 0.6900], so every analysed cell lay within the training limits.

S6.2. Case A: NICE optimisation, exact twin and exact checks

Case A is the $2 \times 2 \times 2$ block of Section 5.8, loaded by a traction load in y on the face $y =$ max opposite the clamp. The exact twin runs the same optimisation from the

same start, with the same settings, constraints and geometry regeneration, but with exact condensation (Table ST16). The NICE run was checked with the exact model at iterations 0, 12 and 23 (Table ST17b). The twin serves as a verification run and is not used as a cost baseline; the cost comparison of the exact and learned routes is that of Section 5.9.

Table ST17. Case A: NICE optimisation, exact twin and exact checks

ST17a. Iteration history

Iteration	$\widehat{C}$ (NICE)	C, exact twin	NICE vs twin (%)
0	24.59081	24.59356	−0.011
1	27.14662	27.14994	−0.012
2	30.16595	30.17025	−0.014
3	33.73640	33.74275	−0.019
4	37.85673	37.86557	−0.023
5	35.69282	35.70004	−0.020
6	33.80530	33.81157	−0.019
7	32.05341	32.05955	−0.019
8	30.48399	30.49000	−0.020
9	29.08392	29.08994	−0.021
10	27.85699	27.86145	−0.016
11	26.84866	26.85332	−0.017
12	26.00158	26.00632	−0.018
13	25.28700	25.29168	−0.018
14	24.78587	24.79256	−0.027
15	24.46873	24.47568	−0.028
16*	24.24430	24.25329	−0.037
17	24.14971	24.15703	−0.030
18	24.10947	24.11624	−0.028
19*	24.08748	24.11211	−0.102
20	24.10488	24.11155	−0.028
21	24.10448	24.11117	−0.028
22	24.10411	24.11081	−0.028
23	24.10377	—	—

* Design perturbed by the geometry-generation fallback (Table ST19a). NICE vs twin: $(\widehat{C} - C_{\text{twin}})/C_{\text{twin}}$ at the same iteration index. The designs coincide (to 4e-14) at iterations 0–4, where every free parameter moves by the move limit or to the lower bound while the volume bound is violated; there the column is the approximate compliance error of the same design. From iteration 5 the corner parameters differ, by at most 8.8e-04. Largest $|\bar{U}^T\rho|/\widehat{C}$ over the NICE run: 1.5e-08.

ST17b. Exact checks of the NICE run

Iteration	Exact C	$\widehat{C}$	Approximate compliance error (%)	Gradient error (%)	Cosine	Component error / max$\lvert g\rvert$: median / 95th percentile / max	Sign agreement	Exact solve: PCG iterations / recomputed residual
0	24.59356	24.59081	−0.0112	0.069	0.9999998	2.2e-04 / 5.1e-04 / 6.3e-04	1.000	178 / 9.1e-11
12	26.00630	26.00158	−0.0182	0.170	0.9999987	4.1e-04 / 1.2e-03 / 1.8e-03	1.000	244 / 9.0e-11
23	24.11050	24.10377	−0.0279	0.329	0.9999966	3.8e-04 / 2.8e-03 / 4.1e-03	1.000	262 / 9.9e-11

Over the 18 free vertex parameters. Approximate compliance error $(\widehat{C} - C)/C$; gradient error $\|\widetilde{\boldsymbol{s}}_g - \boldsymbol{s}_g\|/\|\boldsymbol{s}_g\|$; component error $|\widetilde{s}_{g,i} - s_{g,i}|/\max_j |s_{g,j}|$.

ST17c. Final designs and cost

	NICE run	Exact twin
Exact compliance of the final design	24.110504	24.110806
Final τ range; largest corner span; largest gradient norm	0.1800–0.6239; 0.4439; 0.4500	0.1800–0.6236; 0.4436; 0.4500
PCG iterations; recomputed residual	99–157; 6.2e-05–1.5e-04	178–262; 8.5e-11–9.9e-11
Time per iteration, mean (range) (s)	74 (62–120)	469 (455–534)
Mean phases (s)	geometry 20.8, cell preparation 10.1, lattice and $\mathbb{K}_{PP}$ assembly 0.1, preconditioner 5.9, PCG 31.6, sensitivities and volume gradient 5.5, MMA 0.006	—

Final designs: exact compliance of the NICE design relative to that of the twin's design −1.25e-05; corner parameters differ by at most 0.0051 (root mean square 0.0011). Iterations and first and last compliances of both runs: Table 6. Mean phases over all iterations; the geometry phase is zero at iteration 0.

S6.3. Plate supported on its cut and homogenisation design

The plate of Section 5.10 is cut by a plane that runs from the bottom-right corner to the top edge at two cells from the left end. Its eight cut cells have remaining volume fractions 0.917, 0.667, 0.333 and 0.083, two each. The layout is stored with its two in-plane axes interchanged, a cube-symmetry image of the plate, so that the cut normal lies at $\vartheta = 33.69°$, within the range $0 < \vartheta < \pi/4$ of the validation geometries (Section 5.1), rather than at its image, 56.31°. The network is not equivariant under the cube symmetries (Section 6.3). Apart from the DOFs of the clamped cut-plane elements, no DOF is fixed.

For comparison with a homogenisation-based graded design, the effective elasticity tensor $C^H(\tau)$ of the uncut cell with uniform corner parameter was computed by periodic homogenisation on the same discrete model ($n = 32$, Q2 elements, the stabilised stiffness K with its ghost penalty). Nodes on opposite faces of the cell are identified, and the fluctuation is periodic with one node fixed. Six unit macroscopic strains give $C^H_{ij} = u_i^T K u_j$ for the unit cell, and the material volume fraction $V^H(\tau)$ is the sum of the zeroth element moments. Cubic splines in τ interpolate C^H_{11}, C^H_{12}, C^H_{44} and V^H between the twelve thicknesses of Table ST18b. The macroscale model meshes the plate with Q1 hexahedra, six per cell and axis (4,464 elements, 5,719 nodes). At every quadrature point it interpolates the local parameter $\tau(x)$ trilinearly from the corners of its cell and evaluates $C^H(\tau(x))$ and $V^H(\tau(x))$. It integrates the elements intersected by the cut with 4^3 sub-points, the void part carrying $10^{-6}\, C^H(0.4)$. It applies the clamp on the plane of the cut, $u = 0$ on the section of the plane with the plate, by a penalty $\alpha \int u \cdot v \, dA$ with $\alpha = 10^6\, C^H_{11}(0.4)/h_M$ and $h_M = 1/6$. The penalty is integrated with a seven-point rule on the triangles of the section polygon of every intersected element. The load is a uniform traction of unit resultant on the loaded face. It was optimised with adjoint sensitivities and the same MMA settings, constraints, fixed vertices and volume fraction.

In iterations 0–3, while the volume bound is violated, the macroscale and NICE runs move every free parameter by the move limit or to the lower bound and analyse the same designs. There the macroscale compliance lies 27.0–31.8% below the NICE compliance, and along the rest of its path it lies 29–33% below it. At the uniform start, refining the macroscale mesh to 12 elements per cell and axis (35,136 elements, 39,949 nodes) raises the macroscale compliance from 55.192 to 56.088 (+1.6%), 25.8% instead of 27.0% below the exact compliance 75.599. Raising the penalty factor from 10^6 to 10^8 changes it by -8.7×10^{-6} (6 elements) and -3.7×10^{-6} (12 elements), relative. The optimisation used the six-element mesh. The fine-scale model fixes every DOF of the cut-plane elements of the cut cells (Table ST21). This support is at least as stiff as one acting on the cut surface alone; it lowers the exact compliance and therefore narrows the macroscale underestimation. For the graded homogenisation design, the macroscale volume model no longer equals the fine-scale material volume exactly (Table ST18c).

Table ST18. Plate supported on its cut: NICE optimisation and homogenisation design

ST18a. Runs

	NICE run	Homogenised model	Homogenisation design, NICE analysis
Start design	uniform 0.40	uniform 0.40 (macroscale)	final macroscale design
Largest compliance (iteration)	110.493 (4)	74.557 (4) (macroscale)	—
Final τ range	0.180–0.690	0.180–0.690	0.180–0.690
Largest corner span / gradient norm at the end	0.450 / 0.450	0.450 / 0.450	0.450 / 0.450

	NICE run	Homogenised model	Homogenisation design, NICE analysis
Time per iteration, mean (range) (s)	200 (155–270)	4.1 (macroscale, CPU)	—
Sum of iteration times (s)	4,802	95 (macroscale, CPU)	—
PCG iterations	73–122	—	127
Recomputed residual	3.5e-04–5.8e-04	—	3.9e-04
$\max\lvert\bar{U}^T\rho\rvert/\widehat{C}$	5.2e-08	—	5.4e-08

Every fine-scale value is a NICE value; exact checks in Table ST21. Iterations and first and last compliances: Table 6. Figure 15a,b draws the corner parameters in the layer $z = 0$; those in the layer $z = 1$ differ from them by at most 1.1e-03 (NICE) and 6.3e-13 (homogenisation design).

ST18b. Homogenised law of the uniform-thickness cell

τ	V^H	C^H_{11}	C^H_{12}	C^H_{44}
0.18	0.1027	0.03996	0.02806	0.01920
0.22	0.1256	0.04992	0.03432	0.02384
0.27	0.1541	0.06307	0.04212	0.02988
0.32	0.1827	0.07712	0.04989	0.03620
0.37	0.2113	0.09218	0.05765	0.04279
0.42	0.2399	0.10838	0.06541	0.04968
0.47	0.2685	0.12585	0.07323	0.05688
0.52	0.2971	0.14471	0.08117	0.06440
0.57	0.3258	0.16511	0.08929	0.07226
0.62	0.3545	0.18720	0.09768	0.08049
0.67	0.3832	0.21116	0.10644	0.08912
0.70	0.4004	0.22653	0.11193	0.09450

$E_Y = 1$, $\nu = 0.3$, unit cell of volume 1, Voigt notation with engineering shear strains; C^H_{11}, C^H_{12}, C^H_{44} are the entry values of the computed tensor (the macroscale model averages the three symmetric entries of each). Largest relative spreads over the twelve thicknesses: $C^H_{11}, C^H_{22}, C^H_{33}$ 3.1e-13, $C^H_{12}, C^H_{13}, C^H_{23}$ 6.1e-14, $C^H_{44}, C^H_{55}, C^H_{66}$ 1.4e-13; largest normal–shear or shear–shear coupling 7.5e-14 of C^H_{11}; largest relative equilibrium residual of the periodic fluctuations 2.2e-13.

ST18c. Homogenisation against the fine-scale NICE optimisation

Quantity	Macroscale model	NICE	Exact condensation
Compliance of the uniform design	55.192	75.591	75.599
Macroscale prediction error at the uniform design (%)	—	−26.99	−26.99

Quantity	Macroscale model	NICE	Exact condensation
Compliance of the homogenisation design	55.271	80.172	80.198
Homogenisation design vs NICE design (%)	—	+2.44	+2.44
Fine-scale V/V^*: NICE design / homogenisation design	—	1.00000 / 0.99821	—
Corner parameters, NICE vs homogenisation design: largest difference / RMS / correlation	—	0.262 / 0.057 / 0.946	—

Prediction error: $(C_{\mathrm{macro}} - C)/C$ at the uniform design $\tau = 0.40$. Corner differences and correlation over the 24×8 cell-corner parameters. The macroscale volume of the uniform design, 4.569075, agrees with the fine-scale material volume 4.569074 to 1.2e-07.

S6.4. Geometry-generation perturbations and discrete switches

Table ST19a lists the four applications of the geometry-generation fallback of Table ST16; a failure means that the geometry generator could not certify the material patches of an element (Appendix A.1). Table ST19b counts the cells whose discrete description changed between consecutive iterations. Each iteration evaluates the objective on a different discrete model, and the derivatives of Section 4.2 hold only within each model.

Table ST19. Geometry-generation fallback and discrete switches

ST19a. Applied perturbations

Case	Iteration	Failing cells	Applied ϵ	Perturbed vertices	Cells regenerated	Largest $\lvert\Delta\tau\rvert$
A, NICE	16	010 (uncut)	+1e-04	4 (of 18)	8	5.8e-05
A, NICE	19	010 (uncut)	+1e-03	4 (of 18)	8	5.8e-04
Plate	5	060 (cut, 0.917), 160 (cut, 0.083)	+1e-03	12 (of 64)	5	2.7e-04
Plate	14	000 (uncut)	+1e-04	4 (of 64)	4	3.6e-05

Failing cells by layout index (remaining volume fraction of cut cells): the cells whose generation failed for the design returned by MMA. The applied ϵ acts on the design returned by MMA; largest $|\Delta\tau|$: largest change of a corner parameter by the applied perturbation; no perturbed vertex was clipped to a bound. The exact twin and the analysis of the homogenisation design needed no fallback.

ST19b. Cells whose discrete description changed between consecutive iterations

Case	Active elements; ghost faces	Retained DOFs	Cut-plane-element nodes	Weakly connected nodes	Weak-region element stencils	Weak-region face stencils	Coarse-factor shift	Any of these
A, NICE (8 cells, 23 steps)	2 / 8 / 8	0 / 8 / 8	0 / 4 / 4	3 / 8 / 8	2 / 8 / 8	2 / 8 / 8	0 / 0 / 2	3 / 8 / 8
Plate (24 cells, 23 steps)	8 / 18 / 24	3 / 18 / 24	0 / 3 / 8	11 / 18 / 24	9 / 18 / 24	11 / 18 / 24	0 / 0 / 4	11 / 18 / 24

Minimum / median / maximum, over the steps between consecutive iterations, of the number of cells whose count changed. Counts were taken of active elements and ghost-penalty faces (identical counts), retained DOFs, nodes flagged by the network's binary node indicators as nodes of the cut-plane elements or as weakly connected nodes, element and face stencils selected for the weak-region layers (Appendix G.1), and the diagonal shift of the coarse factorisation (Appendix F.1). A change that leaves a count unchanged is not detected, so the numbers are lower bounds. The exact twin (8 cells, 22 steps), which recorded active elements and retained DOFs only, gives 2 / 8 / 8 and 0 / 8 / 8.

S6.5. Scale study and exact verification of the plate designs

Scale study. Plates were generated with 24, 51, 88 and 110 cells (Table ST20). They have the proportions of the plate of S6.3 (short side : long side 1 : 2, one cell thick), with its planar cut scaled with the plate, and all cut cells have the four remaining volume fractions of S6.3. The plates are clamped on the uncut long side and loaded on the opposite face by a traction load of unit resultant, acting in the plane along the long side. After the cut, this face is two cells wide in the 24-cell plate. The 24-cell plate is the plate of S6.3 with this clamp and load. Each run starts from the uniform $\tau = 0.40$ with $V^* = 0.8\,V(\boldsymbol{\tau}^0)$ and the settings of Table ST16, and was stopped after four analyses (three MMA updates). Degrees of freedom are those of the initial design: the cut finite-element model of all cells, with nodes on shared faces counted once, and the retained DOFs of the assembled lattice without the clamped face.

Table ST20. Scale study. Plates with the proportions and cut of the plate of S6.3, clamped on the uncut long side and loaded in plane on the opposite face, uniform start, four analyses; GPU memory budget for resident learned substructures 4 GiB (Supplementary Note S4.1). DOFs: degrees of freedom of the cut finite-element model / free retained DOFs of the assembled lattice (initial design). Start $\widehat{C}$: NICE compliance of the uniform start (first analysis). Time: mean over the analyses (range), with mean phase times, in s, geometry generation included. Residual: largest recomputed relative residual / largest $|\bar{U}^T\rho|/\widehat{C}$. CPU memory: peak resident memory of the main process, which holds the streamed state of the learned cells, per cell (total), GiB; the geometry generation runs in separate processes. GPU memory: largest memory in use on the device, sampled every 30 s with nvidia-smi, GiB; besides the resident learned cells it holds the assembled retained system: $\mathbb{K}_{PP}$ and its cuDSS factor in the preconditioner and the vectors of the conjugate gradients.

Cells / cut	DOFs: cut model / free retained	Design variables	Start $\widehat{C}$	Time per design iteration (s) and phases	PCG iterations	Residual / residual work	CPU memory per cell (total)	GPU memory in use
24 / 8	6.51 M / 0.388 M	64	94.34	242 (229–252): geometry 21, cell preparation 36, preconditioner 21, PCG 144, sensitivities 19	138–169	3.9e-04 / 2.3e-08	0.62 (15.0)	14.9
51 / 12	14.57 M / 0.780 M	128	89.12	547 (539–559): geometry 37, cell preparation 83, preconditioner 45, PCG 334, sensitivities 43	156–171	6.6e-04 / 3.9e-08	0.69 (35.2)	20.2
88 / 16	25.85 M / 1.305 M	212	86.75	962 (955–980): geometry 63, cell preparation 150, preconditioner 79, PCG 586, sensitivities 74	158–173	9.7e-04 / 6.9e-08	0.71 (62.8)	26.1

Cells / cut	DOFs: cut model / free retained	Design variables	Start $\widehat{C}$	Time per design iteration (s) and phases	PCG iterations	Residual / residual work	CPU memory per cell (total)	GPU memory in use
110 / 18	32.70 M / 1.618 M	262	85.38	1,164 (1,119–1,214): geometry 71, cell preparation 185, preconditioner 99, PCG 698, sensitivities 95	142–172	1.2e-03 / 7.3e-08	0.73 (79.9)	30.0

Exact checks at the first design iteration, with the metrics of Table ST21: 24 cells, $C = 94.353$, $\widehat{C} = 94.341$, approximate compliance error -0.0132%, gradient error 0.045%, cosine 0.99999993, component error median / 95th percentile / max 0.011 / 0.048 / 0.059%, exact sign in all 64 components; 51 cells, $C = 89.129$, $\widehat{C} = 89.119$, -0.0113%, 0.047%, 0.99999994, 0.009 / 0.034 / 0.063%, all 128 components. The exact reference of the 88- and 110-cell plates was not computed.

Table ST21. Exact checks of the plate designs. The uniform start, the final NICE design and the homogenisation design of S6.3, and two uniform designs at the volume bound V^* for comparison; the intermediate designs were not checked. Exact condensation of the 55 distinct cells with PARDISO's Schur-complement option, verified column-wise against interior solves; assembled solve, with every DOF of the cut-plane elements of the cut cells fixed, to a recursive relative residual of 10^{-10}. Approximate compliance error: $\widehat{C}/C - 1$. Gradient: vertex gradient with exact sensitivities (central moment differences, Eq. (H.3)) against the NICE sensitivity estimate, over the 64 free vertex parameters. Exact solves: 136 / 9.4e-11, 190 / 8.8e-11, 191 / 9.5e-11 conjugate-gradient iterations / recomputed residual, in the order of the rows.

Design	Exact C	$\widehat{C}$	Approximate compliance error (%)	Gradient error (%)	Cosine	Component error / max$\lvert g\rvert$ (%): median / 95th percentile / max	Sign agreement (64 variables)
NICE run, iteration 0 (start)	75.599	75.591	−0.0105	0.029	0.99999997	0.003 / 0.027 / 0.043	1.000
NICE run, iteration 23 (final)	78.287	78.264	−0.0296	0.301	0.99999652	0.057 / 0.273 / 0.315	1.000

Design	Exact C	$\widehat{C}$	Approximate compliance error (%)	Gradient error (%)	Cosine	Component error / max$\lvert g\rvert$ (%): median / 95th percentile / max	Sign agreement (64 variables)
Homogenisation design	80.198	80.172	−0.0317	0.320	0.99999596	0.052 / 0.322 / 0.335	1.000
Uniform design at V^*, 64 free parameters (loaded-face parameters 0.40)	115.357	115.335	−0.0191	0.064	0.99999995	—	1.000
Uniform design at V^*, all 74 parameters	113.279	113.259	−0.0179	0.055	0.99999995	—	1.000

Supplementary Note S7. Transfer to a second TPMS family: gyroid sheet cells

The construction of Sections 3 and 4 comprises the condensed energy with the transpose of the complete recovery operator, Propositions 1–4 and the correction $\mathcal{W}$. It uses the symmetry and positive semidefiniteness of the cell stiffness and the positive definiteness of its interior block, and it does not use the level-set function of Eq. (1). The trained network, in contrast, has seen Schwarz-P cells only (Sections 6.1 and 6.3). This note applies NICE to gyroid sheet cells, first with the network parameters of Table 2 unchanged (zero-shot) and then after a short continuation of training that includes a few gyroid cells. It is not part of the evidence of Section 5.

Cells. A gyroid cell replaces the level-set function of Eq. (1) by $\phi_G(x) = \sin 2\pi x_1 \cos 2\pi x_2 + \sin 2\pi x_2 \cos 2\pi x_3 + \sin 2\pi x_3 \cos 2\pi x_1$ and keeps the cell box, the trilinear corner parameters, the optional planar cut and the settings of Table 1 (background mesh $n = 32$, material, ghost penalty, retained DOFs and correction 8 / $Q_1(17)$ / 8). Every gyroid cell is the twin of one P cell and keeps the P cell's position, cut plane and cut-severity group (uncut or cut). Its corner parameters are mapped from the P values so that a uniform-thickness cell keeps its sheet volume fraction (for example 23.3% against 23.2% and 5.8% against 6.2% for two twins). The cells are generated by a version of the geometry stage that takes the level-set function as input; with the P function it reproduces the eight cells of the $2 \times 2 \times 2$ block of Section 5.8 cell by cell. When this version generates a lattice, it keeps the largest face-connected set of active elements of the whole lattice rather than of each cell. It also removes fragments of less than a quarter of an element that have no ghost-penalty support, and it repeats both steps until nothing changes. The retained DOFs of neighbouring cells then coincide on their shared faces except along the cell edges (unmatched DOFs are treated as in Section 2.4). The sixteen single cells are the twins of the validation cells fresh_val_2000 to fresh_val_2015 (geometry identifiers gval_000 to gval_1500 in the data archive). These validation cells include U1, U2, L1, M1, M2 and

H1–H3 of R1 and belong to the 20 checkpoint-selection geometries of Table ST01. The lattice is the twin of the $2 \times 2 \times 2$ block (glat222). No gyroid cell entered the training or checkpoint selection of any variant of Table 2 or of the two variants evaluated only in this supplement.

Propositions 1, 3 and 4 and the properties of Section 3.1 hold for these cells as for the P cells. They hold because they depend only on the stiffness matrix, the assembly and two properties of the recovery operator, and the network's displacement recovery reproduces the retained displacements and rigid-body motion by construction. Proposition 2 holds under its spectral condition, which was not checked on the gyroid cells, as for the cells of Sections 5.8–5.10.

Variants. *NICE, zero-shot*: NICE with the network parameters of Table 2, unchanged. *NICE, continued* (record identifier A3G_ft): NICE's parameters, trained for a further 8,000 steps. The training set comprises 96 P training cells and 18 gyroid twins of P training cells (cells with at most 420,000 DOFs), and the correction 8 / $Q_1(17)$ / 8 is inside the training loop as in Section 3.5. Its checkpoint was selected on the P validation list only (selection score 0.00339, against 0.00237 for NICE; Table ST01). The sixteen gyroid twins and the gyroid lattice therefore entered neither its training nor its selection. Both variants apply the correction 8 / $Q_1(17)$ / 8 at evaluation.

Single cells. Each gyroid twin was evaluated in the identity orientation with 64 validation test displacements per load class (Appendix G.2). The energy error of Eq. (7) was averaged over the test displacements of each cell and then over the sixteen cells with equal weights, as in Section 5.1 (Table ST22). Zero-shot, the mean error under traction loads is 4.48% (largest cell 25.6%), 66 times the 0.068% of NICE on the P twins of the same cells. Over the six load and support classes the ratio of the means is 56 to 234; under the imposed polynomial and multiscale displacements it is 14 and 7. The degradation is not confined to a few cells. In every cell, the error under each load and support class is 20 to 1,150 times that of its P twin, and under the imposed displacements 2 to 30 times. Under traction loads, the three gyroid cells with the largest errors are the twins of the three P cells with the largest NICE errors among the sixteen (fresh_val_2007, 2012 and 2015). The correction is the same as on the P cells. The accuracy of the network's interior displacements does not carry over, since it is tied to the family on which the network was trained.

After the continuation, the means under the six load and support classes fall by factors of 5.8 to 10.2. Under traction loads the mean falls from 4.48% to 0.74%, and the largest cell mean from 25.6% to 2.67%. Under the imposed polynomial and multiscale displacements the means fall by factors of 1.6 and 1.2. The means remain 6 to 23 times those of NICE on the P twins (11 times under traction loads). The reduction is uneven across cells: the twin of H2 (fresh_val_2010) now has the largest errors under nodal point loads and traction loads, 4.36% and 2.67% against 4.73% and 3.33% zero-shot. On the 80 P validation cells, the class means of the continued network are 1.1 to 1.7 times those of NICE in the same evaluation (0.026–0.072% against 0.015–0.065%).

Table ST22. Energy error (%) of the gyroid twins and of the P cells. Geometry-equal mean, with the largest geometry mean in parentheses, identity orientation. Gyroid twins: the sixteen twins of fresh_val_2000 to fresh_val_2015. P twins: these sixteen P validation cells. P validation: the 80 validation cells of Section 5.1 in one evaluation of both variants.

Load class	Gyroid twins, NICE, zero-shot	Gyroid twins, NICE, continued	P twins, NICE	P validation, NICE	P validation, NICE, continued
Traction loads (force_c)	4.48 (25.6)	0.74 (2.67)	0.068 (0.28)	0.065 (0.28)[a]	0.072 (0.30)[a]
Single-face traction loads (face_c)	4.30 (27.2)	0.60 (2.52)	0.031 (0.17)	0.029 (0.17)[a]	0.037 (0.21)[a]
Nodal point loads (force)	6.10 (14.1)	0.78 (4.36)	0.058 (0.18)	0.058 (0.33)	0.065 (0.31)
Single-face nodal point loads (face)	7.35 (15.2)	0.72 (1.59)	0.031 (0.28)	0.037 (0.72)	0.044 (0.47)
Spring supports (support)	5.78 (14.0)	0.60 (1.54)	0.053 (0.15)	0.055 (0.37)	0.064 (0.28)
Stiffness-scaled spring supports (support_k)	3.01 (17.2)	0.52 (2.42)	0.054 (0.22)[b]	0.053 (0.22)[a]	0.059 (0.24)[a]
Polynomial displacements (macro)	0.19 (0.89)	0.12 (0.58)	0.014 (0.075)	0.015 (0.12)	0.026 (0.17)
Multiscale displacements (grf)	0.16 (0.79)	0.13 (0.68)	0.024 (0.13)	0.025 (0.14)	0.037 (0.21)

[a] Evaluated in this run on the 20 checkpoint-selection geometries only (stiffness-scaled spring supports: 19); Table ST03 gives NICE on all 80 (75) geometries. [b] 15 twins; fresh_val_2010 has no stiffness-scaled spring-support test displacements.

Lattice. The gyroid twin of the $2 \times 2 \times 2$ block of Section 5.8 has eight cells, four of them cut, and every cell is learned; it has 160,629 free retained DOFs against 139,002 for the P block. It was solved as in Section 5.8, clamped on one face and loaded by the three face loads and three random loads, with the dense exact condensed matrices as reference (Table ST23). Zero-shot, the lattice compliance errors are 0.98–1.53% under the face loads (2.14% under the random loads), and the largest thickness-sensitivity error over the cells is 13.5% (10.6%), against 0.014% (0.069%) and 0.14% (0.45%) for NICE on the P block. With the continued network they are 0.23% (0.35%) and 1.84% (3.57%), and on the P block 0.019% (0.084%) and 0.25% (0.49%). With exact operators, the gyroid lattice needs 414 conjugate-gradient iterations against 183 for the P block; on the gyroid lattice, the learned operators add 20 (zero-shot) and 22 (continued) iterations.

Table ST23. Lattice compliance and sensitivity errors (%) of the P block and its gyroid twin. Maxima over the three face loads, and over the three random loads in parentheses; sensitivity error: largest relative error of the eight-component vector over

the eight cells. Iterations: preconditioned conjugate gradients (Supplementary Note S4.1) with the learned / the exact condensed stiffness matrices, to a recursive relative residual of 10^{-10}. The exact gyroid solution reaches a recomputed relative residual of 9.6×10^{-11}; for the learned gyroid solves, the recomputed residual stagnates at 2.7×10^{-4} (zero-shot) and 2.8×10^{-4} (continued), as for the P block in Section 5.8.

Lattice	Variant	Compliance error	Sensitivity error	Iterations
P block $(2 \times 2 \times 2)$	NICE	0.014 (0.069)	0.14 (0.45)	186 / 183
P block $(2 \times 2 \times 2)$	NICE, continued	0.019 (0.084)	0.25 (0.49)	187 / 183
Gyroid block $(2 \times 2 \times 2)$	NICE, zero-shot	1.53 (2.14)	13.5 (10.6)	434 / 414
Gyroid block $(2 \times 2 \times 2)$	NICE, continued	0.23 (0.35)	1.84 (3.57)	436 / 414

Reading. The construction carried over unchanged: the energy form, the transpose of the complete recovery operator, the correction and the assembly were applied to the gyroid cells without modification. The properties that do not depend on the network parameters hold for them as for the P cells. The trained network is specific to its family: zero-shot, the gyroid errors under loads and supports are 56 to 234 times those on the P twins in the mean, and the unchanged correction does not make up the difference. A continuation of 8,000 training steps with eighteen gyroid cells lowers them six- to tenfold, to 10 to 23 times the P level. It brings the gyroid lattice to 0.23% in compliance and 1.84% in sensitivity under the face loads, while the class means of the continued network on the P validation cells are 1.1 to 1.7 times those of NICE. Whether more gyroid data and training reach the P level was not tested. A new TPMS family therefore needs new training data (Section 6.3); the construction itself needs no change.

Records. Record identifiers in the data archive (files in `evidence/gcell/`): gval.json (gyroid twins: P twin, cut-severity group and corner parameters); gval_A3.json and gval_A3G.json (single gyroid cells, NICE zero-shot and continued); newval_A3G.json (80 P validation cells, NICE continued; NICE in the same evaluation: `evidence/newval_A3_2grid.json`); lat_hetero_g222.json and lat_hetero_g222_A3G.json (gyroid block, NICE zero-shot and continued); lat_hetero222_A3G.json (P block, NICE continued); g_vs_p_222.json (P and gyroid blocks, NICE).

Supplementary Note S8. Further continuations of the base network

Besides NICE, two further networks continue the training of the base network for 15,000 training steps. The Smoothing-trained variant applies eight smoothing steps without coarse-grid correction in every training step. The Uncorrected continuation is trained without correction. Table ST24 gives their training and evaluation settings in the format of Table 2 of the main text.

Table ST24. Training and evaluation settings of the two further continuations. Columns as in Table 2 of the main text.

Variant	Network parameters	Training geometries (set / used)	Correction in training	Correction at evaluation
Smoothing-trained	Base network continued for 15,000 training steps	591 / at most 153	8 smoothing steps	8 smoothing steps
Uncorrected continuation	Base network continued for 15,000 training steps	591 / at most 153	None	None

Both continuations use the network architecture of Section 3, with about 6×10^5 trainable parameters (Table ST15). The three continuations, NICE, the Smoothing-trained variant and the Uncorrected continuation, draw from the same set of 591 geometries. This set contains 304 of the 305 training geometries of the base network. The three continuations see the same geometries in the same order, at most 153 of the 591 in their 15,000 training steps (Table ST01).

S8.1. Single cells

Under traction loads, the means of NICE by cut-severity group are 64 to 102 times lower than those of the Uncorrected continuation. The group means of the Uncorrected continuation rise from 1.03% for uncut to 11.2% for heavily cut cells (Table ST03b). Over all 80 geometries, the mean energy error of the Uncorrected continuation under traction loads is 6.33%, and its largest single-geometry mean is 42%. Continuing the base network without correction therefore changes its mean only from 6.89% to 6.33%. The Smoothing-trained variant reaches a mean of 1.28%, and its largest single-geometry mean is 7.8% (Table ST03).

S8.2. Two-cell assemblies

The two further continuations were also evaluated in the two-cell assemblies of Section 5.6. The configurations, loads and error measures are those of Section 5.6. Tables ST08 and ST09 list the maxima for every variant and configuration evaluated.

The Uncorrected continuation was evaluated in eleven configurations. It exceeds the 3% sensitivity line in four of them, with sensitivity errors up to 11.4% (Table ST08). On M1 it also exceeds the 3% compliance line, with compliance errors up to 4.1%. The Smoothing-trained variant reduces these errors, but it still exceeds the 3% sensitivity line in the same four configurations, with errors of 3.15–4.43%. Smoothing without the coarse-grid correction leaves the slowly damped error in the low modes described in Section 5.4. This is consistent with the sensitivity errors that remain in U1 and M1. Base network + correction stays below both 3% lines, with a largest sensitivity error of 0.95% on U1/x. The correction therefore brings the assembled responses below the 3% lines.

Under the traction loads on the cut surface of the test cell, the Uncorrected continuation exceeds the 3% line in four of its seven configurations, with sensitivity errors up to 14.1% (Table ST09). Under the same loads, the errors of NICE are at most 0.10% in the compliance and 0.16% in the sensitivity.

Without the complete correction, an accurate compliance does not guarantee an accurate local sensitivity (Table ST25). Under the z traction load on the neighbour face of U1/x, the compliance error of the Smoothing-trained variant is 0.00109%, whereas its test-cell sensitivity error is 3.15%. The test cell carries 0.13% of the exact assembled energy under this load. NICE reduces both errors, and its test-cell sensitivity error under this load is 0.598%. On M1/x under the y traction load on the test-cell face, NICE gives errors of 0.0481% in the compliance and 0.145% in the sensitivity. The Uncorrected continuation gives 3.44% and 11.4% under the same load.

Table ST25. Compliance and test-cell sensitivity under individual face loads. T and N identify the loaded face of the test cell or of the neighbouring cell; x, y and z give the traction direction. The last column gives the fraction of the exact assembled energy carried by the test cell.

Test cell / configuration	Load	Uncorrected continuation: compliance / sensitivity (%)	Smoothing-trained: compliance / sensitivity (%)	NICE: compliance / sensitivity (%)	Energy fraction of the test cell
H1/x	T-x	1.06 / 2.47	0.144 / 0.636	0.0076 / 0.0133	0.643
U1/x	N-z	0.0023 / 4.89	0.00109 / 3.15	7.3×10^{-5} / 0.598	0.0013
M1/x	T-y	3.44 / 11.4	1.14 / 4.43	0.0481 / 0.145	0.311

Supplementary figures




Figure S01: **Verification of the CutFEM reference.** Single cells clamped on one cell face and loaded by unit traction loads on another face in the three Cartesian directions. In (a), (b) and (d), solid lines with filled markers give the compliance and dashed lines with open markers the thickness sensitivity, each as the largest relative change over the three loads. (a) Change against the finest background resolution computed for U1 ($n = 40$) and for M1 and M2 ($n = 48$); the reference used throughout has $n = 32$. (b) Change when the ghost-penalty coefficient is varied from the value 10^{-4} used throughout. (c) Filled: largest relative change of the sensitivity when the finite-difference step of the moment derivatives is varied from the value $h_c = 10^{-5}\tau_c$ used throughout, at most 2.6×10^{-5}% at $10^{-3}\tau_c$ and a hundredfold smaller at $10^{-4}\tau_c$; open: largest relative difference between central compliance differences and the sensitivity at the step used. (d) Refinement to $n = 64$ of H1, H2 and the validation cells with the largest NICE error (W1) and the thinnest walls (W3), the data of Table ST10; H2 has no $n = 56$ solution.




Figure S02: **Distributions of geometry-level energy errors.** Each point is one validation geometry's mean energy error in the identity orientation; horizontal bars are population medians. The classes with nodal point loads, spring supports, single-face nodal point loads, polynomial displacements, multiscale displacements, traction loads and single-face traction loads contain 80 geometries. The class with stiffness-scaled supports and the class with displacements imposed by a neighbouring cell contain 75, the same populations as Table ST03. The five variants of Table ST03 (Base network, Uncorrected continuation, Smoothing-trained, Base network + correction and NICE) use the markers and colours of the main-text figures and of Figure S04; Base network + correction applies the correction to the base network at deployment. Deterministic horizontal offsets separate overlapping observations. All panels share the logarithmic error axis.




Figure S03: **Sensitivity-error diagnostics.** (a) Paired mean energy and sensitivity errors for responses to traction loads and nodal point loads, using six cells of the base network and five of the Uncorrected continuation. (b) Linear-term norm fraction $\|D_1\|_F/(\|D_1\|_F + \|D_2\|_F)$ under traction loads, where $D_1 + D_2$ is the sensitivity-error matrix over all eight design components and evaluated test displacements. (c,d) Fractions of absolute elementwise sensitivity-error contributions and of element counts in four mutually exclusive material-volume-fraction groups for the base network under traction loads. Each error group sums absolute contributions over its elements, design components and test displacements before normalisation by the total. Filled markers identify the base network. In (a,b), open markers and hatched bars identify the Uncorrected continuation, which is shown for U1, U2, M1, H1 and M2 (Table ST05a).




Figure S04: **The other four variants follow the relations of Figure 11.** The counterpart of Figure 11 for (a–c) the base network, (d–f) the Uncorrected continuation, (g–i) the Smoothing-trained variant and (j–l) Base network + correction, which applies the correction at deployment. One point per load in the configurations evaluated for each variant (54, 87, 96 and 114 loads; Tables ST08 and ST09); filled markers denote face loads and open markers cut-surface loads. Top row: compliance error against β; lines denote equality. The ratio of compliance error to β lies between 0.80 and 0.98, 0.79 and 0.99, 0.92 and 0.99, and 0.96 and 1.006 for the four variants; the six ratios above 1 correspond to at most 1.3×10^{-9} of the compliance. Middle and bottom rows: compliance error and test-cell sensitivity error against the exact energy fraction w of the test cell; lines are least-squares fits in logarithmic coordinates, with the slope given in each panel. All panels share the error axis. The circled load in (a–c) is U1/x under the z traction load on the face of the neighbouring cell; its values are given in the note to Table ST08.