

[Dashboard](#) / [My courses](#) / [CS23333-OOPJ-2023](#) / [Lab-04-Classes and Objects](#) / [Lab-04-Logic Building](#)

<b>Status</b>	Finished
<b>Started</b>	Thursday, 3 October 2024, 8:11 PM
<b>Completed</b>	Thursday, 3 October 2024, 9:07 PM
<b>Duration</b>	56 mins 8 secs

## Question 1

Correct

Marked out of 5.00

Create a class Student with two private attributes, name and roll number. Create three objects by invoking different constructors available in the class Student.

Student()

Student(String name)

Student(String name, int rollno)

**Input:**

No input

**Output:**

No-arg constructor is invoked

1 arg constructor is invoked

2 arg constructor is invoked

Name =null , Roll no = 0

Name =Rajalakshmi , Roll no = 0

Name =Lakshmi , Roll no = 101

For example:

Test	Result
1	No-arg constructor is invoked 1 arg constructor is invoked 2 arg constructor is invoked Name =null , Roll no = 0 Name =Rajalakshmi , Roll no = 0 Name =Lakshmi , Roll no = 101

**Answer:** (penalty regime: 0 %)

```
1 public class Student{
2     private String name;
3     private int roll_number;
4     Student(){
5         System.out.println("No-arg constructor is invoked");
6     }
7     Student(String name){
8         System.out.println("1 arg constructor is invoked");
9     }
10    Student(String name,int roll_number){
11        System.out.println("2 arg constructor is invoked");
12    }
13    public static void main(String [] args){
14        Student s1 = new Student();
15        Student s2 = new Student("Rajalakshmi");
16        Student s3 = new Student("Lakshmi",101);
17        s2.name = "Rajalakshmi";
18        s3.name = "Lakshmi";
19        s3.roll_number = 101;
20        System.out.println("Name =" +s1.name + " , "+" Roll no = " +s1.roll_number);
21        System.out.println("Name =" +s2.name+" , Roll no = " +s2.roll_number);
22        System.out.println("Name =" +s3.name+" , Roll no = " +s3.roll_number);
23    }
24 }
25 }
```

	Test	Expected	Got	
✓	1	No-arg constructor is invoked 1 arg constructor is invoked 2 arg constructor is invoked Name =null , Roll no = 0 Name =Rajalakshmi , Roll no = 0 Name =Lakshmi , Roll no = 101	No-arg constructor is invoked 1 arg constructor is invoked 2 arg constructor is invoked Name =null , Roll no = 0 Name =Rajalakshmi , Roll no = 0 Name =Lakshmi , Roll no = 101	✓

Passed all tests! ✓

## Question 2

Correct

Marked out of 5.00

Create a class called "Circle" with a radius attribute. You can access and modify this attribute using getter and setter methods. Calculate the area and circumference of the circle.

Area of Circle =  $\pi r^2$

Circumference =  $2\pi r$

Input:

2

Output:

Area = 12.57

Circumference = 12.57

For example:

Test	Input	Result
1	4	Area = 50.27 Circumference = 25.13

Answer: (penalty regime: 0 %)

Reset answer

```

1 import java.io.*;
2 import java.util.Scanner;
3 class Circle
4 {
5     private double radius;
6     public Circle(double radius){
7         // set the instance variable radius
8         this.radius = radius;
9     }
10
11     public void setRadius(double radius){
12         // set the radius
13         this.radius = radius;
14     }
15
16     }
17     public double getRadius()    {
18         return radius;
19     }
20
21     }
22     public double calculateArea() { // complete the below statement
23         return Math.PI*radius*radius;
24     }
25     }
26     public double calculateCircumference()    {
27         // complete the statement
28         return 2*Math.PI*radius;
29     }
30 }
31 class prog{
32     public static void main(String[] args) {
33         int r;
34         Scanner sc= new Scanner(System.in);
35         r=sc.nextInt();
36         Circle c= new Circle(r);
37         System.out.println("Area = "+String.format("%.2f", c.calculateArea()));
38         // invoke the calculateCircumference method
39         System.out.println("Circumference = "+String.format("%.2f",c.calculateCircumference()));
40
41     }
42 }
43 }
44

```

	Test	Input	Expected	Got	
✓	1	4	Area = 50.27 Circumference = 25.13	Area = 50.27 Circumference = 25.13	✓
✓	2	6	Area = 113.10 Circumference = 37.70	Area = 113.10 Circumference = 37.70	✓
✓	3	2	Area = 12.57 Circumference = 12.57	Area = 12.57 Circumference = 12.57	✓

Passed all tests! ✓

## Question 3

Correct

Marked out of 5.00

Create a Class Mobile with the attributes listed below,

```
private String manufacturer;
private String operating_system;
public String color;
private int cost;
```

Define a Parameterized constructor to initialize the above instance variables.

Define getter and setter methods for the attributes above.

for example : setter method for manufacturer is

```
void setManufacturer(String manufacturer){
    this.manufacturer= manufacturer;
}
```

```
String getManufacturer(){
    return manufacturer;}

```

Display the object details by overriding the toString() method.

**For example:**

Test	Result
1	manufacturer = Redmi operating_system = Andriod color = Blue cost = 34000

**Answer:** (penalty regime: 0 %)

```
1 public class Mobile{
2     private String manufact;
3     private String os;
4     private String Colour;
5     private int cost;
6     public Mobile(String manufact,String os,String Colour,int cost){
7         this.manufact = manufact;
8         this.os = os;
9         this.Colour = Colour;
10        this.cost = cost;
11    }
12    public void setmanu(String manufact){
13        this.manufact = manufact;
14    }
15    public void setOs(String os){
16        this.os = os;
17    }
18    public void setColour(String Colour){
19        this.Colour = Colour;
20    }
21    public void setCost(int cost){
22        this.cost = cost;
23    }
24    public String getmanu(String manufact){
25        return manufact;
26    }
27    public String getOs(String os){
28        return os;
29    }
30    public String getColour(String Colour ){
31        return Colour;
32    }
33    public int getcost(int cost){
34        return cost;
35    }
36    public String toString(){
37        return "manufacturer = "+manufact +"\n"+
38            "operating_system = "+os +"\n"+
39            "color = "+Colour +"\n"+
```

```
40         "cost = "+cost;
41     }
42 }
43 public static void main(String[] args){
44     Mobile m = new Mobile("Redmi", "Andriod", "Blue", 34000);
45     System.out.println(m.toString());
46 }
47 }
48 }
```

	Test	Expected	Got	
✓	1	manufacturer = Redmi operating_system = Andriod color = Blue cost = 34000	manufacturer = Redmi operating_system = Andriod color = Blue cost = 34000	✓

Passed all tests! ✓

◀ Lab-04-MCQ

Jump to...

Number of Primes in a specified range ▶

⚡