

ARP using wireshark

The image shows a Wireshark packet capture analysis. The top toolbar includes standard network analysis tools like File, Edit, View, Go, Capture, Analyze, Statistics, Telephony, Wireless, Tools, Help, and a packet list pane. The main display area shows a list of captured packets with columns for No., Time, Source, Destination, Protocol, and Length. The packets are filtered by 'Apply a display filter... <Ctrl-/>'. The packet list shows 24 packets, with the first 24 packets being ARP requests and replies. The packet details pane shows the selected packet (No. 24) and its details: Ethernet II, Src: 3a:4a:20:03:f4:6b, Dst: LiteonTechno_7f:02:43, and Address Resolution Protocol (reply). The packet bytes pane shows the raw data of the selected packet, including the Ethernet II header and the ARP payload.

No.	Time	Source	Destination	Protocol	Length	Info
4	14.481319	LiteonTechno_7f:02:...	3a:4a:20:03:f4:6b	ARP	42	192.168.33.208 is at 70:08:94:7f:02:43
5	81.678906	3a:4a:20:03:f4:6b	LiteonTechno_7f:02:...	ARP	42	Who has 192.168.33.208? Tell 192.168.33.204
6	81.678935	LiteonTechno_7f:02:...	3a:4a:20:03:f4:6b	ARP	42	192.168.33.208 is at 70:08:94:7f:02:43
7	116.984133	3a:4a:20:03:f4:6b	LiteonTechno_7f:02:...	ARP	42	Who has 192.168.33.208? Tell 192.168.33.204
8	116.984175	LiteonTechno_7f:02:...	3a:4a:20:03:f4:6b	ARP	42	192.168.33.208 is at 70:08:94:7f:02:43
9	192.554814	3a:4a:20:03:f4:6b	LiteonTechno_7f:02:...	ARP	42	Who has 192.168.33.208? Tell 192.168.33.204
10	192.554850	LiteonTechno_7f:02:...	3a:4a:20:03:f4:6b	ARP	42	192.168.33.208 is at 70:08:94:7f:02:43
11	268.740656	3a:4a:20:03:f4:6b	LiteonTechno_7f:02:...	ARP	42	Who has 192.168.33.208? Tell 192.168.33.204
12	268.740703	LiteonTechno_7f:02:...	3a:4a:20:03:f4:6b	ARP	42	192.168.33.208 is at 70:08:94:7f:02:43
13	300.011655	LiteonTechno_7f:02:...	3a:4a:20:03:f4:6b	ARP	42	Who has 192.168.33.204? Tell 192.168.33.208
14	300.027055	3a:4a:20:03:f4:6b	LiteonTechno_7f:02:...	ARP	42	192.168.33.204 is at 3a:4a:20:03:f4:6b
15	368.999399	LiteonTechno_7f:02:...	3a:4a:20:03:f4:6b	ARP	42	Who has 192.168.33.204? Tell 192.168.33.208
16	369.992937	3a:4a:20:03:f4:6b	LiteonTechno_7f:02:...	ARP	42	192.168.33.204 is at 3a:4a:20:03:f4:6b
17	377.694537	3a:4a:20:03:f4:6b	LiteonTechno_7f:02:...	ARP	42	Who has 192.168.33.208? Tell 192.168.33.204
18	377.694574	LiteonTechno_7f:02:...	3a:4a:20:03:f4:6b	ARP	42	192.168.33.208 is at 70:08:94:7f:02:43
19	429.002811	LiteonTechno_7f:02:...	3a:4a:20:03:f4:6b	ARP	42	Who has 192.168.33.204? Tell 192.168.33.208
20	429.015648	3a:4a:20:03:f4:6b	LiteonTechno_7f:02:...	ARP	42	192.168.33.204 is at 3a:4a:20:03:f4:6b
21	429.045699	3a:4a:20:03:f4:6b	LiteonTechno_7f:02:...	ARP	42	Who has 192.168.33.208? Tell 192.168.33.204
22	429.045642	LiteonTechno_7f:02:...	3a:4a:20:03:f4:6b	ARP	42	192.168.33.208 is at 70:08:94:7f:02:43

Frame 2: 42 bytes on wire (336 bits), 42 bytes captured (336 bits) on interface \Device\NPF{3C45CF27-75...} 0000 70 08 94 7f 02 43 3a 4a 20 03 f4 6b 08 06 00 01 packet 1: 42 bytes on wire (336 bits), 42 bytes captured (336 bits) on interface \Device\NPF{3C45CF27-75...} 0010 08 00 06 04 00 02 3a 4a 20 03 f4 6b c0 a8 21 cc packet 2: 42 bytes on wire (336 bits), 42 bytes captured (336 bits) on interface \Device\NPF{3C45CF27-75...} 0020 70 08 94 7f 02 43 c0 a8 21 d0 packet 3: 42 bytes on wire (336 bits), 42 bytes captured (336 bits) on interface \Device\NPF{3C45CF27-75...}

Ethernet II, Src: 3a:4a:20:03:f4:6b, Dst: LiteonTechno_7f:02:43 (70:08:94:7f:02:43)

Address Resolution Protocol (reply)