

SMTP

Capturing from Wi-Fi

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

smtp

No.	Time	Source	Destination	Protocol	Length	Info
9	5.221833	4.213.25.242	192.168.253.75	TLSv1.2	225	Application Data
10	5.269721	192.168.253.75	4.213.25.242	TCP	54	49476 → 443 [ACK] Seq=102 Ack=172 Win=251 Len=0
11	6.546712	192.168.253.75	57.144.211.32	TLSv1.2	123	Application Data
12	6.860089	57.144.211.32	192.168.253.75	TCP	54	443 → 61082 [ACK] Seq=1 Ack=70 Win=352 Len=0
13	7.083788	57.144.211.32	192.168.253.75	TLSv1.2	125	Application Data
14	7.130873	192.168.253.75	57.144.211.32	TCP	54	61082 → 443 [ACK] Seq=70 Ack=72 Win=254 Len=0
15	7.180170	c2:16:ad:5c:c2:e1	Broadcast	ARP	42	Who has 192.168.253.190? Tell 192.168.253.250
16	7.607360	140.82.114.26	192.168.253.75	TLSv1.2	79	Application Data
17	7.608024	192.168.253.75	140.82.114.26	TLSv1.2	83	Application Data
18	8.190285	c2:16:ad:5c:c2:e1	Broadcast	ARP	42	Who has 192.168.253.190? Tell 192.168.253.250
19	8.194150	140.82.114.26	192.168.253.75	TCP	54	443 → 61449 [ACK] Seq=26 Ack=30 Win=75 Len=0
20	9.216037	c2:16:ad:5c:c2:e1	Broadcast	ARP	42	Who has 192.168.253.190? Tell 192.168.253.250
21	10.241872	c2:16:ad:5c:c2:e1	Broadcast	ARP	42	Who has 192.168.253.190? Tell 192.168.253.250

Frame 1: 42 bytes on wire (336 bits), 42 bytes captured (336 bits) on interface \Device\NPF{...} Ethernet II, Src: c2:16:ad:5c:c2:e1 (c2:16:ad:5c:c2:e1), Dst: Broadcast (ff:ff:ff:ff:ff:ff) Address Resolution Protocol (request)

0000

ff ff ff ff ff c2 16 ad 5c c2 e1 08 06 00 01

0010

08 00 06 04 00 01 c2 16 ad 5c c2 e1 c0 a8 fd fa

0020

00 00 00 00 00 00 c0 a8 fd c6

Wi-Fi: <live capture in progress>

Packets: 21

Profile: Default

30°C Sunny

Search

ENG US

08:51 06-08-2025