

Automated Packaging System Design

Sensor-Integrated Conveyor with PLC Control & Vision Inspection

Task 2 — Automation System Design Report | 2024

Course:	Robotics & Automation Engineering
Task:	Task 2 — Automation System Design
System Type:	Automated Packaging System (Conveyor-Based)
Control:	PLC (Programmable Logic Controller)
Sensors Used:	Vision, Weight, Proximity, Flow, Temperature

Abstract

This report presents a complete design for an automated packaging system using a sensor-integrated conveyor belt controlled by a PLC. The design covers system architecture, sensor selection, control logic, safety systems, and performance benchmarking against manual and semi-automated alternatives.

1. Introduction

Packaging is one of the most labour-intensive and error-prone stages in manufacturing and food production. Manual packaging lines typically achieve 150–220 units per hour per operator, with defect rates of 5–8%. This report designs a complete automated packaging system that uses a sensor-integrated conveyor belt, programmable logic control (PLC), machine vision, and automated filling, sealing, and labelling stations to raise throughput to 1,200 units per hour at a defect rate below 1%.

The system is designed for medium-scale food or pharmaceutical packaging, occupying a 12 m x 4 m floor footprint, and is scalable for larger operations. All sensor data feeds into a central PLC via a real-time fieldbus network (Profibus or EtherNet/IP), enabling closed-loop automated adjustments without human intervention in standard operation.

2. System Architecture Overview

The system is divided into seven sequential stations, each controlled by the central PLC with its own local sensors and actuators. A human operator monitors via an HMI (Human-Machine Interface) touchscreen and receives alerts for exceptions (jams, sensor faults, low materials). The diagram below illustrates the complete process flow from raw product input to palletised output.




Figure 1. Automated packaging system process flow diagram showing all seven stations and sensor integration points with PLC central control.

3. Component and Sensor Specifications

3.1 Conveyor Belt System

The conveyor uses a variable-speed AC motor (0.75 kW) with a belt speed range of 0.1–1.5 m/s, controlled by a variable frequency drive (VFD). Belt width is 400 mm with stainless steel side rails for food-grade compliance (FDA 21 CFR, EU 1935/2004).

3.2 Sensor Selection Table

Sensor	Type / Model	Station	Parameter Measured	Response Time
Proximity Sensor	Inductive — Omron E2E	Input Feed	Product presence / gap	< 1 ms
Vision Camera	Cognex In-Sight 7000	Inspection	Shape, defects, orientation	< 50 ms
Load Cell	HBM PW15 (500g range)	Fill Station	Fill weight accuracy	±0.5 g
Temperature Probe	PT100 RTD	Seal Station	Heat seal temp control	±0.3°C
Barcode Scanner	Datalogic Matrix 300N	Label Station	Label verification	< 20 ms
Photoelectric	Sick WL12L	All Stations	Belt jam / blockage detect	< 2 ms
Encoder	Heidenhain ROD 420	Conveyor	Belt speed & position	0.001 mm res.

Table 1. Sensor specifications for all stations. All sensors rated IP67 for washdown environments. Data communicated to PLC via Profibus DP protocol.

4. PLC Control System Design

4.1 Hardware

The central controller is a Siemens S7-1500 PLC with a 300 MHz CPU, 2 MB program memory, and 30 I/O modules accommodating the system's 84 digital inputs, 36 digital outputs, 18 analogue inputs, and 6 analogue outputs. Communication modules support Profibus DP (sensor/actuator network), Modbus TCP (SCADA integration), and OPC-UA (cloud data export for predictive maintenance).

4.2 Control Logic Summary

Station	Trigger Condition	Action	Fault Response
Input Feed	Proximity = ON, gap timer	Release next product	Stop belt, alert HMI
Vision Inspect	Product at camera position	Capture & analyse image	Flag defect, route to reject
Sort / Reject	Defect flag from vision	Actuate air jet diverter	Log to defect counter
Fill Station	Product at fill head	Dispense until target weight	Overfill -> reject & alarm
Seal Station	Filled product present	Apply heat seal at 160°C	Temp deviation -> pause line
Label Station	Sealed product detected	Print & apply label	Scan verify; misread -> reject
Output Pallet	Batch count reached	Signal palletiser robot	Full pallet -> conveyor hold

Table 2. PLC control logic for each station: trigger, action, and fault response. All fault states logged to SCADA with timestamp and station ID.

5. Safety System Design

The system is designed to IEC 62061 SIL 2 and ISO 13849 PLd safety standards. Safety-rated components operate on a dedicated safety PLC (Siemens ET 200SP FS) that monitors the main controller and can command a safe-stop independently.

- **Emergency Stop (E-Stop):** Category 0 hardwired stop at each station and all access points. Response time < 200 ms.
- **Light Curtains:** Sick deTec4 light curtains at all human-accessible zones. Entry detection triggers immediate belt stop.
- **Interlocked Guards:** All maintenance panels use RFID-coded safety interlocks. Guard open = machine de-energised.
- **Belt Jam Detection:** If encoder speed drops > 20% below setpoint for 500 ms, line stops and alarm triggers.
- **Overtemperature:** Seal station thermal cutout at 185°C (25°C above setpoint) to prevent fire risk.
- **Lockout/Tagout (LOTO):** Energy isolation points labelled with ISO 11161-compliant lockout stations.

6. Performance Analysis




Figure 2. Throughput (units/hour) and defect rate comparison across packaging approaches. This system achieves 1,200 units/hour at 0.9% defect rate.

6.1 Key Performance Indicators

KPI	Target	Achieved (Simulation)	Industry Benchmark
-----	--------	-----------------------	--------------------

Throughput	1,000+ units/hr	1,200 units/hr	800–1,500 units/hr
Defect Rate	< 1.5%	0.9%	1.0–2.0%
Downtime (planned)	< 2 hrs/day	1.4 hrs/day	2–3 hrs/day
OEE (Overall Equip. Eff.)	> 80%	86.5%	75–85%
Fill Weight Accuracy	±1 g	±0.6 g	±1–2 g
Seal Integrity Pass Rate	> 99%	99.4%	98–99%
Energy Consumption	< 8 kWh/1000 units	6.8 kWh/1000 units	8–12 kWh/1000

Table 3. System KPIs versus targets and industry benchmarks. Simulation data generated using Factory I/O and Siemens PLCSIM Advanced v5.0.

7. Economic Analysis & Return on Investment

Cost / Benefit Item	Manual Line (Annual)	Automated System (Annual)	Saving
Labour (4 operators @ \$30k)	\$120,000	\$25,000 (1 supervisor)	\$95,000
Defect / Waste Cost	\$38,000	\$8,000	\$30,000
Energy Cost	\$12,000	\$9,500	\$2,500
Maintenance	\$4,000	\$14,000 (contract)	-\$10,000
Total Annual Cost	\$174,000	\$56,500	\$117,500 saved
System Capital Cost	—	\$280,000	—
Payback Period	—	2.4 years	—

Table 4. Annual cost comparison and ROI calculation for the proposed automated system versus a comparable 4-operator manual packaging line.

8. Conclusion

The proposed sensor-integrated automated packaging system delivers a 6.7x improvement in throughput versus manual operation, reduces defects by 85%, and achieves a projected payback period of 2.4 years. The PLC control architecture with Profibus sensor networking, machine vision inspection, and closed-loop fill control represents a technically sound, standards-compliant design suitable for food-grade or pharmaceutical packaging environments.

The most critical design decisions are the sensor selection (vision camera quality directly determines defect catch rate) and the PLC safety architecture (IEC 62061 SIL 2 compliance is non-negotiable for a system operating near personnel). Both have been specified in detail in Sections 3 and 5 respectively. Future enhancements should include machine learning-based anomaly detection on the vision system and OPC-UA integration with cloud-based predictive

maintenance platforms.

References

- [1] Siemens AG (2024). *SIMATIC S7-1500 PLC System Manual*. Siemens Industry Online Support.
- [2] Cognex Corporation (2023). *In-Sight 7000 Series Vision System Datasheet*. cognex.com
- [3] Sick AG (2024). *deTec4 Safety Light Curtain Technical Data*. sick.com
- [4] IEC 62061:2021. *Safety of Machinery — Functional Safety of SCS*. International Electrotechnical Commission.
- [5] ISO 13849-1:2023. *Safety of Machinery — Safety-Related Parts of Control Systems*. ISO.
- [6] Groover, M.P. (2020). *Fundamentals of Modern Manufacturing*, 6th ed. Wiley.
- [7] HBM (2023). *PW15 Load Cell Datasheet*. hbm.com/en/products/load-cells
- [8] Omron (2024). *E2E Proximity Sensor Series Technical Guide*. ia.omron.com
- [9] EU Regulation 1935/2004. *Materials and Articles Intended to Contact Food*. European Parliament.
- [10] Factory I/O (2024). *Industrial Automation Simulation Platform v2.8*. realgames.co
- [11] Datalogic (2023). *Matrix 300N Industrial Barcode Reader Guide*. datalogic.com