

CH-231-A

Algorithms and Data Structures

ADS

Lecture 26

Dr. Kinga Lipskoch

Spring 2022


Deletion (Remember BST)

TREE-DELETE(T, z)

```

1  if  $z.left == \text{NIL}$ 
2    TRANSPLANT( $T, z, z.right$ )
3  elseif  $z.right == \text{NIL}$ 
4    TRANSPLANT( $T, z, z.left$ )
5  else  $y = \text{TREE-MINIMUM}(z.right)$ 
6    if  $y.p \neq z$ 
7      TRANSPLANT( $T, y, y.right$ )
8       $y.right = z.right$ 
9       $y.right.p = y$ 
10   TRANSPLANT( $T, z, y$ )
11    $y.left = z.left$ 
12    $y.left.p = y$ 

```



Deletion (RB) (1)

TREE-DELETE(T, z)

```
1  if  $z.left == \text{NIL}$ 
2      TRANSPLANT( $T, z, z.right$ )
3  elseif  $z.right == \text{NIL}$ 
4      TRANSPLANT( $T, z, z.left$ )
5  else  $y = \text{TREE-MINIMUM}(z.right)$ 
6      if  $y.p \neq z$ 
7          TRANSPLANT( $T, y, y.right$ )
8           $y.right = z.right$ 
9           $y.right.p = y$ 
10     TRANSPLANT( $T, z, y$ )
11      $z.left = z.left$ 
12      $z.left.p = y$ 
```

RB-DELETE(T, z)

```
1   $y = z$ 
2   $y\text{-original-color} = y.color$ 
3  if  $z.left == T.nil$ 
4       $x = z.right$ 
5      RB-TRANSPLANT( $T, z, z.right$ )
6  elseif  $z.right == T.nil$ 
7       $x = z.left$ 
8      RB-TRANSPLANT( $T, z, z.left$ )
9  else  $y = \text{TREE-MINIMUM}(z.right)$ 
10      $y\text{-original-color} = y.color$ 
11      $x = y.right$ 
12     if  $y.p == z$ 
13          $x.p = y$ 
14     else RB-TRANSPLANT( $T, y, y.right$ )
15          $y.right = z.right$ 
16          $y.right.p = y$ 
17     RB-TRANSPLANT( $T, z, y$ )
18      $z.left = z.left$ 
19      $z.left.p = y$ 
20      $y.color = z.color$ 
21     if  $y\text{-original-color} == \text{BLACK}$ 
22         RB-DELETE-FIXUP( $T, x$ )
```

Deletion (RB) (2)


- **node y**
 - either removed (a/b)
 - or moved in the tree (c/d)
 - y-original-color
- **node x**
 - the node that moves into y's original position
 - x.p points to y's original parent (since it moves into y's position, note special case in 12/13)

RB-DELETE(T, z)

```
1  y = z
2  y-original-color = y.color
3  if z.left == T.nil
4      x = z.right
5      RB-TRANSPLANT(T, z, z.right)
6  elseif z.right == T.nil
7      x = z.left
8      RB-TRANSPLANT(T, z, z.left)
9  else y = TREE-MINIMUM(z.right)
10     y-original-color = y.color
11     x = y.right
12     if y.p == z
13         x.p = y
14     else RB-TRANSPLANT(T, y, y.right)
15         y.right = z.right
16         y.right.p = y
17     RB-TRANSPLANT(T, z, y)
18     y.left = z.left
19     y.left.p = y
20     y.color = z.color
21 if y-original-color == BLACK
22     RB-DELETE-FIXUP(T, x)
```

Deletion (RB) (3)

- $y\text{-original-color} == \text{red}$




RB-DELETE(T, z)

```

1   $y = z$ 
2   $y\text{-original-color} = y.\text{color}$ 
3  if  $z.\text{left} == T.\text{nil}$ 
4       $x = z.\text{right}$ 
5      RB-TRANSPLANT( $T, z, z.\text{right}$ )
6  elseif  $z.\text{right} == T.\text{nil}$ 
7       $x = z.\text{left}$ 
8      RB-TRANSPLANT( $T, z, z.\text{left}$ )
9  else  $y = \text{TREE-MINIMUM}(z.\text{right})$ 
10      $y\text{-original-color} = y.\text{color}$ 
11      $x = y.\text{right}$ 
12     if  $y.p == z$ 
13          $x.p = y$ 
14     else RB-TRANSPLANT( $T, y, y.\text{right}$ )
15          $y.\text{right} = z.\text{right}$ 
16          $y.\text{right}.p = y$ 
17     RB-TRANSPLANT( $T, z, y$ )
18      $y.\text{left} = z.\text{left}$ 
19      $y.\text{left}.p = y$ 
20      $y.\text{color} = z.\text{color}$ 
21     if  $y\text{-original-color} == \text{BLACK}$ 
22         RB-DELETE-FIXUP( $T, x$ )
    
```

Deletion (RB) (4)

- $y\text{-original-color} == \text{red}$
 - no problem
- $y\text{-original-color} == \text{black}$
 - violations might occur (2,4,5)
 - main idea to fix
 - x gets an “**extra black**” & needs to get rid of it
 - 4 cases




RB-DELETE(T, z)

```

1   $y = z$ 
2   $y\text{-original-color} = y.\text{color}$ 
3  if  $z.\text{left} == T.\text{nil}$ 
4       $x = z.\text{right}$ 
5      RB-TRANSPLANT( $T, z, z.\text{right}$ )
6  elseif  $z.\text{right} == T.\text{nil}$ 
7       $x = z.\text{left}$ 
8      RB-TRANSPLANT( $T, z, z.\text{left}$ )
9  else  $y = \text{TREE-MINIMUM}(z.\text{right})$ 
10      $y\text{-original-color} = y.\text{color}$ 
11      $x = y.\text{right}$ 
12     if  $y.p == z$ 
13          $x.p = y$ 
14     else RB-TRANSPLANT( $T, y, y.\text{right}$ )
15          $y.\text{right} = z.\text{right}$ 
16          $y.\text{right}.p = y$ 
17     RB-TRANSPLANT( $T, z, y$ )
18      $y.\text{left} = z.\text{left}$ 
19      $y.\text{left}.p = y$ 
20      $y.\text{color} = z.\text{color}$ 
21     if  $y\text{-original-color} == \text{BLACK}$ 
22         RB-DELETE-FIXUP( $T, x$ )
  
```

Extra Black or Double Black Node




Child carries „extra black“ information
also called „double black“ node

Fixing Red-Black Tree Properties (1)

Case 1: x 's sibling w is red.

Transform to Case 2, 3, or 4 by left rotation and changing colors of nodes B and D .




x = node with extra black
 w = x 's sibling

```
if  $w.color == RED$   
     $w.color = BLACK$   
     $x.p.color = RED$   
    LEFT-ROTATE( $T, x.p$ )  
     $w = x.p.right$ 
```


Fixing Red-Black Tree Properties (2)

Case 2: x 's sibling w is black and the children of w are black.
Set color of w to red and propagate upwards.



x = node with extra black

w = x 's sibling

c = color of the node

if $w.left.color == \text{BLACK}$ and $w.right.color == \text{BLACK}$



$w.color = \text{RED}$

$x = x.p$

Fixing Red-Black Tree Properties (3)

Case 3: x 's sibling w is black and the left child of w is red, while the right child of w is black.


Transform to Case 4 by right rotation and changing colors of nodes C and D .



```
else if  $w.right.color == BLACK$ 
     $w.left.color = BLACK$ 
     $w.color = RED$ 
    RIGHT-ROTATE( $T, w$ )
     $w = x.p.right$ 
```

Fixing Red-Black Tree Properties (4)

Case 4: x 's sibling w is black and the right child of w is red. Perform a left-rotate and change colors of B , D , and E . Then, the loop terminates.



$w.color = x.p.color$
 $x.p.color = \text{BLACK}$
 $w.right.color = \text{BLACK}$
 $\text{LEFT-ROTATE}(T, x.p)$

Fixing Red-Black Tree Properties (5)

RB-DELETE-FIXUP(T, x)

```
1  while  $x \neq T.root$  and  $x.color == BLACK$ 
2      if  $x == x.p.left$ 
3           $w = x.p.right$ 
4          if  $w.color == RED$ 
5               $w.color = BLACK$  // case 1
6               $x.p.color = RED$  // case 1
7              LEFT-ROTATE( $T, x.p$ ) // case 1
8               $w = x.p.right$  // case 1
9          if  $w.left.color == BLACK$  and  $w.right.color == BLACK$ 
10              $w.color = RED$  // case 2
11              $x = x.p$  // case 2
12         else if  $w.right.color == BLACK$ 
13              $w.left.color = BLACK$  // case 3
14              $w.color = RED$  // case 3
15             RIGHT-ROTATE( $T, w$ ) // case 3
16              $w = x.p.right$  // case 3
17              $w.color = x.p.color$  // case 4
18              $x.p.color = BLACK$  // case 4
19              $w.right.color = BLACK$  // case 4
20             LEFT-ROTATE( $T, x.p$ ) // case 4
21          $x = T.root$  // case 4
22     else (same as then clause with "right" and "left" exchanged)
23      $x.color = BLACK$ 
```

Time complexity: $O(h) = O(\lg n)$

Conclusion

Modifying operations on red-black trees can be executed in $O(\lg n)$ time.