

IS2020 COMP 2540: Data Structures and Algorithms

Lecture 04: Queues

Dr. Kalyani Selvarajah
kalyanis@uwindsor.ca

School of Computer Science
University of Windsor
Windsor, Ontario, Canada

June 8, 2020




Outline

1. Background
2. Queues Definition and Properties
3. Queue ADT
4. Queue Array based Implementation



Background

- The **Queue ADT** stores arbitrary objects and is a linear data structure.
- Insertions and deletions follow the **first-in first-out (FIFO)** or **Last In Last Out (LILO)** scheme.
- Insertions are at the **rear** of the queue and removals are at the **front** of the queue.
- The insertion of an element into the queue called **enqueue** operation and the deletion of an element from the queue called a **dequeue** operation.



How does the Queue work?


- We need two special pointers Front and Rear. We add elements to the rear of the queue and remove elements from the front of the queue.

Empty Queue



How does the Queue work?

- We need two special pointers Front and Rear. We add elements to the rear of the queue and remove elements from the front of the queue.



Queue ADT

Main queue operations:

- **enqueue(object)**: inserts an element at the end of the queue
- **object dequeue()**: removes and returns the element at the front of the queue


Auxiliary queue operations:

- object **peek()**: returns the element at the front without removing it
- integer **size()**: returns the number of elements stored
- boolean **isEmpty()**: indicates whether no elements are stored


Queue ADT: Applications

- Direct applications
 - Waiting lists, bureaucracy
 - Access to shared resources (e.g., printer)
 - Multiprogramming
- Indirect applications
 - Auxiliary data structure for algorithms
 - Component of other data structures


Queue ADT: Array Based Implementation




Queue ADT: Array Based Implementation




Queue ADT: Array Based Implementation



Queue ADT: Array Based Implementation




Queue ADT: Array Based Implementation




Queue ADT: Array Based Implementation


- Shifting the elements has a time complexity of $O(n)$
- Moving the front and end indices give a time complexity of $O(1)$




Queue ADT: Array Based Implementation



Queue ADT: Array Based Implementation




Queue ADT: Array Based Implementation



Queue ADT: Array Based Implementation

- Using simple array to implement a queue data structure is **inefficient**.
- It is better to use a **circular array** (we move the front and the rear indices and not shifting the elements)

Queue ADT: Array Based Implementation



Queue ADT: Circular Array

```
public class QueueADT {  
  
    int front, rear, size;  
    int capacity;  
    int[] myArray;  
  
    public QueueADT(int capacity)  
    {  
        this.capacity = capacity;  
        this.front = -1;  
        this.rear = -1;  
        myArray = new int[capacity];  
        this.size=0;  
    }  
}
```


Queue ADT: isFull()

Solution 1:

```
public boolean isFull()
{
    return (size == capacity);
}
```

Solution 2:

```
public boolean isFull()
{
    return ((rear+1) % capacity) == front;
}
```




Queue ADT: isEmpty()

Solution 1:

```
public boolean isEmpty()  
{  
    return (size == 0);  
}
```

Solution 2:

```
public boolean isEmpty()  
{  
    return (front == rear);  
}
```




Queue ADT: Insertion (Enqueue)

```
public void enqueue(int data)
{
    if (isFull()) {
        System.out.println("Queue is Full.");
        return;
    }
    else{
        if (isEmpty()) {
            front = 0;
        }
        rear=(rear+1)%capacity;
        myArray[rear]=data;
        size++;
    }
}
```

Circular Array


Queue ADT: Insertion (Enqueue)

```
public void enqueue(int data)
{
    if (isFull()) {
        System.out.println("Queue is Full.");
        return;
    }
    else{
        if (isEmpty()) {
            front = 0;
        }
        rear=(rear+1)%capacity;
        myArray[rear]=data;
        size++;
    }
}
```



Queue ADT: Deletion (Dequeue)

```
public void dequeue()
{
    if(isEmpty())
    {
        System.out.println("Queue is Empty!");
    }
    else{
        if(front==rear) {
            front = rear = -1;
        }
        front = (front + 1)%capacity;
        size--;
    }
}
```



Queue ADT: Peek()

```
public int peek()
{
    if (isEmpty())
        return -1;
    else
        return myArray[front];
}
```

Run-Time Complexity

- The run time complexity of the Queue operations with array-based implementation are:

Operation	Run-Time Complexity
Add an Element	$O(1)$
Remove an Element	$O(1)$
Queue Size	$O(1)$
Is Empty Queue	$O(1)$
Is Full Queue	$O(1)$
Delete Queue queue	$O(1)$

In class assessment

- Write an algorithm to reverse a queue of n elements using only the queue ADT methods?

Self assessment

- Explain how could you implement a FIFO (queue) using linked list?
- Explain how could you implement a FIFO (queue) using stacks?