Flaship

Integration API Documentation

Developer Integration Guide

Generated for **BBG Fashion Clothing Store**

Generated on October 25, 2026

`https://partners.flaship.pk/api/integration`

Authenticate every request with your per-business X-API-KEY. This guide lists all Integration API endpoints, request fields, and sample responses.

Contents

1. COURIERS, RATES & CITIES

GET Couriers, rates & cities (catalog) /catalog/

GET Normalized operational cities /cities/

GET System statuses /statuses/

2. LOCATIONS & RATES

GET List pickup locations /pickups/

POST Create pickup location /pickups/

GET Rate cards /rate-cards/

3. CREATE SHIPMENTS

POST Create booking /bookings/

POST Bulk booking /bookings/bulk/

4. MANAGE ORDERS

GET List orders /orders/

GET Order detail /orders/{tracking_number}/

GET Track order /orders/{tracking_number}/tracking/

POST Cancel order /orders/{tracking_number}/cancel/

5. PAYMENT SETTLEMENTS

GET List payment settlements /payments/

GET Payment settlement detail /payments/{tracking_number}/

POST Bulk payment settlements by CNs /payments/bulk/

6. SHIPPER ADVICE

GET List pending advice /advice/pending/

GET List advice history /advice/history/

GET Check advice eligibility /advice/check/

POST Submit shipper advice /advice/

7. LOADSHEETS & LABELS

GET Loadsheet eligible orders /loadsheets/eligible/

POST	**Generate loadsheet**	`/loadsheets/`
GET	**Download print pack PDF**	`/print-pack/download/`
GET	**Download labels PDF**	`/labels/download/`
POST	**Generate labels**	`/labels/`

1. Couriers, rates & cities

GET Couriers, rates & cities (catalog)

Fetch pickup locations, assigned courier companies, available rate-card service types, and operational cities. Call this before creating bookings.

```
GET https://partners.flaship.pk/api/integration/catalog/
```

- Your business is selected from the X-API-KEY header.
- Use courier codes and city names from this response when creating bookings.

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
pickups	array	See sample response (`pickups`)
couriers	array	See sample response (`couriers`)
rate_cards	object	See sample response (`rate_cards`)
operational_cities	object	See sample response (`operational_cities`)
service_types	array	See sample response (`service_types`)

Sample response


```
{
  "success": true,
  "pickups": [
    {
      "id": 10,
      "is_default": true,
      "name": "Warehouse A",
      "phone_primary": "03001234567",
      "phone_secondary": null,
      "address": "123 Main Street, Block A",
      "city": "Karachi",
      "courier_refs": [
        {
          "courier_company_id": 1,
          "courier_code": "tcs",
          "courier_name": "TCS",
          "external_ref": ""
        }
      ]
    }
  ],
  "couriers": [
    {
      "code": "tcs",
      "name": "TCS",
      "display_name": "TCS"
    },
    {
      "code": "leopard",
      "name": "Leopard",
      "display_name": "Leopard"
    }
  ],
  "rate_cards": {
    "tcs": [
      "overnight",
      "overland"
```

```
    ],
    "leopard": [
      "overnight",
      "overland",
      "detain"
    ]
  },
  "operational_cities": {
    "tcs": [
      "Karachi",
      "Lahore",
      "Islamabad"
    ],
    "leopard": [
      "Karachi",
      "Lahore",
      "Islamabad"
    ]
  },
  "service_types": [
    "overnight",
    "detain",
    "overland"
  ]
}
```

GET Normalized operational cities

Canonical city spellings with assigned couriers that serve each city. Use city.name as consignee_city when booking.

```
GET https://partners.flaship.pk/api/integration/cities/
```

- Only cities mapped for couriers assigned to this merchant account are returned.
- Prefer city.name (canonical Snap spelling) in booking payloads.

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Query parameters

Name	Type	Required	Description
q	string	No	Optional case-insensitive filter on city name

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
count	number	See sample response (`count`)
cities	array	See sample response (`cities`)

Sample response


```
{
  "success": true,
  "count": 2,
  "cities": [
    {
      "id": 12,
      "name": "Karachi",
      "normalized_name": "karachi",
      "couriers": [
        {
          "code": "leopard",
          "name": "Leopard",
          "courier_city_name": "Karachi",
          "terminal_code": "KHI"
        },
        {
          "code": "tcs",
          "name": "TCS",
          "courier_city_name": "KHI",
          "terminal_code": "KHI"
        }
      ]
    },
    {
      "id": 44,
      "name": "Lahore",
      "normalized_name": "lahore",
      "couriers": [
        {
          "code": "leopard",
          "name": "Leopard",
          "courier_city_name": "Lahore",
          "terminal_code": "LHE"
        }
      ]
    }
  ]
}
```

GET System statuses

Order status codes, service types, and shipper-advice status values supported by the Integration API.

```
GET https://partners.flaship.pk/api/integration/statuses/
```

- Use order_statuses when filtering list orders.
- Use advice_statuses when submitting shipper advice.

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
order_statuses	array	See sample response (`order_statuses`)
service_types	array	See sample response (`service_types`)
advice_statuses	array	See sample response (`advice_statuses`)

Sample response


```
{
  "success": true,
  "order_statuses": [
    "BOOKED",
    "IN_TRANSIT",
    "OUT_FOR_DELIVERY",
    "DELIVERED",
    "CANCELLED",
    "DELETED",
    "RETURN_RECEIVED",
    "SHIPPER_ADVISE",
    "RETURN_IN_TRANSIT"
  ],
  "service_types": [
    "overnight",
    "detain",
    "overland"
  ],
  "advice_statuses": [
    "RETURN",
    "REATTEMPT",
    "HOLD"
  ]
}
```

2. Locations & rates

GET List pickup locations

List active pickup locations for the authenticated business.

```
GET https://partners.flaship.pk/api/integration/pickups/
```

- Use pickup id as pickup_id when creating bookings.

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
pickups	array	See sample response (`pickups`)

Sample response


```
{
  "success": true,
  "pickups": [
    {
      "id": 10,
      "is_default": true,
      "name": "Warehouse A",
      "phone_primary": "03001234567",
      "phone_secondary": null,
      "address": "123 Main Street, Block A",
      "city": "Karachi",
      "courier_refs": [
        {
          "courier_company_id": 1,
          "courier_code": "tcs",
          "courier_name": "TCS",
          "external_ref": ""
        }
      ]
    }
  ]
}
```

POST Create pickup location

Create a pickup location and sync courier external refs where possible.

```
POST https://partners.flaship.pk/api/integration/pickups/
```

- City should match a normalized city name from the catalog response.

Request headers

Name	Type	Required	Description
`X-API-KEY`	string	Yes	Per-business Integration API token from My Business → API key access.
`Content-Type`	string	Yes	application/json

Request body

Name	Type	Required	Description
`name`	string	Yes	Pickup / shipper name
`phone_primary`	string	Yes	Primary Pakistan mobile (03XXXXXXXXX)
`phone_secondary`	string	No	Optional secondary phone
`address`	string	Yes	Full pickup address
`city`	string	Yes	City name (use catalog / cities)

Response fields

Name	Type	Description
`success`	boolean	See sample response (`success`)
`pickup`	object	See sample response (`pickup`)
`sync_results`	array	See sample response (`sync_results`)

Sample request

```
{
  "name": "Warehouse A",
  "phone_primary": "03001234567",
  "phone_secondary": "",
  "address": "123 Main Street, Block A",
  "city": "Karachi"
}
```

Sample response

```
{
  "success": true,
  "pickup": {
    "id": 11,
    "is_default": false,
    "name": "Warehouse A",
    "phone_primary": "03001234567",
    "phone_secondary": null,
    "address": "123 Main Street, Block A",
    "city": "Karachi",
    "courier_refs": [
      {
        "courier_company_id": 1,
        "courier_code": "tcs",
        "courier_name": "TCS",
        "external_ref": ""
      }
    ]
  },
```

```
  "sync_results": []
}
```

GET Rate cards

Available service types / rate bands for couriers assigned to your account.

```
GET https://partners.flaship.pk/api/integration/rate-cards/
```

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
couriers	array	See sample response (`couriers`)

Sample response

```
{
  "success": true,
  "couriers": [
    {
      "courier_code": "tcs",
      "courier_name": "TCS",
      "rate_cards": [
        {
          "service_type": "overnight",
          "weight_from_kg": "0.000",
          "weight_to_kg": "0.500",
          "charges": "150.00",
          "additional_charges": "0.00",
          "fuel_charges_percent": "0.00"
        }
      ]
    }
  ]
}
```

3. Create shipments

POST Create booking

Book a single shipment. Business is taken from the API key.

```
POST https://partners.flaship.pk/api/integration/bookings/
```

- piece_tracking lists each physical piece (index/total) with its CN.
- Multi-piece CNs may also fill sub_tracking_numbers.

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.
Content-Type	string	Yes	application/json

Request body

Name	Type	Required	Description
pickup_id	integer	Yes	Pickup location id from /pickups/ or /catalog/
courier_code	string	Yes	Courier code (e.g. tcs, leopard, mnp, trax)
service_type	string	Yes	overnight | detain | overland
product_name	string	Yes	Product description
net_weight	string	Yes	Weight in KG
pieces	integer	No	Physical parcels on this CN (default 1)
quantity	integer	No	Product units inside the shipment (optional)
cod_amount	string	Yes	COD amount (0 for prepaid)
consignee_name	string	Yes	Recipient name
consignee_phone_primary	string	Yes	Primary recipient phone (PK mobile)
consignee_phone_secondary	string	No	Optional secondary phone
consignee_address	string	Yes	Delivery address
consignee_city	string	Yes	Delivery city (use a name from operational_cities)
special_instruction	string	No	Optional handling notes
external_ref_no	string	No	Your order / marketplace reference

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
id	number	See sample response (`id`)
tracking_number	string	See sample response (`tracking_number`)
sub_tracking_numbers	array	See sample response (`sub_tracking_numbers`)
piece_tracking	array	See sample response (`piece_tracking`)
courier_code	string	See sample response (`courier_code`)
status	string	See sample response (`status`)
external_ref_no	string	See sample response (`external_ref_no`)
courier_label_url	null	See sample response (`courier_label_url`)

Sample request

```
{
  "pickup_id": 10,
  "courier_code": "tcs",
  "service_type": "overnight",
  "product_name": "Electronics - Mobile Phone",
  "net_weight": "0.500",
  "pieces": 1,
  "cod_amount": "2500.00",
  "consignee_name": "John Doe",
  "consignee_phone_primary": "03001234567",
  "consignee_phone_secondary": "",
  "consignee_address": "123 Main Street, Block A",
  "consignee_city": "Karachi",
  "special_instruction": "Handle with care",
  "external_ref_no": "WC-1001"
}
```


Sample response


```
{
  "success": true,
  "id": 1119864,
  "tracking_number": "173018378432",
  "sub_tracking_numbers": [],
  "piece_tracking": [
    {
      "is_sub": false,
      "piece_index": 1,
      "piece_total": 1,
      "tracking_number": "173018378432"
    }
  ],
  "courier_code": "tcs",
  "status": "BOOKED",
  "external_ref_no": "WC-1001",
  "courier_label_url": null
}
```

POST Bulk booking

Create multiple bookings with a shared courier and pickup. JSON body uses a rows array (not CSV).

```
POST https://partners.flaship.pk/api/integration/bookings/bulk/
```

- Response uses summary + results[].ok (not a flat success list).
- Row quantity is not accepted on bulk — use pieces for parcel count.

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.
Content-Type	string	Yes	application/json

Request body

Name	Type	Required	Description
pickup_id	integer	Yes	Shared pickup location id
courier_code	string	Yes	Shared courier code
default_service_type	string	No	Default service type for rows that omit service_type
rows	array	Yes	Array of booking row objects (product/consignee fields; optional pieces, service_type, special_instruction, external_ref_no)

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
summary	object	See sample response (`summary`)
results	array	See sample response (`results`)

Sample request

```
{
  "pickup_id": 10,
  "courier_code": "tcs",
  "default_service_type": "overnight",
  "rows": [
    {
      "product_name": "Item A",
      "net_weight": "0.500",
      "pieces": 1,
      "cod_amount": "1000.00",
      "consignee_name": "Jane Doe",
      "consignee_phone_primary": "03001234567",
      "consignee_address": "Street 1",
      "consignee_city": "Lahore",
      "external_ref_no": "WC-1002"
    }
  ]
}
```

Sample response

```
{
  "success": true,
  "summary": {
    "total": 1,
    "booked": 1,
    "failed": 0
  },
  "results": [
    {
      "row_number": 1,
```

```
      "ok": true,
      "id": 1119864,
      "tracking_number": "173018378432",
      "courier_code": "tcs",
      "status": "BOOKED",
      "external_ref_no": "WC-1002",
      "error": null,
      "field_errors": null,
      "consignee_name": "Jane Doe",
      "consignee_phone_primary": "03001234567",
      "consignee_city": "Lahore"
    }
  ]
}
```

4. Manage orders

GET List orders

Paginated list of shipments. Filters: search, status, courier_code, start_date, end_date, page, page_size.

```
GET https://partners.flaship.pk/api/integration/orders/
```

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Query parameters

Name	Type	Required	Description
page	integer	No	Page number (default 1)
page_size	integer	No	Page size (default 20, max 100)
status	string	No	Order status code from /statuses/
courier_code	string	No	Filter by courier code (alias: courier)
search	string	No	Tracking / phone / name search
start_date	string	No	YYYY-MM-DD
end_date	string	No	YYYY-MM-DD

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
count	number	See sample response (`count`)
page	number	See sample response (`page`)
page_size	number	See sample response (`page_size`)
results	array	See sample response (`results`)

Sample response


```
{
  "success": true,
  "count": 1,
  "page": 1,
  "page_size": 20,
  "results": [
    {
      "id": 1119864,
      "tracking_number": "173018378432",
      "status": "BOOKED",
      "courier_code": "tcs",
      "consignee_name": "John Doe",
      "consignee_phone": "03001234567",
      "consignee_city": "Karachi",
      "cod_amount": "2500.00",
      "external_ref_no": "WC-1001",
      "created_at": "2026-08-15T10:00:00Z"
    }
  ]
}
```

GET Order detail

Retrieve a single order by tracking number (CN).

```
GET https://partners.flaship.pk/api/integration/orders/{tracking_number}/
```

- Replace {tracking_number} in the path — Consignment / tracking number.

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
order	object	See sample response (`order`)

Sample response


```
{
  "success": true,
  "order": {
    "id": 1119864,
    "tracking_number": "173018378432",
    "status": "IN_TRANSIT",
    "courier_code": "tcs",
    "consignee_name": "John Doe",
    "consignee_phone": "03001234567",
    "consignee_city": "Karachi",
    "cod_amount": "2500.00",
    "external_ref_no": "WC-1001",
    "created_at": "2026-08-15T10:00:00Z"
  }
}
```

GET Track order

Live tracking history and current status for a CN.

```
GET https://partners.flaship.pk/api/integration/orders/{tracking_number}/tracking/
```

- Replace {tracking_number} in the path — Consignment / tracking number.
- tracking is a list of {status, time} events.
- Every event time is normalized to YYYY-MM-DD HH:MM:SS (Asia/Karachi), regardless of courier.

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
tracking_number	string	See sample response (`tracking_number`)
status	string	See sample response (`status`)
live_courier_status	string	See sample response (`live_courier_status`)
tracking	array	See sample response (`tracking`)
message	null	See sample response (`message`)

Sample response


```
{
  "success": true,
  "tracking_number": "173018378432",
  "status": "IN_TRANSIT",
  "live_courier_status": "In Transit",
  "tracking": [
    {
      "status": "BOOKED",
      "time": "2026-08-15 15:00:00"
    },
    {
      "status": "IN_TRANSIT",
      "time": "2026-08-15 19:30:00"
    }
  ],
  "message": null
}
```

POST Cancel order

Cancel a shipment when the courier still allows cancellation.

```
POST https://partners.flaship.pk/api/integration/orders/{tracking_number}/cancel/
```

- Replace {tracking_number} in the path — Consignment / tracking number.

Request headers

Name	Type	Required	Description
`X-API-KEY`	string	Yes	Per-business Integration API token from My Business → API key access.
`Content-Type`	string	Yes	application/json

Response fields

Name	Type	Description
`success`	boolean	See sample response (`success`)
`tracking_number`	string	See sample response (`tracking_number`)
`status`	string	See sample response (`status`)
`message`	string	See sample response (`message`)

Sample request

```
{}
```

Sample response

```
{
  "success": true,
  "tracking_number": "173018378432",
  "status": "CANCELLED",
  "message": "Order cancelled successfully."
}
```

5. Payment settlements

GET List payment settlements

Paginated COD payment settlement rows. Includes arrival weight, total charges (DC+SC+OSA + 2% IT + 2% WHT on Delivered), settlement date, and Paid/Unpaid status.

```
GET https://partners.flaship.pk/api/integration/payments/
```

- On Delivered orders: income_tax and withholding_tax are each 2% of COD and included in total_charges.
- core_charges is DC+SC+OSA only.
- Each settlement row includes cheque_no and service_invoice_id when available.

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Query parameters

Name	Type	Required	Description
settlement_status	string	No	paid | unpaid (alias: status)
search	string	No	Tracking number contains
start_date	string	No	YYYY-MM-DD
end_date	string	No	YYYY-MM-DD
page	integer	No	Page number (default 1)
page_size	integer	No	Page size (default 20, max 100)

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
count	number	See sample response (`count`)
page	number	See sample response (`page`)
page_size	number	See sample response (`page_size`)
results	array	See sample response (`results`)

Sample response


```
{
  "success": true,
  "count": 1,
  "page": 1,
  "page_size": 20,
  "results": [
    {
      "tracking_number": "173018378432",
      "arrival_weight": "1.3",
      "total_charges": "350.00",
      "core_charges": "250.00",
      "settlement_date": "2026-09-20",
      "settlement_status": "Paid",
      "cheque_no": "FTECH-88",
      "service_invoice_id": "SI-88",
      "payment_invoice_id": "PI-88",
      "cod_amount": "2500.00",
      "line_net": "2150.00",
      "paid_amount": "2150.00",
      "shipment_status": "DELIVERED",
      "finance_status": "PAID",
      "external_ref_no": "WC-1001",
      "courier_code": "tcs",
```

```
      "delivery_charges": "150.00",
      "service_charges": "50.00",
      "osa_charges": "50.00",
      "income_tax": "50.00",
      "withholding_tax": "50.00"
    }
  ]
}
```


GET Payment settlement detail

Settlement detail for one CN wrapped in a payment object.

```
GET https://partners.flaship.pk/api/integration/payments/{tracking_number}/
```

- Replace {tracking_number} in the path — Consignment / tracking number.
- Each settlement row includes cheque_no and service_invoice_id when available.

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
payment	object	See sample response (`payment`)

Sample response


```
{
  "success": true,
  "payment": {
    "tracking_number": "173018378432",
    "arrival_weight": "1.3",
    "total_charges": "350.00",
    "core_charges": "250.00",
    "settlement_date": null,
    "settlement_status": "Unpaid",
    "cheque_no": null,
    "service_invoice_id": null,
    "payment_invoice_id": null,
    "cod_amount": "2500.00",
    "line_net": "2150.00",
    "paid_amount": null,
    "shipment_status": "DELIVERED",
    "finance_status": "PENDING",
    "external_ref_no": "WC-1001",
    "courier_code": "tcs",
    "delivery_charges": "150.00",
    "service_charges": "50.00",
    "osa_charges": "50.00",
    "income_tax": "50.00",
    "withholding_tax": "50.00"
  }
}
```

POST Bulk payment settlements by CNs

Bulk CN settlement lookup (max 200). Returns results and not_found. Alias body key: cns.

```
POST https://partners.flaship.pk/api/integration/payments/bulk/
```

- Each settlement row includes cheque_no and service_invoice_id when available.

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.
Content-Type	string	Yes	application/json

Request body

Name	Type	Required	Description
tracking_numbers	array	Yes	List of tracking numbers (max 200)

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
count	number	See sample response (`count`)
results	array	See sample response (`results`)
not_found	array	See sample response (`not_found`)

Sample request

```
{
  "tracking_numbers": [
    "173018378432",
    "FS7544027382",
    "MISSING-CN"
  ]
}
```

Sample response

```
{
  "success": true,
  "count": 2,
  "results": [
    {
      "tracking_number": "173018378432",
      "arrival_weight": "1.3",
      "total_charges": "350.00",
      "core_charges": "250.00",
      "settlement_date": "2026-09-20",
      "settlement_status": "Paid",
      "cheque_no": "FTECH-88",
      "service_invoice_id": "SI-88",
      "payment_invoice_id": "PI-88",
      "cod_amount": "2500.00",
      "line_net": "2150.00",
      "paid_amount": "2150.00",
      "shipment_status": "DELIVERED",
      "finance_status": "PAID",
      "external_ref_no": "WC-1001",
      "courier_code": "tcs",
      "delivery_charges": "150.00",
      "service_charges": "50.00",
      "osa_charges": "50.00",
      "income_tax": "50.00",
      "withholding_tax": "50.00"
    },
```

```
    {
      "tracking_number": "FS7544027382",
      "arrival_weight": "1.3",
      "total_charges": "350.00",
      "core_charges": "250.00",
      "settlement_date": null,
      "settlement_status": "Unpaid",
      "cheque_no": "FTECH-88",
      "service_invoice_id": "SI-88",
      "payment_invoice_id": "PI-88",
      "cod_amount": "2500.00",
      "line_net": "2150.00",
      "paid_amount": null,
      "shipment_status": "DELIVERED",
      "finance_status": "PENDING",
      "external_ref_no": "WC-1001",
      "courier_code": "tcs",
      "delivery_charges": "150.00",
      "service_charges": "50.00",
      "osa_charges": "50.00",
      "income_tax": "50.00",
      "withholding_tax": "50.00"
    }
  ],
  "not_found": [
    "MISSING-CN"
  ]
}
```

6. Shipper advice

GET List pending advice

Pending courier shipper-advice queue for this business (same data as portal Pending tab).

```
GET https://partners.flaship.pk/api/integration/advice/pending/
```

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Query parameters

Name	Type	Required	Description
search	string	No	Tracking number filter
courier_code	string	No	Courier filter (alias: courier)

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
count	number	See sample response (`count`)
results	array	See sample response (`results`)

Sample response


```
{
  "success": true,
  "count": 1,
  "results": [
    {
      "id": 42,
      "tracking_number": "14417468279761",
      "external_id": "ticket-9",
      "courier_status": "Shipment Shipper Advise Requested",
      "courier_reason": "Address incomplete",
      "last_seen_at": "2026-09-24T10:00:00+00:00",
      "shipment_id": 1119864,
      "order_status": "SHIPPER_ADVISE",
      "courier_code": "trax",
      "courier_name": "Trax",
      "live_courier_status": "Shipper Advice",
      "shipper_advice_submitted": false,
      "consignee_name": "John Doe",
      "consignee_phone": "03001234567",
      "consignee_city": "Karachi",
      "product_name": "Widget",
      "external_ref_no": "WC-1001",
      "cod_amount": "2500.00",
      "service_type": "OVERNIGHT"
    }
  ]
}
```

GET List advice history

Recent shipper-advice submissions (max 200).

```
GET https://partners.flaship.pk/api/integration/advice/history/
```

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Query parameters

Name	Type	Required	Description
search	string	No	Tracking number filter
courier_code	string	No	Courier filter

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
count	number	See sample response (`count`)
results	array	See sample response (`results`)

Sample response


```
{
  "success": true,
  "count": 1,
  "results": [
    {
      "id": 10,
      "tracking_number": "14417468279761",
      "status": "REATTEMPT",
      "action_code": "REATTEMPT",
      "reason": "1",
      "remarks": "Please reattempt tomorrow",
      "address": null,
      "api_success": true,
      "created_at": "2026-09-24T11:00:00+00:00",
      "shipment_id": 1119864,
      "order_status": "IN_TRANSIT",
      "courier_code": "trax",
      "courier_name": "Trax",
      "live_courier_status": "In Transit",
      "consignee_name": "John Doe",
      "consignee_phone": "03001234567",
      "consignee_city": "Karachi",
      "product_name": "Widget",
      "external_ref_no": "WC-1001",
      "cod_amount": "2500.00",
      "service_type": "OVERNIGHT"
    }
  ]
}
```

GET Check advice eligibility

Precheck whether a CN can accept shipper advice. Local pending queue unlocks eligibility immediately; submit still re-checks the courier live queue.

```
GET https://partners.flaship.pk/api/integration/advice/check/
```

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Query parameters

Name	Type	Required	Description
tracking_number	string	Yes	Shipment CN to check

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
eligible	boolean	See sample response (`eligible`)
in_queue	boolean	See sample response (`in_queue`)
precheck_supported	boolean	See sample response (`precheck_supported`)
adapter_ready	boolean	See sample response (`adapter_ready`)
portal_order_status	string	See sample response (`portal_order_status`)
live_courier_status	string	See sample response (`live_courier_status`)
shipper_advice_submitted	boolean	See sample response (`shipper_advice_submitted`)
courier_reason	string	See sample response (`courier_reason`)
courier_code	string	See sample response (`courier_code`)
shipper_advice_status	string	See sample response (`shipper_advice_status`)
reason	string	See sample response (`reason`)
message	string	See sample response (`message`)

Sample response


```
{
  "success": true,
  "eligible": true,
  "in_queue": true,
  "precheck_supported": true,
  "adapter_ready": true,
  "portal_order_status": "SHIPPER_ADVISE",
  "live_courier_status": "Shipment Shipper Advise Requested",
  "shipper_advice_submitted": false,
  "courier_reason": "Address incomplete",
  "courier_code": "trax",
  "shipper_advice_status": "Shipment Shipper Advise Requested",
  "reason": "Address incomplete",
  "message": "This consignment is awaiting your advice."
}
```

POST Submit shipper advice

Submit advice to the courier for a CN owned by this business. status required: RETURN | REATTEMPT | HOLD (HOLD not supported by all couriers).

```
POST https://partners.flaship.pk/api/integration/advice/
```

- Optional reason codes: 1=same address, 0=new address (+address), 2=fake attempt, 3=hold, 5=return.
- Submit re-checks the courier live advice queue and may fail even if check showed eligible from the local pending queue.

Request headers

Name	Type	Required	Description
`X-API-KEY`	string	Yes	Per-business Integration API token from My Business → API key access.
`Content-Type`	string	Yes	application/json

Request body

Name	Type	Required	Description
`tracking_number`	string	Yes	Shipment CN
`status`	string	Yes	RETURN | REATTEMPT | HOLD
`reason`	string	No	Courier reason code when required (e.g. 1=same address)
`remarks`	string	No	Free-text instructions
`address`	string	No	New delivery address when changing address
`phone`	string	No	Updated phone when required by courier

Response fields

Name	Type	Description
`success`	boolean	See sample response (`success`)
`order_status`	string	See sample response (`order_status`)
`live_courier_status`	string	See sample response (`live_courier_status`)
`shipper_advice_id`	number	See sample response (`shipper_advice_id`)
`api_success`	boolean	See sample response (`api_success`)

Sample request

```
{
  "tracking_number": "14417468279761",
  "status": "REATTEMPT",
  "reason": "1",
  "remarks": "Please reattempt tomorrow",
  "address": "",
  "phone": ""
}
```

Sample response

```
{
  "success": true,
  "order_status": "IN_TRANSIT",
  "live_courier_status": "In Transit",
  "shipper_advice_id": 10,
  "api_success": true
}
```

7. Loadsheets & labels

GET Loadsheet eligible orders

List CNs eligible for loadsheet generation. Pass courier_code to return results.

```
GET https://partners.flaship.pk/api/integration/loadsheets/eligible/
```

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Query parameters

Name	Type	Required	Description
courier_code	string	Yes	Courier code (required to list results)
page	integer	No	Page number (default 1)
page_size	integer	No	Page size (default 25, max 100)
start_date	string	No	YYYY-MM-DD
end_date	string	No	YYYY-MM-DD
search	string	No	Search term

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
count	number	See sample response (`count`)
page	number	See sample response (`page`)
page_size	number	See sample response (`page_size`)
courier_code	string	See sample response (`courier_code`)
orders	array	See sample response (`orders`)
stats	object	See sample response (`stats`)

Sample response


```
{
  "success": true,
  "count": 1,
  "page": 1,
  "page_size": 25,
  "courier_code": "tcs",
  "orders": [
    {
      "id": 1119864,
      "tracking_number": "173018378432",
      "status": "BOOKED"
    }
  ],
  "stats": {
    "eligible_count": 1,
    "total_cod": "2500.00"
  }
}
```

POST Generate loadsheet

Generate a loadsheet for the given tracking numbers. Prefer /print-pack/download/ or /labels/download/ with X-API-KEY for PDF files.

```
POST https://partners.flaship.pk/api/integration/loadsheets/
```

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.
Content-Type	string	Yes	application/json

Request body

Name	Type	Required	Description
tracking_numbers	array	Yes	List of tracking numbers

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
loadsheet_id	string	See sample response (`loadsheet_id`)
url	string	See sample response (`url`)
label_url	string	See sample response (`label_url`)
generated_count	number	See sample response (`generated_count`)
skipped_count	number	See sample response (`skipped_count`)
skipped_orders	array	See sample response (`skipped_orders`)
merchant_company_id	number	See sample response (`merchant_company_id`)
courier_code	string	See sample response (`courier_code`)
courier_name	string	See sample response (`courier_name`)
order_count	number	See sample response (`order_count`)
total_cod	string	See sample response (`total_cod`)
tracking_numbers	array	See sample response (`tracking_numbers`)
label_urls	array	See sample response (`label_urls`)
created_at	string	See sample response (`created_at`)
pdf_available	boolean	See sample response (`pdf_available`)
label_download_url	string	See sample response (`label_download_url`)
loadsheet_download_url	string	See sample response (`loadsheet_download_url`)
label_file_public_id	string	See sample response (`label_file_public_id`)
loadsheet_file_public_id	string	See sample response (`loadsheet_file_public_id`)

Sample request

```
{
  "tracking_numbers": [
    "173018378432",
    "FS7544027382",
    "FS7544027477",
    "FS7544034991"
  ]
}
```

Sample response


```
{
  "success": true,
  "loadsheet_id": "55",
  "url": "/media/merchant/loadsheets/55.pdf",
  "label_url": "/media/merchant/labels/55.pdf",
  "generated_count": 4,
  "skipped_count": 0,
  "skipped_orders": [],
  "merchant_company_id": 1,
  "courier_code": "tcs",
  "courier_name": "TCS",
  "order_count": 4,
  "total_cod": "3500.00",
  "tracking_numbers": [
    "173018378432",
    "FS7544027382",
    "FS7544027477",
    "FS7544034991"
  ],
  "label_urls": [],
  "created_at": "2026-08-15T10:05:00Z",
  "pdf_available": true,
  "label_download_url": "/media/merchant/labels/55.pdf",
  "loadsheet_download_url": "/media/merchant/loadsheets/55.pdf",
  "label_file_public_id": "labels/abc123",
  "loadsheet_file_public_id": "loadsheets/abc123"
}
```

GET Download print pack PDF

One PDF: 2 labels per page + 3 loadsheet receiving copies (same as dashboard Download PDF). Also accepts POST with JSON body. Response is application/pdf.

```
GET https://partners.flaship.pk/api/integration/print-pack/download/
```

- Auth with X-API-KEY — save the response body as a .pdf file.
- Tracking numbers always work with or without loadsheet_id.

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Query parameters

Name	Type	Required	Description
tracking_numbers	string	No	Comma-separated CNs (or JSON array on POST)
loadsheet_id	string	No	Optional loadsheet id
paper	string	No	a4 | thermal (default a4)
per_page	integer	No	Labels per page (default 2)

Response fields

Name	Type	Description
content_type	string	See sample response (`content_type`)
note	string	See sample response (`note`)

Sample request

```
{
  "tracking_numbers": [
    "173018378432",
    "FS7544027382",
    "FS7544027477",
    "FS7544034991"
  ],
  "paper": "a4",
  "per_page": 2
}
```

Sample response

```
{
  "content_type": "application/pdf",
  "note": "Binary PDF body (not JSON)"
}
```

GET Download labels PDF

Labels-only PDF (no loadsheet copies). Response is application/pdf. POST with JSON body also works.

```
GET https://partners.flaship.pk/api/integration/labels/download/
```

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.

Query parameters

Name	Type	Required	Description
tracking_numbers	string	No	Comma-separated CNs
paper	string	No	a4 | thermal
per_page	integer	No	Labels per page (default 2)

Response fields

Name	Type	Description
content_type	string	See sample response (`content_type`)
note	string	See sample response (`note`)

Sample request

```
{
  "tracking_numbers": [
    "173018378432",
    "FS7544027382",
    "FS7544027477",
    "FS7544034991"
  ],
  "paper": "a4",
  "per_page": 2
}
```

Sample response

```
{
  "content_type": "application/pdf",
  "note": "Binary PDF body (not JSON)"
}
```

POST Generate labels

Generate shipping labels metadata / persisted PDF for tracking_numbers or loadsheet_id. Prefer /labels/download/ for a direct labels-only file.

```
POST https://partners.flaship.pk/api/integration/labels/
```

Request headers

Name	Type	Required	Description
X-API-KEY	string	Yes	Per-business Integration API token from My Business → API key access.
Content-Type	string	Yes	application/json

Request body

Name	Type	Required	Description
tracking_numbers	array	No	List of tracking numbers
loadsheet_id	string	No	Loadsheet id alternative to tracking_numbers
paper	string	No	a4 | thermal
per_page	integer	No	Labels per page (default 2)

Response fields

Name	Type	Description
success	boolean	See sample response (`success`)
url	string	See sample response (`url`)
document_id	string	See sample response (`document_id`)
count	number	See sample response (`count`)
tracking_numbers	array	See sample response (`tracking_numbers`)
courier_code	string	See sample response (`courier_code`)
pdf_available	boolean	See sample response (`pdf_available`)
label_file_public_id	string	See sample response (`label_file_public_id`)
pdf_error	null	See sample response (`pdf_error`)

Sample request

```
{
  "tracking_numbers": [
    "173018378432",
    "FS7544027382",
    "FS7544027477",
    "FS7544034991"
  ],
  "paper": "a4",
  "per_page": 2
}
```

Sample response

```
{
  "success": true,
  "url": "/media/merchant/labels/batch.pdf",
  "document_id": "doc_abc123",
  "count": 4,
  "tracking_numbers": [
    "173018378432",
    "FS7544027382",
    "FS7544027477",
    "FS7544034991"
  ],
```

```
  "courier_code": "tcs",
  "pdf_available": true,
  "label_file_public_id": "labels/abc123",
  "pdf_error": null
}
```


© Flaship — Integration API