



Flaship

API Documentation

Developer Integration Guide

Generated for: **BBG Fashion Clothing Store**

Version 1.1 | Generated on August 18, 2026

Comprehensive API reference for seamless integration with Flaship's courier services platform

Table of Contents

Authentication	3
Important Notes	3
API Reference	4
1. Couriers, Rates & Cities [GET]	4
2. System Statuses [GET]	5
3. Pickup Locations [GET]	6
4. Create Pickup Location [POST]	7
5. Rate Card [GET]	8
6. Create Booking [POST]	8
7. Bulk Booking [POST]	10
8. List Orders [GET]	11
9. Order Detail [GET]	12
10. Track Order [GET]	13
11. Cancel Order [POST]	14
12. Loadsheets Eligible Orders [GET]	16
13. Generate Loadsheets [POST]	17
14. Generate Label [POST]	18

Authentication

All API endpoints require authentication using the **X-API-KEY** header with your unique API key.

Header Name	Value	Required
X-API-KEY	Your unique API key	Yes
Content-Type	application/json	Yes (for POST)

Important Notes

	Security: Keep your API key secure and never expose it in client-side code or public repositories.
	Content-Type: All POST requests must include Content-Type: application/json header.
	Rate Limiting: Maximum 100 requests per minute per API key.
	Validation: Always validate response status before processing the data.
	Support: For support, contact: support@flaship.pk

API Reference

Endpoints are listed in the recommended integration order.

1. Couriers, Rates & Cities [GET]

Fetch pickup addresses, assigned courier companies, rate cards (service types), and operational cities for booking.

Endpoint:

```
https://partners.flaship.pk/mr/company_list/
```

Ways to Call:

1. Minimal:

GET `https://partners.flaship.pk/mr/company_list/`

Headers: X-API-KEY: `your_api_key`

Sample Response:

```
{
  "success": true,
  "pickupAddress": [
    {
      "id": 17,
      "address": "Colony Road, Near 123 High School"
    },
    {
      "id": 102,
      "address": "123 Main Street, Block A Warehouse"
    }
  ],
  "companies": ["TCS", "Leopard", "Trax", "MNP"],
  "rateCards": {
    "Leopard": ["overnight", "detain", "overland"],
    "TCS": ["overnight", "overland"]
  },
  "operations_cities": {
    "Leopard_all": ["Lahore", "Karachi", ...],
    "MNP_all": ["Pir Mahal", "Nankana Sahib", ...]
  }
}
```

2. System Statuses [GET]

Fetch integration order statuses and courier service types. Use `order_statuses.all` when filtering List Orders.

Endpoint:

```
https://partners.flaship.pk/mr/api/statuses/
```

Ways to Call:

1. Minimal:

GET `https://partners.flaship.pk/mr/api/statuses/`

Headers: X-API-KEY: `your_api_key`

Sample Response:

```
{
  "success": true,
  "order_statuses": {
    "all": [
      "Booked",
      "Delivered",
      "Cancelled",
      "In Transit",
      "Out for Delivery",
      "Picked up",
      "Return Received",
      "Shipper Advise",
      "Return in Transit"
    ]
  },
  "service_types": ["overnight", "detain", "overland"]
}
```

3. Pickup Locations [GET]

List all pickup locations registered on your account.

Endpoint:

```
https://partners.flaship.pk/mr/api/pickup-locations/
```

Ways to Call:

1. Minimal:
GET <https://partners.flaship.pk/mr/api/pickup-locations/>
Headers: X-API-KEY: your_api_key

Sample Response:

```
{
  "success": true,
  "pickup_locations": [{ "id": 17, "address": "...", "is_default": true }],
  "user_companies": ["Leopard", "TCS"]
}
```

4. Create Pickup Location [POST]

Create a new pickup location for your account and sync it with assigned courier companies.

Endpoint:

```
https://partners.flaship.pk/mr/api/create_pickuplocation
```

Request Parameters:

Parameter	Type	Required	Description
pickupAddress	string	Yes	Complete pickup address
city	string	Yes	City name for pickup location
shipperPhone	string	Yes	Pickup contact phone
shipperName	string	Yes	Pickup contact person name

Sample Request:

```
{
  "pickupAddress": "Plot 91, Ahmad Street, Khayaban Colony #1",
  "city": "Faisalabad",
  "shipperPhone": "03001234567",
  "shipperName": "W. Mustafa"
}
```

Sample Response:

```
{
  "success": true,
  "companies": ["Leopard", "TCS", "Trax"]
}
```

5. Rate Card [GET]

Get rate cards with charges per courier company and service type.

Endpoint:

```
https://partners.flaship.pk/mr/api/rate-card/
```

Ways to Call:

1. Minimal:
GET <https://partners.flaship.pk/mr/api/rate-card/>
Headers: X-API-KEY: your_api_key

Sample Response:

```
{
  "success": true,
  "companies": [
    {
      "company_name": "Leopard",
      "rate_cards": [
        {"service_type": "overnight", "charges": 150, "weight_from": 0, "weight_to": 1000}
      ]
    }
  ]
}
```

6. Create Booking [POST]

Create a new packet booking with specified courier company.

Endpoint:

```
https://partners.flaship.pk/mr/api/packet_booking
```

Request Parameters:

Parameter	Type	Required	Description
consigneeName	string	Yes	Recipient name
consigneePhone1	string	Yes	Primary phone number
consigneeAddress	string	Yes	Delivery address
destinationCity	string	Yes	Delivery city name
codAmount	string	Yes	Cash on delivery amount
productName	string	Yes	Product description
productWeight	string	Yes	Weight in KG
productPieces	string	Yes	Number of pieces
courierCompany	string	Yes	Courier name (e.g., Leopard, TCS)
courierOption	string	Yes	Service type (overnight/overland/deta in)
pickuplocation	string	Yes	Pickup location ID

Sample Request:

```
{
  "consigneeName": "John Doe",
  "consigneePhone1": "03001234567",
  "consigneePhone2": "",
  "consigneeAddress": "123 Main Street, Block A",
  "destinationCity": "Karachi",
  "codAmount": "2500",
  "productName": "Electronics - Mobile Phone",
  "productWeight": "0.5",
  "productPieces": "1",
  "courierCompany": "Leopard",
  "courierOption": "overnight",
  "pickuplocation": "10",
  "specialInstructions": "Handle with care",
  "externalref": ""
}
```

Sample Response:

```
{
  "success": true,
  "orderNo": 12345,
  "trackingId": "FLP123456789"
}
```

7. Bulk Booking [POST]

Upload a CSV file to create multiple bookings. Rows without Shipment type are skipped.

Endpoint:

```
https://partners.flaship.pk/mr/api/bulk/booking/
```

Request Parameters:

Parameter	Type	Required	Description
courierCompany	string	Yes	Courier company name
pickuplocation	string	Yes	Pickup location ID
file	file	Yes	CSV file (multipart/form-data)

Ways to Call:

1. cURL multipart:

```
curl -X POST .../mr/api/bulk/booking/ -H "X-API-KEY: ..." \
-F courierCompany=Leopard -F pickuplocation=17 -F file=@orders.csv
```

2. Postman: Body > form-data (courierCompany, pickuplocation, file)

Sample Response:

```
{
  "success": { "...": "courier bulk booking response" },
  "error": [
    { "row_number": 3, "error": "Invalid destination City" }
  ]
}
```

8. List Orders [GET]

List and filter your orders with pagination. Use type=download to export all matching orders.

Endpoint:

```
https://partners.flaship.pk/mr/api/orders/
```

Request Parameters:

Parameter	Type	Required	Description
page	integer	No	Page number (default 1, 100 per page)
company	string	No	Filter by courier company
status	string	No	Filter by order status
startDate	string	No	Start date YYYY-MM-DD
endDate	string	No	End date YYYY-MM-DD
search	string	No	Search CN, reference, shipper, consignee
type	string	No	Set to download for full export

Ways to Call:

1. Minimal: GET .../mr/api/orders/
 2. Paginated: ?page=2
 3. By status: ?status=Booked
 4. By courier: ?company=Leopard
 5. By dates: ?startDate=2026-01-01&endDate=2026-05-19
 6. Search: ?search=FLP123
 7. All filters: ?page=1&company=Leopard&status=Booked&startDate=...&search=FLP
 8. Export: ?type=download&startDate=...&endDate=...&status=Delivered
- Headers: X-API-KEY: your_api_key

Sample Response:

```
{
  "success": true,
  "orders": [...],
  "total_pages": 5,
  "current_page": 1,
  "stats_count": [{"order_status": "Booked", "count": 42}]
}
```

9. Order Detail [GET]

Get full details for a single order by tracking number (CN).

Endpoint:

```
https://partners.flaship.pk/mr/api/orders/{tracking_number}/
```

Request Parameters:

Parameter	Type	Required	Description
tracking_number	string	Yes	Tracking number in URL path

Ways to Call:

1. By tracking number:

GET https://partners.flaship.pk/mr/api/orders/FLP123456789/

Headers: X-API-KEY: your_api_key

Sample Response:

```
{
  "success": true,
  "order": {
    "packet_id": 12345,
    "tracking_number": "FLP123456789",
    "order_status": "Booked",
    "company": "Leopard",
    "cod_amount": 2500,
    "payment_status": "initiated"
  }
}
```

10. Track Order [GET]

Track the status of your shipment using tracking number.

Endpoint:

```
https://partners.flaship.pk/mr/api/order_tracking/{tracking_number}/
```

Request Parameters:

Parameter	Type	Required	Description
tracking_number	string	Yes	The tracking number of the order (URL parameter)

Ways to Call:

1. By CN in URL path:

GET `https://partners.flaship.pk/mr/api/order_tracking/FLP123456789/`

Headers: X-API-KEY: `your_api_key`

Sample Response:

```
{
  "status": true,
  "tracking": [
    {"status": "In Transit", "time": "2026-06-10T14:30:00"},
    {"status": "Picked Up", "time": "2026-06-09T10:00:00"}
  ],
  "order_status": "In Transit"
}
```

OR (Error - HTTP 404):

```
{
  "status": false,
  "error": "Order not found. Use the tracking number (CN), not the internal order ID."
}
```

11. Cancel Order [POST]

Cancel a booked order before it is picked up. Send the tracking number in the request body as JSON.

Endpoint:

```
https://partners.flaship.pk/mr/api/cancel_order/
```

Request Parameters:

Parameter	Type	Required	Description
cn	string	Yes	The tracking number to cancel

Sample Request:

```
{
  "cn": "FLP123456789"
}
```

Sample Response:

```
{
  "status": true,
  "message": "Order cancelled"
}
```

OR (Already Cancelled):

```
{
  "status": true,
  "message": "Order already cancelled"
}
```

OR (Error - Order not found):

```
{
  "status": false,
  "message": "Order not found"
}
```

OR (Error - Missing parameter):

```
{
  "status": false,
  "message": "cn is required"
}
```

OR (Error - Invalid JSON):

```
{
  "status": false,
  "message": "Invalid JSON"
}
```

12. Loadsheet Eligible Orders [GET]

List booked orders without a loadsheet, ready for loadsheet generation.

Endpoint:


```
https://partners.flaship.pk/mr/api/loadsheet/eligible-orders/  
/
```

Request Parameters:

Parameter	Type	Required	Description
company_name	string	No	Filter by courier
startDate	string	No	Start date (default: 10 days ago)
endDate	string	No	End date (default: today)
search	string	No	Search CN, phone, or consignee name

Ways to Call:

1. Minimal (last 10 days): GET .../eligible-orders/
 2. By courier: ?company_name=Leopard
 3. By dates: ?startDate=2026-05-01&endDate=2026-05-19
 4. Search: ?search=03001234567
 5. All filters: ?company_name=Leopard&startDate=...&search=FLP
- Headers: X-API-KEY: your_api_key

Sample Response:

```
{  
  "success": true,  
  "orders": [  
    {"tracking_number": "FLP123456789", "order_status": "Booked", "cod_amount": 2500}  
  ]  
}
```

13. Generate Loadsheet [POST]

Generate loadsheet PDF for specific orders.

Endpoint:

```
https://partners.flaship.pk/mr/api/loadsheet/
```

Request Parameters:

Parameter	Type	Required	Description
cns	array	Yes	Array of tracking numbers to include

Ways to Call:

1. By tracking numbers:

```
POST https://partners.flaship.pk/mr/api/loadsheet/  
{  
  "cns": ["FLP123456789", "FLP987654321"]  
}
```

Tip: GET /mr/api/loadsheet/eligible-orders/ first

Sample Response:

```
{  
  "success": true,  
  "url": "/media/merchant/loadsheets/123/5234.pdf",  
  "loadsheet_id": 5234,  
  "generated_count": 18,  
  "skipped_orders": []  
}
```

14. Generate Label [POST]

Generate shipping labels for booked orders. Either cns or loadsheet_id must be provided.

Endpoint:

```
https://partners.flaship.pk/mr/generate_label
```

Request Parameters:

Parameter	Type	Required	Description
cns	array	Yes*	Array of tracking numbers
loadsheets_id	integer	Yes*	Loadsheets ID (alternative to cns)

Ways to Call:

1. By tracking numbers (body JSON):

```
POST https://partners.flaship.pk/mr/generate_label
{"cns": ["FLP123456789", "FLP987654321"]}
```

2. By loadsheets ID:

```
POST https://partners.flaship.pk/mr/generate_label
{"loadsheets_id": 5234}
```

Sample Response:

```
HTTP/1.1 200 OK
Content-Type: application/pdf
Content-Disposition: attachment; filename="label.pdf"
```

[Binary PDF Data]

OR (if no orders found):

```
{
  "success": false,
  "reason": "No order found for this url"
}
```