Decision-Support Content Refresh Prioritization on Unseen Client Domains: An Empirical Machine Learning Approach

Md. Fardin Hossain
FlyRankAI Machine Learning Internship
Applied Search Intelligence Track
Dhaka, Bangladesh
fardin.hosn@gmail.com

***Abstract*—For large-scale websites, mature articles often suffer from gradual search visibility erosion and organic traffic decay on search engines over time. Because editorial teams cannot manually check thousands of published pages each week, this study investigates whether supervised machine learning models can accurately identify and prioritize decaying content candidates across unseen client websites. To evaluate this approach, a leak-free dataset of 30,000 mature web pages was constructed across 32 client accounts from FlyRank's 78.8-million-row search database, validating candidate models under a client-grouped holdout partition with strictly isolated test domains. Under this rigorous evaluation on unseen clients, standalone supervised classifiers achieved top-50 precision between 0.420 and 0.780 (0.680 for Random Forest)—more than doubling the 0.300 precision of heuristic baseline rules—while combining predicted decay probabilities with search demand in a composite Action Score reached a top-50 precision of 0.980. Finally, these model outputs were operationalized into an interpretable editorial action playbook featuring diagnostic reason codes and human-in-the-loop safety rules, transforming ad-hoc content maintenance into a reliable decision-support system.**

***Index Terms*—search engine optimization, machine learning triage, content refresh, client-grouped validation, decision support systems**

I. Introduction

Organic search traffic from search engines represents a primary source of audience acquisition for digital publishers and enterprise platforms. While high-quality articles can maintain stable readership for extended periods, search visibility inevitably degrades as competitor content emerges, algorithms evolve, and user query phrasing shifts. This visibility loss is especially acute within top search positions: slipping from position 4 to position 11 typically causes an organic click loss exceeding 70% [1], [2].

Managing content decay poses a severe operational bottleneck because editorial bandwidth is finite. Large websites routinely maintain between 10,000 and 50,000 published pages, yet an editorial team can realistically revise only 20 to 50 URLs during a weekly content sprint. Consequently, URL prioritization determines operational efficiency. Allocating writers to stable pages wastes labor, while high-value decaying assets continue to bleed traffic undetected.

Historically, organizations have relied on deterministic heuristic rules, such as flagging articles older than 90 days or pages ranking on search engine results page (SERP) Page 2. However, these heuristics suffer from three structural shortcomings:

1) **Authority Disconnect:** High-authority domains often preserve rankings for months without updates, whereas smaller domains decay rapidly. Uniform age thresholds ignore domain authority differences.
2) **Arbitrary Cutoffs:** Rigid thresholds treat position 20 as an urgent failure while ignoring position 21, overlooking longitudinal momentum and reader engagement.
3) **Demand Disconnect:** Simple rules often flag stale pages ranking deep in search results despite negligible query impressions, expending editorial effort on zero-demand assets.

To resolve these limitations, this study evaluates whether supervised machine learning can learn decay dynamics from observable search telemetry and rank URLs by potential business impact. Specifically, this research addresses the following formal question:

> *Can a supervised machine learning model, trained on observable search signals without data leakage, outperform deterministic heuristic baseline rules in ranking candidate URLs for editorial refresh on completely unseen client domains?*

This paper provides four primary contributions:

- Construction of an anonymized benchmark dataset containing 30,000 mature URLs across 32 client accounts from an industrial 78.8-million-row warehouse release.
- Demonstration that naive random splits yield an artificial 1.000 top-50 precision due to domain memorization, establishing that client-grouped validation is mandatory.
- Empirical evidence that supervised models more than double baseline triage precision on unseen domains (0.420–0.780 vs. 0.300, 0.680 for Random Forest), reaching 0.980 when combined with search demand in a composite Action Score.
- Design of an interpretable editorial playbook with five action archetypes, diagnostic reason codes, and human-

in-the-loop governance guardrails.

II. Related Work

A. Search Dynamics and Position Bias

This research builds upon established findings in web search and user behavior. Radlinski and Craswell [1] and Joachims et al. [2] demonstrated that user attention drops precipitously outside the top search positions. Craswell et al. [3] formalized this drop via click cascade models, showing that users inspect search results sequentially and rarely proceed past the initial entries. Agichtein et al. [4] established that click-through rates and browsing interactions provide strong implicit feedback regarding content relevance. Furthermore, longitudinal search analysis by FlyRank [5] revealed that monitoring aggregate impression trajectories enables detection of content decay weeks prior to site-wide traffic drops.

B. Machine Learning for Tabular Ranking

Learning-to-rank algorithms provide standard methodologies for converting multi-dimensional search features into prioritized queues [6], [7]. For tabular data exhibiting skewed distributions, tree-based ensembles including Random Forests [8] and Gradient Boosted Trees [9] have demonstrated strong empirical performance [10]. Tree ensembles effectively capture non-linear interactions—such as high query volume coupled with declining reader dwell time—without requiring restrictive parametric assumptions.

C. Data Leakage and Validation Integrity

Deploying machine learning across multi-tenant domains requires strict defenses against data leakage. Kaufman et al. [11] established that offline models frequently report inflated accuracy because input features inadvertently encode the target label. Sculley et al. [12] highlighted that undeclared feedback loops create critical technical debt in machine learning systems. In multi-client search environments, evaluating models via naive random splits causes algorithms to memorize client-specific volume baselines rather than learning generalizable decay patterns [13], [14]. Client-grouped partitioning is therefore required for realistic out-of-domain evaluation. Finally, official search guidelines emphasize that content must remain reliable and up-to-date [15], while balanced natural class distributions avoid artificial oversampling artifacts [16].

III. Data

A. Warehouse Source and Scale

Experiments utilize the FlyRank AI/ML Internship Warehouse Release (`v20260703`), hosted publicly on Hugging Face at `FlyRank/internship-warehouse`. The complete repository comprises 78,835,655 daily performance records, 519,606 unique content entries, and 2,414,248 search query observations across 104 client accounts over a 17-month window from January 27, 2025 to June 30, 2026.

B. Mature Content Selection and Client Filtering

Search engines frequently test newly published URLs through exploratory ranking placements, producing temporary volatility that does not reflect intrinsic content stability. To isolate mature lifecycle dynamics, the study population is restricted to URLs with at least 90 days of age and non-zero search impressions:

$$\mathcal{S}_{\text{mature}} = \{i \mid \text{imp}_{90\text{d}}(i) > 0 \ \wedge \ \text{age}(i) \geq 90\} \tag{1}$$

To ensure robust longitudinal telemetry, client accounts were included in the analytical release only if they maintained: (1) continuous 90-day tracking without telemetry gaps; (2) at least 100 indexed URLs; and (3) verified Google Search Console telemetry. This filtering produced a standardized study cohort of **30,000 unique URLs across 32 client accounts**.

C. Target Label Definition and Observation Window

The triage task is framed as identifying historical traffic decay. Traffic momentum is calculated by comparing impressions during the most recent 30-day window ($\text{imp}_{t-30:t}$) to the preceding 30-day window ($\text{imp}_{t-60:t-30}$):

$$\text{trend_pct}_i = \frac{\text{imp}_{t-30:t}(i) - \text{imp}_{t-60:t-30}(i)}{\text{imp}_{t-60:t-30}(i)} \tag{2}$$

An article is labeled as declining ($y_i = 1$) if its impression momentum drops below negative five percent (trend_pct < -0.05):

$$y_i = \mathbb{I}(\text{trend_direction}_i = \text{“down”}) \tag{3}$$

Across the 30,000 mature URLs, 16,262 items exhibit negative momentum, yielding a natural base rate of **54.21%**.

Methodological Framing: This label captures observed historical decline within the 90-day observation window, rather than a forward-looking future forecast. The system therefore performs retrospective decline triage and candidate prioritization for human review, rather than automated future traffic forecasting.

D. Data Privacy and Public Safety

To protect client confidentiality, all domain identifiers, URLs, and query strings were mapped to synthetic anonymized tokens. All reported metrics utilize public-safe aggregate statistics.

IV. Methodology

A. Feature Engineering (X)

To model decay patterns without data leakage, 27 observable signals available at review time ($t = 0$) were extracted, following standard feature selection principles [17]. Crucially, the 30-day sub-windows ($\text{imp}_{t-30:t}$, $\text{imp}_{t-60:t-30}$) and percentage trend column (trend_pct) were strictly excluded from the feature matrix because they were used directly to construct the label.

Table I details the feature taxonomy, organized into four operational categories.

Logarithmic transformation, $\log(1 + x)$, was applied to volume counters to compress heavy-tailed power-law distributions. This prevents high-traffic outliers from distorting loss gradients while enabling equitable comparison across small and large pages.

TABLE I
FEATURE TAXONOMY AND EXTRACTION WINDOWS ($M = 27$)

Category	Observable Signals	Window
Traffic Volume & Momentum	$\log(1 + \text{imp}_{90d})$, $\log(1 + \text{clicks}_{90d})$, $\log(1+\text{sessions}_{90d})$, $\log(1+\text{ai_sess}_{90d})$, days with impressions, days with sessions	90-day history
Search Visibility & SERP	Average rank position, CTR, discrete position brackets (Top 3, 4–10, 11–20, Deep SERP), impression tier	90-day SERP telemetry
Content Lifecycle & Freshness	Content age in days, days since update, age tier, freshness tier, freshness ratio	Review date ($t = 0$)
Engagement & Quality	Word count, character count, scroll rate, engagement rate, AI traffic share, competition level, content type, intent, CPC	Review date ($t = 0$)

B. Composite Action Score Formulation

Predicted decay probability alone is insufficient for setting sprint priorities. A page with a 95% probability of decline that generates only five monthly impressions does not justify manual revision. To align recommendations with business value, predicted decline probabilities are combined with search demand and ranking leverage into an operational *Action Score*:

$$\text{Action_Score}_i = \log(1 + \text{imp}_i) \cdot \hat{p}_i \cdot w(\text{pos}_i) \tag{4}$$

where imp_i is the 90-day impression volume, $\hat{p}_i = P(y = 1 \mid X_i)$ is the model's predicted decline probability, and $w(\text{pos}_i)$ is a discrete position weight reflecting SERP click sensitivity [1], [3]:

$$w(p) = \begin{cases} 1.0, & 0 < p \leq 10 \text{ (Page 1)} \\ 0.8, & 10 < p \leq 20 \text{ (Page 2)} \\ 0.5, & p > 20 \text{ (Deep SERP)} \\ 0.2, & p \leq 0 \text{ (Unranked)} \end{cases} \tag{5}$$

Position weights reflect heuristic domain multipliers prioritizing assets where modest ranking drops produce severe click losses. Scores are linearly scaled to a 0–100 index for planning.

C. Leakage Prevention and Auditing

Four systematic verification checks were conducted following Kaufman et al. [11]:

1) **Exclusion of Target Derivatives:** All fields derived directly from the outcome, including trend_pct, were excluded.
2) **Exclusion of Downstream Flags:** Production scores and post-outcome metrics were removed to prevent circular feedback.
3) **Intentional Leakage Sanity Check:** Injecting the raw trend column into the training matrix produced an artificial validation score of 1.0000, confirming that the pipeline detects leakage immediately. Removing the column returned scores to an honest 0.610.
4) **Correlation Tower Audit:** Pearson correlation against the target showed a maximum value of $r = 0.1901$ (active impression days), proving that no individual feature exposes the label.

V. EXPERIMENTAL SETUP AND VALIDATION

A. Client-Grouped Holdout Design

To evaluate generalization to unseen client domains, the dataset was partitioned using `GroupShuffleSplit` grouped strictly on client_id with an 80/20 train/test split:

- **Training Partition:** 23,837 pages from 25 client accounts (55.0% decline rate).
- **Testing Partition:** 6,163 pages from 7 held-out client accounts (51.1% decline rate).
- **Domain Isolation:** $\text{Clients}_{\text{train}} \cap \text{Clients}_{\text{test}} = \emptyset$ (zero client overlap).

Because each client account represents a distinct domain property, zero client overlap ensures that algorithms cannot memorize site-specific traffic levels.

B. Candidate Models and Benchmark Baseline

Four modeling approaches were evaluated on this split:

1) **Baseline Rules (Week 4):** A heuristic formula multiplying log-impressions by discrete position and freshness tiers.
2) **Logistic Regression:** A standardized linear classifier (L_2 regularization, $C = 1.0$) evaluating monotonic linear relationships.
3) **Decision Tree:** A depth-constrained tree (max_depth = 5) modeling discrete step-function thresholds.
4) **Random Forest:** An ensemble of 100 decision trees (max_depth = 12, random_state = 42) capturing non-linear feature interactions.

C. Evaluation Metrics

Because editorial teams realistically review 50 pages per week, the primary evaluation metric is **Precision@50**:

$$\text{Precision@}K = \frac{1}{K} \sum_{i=1}^{K} y_{(i)} \tag{6}$$

where $y_{(i)}$ is the true label of the candidate ranked at index i. Across the entire test set, Average Precision (PR-AUC), ROC-AUC [18], Recall, and F1-score are also evaluated.

VI. RESULTS

A. Model vs. Baseline Performance

Table II summarizes model performance on the held-out test split of 6,163 pages across 7 unseen client websites.

Both supervised models decisively outperform the heuristic baseline. In top-50 precision, standalone Logistic Regression

TABLE II
MODEL PERFORMANCE ON UNSEEN CLIENT WEBSITES ($N = 6,163$, HOLDOUT BASE RATE = 0.511)

Model	P@50	PR-AUC	ROC-AUC	Recall	F1
Baseline Rules (Week 4)	0.300	0.522	0.538	—	—
Logistic Regression	**0.780**	**0.615**	**0.625**	**0.669**	**0.624**
Decision Tree (max_depth=5)	0.420	0.570	0.592	0.574	0.584
Random Forest (100 trees)	0.680*	0.602	0.612	0.668	0.618

*When Random Forest probabilities are combined with search demand and position leverage in the composite Action Score, Precision@50 reaches **0.980** (49 out of 50 pages verified declining).




Fig. 1. Cost/Value Matrix mapping logarithmic search demand against predicted decay probability. The upper-right quadrant isolates high-priority refresh candidates.




Fig. 2. Portfolio distribution across five suggested editorial intervention archetypes (left) and triage confidence tiers (right).

reaches 0.780 and standalone Random Forest reaches 0.680, compared to 0.300 for the baseline rules—representing a **+127% to +160% relative improvement**. Furthermore, combining Random Forest probabilities with search volume and position weighting in the composite Action Score yields a top-50 precision of **0.980**, successfully identifying 49 truly declining pages out of 50 recommendations.

Comparing models reveals operational trade-offs. Logistic Regression provides well-calibrated linear ranking, yielding the highest standalone precision among top candidates (0.780) and balanced full-test performance (PR-AUC = 0.615, ROC-AUC = 0.625, F1 = 0.624). In contrast, Random Forest captures non-linear interactions across impressions and ranking drops, achieving 0.680 standalone top-50 precision and 0.668 recall across all 6,163 test pages. Thus, teams executing focused weekly sprints benefit most from high-precision ranking, while teams conducting broad quarterly audits can utilize Random Forest to discover a wider set of declining assets.

B. The Validation Split Gap

Table III illustrates the consequences of improper validation design.

TABLE III
COMPARISON OF NAIVE RANDOM SPLIT VS. HONEST CLIENT-GROUPED SPLIT

Split Design	Client Overlap	Base Rate	P@50	ROC-AUC
Naive Random Split	31 clients (100%)	0.545	1.000	0.775
Honest Grouped Split	0 clients (0%)	0.511	0.680	0.612

Evaluating Random Forest via standard random splitting produced an artificial Precision@50 of 1.000 and ROC-AUC of 0.775 due to client memorization. When evaluated on unseen client accounts, Precision@50 settled at an honest 0.680. This substantial gap confirms that grouped validation is mandatory for assessing out-of-domain transfer.

C. Feature Importance Analysis

Random Forest Gini feature importances reveal the primary signals utilized during tree splitting:

1) Active impression days (**13.1%**): consistency of search presence over time.
2) Logarithmic impressions (**10.7%**): baseline traffic magnitude separating real decay from statistical noise.
3) Average position (**10.1%**): physical position cliff on search engines (Page 1 vs. deep SERP).
4) Content age in days (**9.4%**): content lifecycle maturity and freshness erosion.
5) Word count (**6.1%**): article length and depth of coverage.

Gini importance indicates feature reliance within tree splits, rather than direct physical causation in search ranking algorithms.




Fig. 3. Frequencies of explainable diagnostic reason codes in the final editorial triage queue.

VII. DISCUSSION

Experimental findings indicate that organic search decay does not follow arbitrary calendar schedules. Deterministic rules assume articles become obsolete after 90 days. In reality, decay is a continuous process accelerating when URLs slip to positions 11–20 while retaining active query demand. Machine learning models succeed because they learn smooth non-linear

boundaries, avoiding false alarms common to rigid cutoff thresholds.

Furthermore, empirical results qualify the assumption that content age is the primary driver of traffic loss. Content age accounts for only 9.4% of predictive importance, whereas ranking position and impression consistency account for nearly 34%. Articles decline not merely because of age, but when competitor coverage improves or search intent shifts. Detecting ranking erosion early enables teams to intervene before search visibility collapses.

Error analysis on unseen domains reveals two notable edge cases:

- **False Positives:** URLs ranking near position 35 that have remained dormant for months. Tree models identify low rank and high age and predict active decay, whereas traffic had flatlined long ago.
- **False Negatives:** Top-ranking articles receiving minimal weekly impressions. Losing one impression represents a large percentage drop mathematically, but has negligible business significance. Weighting decay probability by demand resolves both issues by filtering inactive pages from the priority queue.

VIII. Limitations and Honest Framing

The boundaries of this research are explicitly defined:

- **Observational Data:** Models are trained on observational telemetry. While models reliably identify pages exhibiting traffic decline, this association does not prove that refreshing an article will automatically restore lost rankings. Historical updates in real portfolios suffer from selection bias because human editors naturally choose to update pages they believe have high commercial potential.
- **No Search Engine Reverse-Engineering:** This study does not attempt to reverse-engineer proprietary ranking algorithms, but models observable search metrics across commercial portfolios.
- **Mature Content Scope:** Conclusions apply strictly to mature content (≥ 90 days old with search impressions), and do not describe new URLs.
- **Offline vs. Online Divergence:** High offline precision does not guarantee online traffic recovery, which depends on editorial revision quality.
- **Platform Covariate Shift:** Search layout alterations (e.g., AI Overviews, video modules) alter CTR independently of content quality.
- **Single Grouped Partition:** Evaluation relies on an 80/20 grouped split across 7 test clients. Future work should assess multi-fold cross-validation to quantify client-level variance.

IX. Ranked Recommendations

Editorial actions are organized into five evidence-backed archetypes:

1) **`refresh_and_review_ctr` (24.7% of pages):** Strong rankings (positions 1–20) with below-average CTR ($< 0.5\%$). *Action:* Rewrite title tags and meta descriptions to improve SERP appeal.
2) **`refresh` (27.7%):** Clear decay indicators with solid underlying content. *Action:* Update outdated facts, statistics, and examples.
3) **`refresh_and_review_engagement` (7.0%):** Steady impressions with low scroll depth ($< 30\%$). *Action:* Redesign introductory layouts to improve visual readability.
4) **`expand_and_refresh` ($< 0.1\%$):** Visible search positions despite brief coverage ($< 1,000$ words). *Action:* Substantially expand content depth and topical breadth.
5) **`monitor` (40.6%):** Low decay probability or negligible search demand. *Action:* Retain in automated monitoring without spending writer hours.

To protect search equity, three human-in-the-loop policies are enforced: (1) no autonomous AI publishing without human review; (2) no automated deletions or 301 redirects, preserving backlink equity; and (3) mandatory subject-matter expert review for sensitive medical, legal, or financial content.

A. Illustrative Economic Sprint Simulation

To evaluate operational utility, a standard weekly 50-page editorial sprint is modeled under a transparent economic simulation. Assuming an industry-standard refresh cost of $150 per in-depth revision (3 hours at $50 per hour), reviewing 50 pages requires a $7,500 budget. Assuming successfully identifying and updating a true declining page protects $500 in annual organic traffic value (200 visits at an average $2.50 CPC equivalent):

- **Baseline Heuristic Queue (P@50 = 0.300):** Identifies 15 declining pages ($15 \times \$500 = \$7,500$ gross value), yielding $0 net return (**0.0% net ROI**, breaking even) while misallocating 35 writer slots. (Exploratory full-portfolio sorts reached 0.380–0.420 under alternate tie-breaking, but held-out test precision is strictly 0.300.)
- **Action Score Prioritized Queue (P@50 = 0.980):** Identifies 49 declining pages ($49 \times \$500 = \$24,500$ gross value), yielding $17,000 net return (**+226.7% net ROI**).
- **Incremental Operational Lift:** Produces an incremental gain of **+$17,000 in net protected value per sprint** (+34 additional true declining pages accurately targeted) compared to the heuristic baseline.

These figures represent an illustrative decision-support economic model based on operational cost assumptions rather than measured post-intervention revenue recovery. Retraining is recommended following major core search updates, whenever writer agreement drops below 60%, or every 90 days.

X. Reproducibility

All code, models, and figure generation scripts are publicly available. Experiments can be reproduced on Python 3.12 via four steps:

1) Clone repository and install dependencies from `requirements.txt` (`scikit-learn`, `pandas`, `duckdb`, `numpy`, `matplotlib`).

2) Execute `python scripts/run_all.py` to run cleaning, model training, and chart generation on the bundled sample dataset in under two minutes.
3) Open and execute the capstone notebook at `work/notebooks/capstone.ipynb` to verify the grouped split and baseline comparisons.
4) Inspect exported JSON receipts in `work/outputs/` to verify every reported experimental metric.

The complete open-source project is available at: https://github.com/fardinhossain/FlyRankAI-ML-Internship-Task.

XI. Conclusion

This paper investigated supervised machine learning for prioritizing content refresh candidates on unseen client websites. Evaluating 30,000 mature URLs across 32 client accounts from an industrial search warehouse demonstrated that supervised models achieve top-50 precision between 0.420 and 0.780 (0.680 for Random Forest) under honest client-grouped validation, more than doubling the 0.300 precision of heuristic rules. Combining predicted decay probabilities with search demand and ranking leverage in a composite Action Score reached a top-50 precision of 0.980.

Furthermore, empirical results confirmed that naive random validation causes severe domain memorization, establishing client-grouped splitting as essential for reliable evaluation. This decision-support system transforms content maintenance from subjective guesswork into an evidence-backed workflow. Future research will explore counterfactual evaluation methods to measure post-update recovery directly and develop multi-task architectures that jointly predict rank drops and click-through changes.

Acknowledgment

Built on the FlyRank ML Internship dataset. The author thanks the FlyRank engineering and data intelligence teams for provisioning the pseudonymized production search warehouse release under educational research terms. FlyRank does not endorse the specific models or operational recommendations presented in this paper.

References

[1] F. Radlinski and N. Craswell, "Comparing the sensitivity of information retrieval metrics," in *Proceedings of the 33rd International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR '10)*. ACM, 2010, pp. 667–674.

[2] T. Joachims, L. Granka, B. Pan, H. Hembrooke, F. Radlinski, and G. Gay, "Accurately interpreting clickthrough data as implicit feedback," *ACM SIGIR Forum*, vol. 51, no. 1, pp. 4–11, 2017.

[3] N. Craswell, O. Zoeter, M. Taylor, and B. Ramsey, "An experimental comparison of click position-bias models," in *Proceedings of the International Conference on Web Search and Web Data Mining (WSDM '08)*. ACM, 2008, pp. 87–94.

[4] E. Agichtein, E. Brill, and S. Dumais, "Improving web search ranking by incorporating user behavior information," in *Proceedings of the 29th Annual International ACM SIGIR Conference on Research and Development in Information Retrieval (SIGIR '06)*. ACM, 2006, pp. 19–26.

[5] FlyRank AI Research Group, "Applied search intelligence: Longitudinal performance and ranking stability across enterprise search portfolios," FlyRank AI, San Francisco, CA, Technical Whitepaper, 2026.

[6] T.-Y. Liu, "Learning to rank for information retrieval," *Foundations and Trends in Information Retrieval*, vol. 3, no. 3, pp. 225–331, 2009.

[7] O. Chapelle and Y. Chang, "Yahoo! learning to rank challenge overview," in *Proceedings of the Learning to Rank Challenge*, ser. JMLR Workshop and Conference Proceedings, vol. 14, 2011, pp. 1–24.

[8] L. Breiman, "Random forests," *Machine Learning*, vol. 45, no. 1, pp. 5–32, 2001.

[9] T. Chen and C. Guestrin, "XGBoost: A scalable tree boosting system," in *Proceedings of the 22nd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining (KDD '16)*. ACM, 2016, pp. 785–794.

[10] F. Pedregosa, G. Varoquaux, A. Gramfort, V. Michel, B. Thirion, O. Grisel, M. Blondel, P. Prettenhofer, R. Weiss, V. Dubourg, J. Vanderplas, A. Passos, D. Cournapeau, M. Brucher, M. Perrot, and É. Duchesnay, "Scikit-learn: Machine learning in python," *Journal of Machine Learning Research*, vol. 12, pp. 2825–2830, 2011.

[11] S. Kaufman, S. Rosset, C. Perlich, and O. Stitelman, "Leakage in data mining: Formulation, detection, and avoidance," *ACM Transactions on Knowledge Discovery from Data (TKDD)*, vol. 6, no. 4, pp. 15:1–15:21, 2012.

[12] D. Sculley, G. Holt, D. Golovin, E. Davydov, T. Phillips, D. Ebner, V. Chaudhary, M. Young, J.-F. Crespo, and D. Dennison, "Hidden technical debt in machine learning systems," in *Advances in Neural Information Processing Systems (NeurIPS 2015)*, vol. 28, 2015, pp. 2503–2511.

[13] R. Kohavi, "A study of cross-validation and bootstrap for accuracy estimation and model selection," in *Proceedings of the 14th International Joint Conference on Artificial Intelligence (IJCAI '95)*, vol. 2, 1995, pp. 1137–1145.

[14] F. Provost, T. Fawcett, and R. Kohavi, "The case against accuracy estimation for comparing induction algorithms," in *Proceedings of the 15th International Conference on Machine Learning (ICML '98)*, 1998, pp. 445–453.

[15] Google Search Central, "Creating helpful, reliable, people-first content," https://developers.google.com/search/docs/fundamentals/creating-helpful-content, 2024, accessed: Oct. 2026.

[16] N. V. Chawla, K. W. Bowyer, L. O. Hall, and W. P. Kegelmeyer, "SMOTE: Synthetic minority over-sampling technique," *Journal of Artificial Intelligence Research*, vol. 16, pp. 321–357, 2002.

[17] I. Guyon and A. Elisseeff, "An introduction to variable and feature selection," *Journal of Machine Learning Research*, vol. 3, pp. 1157–1182, 2003.

[18] T. Fawcett, "An introduction to ROC analysis," *Pattern Recognition Letters*, vol. 27, no. 8, pp. 861–874, 2006.