Status	Finished
Started	Monday, 19 October 2026, 4:51 PM
Completed	Monday, 19 October 2026, 4:55 PM
Duration	4 mins 49 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

- a. (16,17,18,19) ✓
- b. Error
- c. (16,17,18)
- d. (25,19,18,17)

Question **2**

Correct

Mark 1.00 out of 1.00

What will set1|set2 do?

```
If set1={"a","b",3}
set2={3,7}
```

- a. Elements of set2 will get appended to set1
- b. A new set will be created with the unique elements of set1 and set2.
- c. A new set will be created with the elements of both set1 and set2 ✓
- d. Elements of set1 will get appended to set2

Question **3**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={2,5,3}

set2={3,1}

set3={}

set3=set1&set2

print(set3)
```

a. {3} ✓

b. {2,5,1}

c. {2,5,3,1}

d. {}

Question **4**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. Name Error

b. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

c. TypeError: update() doesn't allow list as a argument.

d. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

Question **5**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)
>>>[t[i] for i in range(0, len(t), 2)]
```

a. [1, 4, 8] ✓

b. [1, 2, 4, 3, 8, 9]

c. (1, 4, 8)

d. [2, 3, 9]

Question **6**

Correct

Mark 1.00 out of 1.00

A python tuple can be created without using any parentheses. (True/False)

a. False

b. True ✓

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the following code?

```
aTuple = (10, 20, 30, 40, 50, 60, 70, 80)
print(aTuple[2:5], aTuple[:4], aTuple[3:])
```

a. (30, 40, 50) (10, 20, 30, 40)

b. (30, 40, 50) (10, 20, 30, 40) (40, 50, 60, 70, 80) ✓

c. (10, 20, 30, 40) (40, 50, 60, 70, 80)

d. (30, 40, 50)(40, 50, 60, 70, 80)

Question **8**

Correct

Mark 1.00 out of 1.00

What is the output of the following

```
set1 = {1, 2, 3, 4, 5}
set2 = {6, 7, 1, 3, 4, 8, 2, 5}

print(set1.issubset(set2))
print(set2.issuperset(set1))
```

a. False
True

b. True
False

c. False
False

d. True ✓
True

Question **9**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. {40, '10', 50, 20, 60, 30}

b. {40, 10, '10', 50, 20, 60, 30} ✓

c. {40, 10, 50, 20, 60, 30}

d. SynatxError: Different types cannot be used with sets

Question **10**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

a. It will throw an error as there are two 0 while creating the set.

b. {0,0,9}

c. {9}

d. {0,9} ✓

Question **11**

Correct

Mark 1.00 out of 1.00

What will the below Python code do?

```
set1={2,3}

set2={3,2}

set3={2,1}

if(set1==set2):

    print("yes")

else:

    print("no")

if(set1==set3):

    print("yes")

else:

    print("no")
```

a. Yes, Yes

b. Yes, No ✓

c. No, No

d. "==" is not supported for set in Python

Question **12**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

my_t1 = (1, 2, 3, 4)

my_t1.append((5, 6, 7))

print(len(my_t1))

- a. 1
- b. 2
- c. Error ✓
- d. 5

Question **13**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

- a. (12)
- b. (55,78,64,25)
- c. Error ✓
- d. 12

Question **14**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
list1=[1,3,4,2]

x=list1.pop(2)

print(set([x]))
```

- a. {1,3,2}
- b. {4} ✓
- c. {2}
- d. {1,3,4}

Question **15**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

a. None of these

b. A tuple is unordered

c. A tuple maintains the order of items ✓

d. We can change the tuple once created