

Day 17 – Microsoft Entra ID Application Permissions

Objective

Learn how Microsoft Entra applications use API permissions and understand the difference between delegated and application permissions.

Skills You'll Learn

- App Registrations
- API Permissions
- Microsoft Graph
- Delegated Permissions
- Application Permissions

Step 1 – Open Your App Registration

Go to:

Microsoft Entra admin center

→ Identity

→ Applications

→ App registrations

→ IAM-Lab-App

Screenshot 1

- IAM-Lab-App Overview

IAM-Lab-App

Search Deactivate Delete Endpoints

- Overview
- Quickstart
- Integration assistant
- Diagnose and solve problems
- Manage
 - Branding & properties
 - Authentication (Preview)
 - Certificates & secrets
 - Token configuration
 - API permissions
 - Expose an API
 - App roles
 - Owners

Essentials

Display name : [IAM-Lab-App](#) Client credentials : [Add a certificate or secret](#)
Application (client) ID : 5880804f-6ecb-4c8f-8954-a76aa9e60bd7 Redirect URIs : [1 web, 0 spa, 0 public client](#)
Object ID : 81b17707-5416-4702-8c6d-f660912c546f Application ID URI : [Add an Application ID URI](#)
Directory (tenant) ID : 1e95522d-4bbb-4ade-b300-c9049924da7f Managed application in L... : [IAM-Lab-App](#)
Supported account types : [My organization only](#) State : [Activated](#)

Azure Active Directory Authentication Library (ADAL) and Azure AD Graph no longer receive new feature updates. We continue to provide technical support and security updates. Applications should be upgraded to Microsoft Authentication Library (MSAL) and Microsoft Graph. [Learn more](#)

[Get Started](#) [Documentation](#)

Build your application with the Microsoft identity platform

The Microsoft identity platform is an authentication service, open-source libraries, and application management tools. You can create modern, standards-based authentication solutions, access and protect APIs, and add sign-in for your users and customers. [Learn more](#)

Step 2 – Open API Permissions

In the left menu, click:

API permissions

Review the permissions already assigned (for example, **User.Read**).

Screenshot 2

- API Permissions page

IAM-Lab-App | API permissions

Search Refresh Got feedback?

- Overview
- Quickstart
- Integration assistant
- Diagnose and solve problems
- Manage
 - Branding & properties
 - Authentication (Preview)
 - Certificates & secrets
 - Token configuration
 - API permissions
 - Expose an API
 - App roles
 - Owners
 - Roles and administrators
 - Manifest
- Support + Troubleshooting
 - New support request

Granting tenant-wide consent may revoke permissions that have already been granted tenant-wide for that application. Permissions that users have already granted on their own behalf aren't affected. [Learn more](#)

The "Admin consent required" column shows the default value for an organization. However, user consent can be customized per permission, user, or app. This column may not reflect the value in your organization, or in organizations where this app will be used. [Learn more](#)

Configured permissions

Applications are authorized to call APIs when they are granted permissions by users/admins as part of the consent process. The list of configured permissions should include all the permissions the application needs. [Learn more about permissions and consent](#)

[Add a permission](#) [Grant admin consent for Default Directory](#)

API / Permissions name	Type	Description	Admin consent requ...	Status
Microsoft Graph (1)				
User.Read	Delegated	Sign in and read user profile	No	...

To view and manage consented permissions for individual apps, as well as your tenant's consent settings, try [Enterprise applications](#).

Step 3 – Add a Permission

1. Click **+ Add a permission**.
2. Select **Microsoft Graph**.
3. Choose **Delegated permissions**.
4. Search for:

User.ReadBasic.All

5. Check the box.
6. Click **Add permissions**.

If you don't have permission to grant admin consent, that's okay. You only need to add the permission for this lab.

Screenshot 3

- Added API Permission

Home > Named locations > Audit Logs > Sign-in events > Groups | All groups > IAM-Lab-Security | Members > Alex Brown > App registrations > IAM-Lab-App

 IAM-Lab-App | API permissions ✎ ⋮

Search

Overview

Quickstart

Integration assistant

Diagnose and solve problems

Manage

Branding & properties

Authentication (Preview)

Certificates & secrets

Token configuration

API permissions

Expose an API

App roles

Owners

Roles and administrators

Manifest

Support + Troubleshooting

New support request

Refresh Got feedback?

You are editing permission(s) to your application, users will have to consent even if they've already done so previously.

Granting tenant-wide consent may revoke permissions that have already been granted tenant-wide for that application. Permissions that users have already granted on their own behalf aren't affected. [Learn more](#)

The "Admin consent required" column shows the default value for an organization. However, user consent can be customized per permission, user, or app. This column may not reflect the value in your organization, or in organizations where this app will be used. [Learn more](#)

Configured permissions

Applications are authorized to call APIs when they are granted permissions by users/admins as part of the consent process. The list of configured permissions should include all the permissions the application needs. [Learn more about permissions and consent](#)

+ Add a permission

✓ Grant admin consent for Default Directory

API / Permissions name	Type	Description	Admin consent requ...	Status
Microsoft Graph (2)				
User.Read	Delegated	Sign in and read user profile	No	...
User.ReadBasic.All	Delegated	Read all users' basic profiles	No	...

To view and manage consented permissions for individual apps, as well as your tenant's consent settings, try [Enterprise applications](#).

Step 4 – Compare Permission Types

Review the difference between:

- **Delegated permissions** – Used when a signed-in user is present. The app acts on behalf of that user.
- **Application permissions** – Used by background services or daemons. The app acts as itself and typically requires administrator consent.

