

# Skylar IQ QA Tool

---

A practical guide for testers

---

|                 |                                                                                       |
|-----------------|---------------------------------------------------------------------------------------|
| <b>Version</b>  | 3.6                                                                                   |
| <b>Updated</b>  | May 2026                                                                              |
| <b>Audience</b> | QA testers running automated tests against the Celerant SQL AI Engine and Site Search |

# Contents

---

|     |                              |    |
|-----|------------------------------|----|
| 1.  | Get access                   | 3  |
| 2.  | The two test types           | 4  |
| 3.  | Excel format                 | 5  |
| 4.  | Running a SQL AI Engine test | 6  |
| 5.  | Running a Site Search test   | 7  |
| 6.  | Reading a run report         | 9  |
| 7.  | Status meanings              | 10 |
| 8.  | Stopping a run               | 10 |
| 9.  | Per-user data isolation      | 11 |
| 10. | Common issues / FAQ          | 11 |
| 11. | Sharing results              | 13 |
| 12. | Quick reference card         | 13 |
| 13. | Need help                    | 14 |

**What this tool does.** A web app that drives the Celerant **SQL AI Engine** and **Site Search** through real browser automation, captures every API call, and produces detailed HTML reports. You upload a list of test inputs; the tool runs them; you read the report.

# 1 • Get access

---

## The live URL

```
https://ai-platform-auto-tester.thankfulmushroom-67b2c86a.centralus.azurecontainerapps.io/
```

Bookmark this — you'll use it daily.

## Sign in

You have two paths.

### Path A — Use the shared QA account

|          |                             |
|----------|-----------------------------|
| Email    | qa@aiplatformautotester.com |
| Password | AiPlatform2026              |

Use this for quick testing. Note: everyone using this account shares the same runs, test files, and presets — fine for a small team but won't isolate your work.

### Path B — Create your own account (recommended)

1. Open the URL → click **Create one** under the sign-in form.
2. Enter your name, work email, and a password (≥ 8 characters).
3. Click **Create account** — you're in.

Your runs, uploaded test files, and saved login presets are private to you. No other tester can see them.

## 2 · The two test types

| TEST TYPE                                                                                              | WHAT IT TESTS                                                                                                                                                                              | INPUTS NEEDED                                                             |
|--------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------|
|  <b>SQL AI Engine</b> | A Celerant tenant's Skylar IQ chat box: types every NL question, captures the <code>generate-sql</code> → <code>run-sql</code> → <code>generate-viz</code> chain, validates response shape | Login URL of the tenant, username, password, .xlsx of questions           |
|  <b>Site Search</b>   | An ssLibrary search widget: types each keyword, captures <code>search_keywords</code> and <code>search_results</code> , validates that products come back                                  | Page URL or uploaded ssLibrary bundle, JWT credentials, .xlsx of keywords |

## 3 · Excel format

---

Both test types use the same xlsx shape — column A is the test input.

### For SQL AI Engine

| COLUMN A — NATURAL-LANGUAGE QUESTION         | COLUMN B — EXPECTED SQL ( <i>OPTIONAL</i> ) |
|----------------------------------------------|---------------------------------------------|
| What are my top 10 selling brands this year? | <i>(leave blank)</i>                        |
| Show inventory cost by department            | <i>(leave blank)</i>                        |

### For Site Search

| COLUMN A — SEARCH KEYWORD | COLUMN B         |
|---------------------------|------------------|
| shirt                     | <i>(ignored)</i> |
| boots                     | <i>(ignored)</i> |
| knife                     | <i>(ignored)</i> |

### Rules

- The first row may be a header ( **question** , **keyword** , **query** , etc.) — auto-skipped.
- Empty rows are skipped.
- Anything past column B is ignored.

**Tip.** A 12-question sample lives at `~/Downloads/que_test-1.xlsx` — ask Farhan for it if you don't have it yet.

## 4 · Running a SQL AI Engine test

---

1. Click **+ New Run** in the top right.
2. **Test type:** 🧠 **SQL AI Engine**
3. Fill in:

|                       |                                                                                                                                                    |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOGIN URL</b>      | The full Celerant login URL of the tenant — e.g.<br><code>https://209.208.39.72:8443/backoffice/?mid=100</code>                                    |
| <b>USERNAME</b>       | The Celerant username for that tenant                                                                                                              |
| <b>PASSWORD</b>       | The Celerant password                                                                                                                              |
| <b>MACHINE ID</b>     | <code>100</code> by default — change if your tenant uses something else                                                                            |
| <b>SQL AGENT PATH</b> | <code>/backoffice/mv-assets/index-modern.html#/listScreen/sqlagent</code><br>(default — leave alone unless tenant deploys at a non-standard route) |

4. **Questions: Upload new file** → pick your `.xlsx` — or **Use saved test file** if you've uploaded one before to the **Test Files** page.
5. Click ► **Start QA Run**.

You'll be taken to the run page. Watch the live progress:

- **PASS / PARTIAL / FAIL / TIMEOUT** counters update as queries run.
- **Last 5 queries** table shows the most recent results — click any row to drill down.
- **Event log** tab streams every event line from the runner.
- **All queries** tab shows every query in a searchable, filterable table.

A typical 12-question run takes 2–5 minutes.

## 5 · Running a Site Search test

1. + New Run →  Site Search

2. Where is your search page?

- **Live URL** — paste the URL of the page hosting the search widget (anywhere publicly reachable).
- **Use uploaded bundle** — pick from your saved bundles (upload one first on **Test Pages** if you don't have one yet).

3. **Search input selector:** `#searchbox` by default — only change if the page uses a different selector.

4. **Tenant override** (*recommended*) — substitute the tenant config that the page hardcodes:

| FIELD        | EXAMPLE FOR THE DEMO                        |
|--------------|---------------------------------------------|
| Org ID       | <code>r222ipid</code>                       |
| Console URL  | <code>https://celerantai.com/</code>        |
| JWT username | <code>r222ipid</code> (blank → uses Org ID) |
| JWT password | <code>W0rkH0us3!</code>                     |

Leave these blank to use whatever the page itself passes to `ssLibrary.init(...)`. Filling them lets you point the same page at any tenant.

5. **Search keywords:** upload your .xlsx.

6. **Start QA Run.**

A 20-keyword run typically takes 2–3 minutes.

### When to upload a bundle

Use **Test Pages** → + **Upload bundle** if:

- You have only the `dist/` folder of an ssLibrary build ( `.bundle.js` + `.css` ) but *no public URL* to host it.
- Zip the folder before uploading: `zip -r my-bundle.zip dist/ -x "__MACOSX*" "*.*DS_Store" ".*_*"` — the `-x` flags strip macOS metadata.
- Upload the zip → the tool generates a private hosted page at `/hosted/<id>/index.html` and runs against that.

## 6 · Reading a run report

---

When the run finishes, four primary outputs are available from the run page.

### A · The HTML report

Click **Open report** ↗. You'll see:

- **Executive summary** — total / PASS / PARTIAL / FAIL / TIMEOUT counts, avg + max duration.
- **API health** table — captured / HTTP-2xx / usable-payload counts per endpoint.
- **Failing queries + Partial / warnings** sections with reasons.
- **Per-query detail** — collapsible blocks for every query showing:
  - Status, duration, timestamps
  - Captured **request**: method, URL, headers (sanitized), body
  - Captured **response**: status, headers, body
  - Inline screenshots (input state + result state)
  - Runner notes — every selector tried, every fallback
  - All XHR/fetch calls table

### B · Download the run as a zip

↓ **Download report (zip)** — packages REPORT.html + screenshots + raw per-query JSONs into one file you can email or attach to a JIRA ticket.

### C · Download just the failed queries

↓ **Download failed queries (xlsx)** — a re-runnable Excel of only the FAIL/PARTIAL/TIMEOUT queries, same column shape as the input. Hand it to a developer to fix the underlying bug, then re-run that same xlsx after their patch lands.

### D · CSV export

**Export CSV** — a flat results table for spreadsheet pivots. One row per query.

## 7 · Status meanings

---

| BADGE                                                                             | WHAT IT MEANS                                                                                         |
|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
|  | All assertions green — captured both API calls, both 2xx, response payload had usable data.           |
|  | At least one warning — e.g. zero rows returned, or columns mismatch between run-sql and generate-viz. |
|  | A hard failure — required call missing or HTTP non-2xx.                                               |
|  | A request didn't return within 120 seconds.                                                           |

## 8 · Stopping a run

---

If you started a run and want to abort:

1. On the run page, click the red  **Stop run** button.
2. Confirm — the runner finishes the current query, then stops cleanly.
3. The report is still generated for queries that already completed.

## 9 · Per-user data isolation

---

| OBJECT                  | VISIBILITY                       |
|-------------------------|----------------------------------|
| Runs                    | Private — only you see your own. |
| Test files (saved xlsx) | Private.                         |
| Login presets           | Private.                         |
| Hosted bundles          | Private.                         |

Bob can't view, list, or even guess the URLs to Alice's runs/files even with the run ID. Each user has a fully separate workspace.

# 10 · Common issues / FAQ

---

## "Login failed at ... : Machine ID is empty"

Wrong **Machine ID** for the tenant. Try `100` first, or get the right value from the Celerant admin for that client.

## Lots of TIMEOUTs

The Celerant LLM endpoint ( `celerantai.com` ) can be slow for some questions. Bump **run-sql timeout** to `300000` – `600000` (5–10 min) under **Advanced timeouts** on the New Run page.

## Site Search popup not showing in screenshots

The page must be HTTPS or localhost — `crypto.subtle` only works in secure contexts. If you're using a tunnel (cloudflared/ngrok), the auto-issued HTTPS URL works. If pointing at a plain HTTP URL, the tool falls back to a polyfill but some real-world pages need the genuine API.

## "file:// URLs cannot be reached from inside Docker"

You can't point the tool at a `file:///Users/...` path on your laptop — the QA runner runs on Azure, with no access to your local files. Either:

- Deploy the page to a public URL (or a tunnel), then paste that URL.
- Or upload the `dist/` zip via **Test Pages** so the tool serves it for you.

## "Search keywords / search\_results call missing"

The bundle's `ssLibrary.init(...)` failed to authenticate. Most often: wrong **JWT credentials** in the Tenant Override section. Try the demo's `r222ipid` / `W0rkH0us3!` first to verify the flow works, then plug in your tenant's real creds.

## My run is stuck "running" but nothing is happening

If the tool was redeployed while a run was in progress, the runner thread can die. Click ■ **Stop run** on that run to mark it failed. Start a new one.

## 11 · Sharing results

---

Three good patterns:

1. **Just the URL** — paste the full `/jobs/<run-id>` URL. Anyone signed in can view it.
2. **Download the zip** + email — recipient extracts and opens REPORT.html offline.
3. **Download failed queries (xlsx)** + tag the developer → they fix the bug → re-run the same xlsx after patch lands.

## 12 · Quick reference card

---

|                 |                                                                                                                                                                                                   |
|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| URL             | <code>https://ai-platform-auto-tester.thankfulmushroom-67b2c86a.centralus.azurecontainerapps.io/</code>                                                                                           |
| SHARED QA LOGIN | <code>qa@aiplatformautotester.com</code> / <code>AiPlatform2026</code>                                                                                                                            |
| SIGN UP         | <code>/signup</code> (private workspace)                                                                                                                                                          |
| NEW RUN         | + New Run (top right)                                                                                                                                                                             |
| TEST TYPES      |  SQL AI Engine  Site Search |
| EXCEL COLUMN A  | The test input (question or keyword)                                                                                                                                                              |
| STOP A RUN      | red ■ <b>Stop run</b> button on the run page                                                                                                                                                      |
| OPEN REPORT     | blue <b>Open report</b> ↗ button on the run page                                                                                                                                                  |
| DOWNLOAD ZIP    | ↓ Download report (zip)                                                                                                                                                                           |
| JUST FAILURES   | ↓ Download failed queries (xlsx)                                                                                                                                                                  |

## 13 · Need help?

---

Contact Farhan or post in the QA channel. Common questions are answered in section 10. If your issue isn't, paste these three things:

1. The run ID (top of the run page).
2. A screenshot of the failing query's detail page.
3. What you expected vs. what happened.

— and we'll diagnose it.

---

Skylar IQ QA Tool — Internal QA documentation · Version 3.6 · May 2026  
Not for external distribution without permission.