

## **QUALITY ASSURANCE**

Diperiksa oleh :

MR&Mgr. QA

Disetujui oleh:

No. Registrasi : F.07.03.00.13

: 8 Desember 2015

Status Revisi : 0

Plant Manager Halaman :1/1

Tanggal

## PENGUJIAN BARANG JADI KABEL MEDIUM

PENGUJIAN BARANG JADI KABEL MEDIUM

Disusun oleh:

QA Engineer

No order Type		:																		Tegang	an	:		
		:	:															3	:					
Ukuraı		:																		Standar	:			
F.07.03.00	0.13									l											Ι.			
No	Diameter (mm)							1				Tebal (mm								1	Armo	ur (mm)		n (mm)
		Kondukto			Isolasi	T	Filler	Armour	Selubung			1	Isolasi				ter semincond.		Filler	Selubung	Dia. Wire		Dia. Wire	Copper tape
	Merah	Kuning	Hitam	Merah	Kuning	Hitam				Merah	Kuning	Hitam	Merah	Kuning	Hitam	Merah	Kuning	Hitam		-		(T x L)	<b>——</b>	(T x L)
																							<u> </u>	
																							<del>                                     </del>	
	+																							
Standar	Min.	Min.																						
	Nom.																							
	Maks.																							
Water	blocking:	kondukti	or / Scree	n .				<u> </u>					<u> </u>			<u> </u>				<u> </u>			i	
Visual :		Kondukti	01 / 30100	-11																				
Penano	daan kabe	el : 																						
Tegangan: kV/5 menit (passed / failed) Tahanan conductor:									Tahanan isolasi : Hasil uji : Passed / Failed															
Partial dischargekV/1 menit						Merah : Ω/km					Merah : Μ.Ω													
Merah :pC Kuning :						: Ω/km				Kuning : Μ.Ω														
Kuning : pC Hitam :								Ω/km		Hitam : Μ.Ω														
Hitam :pC Max. standar :pC Max. standa					ndar :	r:Ω/km				Min. standar : M.Ω														
Catatan :																			Kab	ag. QA	Pr	enguji		
																							Ì	
																							Ì	
																						_		_