



PRODUCT DATA SHEET · INSULATED DOORS

Hinged Door

Hinged door for negative temperatures down to -20°C , with a CSI handle certified to EN 179:2008 and a heating cable on the blade. 92 mm polyurethane-insulated blade, available in one-blade or two-blade versions.

Applications

- Meat processing plants and slaughterhouses
- Cheese factories
- Fruit and vegetable preservation stores
- Food warehouses
- Shops: delicatessens, fish shops, ice cream parlours
- Fish processing plants and the ice cream industry

Key data

Application	Food processing and storage, -18°C to -20°C
Blade thickness	92 mm
Insulation	Polyurethane, 42 kg/m³
Handle	CSI, certified EN 179:2008
Heating	Heating cable on the blade
Versions	One blade or two blades
Steel thickness	0.5 mm
Finish	Polyester, RAL 9003
Max. size, one blade	1500 × 2500 mm

Suitable for cold rooms used for the processing and preservation of foods at negative temperature.

Specification

COMPONENT	SPECIFICATION
Steel thickness	0.5 mm
Heater	Double heater
Insulation type	Polyurethane foam
Closed cell structure	95%
Tensile strength	3.0 kg/m ²
Compressive strength	1.62 kg/m ²
Density	42 kg/m ³
Resistance	Resistant to fire and rust; waterproof
Colour	Polyester, RAL 9003, 25 micron

Standard dimensions

One-blade version

- Up to 1200 × 2500 mm: blade with the CSI handle only.
- From 1200 × 2500 mm up to 1500 × 2500 mm: blade with CSI handle plus closing latch (additional spring closing system).

Two-blade version

- A mobile blade (the right one, unless otherwise specified) and a semi-fixed blade with 2 internal hatches, 1 above and 1 below.
- Total width can be up to double that of the one-blade version.
- The two blades can have different widths. The fixed blade is usually requested narrower.



(Fig1): hinged door