



PRODUCT DATA SHEET · INSULATED DOORS

Sliding Door Freezer

Sliding door for cold rooms at negative temperature, down to -20°C , with the patented "Mirror" sliding system. 92 mm polyurethane-insulated blade, available in one-blade or two-blade versions.

Applications

- Meat processing plants and slaughterhouses
- Cheese factories
- Fruit and vegetable preservation stores
- Food warehouses
- Shops: delicatessens, fish shops, ice cream parlours
- Fish processing plants and the ice cream industry

Key data

Application	Freezer rooms, down to -20°C
Blade thickness	92 mm
Insulation	Polyurethane, 40 kg/m ³
Versions	One blade or two blades
Sliding system	Patented "Mirror" model
Steel thickness	0.5 mm
Finish	RAL 9010, food-grade plastic-coated sheet
Standard sizes	Up to 3000 × 4000 mm

Suitable for the preservation, processing and seasoning of foods at negative temperature.

Specification

COMPONENT	SPECIFICATION
Steel thickness	0.5 mm
Blade edge	Anodized aluminium, 92 mm thickness
Blade covering	Plastic-coated metal sheet for food application, RAL 9010, 5/10 mm thickness
Heater	Included
Outside handle	Lever
Inside handle	Lever
Side gaskets	EPDM double-density gasket on 3 sides
Lower gasket	PVC
Frame and side-frame	"L" 110/60 profile in PVC, RAL 9010. Thermo-welded at 45° up to 160 mm thickness; above 160 mm, assembled at 90° with joints
Counter-frame	PVC, RAL 9010, thermo-welded at 45°
Floor threshold	Flush floor, S/3 model (without threshold)

Standard dimensions up to 3000 × 4000 mm. When both sides exceed 2500 mm, the blade is divided horizontally in two parts: the lower part is made at H = 1250 mm and the upper part takes the difference. In that case the frame is supplied dismounted.

Sliding and frame systems

Sliding system. The patented "Mirror" system is fully symmetrical, so the opening direction can be changed without any adjustment. The sliding profile is anodized extruded aluminium with anti-fall section ramps, or falling bends. These are assembled on the closing side of the door and press the door firmly against the frame, giving the best insulation between the inside and the outside of the cold room.

Cover (optional). Extruded anodized aluminium. It opens on hinges along its top edge for inspection and cleaning.

Pulleys. Plastic pulleys carry the door along the "Mirror" sliding system, adjustable in both height and depth.

Rear register. Adjustable; guides the door along the lower guides.

Lower closing hook. Plastic, fixed on the closing side of the frame. As the door closes, it ensures a hermetic contact between the door and the frame.

Hook striker. Plastic, fixed on the blade on the handle side. On closing it engages the lower hook to hold the door hermetically against the frame.

Larger doors. Above the standard dimensions, the door is built with heavy-duty hardware in place of standard parts, for example stainless-steel pulleys with aluminium wheels and a stainless-steel sliding rail.

Door, accessories and upper rail



Fig (1): Sliding door



Fig (2): Sliding door accessories



Fig (3): Sliding upper rail