SERVICE REPORT PREVENTIVE MAINTENANCE PRECISION AIR CONDITIONING (PAC) PT. HM SAMPOERNA SUKOREJO PLANT

Loka	si :	Model Unit :			Team Engine	er List :		Date :
Code	e unit :	No. Seri :			†			Start PM:
Nom	or Unit :	Periode :						Close PM:
	CKLIST TEAM BRIEFING						01/	?
INTE	NSIVE SAFETY BRIEFING TEAR	M					OK	ſ
Α	Filter Section							
	Item Checked	Spec. Range / Cond. Std.	Actual Ch	ecked	Item Che	cked	Spec. Range	Actua
	1. Check/Replace filters	Clean or Dirty			5. Clean con	densate	Clean or Dirty	
	2. Grille area unrestricted	OK / Not OK			6. Clean trap condensate		Clean or Dirty	
	3. Wipe section clean	Clean or Dirty			7. Check/Tes	t filter-	Ola sa Nis	
	4. Coil clean	Clean or Dirty			clog switch o	peration	Ok or No	
В	Blower Section							
	Item Checked	Spec. Range /	Blower	·1	Blower	· 2	Blower	. 3
	item onecked	Cond. Std.	Before	After	Before	After	Before	After
	1. Mounting bolts tight	Ok or No						
	2. Fan-guard bolts tight	Ok or No						
	3. Impeller spins freely	Ok or No						
	4. Check/Test air sail switch	Ok or No						
	5. Motor amp draw	FLA L1 = A	L1	L1	L1	L1	L1	L1
	Compare to nameplate	FLA L2 = A	L2	L2	L2	L2	L2	L2
	amps	FLA L3 = A	L3	L3	L3	L3	L3	L3
	6. Check belt tension and condition	Ok or No						
	7. Check sheave/pulley	Ok or No						
С	7. Check sheave/pulley Reheat	Ok or No						
С	7. Check sheave/pulley Reheat Item Checked	Spec. Range /	Heater Before		Heater		Heater Before	
С	Reheat Item Checked	Spec. Range / Cond. Std.	Heater Before	1 After	Heater Before	2 After	Heater Before	3 After
C	Reheat Item Checked 1. Reheat amp draw 2. Check Heater	Spec. Range /						
С	Reheat Item Checked 1. Reheat amp draw 2. Check Heater Resistance	Spec. Range / Cond. Std. FLA = A 18-22 ohm						
С	Reheat Item Checked 1. Reheat amp draw 2. Check Heater	Spec. Range / Cond. Std.						
	Reheat Item Checked 1. Reheat amp draw 2. Check Heater Resistance 3. Inspect elements 4. Check wire connections	Spec. Range / Cond. Std. FLA = A 18-22 ohm Ok or No Ok or No						
D	Reheat Item Checked 1. Reheat amp draw 2. Check Heater Resistance 3. Inspect elements	Spec. Range / Cond. Std. FLA = A 18-22 ohm Ok or No Ok or No		After	Before			
	Reheat Item Checked 1. Reheat amp draw 2. Check Heater Resistance 3. Inspect elements 4. Check wire connections Steam Generating Humidified Item Checked 1. Humidifier amp draw	Spec. Range / Cond. Std. FLA = A 18-22 ohm Ok or No Ok or No	Before	After	Before	After	Before	After Spec.
	Reheat Item Checked 1. Reheat amp draw 2. Check Heater Resistance 3. Inspect elements 4. Check wire connections Steam Generating Humidified	Spec. Range / Cond. Std. FLA = A 18-22 ohm Ok or No Ok or No Spec. Range	Before	After	Before	After Checked	Before	After Spec. Range
	Item Checked 1. Reheat amp draw 2. Check Heater Resistance 3. Inspect elements 4. Check wire connections Steam Generating Humidifie Item Checked 1. Humidifier amp draw 2. Check drain valve/drain lines/trap for damage/clogs/leaks 3. Check water fill valve and all supply lines/connection for	Spec. Range / Cond. Std. FLA = A 18-22 ohm Ok or No Ok or No Spec. Range	Before	After	Item 4. Check cor 5. Clean stra	After Checked	Before	Spec. Range Ok or No
D	Item Checked 1. Reheat amp draw 2. Check Heater Resistance 3. Inspect elements 4. Check wire connections Steam Generating Humidified Item Checked 1. Humidifier amp draw 2. Check drain valve/drain lines/trap for damage/clogs/leaks 3. Check water fill valve and all supply lines/connection for leaks	Spec. Range / Cond. Std. FLA = A 18-22 ohm Ok or No Ok or No Spec. Range	Before	After	Item 4. Check cor 5. Clean stra 6. Check huntank)	After Checked Indition of stea	Before am hose (Boiler	Spec. Range Ok or No Ok or No
	Item Checked 1. Reheat amp draw 2. Check Heater Resistance 3. Inspect elements 4. Check wire connections Steam Generating Humidifie Item Checked 1. Humidifier amp draw 2. Check drain valve/drain lines/trap for damage/clogs/leaks 3. Check water fill valve and all supply lines/connection for	Spec. Range / Cond. Std. FLA = A 18-22 ohm Ok or No Ok or No Spec. Range	Before	After	Item 4. Check cor 5. Clean stra 6. Check huntank) 7. Check ope	After Checked Indition of steadiner Indifier bottle Paration of hum	Before am hose (Boiler	Spec. Range Ok or No Ok or No
D	Item Checked 1. Reheat amp draw 2. Check Heater Resistance 3. Inspect elements 4. Check wire connections Steam Generating Humidified Item Checked 1. Humidifier amp draw 2. Check drain valve/drain lines/trap for damage/clogs/leaks 3. Check water fill valve and all supply lines/connection for leaks	Spec. Range / Cond. Std. FLA = A 18-22 ohm Ok or No Ok or No Spec. Range	Before	After	Item 4. Check cor 5. Clean stra 6. Check huntank)	After Checked Indition of steadiner Indifier bottle Paration of hum	Before am hose (Boiler	Spec. Range Ok or No Ok or No
D	Item Checked 1. Reheat amp draw 2. Check Heater Resistance 3. Inspect elements 4. Check wire connections Steam Generating Humidified Item Checked 1. Humidifier amp draw 2. Check drain valve/drain lines/trap for damage/clogs/leaks 3. Check water fill valve and all supply lines/connection for leaks Electrical Panel	Spec. Range / Cond. Std. FLA = A 18-22 ohm Ok or No Ok or No Spec. Range A Ok or No	Before	ecked	Item 4. Check cor 5. Clean stra 6. Check huntank) 7. Check ope	After Checked Indition of steadiner Indifier bottle Paration of hum	Before am hose (Boiler	Spec. Range Ok or No Ok or No
D	Item Checked 1. Reheat amp draw 2. Check Heater Resistance 3. Inspect elements 4. Check wire connections Steam Generating Humidifier Item Checked 1. Humidifier amp draw 2. Check drain valve/drain lines/trap for damage/clogs/leaks 3. Check water fill valve and all supply lines/connection for leaks Electrical Panel Item Checked	Spec. Range / Cond. Std. FLA =	Before	ecked	Item 4. Check cor 5. Clean stra 6. Check huntank) 7. Check ope	After Checked Indition of steadiner Indifier bottle Paration of hum	Before am hose (Boiler	Spec. Range Ok or No Ok or No

Ε	Electrical Panel								
	Item Checked	Spec. Range				tual cked			Keterangan
		/ Cond. Std.		Before	Cite	ckeu	After		_
	4. Voltage Line to								
	Neutral	220 + 10%	L1/L2/L3 =		V	L1/L2/L3 =		V	
	Ground	220 1 1070							
	5. Voltage Line to Line	380 + 10%	L1L2/L2L3/L1	L3 =	V	L1L2/L2L3/L	1L3 =	V	
	6. Frequency	50 + 10%	F =		Hz	F =		Hz	
E	Controls	Constant						Cmaa	
	Item Checked	Spec. Range / Cond. Std.	Actual	Checked	I	tem Check	ed	Spec. Range	Actual Checked
	1. Check/Verify control operation	Ok or No			3. Check/ detection	Test water- device		Ok or No	
	2. Check/Test changeover device	Ok or No			4. Check/ connection between in	on ndoor and		Ok or No	
G	Refrigeration Piping				outuooi u	iiito			
	Item Checked	Spec. Range	Actual	Checked	ı	tem Check	ed	Spec. Range	Actual Checked
	1. Check refrigerant lines (clamps secure/no rubbing/no leaks)	Ok or No				for restrict ure drop ac		Ok or No	5.1551.04
	2. Check for moisture (sight glass) Compressor Section	Ok or No							
	-	Spec. Range	Con	np. 1	Cou	mp. 2	Cor	np. 3	
	Item Checked	/	Before	After	Before	After	Before	After	Keterangan
		Cond. Std.	20.0.0	7 11101	20.0.0	7	20.0.0	7 11.01	
	Ampere draw Check oil level	OA A 55 - 90 PsiG							
	3. Check for oil leaks	200 - 300 PsiG							
	4. Check compressor mounts (springs/bushings)	Ok or No							
	5. Cap tubes (not rubbing)	Ok or No							
	6. Check/Re-torque wireconnections (inside compressor box)	Ok or No							
	7. Compressor	Hz							
	operation (vibration/noise)	dB							
	8. Check crank-case heater	Ok or No							
	fuses/operation 9. Check for refrigerantleaks	Ok or No							
	10. Suction pressure Circuit	55 - 90 PsiG							
	11. Discharge PressureCircuit	200 - 300 PsiG							
	12. Superheat Circuit	?C							
	13. Low-pressure switchcut out Circuit	Ok or No							

1 4	Ok or No						
L							
0							
w							
р							
r							
е							
s							
S							
u							
r e							
C							
u							
t							
i							
n							
C							
i r							
C							
u							
i							
t						-	_
	15. High pressure cut	Ola an Ni					
	out	Ok or No					
	Circuit						
	16. Sight Glass	Ok or No					

				
Condensor Section				
ltem Checked	Spec. Range	Before	After	Keteranga
Coil clean of debris (Clean coil ifrequired)	Clean or Dirty			
2. Fans free of debris	Clean or Dirty			
3. Fans securely mounted				
4. Motor bearings in good condi	tion			
5. Check all refrigerant lines for vibration isolation. Support as necessary	Ok or No			
6. Check for refrigerant leaks	Ok or No		-	
7. Check surge-protection device (ifinstalled) status-indicator lights	Ok or No			
8. Check/Re-torque wire connec	tions Ok or No			
9. Check contactors for pitting (replace if pitted)	Ok or No			
10. Verify operation sequence/se points	et			
11. Charge verification:				
a. Outdoor Ambient Temperatur	e			
b. Subcooling				
c. Indoor-unit Return-air Temper	rature			
d. Sight-glass level (if Lee- Temp orpumped refrigerant)				
12. Motor amp draw	FLA = A	L1/L2/L3 =	L1/L2/L3 = Amp	
General Function				
Item Checked Spec Ra	ange Actual	Item Check	Spec.	Actual

Item Checked	Spec. Range	Actual Checked	Item Checked	Spec. Range	Actual Checked
1. Cooling Test	Ok or No		4. Dehumidification Test	Ok or No	
2. Heating Test	Ok or No		5. Alarm Test	Ok or No	
3. Humidification Test	Ok or No				

	Spec. Range	Actual Checked	Item Checked	Spec. Range	Actual Checked
1. Temperature	?C		2. Humidity	%	
		NOTI	ES		
「emuan :					
Rekomendasi :					
		RESU	ME		
	0.450				
JOB COMPLETED ?	? YES	? NO, please check	on NOTES RUNN	ING HOURS :	
	? YES	APPRO	DVAL	ING HOURS :	
?	? YES	APPRO SIGNI	DVAL NG		Service By
	? YES	APPRO	DVAL ING Y	\$	Service By m Leader/Staf,
? Approved by	? YES	APPRO SIGNI Verified B	DVAL ING Y	\$	

Keterangan : Lembar 1 untuk Teknisi; Lembar 2 untuk User; Lembar 3 Arsip Kantor