

Name: Farida Ahmed Abdelaal

Track: Web & UI

Course Name: ES6

Date: 2/1/2026 “Day3”

Reflect API Documentation

1. Reflect.apply(target, thisArg, args)

- ✓ **Bt3mel eh:** De bt-nady function mo3ayana. Hya nafs fekret `Function.prototype.apply.call()`. Btsta5demha lamma tkoon 3ayz tdary function w tgarrabha testa5dem this mo3ayan ana elli m7dedah.
- ✓ **Arguments:**
 - **target:** El function nafsaha elli 3ayza asha8alha.
 - **thisArg:** El object elli 3ayza this yshawer 3leih gowa el function de.
 - **args:** Array feeh el parameters elli hab3athom lel function.
- ✓ **Btrga3 eh:** El nateg bta3 el function lamma eshta8alet.

2. Reflect.construct(target, args, newTarget)

- ✓ **Bt3mel eh:** De btel3ab dor new `ClassName()`. Bt3mel instance gdeed mn constructor/class. El 7etta el zyada hena hya newTarget, de bt5alleena n3ml object mn Class A, bas yewres (prototype) mn Class B.
- ✓ **Arguments:**
 - **target:** El constructor elli 3ayza anadeeh.
 - **args:** Array of arguments lel constructor.
 - **newTarget (Optional):** Constructor tany 3ashan nsta5dem el prototype bta3o.
- ✓ **Btrga3 eh:** El Object el gdeed elli et3amal (The new instance).

3. Reflect.defineProperty(target, prop, descriptor)

- ✓ Bt3mel eh: De bt3arrafa property gdeeda 3la object, aw bt3addel mwasafat property mawgoda (zay ennaha tkon writable: false).
- ✓ Far2 mohem: Object.defineProperty bdrab Error law fashalet, laken Reflect bthandle el mawdoo3 b hadawa w traga3 false.
- ✓ Arguments:
 - target: El object.
 - prop: Esm el property.
 - descriptor: Object feeh el tafaseel (value, writable, enumerable, configurable).
- ✓ Btrga3 eh: true law el property et3amal leeha define sa7, false law ma3rftsh.

4. Reflect.deleteProperty(target, prop)

- ✓ Bt3mel eh: De function badal el operator delete. Btmsa7 property mn el object.
- ✓ Arguments:
 - target: El object elli hanmsa7 menno.
 - prop: Esm el property elli htatmasa7.
- ✓ Btrga3 eh: true law etmsa7et (aw aslan mkanetsh mawgoda), w false law el property de mamnou3 ttmeset.

5. Reflect.get(target, prop, receiver)

- ✓ Bt3mel eh: De bt-read value of property. Zay target[prop].
- ✓ Btrga3 eh: El value bta3et el property.

6. Reflect.getOwnPropertyDescriptor(target, prop)

- ✓ Bt3mel eh: Law 3ayza a3rf el "metadata" bta3 property mo3ayana (ya3ny hal hya read-only? hal hya btban f el loops? Kda ya3ny).
- ✓ Arguments:
 - target: El object.
 - prop: Esm el property.
- ✓ Btrga3 eh: Object feeh el wasf ({ value: ..., writable: ..., etc }) aw undefined law el property msh mawgoda.

7. Reflect.getPrototypeOf(target)

- ✓ Bt3mel eh: Btgeeb el prototype el asly elli el object da wares menno (el internal [[Prototype]]).
- ✓ Far2: Hya zay Object.getPrototypeOf bs Strict aktar; lazem el target ykon object, law primitive (zay string aw number) bydrab Error.
- ✓ Btrga3 eh: El Prototype object, aw null law mafish.

8. Reflect.has(target, prop)

- ✓ Bt3mel eh: De function badal el operator in. Bt-check hal el property de mawgoda gowa el object AW f Prototype Chain bta3to?
- ✓ Arguments:
 - target: El object.
 - prop: Esm el property.
- ✓ Btrga3 eh: true law mawgoda, false law la2.

9. Reflect.isExtensible(target)

- ✓ Bt3mel eh: Bt-check hal masmo7 n-zawwed properties gdeeda lel object da wala la2? (Momken ykon ma3mollo Object.freeze aw preventExtensions).
- ✓ Btrga3 eh: true law yenfa3 nzawwed, false law ma3mollo lock.

10. Reflect.ownKeys(target)

- ✓ Bt3mel eh: Btgeeb array feeha KOL el keys elli gowa el object
- ✓ Leeha meeza De el function el wa7eeda elli btgeeb el String keys + Symbol keys ma3 ba3d f nafs el array.
- ✓ Btrga3 eh: Array of keys (Strings & Symbols).

11. Reflect.preventExtensions(target)

- ✓ Bt3mel eh: Bte2fel el object bel dabba w el mofta7. Btamna3 ay 7ad y-add properties gdeeda 3leih lel abad.
- ✓ Far2: Object.preventExtensions byrga3 el object nafso, laken Reflect byrga3 boolean y2ollek neg7et wala la2.
- ✓ Btrga3 eh: true law el object et2afel sa7.

12. Reflect.set(target, prop, value, receiver)

- ✓ Bt3mel eh: De assign value le property. Zay target[prop] = value.
- ✓ Btrga3 eh: true law el value etkatabet w eldonya tmm, false law fesheet (maslan law el prop read-only).

13. Reflect.setPrototypeOf(target, proto)

- ✓ Bt3mel eh: De btghayar el parent prototype bta3 el object f wa2t el runtime. Ya3ny bt5alleeh yewres mn object tany.
- ✓ Far2: Object.setPrototypeOf momken tdrab Error law el operation 8alat, bas Reflect btrga3 false .
- ✓ Arguments:
 - target: El object elli 3ayza a8ayyar el prototype bta3o.
 - proto: El object el gdeed elli hayb2a howa el parent (aw null).
- ✓ Btrga3 eh: true law el taghyeer tamm, false law ma3rftsh.