

Well Name: Sample 11 - Full Data

API/UWI 0987656789	Surface Legal Location	Field Name Akuinu	License # 8818838	State/Province Texas	Well Configuration Type Deviated
Ground Elevation (ft)	Casing Flange Elevation (ft) 0.00	KB-Ground Distance (ft)	KB-Casing Flange Distance (ft) 210.00	Spud Date 2000-02-21 00:00	Rig Release Date 2000-03-18 00:00

Structural Casing, 1,598.8ftKB

Set Depth (ftKB) 1,598.8		Set Tension (kips) 65.0		String Nominal OD (in) 30		String Min Drift (in) 28.000		Centralizers 2/joint every 4th joint		Scratchers None	
Jts	Item Des	OD (in)	ID (in)	Wt (lb/ft)	Grade	Top Thread	Top (ftKB)	Btm (ftKB)	Len (ft)	P Burst (psi)	P Collapse (psi)
2	Casing Joint(s)	30	28.000	310.00	X-52	RL-4HT	1,381.2	1,483.6	102.40		
1	Cross-Over Joint	30	28.000	310.00	X-52	RL-4HT	1,483.6	1,521.6	37.99		
1	Casing Joint(s)	30	28.000	310.00	X-52	RL-4S	1,521.6	1,559.9	38.29		
1	Float Shoe Joint	30	28.000	310.00	X-52	RL-4S	1,559.9	1,598.8	38.85		

Conductor Pipe, 2,239.0ftKB

Set Depth (ftKB) 2,239.0		Set Tension (kips)		String Nominal OD (in) 20		String Min Drift (in) 17.500		Centralizers Two every 5th joint		Scratchers None	
Jts	Item Des	OD (in)	ID (in)	Wt (lb/ft)	Grade	Top Thread	Top (ftKB)	Btm (ftKB)	Len (ft)	P Burst (psi)	P Collapse (psi)
21	Casing Joint(s)	20	18.750	129.33	X-56	RL-4S	1,381.2	2,199.8	818.60	2,840.0	1,410.0
1	Float Shoe	20	18.750	129.33	X-56	RL-4S	2,199.8	2,239.0	39.21	2,840.0	1,410.0

Surface Casing, 4,253.0ftKB

Set Depth (ftKB) 4,253.0		Set Tension (kips)		String Nominal OD (in) 13 3/8		String Min Drift (in) 12.410		Centralizers 2/joint on shoe track.		Scratchers None	
Jts	Item Des	OD (in)	ID (in)	Wt (lb/ft)	Grade	Top Thread	Top (ftKB)	Btm (ftKB)	Len (ft)	P Burst (psi)	P Collapse (psi)
72	Casing Joint(s)	13 3/8	12.415	68.00	K-55	BTC	1,381.2	4,172.6	2,791.40	3,450.0	1,950.0
1	Float Collar	13 3/8	12.415	68.00	K-55	BTC	4,172.6	4,173.8	1.15	3,450.0	1,950.0
2	Casing Joint(s)	13 3/8	12.415	68.00	K-55	BTC	4,173.8	4,251.2	77.49	3,450.0	1,950.0
1	Float Shoe	13 3/8	12.415	68.00	K-55	BTC	4,251.2	4,253.0	1.74	3,450.0	1,950.0

Production Casing, 12,478.9ftKB

Set Depth (ftKB) 12,478.9		Set Tension (kips)		String Nominal OD (in) 9 5/8		String Min Drift (in) 8.525		Centralizers 2/joint on shoe track		Scratchers	
Jts	Item Des	OD (in)	ID (in)	Wt (lb/ft)	Grade	Top Thread	Top (ftKB)	Btm (ftKB)	Len (ft)	P Burst (psi)	P Collapse (psi)
62	Casing Joint(s)	10.752	9.602	55.50	L-80	VAM	1,378.6	3,817.5	2,438.91	6,450.0	4,020.0
1	Cross Over	10.752	8.524	55.50	L-80	VAM	3,817.5	3,819.0	1.54	6,450.0	4,020.0
222	Casing Joint(s)	9 5/8	8.524	53.50	L-80	LTC	3,819.0	12,398.6	8,579.53	7,930.0	6,620.0
1	Float Collar	9 5/8	8.524	53.50	L-80	LTC	12,398.6	12,399.7	1.18	7,930.0	6,620.0
2	Casing Joint(s)	9 5/8	8.524	53.50	L-80	LTC	12,399.7	12,477.3	77.56	7,930.0	6,620.0
1	Float Shoe	9 5/8	8.524	53.50	L-80	LTC	12,477.3	12,478.9	1.64	7,930.0	6,620.0